

OPEN TRACE FORMAT 2 USER MANUAL

1.2 (revision 3183)

Tue Aug 13 2013 12:40:20

OTF2 LICENSE AGREEMENT

COPYRIGHT ©2009-2012,
RWTH Aachen University, Germany
COPYRIGHT ©2009-2012,
Gesellschaft fuer numerische Simulation mbH, Germany
COPYRIGHT ©2009-2013,
Technische Universitaet Dresden, Germany
COPYRIGHT ©2009-2012,
University of Oregon, Eugene, USA
COPYRIGHT ©2009-2013,
Forschungszentrum Juelich GmbH, Germany
COPYRIGHT ©2009-2013,
German Research School for Simulation Sciences GmbH, Germany
COPYRIGHT ©2009-2012,
Technische Universitaet Muenchen, Germany

All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

* Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.

* Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.

* Neither the names of
RWTH Aachen University,
Gesellschaft fuer numerische Simulation mbH Braunschweig,
Technische Universitaet Dresden,
University of Oregon, Eugene,
Forschungszentrum Juelich GmbH,
German Research School for Simulation Sciences GmbH, or the
Technische Universitaet Muenchen,
nor the names of their contributors may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY,

WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

Contents

| | Page |
|--|-------------|
| Contents | v |
| 1 Open Trace Format 2 | 1 |
| 1.1 Introduction | 1 |
| 1.2 Get started | 1 |
| Appendix A OTF2 Tools | 5 |
| A.1 Usage of OTF2 tools | 5 |
| A.1.1 OTF2 config tool | 5 |
| A.1.2 OTF2 print tool | 6 |
| A.1.3 OTF2 snapshots tool | 6 |
| A.1.4 OTF2 marker tool | 6 |
| Appendix B OTF2 INSTALL | 9 |
| Appendix C List of all definition records | 19 |
| C.1 ClockProperties | 19 |
| C.2 MappingTable | 20 |
| C.3 ClockOffset | 20 |
| C.4 String | 21 |
| C.5 Attribute | 21 |
| C.6 SystemTreeNode | 22 |
| C.7 LocationGroup | 22 |
| C.8 Location | 23 |
| C.9 Region | 23 |
| C.10 Callsite | 24 |
| C.11 Callpath | 25 |
| C.12 Group | 25 |
| C.13 MetricMember | 26 |
| C.14 MetricClass | 27 |
| C.15 MetricInstance | 27 |
| C.16 Comm | 28 |
| C.17 Parameter | 29 |
| C.18 RmaWin | 29 |

| | |
|---|-----------|
| C.19 MetricClassRecorder | 30 |
| C.20 SystemTreeNodeProperty | 30 |
| C.21 SystemTreeNodeDomain | 31 |
| | |
| Appendix D List of all event records | 33 |
| D.1 BufferFlush | 33 |
| D.2 MeasurementOnOff | 33 |
| D.3 Enter | 34 |
| D.4 Leave | 34 |
| D.5 MpiSend | 35 |
| D.6 MpiIsend | 35 |
| D.7 MpiIsendComplete | 36 |
| D.8 MpiIrecvRequest | 37 |
| D.9 MpiRecv | 37 |
| D.10 MpiIrecv | 38 |
| D.11 MpiRequestTest | 38 |
| D.12 MpiRequestCancelled | 39 |
| D.13 MpiCollectiveBegin | 39 |
| D.14 MpiCollectiveEnd | 40 |
| D.15 OmpFork | 40 |
| D.16 OmpJoin | 41 |
| D.17 OmpAcquireLock | 41 |
| D.18 OmpReleaseLock | 42 |
| D.19 OmpTaskCreate | 43 |
| D.20 OmpTaskSwitch | 43 |
| D.21 OmpTaskComplete | 44 |
| D.22 Metric | 45 |
| D.23 ParameterString | 45 |
| D.24 ParameterInt | 46 |
| D.25 ParameterUnsignedInt | 47 |
| D.26 RmaWinCreate | 47 |
| D.27 RmaWinDestroy | 48 |
| D.28 RmaCollectiveBegin | 48 |
| D.29 RmaCollectiveEnd | 49 |
| D.30 RmaGroupSync | 49 |
| D.31 RmaRequestLock | 50 |
| D.32 RmaAcquireLock | 51 |
| D.33 RmaTryLock | 51 |
| D.34 RmaReleaseLock | 52 |
| D.35 RmaSync | 53 |
| D.36 RmaWaitChange | 53 |
| D.37 RmaPut | 54 |
| D.38 RmaGet | 54 |
| D.39 RmaAtomic | 55 |

CONTENTS

| | |
|--|-----------|
| D.40 RmaOpCompleteBlocking | 56 |
| D.41 RmaOpCompleteNonBlocking | 56 |
| D.42 RmaOpTest | 57 |
| D.43 RmaOpCompleteRemote | 57 |
| D.44 ThreadFork | 58 |
| D.45 ThreadJoin | 58 |
| D.46 ThreadTeamBegin | 59 |
| D.47 ThreadTeamEnd | 59 |
| D.48 ThreadAcquireLock | 60 |
| D.49 ThreadReleaseLock | 60 |
| D.50 ThreadTaskCreate | 61 |
| D.51 ThreadTaskSwitch | 62 |
| D.52 ThreadTaskComplete | 62 |
| Appendix E List of all snapshot records | 65 |
| E.1 SnapshotStart | 65 |
| E.2 SnapshotEnd | 66 |
| E.3 MeasurementOnOffSnap | 66 |
| E.4 EnterSnap | 67 |
| E.5 MpiSendSnap | 67 |
| E.6 MpiIsendSnap | 68 |
| E.7 MpiIsendCompleteSnap | 69 |
| E.8 MpiRecvSnap | 69 |
| E.9 MpiIrecvRequestSnap | 70 |
| E.10 MpiIrecvSnap | 71 |
| E.11 MpiCollectiveBeginSnap | 72 |
| E.12 MpiCollectiveEndSnap | 72 |
| E.13 OmpForkSnap | 73 |
| E.14 OmpAcquireLockSnap | 73 |
| E.15 OmpTaskCreateSnap | 74 |
| E.16 OmpTaskSwitchSnap | 75 |
| E.17 MetricSnap | 75 |
| E.18 ParameterStringSnap | 76 |
| E.19 ParameterIntSnap | 77 |
| E.20 ParameterUnsignedIntSnap | 77 |
| Appendix F Usage in writing mode | 79 |
| F.1 Usage in writing mode - a simple example | 79 |
| Appendix G Usage in reading mode | 83 |
| G.1 Usage in reading mode - a simple example | 83 |
| Appendix H Deprecated List | 87 |

| | | |
|-------------------|---|-----------|
| Appendix I | Data Structure Documentation | 89 |
| I.1 | OTF2_AttributeValue Union Reference | 89 |
| I.1.1 | Detailed Description | 91 |
| I.2 | OTF2_FileSionCallbacks Struct Reference | 91 |
| I.2.1 | Detailed Description | 91 |
| I.3 | OTF2_FlushCallbacks Struct Reference | 92 |
| I.3.1 | Detailed Description | 92 |
| I.4 | OTF2_MemoryCallbacks Struct Reference | 92 |
| I.4.1 | Detailed Description | 93 |
| I.5 | OTF2_MetricValue Union Reference | 93 |
| I.5.1 | Detailed Description | 93 |
| | | |
| Appendix J | File Documentation | 95 |
| J.1 | otf2.h File Reference | 95 |
| J.1.1 | Detailed Description | 95 |
| J.2 | OTF2_Archive.h File Reference | 95 |
| J.2.1 | Detailed Description | 102 |
| J.2.2 | Define Documentation | 102 |
| J.2.3 | Typedef Documentation | 103 |
| J.2.4 | Enumeration Type Documentation | 103 |
| J.2.5 | Function Documentation | 103 |
| J.3 | OTF2_AttributeList.h File Reference | 125 |
| J.3.1 | Detailed Description | 131 |
| J.3.2 | How to use the attribute list for writing | 132 |
| J.3.3 | Function Documentation | 132 |
| J.4 | OTF2_Callbacks.h File Reference | 152 |
| J.4.1 | Detailed Description | 153 |
| J.4.2 | Typedef Documentation | 154 |
| J.5 | OTF2_Definitions.h File Reference | 157 |
| J.5.1 | Detailed Description | 163 |
| J.5.2 | Enumeration Type Documentation | 163 |
| J.6 | OTF2_DefReader.h File Reference | 172 |
| J.6.1 | Detailed Description | 172 |
| J.6.2 | Function Documentation | 173 |
| J.7 | OTF2_DefReaderCallbacks.h File Reference | 174 |
| J.7.1 | Detailed Description | 180 |
| J.7.2 | Typedef Documentation | 181 |
| J.7.3 | Function Documentation | 194 |
| J.8 | OTF2_DefWriter.h File Reference | 205 |
| J.8.1 | Detailed Description | 208 |
| J.8.2 | Function Documentation | 208 |
| J.9 | OTF2_ErrorCodes.h File Reference | 220 |
| J.9.1 | Detailed Description | 224 |
| J.9.2 | Typedef Documentation | 224 |

CONTENTS

| | | |
|--------|---|-----|
| J.9.3 | Enumeration Type Documentation | 225 |
| J.9.4 | Function Documentation | 228 |
| J.10 | OTF2_Events.h File Reference | 229 |
| J.10.1 | Detailed Description | 231 |
| J.10.2 | Enumeration Type Documentation | 232 |
| J.11 | OTF2_EvtReader.h File Reference | 234 |
| J.11.1 | Detailed Description | 235 |
| J.11.2 | Function Documentation | 236 |
| J.12 | OTF2_EvtReaderCallbacks.h File Reference | 239 |
| J.12.1 | Detailed Description | 254 |
| J.12.2 | Typedef Documentation | 254 |
| J.12.3 | Function Documentation | 293 |
| J.13 | OTF2_EvtWriter.h File Reference | 320 |
| J.13.1 | Detailed Description | 328 |
| J.13.2 | Function Documentation | 328 |
| J.14 | OTF2_GeneralDefinitions.h File Reference | 363 |
| J.14.1 | Detailed Description | 371 |
| J.14.2 | Define Documentation | 371 |
| J.14.3 | Enumeration Type Documentation | 371 |
| J.15 | OTF2_GlobalDefReader.h File Reference | 376 |
| J.15.1 | Detailed Description | 376 |
| J.15.2 | Function Documentation | 377 |
| J.16 | OTF2_GlobalDefReaderCallbacks.h File Reference | 378 |
| J.16.1 | Detailed Description | 384 |
| J.16.2 | Typedef Documentation | 384 |
| J.16.3 | Function Documentation | 397 |
| J.17 | OTF2_GlobalDefWriter.h File Reference | 408 |
| J.17.1 | Detailed Description | 411 |
| J.17.2 | Function Documentation | 411 |
| J.18 | OTF2_GlobalEvtReader.h File Reference | 424 |
| J.18.1 | Detailed Description | 425 |
| J.18.2 | Function Documentation | 426 |
| J.19 | OTF2_GlobalEvtReaderCallbacks.h File Reference | 427 |
| J.19.1 | Detailed Description | 441 |
| J.19.2 | Typedef Documentation | 442 |
| J.19.3 | Function Documentation | 478 |
| J.20 | OTF2_GlobalSnapReader.h File Reference | 506 |
| J.20.1 | Detailed Description | 507 |
| J.20.2 | Function Documentation | 507 |
| J.21 | OTF2_GlobalSnapReaderCallbacks.h File Reference | 508 |
| J.21.1 | Detailed Description | 514 |
| J.21.2 | Typedef Documentation | 515 |
| J.21.3 | Function Documentation | 531 |
| J.22 | OTF2_IdMap.h File Reference | 544 |

CONTENTS

| | | |
|--------|---|-----|
| J.22.1 | Detailed Description | 545 |
| J.22.2 | Typedef Documentation | 546 |
| J.22.3 | Enumeration Type Documentation | 546 |
| J.22.4 | Function Documentation | 546 |
| J.23 | OTF2_Marker.h File Reference | 550 |
| J.23.1 | Detailed Description | 551 |
| J.23.2 | Enumeration Type Documentation | 551 |
| J.24 | OTF2_MarkerReader.h File Reference | 552 |
| J.24.1 | Detailed Description | 553 |
| J.24.2 | Function Documentation | 553 |
| J.25 | OTF2_MarkerReaderCallbacks.h File Reference | 554 |
| J.25.1 | Detailed Description | 556 |
| J.25.2 | Typedef Documentation | 556 |
| J.25.3 | Function Documentation | 557 |
| J.26 | OTF2_MarkerWriter.h File Reference | 560 |
| J.26.1 | Detailed Description | 561 |
| J.26.2 | Function Documentation | 561 |
| J.27 | OTF2_Reader.h File Reference | 562 |
| J.27.1 | Detailed Description | 569 |
| J.27.2 | Function Documentation | 569 |
| J.28 | OTF2_SnapReader.h File Reference | 594 |
| J.28.1 | Detailed Description | 594 |
| J.28.2 | Function Documentation | 595 |
| J.29 | OTF2_SnapReaderCallbacks.h File Reference | 597 |
| J.29.1 | Detailed Description | 603 |
| J.29.2 | Typedef Documentation | 603 |
| J.29.3 | Function Documentation | 619 |
| J.30 | OTF2_SnapWriter.h File Reference | 632 |
| J.30.1 | Detailed Description | 635 |
| J.30.2 | Typedef Documentation | 636 |
| J.30.3 | Function Documentation | 636 |
| J.31 | OTF2_Thumbnail.h File Reference | 650 |
| J.31.1 | Detailed Description | 651 |
| J.31.2 | Function Documentation | 651 |

Chapter 1

Open Trace Format 2

1.1 Introduction

The OTF2 library provides an interface to write and read trace data.

OTF2 is developed within the Score-P project. The Score-P project is funded by the German Federal Ministry of Education and Research. OTF2 is available under the BSD open source license that allows free usage for academic and commercial applications.

1.2 Get started

[Usage in writing mode](#)

[Usage in reading mode](#)

[Definition records](#)

[Event records](#)

[Snapshot records](#)

[Usage of OTF2 tools](#)

Appendices

Appendix A

OTF2 Tools

A.1 Usage of OTF2 tools

A.1.1 OTF2 config tool

A call to `otf2-config` has the following syntax:

```
Usage: otf2-config [OPTION]... COMMAND
```

Commands:

```
--cflags      prints additional compiler flags. They already contain  
              the include flags  
--cppflags    prints the include flags for the OTF2 headers  
--libs        prints the required libraries for linking  
--ldflags     prints the required linker flags  
--cc          prints the C compiler name  
--help        prints this usage information  
  
--version     prints the version number of the OTF2 package and  
--otf2-revision  
              prints the revision number of the OTF2 package  
--common-revision  
              prints the revision number of the common package  
--interface-version  
              prints the interface version number
```

Options:

```
--backend     on systems, which required cross-compiling, this flag  
              specifies that the information for the backend is displayed.  
              By default the information for the frontend is displayed.  
              On non-cross compiling systems, this flag is ignored  
--cuda        specifies that the required flags are for the CUDA compiler
```

A.1.2 OTF2 print tool

A call to `oft2-print` has the following syntax:

Usage: `oft2-print` [OPTION]... [--] ANCHORFILE
Print selected content of the OTF2 archive specified by ANCHORFILE.

Options:

| | |
|---|--|
| <code>-A, --show-all</code> | print all output including definitions and anchor file |
| <code>-G, --show-global-defs</code> | print all global definitions |
| <code>-I, --show-info</code> | print information from the anchor file |
| <code>-T, --show-thumbnails</code> | print the headers from all thumbnails |
| <code>-M, --show-mappings</code> | print mappings to global definitions |
| <code>-C, --show-clock-offsets</code> | print clock offsets to global timer |
| <code>-L, --location <LID></code> | limit output to location <LID> |
| <code>-s, --step <N></code> | step through output by steps of <N> events |
| <code>--time <MIN> <MAX></code> | limit output to events within time interval |
| <code>--system-tree</code> | output system tree to dot-file |
| <code>--silent</code> | only validate trace and do not print any events |
| <code>-d, --debug</code> | turn on debug mode |
| <code>-V, --version</code> | print version information |
| <code>-h, --help</code> | print this help information |

A.1.3 OTF2 snapshots tool

A call to `oft2-snapshots` has the following syntax:

Usage: `oft2-snapshots` [OPTION]... ANCHORFILE
Append snapshots to existing `oft2` traces at given 'break' timestamps.

Options:

| | |
|--|---|
| <code>-n, --number <BREAKS></code> | Number of breaks (distributed regularly) if <code>-p</code> and <code>-t</code> are not set, the default for <code>-n</code> is 10 breaks. |
| <code>-p <TICK_RATE></code> | Create break every <TICK_RATE> ticks if both, <code>-n</code> and <code>-p</code> are specified the one producing more breaks wins. |
| <code>--progress</code> | Brief mode, print progress information. |
| <code>--verbose</code> | Verbose mode, print break timestamps, i.e. snapshot informations to stdout. |
| <code>-V, --version</code> | Print version information. |
| <code>-h, --help</code> | Print this help information. |

A.1.4 OTF2 marker tool

A call to `oft2-marker` has the following syntax:

Usage: `oft2-marker` [OPTION] [ARGUMENTS]... ANCHORFILE

A.1 Usage of OTF2 tools

Read or edit a marker file.

Options:

```
Print all markers sorted by group.
--def <GROUP> [<CATEGORY>]
    Print all marker definitions of group <GROUP> or of
    category <CATEGORY> from group <GROUP>.
--defs-only      Print only marker definitions.
--add-def <GROUP> <CATEGORY> <SEVERITY>
    Add a new marker definition.
--add <GROUP> <CATEGORY> <TIME> <SCOPE> <TEXT>
    Add a marker to an existing definition.
--remove-def <GROUP> [<CATEGORY>]
    Remove all marker classes of group <GROUP> or only the
    category <CATEGORY> of group <GROUP>; and all according
    markers.
--clear-def <GROUP> [<CATEGORY>]
    Remove all markers of group <GROUP> or only of category
    <CATEGORY> of group <GROUP>.
--reset          Reset all marker.
-V, --version    Print version information.
-h, --help       Print this help information.
```

Argument descriptions:

```
<GROUP>, <CATEGORY>, <TEXT>
    Arbitrary strings.
<SEVERITY>
    One of:
    * NONE
    * LOW
    * MEDIUM
    * HIGH
<TIME>
    One of the following formats:
    * <TIMESTAMP>
      A valid timestamp inside the trace range
      'global offset' and 'global offset' + 'trace
      length'.
    * <TIMESTAMP>+<DURATION>
      <TIMESTAMP> and <TIMESTAMP> + <DURATION> must be valid
      timestamps inside the trace range 'global
      offset' and 'global offset' + 'trace length'.
    * <TIMESTAMP-START>-<TIMESTAMP-END>
      Two valid timestamps inside the trace range 'global
      offset' and 'global offset' + 'trace length', with
      <TIMESTAMP-START> <= <TIMESTAMP-END>.
    See the CLOCK_PROPERTIES definition with the help
    of the 'otf2-print -G' tool.
<SCOPE>[:<SCOPE-REF>]
    The <SCOPE> must be one of:
    * GLOBAL
    * LOCATION:<LOCATION-REF>
    * LOCATION_GROUP:<LOCATION-GROUP-REF>
    * SYSTEM_TREE_NODE:<SYSTEM-TREE-NODE-REF>
    * GROUP:<GROUP-REF>
    * COMM:<COMMUNICATOR-REF>
```

APPENDIX A. OTF2 TOOLS

<SCOPE-REF> must be a valid definition reference of the specified scope. Use 'otf2-print -G' for a list of defined references.

There is no <SCOPE-REF> for <SCOPE> 'GLOBAL'.
For a scope 'GROUP' the type of the referenced group must be 'OTF2_GROUP_TYPE_LOCATIONS' or 'OTF2_GROUP_TYPE_COMM_LOCATIONS'.

Appendix B

OTF2 INSTALL

For generic installation instructions see below.

Configuration of OTF2

'configure' configures scorep to adapt to many kinds of systems.

Usage: ./configure [OPTION]... [VAR=VALUE]...

To assign environment variables (e.g., CC, CFLAGS...), specify them as VAR=VALUE. See below for descriptions of some of the useful variables.

Defaults for the options are specified in brackets.

Configuration:

| | |
|-----------------------|---|
| -h, --help | display this help and exit |
| --help=short | display options specific to this package |
| --help=recursive | display the short help of all the included packages |
| -V, --version | display version information and exit |
| -q, --quiet, --silent | do not print 'checking ...' messages |
| --cache-file=FILE | cache test results in FILE [disabled] |
| -C, --config-cache | alias for '--cache-file=config.cache' |
| -n, --no-create | do not create output files |
| --srcdir=DIR | find the sources in DIR [configure dir or '..'] |

Installation directories:

| | |
|-----------------------|---|
| --prefix=PREFIX | install architecture-independent files in PREFIX [/opt/otf2] |
| --exec-prefix=EPREFIX | install architecture-dependent files in EPREFIX [PREFIX] |

By default, 'make install' will install all the files in '/opt/otf2/bin', '/opt/otf2/lib' etc. You can specify an installation prefix other than '/opt/otf2' using '--prefix', for instance '--prefix=\$HOME'.

APPENDIX B. OTF2 INSTALL

For better control, use the options below.

Fine tuning of the installation directories:

```
--bindir=DIR          user executables [EPREFIX/bin]
--sbindir=DIR         system admin executables [EPREFIX/sbin]
--libexecdir=DIR     program executables [EPREFIX/libexec]
--sysconfdir=DIR     read-only single-machine data [PREFIX/etc]
--sharedstatedir=DIR modifiable architecture-independent data [PREFIX/com]
--localstatedir=DIR  modifiable single-machine data [PREFIX/var]
--libdir=DIR         object code libraries [EPREFIX/lib]
--includedir=DIR     C header files [PREFIX/include]
--oldincludedir=DIR  C header files for non-gcc [/usr/include]
--datarootdir=DIR    read-only arch.-independent data root [PREFIX/share]
--datadir=DIR        read-only architecture-independent data [DATAROOTDIR]
--infodir=DIR        info documentation [DATAROOTDIR/info]
--localedir=DIR      locale-dependent data [DATAROOTDIR/locale]
--mandir=DIR         man documentation [DATAROOTDIR/man]
--docdir=DIR         documentation root [DATAROOTDIR/doc/otf2]
--htmldir=DIR        html documentation [DOCDIR]
--dvidir=DIR         dvi documentation [DOCDIR]
--pdfdir=DIR         pdf documentation [DOCDIR]
--psdir=DIR          ps documentation [DOCDIR]
```

Program names:

```
--program-prefix=PREFIX      prepend PREFIX to installed program names
--program-suffix=SUFFIX      append SUFFIX to installed program names
--program-transform-name=PROGRAM  run sed PROGRAM on installed program names
```

System types:

```
--build=BUILD      configure for building on BUILD [guessed]
--host=HOST        cross-compile to build programs to run on HOST [BUILD]
```

Optional Features:

```
--disable-option-checking  ignore unrecognized --enable/--with options
--disable-FEATURE          do not include FEATURE (same as --enable-FEATURE=no)
--enable-FEATURE[=ARG]    include FEATURE [ARG=yes]
--enable-silent-rules      less verbose build output (undo: 'make V=1')
--disable-silent-rules    verbose build output (undo: 'make V=0')
--with-platform=(auto,disabled,<platform>)
                           autodetect platform [auto], disabled or select one
                           from: altix, aix, arm, bgl, bgp, bgq, crayxt, linux,
                           solaris, mac, necsx.
--disable-dependency-tracking  speeds up one-time build
--enable-dependency-tracking  do not reject slow dependency extractors
--enable-debug              activate internal debug output [no]
--enable-backend-test-runs
                           Run tests at make check [no]. If disabled, tests are
                           still build at make check. Additionally, scripts
                           (scorep_*tests.sh) containing the tests are
                           generated in <builddir>/build-backend.
--enable-shared[=PKGS]    build shared libraries [default=no]
--enable-static[=PKGS]    build static libraries [default=yes]
--enable-fast-install[=PKGS]
                           optimize for fast installation [default=yes]
```

`--disable-libtool-lock` avoid locking (might break parallel builds)

Optional Packages:

`--with-PACKAGE[=ARG]` use PACKAGE [ARG=yes]
`--without-PACKAGE` do not use PACKAGE (same as `--with-PACKAGE=no`)
`--with-sionconfig=(yes|no|<path-to-sionconfig>)`
Whether to use sionconfig and where to find it.
"yes" assumes it is in PATH [no].
`--with-otf-prefix=PREFIX`
Prefix where otf is installed (optional)
`--with-otf-exec-prefix=PREFIX`
Exec prefix where otf is installed (optional)
`--with-pic` try to use only PIC/non-PIC objects [default=use
both]
`--with-gnu-ld` assume the C compiler uses GNU ld [default=no]
`--with-sysroot=DIR` Search for dependent libraries within DIR
(or the compiler's sysroot if not specified).

Some influential environment variables:

`CC_FOR_BUILD`
C compiler command for the frontend build
`CXX_FOR_BUILD`
C++ compiler command for the frontend build
`F77_FOR_BUILD`
Fortran 77 compiler command for the frontend build
`FC_FOR_BUILD`
Fortran compiler command for the frontend build
`CPPFLAGS_FOR_BUILD`
(Objective) C/C++ preprocessor flags for the frontend build,
e.g. `-I<include dir>` if you have headers in a nonstandard
directory `<include dir>`
`CFLAGS_FOR_BUILD`
C compiler flags for the frontend build
`CXXFLAGS_FOR_BUILD`
C++ compiler flags for the frontend build
`FFLAGS_FOR_BUILD`
Fortran 77 compiler flags for the frontend build
`FCFLAGS_FOR_BUILD`
Fortran compiler flags for the frontend build
`LDFLAGS_FOR_BUILD`
linker flags for the frontend build, e.g. `-L<lib dir>` if you
have libraries in a nonstandard directory `<lib dir>`
`LIBS_FOR_BUILD`
libraries to pass to the linker for the frontend build, e.g.
`-l<library>`
`CC` C compiler command
`CFLAGS` C compiler flags
`LDFLAGS` linker flags, e.g. `-L<lib dir>` if you have libraries in a
nonstandard directory `<lib dir>`
`LIBS` libraries to pass to the linker, e.g. `-l<library>`
`CPPFLAGS` (Objective) C/C++ preprocessor flags, e.g. `-I<include dir>` if
you have headers in a nonstandard directory `<include dir>`
`CXX` C++ compiler command
`CXXFLAGS` C++ compiler flags

APPENDIX B. OTF2 INSTALL

CPP C preprocessor
SIONCONFIG Absolute path to sionconfig, including "sionconfig".
OTF_CONFIG config script used for otf
OTF_CFLAGS CFLAGS used for the otf
OTF_LIBS LIBS used for the otf
CXXCPP C++ preprocessor

Use these variables to override the choices made by 'configure' or to help it to find libraries and programs with nonstandard names/locations.

Please report bugs to <support@score-p.org>.

Installation Instructions

Copyright (C) 1994, 1995, 1996, 1999, 2000, 2001, 2002, 2004, 2005, 2006, 2007, 2008, 2009 Free Software Foundation, Inc.

Copying and distribution of this file, with or without modification, are permitted in any medium without royalty provided the copyright notice and this notice are preserved. This file is offered as-is, without warranty of any kind.

Basic Installation

=====

Briefly, the shell commands './configure; make; make install' should configure, build, and install this package. The following more-detailed instructions are generic; see the 'README' file for instructions specific to this package. Some packages provide this 'INSTALL' file but do not implement all of the features documented below. The lack of an optional feature in a given package is not necessarily a bug. More recommendations for GNU packages can be found in *note Makefile Conventions: (standards)Makefile Conventions.

The 'configure' shell script attempts to guess correct values for various system-dependent variables used during compilation. It uses those values to create a 'Makefile' in each directory of the package. It may also create one or more '.h' files containing system-dependent definitions. Finally, it creates a shell script 'config.status' that you can run in the future to recreate the current configuration, and a file 'config.log' containing compiler output (useful mainly for debugging 'configure').

It can also use an optional file (typically called 'config.cache' and enabled with '--cache-file=config.cache' or simply '-C') that saves the results of its tests to speed up reconfiguring. Caching is disabled by default to prevent problems with accidental use of stale cache files.

If you need to do unusual things to compile the package, please try to figure out how 'configure' could check whether to do them, and mail diffs or instructions to the address given in the 'README' so they can be considered for the next release. If you are using the cache, and at

some point `'config.cache'` contains results you don't want to keep, you may remove or edit it.

The file `'configure.ac'` (or `'configure.in'`) is used to create `'configure'` by a program called `'autoconf'`. You need `'configure.ac'` if you want to change it or regenerate `'configure'` using a newer version of `'autoconf'`.

The simplest way to compile this package is:

1. `'cd'` to the directory containing the package's source code and type `'./configure'` to configure the package for your system.

Running `'configure'` might take a while. While running, it prints some messages telling which features it is checking for.

2. Type `'make'` to compile the package.
3. Optionally, type `'make check'` to run any self-tests that come with the package, generally using the just-built uninstalled binaries.
4. Type `'make install'` to install the programs and any data files and documentation. When installing into a prefix owned by root, it is recommended that the package be configured and built as a regular user, and only the `'make install'` phase executed with root privileges.
5. Optionally, type `'make installcheck'` to repeat any self-tests, but this time using the binaries in their final installed location. This target does not install anything. Running this target as a regular user, particularly if the prior `'make install'` required root privileges, verifies that the installation completed correctly.
6. You can remove the program binaries and object files from the source code directory by typing `'make clean'`. To also remove the files that `'configure'` created (so you can compile the package for a different kind of computer), type `'make distclean'`. There is also a `'make maintainer-clean'` target, but that is intended mainly for the package's developers. If you use it, you may have to get all sorts of other programs in order to regenerate files that came with the distribution.
7. Often, you can also type `'make uninstall'` to remove the installed files again. In practice, not all packages have tested that uninstallation works correctly, even though it is required by the GNU Coding Standards.
8. Some packages, particularly those that use Automake, provide `'make distcheck'`, which can be used by developers to test that all other targets like `'make install'` and `'make uninstall'` work correctly. This target is generally not run by end users.

Compilers and Options

APPENDIX B. OTF2 INSTALL

=====

Some systems require unusual options for compilation or linking that the 'configure' script does not know about. Run './configure --help' for details on some of the pertinent environment variables.

You can give 'configure' initial values for configuration parameters by setting variables in the command line or in the environment. Here is an example:

```
./configure CC=c99 CFLAGS=-g LIBS=-lposix
```

*Note Defining Variables::, for more details.

Compiling For Multiple Architectures

=====

You can compile the package for more than one kind of computer at the same time, by placing the object files for each architecture in their own directory. To do this, you can use GNU 'make'. 'cd' to the directory where you want the object files and executables to go and run the 'configure' script. 'configure' automatically checks for the source code in the directory that 'configure' is in and in '..'. This is known as a "VPATH" build.

With a non-GNU 'make', it is safer to compile the package for one architecture at a time in the source code directory. After you have installed the package for one architecture, use 'make distclean' before reconfiguring for another architecture.

On MacOS X 10.5 and later systems, you can create libraries and executables that work on multiple system types--known as "fat" or "universal" binaries--by specifying multiple '-arch' options to the compiler but only a single '-arch' option to the preprocessor. Like this:

```
./configure CC="gcc -arch i386 -arch x86_64 -arch ppc -arch ppc64" \  
CXX="g++ -arch i386 -arch x86_64 -arch ppc -arch ppc64" \  
CPP="gcc -E" CXXCPP="g++ -E"
```

This is not guaranteed to produce working output in all cases, you may have to build one architecture at a time and combine the results using the 'lipo' tool if you have problems.

Installation Names

=====

By default, 'make install' installs the package's commands under '/usr/local/bin', include files under '/usr/local/include', etc. You can specify an installation prefix other than '/usr/local' by giving 'configure' the option '--prefix=PREFIX', where PREFIX must be an absolute file name.

You can specify separate installation prefixes for

architecture-specific files and architecture-independent files. If you pass the option `--exec-prefix=PREFIX` to `configure`, the package uses PREFIX as the prefix for installing programs and libraries. Documentation and other data files still use the regular prefix.

In addition, if you use an unusual directory layout you can give options like `--bindir=DIR` to specify different values for particular kinds of files. Run `configure --help` for a list of the directories you can set and what kinds of files go in them. In general, the default for these options is expressed in terms of `${prefix}`, so that specifying just `--prefix` will affect all of the other directory specifications that were not explicitly provided.

The most portable way to affect installation locations is to pass the correct locations to `configure`; however, many packages provide one or both of the following shortcuts of passing variable assignments to the `make install` command line to change installation locations without having to reconfigure or recompile.

The first method involves providing an override variable for each affected directory. For example, `make install prefix=/alternate/directory` will choose an alternate location for all directory configuration variables that were expressed in terms of `${prefix}`. Any directories that were specified during `configure`, but not in terms of `${prefix}`, must each be overridden at install time for the entire installation to be relocated. The approach of makefile variable overrides for each directory variable is required by the GNU Coding Standards, and ideally causes no recompilation. However, some platforms have known limitations with the semantics of shared libraries that end up requiring recompilation when using this method, particularly noticeable in packages that use GNU Libtool.

The second method involves providing the `DESTDIR` variable. For example, `make install DESTDIR=/alternate/directory` will prepend `/alternate/directory` before all installation names. The approach of `DESTDIR` overrides is not required by the GNU Coding Standards, and does not work on platforms that have drive letters. On the other hand, it does better at avoiding recompilation issues, and works well even when some directory options were not specified in terms of `${prefix}` at `configure` time.

Optional Features =====

If the package supports it, you can cause programs to be installed with an extra prefix or suffix on their names by giving `configure` the option `--program-prefix=PREFIX` or `--program-suffix=SUFFIX`.

Some packages pay attention to `--enable-FEATURE` options to `configure`, where FEATURE indicates an optional part of the package. They may also pay attention to `--with-PACKAGE` options, where PACKAGE is something like `gnu-as` or `x` (for the X Window System). The `README` should mention any `--enable-` and `--with-` options that the package recognizes.

APPENDIX B. OTF2 INSTALL

For packages that use the X Window System, 'configure' can usually find the X include and library files automatically, but if it doesn't, you can use the 'configure' options '--x-includes=DIR' and '--x-libraries=DIR' to specify their locations.

Some packages offer the ability to configure how verbose the execution of 'make' will be. For these packages, running './configure --enable-silent-rules' sets the default to minimal output, which can be overridden with 'make V=1'; while running './configure --disable-silent-rules' sets the default to verbose, which can be overridden with 'make V=0'.

Particular systems
=====

On HP-UX, the default C compiler is not ANSI C compatible. If GNU CC is not installed, it is recommended to use the following options in order to use an ANSI C compiler:

```
./configure CC="cc -Ae -D_XOPEN_SOURCE=500"
```

and if that doesn't work, install pre-built binaries of GCC for HP-UX.

On OSF/1 a.k.a. Tru64, some versions of the default C compiler cannot parse its '<wchar.h>' header file. The option '-nodtk' can be used as a workaround. If GNU CC is not installed, it is therefore recommended to try

```
./configure CC="cc"
```

and if that doesn't work, try

```
./configure CC="cc -nodtk"
```

On Solaris, don't put '/usr/ucb' early in your 'PATH'. This directory contains several dysfunctional programs; working variants of these programs are available in '/usr/bin'. So, if you need '/usr/ucb' in your 'PATH', put it after '/usr/bin'.

On Haiku, software installed for all users goes in '/boot/common', not '/usr/local'. It is recommended to use the following options:

```
./configure --prefix=/boot/common
```

Specifying the System Type
=====

There may be some features 'configure' cannot figure out automatically, but needs to determine by the type of machine the package will run on. Usually, assuming the package is built to be run on the same architectures, 'configure' can figure that out, but if it prints a message saying it cannot guess the machine type, give it the '--build=TYPE' option. TYPE can either be a short name for the system

type, such as `'sun4'`, or a canonical name which has the form:

CPU-COMPANY-SYSTEM

where SYSTEM can have one of these forms:

OS
KERNEL-OS

See the file `'config.sub'` for the possible values of each field. If `'config.sub'` isn't included in this package, then this package doesn't need to know the machine type.

If you are `_building_` compiler tools for cross-compiling, you should use the option `'--target=TYPE'` to select the type of system they will produce code for.

If you want to `_use_` a cross compiler, that generates code for a platform different from the build platform, you should specify the "host" platform (i.e., that on which the generated programs will eventually be run) with `'--host=TYPE'`.

Sharing Defaults =====

If you want to set default values for `'configure'` scripts to share, you can create a site shell script called `'config.site'` that gives default values for variables like `'CC'`, `'cache_file'`, and `'prefix'`. `'configure'` looks for `'PREFIX/share/config.site'` if it exists, then `'PREFIX/etc/config.site'` if it exists. Or, you can set the `'CONFIG_SITE'` environment variable to the location of the site script. A warning: not all `'configure'` scripts look for a site script.

Defining Variables =====

Variables not defined in a site shell script can be set in the environment passed to `'configure'`. However, some packages may run `configure` again during the build, and the customized values of these variables may be lost. In order to avoid this problem, you should set them in the `'configure'` command line, using `'VAR=value'`. For example:

```
./configure CC=/usr/local2/bin/gcc
```

causes the specified `'gcc'` to be used as the C compiler (unless it is overridden in the site shell script).

Unfortunately, this technique does not work for `'CONFIG_SHELL'` due to an Autoconf bug. Until the bug is fixed you can use this workaround:

```
CONFIG_SHELL=/bin/bash /bin/bash ./configure CONFIG_SHELL=/bin/bash
```

`'configure'` Invocation =====

APPENDIX B. OTF2 INSTALL

'configure' recognizes the following options to control how it operates.

'--help'

'-h'

Print a summary of all of the options to 'configure', and exit.

'--help=short'

'--help=recursive'

Print a summary of the options unique to this package's 'configure', and exit. The 'short' variant lists options used only in the top level, while the 'recursive' variant lists options also present in any nested packages.

'--version'

'-v'

Print the version of Autoconf used to generate the 'configure' script, and exit.

'--cache-file=FILE'

Enable the cache: use and save the results of the tests in FILE, traditionally 'config.cache'. FILE defaults to '/dev/null' to disable caching.

'--config-cache'

'-C'

Alias for '--cache-file=config.cache'.

'--quiet'

'--silent'

'-q'

Do not print messages saying which checks are being made. To suppress all normal output, redirect it to '/dev/null' (any error messages will still be shown).

'--srcdir=DIR'

Look for the package's source code in directory DIR. Usually 'configure' can determine that directory automatically.

'--prefix=DIR'

Use DIR as the installation prefix. *note Installation Names:: for more details, including other options available for fine-tuning the installation locations.

'--no-create'


'-n'

Run the configure checks, but stop before creating any output files.

'configure' also accepts some other, not widely useful, options. Run 'configure --help' for more details.

Appendix C

List of all definition records



C.1 ClockProperties

Defines the timer resolution and time range of this trace. There will be no event with a timestamp less than *globalOffset*, and no event with timestamp greater than (*globalOffset* + *traceLength*).

This definition is only valid as a global definition.

APPENDIX C. LIST OF ALL DEFINITION RECORDS

Attributes

| | | |
|----------|-----------------|---|
| uint64_t | timerResolution | Ticks per seconds. |
| uint64_t | globalOffset | A timestamp smaller than all event timestamps. |
| uint64_t | traceLength | A timespan which includes the timespan between the smallest and greatest timestamp of all event timestamps. |

See also

[OTF2_GlobalDefWriter_WriteClockProperties\(\)](#)

Since

Version 1.0

C.2 MappingTable

Mapping tables are needed for situations where an ID is not globally known at measurement time. They are applied automatically at reading.

This definition is only valid as a local definition.

Attributes

| | | |
|----------------------------------|-------------|--|
| OTF2_MappingType | mappingType | Says to what type of ID the mapping table has to be applied. |
| const OTF2_IdMap* | idMap | Mapping table. |

See also

[OTF2_DefWriter_WriteMappingTable\(\)](#)

Since

Version 1.0

C.3 ClockOffset

Clock offsets are used for clock corrections.

C.5 Attribute

This definition is only valid as a local definition.

Attributes

| | | |
|--------------------------------|--------------------|---|
| OTF2_TimeStamp | time | Time when this offset was determined. |
| int64_t | offset | The offset to the global clock which was determined at <i>time</i> . |
| double | standard-Deviation | A possible standard deviation, which can be used as a metric for the quality of the offset. |

See also

[OTF2_DefWriter_WriteClockOffset\(\)](#)

Since

Version 1.0

C.4 [OTF2_StringRef](#) String

Attributes

| | | |
|-----------------------------|--------|------------------------------|
| const char* | string | The string, null terminated. |
|-----------------------------|--------|------------------------------|

See also

[OTF2_GlobalDefWriter_WriteString\(\)](#)

[OTF2_DefWriter_WriteString\(\)](#)

Since

Version 1.0

C.5 [OTF2_AttributeRef](#) Attribute

Attributes

| | | |
|--------------------------------|------|--|
| OTF2_StringRef | name | Name of the attribute. References a String definition. |
| OTF2_Type | type | Type of the attribute value. |

APPENDIX C. LIST OF ALL DEFINITION RECORDS

See also

[OTF2_GlobalDefWriter_WriteAttribute\(\)](#)

[OTF2_DefWriter_WriteAttribute\(\)](#)

Since

Version 1.0

C.6 [OTF2_SystemTreeNodeRef](#) SystemTreeNode

Attributes

| | | |
|--|-----------|---|
| OTF2_StringRef | name | Free form instance name of this node. References a String definition. |
| OTF2_StringRef | className | Free form class name of this node References a String definition. |
| OTF2_SystemTreeNodeRef | parent | Parent id of this node. May be OTF2_UNDEFINED_SYSTEM_TREE_NODE to indicate that there is no parent. References a SystemTreeNode definition. |

See also

[OTF2_GlobalDefWriter_WriteSystemTreeNode\(\)](#)

[OTF2_DefWriter_WriteSystemTreeNode\(\)](#)

Since

Version 1.0

C.7 [OTF2_LocationGroupRef](#) LocationGroup

Attributes

| | | |
|--|--------------------|---|
| OTF2_StringRef | name | Name of the group. References a String definition. |
| OTF2_LocationGroupType | location-GroupType | Type of this group. |
| OTF2_SystemTreeNodeRef | systemTreeParent | Parent of this location group in the system tree. References a SystemTreeNode definition. |

C.9 Region

See also

[OTF2_GlobalDefWriter_WriteLocationGroup\(\)](#)

[OTF2_DefWriter_WriteLocationGroup\(\)](#)

Since

Version 1.0

C.8 OTF2_LocationRef Location

Attributes

| | | |
|---------------------------------------|----------------|---|
| OTF2_StringRef | name | Name of the location References a String definition. |
| OTF2_LocationType | location-Type | Location type. |
| uint64_t | numberOfEvents | Number of events this location has recorded. |
| OTF2_LocationGroupRef | location-Group | Location group which includes this location. References a LocationGroup definition. |

See also

[OTF2_GlobalDefWriter_WriteLocation\(\)](#)

[OTF2_DefWriter_WriteLocation\(\)](#)

Since

Version 1.0

C.9 OTF2_RegionRef Region

Attributes

| | | |
|---------------------------------|----------------|--|
| OTF2_StringRef | name | Name of the region (demangled name if available). References a String definition. |
| OTF2_StringRef | canonical-Name | Alternative name of the region (e.g. mangled name). References a String definition. Since version 1.1. |
| OTF2_StringRef | description | A more detailed description of this region. References a String definition. |
| OTF2_RegionRole | regionRole | Region role. Since version 1.1. |

APPENDIX C. LIST OF ALL DEFINITION RECORDS

| | | |
|---------------------------------|-----------------|---|
| OTF2_Paradigm | paradigm | Paradigm. Since version 1.1. |
| OTF2_RegionFlag | regionFlags | Region flags. Since version 1.1. |
| OTF2_StringRef | sourceFile | The source file where this region was declared. References a String definition. |
| uint32_t | beginLineNumber | Starting line number of this region in the source file. |
| uint32_t | endLineNumber | Ending line number of this region in the source file. |

See also

[OTF2_GlobalDefWriter_WriteRegion\(\)](#)
[OTF2_DefWriter_WriteRegion\(\)](#)

Since

Version 1.0

C.10 [OTF2_CallsiteRef](#) Callsite

Attributes

| | | |
|--------------------------------|---------------|---|
| OTF2_StringRef | sourceFile | The source file where this call was made. References a String definition. |
| uint32_t | lineNumber | Line number in the source file where this call was made. |
| OTF2_RegionRef | enteredRegion | The region which was called. References a Region definition. |
| OTF2_RegionRef | leftRegion | The region which made the call. References a Region definition. |

See also

[OTF2_GlobalDefWriter_WriteCallsite\(\)](#)
[OTF2_DefWriter_WriteCallsite\(\)](#)

Since

Version 1.0

C.12 Group

C.11 [OTF2_CallpathRef](#) Callpath

Attributes

| | | |
|----------------------------------|--------|---|
| OTF2_CallpathRef | parent | References a Callpath definition. |
| OTF2_RegionRef | region | References a Region definition. |

See also

[OTF2_GlobalDefWriter_WriteCallpath\(\)](#)

[OTF2_DefWriter_WriteCallpath\(\)](#)

Since

Version 1.0

C.12 [OTF2_GroupRef](#) Group

Attributes

| | | |
|--------------------------------|-------------------------------|--|
| OTF2_StringRef | name | Name of this group References a String definition. |
| OTF2_GroupType | groupType | The type of this group. Since version 1.2. |
| OTF2_Paradigm | paradigm | The paradigm of this communication group. Since version 1.2. |
| OTF2_GroupFlag | groupFlags | Flags for this group. Since version 1.2. |
| uint32_t | num-berOfMem-bers | The number of members in this group. |
| uint64_t | members [num-berOfMem-bers] | The identifiers of the group members. |

See also

[OTF2_GlobalDefWriter_WriteGroup\(\)](#)

[OTF2_DefWriter_WriteGroup\(\)](#)

Since

Version 1.0

C.13 [OTF2_MetricMemberRef](#) MetricMember

A metric is defined by a metric member definition. A metric member is always a member of a metric class. Therefore, a single metric is a special case of a metric class with only one member. It is not allowed to reference a metric member id in a metric event, but only metric class IDs.

Attributes

| | | |
|---------------------------------|-------------|---|
| OTF2_StringRef | name | Name of the metric. References a String definition. |
| OTF2_StringRef | description | Description of the metric. References a String definition. |
| OTF2_MetricType | metricType | Metric type: PAPI, etc. |
| OTF2_MetricMode | metric-Mode | Metric mode: accumulative, fix, relative, etc. |
| OTF2_Type | valueType | Type of the value: int64_t, uint64_t, or double. |
| OTF2_MetricBase | metricBase | The recorded values should be handled in this given base, either binary or decimal. This information can be used if the value needs to be scaled. |
| int64_t | exponent | The values inside the Metric events should be scaled by the factor $base^{exponent}$, to get the value in its base unit. For example, if the metric values come in as KiBi, than the base should be OTF2_BASE_BINARY and the exponent 10. Than the writer does not need to scale the values up to bytes, but can directly write the KiBi values into the Metric event. At reading time, the reader can apply the scaling factor to get the value in its base unit, ie. in bytes. |
| OTF2_StringRef | unit | Unit of the metric. This needs to be the scale free base unit, ie. "bytes", "operations", or "seconds". In particular this unit should not have any scale prefix. References a String definition. |

See also

[OTF2_GlobalDefWriter_WriteMetricMember\(\)](#)

C.15 MetricInstance

[OTF2_DefWriter_WriteMetricMember\(\)](#)

Since

Version 1.0

C.14 [OTF2_MetricRef](#) MetricClass

For a metric class it is implicitly given that the event stream that records the metric is also the scope. A metric class can contain multiple different metrics.

Attributes

| | | |
|---------------------------------------|-----------------------------------|--|
| uint8_t | numberOfMetrics | Number of metrics within the set. |
| OTF2_MetricMemberRef | metricMembers [numberOfMetrics] | List of metric members. References a MetricMember definition. |
| OTF2_MetricOccurrence | metricOccurrence | Defines occurrence of a metric set. |
| OTF2_RecorderKind | recorderKind | What kind of locations will record this metric class, or will this metric class only be recorded by metric instances. Since version 1.2. |

See also

[OTF2_GlobalDefWriter_WriteMetricClass\(\)](#)
[OTF2_DefWriter_WriteMetricClass\(\)](#)

Since

Version 1.0

C.15 [OTF2_MetricRef](#) MetricInstance

A metric instance is used to define metrics that are recorded at one location for multiple locations or for another location. The occurrence of a metric instance is implicitly of type [OTF2_METRIC_ASYNCHRONOUS](#).

APPENDIX C. LIST OF ALL DEFINITION RECORDS

Attributes

| | | |
|----------------------------------|--------------|--|
| OTF2_MetricRef | metricClass | The instanced <i>MetricClass</i> . This metric class must be of kind <i>OTF2_RECORDER_KIND_ABSTRACT</i> . References a MetricClass definition. |
| OTF2_LocationRef | recorder | Recorder of the metric: location ID. References a Location definition. |
| OTF2_MetricScope | metric-Scope | Defines type of scope: location, location group, system tree node, or a generic group of locations. |
| uint64_t | scope | Scope of metric: ID of a location, location group, system tree node, or a generic group of locations. |

See also

[OTF2_GlobalDefWriter_WriteMetricInstance\(\)](#)
[OTF2_DefWriter_WriteMetricInstance\(\)](#)

Since

Version 1.0

C.16 [OTF2_CommRef](#) Comm

Attributes

| | | |
|--------------------------------|--------|--|
| OTF2_StringRef | name | The name given by calling <code>MPI_Comm_set_name</code> on this communicator. Or the empty name to indicate that no name was given. References a String definition. |
| OTF2_GroupRef | group | The describing MPI group of this MPI communicator The group needs to be of type <i>OTF2_GROUP_TYPE_MPI_GROUP</i> or <i>OTF2_GROUP_TYPE_MPI_COMM_SELF</i> . References a Group definition. |
| OTF2_CommRef | parent | The parent MPI communicator from which this communicator was created, if any. Use OTF2_UNDEFINED_COMM to indicate no parent. References a Comm definition. |

C.18 RmaWin

See also

[OTF2_GlobalDefWriter_WriteComm\(\)](#)
[OTF2_DefWriter_WriteComm\(\)](#)

Since

Version 1.0

C.17 OTF2_ParameterRef Parameter

Attributes

| | | |
|------------------------------------|----------------|--|
| OTF2_StringRef | name | Name of the parameter (variable name etc.) References a String definition. |
| OTF2_ParameterType | parameter-Type | Type of the parameter, OTF2_ParameterType for possible types. |

See also

[OTF2_GlobalDefWriter_WriteParameter\(\)](#)
[OTF2_DefWriter_WriteParameter\(\)](#)

Since

Version 1.0

C.18 OTF2_RmaWinRef RmaWin

A window defines the communication context for any remote-memory access operation.

Attributes

| | | |
|--------------------------------|------|--|
| OTF2_StringRef | name | Name, e.g. 'GASPI Queue 1', 'NVidia Card 2', etc.. References a String definition. |
| OTF2_CommRef | comm | Communicator object used to create the window. References a Comm definition. |

See also

[OTF2_GlobalDefWriter_WriteRmaWin\(\)](#)
[OTF2_DefWriter_WriteRmaWin\(\)](#)

Since

Version 1.2

C.19 MetricClassRecorder

Attributes

| | | |
|----------------------------------|-------------|---|
| OTF2_MetricRef | metricClass | Parent MetricClass definition to which this one is a supplementary definition. References a MetricClass definition. |
| OTF2_LocationRef | recorder | The location which recorded the referenced metric class. References a Location definition. |

See also

[OTF2_GlobalDefWriter_WriteMetricClassRecorder\(\)](#)

[OTF2_DefWriter_WriteMetricClassRecorder\(\)](#)

Since

Version 1.2

C.20 SystemTreeNodeProperty

Attributes

| | | |
|--|----------------|---|
| OTF2_SystemTreeNodeRef | systemTreeNode | Parent SystemTreeNode definition to which this one is a supplementary definition. References a SystemTreeNode definition. |
| OTF2_StringRef | name | Name of the property. References a String definition. |
| OTF2_StringRef | value | Property value. References a String definition. |

See also

[OTF2_GlobalDefWriter_WriteSystemTreeNodeProperty\(\)](#)

[OTF2_DefWriter_WriteSystemTreeNodeProperty\(\)](#)

Since

Version 1.2

C.21 SystemTreeNodeDomain

C.21 SystemTreeNodeDomain

Attributes

| | | |
|--|------------------|---|
| OTF2_SystemTreeNodeRef | systemTreeNode | Parent SystemTreeNode definition to which this one is a supplementary definition. References a SystemTreeNode definition. |
| OTF2_SystemTreeDomain | systemTreeDomain | |

See also

[OTF2_GlobalDefWriter_WriteSystemTreeNodeDomain\(\)](#)
[OTF2_DefWriter_WriteSystemTreeNodeDomain\(\)](#)

Since

Version 1.2

APPENDIX C. LIST OF ALL DEFINITION RECORDS

Appendix D

List of all event records

D.1 BufferFlush

This event signals that the internal buffer was flushed at the given time.

Attributes

| | | |
|----------------------------------|-----------|---|
| OTF2_LocationRef | location | The location where this event happened. |
| OTF2_TimeStamp | timestamp | The time when this event happened. |
| OTF2_TimeStamp | stopTime | The time the buffer flush finished. |

See also

[OTF2_EvtWriter_BufferFlush\(\)](#)

Since

Version 1.0

D.2 MeasurementOnOff

This event signals where the measurement system turned measurement on or off.

Attributes

| | | |
|--------------------------------------|-----------------|---|
| OTF2_LocationRef | location | The location where this event happened. |
| OTF2_TimeStamp | timestamp | The time when this event happened. |
| OTF2_MeasurementMode | measurementMode | Is the measurement turned on (OTF2_MEASUREMENT_ON) or off (OTF2_MEASUREMENT_OFF)? |

APPENDIX D. LIST OF ALL EVENT RECORDS

See also

[OTF2_EvtWriter_MeasurementOnOff\(\)](#)

Since

Version 1.0

D.3 Enter

An enter record indicates that the program enters a code region.

Attributes

| | | |
|----------------------------------|-----------|--|
| OTF2_LocationRef | location | The location where this event happened. |
| OTF2_TimeStamp | timestamp | The time when this event happened. |
| OTF2_RegionRef | region | Needs to be defined in a definition record References a Region definition and will be mapped to the global definition if a mapping table of type OTF2-MAPPING_REGION is available. |

See also

[OTF2_EvtWriter_Enter\(\)](#)

Since

Version 1.0

D.4 Leave

A leave record indicates that the program leaves a code region.

Attributes

| | | |
|----------------------------------|-----------|--|
| OTF2_LocationRef | location | The location where this event happened. |
| OTF2_TimeStamp | timestamp | The time when this event happened. |
| OTF2_RegionRef | region | Needs to be defined in a definition record References a Region definition and will be mapped to the global definition if a mapping table of type OTF2-MAPPING_REGION is available. |

D.6 MpiIsend

See also

[OTF2_EvtWriter_Leave\(\)](#)

Since

Version 1.0

D.5 MpiSend

A MpiSend record indicates that a MPI message send process was initiated (MPI_SEND). It keeps the necessary information for this event: receiver of the message, communicator, and the message tag. You can optionally add further information like the message length (size of the send buffer).

Attributes

| | | |
|----------------------------------|--------------|--|
| OTF2_LocationRef | location | The location where this event happened. |
| OTF2_TimeStamp | timestamp | The time when this event happened. |
| uint32_t | receiver | MPI rank of receiver in <i>communicator</i> . |
| OTF2_CommRef | communicator | Communicator ID. References a Comm definition and will be mapped to the global definition if a mapping table of type OTF2_MAPPING_COMM is available. |
| uint32_t | msgTag | Message tag |
| uint64_t | msgLength | Message length |

See also

[OTF2_EvtWriter_MpiSend\(\)](#)

Since

Version 1.0

D.6 Mpilsend

A Mpilsend record indicates that a MPI message send process was initiated (MPI_ISEND). It keeps the necessary information for this event: receiver of the message, communicator, and the message tag. You can optionally add further information like the message length (size of the send buffer).

APPENDIX D. LIST OF ALL EVENT RECORDS

Attributes

| | | |
|----------------------------------|-------------------|--|
| OTF2_LocationRef | location | The location where this event happened. |
| OTF2_TimeStamp | timestamp | The time when this event happened. |
| uint32_t | receiver | MPI rank of receiver in <i>communicator</i> . |
| OTF2_CommRef | communi- cator | Communicator ID. References a Comm definition and will be mapped to the global definition if a mapping table of type OTF2_MAPPING_COMM is available. |
| uint32_t | msgTag | Message tag |
| uint64_t | msgLength | Message length |
| uint64_t | requestID | ID of the related request |

See also

[OTF2_EvtWriter_MpiSend\(\)](#)

Since

Version 1.0

D.7 MpiSendComplete

Signals the completion of non-blocking send request.

Attributes

| | | |
|----------------------------------|-----------|---|
| OTF2_LocationRef | location | The location where this event happened. |
| OTF2_TimeStamp | timestamp | The time when this event happened. |
| uint64_t | requestID | ID of the related request |

See also

[OTF2_EvtWriter_MpiSendComplete\(\)](#)

Since

Version 1.0

D.9 MpiRecv

D.8 MpiRecvRequest

Signals the request of an receive, which can be completed later.

Attributes

| | | |
|----------------------------------|-----------|---|
| OTF2_LocationRef | location | The location where this event happened. |
| OTF2_TimeStamp | timestamp | The time when this event happened. |
| uint64_t | requestID | ID of the requested receive |

See also

[OTF2_EvtWriter_MpiRecvRequest\(\)](#)

Since

Version 1.0

D.9 MpiRecv

A MpiRecv record indicates that a MPI message was received (MPI_RECV). It keeps the necessary information for this event: sender of the message, communicator, and the message tag. You can optionally add further information like the message length (size of the receive buffer).

Attributes

| | | |
|----------------------------------|--------------|--|
| OTF2_LocationRef | location | The location where this event happened. |
| OTF2_TimeStamp | timestamp | The time when this event happened. |
| uint32_t | sender | MPI rank of sender in <i>communicator</i> . |
| OTF2_CommRef | communicator | Communicator ID. References a Comm definition and will be mapped to the global definition if a mapping table of type OTF2_MAPPING_COMM is available. |
| uint32_t | msgTag | Message tag |
| uint64_t | msgLength | Message length |

See also

[OTF2_EvtWriter_MpiRecv\(\)](#)

APPENDIX D. LIST OF ALL EVENT RECORDS

Since

Version 1.0

D.10 MpiIrecv

A MpiIrecv record indicates that a MPI message was received (MPI_IRecv). It keeps the necessary information for this event: sender of the message, communicator, and the message tag. You can optionally add further information like the message length (size of the receive buffer).

Attributes

| | | |
|----------------------------------|--------------|--|
| OTF2_LocationRef | location | The location where this event happened. |
| OTF2_TimeStamp | timestamp | The time when this event happened. |
| uint32_t | sender | MPI rank of sender in <i>communicator</i> . |
| OTF2_CommRef | communicator | Communicator ID. References a Comm definition and will be mapped to the global definition if a mapping table of type OTF2_MAPPING_COMM is available. |
| uint32_t | msgTag | Message tag |
| uint64_t | msgLength | Message length |
| uint64_t | requestID | ID of the related request |

See also

[OTF2_EvtWriter_MpiIrecv\(\)](#)

Since

Version 1.0

D.11 MpiRequestTest

This events appears if the program tests if a request has already completed but the test failed.

Attributes

| | | |
|----------------------------------|-----------|---|
| OTF2_LocationRef | location | The location where this event happened. |
| OTF2_TimeStamp | timestamp | The time when this event happened. |
| 38 uint64_t | requestID | ID of the related request |

D.13 MpiCollectiveBegin

See also

[OTF2_EvtWriter_MpiRequestTest\(\)](#)

Since

Version 1.0

D.12 MpiRequestCancelled

This events appears if the program canceled a request.

Attributes

| | | |
|----------------------------------|-----------|---|
| OTF2_LocationRef | location | The location where this event happened. |
| OTF2_TimeStamp | timestamp | The time when this event happened. |
| uint64_t | requestID | ID of the related request |

See also

[OTF2_EvtWriter_MpiRequestCancelled\(\)](#)

Since

Version 1.0

D.13 MpiCollectiveBegin

A MpiCollectiveBegin record marks the begin of an MPI collective operation (MPI_GATHER, MPI_SCATTER etc.).

Attributes

| | | |
|----------------------------------|-----------|---|
| OTF2_LocationRef | location | The location where this event happened. |
| OTF2_TimeStamp | timestamp | The time when this event happened. |

See also

[OTF2_EvtWriter_MpiCollectiveBegin\(\)](#)

Since

Version 1.0

D.14 `MpiCollectiveEnd`

A `MpiCollectiveEnd` record marks the end of an MPI collective operation (`MPI_GATHER`, `MPI_SCATTER` etc.). It keeps the necessary information for this event: type of collective operation, communicator, the root of this collective operation. You can optionally add further information like sent and received bytes.

Attributes

| | | |
|-----------------------------------|--------------|--|
| OTF2_LocationRef | location | The location where this event happened. |
| OTF2_TimeStamp | timestamp | The time when this event happened. |
| OTF2_CollectiveOp | collectiveOp | Determines which collective operation it is. |
| OTF2_CommRef | communicator | Communicator References a Comm definition and will be mapped to the global definition if a mapping table of type OTF2_MAPPING_COMM is available. |
| <code>uint32_t</code> | root | MPI rank of root in <i>communicator</i> . |
| <code>uint64_t</code> | sizeSent | Size of the sent message. |
| <code>uint64_t</code> | sizeReceived | Size of the received message. |

See also

[OTF2_EvtWriter_MpiCollectiveEnd\(\)](#)

Since

Version 1.0

D.15 `OmpFork`

An `OmpFork` record marks that an OpenMP Thread forks a thread team.

This event record is superseded by the [ThreadFork](#) event record and should not be used when the [ThreadFork](#) event record is in use.

Attributes

| | | |
|----------------------------------|--------------------------|---|
| OTF2_LocationRef | location | The location where this event happened. |
| OTF2_TimeStamp | timestamp | The time when this event happened. |
| <code>uint32_t</code> | numberOfRequestedThreads | Requested size of the team. |

D.17 OmpAcquireLock

See also

[OTF2_EvtWriter_OmpFork\(\)](#)

Since

Version 1.0

Deprecated

In version 1.2

D.16 OmpJoin

An OmpJoin record marks that a team of threads is joint and only the master thread continues execution.

This event record is superseded by the *ThreadJoin* event record and should not be used when the *ThreadJoin* event record is in use.

Attributes

| | | |
|----------------------------------|-----------|---|
| OTF2_LocationRef | location | The location where this event happened. |
| OTF2_TimeStamp | timestamp | The time when this event happened. |

See also

[OTF2_EvtWriter_OmpJoin\(\)](#)

Since

Version 1.0

Deprecated

In version 1.2

D.17 OmpAcquireLock

An OmpAcquireLock record marks that a thread acquires an OpenMP lock.

This event record is superseded by the *ThreadAcquireLock* event record and should not be used when the *ThreadAcquireLock* event record is in use record.

APPENDIX D. LIST OF ALL EVENT RECORDS

Attributes

| | | |
|----------------------------------|------------------|---|
| OTF2_LocationRef | location | The location where this event happened. |
| OTF2_TimeStamp | timestamp | The time when this event happened. |
| uint32_t | lockID | ID of the lock. |
| uint32_t | acquisitionOrder | A monotonically increasing number to determine the order of lock acquisitions (with unsynchronized clocks this is otherwise not possible). Corresponding acquire-release events have same number. |

See also

[OTF2_EvtWriter_OmpAcquireLock\(\)](#)

Since

Version 1.0

Deprecated

In version 1.2

D.18 OmpReleaseLock

An OmpReleaseLock record marks that a thread releases an OpenMP lock.

This event record is superseded by the [ThreadReleaseLock](#) event record and should not be used when the [ThreadReleaseLock](#) event record is in use.

Attributes

| | | |
|----------------------------------|------------------|---|
| OTF2_LocationRef | location | The location where this event happened. |
| OTF2_TimeStamp | timestamp | The time when this event happened. |
| uint32_t | lockID | ID of the lock. |
| uint32_t | acquisitionOrder | A monotonically increasing number to determine the order of lock acquisitions (with unsynchronized clocks this is otherwise not possible). Corresponding acquire-release events have same number. |

D.20 OmpTaskSwitch

See also

[OTF2_EvtWriter_OmpReleaseLock\(\)](#)

Since

Version 1.0

Deprecated

In version 1.2

D.19 OmpTaskCreate

An OmpTaskCreate record marks that an OpenMP Task was/will be created in the current region.

This event record is superseded by the *ThreadTaskCreate* event record and should not be used when the *ThreadTaskCreate* event record is in use.

Attributes

| | | |
|----------------------------------|-----------|--|
| OTF2_LocationRef | location | The location where this event happened. |
| OTF2_TimeStamp | timestamp | The time when this event happened. |
| uint64_t | taskID | Identifier of the newly created task instance. |

See also

[OTF2_EvtWriter_OmpTaskCreate\(\)](#)

Since

Version 1.0

Deprecated

In version 1.2

D.20 OmpTaskSwitch

An OmpTaskSwitch record indicates that the execution of the current task will be suspended and another task starts/restarts its execution. Please note that this may change the current call stack of the executing location.

APPENDIX D. LIST OF ALL EVENT RECORDS

This event record is superseded by the *ThreadTaskSwitch* event record and should not be used when the *ThreadTaskSwitch* event record is in use.

Attributes

| | | |
|----------------------------------|-----------|---|
| OTF2_LocationRef | location | The location where this event happened. |
| OTF2_TimeStamp | timestamp | The time when this event happened. |
| uint64_t | taskID | Identifier of the now active task instance. |

See also

[OTF2_EvtWriter_OmpTaskSwitch\(\)](#)

Since

Version 1.0

Deprecated

In version 1.2

D.21 OmpTaskComplete

An OmpTaskComplete record indicates that the execution of an OpenMP task has finished.

This event record is superseded by the *ThreadTaskComplete* event record and should not be used when the *ThreadTaskComplete* event record is in use.

Attributes

| | | |
|----------------------------------|-----------|--|
| OTF2_LocationRef | location | The location where this event happened. |
| OTF2_TimeStamp | timestamp | The time when this event happened. |
| uint64_t | taskID | Identifier of the completed task instance. |

See also

[OTF2_EvtWriter_OmpTaskComplete\(\)](#)

Since

Version 1.0

Deprecated

In version 1.2

D.23 ParameterString

D.22 Metric

A metric event is always stored at the location that recorded the metric. A metric event can reference a metric class or metric instance. Therefore, metric classes and instances share same ID space. Synchronous metrics are always located right before the according enter and leave event.

Attributes

| | | |
|----------------------------------|----------------------------------|--|
| OTF2_LocationRef | location | The location where this event happened. |
| OTF2_TimeStamp | timestamp | The time when this event happened. |
| OTF2_MetricRef | metric | Could be a metric class or a metric instance. References a MetricClass , or a MetricInstance definition and will be mapped to the global definition if a mapping table of type OTF2_MAPPING_METRIC is available. |
| uint8_t | numberOfMetrics | Number of metrics with in the set. |
| OTF2_Type | typeIDs [numberOfMetrics] | List of metric types. |
| OTF2_MetricValue | metricValues [numberOfMetrics] | List of metric values. |

See also

[OTF2_EvtWriter_Metric\(\)](#)

Since

Version 1.0

D.23 ParameterString

A ParameterString record marks that in the current region, the specified string parameter has the specified value.

APPENDIX D. LIST OF ALL EVENT RECORDS

Attributes

| | | |
|-----------------------------------|-----------|--|
| OTF2_LocationRef | location | The location where this event happened. |
| OTF2_TimeStamp | timestamp | The time when this event happened. |
| OTF2_ParameterRef | parameter | Parameter ID. References a Parameter definition and will be mapped to the global definition if a mapping table of type OTF2_MAPPING_PARAMETER is available. |
| OTF2_StringRef | string | Value: Handle of a string definition References a String definition and will be mapped to the global definition if a mapping table of type OTF2_MAPPING_STRING is available. |

See also

[OTF2_EvtWriter_ParameterString\(\)](#)

Since

Version 1.0

D.24 ParameterInt

A ParameterInt record marks that in the current region, the specified integer parameter has the specified value.

Attributes

| | | |
|-----------------------------------|-----------|---|
| OTF2_LocationRef | location | The location where this event happened. |
| OTF2_TimeStamp | timestamp | The time when this event happened. |
| OTF2_ParameterRef | parameter | Parameter ID. References a Parameter definition and will be mapped to the global definition if a mapping table of type OTF2_MAPPING_PARAMETER is available. |
| <code>int64_t</code> | value | Value of the recorded parameter. |

See also

[OTF2_EvtWriter_ParameterInt\(\)](#)

D.26 RmaWinCreate

Since

Version 1.0

D.25 ParameterUnsignedInt

A ParameterUnsignedInt record marks that in the current region, the specified unsigned integer parameter has the specified value.

Attributes

| | | |
|-----------------------------------|-----------|---|
| OTF2_LocationRef | location | The location where this event happened. |
| OTF2_TimeStamp | timestamp | The time when this event happened. |
| OTF2_ParameterRef | parameter | Parameter ID. References a Parameter definition and will be mapped to the global definition if a mapping table of type OTF2_MAPPING_PARAMETER is available. |
| uint64_t | value | Value of the recorded parameter. |

See also

[OTF2_EvtWriter_ParameterUnsignedInt\(\)](#)

Since

Version 1.0

D.26 RmaWinCreate

An RmaWinCreate record denotes the creation of an RMA window.

Attributes

| | | |
|----------------------------------|-----------|--|
| OTF2_LocationRef | location | The location where this event happened. |
| OTF2_TimeStamp | timestamp | The time when this event happened. |
| OTF2_RmaWinRef | win | ID of the window created. References a RmaWin definition and will be mapped to the global definition if a mapping table of type OTF2_MAPPING_RMA_WIN is available. |

APPENDIX D. LIST OF ALL EVENT RECORDS

See also

[OTF2_EvtWriter_RmaWinCreate\(\)](#)

Since

Version 1.2

D.27 RmaWinDestroy

An RmaWinDestroy record denotes the destruction of an RMA window.

Attributes

| | | |
|----------------------------------|-----------|--|
| OTF2_LocationRef | location | The location where this event happened. |
| OTF2_TimeStamp | timestamp | The time when this event happened. |
| OTF2_RmaWinRef | win | ID of the window destroyed. References a RmaWin definition and will be mapped to the global definition if a mapping table of type OTF2_MAPPING_RMA_WIN is available. |

See also

[OTF2_EvtWriter_RmaWinDestroy\(\)](#)

Since

Version 1.2

D.28 RmaCollectiveBegin

An RmaCollectiveBegin record denotes the beginning of a collective RMA operation.

Attributes

| | | |
|----------------------------------|-----------|---|
| OTF2_LocationRef | location | The location where this event happened. |
| OTF2_TimeStamp | timestamp | The time when this event happened. |

See also

[OTF2_EvtWriter_RmaCollectiveBegin\(\)](#)

D.30 RmaGroupSync

Since

Version 1.2

D.29 RmaCollectiveEnd

"An RmaCollectiveEnd record denotes the end of a collective RMA operation.

Attributes

| | | |
|-----------------------------------|---------------|--|
| OTF2_LocationRef | location | The location where this event happened. |
| OTF2_TimeStamp | timestamp | The time when this event happened. |
| OTF2_CollectiveOp | collectiveOp | Determines which collective operation it is. |
| OTF2_RmaSyncLevel | syncLevel | Synchronization level of this collective operation. |
| OTF2_RmaWinRef | win | ID of the window used for this operation. References a RmaWin definition and will be mapped to the global definition if a mapping table of type OTF2_MAPPING_RMA_WIN is available. |
| uint32_t | root | Root process for this operation. |
| uint64_t | bytesSent | Bytes sent in operation. |
| uint64_t | bytesReceived | Bytes receives in operation. |

See also

[OTF2_EvtWriter_RmaCollectiveEnd\(\)](#)

Since

Version 1.2

D.30 RmaGroupSync

An RmaGroupSync record denotes the synchronization with a subgroup of processes on a window.

Attributes

| | | |
|----------------------------------|----------|---|
| OTF2_LocationRef | location | The location where this event happened. |
|----------------------------------|----------|---|

APPENDIX D. LIST OF ALL EVENT RECORDS

| | | |
|-----------------------------------|-----------|--|
| OTF2_TimeStamp | timestamp | The time when this event happened. |
| OTF2_RmaSyncLevel | syncLevel | Synchronization level of this collective operation. |
| OTF2_RmaWinRef | win | ID of the window used for this operation. References a RmaWin definition and will be mapped to the global definition if a mapping table of type OTF2_MAPPING_RMA_WIN is available. |
| OTF2_GroupRef | group | Group of remote processes involved in synchronization. References a Group definition and will be mapped to the global definition if a mapping table of type OTF2_MAPPING_GROUP is available. |

See also

[OTF2_EvtWriter_RmaGroupSync\(\)](#)

Since

Version 1.2

D.31 RmaRequestLock

An `RmaRequestLock` record denotes the time a lock was requested and with it the earliest time it could have been granted. It is used to mark (possibly) non-blocking lock request, as defined by the MPI standard.

Attributes

| | | |
|----------------------------------|-----------|--|
| OTF2_LocationRef | location | The location where this event happened. |
| OTF2_TimeStamp | timestamp | The time when this event happened. |
| OTF2_RmaWinRef | win | ID of the window used for this operation. References a RmaWin definition and will be mapped to the global definition if a mapping table of type OTF2_MAPPING_RMA_WIN is available. |
| <code>uint32_t</code> | remote | Rank of the locked remote process. |
| <code>uint64_t</code> | lockId | ID of the lock acquired, if multiple locks are defined on a window. |
| OTF2_LockType | lockType | Type of lock acquired. |

D.33 RmaTryLock

See also

[OTF2_EvtWriter_RmaRequestLock\(\)](#)

Since

Version 1.2

D.32 RmaAcquireLock

An RmaAcquireLock record denotes the time a lock was acquired by the process.

Attributes

| | | |
|----------------------------------|-----------|--|
| OTF2_LocationRef | location | The location where this event happened. |
| OTF2_TimeStamp | timestamp | The time when this event happened. |
| OTF2_RmaWinRef | win | ID of the window used for this operation. References a RmaWin definition and will be mapped to the global definition if a mapping table of type OTF2_MAPPING_RMA_WIN is available. |
| uint32_t | remote | Rank of the locked remote process. |
| uint64_t | lockId | ID of the lock acquired, if multiple locks are defined on a window. |
| OTF2_LockType | lockType | Type of lock acquired. |

See also

[OTF2_EvtWriter_RmaAcquireLock\(\)](#)

Since

Version 1.2

D.33 RmaTryLock

An RmaTryLock record denotes the time of an unsuccessful attempt to acquire the lock.

Attributes

| | | |
|----------------------------------|----------|---|
| OTF2_LocationRef | location | The location where this event happened. |
|----------------------------------|----------|---|

APPENDIX D. LIST OF ALL EVENT RECORDS

| | | |
|--------------------------------|-----------|--|
| OTF2_TimeStamp | timestamp | The time when this event happened. |
| OTF2_RmaWinRef | win | ID of the window used for this operation. References a RmaWin definition and will be mapped to the global definition if a mapping table of type OTF2_MAPPING_RMA_WIN is available. |
| uint32_t | remote | Rank of the locked remote process. |
| uint64_t | lockId | ID of the lock aquired, if multiple locks are defined on a window. |
| OTF2_LockType | lockType | Type of lock aquired. |

See also

[OTF2_EvtWriter_RmaTryLock\(\)](#)

Since

Version 1.2

D.34 RmaReleaseLock

An `RmaReleaseLock` record denotes the time the lock was released.

Attributes

| | | |
|----------------------------------|-----------|--|
| OTF2_LocationRef | location | The location where this event happened. |
| OTF2_TimeStamp | timestamp | The time when this event happened. |
| OTF2_RmaWinRef | win | ID of the window used for this operation. References a RmaWin definition and will be mapped to the global definition if a mapping table of type OTF2_MAPPING_RMA_WIN is available. |
| uint32_t | remote | Rank of the locked remote process. |
| uint64_t | lockId | ID of the lock released, if multiple locks are defined on a window. |

See also

[OTF2_EvtWriter_RmaReleaseLock\(\)](#)

Since

Version 1.2

D.36 RmaWaitChange

D.35 RmaSync

An RmaSync record denotes the direct synchronization with a possibly remote process.

Attributes

| | | |
|-----------------------------------|-----------|---|
| OTF2_LocationRef | location | The location where this event happened. |
| OTF2_TimeStamp | timestamp | The time when this event happened. |
| OTF2_RmaWinRef | win | ID of the window used for this operation. References a RmaWin definition and will be mapped to the global definition if a mapping table of type OTF2_-MAPPING_RMA_WIN is available. |
| uint32_t | remote | Rank of the locked remote process. |
| OTF2_-RmaSyncType | syncType | Type of synchronization. |

See also

[OTF2_EvtWriter_RmaSync\(\)](#)

Since

Version 1.2

D.36 RmaWaitChange

An RmaWaitChange record denotes the change of a window that was waited for.

Attributes

| | | |
|----------------------------------|-----------|---|
| OTF2_LocationRef | location | The location where this event happened. |
| OTF2_TimeStamp | timestamp | The time when this event happened. |
| OTF2_RmaWinRef | win | ID of the window used for this operation. References a RmaWin definition and will be mapped to the global definition if a mapping table of type OTF2_-MAPPING_RMA_WIN is available. |

See also

[OTF2_EvtWriter_RmaWaitChange\(\)](#)

APPENDIX D. LIST OF ALL EVENT RECORDS

Since

Version 1.2

D.37 RmaPut

An RmaPut record denotes the time a put operation was issued.

Attributes

| | | |
|----------------------------------|------------|--|
| OTF2_LocationRef | location | The location where this event happened. |
| OTF2_TimeStamp | timestamp | The time when this event happened. |
| OTF2_RmaWinRef | win | ID of the window used for this operation. References a RmaWin definition and will be mapped to the global definition if a mapping table of type OTF2_MAPPING_RMA_WIN is available. |
| uint32_t | remote | Rank of the target process. |
| uint64_t | bytes | Bytes sent to target. |
| uint64_t | matchingId | ID used for matching the appropriate completion record. |

See also

[OTF2_EvtWriter_RmaPut\(\)](#)

Since

Version 1.2

D.38 RmaGet

An RmaGet record denotes the time a put operation was issued.

Attributes

| | | |
|----------------------------------|-----------|--|
| OTF2_LocationRef | location | The location where this event happened. |
| OTF2_TimeStamp | timestamp | The time when this event happened. |
| OTF2_RmaWinRef | win | ID of the window used for this operation. References a RmaWin definition and will be mapped to the global definition if a mapping table of type OTF2_MAPPING_RMA_WIN is available. |

D.39 RmaAtomic

| | | |
|----------|------------|---|
| uint32_t | remote | Rank of the target process. |
| uint64_t | bytes | Bytes received from target. |
| uint64_t | matchingId | ID used for matching the appropriate completion record. |

See also

[OTF2_EvtWriter_RmaGet\(\)](#)

Since

Version 1.2

D.39 RmaAtomic

An RmaAtomic record denotes the time a atomic operation was issued.

Attributes

| | | |
|------------------------------------|---------------|--|
| OTF2_LocationRef | location | The location where this event happened. |
| OTF2_TimeStamp | timestamp | The time when this event happened. |
| OTF2_RmaWinRef | win | ID of the window used for this operation. References a RmaWin definition and will be mapped to the global definition if a mapping table of type OTF2_MAPPING_RMA_WIN is available. |
| uint32_t | remote | Rank of the target process. |
| OTF2_RmaAtomicType | type | Type of atomic operation. |
| uint64_t | bytesSent | Bytes sent to target. |
| uint64_t | bytesReceived | Bytes received from target. |
| uint64_t | matchingId | ID used for matching the appropriate completion record. |

See also

[OTF2_EvtWriter_RmaAtomic\(\)](#)

Since

Version 1.2

D.40 RmaOpCompleteBlocking

An RmaOpCompleteBlocking record denotes the local completion of a blocking RMA operation.

Attributes

| | | |
|----------------------------------|------------|--|
| OTF2_LocationRef | location | The location where this event happened. |
| OTF2_TimeStamp | timestamp | The time when this event happened. |
| OTF2_RmaWinRef | win | ID of the window used for this operation. References a RmaWin definition and will be mapped to the global definition if a mapping table of type OTF2_MAPPING_RMA_WIN is available. |
| uint64_t | matchingId | ID used for matching the appropriate completion record. |

See also

[OTF2_EvtWriter_RmaOpCompleteBlocking\(\)](#)

Since

Version 1.2

D.41 RmaOpCompleteNonBlocking

An RmaOpCompleteNonBlocking record denotes the local completion of a non-blocking RMA operation.

Attributes

| | | |
|----------------------------------|------------|--|
| OTF2_LocationRef | location | The location where this event happened. |
| OTF2_TimeStamp | timestamp | The time when this event happened. |
| OTF2_RmaWinRef | win | ID of the window used for this operation. References a RmaWin definition and will be mapped to the global definition if a mapping table of type OTF2_MAPPING_RMA_WIN is available. |
| uint64_t | matchingId | ID used for matching the appropriate completion record. |

D.43 RmaOpCompleteRemote

See also

[OTF2_EvtWriter_RmaOpCompleteNonBlocking\(\)](#)

Since

Version 1.2

D.42 RmaOpTest

An RmaOpTest record denotes that a non-blocking RMA operation has been tested for completion unsuccessfully.

Attributes

| | | |
|----------------------------------|------------|--|
| OTF2_LocationRef | location | The location where this event happened. |
| OTF2_TimeStamp | timestamp | The time when this event happened. |
| OTF2_RmaWinRef | win | ID of the window used for this operation. References a RmaWin definition and will be mapped to the global definition if a mapping table of type OTF2_MAPPING_RMA_WIN is available. |
| uint64_t | matchingId | ID used for matching the appropriate completion record. |

See also

[OTF2_EvtWriter_RmaOpTest\(\)](#)

Since

Version 1.2

D.43 RmaOpCompleteRemote

An RmaOpCompleteRemote record denotes the local completion of an RMA operation.

Attributes

| | | |
|----------------------------------|-----------|---|
| OTF2_LocationRef | location | The location where this event happened. |
| OTF2_TimeStamp | timestamp | The time when this event happened. |

APPENDIX D. LIST OF ALL EVENT RECORDS

| | | |
|--------------------------------|------------|--|
| OTF2_RmaWinRef | win | ID of the window used for this operation. References a RmaWin definition and will be mapped to the global definition if a mapping table of type OTF2_MAPPING_RMA_WIN is available. |
| uint64_t | matchingId | ID used for matching the appropriate completion record. |

See also

[OTF2_EvtWriter_RmaOpCompleteRemote\(\)](#)

Since

Version 1.2

D.44 ThreadFork

An ThreadFork record marks that an thread forks a thread team.

Attributes

| | | |
|----------------------------------|--------------------------|---|
| OTF2_LocationRef | location | The location where this event happened. |
| OTF2_TimeStamp | timestamp | The time when this event happened. |
| OTF2_Paradigm | model | |
| uint32_t | numberOfRequestedThreads | Requested size of the team. |

See also

[OTF2_EvtWriter_ThreadFork\(\)](#)

Since

Version 1.2

D.45 ThreadJoin

An ThreadJoin record marks that a team of threads is joint and only the master thread continues execution.

D.47 ThreadTeamEnd

Attributes

| | | |
|----------------------------------|-----------|---|
| OTF2_LocationRef | location | The location where this event happened. |
| OTF2_TimeStamp | timestamp | The time when this event happened. |
| OTF2_Paradigm | model | |

See also

[OTF2_EvtWriter_ThreadJoin\(\)](#)

Since

Version 1.2

D.46 ThreadTeamBegin

Attributes

| | | |
|----------------------------------|------------|--|
| OTF2_LocationRef | location | The location where this event happened. |
| OTF2_TimeStamp | timestamp | The time when this event happened. |
| OTF2_CommRef | threadTeam | Thread team References a Comm definition and will be mapped to the global definition if a mapping table of type OTF2_-MAPPING_COMM is available. |

See also

[OTF2_EvtWriter_ThreadTeamBegin\(\)](#)

Since

Version 1.2

D.47 ThreadTeamEnd

Attributes

| | | |
|----------------------------------|------------|--|
| OTF2_LocationRef | location | The location where this event happened. |
| OTF2_TimeStamp | timestamp | The time when this event happened. |
| OTF2_CommRef | threadTeam | Thread team References a Comm definition and will be mapped to the global definition if a mapping table of type OTF2_-MAPPING_COMM is available. |

APPENDIX D. LIST OF ALL EVENT RECORDS

See also

[OTF2_EvtWriter_ThreadTeamEnd\(\)](#)

Since

Version 1.2

D.48 ThreadAcquireLock

An ThreadAcquireLock record marks that a thread acquires an lock.

Attributes

| | | |
|----------------------------------|------------------|---|
| OTF2_LocationRef | location | The location where this event happened. |
| OTF2_TimeStamp | timestamp | The time when this event happened. |
| OTF2_Paradigm | model | |
| uint32_t | lockID | ID of the lock. |
| uint32_t | acquisitionOrder | A monotonically increasing number to determine the order of lock acquisitions (with unsynchronized clocks this is otherwise not possible). Corresponding acquire-release events have same number. |

See also

[OTF2_EvtWriter_ThreadAcquireLock\(\)](#)

Since

Version 1.2

D.49 ThreadReleaseLock

An ThreadReleaseLock record marks that a thread releases an lock.

Attributes

| | | |
|----------------------------------|-----------|---|
| OTF2_LocationRef | location | The location where this event happened. |
| OTF2_TimeStamp | timestamp | The time when this event happened. |
| OTF2_Paradigm | model | |

D.50 ThreadTaskCreate

| | | |
|----------|------------------|---|
| uint32_t | lockID | ID of the lock. |
| uint32_t | acquisitionOrder | A monotonically increasing number to determine the order of lock acquisitions (with unsynchronized clocks this is otherwise not possible). Corresponding acquire-release events have same number. |

See also

[OTF2_EvtWriter_ThreadReleaseLock\(\)](#)

Since

Version 1.2

D.50 ThreadTaskCreate

An ThreadTaskCreate record marks that an task in was/will be created and will be processed by the specified thread team.

Attributes

| | | |
|----------------------------------|------------------|---|
| OTF2_LocationRef | location | The location where this event happened. |
| OTF2_TimeStamp | timestamp | The time when this event happened. |
| OTF2_CommRef | threadTeam | Thread team References a Comm definition and will be mapped to the global definition if a mapping table of type OTF2_MAPPING_COMM is available. |
| uint32_t | creatingThread | Creating thread of this task. (This is redundant, remove?) |
| uint32_t | generationNumber | Thread-private generation number of task's creating thread. |

See also

[OTF2_EvtWriter_ThreadTaskCreate\(\)](#)

Since

Version 1.2

D.51 ThreadTaskSwitch

An ThreadTaskSwitch record indicates that the execution of the current task will be suspended and another task starts/restarts its execution. Please note that this may change the current call stack of the executing location.

Attributes

| | | |
|----------------------------------|------------------|--|
| OTF2_LocationRef | location | The location where this event happened. |
| OTF2_TimeStamp | timestamp | The time when this event happened. |
| OTF2_CommRef | threadTeam | Thread team References a Comm definition and will be mapped to the global definition if a mapping table of type OTF2_-MAPPING_COMM is available. |
| uint32_t | creatingThread | Creating thread of this task. |
| uint32_t | generationNumber | Thread-private generation number of task's creating thread. |

See also

[OTF2_EvtWriter_ThreadTaskSwitch\(\)](#)

Since

Version 1.2

D.52 ThreadTaskComplete

An ThreadTaskComplete record indicates that the execution of an OpenMP task has finished.

Attributes

| | | |
|----------------------------------|------------------|--|
| OTF2_LocationRef | location | The location where this event happened. |
| OTF2_TimeStamp | timestamp | The time when this event happened. |
| OTF2_CommRef | threadTeam | Thread team References a Comm definition and will be mapped to the global definition if a mapping table of type OTF2_-MAPPING_COMM is available. |
| uint32_t | creatingThread | Creating thread of this task. |
| uint32_t | generationNumber | Thread-private generation number of task's creating thread. |

D.52 ThreadTaskComplete

See also

[OTF2_EvtWriter_ThreadTaskComplete\(\)](#)

Since

Version 1.2

APPENDIX D. LIST OF ALL EVENT RECORDS

Appendix E

List of all snapshot records

E.1 SnapshotStart

This record marks the start of a snapshot.

A snapshot consists of an timestamp and a set of snapshot records. All these snapshot records have the same snapshot time. A snapshot starts with one *SnapshotStart* record and closes with one *SnapshotEnd* record. All snapshot records inbetween are ordered by the *origEventTime*, which are also less than the snapshot timestamp. Ie. The timestamp of the next event read from the event stream is greater or equal to the snapshot time.

Attributes

| | | |
|----------------------------------|-----------------|---|
| OTF2_LocationRef | location | The location of the snapshot. |
| OTF2_TimeStamp | timestamp | The snapshot time of this record. |
| uint64_t | num-berOfRecord | Number of snapshot event records in this snapshot. Excluding the <i>SnapshotEnd</i> record. |

See also

[OTF2_SnapWriter_SnapshotStart\(\)](#)

Since

Version 1.2

E.2 SnapshotEnd

This record marks the end of a snapshot. It contains the position to continue reading in the event trace for this location. Use [OTF2_EvtReader_Seek](#) with *contReadPos* as the position.

Attributes

| | | |
|----------------------------------|------------------|--|
| OTF2_LocationRef | location | The location of the snapshot. |
| OTF2_TimeStamp | timestamp | The snapshot time of this record. |
| uint64_t | contRead- Pos | Position to continue reading in the event trace. |

See also

[OTF2_SnapWriter_SnapshotEnd\(\)](#)

Since

Version 1.2

E.3 MeasurementOnOffSnap

The last occurrence of an *MeasurementOnOff* event of this location, if any.

Attributes

| | | |
|--|----------------------|---|
| OTF2_LocationRef | location | The location of the snapshot. |
| OTF2_TimeStamp | timestamp | The snapshot time of this record. |
| OTF2_TimeStamp | origEvent- Time | The original time this event happened. |
| OTF2_- MeasurementMode | measure- mentMode | Is the measurement turned on (OTF2_- MEASUREMENT_ON) or off (OTF2_- MEASUREMENT_OFF)? |

See also

MeasurementOnOff event
[OTF2_SnapWriter_MeasurementOnOff\(\)](#)

Since

Version 1.2

E.5 MpiSendSnap

E.4 EnterSnap

This record exists for each *Enter* event where the corresponding *Leave* event did not occur before the snapshot.

Attributes

| | | |
|----------------------------------|----------------|---|
| OTF2_LocationRef | location | The location of the snapshot. |
| OTF2_TimeStamp | timestamp | The snapshot time of this record. |
| OTF2_TimeStamp | origEvent-Time | The original time this event happended. |
| OTF2_RegionRef | region | Needs to be defined in a definition record References a Region definition and will be mapped to the global definition if a mapping table of type OTF2_-MAPPING_REGION is available. |

See also

[Enter](#) event
[OTF2_SnapWriter_Enter\(\)](#)

Since

Version 1.2

E.5 MpiSendSnap

This record exists for each *MpiSend* event where the matching receive message event did not occur on the remote location before the snapshot. This could either be an *MpiRecv* or an *MpiIrecv* event. Note that it may so, that a previous *MpiSend* with the same envelope than this one is neither completed not canceled yet, thus the matching receive may already occurred, but the matching couldn't be done yet.

Attributes

| | | |
|----------------------------------|----------------|---|
| OTF2_LocationRef | location | The location of the snapshot. |
| OTF2_TimeStamp | timestamp | The snapshot time of this record. |
| OTF2_TimeStamp | origEvent-Time | The original time this event happended. |
| uint32_t | receiver | MPI rank of receiver in <i>communicator</i> . |

APPENDIX E. LIST OF ALL SNAPSHOT RECORDS

| | | |
|------------------------------|-------------------|--|
| OTF2_CommRef | communi- cator | Communicator ID. References a Comm definition and will be mapped to the global definition if a mapping table of type OTF2_MAPPING_COMM is available. |
| uint32_t | msgTag | Message tag |
| uint64_t | msgLength | Message length |

See also

[MpiSend](#) event
[OTF2_SnapWriter_MpiSend\(\)](#)

Since

Version 1.2

E.6 MpisendSnap

This record exists for each [MpiSend](#) event where an corresponding [MpiSendComplete](#) or [MpiRequestCancelled](#) event did not occur on this location before the snapshot. Or the corresponding [MpiSendComplete](#) did occurred (the [MpiSendCompleteSnap](#) record exists in the snapshot) but the matching receive message event did not occur on the remote location before the snapshot. (This could either be an [MpiRecv](#) or an [MpiIrecv](#) event.)

Attributes

| | | |
|----------------------------------|--------------------|--|
| OTF2_LocationRef | location | The location of the snapshot. |
| OTF2_TimeStamp | timestamp | The snapshot time of this record. |
| OTF2_TimeStamp | origEvent- Time | The original time this event happened. |
| uint32_t | receiver | MPI rank of receiver in <i>communicator</i> . |
| OTF2_CommRef | communi- cator | Communicator ID. References a Comm definition and will be mapped to the global definition if a mapping table of type OTF2_MAPPING_COMM is available. |
| uint32_t | msgTag | Message tag |
| uint64_t | msgLength | Message length |
| uint64_t | requestID | ID of the related request |

E.8 `MpiRecvSnap`

See also

[MpiIsend](#) event
`OTF2_SnapWriter_MpiIsend()`

Since

Version 1.2

E.7 `MpIsendCompleteSnap`

This record exists for each [MpiIsend](#) event where the corresponding [MpiIsendComplete](#) event occurred, but where the matching receive message event did not occur on the remote location before the snapshot. (This could either be an [MpiRecv](#) or an [MpiIrecv](#) event.) .

Attributes

| | | |
|----------------------------------|----------------|--|
| OTF2_LocationRef | location | The location of the snapshot. |
| OTF2_TimeStamp | timestamp | The snapshot time of this record. |
| OTF2_TimeStamp | origEvent-Time | The original time this event happened. |
| <code>uint64_t</code> | requestID | ID of the related request |

See also

[MpiIsendComplete](#) event
`OTF2_SnapWriter_MpiIsendComplete()`

Since

Version 1.2

E.8 `MpiRecvSnap`

This record exists for each [MpiRecv](#) event where the matching send message event did not occur on the remote location before the snapshot. This could either be an [MpiSend](#) or an [MpiIsendComplete](#) event. Or an [MpiIrecvRequest](#) occurred before this event but the corresponding [MpiIrecv](#) event did not occurred before this snapshot. In this case the message matching couldn't performed yet, because the envelope of the ongoing [MpiIrecvRequest](#) is not yet known.

APPENDIX E. LIST OF ALL SNAPSHOT RECORDS

Attributes

| | | |
|----------------------------------|----------------|--|
| OTF2_LocationRef | location | The location of the snapshot. |
| OTF2_TimeStamp | timestamp | The snapshot time of this record. |
| OTF2_TimeStamp | origEvent-Time | The original time this event happened. |
| uint32_t | sender | MPI rank of sender in <i>communicator</i> . |
| OTF2_CommRef | communicator | Communicator ID. References a Comm definition and will be mapped to the global definition if a mapping table of type OTF2_MAPPING_COMM is available. |
| uint32_t | msgTag | Message tag |
| uint64_t | msgLength | Message length |

See also

[MpiRecv](#) event
[OTF2_SnapWriter_MpiRecv\(\)](#)

Since

Version 1.2

E.9 MpilrecvRequestSnap

This record exists for each [MpilrecvRequest](#) event where an corresponding [MpiIrecv](#) or [MpiRequestCancelled](#) event did not occur on this location before the snapshot. Or the corresponding [MpiIrecv](#) did occurred (the [MpilrecvSnap](#) record exists in the snapshot) but the matching receive message event did not occur on the remote location before the snapshot. This could either be an [MpiRecv](#) or an [Mpilrecv](#) event.

Attributes

| | | |
|----------------------------------|----------------|--|
| OTF2_LocationRef | location | The location of the snapshot. |
| OTF2_TimeStamp | timestamp | The snapshot time of this record. |
| OTF2_TimeStamp | origEvent-Time | The original time this event happened. |
| uint64_t | requestID | ID of the requested receive |

E.10 `MpiIrecvSnap`

See also

[MpiIrecvRequest](#) event
[OTF2_SnapWriter_MpiIrecvRequest\(\)](#)

Since

Version 1.2

E.10 `MpilrecvSnap`

This record exists for each [MpiIrecv](#) event where the matching send message event did not occur on the remote location before the snapshot. This could either be an [MpiSend](#) or an [MpiSendComplete](#) event. Or an [MpiIrecvRequest](#) occurred before this event but the corresponding [MpiIrecv](#) event did not occur before this snapshot. In this case the message matching couldn't be performed yet, because the envelope of the ongoing [MpiIrecvRequest](#) is not yet known.

Attributes

| | | |
|----------------------------------|----------------|--|
| OTF2_LocationRef | location | The location of the snapshot. |
| OTF2_TimeStamp | timestamp | The snapshot time of this record. |
| OTF2_TimeStamp | origEvent-Time | The original time this event happened. |
| uint32_t | sender | MPI rank of sender in <i>communicator</i> . |
| OTF2_CommRef | communicator | Communicator ID. References a Comm definition and will be mapped to the global definition if a mapping table of type OTF2_MAPPING_COMM is available. |
| uint32_t | msgTag | Message tag |
| uint64_t | msgLength | Message length |
| uint64_t | requestID | ID of the related request |

See also

[MpiIrecv](#) event
[OTF2_SnapWriter_MpiIrecv\(\)](#)

Since

Version 1.2

E.11 `MpiCollectiveBeginSnap`

Indicates that this location started a collective operation but not all of the participating locations completed the operation yet, including this location.

Attributes

| | | |
|----------------------------------|----------------|--|
| OTF2_LocationRef | location | The location of the snapshot. |
| OTF2_TimeStamp | timestamp | The snapshot time of this record. |
| OTF2_TimeStamp | origEvent-Time | The original time this event happened. |

See also

[MpiCollectiveBegin](#) event
[OTF2_SnapWriter_MpiCollectiveBegin\(\)](#)

Since

Version 1.2

E.12 `MpiCollectiveEndSnap`

Indicates that this location completed a collective operation locally but not all of the participating locations completed the operation yet. The corresponding *MpiCollectiveBeginSnaps* record is still in the snapshot though.

Attributes

| | | |
|-----------------------------------|----------------|--|
| OTF2_LocationRef | location | The location of the snapshot. |
| OTF2_TimeStamp | timestamp | The snapshot time of this record. |
| OTF2_TimeStamp | origEvent-Time | The original time this event happened. |
| OTF2_CollectiveOp | collectiveOp | Determines which collective operation it is. |
| OTF2_CommRef | communicator | Communicator References a Comm definition and will be mapped to the global definition if a mapping table of type OTF2_MAPPING_COMM is available. |
| <code>uint32_t</code> | root | MPI rank of root in <i>communicator</i> . |
| <code>uint64_t</code> | sizeSent | Size of the sent message. |
| <code>uint64_t</code> | sizeReceived | Size of the received message. |

E.14 OmpAcquireLockSnap

See also

[MpiCollectiveEnd](#) event
[OTF2_SnapWriter_MpiCollectiveEnd\(\)](#)

Since

Version 1.2

E.13 OmpForkSnap

This record exists for each *OmpFork* event where the corresponding *OmpJoin* did not occur before this snapshot.

Attributes

| | | |
|----------------------------------|-----------------------------|--|
| OTF2_LocationRef | location | The location of the snapshot. |
| OTF2_TimeStamp | timestamp | The snapshot time of this record. |
| OTF2_TimeStamp | origEvent-Time | The original time this event happened. |
| uint32_t | num-berOfRe-quest-edThreads | Requested size of the team. |

See also

[OmpFork](#) event
[OTF2_SnapWriter_OmpFork\(\)](#)

Since

Version 1.2

E.14 OmpAcquireLockSnap

This record exists for each *OmpAcquireLock* event where the corresponding *OmpReleaseLock* did not occur before this snapshot yet.

Attributes

| | | |
|----------------------------------|----------|-------------------------------|
| OTF2_LocationRef | location | The location of the snapshot. |
|----------------------------------|----------|-------------------------------|

APPENDIX E. LIST OF ALL SNAPSHOT RECORDS

| | | |
|--------------------------------|------------------|---|
| OTF2_TimeStamp | timestamp | The snapshot time of this record. |
| OTF2_TimeStamp | origEvent-Time | The original time this event happened. |
| uint32_t | lockID | ID of the lock. |
| uint32_t | acquisitionOrder | A monotonically increasing number to determine the order of lock acquisitions (with unsynchronized clocks this is otherwise not possible). Corresponding acquire-release events have same number. |

See also

[OmpAcquireLock](#) event
[OTF2_SnapWriter_OmpAcquireLock\(\)](#)

Since

Version 1.2

E.15 OmpTaskCreateSnap

This record exists for each [OmpTaskCreate](#) event where the corresponding [OmpTaskComplete](#) event did not occurred before this snapshot. Neither on this location nor on any other location in the current thread team.

Attributes

| | | |
|----------------------------------|----------------|--|
| OTF2_LocationRef | location | The location of the snapshot. |
| OTF2_TimeStamp | timestamp | The snapshot time of this record. |
| OTF2_TimeStamp | origEvent-Time | The original time this event happened. |
| uint64_t | taskID | Identifier of the newly created task instance. |

See also

[OmpTaskCreate](#) event
[OTF2_SnapWriter_OmpTaskCreate\(\)](#)

Since

Version 1.2

E.17 MetricSnap

E.16 OmpTaskSwitchSnap

This record exists for each *OmpTaskSwitch* event where the corresponding *OmpTaskComplete* event did not occurred before this snapshot. Neither on this location nor on any other location in the current thread team.

Attributes

| | | |
|----------------------------------|----------------|---|
| OTF2_LocationRef | location | The location of the snapshot. |
| OTF2_TimeStamp | timestamp | The snapshot time of this record. |
| OTF2_TimeStamp | origEvent-Time | The original time this event happened. |
| uint64_t | taskID | Identifier of the now active task instance. |

See also

[OmpTaskSwitch](#) event
[OTF2_SnapWriter_OmpTaskSwitch\(\)](#)

Since

Version 1.2

E.17 MetricSnap

This record exists for each referenced metric class or metric instance event this location recorded metrics before and provides the last known recorded metric values.

As an exception for metric classes where the metric mode detontes an *OTF2-METRIC_VALUE_RELATIVE* mode the value indicates the accumulation of all previous metric values recorded.

Attributes

| | | |
|----------------------------------|----------------|--|
| OTF2_LocationRef | location | The location of the snapshot. |
| OTF2_TimeStamp | timestamp | The snapshot time of this record. |
| OTF2_TimeStamp | origEvent-Time | The original time this event happened. |
| OTF2_MetricRef | metric | Could be a metric class or a metric instance. References a MetricClass , or a MetricInstance definition and will be mapped to the global definition if a mapping table of type OTF2_MAPPING-METRIC is available. |

APPENDIX E. LIST OF ALL SNAPSHOT RECORDS

| | | |
|---------------------------|----------------------------------|------------------------------------|
| uint8_t | numberOfMetrics | Number of metrics with in the set. |
| OTF2_Type | typeIDs [numberOfMetrics] | List of metric types. |
| OTF2_MetricValue | metricValues [numberOfMetrics] | List of metric values. |

See also

[Metric](#) event
[OTF2_SnapWriter_Metric\(\)](#)

Since

Version 1.2

E.18 ParameterStringSnap

This record must be included in the snapshot until the leave event for the enter event occurs which has the greatest timestamp less or equal the timestamp of this record.

Attributes

| | | |
|-----------------------------------|---------------|--|
| OTF2_LocationRef | location | The location of the snapshot. |
| OTF2_TimeStamp | timestamp | The snapshot time of this record. |
| OTF2_TimeStamp | origEventTime | The original time this event happened. |
| OTF2_ParameterRef | parameter | Parameter ID. References a Parameter definition and will be mapped to the global definition if a mapping table of type OTF2_MAPPING_PARAMETER is available. |
| OTF2_StringRef | string | Value: Handle of a string definition References a String definition and will be mapped to the global definition if a mapping table of type OTF2_MAPPING_STRING is available. |

E.20 ParameterUnsignedIntSnap

See also

[ParameterString](#) event
[OTF2_SnapWriter_ParameterString\(\)](#)

Since

Version 1.2

E.19 ParameterIntSnap

This record must be included in the snapshot until the leave event for the enter event occurs which has the greatest timestamp less or equal the timestamp of this record.

Attributes

| | | |
|-----------------------------------|----------------|---|
| OTF2_LocationRef | location | The location of the snapshot. |
| OTF2_TimeStamp | timestamp | The snapshot time of this record. |
| OTF2_TimeStamp | origEvent-Time | The original time this event happened. |
| OTF2_ParameterRef | parameter | Parameter ID. References a Parameter definition and will be mapped to the global definition if a mapping table of type OTF2_MAPPING_PARAMETER is available. |
| int64_t | value | Value of the recorded parameter. |

See also

[ParameterInt](#) event
[OTF2_SnapWriter_ParameterInt\(\)](#)

Since

Version 1.2

E.20 ParameterUnsignedIntSnap

This record must be included in the snapshot until the leave event for the enter event occurs which has the greatest timestamp less or equal the timestamp of this record.

APPENDIX E. LIST OF ALL SNAPSHOT RECORDS

Attributes

| | | |
|-----------------------------------|----------------|---|
| OTF2_LocationRef | location | The location of the snapshot. |
| OTF2_TimeStamp | timestamp | The snapshot time of this record. |
| OTF2_TimeStamp | origEvent-Time | The original time this event happended. |
| OTF2_ParameterRef | parameter | Parameter ID. References a Parameter definition and will be mapped to the global definition if a mapping table of type OTF2_MAPPING_PARAMETER is available. |
| uint64_t | value | Value of the recorded parameter. |

See also

[ParameterUnsignedInt](#) event
[OTF2_SnapWriter_ParameterUnsignedInt\(\)](#)

Since

Version 1.2

Appendix F

Usage in writing mode

F.1 Usage in writing mode - a simple example

This is a short example of how to use the OTF2 writing interface.

First include the OTF2 header.

```
#include <otf2/otf2.h>
```

For this example an additional include statement is necessary.

```
#include <stdlib.h>
```

Furthermore this example uses a function delivering dummy timestamps. Real world applications will use a timer like `gettimeofday`.

```
OTF2_TimeStamp get_time( void )
{
    static uint64_t sequence;
    return sequence++;
}
```

Define a pre and post flush callback. If no memory is left in OTF2's internal memory buffer or the writer handle is closed a memory buffer flushing routine is triggered. The pre flush callback is triggered right before a buffer flush. It needs to return either `OTF2_FLUSH` to flush the recorded data to a file or `OTF2_NO_FLUSH` to suppress flushing data to a file. The post flush callback is triggered right after a memory buffer flush. It has to return a current timestamp which is recorded to mark the time spend in a buffer flush.

APPENDIX F. USAGE IN WRITING MODE

```
OTF2_FlushType pre_flush( void*          userData,
                          OTF2_FileType  fileType,
                          OTF2_LocationRef location,
                          void*          callerData,
                          bool           final )
{
    return OTF2_FLUSH;
}

OTF2_TimeStamp post_flush( void*          userData,
                           OTF2_FileType  fileType,
                           OTF2_LocationRef location )
{
    return get_time();
}

OTF2_FlushCallbacks flush_callbacks =
{
    .otf2_pre_flush = pre_flush,
    .otf2_post_flush = post_flush
};

int main( int argc, char** argv )
{
```

Create new archive handle.

```
OTF2_Archive* archive = OTF2_Archive_Open( "ArchivePath", "ArchiveName",
OTF2_FILEMODE_WRITE, 1024 * 1024, 4 * 1024 * 1024, OTF2_SUBSTRATE_POSIX,
OTF2_COMPRESSION_NONE );
```

Set the flush callbacks.

```
OTF2_Archive_SetFlushCallbacks( archive, &flush_callbacks, NULL );
```

Define archive as master.

```
OTF2_Archive_SetMasterSlaveMode( archive, OTF2_MASTER );
```

Get a local event writer and a local definition writer for location 0. Additionally a global definition writer is needed.

```
OTF2_EvtWriter*      evt_writer      = OTF2_Archive_GetEvtWriter( archiv
e, 0 );
OTF2_DefWriter*     def_writer      = OTF2_Archive_GetDefWriter( archiv
e, 0 );
OTF2_GlobalDefWriter* global_def_writer = OTF2_Archive_GetGlobalDefWriter(
archive );
```

Write an enter and a leave record for region 23 to the local event writer.

F.1 Usage in writing mode - a simple example

```
OTF2_EvtWriter_Enter( evt_writer, NULL, get_time(), 23 );
OTF2_EvtWriter_Leave( evt_writer, NULL, get_time(), 23 );
```

Write definitions for the strings as the first records to the global definition writer.

```
OTF2_GlobalDefWriter_WriteString( global_def_writer, 0, "" );
OTF2_GlobalDefWriter_WriteString( global_def_writer, 1, "Master Process" );

OTF2_GlobalDefWriter_WriteString( global_def_writer, 2, "Main Thread" );
OTF2_GlobalDefWriter_WriteString( global_def_writer, 3, "MyFunction" );
OTF2_GlobalDefWriter_WriteString( global_def_writer, 4, "Alternative function name (e.g. mangled one)" );
OTF2_GlobalDefWriter_WriteString( global_def_writer, 5, "Computes something" );
OTF2_GlobalDefWriter_WriteString( global_def_writer, 6, "MyHost" );
OTF2_GlobalDefWriter_WriteString( global_def_writer, 7, "node" );
```

Write definition for the code region which was just entered and left to the global definition writer.

```
OTF2_GlobalDefWriter_WriteRegion( global_def_writer, 23, 3, 4, 5,
OTF2_REGION_ROLE_FUNCTION, OTF2_PARADIGM_USER, OTF2_REGION_FLAG_NONE, 0, 0, 0 );
```

Write the system tree including a definition for the location group to the global definition writer.

```
OTF2_GlobalDefWriter_WriteSystemTreeNode( global_def_writer, 0, 6, 7,
OTF2_UNDEFINED_SYSTEM_TREE_NODE );
OTF2_GlobalDefWriter_WriteLocationGroup( global_def_writer, 0, 1,
OTF2_LOCATION_GROUP_TYPE_PROCESS, 0 );
```

Write a definition for the location to the global definition writer.

```
OTF2_GlobalDefWriter_WriteLocation( global_def_writer, 0, 2,
OTF2_LOCATION_TYPE_CPU_THREAD, 2, 0 );
```

At the end, close the archive and exit. All opened event and definition writers are closed automatically and the according files are created.

```
OTF2_Archive_Close( archive );

return EXIT_SUCCESS;
}
```

To compile your program use a command like:

```
gcc `otf2-config --cflags` -c otf2_writer_example.c -o otf2_writer_example.o
```

Now you can link your program with:

```
gcc otf2_writer_example.o `otf2-config --ldflags` `otf2-config --libs` -o otf2_writer_example
```

APPENDIX F. USAGE IN WRITING MODE

Appendix G

Usage in reading mode

G.1 Usage in reading mode - a simple example

This is a short example of how to use the OTF2 reading interface. It shows how to define and register callbacks and how to use the reader interface to read all events of a given OTF2 archive.

First include the OTF2 header.

```
#include <otf2/otf2.h>
```

For this example two additional include statements are necessary.

```
#include <stdlib.h>
#include <string.h>
#include <stdint.h>
#include <inttypes.h>
```

Define an event callback for entering and leaving a region.

```
OTF2_CallbackCode
Enter_print( OTF2_LocationRef    location,
             OTF2_TimeStamp     time,
             void*               userData,
             OTF2_AttributeList* attributes,
             OTF2_RegionRef     region )
{
    printf( "Entering region %u at location: %" PRIu64 " at time %" PRIu64 ".\n",
           region, location, time );

    return OTF2_SUCCESS;
}
```

APPENDIX G. USAGE IN READING MODE

```
OTF2_CallbackCode
Leave_print( OTF2_LocationRef    location,
            OTF2_TimeStamp      time,
            void*                userData,
            OTF2_AttributeList* attributes,
            OTF2_RegionRef       region )
{
    printf( "Leaving region %u at location: %" PRIu64 " at time %" PRIu64 ".\n"
            ,
            region, location, time );

    return OTF2_SUCCESS;
}
```

Define a definition callback that opens a new local event reader for each found location definition. The global event reader will use only events from opened local event readers. Therefore, if only a subset of locations should be read from, only for those locations a local event reader has to be opened. In addition, open a local definition reader, if there are local definitions present in the trace archive. Local definitions contain location specific definitions. Please note: Local definitions must be read in order to use automated identifier translation. Otherwise, all delivered identifiers are invalid.

```
OTF2_CallbackCode
GlobDefLocation_Register( void*                userData,
                          OTF2_LocationRef     location,
                          OTF2_StringRef       name,
                          OTF2_LocationType     locationType,
                          uint64_t            numberOfEvents,
                          OTF2_LocationGroupRef locationGroup )
{
    OTF2_Reader* reader = ( OTF2_Reader* )userData;
    OTF2_EvtReader* evt_reader = OTF2_Reader_GetEvtReader( reader, location );

    OTF2_DefReader* def_reader = OTF2_Reader_GetDefReader( reader, location );
    uint64_t definitions_read = 0;
    OTF2_Reader_ReadAllLocalDefinitions( reader, def_reader, &definitions_read
    );
}

int main( int argc, char** argv )
{
```

Create a new reader handle. The path to the OTF2 anchor file must be provided as argument.

```
OTF2_Reader* reader = OTF2_Reader_Open( "ArchivePath/ArchiveName.otf2" );
```

Get a global definition reader with the above reader handle as argument.

```
OTF2_GlobalDefReader* global_def_reader = OTF2_Reader_GetGlobalDefReader( reader );
```

G.1 Usage in reading mode - a simple example

Register the above defined global definition callbacks. All other definition callbacks will be deactivated.

```
OTF2_GlobalDefReaderCallbacks* global_def_callbacks =
OTF2_GlobalDefReaderCallbacks_New();
OTF2_GlobalDefReaderCallbacks_SetLocationCallback( global_def_callbacks, &G
lobDefLocation_Register );
OTF2_Reader_RegisterGlobalDefCallbacks( reader, global_def_reader, global_d
ef_callbacks, reader );
OTF2_GlobalDefReaderCallbacks_Delete( global_def_callbacks );
```

Read all global definitions. Everytime a location definition is read, the previously registered callback is triggered. In `definitions_read` the number of read definitions is returned.

```
uint64_t definitions_read = 0;
OTF2_Reader_ReadAllGlobalDefinitions( reader, global_def_reader, &definitio
ns_read );
```

Open a new global event reader. This global reader automatically contains all previously opened local event readers.

```
OTF2_GlobalEvtReader* global_evt_reader = OTF2_Reader_GetGlobalEvtReader( r
eader );
```

Register the above defined global event callbacks. All other global event callbacks will be deactivated.

```
OTF2_GlobalEvtReaderCallbacks* event_callbacks =
OTF2_GlobalEvtReaderCallbacks_New();
OTF2_GlobalEvtReaderCallbacks_SetEnterCallback( event_callbacks, &Enter_pri
nt );
OTF2_GlobalEvtReaderCallbacks_SetLeaveCallback( event_callbacks, &Leave_pri
nt );

OTF2_Reader_RegisterGlobalEvtCallbacks( reader, global_evt_reader, event_ca
llbacks, NULL );
OTF2_GlobalEvtReaderCallbacks_Delete( event_callbacks );
```

Read all events in the OTF2 archive. The events are automatically ordered by the time they occurred in the trace. Everytime an enter or leave event is read, the previously registered callbacks are triggered. In `events_read` the number of read events is returned.

```
uint64_t events_read = 0;
OTF2_Reader_ReadAllGlobalEvents( reader, global_evt_reader, &events_read );
```

At the end, close the reader and exit. All opened event and definition readers are closed automatically.

APPENDIX G. USAGE IN READING MODE

```
    OTF2_Reader_Close( reader );  
  
    return EXIT_SUCCESS;  
}
```

To compile your program use a command like:

```
gcc `otf2-config --cflags` -c otf2_reader_example.c -o otf2_reader_example.o
```

Now you can link your program with:

```
gcc otf2_reader_example.o `otf2-config --ldflags` `otf2-config --libs` -o otf2_  
reader_example
```

Appendix H

Deprecated List

Page [List of all event records](#) In version 1.2

Global [OTF2_AttributeList_AddString](#)(OTF2_AttributeList *attributeList, OTF2_AttributeRef attribute, ...)
Use [OTF2_AttributeList_AddStringRef](#)() instead.

Global [OTF2_AttributeList_GetString](#)(const OTF2_AttributeList *attributeList, OTF2_AttributeRef attribute, ...)
Use [OTF2_AttributeList_GetStringRef](#)() instead.

Global [OTF2_EvtWriter_OmpAcquireLock](#)(OTF2_EvtWriter *writer, OTF2_AttributeList *attributeList, ...)
In version 1.2

Global [OTF2_EvtWriter_OmpFork](#)(OTF2_EvtWriter *writer, OTF2_AttributeList *attributeList, OTF2_AttributeList *attributeList, ...)
In version 1.2

Global [OTF2_EvtWriter_OmpJoin](#)(OTF2_EvtWriter *writer, OTF2_AttributeList *attributeList, OTF2_AttributeList *attributeList, ...)
In version 1.2

APPENDIX H. DEPRECATED LIST

Global **OTF2_EvtWriter_OmpReleaseLock**(OTF2_EvtWriter *writer, OTF2_AttributeList *attributeList, C
In version 1.2

Global **OTF2_EvtWriter_OmpTaskComplete**(OTF2_EvtWriter *writer, OTF2_AttributeList *attributeList, C
In version 1.2

Global **OTF2_EvtWriter_OmpTaskCreate**(OTF2_EvtWriter *writer, OTF2_AttributeList *attributeList, C
In version 1.2

Global **OTF2_EvtWriter_OmpTaskSwitch**(OTF2_EvtWriter *writer, OTF2_AttributeList *attributeList, C
In version 1.2

Appendix I

Data Structure Documentation

I.1 OTF2_AttributeValue Union Reference

Value container for an attributes.

```
#include <OTF2_AttributeList.h>
```

Data Fields

- [OTF2_AttributeRef attributeRef](#)
References a [Attribute](#) definition and will be mapped to the global definition if a mapping table of type [OTF2_MAPPING_ATTRIBUTE](#) is available.
- [OTF2_CommRef commRef](#)
References a [Comm](#) definition and will be mapped to the global definition if a mapping table of type [OTF2_MAPPING_COMM](#) is available.
- float [float32](#)
Arbitrary value of type float.
- double [float64](#)
Arbitrary value of type double.
- [OTF2_GroupRef groupRef](#)
References a [Group](#) definition and will be mapped to the global definition if a mapping table of type [OTF2_MAPPING_GROUP](#) is available.
- int16_t [int16](#)
Arbitrary value of type [int16_t](#).

APPENDIX I. DATA STRUCTURE DOCUMENTATION

- `int32_t int32`
Arbitrary value of type `int32_t`.
- `int64_t int64`
Arbitrary value of type `int64_t`.
- `int8_t int8`
Arbitrary value of type `int8_t`.
- `OTF2_LocationRef locationRef`
References a `Location` definition and will be mapped to the global definition if a mapping table of type `OTF2_MAPPING_LOCATION` is available.
- `OTF2_MetricRef metricRef`
References a `MetricClass`, or a `MetricInstance` definition and will be mapped to the global definition if a mapping table of type `OTF2_MAPPING_METRIC` is available.
- `OTF2_ParameterRef parameterRef`
References a `Parameter` definition and will be mapped to the global definition if a mapping table of type `OTF2_MAPPING_PARAMETER` is available.
- `OTF2_RegionRef regionRef`
References a `Region` definition and will be mapped to the global definition if a mapping table of type `OTF2_MAPPING_REGION` is available.
- `OTF2_RmaWinRef rmaWinRef`
References a `RmaWin` definition and will be mapped to the global definition if a mapping table of type `OTF2_MAPPING_RMA_WIN` is available.
- `OTF2_StringRef stringRef`
References a `String` definition and will be mapped to the global definition if a mapping table of type `OTF2_MAPPING_STRING` is available.
- `uint16_t uint16`
Arbitrary value of type `uint16_t`.
- `uint32_t uint32`
Arbitrary value of type `uint32_t`.
- `uint64_t uint64`

I.2 OTF2_FileSionCallbacks Struct Reference

Arbitrary value of type uint64_t.

- `uint8_t uint8`

Arbitrary value of type uint8_t.

I.1.1 Detailed Description

Value container for an attributes. For definition references ([OTF2_MappingType](#)) use the same data type as the definition.

The documentation for this union was generated from the following file:

- [OTF2_AttributeList.h](#)

I.2 OTF2_FileSionCallbacks Struct Reference

Structure holding the SION callbacks.

```
#include <OTF2_Callbacks.h>
```

Data Fields

- [OTF2_FileSionClose](#) `otf2_file_sion_close`
Callback which is called to close a SION file.
- [OTF2_FileSionGetRank](#) `otf2_file_sion_get_rank`
Callback which is called to get the MPI rank in read mode.
- [OTF2_FileSionOpen](#) `otf2_file_sion_open`
Callback which is called to open a SION file.

I.2.1 Detailed Description

Structure holding the SION callbacks. To be used in a call to [OTF2_Archive_-SetFileSionCallbacks](#).

The documentation for this struct was generated from the following file:

- [OTF2_Callbacks.h](#)

I.3 OTF2_FlushCallbacks Struct Reference

Structure holding the flush callbacks.

```
#include <OTF2_Callbacks.h>
```

Data Fields

- [OTF2_PostFlushCallback otf2_post_flush](#)
Callback which is called after a flush.
- [OTF2_PreFlushCallback otf2_pre_flush](#)
Callback which is called prior a flush.

I.3.1 Detailed Description

Structure holding the flush callbacks. To be used in a call to [OTF2_Archive_-SetFlushCallbacks](#).

otf2_post_flush callback may be NULL to suppress writing a BufferFlush record.

The documentation for this struct was generated from the following file:

- [OTF2_Callbacks.h](#)

I.4 OTF2_MemoryCallbacks Struct Reference

Structure holding the memory callbacks.

```
#include <OTF2_Callbacks.h>
```

Data Fields

- [OTF2_MemoryAllocate otf2_allocate](#)
Callback which is called to allocate a new chunk.
- [OTF2_MemoryFreeAll otf2_free_all](#)
Callback which is called to release all previous allocated chunks.

I.5 OTF2_MetricValue Union Reference

I.4.1 Detailed Description

Structure holding the memory callbacks. To be used in a call to [OTF2_Archive_-SetMemoryCallbacks](#).

The documentation for this struct was generated from the following file:

- [OTF2_Callbacks.h](#)

I.5 OTF2_MetricValue Union Reference

Metric value.

I.5.1 Detailed Description

Metric value.

The documentation for this union was generated from the following file:

- [OTF2_Events.h](#)

APPENDIX I. DATA STRUCTURE DOCUMENTATION

Appendix J

File Documentation

J.1 otf2.h File Reference

Main include file for applications using OTF2.

```
#include <otf2/OTF2_Reader.h>
```

J.1.1 Detailed Description

Main include file for applications using OTF2.

Maintainer:

Michael Wagner <michael.wagner@zih.tu-dresden.de>

Authors

Dominic Eschweiler <d.eschweiler@fz-juelich.de>, Michael Wagner <michael.wagner@zih.tu-dresden.de>

J.2 OTF2_Archive.h File Reference

Writing interface for OTF2 archives.

```
#include <stdint.h>
#include <otf2/OTF2_ErrorCodes.h>
#include <otf2/OTF2_Callbacks.h>
#include <otf2/OTF2_DefWriter.h>
#include <otf2/OTF2_DefReader.h>
```

APPENDIX J. FILE DOCUMENTATION

```
#include <otf2/OTF2_EvtWriter.h>
#include <otf2/OTF2_EvtReader.h>
#include <otf2/OTF2_SnapWriter.h>
#include <otf2/OTF2_SnapReader.h>
#include <otf2/OTF2_GlobalDefWriter.h>
#include <otf2/OTF2_GlobalDefReader.h>
#include <otf2/OTF2_GlobalEvtReader.h>
#include <otf2/OTF2_GlobalSnapReader.h>
#include <otf2/OTF2_Thumbnail.h>
#include <otf2/OTF2_MarkerWriter.h>
#include <otf2/OTF2_MarkerReader.h>
```

Defines

- #define [OTF2_CHUNK_SIZE_DEFINITIONS_DEFAULT](#) (4 * 1024 * 1024)
Default size for OTF2's internal event chunk memory handling.
- #define [OTF2_CHUNK_SIZE_EVENTS_DEFAULT](#) (1024 * 1024)
Default size for OTF2's internal event chunk memory handling.

Typedefs

- typedef struct OTF2_Archive_struct [OTF2_Archive](#)
Keeps all meta-data for an OTF2 archive.
- typedef uint8_t [OTF2_MasterSlaveMode](#)
Defines whether a location is master or slave.

Enumerations

- enum [OTF2_MasterSlaveMode_enum](#) {
 [OTF2_SLAVE](#) = 0,
 [OTF2_MASTER](#) = 1 }
Defines whether a location is master or slave.

J.2 OTF2_Archive.h File Reference

Functions

- [OTF2_ErrorCode OTF2_Archive_Close](#) ([OTF2_Archive *archive](#))
Close an opened archive.
- [OTF2_ErrorCode OTF2_Archive_CloseDefReader](#) ([OTF2_Archive *archive](#),
[OTF2_DefReader *reader](#))
Close an opened local definition reader.
- [OTF2_ErrorCode OTF2_Archive_CloseDefWriter](#) ([OTF2_Archive *archive](#),
[OTF2_DefWriter *writer](#))
Close an opened local definition writer.
- [OTF2_ErrorCode OTF2_Archive_CloseEvtReader](#) ([OTF2_Archive *archive](#),
[OTF2_EvtReader *reader](#))
Close an opened local event reader.
- [OTF2_ErrorCode OTF2_Archive_CloseEvtWriter](#) ([OTF2_Archive *archive](#),
[OTF2_EvtWriter *writer](#))
Close an opened local event writer.
- [OTF2_ErrorCode OTF2_Archive_CloseGlobalDefReader](#) ([OTF2_Archive *archive](#),
[OTF2_GlobalDefReader *globalDefReader](#))
Closes the global definition reader.
- [OTF2_ErrorCode OTF2_Archive_CloseGlobalEvtReader](#) ([OTF2_Archive *archive](#),
[OTF2_GlobalEvtReader *globalEvtReader](#))
Closes the global event reader.
- [OTF2_ErrorCode OTF2_Archive_CloseGlobalSnapReader](#) ([OTF2_Archive *archive](#),
[OTF2_GlobalSnapReader *globalSnapReader](#))
Close the opened global snapshot reader.
- [OTF2_ErrorCode OTF2_Archive_CloseMarkerReader](#) ([OTF2_Archive *archive](#),
[OTF2_MarkerReader *markerReader](#))
Closes the marker reader.
- [OTF2_ErrorCode OTF2_Archive_CloseMarkerWriter](#) ([OTF2_Archive *archive](#),
[OTF2_MarkerWriter *writer](#))
Close an opened marker writer.

APPENDIX J. FILE DOCUMENTATION

- [OTF2_ErrorCode](#) [OTF2_Archive_CloseSnapReader](#) ([OTF2_Archive](#) *archive, [OTF2_SnapReader](#) *reader)
Close an opened local snap reader.
- [OTF2_ErrorCode](#) [OTF2_Archive_CloseSnapWriter](#) ([OTF2_Archive](#) *archive, [OTF2_SnapWriter](#) *writer)
Close an opened local snap writer.
- [OTF2_ErrorCode](#) [OTF2_Archive_CloseThumbReader](#) ([OTF2_Archive](#) *archive, [OTF2_ThumbReader](#) *reader)
Close an opened thumbnail reader.
- [OTF2_ErrorCode](#) [OTF2_Archive_GetChunkSize](#) ([OTF2_Archive](#) *archive, [uint64_t](#) *chunkSizeEvents, [uint64_t](#) *chunkSizeDefs)
Get the chunksize.
- [OTF2_ErrorCode](#) [OTF2_Archive_GetCompression](#) ([OTF2_Archive](#) *archive, [OTF2_Compression](#) *compression)
Get compression mode (none or zlib)
- [OTF2_ErrorCode](#) [OTF2_Archive_GetCreator](#) ([OTF2_Archive](#) *archive, [char](#) **creator)
Get creator information.
- [OTF2_DefReader](#) * [OTF2_Archive_GetDefReader](#) ([OTF2_Archive](#) *archive, [OTF2_LocationRef](#) location)
Get a local definition reader.
- [OTF2_DefWriter](#) * [OTF2_Archive_GetDefWriter](#) ([OTF2_Archive](#) *archive, [OTF2_LocationRef](#) location)
Get a local definition writer.
- [OTF2_ErrorCode](#) [OTF2_Archive_GetDescription](#) ([OTF2_Archive](#) *archive, [char](#) **description)
Get description.
- [OTF2_EvtReader](#) * [OTF2_Archive_GetEvtReader](#) ([OTF2_Archive](#) *archive, [OTF2_LocationRef](#) location)
Get a local event reader.
- [OTF2_EvtWriter](#) * [OTF2_Archive_GetEvtWriter](#) ([OTF2_Archive](#) *archive, [OTF2_LocationRef](#) location)

J.2 OTF2_Archive.h File Reference

Get a local event writer.

- [OTF2_ErrorCode](#) [OTF2_Archive_GetFileSubstrate](#) ([OTF2_Archive](#) *archive, [OTF2_FileSubstrate](#) *substrate)

Get the file substrate (posix, sion, none)

- [OTF2_GlobalDefReader](#) * [OTF2_Archive_GetGlobalDefReader](#) ([OTF2_Archive](#) *archive)

Get a global definition reader.

- [OTF2_GlobalDefWriter](#) * [OTF2_Archive_GetGlobalDefWriter](#) ([OTF2_Archive](#) *archive)

Get a global definition writer.

- [OTF2_GlobalEvtReader](#) * [OTF2_Archive_GetGlobalEvtReader](#) ([OTF2_Archive](#) *archive)

Get a global event reader.

- [OTF2_GlobalSnapReader](#) * [OTF2_Archive_GetGlobalSnapReader](#) ([OTF2_Archive](#) *archive)

Get a global snap reader.

- [OTF2_ErrorCode](#) [OTF2_Archive_GetMachineName](#) ([OTF2_Archive](#) *archive, [char](#) **machineName)

Get machine name.

- [OTF2_MarkerReader](#) * [OTF2_Archive_GetMarkerReader](#) ([OTF2_Archive](#) *archive)

Get a marker reader.

- [OTF2_MarkerWriter](#) * [OTF2_Archive_GetMarkerWriter](#) ([OTF2_Archive](#) *archive)

Get a marker writer.

- [OTF2_ErrorCode](#) [OTF2_Archive_GetMasterSlaveMode](#) ([OTF2_Archive](#) *archive, [OTF2_MasterSlaveMode](#) *masterOrSlave)

Get master slave mode.

- [OTF2_ErrorCode](#) [OTF2_Archive_GetNumberOfGlobalDefinitions](#) ([OTF2_Archive](#) *archive, [uint64_t](#) *numberOfDefinitions)

Get the number of global definitions.

APPENDIX J. FILE DOCUMENTATION

- [OTF2_ErrorCode OTF2_Archive_GetNumberOfLocations](#) ([OTF2_Archive](#) *archive, [uint64_t](#) *numberOfLocations)
Get the number of locations.
- [OTF2_ErrorCode OTF2_Archive_GetNumberOfSnapshots](#) ([OTF2_Archive](#) *archive, [uint32_t](#) *number)
Get the number of snapshots.
- [OTF2_ErrorCode OTF2_Archive_GetNumberOfThumbnails](#) ([OTF2_Archive](#) *archive, [uint32_t](#) *number)
Get the number of thumbnails.
- [OTF2_ErrorCode OTF2_Archive_GetProperty](#) ([OTF2_Archive](#) *archive, [const char](#) *name, [char](#) **value)
Get the value of the named trace file property.
- [OTF2_ErrorCode OTF2_Archive_GetPropertyNames](#) ([OTF2_Archive](#) *archive, [uint32_t](#) *numberOfProperties, [char](#) ***names)
Get the names of all trace file properties.
- [OTF2_SnapReader * OTF2_Archive_GetSnapReader](#) ([OTF2_Archive](#) *archive, [OTF2_LocationRef](#) location)
Get a local snap reader.
- [OTF2_SnapWriter * OTF2_Archive_GetSnapWriter](#) ([OTF2_Archive](#) *archive, [OTF2_LocationRef](#) location)
Get a local snap writer.
- [OTF2_ThumbReader * OTF2_Archive_GetThumbReader](#) ([OTF2_Archive](#) *archive, [uint32_t](#) number)
Get a thumb reader.
- [OTF2_ThumbWriter * OTF2_Archive_GetThumbWriter](#) ([OTF2_Archive](#) *archive, [const char](#) *name, [const char](#) *description, [OTF2_ThumbnailType](#) type, [uint32_t](#) numberOfSamples, [uint32_t](#) numberOfMetrics, [const uint64_t](#) *refsToDefs)
Get a thumb writer.
- [OTF2_ErrorCode OTF2_Archive_GetTraceId](#) ([OTF2_Archive](#) *archive, [uint64_t](#) *id)
Get the identifier of the trace file.

J.2 OTF2_Archive.h File Reference

- [OTF2_ErrorCode](#) [OTF2_Archive_GetVersion](#) ([OTF2_Archive](#) *archive, [uint8_t](#) *major, [uint8_t](#) *minor, [uint8_t](#) *bugfix)
Get format version.
- [OTF2_Archive](#) * [OTF2_Archive_Open](#) (const char *archivePath, const char *archiveName, const [OTF2_FileMode](#) fileMode, const [uint64_t](#) chunkSizeEvents, const [uint64_t](#) chunkSizeDefs, const [OTF2_FileSubstrate](#) fileSubstrate, const [OTF2_Compression](#) compression)
Create a new archive.
- [OTF2_ErrorCode](#) [OTF2_Archive_SetBoolProperty](#) ([OTF2_Archive](#) *archive, const char *name, bool value, bool overwrite)
Add or remove a boolean trace file property to this archive.
- [OTF2_ErrorCode](#) [OTF2_Archive_SetCreator](#) ([OTF2_Archive](#) *archive, const char *creator)
Set creator.
- [OTF2_ErrorCode](#) [OTF2_Archive_SetDescription](#) ([OTF2_Archive](#) *archive, const char *description)
Set a description.
- [OTF2_ErrorCode](#) [OTF2_Archive_SetFileSionCallbacks](#) ([OTF2_Archive](#) *archive, const [OTF2_FileSionCallbacks](#) *fileSionCallbacks, void *fileSionData)
Set the SION callbacks for the archive.
- [OTF2_ErrorCode](#) [OTF2_Archive_SetFlushCallbacks](#) ([OTF2_Archive](#) *archive, const [OTF2_FlushCallbacks](#) *flushCallbacks, void *flushData)
Set the flush callbacks for the archive.
- [OTF2_ErrorCode](#) [OTF2_Archive_SetMachineName](#) ([OTF2_Archive](#) *archive, const char *machineName)
Set machine name.
- [OTF2_ErrorCode](#) [OTF2_Archive_SetMasterSlaveMode](#) ([OTF2_Archive](#) *archive, [OTF2_MasterSlaveMode](#) masterOrSlave)
Set master slave mode.
- [OTF2_ErrorCode](#) [OTF2_Archive_SetMemoryCallbacks](#) ([OTF2_Archive](#) *archive, const [OTF2_MemoryCallbacks](#) *memoryCallbacks, void *memoryData)
Set the memory callbacks for the archive.

APPENDIX J. FILE DOCUMENTATION

- [OTF2_ErrorCode](#) [OTF2_Archive_SetNumberOfSnapshots](#) ([OTF2_Archive](#) *archive, uint32_t number)

Set the number of snapshots.

- [OTF2_ErrorCode](#) [OTF2_Archive_SetProperty](#) ([OTF2_Archive](#) *archive, const char *name, const char *value, bool overwrite)

Add or remove a trace file property to this archive.

- [OTF2_ErrorCode](#) [OTF2_Archive_SwitchFileMode](#) ([OTF2_Archive](#) *archive, [OTF2_FileMode](#) newFileMode)

Switch file mode of the archive.

J.2.1 Detailed Description

Writing interface for OTF2 archives.

Maintainer:

Michael Wagner <michael.wagner@zih.tu-dresden.de>

Authors

Dominic Eschweiler <d.eschweiler@fz-juelich.de>, Michael Wagner <michael.wagner@zih.tu-dresden.de>

J.2.2 Define Documentation

J.2.2.1 `#define OTF2_CHUNK_SIZE_DEFINITIONS_DEFAULT (4 * 1024 * 1024)`

Default size for OTF2's internal event chunk memory handling.

If you are not sure which chunk size is the best to use, use this default value.

J.2.2.2 `#define OTF2_CHUNK_SIZE_EVENTS_DEFAULT (1024 * 1024)`

Default size for OTF2's internal event chunk memory handling.

If you are not sure which chunk size is the best to use, use this default value.

J.2 OTF2_Archive.h File Reference

J.2.3 Typedef Documentation

J.2.3.1 typedef struct OTF2_Archive_struct OTF2_Archive

Keeps all meta-data for an OTF2 archive.

An OTF2 archive handle keeps all runtime information about an OTF2 archive. It is the central handle to get and set information about the archive and to request event and definition writer handles.

J.2.3.2 typedef uint8_t OTF2_MasterSlaveMode

Defines whether a location is master or slave.

The master of creates the directory layout and writes the anchor file. Therefore, only one archive handle can be the master, e.g. the MPI rank 0. All other archive handles must be defined as slaves.

Please see OTF2_MasterSlaveMode_enum for a description of available values.

J.2.4 Enumeration Type Documentation

J.2.4.1 enum OTF2_MasterSlaveMode_enum

Defines whether a location is master or slave.

Enumerator:

OTF2_SLAVE Location is slave.

OTF2_MASTER Location is master.

J.2.5 Function Documentation

J.2.5.1 OTF2_ErrorCode OTF2_Archive_Close (OTF2_Archive * *archive*)

Close an opened archive.

Closes an opened archive and releases the associated resources. Closes also all opened writer and reader handles. Does nothing if NULL is passed.

Parameters

| | |
|----------------|-----------------|
| <i>archive</i> | Archive handle. |
|----------------|-----------------|

Returns

OTF2_SUCCESS if successful, an error code if an error occurs.

J.2.5.2 **OTF2_ErrorCode** **OTF2_Archive_CloseDefReader** (**OTF2_Archive** * *archive*,
OTF2_DefReader * *reader*)

Close an opened local definition reader.

Parameters

| | |
|----------------|-----------------------------|
| <i>archive</i> | Archive handle. |
| <i>reader</i> | Reader handle to be closed. |

Returns

OTF2_SUCCESS if successful, an error code if an error occurs.

J.2.5.3 **OTF2_ErrorCode** **OTF2_Archive_CloseDefWriter** (**OTF2_Archive** * *archive*,
OTF2_DefWriter * *writer*)

Close an opened local definition writer.

Parameters

| | |
|----------------|-----------------------------|
| <i>archive</i> | Archive handle. |
| <i>writer</i> | Writer handle to be closed. |

Returns

OTF2_SUCCESS if successful, an error code if an error occurs.

J.2.5.4 **OTF2_ErrorCode** **OTF2_Archive_CloseEvtReader** (**OTF2_Archive** * *archive*,
OTF2_EvtReader * *reader*)

Close an opened local event reader.

Parameters

| | |
|----------------|-----------------------------|
| <i>archive</i> | Archive handle. |
| <i>reader</i> | Reader handle to be closed. |

J.2 OTF2_Archive.h File Reference

Returns

OTF2_SUCCESS if successful, an error code if an error occurs.

J.2.5.5 OTF2_ErrorCode OTF2_Archive_CloseEvtWriter (OTF2_Archive * archive, OTF2_EvtWriter * writer)

Close an opened local event writer.

Parameters

| | |
|----------------|-----------------------------|
| <i>archive</i> | Archive handle. |
| <i>writer</i> | Writer handle to be closed. |

Returns

OTF2_SUCCESS if successful, an error code if an error occurs.

J.2.5.6 OTF2_ErrorCode OTF2_Archive_CloseGlobalDefReader (OTF2_Archive * archive, OTF2_GlobalDefReader * globalDefReader)

Closes the global definition reader.

Parameters

| | |
|-------------------------|-------------------------------|
| <i>archive</i> | Archive handle. |
| <i>globalDef-Reader</i> | The global definition reader. |

Returns

OTF2_SUCCESS if successful, an error code if an error occurs.

J.2.5.7 OTF2_ErrorCode OTF2_Archive_CloseGlobalEvtReader (OTF2_Archive * archive, OTF2_GlobalEvtReader * globalEvtReader)

Closes the global event reader.

This closes also all local event readers.

Parameters

| | |
|----------------|-----------------|
| <i>archive</i> | Archive handle. |
|----------------|-----------------|

APPENDIX J. FILE DOCUMENTATION

| | |
|------------------------|--------------------------|
| <i>globalEvtReader</i> | The global event reader. |
|------------------------|--------------------------|

Returns

[*OTF2_SUCCESS*](#) if successful, an error code if an error occurs.

J.2.5.8 **OTF2_StatusCode** **OTF2_Archive_CloseGlobalSnapReader** (**OTF2_Archive *** *archive*, **OTF2_GlobalSnapReader *** *globalSnapReader*)

Close the opened global snapshot reader.

Parameters

| | |
|----------------|-----------------------------|
| <i>archive</i> | Archive handle. |
| <i>reader</i> | Reader handle to be closed. |

Since

Version 1.2

Returns

[*OTF2_SUCCESS*](#) if successful, an error code if an error occurs.

J.2.5.9 **OTF2_StatusCode** **OTF2_Archive_CloseMarkerReader** (**OTF2_Archive *** *archive*, **OTF2_MarkerReader *** *markerReader*)

Closes the marker reader.

Parameters

| | |
|----------------------|--------------------|
| <i>archive</i> | Archive handle. |
| <i>marker-Reader</i> | The marker reader. |

Since

Version 1.2

Returns

[*OTF2_SUCCESS*](#) if successful, an error code if an error occurs.

J.2 OTF2_Archive.h File Reference

J.2.5.10 **OTF2_ErrorCode** **OTF2_Archive_CloseMarkerWriter** (**OTF2_Archive *** *archive*, **OTF2_MarkerWriter *** *writer*)

Close an opened marker writer.

Parameters

| | |
|----------------|-----------------------------|
| <i>archive</i> | Archive handle. |
| <i>writer</i> | Writer handle to be closed. |

Since

Version 1.2

Returns

[*OTF2_SUCCESS*](#) if successful, an error code if an error occurs.

J.2.5.11 **OTF2_ErrorCode** **OTF2_Archive_CloseSnapReader** (**OTF2_Archive *** *archive*, **OTF2_SnapReader *** *reader*)

Close an opened local snap reader.

Parameters

| | |
|----------------|-----------------------------|
| <i>archive</i> | Archive handle. |
| <i>reader</i> | Reader handle to be closed. |

Returns

[*OTF2_SUCCESS*](#) if successful, an error code if an error occurs.

Since

Version 1.2

J.2.5.12 **OTF2_ErrorCode** **OTF2_Archive_CloseSnapWriter** (**OTF2_Archive *** *archive*, **OTF2_SnapWriter *** *writer*)

Close an opened local snap writer.

Parameters

| | |
|----------------|-----------------------------|
| <i>archive</i> | Archive handle. |
| <i>writer</i> | Writer handle to be closed. |

Since

Version 1.2

Returns

OTF2_SUCCESS if successful, an error code if an error occurs.

J.2.5.13 `OTF2_StatusCode OTF2_Archive.CloseThumbReader (OTF2_Archive * archive, OTF2_ThumbReader * reader)`

Close an opened thumbnail reader.

Parameters

| | |
|----------------|-----------------------------|
| <i>archive</i> | Archive handle. |
| <i>reader</i> | Reader handle to be closed. |

Since

Version 1.2

Returns

OTF2_SUCCESS if successful, an error code if an error occurs.

J.2.5.14 `OTF2_StatusCode OTF2_Archive.GetChunkSize (OTF2_Archive * archive, uint64_t * chunkSizeEvents, uint64_t * chunkSizeDefs)`

Get the chunksize.

Parameters

| | | |
|-----|-------------------------|----------------------------------|
| | <i>archive</i> | Archive handle. |
| out | <i>chunk-SizeEvents</i> | Chunk size for event files. |
| out | <i>chunk-SizeDefs</i> | Chunk size for definition files. |

Returns

OTF2_SUCCESS if successful, an error code if an error occurs.

J.2 OTF2_Archive.h File Reference

J.2.5.15 `OTF2_ErrorCode OTF2_Archive_GetCompression (OTF2_Archive * archive, OTF2_Compression * compression)`

Get compression mode (none or zlib)

Parameters

| | | |
|-----|--------------------|----------------------------|
| | <i>archive</i> | Archive handle. |
| out | <i>compression</i> | Returned compression mode. |

Returns

OTF2_SUCCESS if successful, an error code if an error occurs.

J.2.5.16 `OTF2_ErrorCode OTF2_Archive_GetCreator (OTF2_Archive * archive, char ** creator)`

Get creator information.

Parameters

| | | |
|-----|----------------|--|
| | <i>archive</i> | Archive handle. |
| out | <i>creator</i> | Returned creator. Allocated with <i>malloc</i> . |

Returns

OTF2_SUCCESS if successful, an error code if an error occurs.

J.2.5.17 `OTF2_DefReader* OTF2_Archive_GetDefReader (OTF2_Archive * archive, OTF2_LocationRef location)`

Get a local definition reader.

Parameters

| | |
|-----------------|---|
| <i>archive</i> | Archive handle. |
| <i>location</i> | Location ID of the requested reader handle. |

Returns

Returns a local definition reader handle if successful, NULL if an error occurs.

APPENDIX J. FILE DOCUMENTATION

J.2.5.18 `OTF2_DefWriter*` `OTF2_Archive_GetDefWriter (OTF2_Archive * archive,
OTF2_LocationRef location)`

Get a local definition writer.

Parameters

| | |
|-----------------|---|
| <i>archive</i> | Archive handle. |
| <i>location</i> | Location ID of the requested writer handle. |

Returns

Returns a local definition writer handle if successful, NULL if an error occurs.

J.2.5.19 `OTF2_ErrorCode` `OTF2_Archive_GetDescription (OTF2_Archive * archive,
char ** description)`

Get description.

Parameters

| | | |
|-----|--------------------|--|
| | <i>archive</i> | Archive handle. |
| out | <i>description</i> | Returned description. Allocated with <i>malloc</i> . |

Returns

[*OTF2_SUCCESS*](#) if successful, an error code if an error occurs.

J.2.5.20 `OTF2_EvtReader*` `OTF2_Archive_GetEvtReader (OTF2_Archive * archive,
OTF2_LocationRef location)`

Get a local event reader.

Parameters

| | |
|-----------------|---|
| <i>archive</i> | Archive handle. |
| <i>location</i> | Location ID of the requested reader handle. |

Returns

Returns a local event reader handle if successful, NULL if an error occurs.

J.2 OTF2_Archive.h File Reference

J.2.5.21 OTF2_EvtWriter* OTF2_Archive_GetEvtWriter (OTF2_Archive * *archive*, OTF2_LocationRef *location*)

Get a local event writer.

Parameters

| | |
|-----------------|---|
| <i>archive</i> | Archive handle. |
| <i>location</i> | Location ID of the requested writer handle. |

Returns

Returns a local event writer handle if successful, NULL if an error occurs.

J.2.5.22 OTF2_ErrorCode OTF2_Archive_GetFileSubstrate (OTF2_Archive * *archive*, OTF2_FileSubstrate * *substrate*)

Get the file substrate (posix, sion, none)

Parameters

| | | |
|-----|------------------|--------------------------|
| | <i>archive</i> | Archive handle. |
| out | <i>substrate</i> | Returned file substrate. |

Returns

[*OTF2_SUCCESS*](#) if successful, an error code if an error occurs.

J.2.5.23 OTF2_GlobalDefReader* OTF2_Archive_GetGlobalDefReader (OTF2_Archive * *archive*)

Get a global definition reader.

Parameters

| | |
|----------------|-----------------|
| <i>archive</i> | Archive handle. |
|----------------|-----------------|

Returns

Returns a global definition reader handle if successful, NULL if an error occurs.

APPENDIX J. FILE DOCUMENTATION

J.2.5.24 **OTF2_GlobalDefWriter*** **OTF2_Archive_GetGlobalDefWriter (**
OTF2_Archive * archive)

Get a global definition writer.

Parameters

| | |
|----------------|-----------------|
| <i>archive</i> | Archive handle. |
|----------------|-----------------|

Returns

Returns a global definition writer handle if successful, NULL if an error occurs.

J.2.5.25 **OTF2_GlobalEvtReader*** **OTF2_Archive_GetGlobalEvtReader (**
OTF2_Archive * archive)

Get a global event reader.

Parameters

| | |
|----------------|-----------------|
| <i>archive</i> | Archive handle. |
|----------------|-----------------|

Returns

Returns a global event reader handle if successful, NULL if an error occurs.

J.2.5.26 **OTF2_GlobalSnapReader*** **OTF2_Archive_GetGlobalSnapReader (**
OTF2_Archive * archive)

Get a global snap reader.

Parameters

| | |
|----------------|-----------------|
| <i>archive</i> | Archive handle. |
|----------------|-----------------|

Since

Version 1.2

Returns

Returns a global snap reader handle if successful, NULL if an error occurs.

J.2 OTF2_Archive.h File Reference

J.2.5.27 `OTF2_ErrorCode OTF2_Archive_GetMachineName (OTF2_Archive * archive, char ** machineName)`

Get machine name.

Parameters

| | | |
|-----|---------------------|---|
| | <i>archive</i> | Archive handle. |
| out | <i>machine-Name</i> | Returned machine name. Allocated with <i>malloc</i> . |

Returns

OTF2_SUCCESS if successful, an error code if an error occurs.

J.2.5.28 `OTF2_MarkerReader* OTF2_Archive_GetMarkerReader (OTF2_Archive * archive)`

Get a marker reader.

Parameters

| | |
|----------------|-----------------|
| <i>archive</i> | Archive handle. |
|----------------|-----------------|

Since

Version 1.2

Returns

Returns a marker reader handle if successful, NULL if an error occurs.

J.2.5.29 `OTF2_MarkerWriter* OTF2_Archive_GetMarkerWriter (OTF2_Archive * archive)`

Get a marker writer.

Parameters

| | |
|----------------|-----------------|
| <i>archive</i> | Archive handle. |
|----------------|-----------------|

Since

Version 1.2

APPENDIX J. FILE DOCUMENTATION

Returns

Returns a marker writer handle if successful, NULL if an error occurs.

J.2.5.30 `OTF2_ErrorCode OTF2_Archive.GetMasterSlaveMode (OTF2_Archive * archive, OTF2_MasterSlaveMode * masterOrSlave)`

Get master slave mode.

Parameters

| | | |
|-----|----------------------|--|
| | <i>archive</i> | Archive handle. |
| out | <i>masterOrSlave</i> | Return pointer to the master slave mode. |

Returns

[*OTF2_SUCCESS*](#) if successful, an error code if an error occurs.

J.2.5.31 `OTF2_ErrorCode OTF2_Archive.GetNumberOfGlobalDefinitions (OTF2_Archive * archive, uint64_t * numberOfDefinitions)`

Get the number of global definitions.

Parameters

| | | |
|-----|----------------------------|---|
| | <i>archive</i> | Archive handle. |
| out | <i>numberOfDefinitions</i> | Return pointer to the number of global definitions. |

Returns

[*OTF2_SUCCESS*](#) if successful, an error code if an error occurs.

J.2.5.32 `OTF2_ErrorCode OTF2_Archive.GetNumberOfLocations (OTF2_Archive * archive, uint64_t * numberOfLocations)`

Get the number of locations.

Parameters

| | | |
|--|----------------|-----------------|
| | <i>archive</i> | Archive handle. |
|--|----------------|-----------------|

J.2 OTF2_Archive.h File Reference

| | | |
|-----|--------------------------------------|--|
| out | <i>num- berOfLoca- tions</i> | Return pointer to the number of locations. |
|-----|--------------------------------------|--|

Returns

OTF2_SUCCESS if successful, an error code if an error occurs.

J.2.5.33 OTF2_StatusCode OTF2_Archive.GetNumberOfSnapshots (OTF2_Archive * archive, uint32_t * number)

Get the number of snapshots.

Parameters

| | |
|----------------|------------------|
| <i>archive</i> | Archive handle. |
| <i>number</i> | Snapshot number. |

Since

Version 1.2

Returns

OTF2_SUCCESS if successful, an error code if an error occurs.

J.2.5.34 OTF2_StatusCode OTF2_Archive.GetNumberOfThumbnails (OTF2_Archive * archive, uint32_t * number)

Get the number of thumbnails.

Parameters

| | |
|----------------|-----------------|
| <i>archive</i> | Archive handle. |
| <i>number</i> | Thumb number. |

Since

Version 1.2

Returns

OTF2_SUCCESS if successful, an error code if an error occurs.

APPENDIX J. FILE DOCUMENTATION

J.2.5.35 `OTF2_ErrorCode OTF2_Archive.GetProperty (OTF2_Archive * archive, const char * name, char ** value)`

Get the value of the named trace file property.

Parameters

| | | |
|-----|----------------|--|
| | <i>archive</i> | Archive handle. |
| | <i>name</i> | Name of the property. |
| out | <i>value</i> | Returned value of the property. Allocated with <i>malloc</i> . |

Returns

OTF2_SUCCESS if successful

OTF2_ERROR_PROPERTY_NOT_FOUND if the named property was not found

J.2.5.36 `OTF2_ErrorCode OTF2_Archive.GetPropertyNames (OTF2_Archive * archive, uint32_t * numberOfProperties, char *** names)`

Get the names of all trace file properties.

Parameters

| | | |
|-----|---------------------------|---|
| | <i>archive</i> | Archive handle. |
| out | <i>numberOfProperties</i> | Returned number of trace file properties. |
| out | <i>names</i> | Returned list of property names. Allocated with <i>malloc</i> . To release memory, just pass <i>*names</i> to <i>free</i> . |

Returns

OTF2_SUCCESS if successful, an error code if an error occurs.

J.2.5.37 `OTF2_SnapReader* OTF2_Archive.GetSnapReader (OTF2_Archive * archive, OTF2_LocationRef location)`

Get a local snap reader.

Parameters

| | | |
|--|-----------------|---|
| | <i>archive</i> | Archive handle. |
| | <i>location</i> | Location ID of the requested snap handle. |

J.2 OTF2_Archive.h File Reference

Since

Version 1.2

Returns

Returns a local snap handle if successful, NULL if an error occurs.

J.2.5.38 `OTF2_SnapWriter*` `OTF2_Archive_GetSnapWriter (OTF2_Archive *
archive, OTF2_LocationRef location)`

Get a local snap writer.

Parameters

| | |
|-----------------|---|
| <i>archive</i> | Archive handle. |
| <i>location</i> | Location ID of the requested writer handle. |

Since

Version 1.2

Returns

Returns a local event writer handle if successful, NULL if an error occurs.

J.2.5.39 `OTF2_ThumbReader*` `OTF2_Archive_GetThumbReader (OTF2_Archive *
archive, uint32_t number)`

Get a thumb reader.

Parameters

| | |
|----------------|-------------------|
| <i>archive</i> | Archive handle. |
| <i>number</i> | Thumbnail number. |

Since

Version 1.2

Returns

Returns a global definition writer handle if successful, NULL if an error occurs.

APPENDIX J. FILE DOCUMENTATION

J.2.5.40 `OTF2_ThumbWriter*` `OTF2_Archive_GetThumbWriter (OTF2_Archive * archive, const char * name, const char * description, OTF2_ThumbnailType type, uint32_t numberOfSamples, uint32_t numberOfMetrics, const uint64_t * refsToDefs)`

Get a thumb writer.

Parameters

| | |
|------------------------|--|
| <i>archive</i> | Archive handle. |
| <i>name</i> | Name of thumb. |
| <i>description</i> | Description of thumb. |
| <i>type</i> | Type of thumb. |
| <i>numberOfSamples</i> | Number of samples. |
| <i>numberOfMetrics</i> | Number of metrics. |
| <i>refsToDefs</i> | <i>numberOfMetrics</i> references to definition matching the thumbnail type. |

Since

Version 1.2

Returns

Returns a thumb writer handle if successful, NULL if an error occurs.

J.2.5.41 `OTF2_ErrorCode` `OTF2_Archive_GetTraceId (OTF2_Archive * archive, uint64_t * id)`

Get the identifier of the trace file.

Note

This call is only allowed when the archive was opened with mode `OTF2_-FILEMODE_READ`.

Parameters

| | | |
|-----|----------------|-------------------|
| | <i>archive</i> | Archive handle. |
| out | <i>id</i> | Trace identifier. |

Returns

[*OTF2_SUCCESS*](#) if successful, an error code if an error occurs.

J.2 OTF2_Archive.h File Reference

J.2.5.42 `OTF2_ErrorCode OTF2_Archive_GetVersion (OTF2_Archive * archive, uint8_t * major, uint8_t * minor, uint8_t * bugfix)`

Get format version.

Parameters

| | | |
|-----|----------------|----------------------|
| | <i>archive</i> | Archive handle |
| out | <i>major</i> | Major version number |
| out | <i>minor</i> | Minor version number |
| out | <i>bugfix</i> | Bugfix revision |

Returns

[*OTF2_SUCCESS*](#) if successful, an error code if an error occurs.

J.2.5.43 `OTF2_Archive* OTF2_Archive_Open (const char * archivePath, const char * archiveName, const OTF2_FileMode fileMode, const uint64_t chunkSizeEvents, const uint64_t chunkSizeDefs, const OTF2_FileSubstrate fileSubstrate, const OTF2_Compression compression)`

Create a new archive.

Creates a new archive handle that keeps all meta data about the archive on runtime.

Parameters

| | |
|-------------------------|---|
| <i>archivePath</i> | Path to the archive i.e. the directory where the anchor file is located. |
| <i>archive-Name</i> | Name of the archive. It is used to generate sub pathes e.g. 'archive-Name.otf2'. |
| <i>fileMode</i> | Determines if in reading or writing mode. Available values are <i>OTF2_FILEMODE_WRITE</i> or <i>OTF2_FILEMODE_READ</i> . |
| <i>chunk-SizeEvents</i> | Requested size of OTF2's internal event chunks in writing mode. Available values are from 256kB to 16MB. The event chunk size affects performance as well as total memory usage. A value satisfying both is about 1MB. If you are not sure which chunk size is the best to use, use <i>OTF2_CHUNK_SIZE_EVENTS_DEFAULT</i> . In reading mode this value is ignored because the correct chunk size is extracted from the anchor file. |

APPENDIX J. FILE DOCUMENTATION

| | |
|-----------------------|--|
| <i>chunk-SizeDefs</i> | Requested size of OTF2's internal definition chunks in writing mode. Available values are from 256kB to 16MB. The definition chunk size affects performance as well as total memory usage. In addition, the definition chunk size must be big enough to carry the largest possible definition record. Therefore, the definition chunk size must be at least 10 times the number of locations. A value satisfying these requirements is about 4MB. If you are not sure which chunk size is the best to use, use OTF2_CHUNK_SIZE_DEFINITIONS_DEFAULT . In reading mode this value is ignored because the correct chunk size is extracted from the anchor file. |
| <i>fileSubstrate</i> | Determines which file substrate should be used in writing mode. Available values are OTF2_SUBSTRATE_POSIX to use the standard Posix interface, OTF2_SUBSTRATE_SION to use an installed SION library to store multiple logical files into fewer or one physical file, and OTF2_SUBSTRATE_NONE to suppress file writing at all. In reading mode this value is ignored because the correct file substrated is extracted from the anchor file. |
| <i>compression</i> | Determines if compression is used to reduce the size of data in files. Available values are OTF2_COMPRESSION_ZLIB to use an installed zlib and OTF2_COMPRESSION_NONE to disable compression. In reading mode this value is ignored because the correct file compression is extracted from the anchor file. |

Returns

Returns an archive handle if successful, NULL otherwise.

J.2.5.44 OTF2_ErrorCode OTF2_Archive.SetBoolProperty (OTF2_Archive * archive, const char * name, bool value, bool overwrite)

Add or remove a boolean trace file property to this archive.

Note

This call is only allowed when the archive was opened with mode [OTF2_FILEMODE_WRITE](#).

Parameters

| | |
|------------------|--|
| <i>archive</i> | Archive handle. |
| <i>name</i> | Name of the trace file property (case insensitive, [A-Z0-9_]). |
| <i>value</i> | Boolean value of property (e.g. true or false). |
| <i>overwrite</i> | If true a previous trace file property with the same name <i>name</i> will be overwritten. |

J.2 OTF2_Archive.h File Reference

Returns

OTF2_SUCCESS if successful

OTF2_ERROR_PROPERTY_NAME_INVALID if property name does not conform to the naming scheme

OTF2_ERROR_PROPERTY_NOT_FOUND if property was not found, but requested to remove

OTF2_ERROR_PROPERTY_EXISTS if property exists but overwrite was not set

J.2.5.45 OTF2_ErrorCode OTF2_Archive.SetCreator (OTF2_Archive * *archive*, const char * *creator*)

Set creator.

Sets information about the creator of the trace archive. This value is optional. It only needs to be set for an archive handle marked as 'master' or does not need to be set at all.

Parameters

| | |
|----------------|----------------------|
| <i>archive</i> | Archive handle. |
| <i>creator</i> | Creator information. |

Returns

OTF2_SUCCESS if successful, an error code if an error occurs.

J.2.5.46 OTF2_ErrorCode OTF2_Archive.SetDescription (OTF2_Archive * *archive*, const char * *description*)

Set a description.

Sets a description for a trace archive. This value is optional. It only needs to be set for an archive handle marked as 'master' or does not need to be set at all.

Parameters

| | |
|--------------------|-----------------|
| <i>archive</i> | Archive handle. |
| <i>description</i> | Description. |

Returns

OTF2_SUCCESS if successful, an error code if an error occurs.

APPENDIX J. FILE DOCUMENTATION

J.2.5.47 `OTF2_StatusCode OTF2_Archive_SetFileSionCallbacks (OTF2_Archive * archive, const OTF2_FileSionCallbacks * fileSionCallbacks, void * fileSionData)`

Set the SION callbacks for the archive.

Parameters

| | |
|---------------------------|--|
| <i>archive</i> | Archive handle. |
| <i>fileSion-Callbacks</i> | Struct holding the SION callback functions. |
| <i>fileSion-Data</i> | Data passed to the SION callbacks in the <code>userData</code> argument. |

Returns

`OTF2_StatusCode`, or error code.

J.2.5.48 `OTF2_StatusCode OTF2_Archive_SetFlushCallbacks (OTF2_Archive * archive, const OTF2_FlushCallbacks * flushCallbacks, void * flushData)`

Set the flush callbacks for the archive.

Parameters

| | |
|-----------------------|---|
| <i>archive</i> | Archive handle. |
| <i>flushCallbacks</i> | Struct holding the flush callback functions. |
| <i>flushData</i> | Data passed to the flush callbacks in the <code>userData</code> argument. |

Returns

`OTF2_StatusCode`, or error code.

J.2.5.49 `OTF2_StatusCode OTF2_Archive_SetMachineName (OTF2_Archive * archive, const char * machineName)`

Set machine name.

Sets the name for the machine the trace was recorded. This value is optional. It only needs to be set for an archive handle marked as 'master' or does not need to be set at all.

J.2 OTF2_Archive.h File Reference

Parameters

| | |
|---------------------|-----------------|
| <i>archive</i> | Archive handle. |
| <i>machine-Name</i> | Machine name. |

Returns

[*OTF2_SUCCESS*](#) if successful, an error code if an error occurs.

J.2.5.50 `OTF2_ErrorCode OTF2_Archive_SetMasterSlaveMode (OTF2_Archive * archive, OTF2_MasterSlaveMode masterOrSlave)`

Set master slave mode.

Sets master slave mode for a location. If `OTF2_MASTER` is passed, the location creates the directory structure for the trace files to store. Therefore, exactly one location can be master, all other locations must be slaves.

Please note: This call is only allowed in writing mode.

Parameters

| | |
|----------------------|--|
| <i>archive</i> | Archive handle. |
| <i>masterOrSlave</i> | Master or slave. Available values are <i>OTF2_MASTER</i> and <i>OTF2_SLAVE</i> . |

Returns

[*OTF2_SUCCESS*](#) if successful, an error code if an error occurs.

J.2.5.51 `OTF2_ErrorCode OTF2_Archive_SetMemoryCallbacks (OTF2_Archive * archive, const OTF2_MemoryCallbacks * memoryCallbacks, void * memoryData)`

Set the memory callbacks for the archive.

Parameters

| | |
|------------------------|--|
| <i>archive</i> | Archive handle. |
| <i>memoryCallbacks</i> | Struct holding the memory callback functions. |
| <i>memoryData</i> | Data passed to the memory callbacks in the <code>userData</code> argument. |

Returns

OTF2_ErrorCode, or error code.

J.2.5.52 **OTF2_ErrorCode** **OTF2_Archive.SetNumberOfSnapshots (OTF2_Archive * archive, uint32_t number)**

Set the number of snapshots.

Parameters

| | |
|----------------|------------------|
| <i>archive</i> | Archive handle. |
| <i>number</i> | Snapshot number. |

Since

Version 1.2

Returns

[OTF2_SUCCESS](#) if successful, an error code if an error occurs.

J.2.5.53 **OTF2_ErrorCode** **OTF2_Archive.SetProperty (OTF2_Archive * archive, const char * name, const char * value, bool overwrite)**

Add or remove a trace file property to this archive.

Removing a trace file property is done by passing "" in the `value` parameter. The `overwrite` parameter is ignored than.

Note

This call is only allowed when the archive was opened with mode [OTF2_FILEMODE_WRITE](#).

Parameters

| | |
|------------------|---|
| <i>archive</i> | Archive handle. |
| <i>name</i> | Name of the trace file property (case insensitive, [A-Z0-9_]). |
| <i>value</i> | Value of property. |
| <i>overwrite</i> | If true a previous trace file property with the same name name will be overwritten. |

J.3 OTF2_AttributeList.h File Reference

Returns

OTF2_SUCCESS if successful

OTF2_ERROR_PROPERTY_NAME_INVALID if property name does not conform to the naming scheme

OTF2_ERROR_PROPERTY_NOT_FOUND if property was not found, but requested to remove

OTF2_ERROR_PROPERTY_EXISTS if property exists but overwrite was not set

J.2.5.54 OTF2_ErrorCode OTF2_Archive_SwitchFileMode (OTF2_Archive * archive, OTF2_FileMode newFileMode)

Switch file mode of the archive.

Currently only a switch from *OTF2_FILEMODE_READ* to *OTF2_FILEMODE_WRITE* is permitted and in this case, the master/slave mode is reset and must be set again with *OTF2_Archive_SetMasterSlaveMode*. Currently it is also only permitted when operating on an OTF2 archive with the *OTF2_SUBSTRATE_POSIX* file substrate.

Parameters

| | |
|---------------------|--|
| <i>archive</i> | Archive handle. |
| <i>newFile-Mode</i> | New <i>OTF2_FileMode</i> to switch to. |

Returns

OTF2_SUCCESS if successful, an error code if an error occurs.

Since

Version 1.2

J.3 OTF2_AttributeList.h File Reference

This layer enables dynamic appending of arbitrary attributes to any type of event record.

```
#include <stdint.h>
```

```
#include <stdbool.h>
```

```
#include <otf2/OTF2_ErrorCodes.h>
```

APPENDIX J. FILE DOCUMENTATION

```
#include <otf2/OTF2_GeneralDefinitions.h>
```

Data Structures

- union [OTF2_AttributeValue](#)
Value container for an attributes.

Typedefs

- typedef struct OTF2_AttributeList_struct [OTF2_AttributeList](#)
Attribute list handle.

Functions

- [OTF2_ErrorCode](#) [OTF2_AttributeList_AddAttribute](#) ([OTF2_AttributeList](#) *attributeList, [OTF2_AttributeRef](#) attribute, [OTF2_Type](#) type, [OTF2_AttributeValue](#) attributeValue)
Add an attribute to an attribute list.
- [OTF2_ErrorCode](#) [OTF2_AttributeList_AddAttributeRef](#) ([OTF2_AttributeList](#) *attributeList, [OTF2_AttributeRef](#) attribute, [OTF2_AttributeRef](#) attributeRef)
Add an OTF2_TYPE_ATTRIBUTE attribute to an attribute list.
- [OTF2_ErrorCode](#) [OTF2_AttributeList_AddCommRef](#) ([OTF2_AttributeList](#) *attributeList, [OTF2_AttributeRef](#) attribute, [OTF2_CommRef](#) commRef)
Add an OTF2_TYPE_COMM attribute to an attribute list.
- [OTF2_ErrorCode](#) [OTF2_AttributeList_AddDouble](#) ([OTF2_AttributeList](#) *attributeList, [OTF2_AttributeRef](#) attribute, double float64Value)
Add an OTF2_TYPE_DOUBLE attribute to an attribute list.
- [OTF2_ErrorCode](#) [OTF2_AttributeList_AddFloat](#) ([OTF2_AttributeList](#) *attributeList, [OTF2_AttributeRef](#) attribute, float float32Value)
Add an OTF2_TYPE_FLOAT attribute to an attribute list.
- [OTF2_ErrorCode](#) [OTF2_AttributeList_AddGroupRef](#) ([OTF2_AttributeList](#) *attributeList, [OTF2_AttributeRef](#) attribute, [OTF2_GroupRef](#) groupRef)
Add an OTF2_TYPE_GROUP attribute to an attribute list.

J.3 OTF2_AttributeList.h File Reference

- [OTF2_ErrorCode](#) [OTF2_AttributeList_AddInt16](#) ([OTF2_AttributeList](#) *attributeList, [OTF2_AttributeRef](#) attribute, [int16_t](#) int16Value)
Add an OTF2_TYPE_INT16 attribute to an attribute list.
- [OTF2_ErrorCode](#) [OTF2_AttributeList_AddInt32](#) ([OTF2_AttributeList](#) *attributeList, [OTF2_AttributeRef](#) attribute, [int32_t](#) int32Value)
Add an OTF2_TYPE_INT32 attribute to an attribute list.
- [OTF2_ErrorCode](#) [OTF2_AttributeList_AddInt64](#) ([OTF2_AttributeList](#) *attributeList, [OTF2_AttributeRef](#) attribute, [int64_t](#) int64Value)
Add an OTF2_TYPE_INT64 attribute to an attribute list.
- [OTF2_ErrorCode](#) [OTF2_AttributeList_AddInt8](#) ([OTF2_AttributeList](#) *attributeList, [OTF2_AttributeRef](#) attribute, [int8_t](#) int8Value)
Add an OTF2_TYPE_INT8 attribute to an attribute list.
- [OTF2_ErrorCode](#) [OTF2_AttributeList_AddLocationRef](#) ([OTF2_AttributeList](#) *attributeList, [OTF2_AttributeRef](#) attribute, [OTF2_LocationRef](#) locationRef)
Add an OTF2_TYPE_LOCATION attribute to an attribute list.
- [OTF2_ErrorCode](#) [OTF2_AttributeList_AddMetricRef](#) ([OTF2_AttributeList](#) *attributeList, [OTF2_AttributeRef](#) attribute, [OTF2_MetricRef](#) metricRef)
Add an OTF2_TYPE_METRIC attribute to an attribute list.
- [OTF2_ErrorCode](#) [OTF2_AttributeList_AddParameterRef](#) ([OTF2_AttributeList](#) *attributeList, [OTF2_AttributeRef](#) attribute, [OTF2_ParameterRef](#) parameterRef)
Add an OTF2_TYPE_PARAMETER attribute to an attribute list.
- [OTF2_ErrorCode](#) [OTF2_AttributeList_AddRegionRef](#) ([OTF2_AttributeList](#) *attributeList, [OTF2_AttributeRef](#) attribute, [OTF2_RegionRef](#) regionRef)
Add an OTF2_TYPE_REGION attribute to an attribute list.
- [OTF2_ErrorCode](#) [OTF2_AttributeList_AddRmaWinRef](#) ([OTF2_AttributeList](#) *attributeList, [OTF2_AttributeRef](#) attribute, [OTF2_RmaWinRef](#) rmaWinRef)
Add an OTF2_TYPE_RMA_WIN attribute to an attribute list.
- [OTF2_ErrorCode](#) [OTF2_AttributeList_AddString](#) ([OTF2_AttributeList](#) *attributeList, [OTF2_AttributeRef](#) attribute, [OTF2_StringRef](#) stringRef)

APPENDIX J. FILE DOCUMENTATION

Add an OTF2_STRING attribute to an attribute list.

- [OTF2_ErrorCode](#) [OTF2_AttributeList_AddStringRef](#) ([OTF2_AttributeList](#) *attributeList, [OTF2_AttributeRef](#) attribute, [OTF2_StringRef](#) stringRef)

Add an OTF2_TYPE_STRING attribute to an attribute list.

- [OTF2_ErrorCode](#) [OTF2_AttributeList_AddUint16](#) ([OTF2_AttributeList](#) *attributeList, [OTF2_AttributeRef](#) attribute, [uint16_t](#) uint16Value)

Add an OTF2_TYPE_UINT16 attribute to an attribute list.

- [OTF2_ErrorCode](#) [OTF2_AttributeList_AddUint32](#) ([OTF2_AttributeList](#) *attributeList, [OTF2_AttributeRef](#) attribute, [uint32_t](#) uint32Value)

Add an OTF2_TYPE_UINT32 attribute to an attribute list.

- [OTF2_ErrorCode](#) [OTF2_AttributeList_AddUint64](#) ([OTF2_AttributeList](#) *attributeList, [OTF2_AttributeRef](#) attribute, [uint64_t](#) uint64Value)

Add an OTF2_TYPE_UINT64 attribute to an attribute list.

- [OTF2_ErrorCode](#) [OTF2_AttributeList_AddUint8](#) ([OTF2_AttributeList](#) *attributeList, [OTF2_AttributeRef](#) attribute, [uint8_t](#) uint8Value)

Add an OTF2_TYPE_UINT8 attribute to an attribute list.

- [OTF2_ErrorCode](#) [OTF2_AttributeList_Delete](#) ([OTF2_AttributeList](#) *attributeList)

Delete an attribute list handle.

- [OTF2_ErrorCode](#) [OTF2_AttributeList_GetAttributeByID](#) (const [OTF2_AttributeList](#) *attributeList, [OTF2_AttributeRef](#) attribute, [OTF2_Type](#) *type, [OTF2_AttributeValue](#) *attributeValue)

Get an attribute from an attribute list by attribute ID.

- [OTF2_ErrorCode](#) [OTF2_AttributeList_GetAttributeByIndex](#) (const [OTF2_AttributeList](#) *attributeList, [uint32_t](#) index, [OTF2_AttributeRef](#) *attribute, [OTF2_Type](#) *type, [OTF2_AttributeValue](#) *attributeValue)

Get an attribute from an attribute list by attribute index.

- [OTF2_ErrorCode](#) [OTF2_AttributeList_GetAttributeRef](#) (const [OTF2_AttributeList](#) *attributeList, [OTF2_AttributeRef](#) attribute, [OTF2_AttributeRef](#) *attributeRef)

Get an OTF2_TYPE_ATTRIBUTE attribute from an attribute list by attribute ID.

J.3 OTF2_AttributeList.h File Reference

- [OTF2_ErrorCode OTF2_AttributeList_GetCommRef](#) (const [OTF2_AttributeList](#) *attributeList, [OTF2_AttributeRef](#) attribute, [OTF2_CommRef](#) *commRef)
Get an OTF2_TYPE_COMM attribute from an attribute list by attribute ID.
- [OTF2_ErrorCode OTF2_AttributeList_GetDouble](#) (const [OTF2_AttributeList](#) *attributeList, [OTF2_AttributeRef](#) attribute, double *float64Value)
Get an OTF2_TYPE_DOUBLE attribute from an attribute list by attribute ID.
- [OTF2_ErrorCode OTF2_AttributeList_GetFloat](#) (const [OTF2_AttributeList](#) *attributeList, [OTF2_AttributeRef](#) attribute, float *float32Value)
Get an OTF2_TYPE_FLOAT attribute from an attribute list by attribute ID.
- [OTF2_ErrorCode OTF2_AttributeList_GetGroupRef](#) (const [OTF2_AttributeList](#) *attributeList, [OTF2_AttributeRef](#) attribute, [OTF2_GroupRef](#) *groupRef)
Get an OTF2_TYPE_GROUP attribute from an attribute list by attribute ID.
- [OTF2_ErrorCode OTF2_AttributeList_GetInt16](#) (const [OTF2_AttributeList](#) *attributeList, [OTF2_AttributeRef](#) attribute, int16_t *int16Value)
Get an OTF2_TYPE_INT16 attribute from an attribute list by attribute ID.
- [OTF2_ErrorCode OTF2_AttributeList_GetInt32](#) (const [OTF2_AttributeList](#) *attributeList, [OTF2_AttributeRef](#) attribute, int32_t *int32Value)
Get an OTF2_TYPE_INT32 attribute from an attribute list by attribute ID.
- [OTF2_ErrorCode OTF2_AttributeList_GetInt64](#) (const [OTF2_AttributeList](#) *attributeList, [OTF2_AttributeRef](#) attribute, int64_t *int64Value)
Get an OTF2_TYPE_INT64 attribute from an attribute list by attribute ID.
- [OTF2_ErrorCode OTF2_AttributeList_GetInt8](#) (const [OTF2_AttributeList](#) *attributeList, [OTF2_AttributeRef](#) attribute, int8_t *int8Value)
Get an OTF2_TYPE_INT8 attribute from an attribute list by attribute ID.
- [OTF2_ErrorCode OTF2_AttributeList_GetLocationRef](#) (const [OTF2_AttributeList](#) *attributeList, [OTF2_AttributeRef](#) attribute, [OTF2_LocationRef](#) *locationRef)
Get an OTF2_TYPE_LOCATION attribute from an attribute list by attribute ID.
- [OTF2_ErrorCode OTF2_AttributeList_GetMetricRef](#) (const [OTF2_AttributeList](#) *attributeList, [OTF2_AttributeRef](#) attribute, [OTF2_MetricRef](#) *metricRef)
Get an OTF2_TYPE_METRIC attribute from an attribute list by attribute ID.

APPENDIX J. FILE DOCUMENTATION

- `uint32_t OTF2_AttributeList_GetNumberOfElements` (`const OTF2_AttributeList *attributeList`)
Get the number of entries in an attribute list.
- `OTF2_ErrorCode OTF2_AttributeList_GetParameterRef` (`const OTF2_AttributeList *attributeList`, `OTF2_AttributeRef` attribute, `OTF2_ParameterRef *parameterRef`)
Get an OTF2_TYPE_PARAMETER attribute from an attribute list by attribute ID.
- `OTF2_ErrorCode OTF2_AttributeList_GetRegionRef` (`const OTF2_AttributeList *attributeList`, `OTF2_AttributeRef` attribute, `OTF2_RegionRef *regionRef`)
Get an OTF2_TYPE_REGION attribute from an attribute list by attribute ID.
- `OTF2_ErrorCode OTF2_AttributeList_GetRmaWinRef` (`const OTF2_AttributeList *attributeList`, `OTF2_AttributeRef` attribute, `OTF2_RmaWinRef *rmaWinRef`)
Get an OTF2_TYPE_RMA_WIN attribute from an attribute list by attribute ID.
- `OTF2_ErrorCode OTF2_AttributeList_GetString` (`const OTF2_AttributeList *attributeList`, `OTF2_AttributeRef` attribute, `OTF2_StringRef *stringRef`)
Add an OTF2_STRING attribute to an attribute list.
- `OTF2_ErrorCode OTF2_AttributeList_GetStringRef` (`const OTF2_AttributeList *attributeList`, `OTF2_AttributeRef` attribute, `OTF2_StringRef *stringRef`)
Get an OTF2_TYPE_STRING attribute from an attribute list by attribute ID.
- `OTF2_ErrorCode OTF2_AttributeList_GetUint16` (`const OTF2_AttributeList *attributeList`, `OTF2_AttributeRef` attribute, `uint16_t *uint16Value`)
Get an OTF2_TYPE_UINT16 attribute from an attribute list by attribute ID.
- `OTF2_ErrorCode OTF2_AttributeList_GetUint32` (`const OTF2_AttributeList *attributeList`, `OTF2_AttributeRef` attribute, `uint32_t *uint32Value`)
Get an OTF2_TYPE_UINT32 attribute from an attribute list by attribute ID.
- `OTF2_ErrorCode OTF2_AttributeList_GetUint64` (`const OTF2_AttributeList *attributeList`, `OTF2_AttributeRef` attribute, `uint64_t *uint64Value`)
Get an OTF2_TYPE_UINT64 attribute from an attribute list by attribute ID.

J.3 OTF2_AttributeList.h File Reference

- [OTF2_ErrorCode OTF2_AttributeList_GetUint8](#) (const [OTF2_AttributeList](#) *attributeList, [OTF2_AttributeRef](#) attribute, [uint8_t](#) *uint8Value)
Get an OTF2_TYPE_UINT8 attribute from an attribute list by attribute ID.
- [OTF2_AttributeList * OTF2_AttributeList_New](#) (void)
Create a new attribute list handle.
- [OTF2_ErrorCode OTF2_AttributeList_PopAttribute](#) ([OTF2_AttributeList](#) *attributeList, [OTF2_AttributeRef](#) *attribute, [OTF2_Type](#) *type, [OTF2_AttributeValue](#) *attributeValue)
Get first attribute from an attribute list and remove it.
- [OTF2_ErrorCode OTF2_AttributeList_RemoveAllAttributes](#) ([OTF2_AttributeList](#) *attributeList)
Remove all attributes from an attribute list.
- [OTF2_ErrorCode OTF2_AttributeList_RemoveAttribute](#) ([OTF2_AttributeList](#) *attributeList, [OTF2_AttributeRef](#) attribute)
Remove an attribute from an attribute list.
- [bool OTF2_AttributeList_TestAttributeByID](#) (const [OTF2_AttributeList](#) *attributeList, [OTF2_AttributeRef](#) attribute)
Test if an attribute is in the attribute list.

J.3.1 Detailed Description

This layer enables dynamic appending of arbitrary attributes to any type of event record.

Source Template:

template/OTF2_AttributeList.tmpl.h

Maintainer:

Michael Wagner <michael.wagner@zih.tu-dresden.de>

Authors

Dominic Eschweiler <d.eschweiler@fz-juelich.de>, Michael Wagner <michael.wagner@zih.tu-dresden.de>

APPENDIX J. FILE DOCUMENTATION

J.3.2 How to use the attribute list for writing

additional attributes to event records.

First create an attribute list handle.

```
OTF2_AttributeList attribute_list = OTF2_AttributeList_New();
```

To write your additional attribute to an event record add your attributes to an empty attribute list right before you call the routine to write the event.

```
OTF2_AttributeValue attr_value;
attr_value.uint32 = attribute_value;
OTF2_AttributeList_AddAttribute( attribute_list, attribute_id, OTF2_UINT8, attr
    _value );
...
```

Then call the routine to write the event and pass the attribute list. The additional attributes are added to the event record and will be appended when reading the event later on. Please note: All attributes in the list will be added to event record. So make sure that there are only those attributes in the attribute list that you actually like to write. Please note: After writing the event record all attributes are removed from the attribute list. So the attribute list is empty again. If you want to write identical attributes to multiple events you have to add them each time new.

```
OTF2_EvtWriter_WriteEnter( ..., attribute_list, ... );
```

J.3.3 Function Documentation

J.3.3.1 OTF2_ErrorCode OTF2_AttributeList_AddAttribute (OTF2_AttributeList * *attributeList*, OTF2_AttributeRef *attribute*, OTF2_Type *type*, OTF2_AttributeValue *attributeValue*)

Add an attribute to an attribute list.

Adds an attribute to an attribute list. If the attribute already exists, it fails and returns an error.

Parameters

| | |
|------------------------|------------------------------------|
| <i>attributeList</i> | Attribute list handle. |
| <i>attribute</i> | Reference to attribute definition. |
| <i>type</i> | Type of the attribute. |
| <i>attribute-Value</i> | Value of the attribute. |

J.3 OTF2_AttributeList.h File Reference

Returns

OTF2_SUCCESS if successful, an error code if an error occurs.

J.3.3.2 **OTF2_ErrorCode** **OTF2_AttributeList_AddAttributeRef** (**OTF2_AttributeList** * *attributeList*, **OTF2_AttributeRef** *attribute*, **OTF2_AttributeRef** *attributeRef*)

Add an OTF2_TYPE_ATTRIBUTE attribute to an attribute list.

Convenient function around *OTF2_AttributeList_AddAttribute*.

Parameters

| | |
|----------------------|------------------------------------|
| <i>attributeList</i> | Attribute list handle. |
| <i>attribute</i> | Reference to Attribute definition. |
| <i>attributeRef</i> | Reference to Attribute definition. |

Returns

OTF2_SUCCESS if successful, an error code if an error occurs.

J.3.3.3 **OTF2_ErrorCode** **OTF2_AttributeList_AddCommRef** (**OTF2_AttributeList** * *attributeList*, **OTF2_AttributeRef** *attribute*, **OTF2_CommRef** *commRef*)

Add an OTF2_TYPE_COMM attribute to an attribute list.

Convenient function around *OTF2_AttributeList_AddAttribute*.

Parameters

| | |
|----------------------|------------------------------------|
| <i>attributeList</i> | Attribute list handle. |
| <i>attribute</i> | Reference to Attribute definition. |
| <i>commRef</i> | Reference to Comm definition. |

Returns

OTF2_SUCCESS if successful, an error code if an error occurs.

J.3.3.4 **OTF2_ErrorCode** **OTF2_AttributeList_AddDouble** (**OTF2_AttributeList** * *attributeList*, **OTF2_AttributeRef** *attribute*, **double** *float64Value*)

Add an OTF2_TYPE_DOUBLE attribute to an attribute list.

APPENDIX J. FILE DOCUMENTATION

Convenient function around *OTF2_AttributeList_AddAttribute*.

Parameters

| | |
|----------------------|------------------------------------|
| <i>attributeList</i> | Attribute list handle. |
| <i>attribute</i> | Reference to attribute definition. |
| <i>float64Value</i> | Value of the attribute. |

Returns

OTF2_SUCCESS if successful, an error code if an error occurs.

J.3.3.5 OTF2_ErrorCode OTF2_AttributeList_AddFloat (OTF2_AttributeList * attributeList, OTF2_AttributeRef attribute, float float32Value)

Add an OTF2_TYPE_FLOAT attribute to an attribute list.

Convenient function around *OTF2_AttributeList_AddAttribute*.

Parameters

| | |
|----------------------|------------------------------------|
| <i>attributeList</i> | Attribute list handle. |
| <i>attribute</i> | Reference to attribute definition. |
| <i>float32Value</i> | Value of the attribute. |

Returns

OTF2_SUCCESS if successful, an error code if an error occurs.

J.3.3.6 OTF2_ErrorCode OTF2_AttributeList_AddGroupRef (OTF2_AttributeList * attributeList, OTF2_AttributeRef attribute, OTF2_GroupRef groupRef)

Add an OTF2_TYPE_GROUP attribute to an attribute list.

Convenient function around *OTF2_AttributeList_AddAttribute*.

Parameters

| | |
|----------------------|------------------------------------|
| <i>attributeList</i> | Attribute list handle. |
| <i>attribute</i> | Reference to Attribute definition. |
| <i>groupRef</i> | Reference to Group definition. |

J.3 OTF2_AttributeList.h File Reference

Returns

OTF2_SUCCESS if successful, an error code if an error occurs.

J.3.3.7 OTF2_ErrorCode OTF2_AttributeList_AddInt16 (OTF2_AttributeList * attributeList, OTF2_AttributeRef attribute, int16_t int16Value)

Add an OTF2_TYPE_INT16 attribute to an attribute list.

Convenient function around *OTF2_AttributeList_AddAttribute*.

Parameters

| | |
|----------------------|------------------------------------|
| <i>attributeList</i> | Attribute list handle. |
| <i>attribute</i> | Reference to attribute definition. |
| <i>int16Value</i> | Value of the attribute. |

Returns

OTF2_SUCCESS if successful, an error code if an error occurs.

J.3.3.8 OTF2_ErrorCode OTF2_AttributeList_AddInt32 (OTF2_AttributeList * attributeList, OTF2_AttributeRef attribute, int32_t int32Value)

Add an OTF2_TYPE_INT32 attribute to an attribute list.

Convenient function around *OTF2_AttributeList_AddAttribute*.

Parameters

| | |
|----------------------|------------------------------------|
| <i>attributeList</i> | Attribute list handle. |
| <i>attribute</i> | Reference to attribute definition. |
| <i>int32Value</i> | Value of the attribute. |

Returns

OTF2_SUCCESS if successful, an error code if an error occurs.

J.3.3.9 OTF2_ErrorCode OTF2_AttributeList_AddInt64 (OTF2_AttributeList * attributeList, OTF2_AttributeRef attribute, int64_t int64Value)

Add an OTF2_TYPE_INT64 attribute to an attribute list.

Convenient function around *OTF2_AttributeList_AddAttribute*.

APPENDIX J. FILE DOCUMENTATION

Parameters

| | |
|----------------------|------------------------------------|
| <i>attributeList</i> | Attribute list handle. |
| <i>attribute</i> | Reference to attribute definition. |
| <i>int64Value</i> | Value of the attribute. |

Returns

[*OTF2_SUCCESS*](#) if successful, an error code if an error occurs.

J.3.3.10 `OTF2_StatusCode OTF2_AttributeList_AddInt8 (OTF2_AttributeList *
attributeList, OTF2_AttributeRef attribute, int8_t int8Value)`

Add an OTF2_TYPE_INT8 attribute to an attribute list.

Convenient function around *OTF2_AttributeList_AddAttribute*.

Parameters

| | |
|----------------------|------------------------------------|
| <i>attributeList</i> | Attribute list handle. |
| <i>attribute</i> | Reference to attribute definition. |
| <i>int8Value</i> | Value of the attribute. |

Returns

[*OTF2_SUCCESS*](#) if successful, an error code if an error occurs.

J.3.3.11 `OTF2_StatusCode OTF2_AttributeList_AddLocationRef (
OTF2_AttributeList * attributeList, OTF2_AttributeRef attribute,
OTF2_LocationRef locationRef)`

Add an OTF2_TYPE_LOCATION attribute to an attribute list.

Convenient function around *OTF2_AttributeList_AddAttribute*.

Parameters

| | |
|----------------------|------------------------------------|
| <i>attributeList</i> | Attribute list handle. |
| <i>attribute</i> | Reference to Attribute definition. |
| <i>locationRef</i> | Reference to Location definition. |

Returns

[*OTF2_SUCCESS*](#) if successful, an error code if an error occurs.

J.3 OTF2_AttributeList.h File Reference

J.3.3.12 `OTF2_ErrorCode OTF2_AttributeList_AddMetricRef (OTF2_AttributeList * attributeList, OTF2_AttributeRef attribute, OTF2_MetricRef metricRef)`

Add an OTF2_TYPE_METRIC attribute to an attribute list.

Convenient function around *OTF2_AttributeList_AddAttribute*.

Parameters

| | |
|----------------------|------------------------------------|
| <i>attributeList</i> | Attribute list handle. |
| <i>attribute</i> | Reference to Attribute definition. |
| <i>metricRef</i> | Reference to Metric definition. |

Returns

OTF2_SUCCESS if successful, an error code if an error occurs.

J.3.3.13 `OTF2_ErrorCode OTF2_AttributeList_AddParameterRef (OTF2_AttributeList * attributeList, OTF2_AttributeRef attribute, OTF2_ParameterRef parameterRef)`

Add an OTF2_TYPE_PARAMETER attribute to an attribute list.

Convenient function around *OTF2_AttributeList_AddAttribute*.

Parameters

| | |
|----------------------|------------------------------------|
| <i>attributeList</i> | Attribute list handle. |
| <i>attribute</i> | Reference to Attribute definition. |
| <i>parameter-Ref</i> | Reference to Parameter definition. |

Returns

OTF2_SUCCESS if successful, an error code if an error occurs.

J.3.3.14 `OTF2_ErrorCode OTF2_AttributeList_AddRegionRef (OTF2_AttributeList * attributeList, OTF2_AttributeRef attribute, OTF2_RegionRef regionRef)`

Add an OTF2_TYPE_REGION attribute to an attribute list.

Convenient function around *OTF2_AttributeList_AddAttribute*.

APPENDIX J. FILE DOCUMENTATION

Parameters

| | |
|----------------------|------------------------------------|
| <i>attributeList</i> | Attribute list handle. |
| <i>attribute</i> | Reference to Attribute definition. |
| <i>regionRef</i> | Reference to Region definition. |

Returns

[*OTF2_SUCCESS*](#) if successful, an error code if an error occurs.

J.3.3.15 `OTF2_StatusCode OTF2_AttributeList_AddRmaWinRef (OTF2_AttributeList * attributeList, OTF2_AttributeRef attribute, OTF2_RmaWinRef rmaWinRef)`

Add an `OTF2_TYPE_RMA_WIN` attribute to an attribute list.

Convenient function around `OTF2_AttributeList_AddAttribute`.

Parameters

| | |
|----------------------|------------------------------------|
| <i>attributeList</i> | Attribute list handle. |
| <i>attribute</i> | Reference to Attribute definition. |
| <i>rmaWinRef</i> | Reference to RmaWin definition. |

Returns

[*OTF2_SUCCESS*](#) if successful, an error code if an error occurs.

J.3.3.16 `OTF2_StatusCode OTF2_AttributeList_AddString (OTF2_AttributeList * attributeList, OTF2_AttributeRef attribute, OTF2_StringRef stringRef)`

Add an `OTF2_STRING` attribute to an attribute list.

Deprecated

Use `OTF2_AttributeList_AddStringRef()` instead.

Convenient function around `OTF2_AttributeList_AddAttribute`.

Parameters

| | |
|----------------------|------------------------------------|
| <i>attributeList</i> | Attribute list handle. |
| <i>attribute</i> | Reference to Attribute definition. |
| <i>stringRef</i> | Reference to String definition. |

J.3 OTF2_AttributeList.h File Reference

Returns

OTF2_SUCCESS if successful, an error code if an error occurs.

J.3.3.17 `OTF2_ErrorCode OTF2_AttributeList_AddStringRef (OTF2_AttributeList * attributeList, OTF2_AttributeRef attribute, OTF2_StringRef stringRef)`

Add an OTF2_TYPE_STRING attribute to an attribute list.

Convenient function around *OTF2_AttributeList_AddAttribute*.

Parameters

| | |
|----------------------|------------------------------------|
| <i>attributeList</i> | Attribute list handle. |
| <i>attribute</i> | Reference to Attribute definition. |
| <i>stringRef</i> | Reference to String definition. |

Returns

OTF2_SUCCESS if successful, an error code if an error occurs.

J.3.3.18 `OTF2_ErrorCode OTF2_AttributeList_AddUInt16 (OTF2_AttributeList * attributeList, OTF2_AttributeRef attribute, uint16_t uint16Value)`

Add an OTF2_TYPE_UINT16 attribute to an attribute list.

Convenient function around *OTF2_AttributeList_AddAttribute*.

Parameters

| | |
|----------------------|------------------------------------|
| <i>attributeList</i> | Attribute list handle. |
| <i>attribute</i> | Reference to attribute definition. |
| <i>uint16Value</i> | Value of the attribute. |

Returns

OTF2_SUCCESS if successful, an error code if an error occurs.

J.3.3.19 `OTF2_ErrorCode OTF2_AttributeList_AddUInt32 (OTF2_AttributeList * attributeList, OTF2_AttributeRef attribute, uint32_t uint32Value)`

Add an OTF2_TYPE_UINT32 attribute to an attribute list.

Convenient function around *OTF2_AttributeList_AddAttribute*.

APPENDIX J. FILE DOCUMENTATION

Parameters

| | |
|----------------------|------------------------------------|
| <i>attributeList</i> | Attribute list handle. |
| <i>attribute</i> | Reference to attribute definition. |
| <i>uint32Value</i> | Value of the attribute. |

Returns

OTF2_SUCCESS if successful, an error code if an error occurs.

J.3.3.20 `OTF2_ErrorCode OTF2_AttributeList_AddUInt64 (OTF2_AttributeList * attributeList, OTF2_AttributeRef attribute, uint64_t uint64Value)`

Add an OTF2_TYPE_UINT64 attribute to an attribute list.

Convenient function around *OTF2_AttributeList_AddAttribute*.

Parameters

| | |
|----------------------|------------------------------------|
| <i>attributeList</i> | Attribute list handle. |
| <i>attribute</i> | Reference to attribute definition. |
| <i>uint64Value</i> | Value of the attribute. |

Returns

OTF2_SUCCESS if successful, an error code if an error occurs.

J.3.3.21 `OTF2_ErrorCode OTF2_AttributeList_AddUInt8 (OTF2_AttributeList * attributeList, OTF2_AttributeRef attribute, uint8_t uint8Value)`

Add an OTF2_TYPE_UINT8 attribute to an attribute list.

Convenient function around *OTF2_AttributeList_AddAttribute*.

Parameters

| | |
|----------------------|------------------------------------|
| <i>attributeList</i> | Attribute list handle. |
| <i>attribute</i> | Reference to attribute definition. |
| <i>uint8Value</i> | Value of the attribute. |

Returns

OTF2_SUCCESS if successful, an error code if an error occurs.

J.3 OTF2_AttributeList.h File Reference

J.3.3.22 OTF2_ErrorCode OTF2_AttributeList_Delete (OTF2_AttributeList * *attributeList*)

Delete an attribute list handle.

Deletes an attribute list handle and releases all associated resources.

Parameters

| | |
|----------------------|------------------------|
| <i>attributeList</i> | Attribute list handle. |
|----------------------|------------------------|

Returns

[OTF2_SUCCESS](#) if successful, an error code if an error occurs.

J.3.3.23 OTF2_ErrorCode OTF2_AttributeList_GetAttributeByID (const OTF2_AttributeList * *attributeList*, OTF2_AttributeRef *attribute*, OTF2_Type * *type*, OTF2_AttributeValue * *attributeValue*)

Get an attribute from an attribute list by attribute ID.

Parameters

| | | |
|-----|------------------------|------------------------------------|
| | <i>attributeList</i> | Attribute list handle. |
| | <i>attribute</i> | Reference to Attribute definition. |
| out | <i>type</i> | Returned type of the attribute. |
| out | <i>attribute-Value</i> | Returned value of the attribute. |

Returns

[OTF2_SUCCESS](#) if successful, an error code if an error occurs.

J.3.3.24 OTF2_ErrorCode OTF2_AttributeList_GetAttributeByIndex (const OTF2_AttributeList * *attributeList*, uint32_t *index*, OTF2_AttributeRef * *attribute*, OTF2_Type * *type*, OTF2_AttributeValue * *attributeValue*)

Get an attribute from an attribute list by attribute index.

Parameters

| | | |
|-----|----------------------|--|
| | <i>attributeList</i> | Attribute list handle. |
| | <i>index</i> | Position of the attribute in the attribute list. |
| out | <i>attribute</i> | Returned attribute reference. |

APPENDIX J. FILE DOCUMENTATION

| | | |
|-----|------------------------|----------------------------------|
| out | <i>type</i> | Returned type of the attribute. |
| out | <i>attribute-Value</i> | Returned value of the attribute. |

Returns

OTF2_SUCCESS if successful, an error code if an error occurs.

J.3.3.25 `OTF2_ErrorCode OTF2_AttributeList_GetAttributeRef (const OTF2_AttributeList * attributeList, OTF2_AttributeRef attribute, OTF2_AttributeRef * attributeRef)`

Get an `OTF2_TYPE_ATTRIBUTE` attribute from an attribute list by attribute ID.
Convenient function around `OTF2_AttributeList_GetAttributeByID`.

Parameters

| | | |
|-----|----------------------|------------------------------------|
| | <i>attributeList</i> | Attribute list handle. |
| | <i>attribute</i> | Reference to attribute definition. |
| out | <i>attributeRef</i> | Returned attribute value. |

Returns

OTF2_SUCCESS if successful, an error code if an error occurs.

J.3.3.26 `OTF2_ErrorCode OTF2_AttributeList_GetCommRef (const OTF2_AttributeList * attributeList, OTF2_AttributeRef attribute, OTF2_CommRef * commRef)`

Get an `OTF2_TYPE_COMM` attribute from an attribute list by attribute ID.
Convenient function around `OTF2_AttributeList_GetAttributeByID`.

Parameters

| | | |
|-----|----------------------|------------------------------------|
| | <i>attributeList</i> | Attribute list handle. |
| | <i>attribute</i> | Reference to attribute definition. |
| out | <i>commRef</i> | Returned comm value. |

Returns

OTF2_SUCCESS if successful, an error code if an error occurs.

J.3 OTF2_AttributeList.h File Reference

J.3.3.27 `OTF2_ErrorCode OTF2_AttributeList_GetDouble (const
OTF2_AttributeList * attributeList, OTF2_AttributeRef attribute, double
* float64Value)`

Get an OTF2_TYPE_DOUBLE attribute from an attribute list by attribute ID.

Convenient function around *OTF2_AttributeList_GetAttributeByID*.

Parameters

| | | |
|-----|----------------------|------------------------------------|
| | <i>attributeList</i> | Attribute list handle. |
| | <i>attribute</i> | Reference to Attribute definition. |
| out | <i>float64Value</i> | Returned value of the attribute. |

Returns

OTF2_SUCCESS if successful, an error code if an error occurs.

J.3.3.28 `OTF2_ErrorCode OTF2_AttributeList_GetFloat (const
OTF2_AttributeList * attributeList, OTF2_AttributeRef attribute, float *
float32Value)`

Get an OTF2_TYPE_FLOAT attribute from an attribute list by attribute ID.

Convenient function around *OTF2_AttributeList_GetAttributeByID*.

Parameters

| | | |
|-----|----------------------|------------------------------------|
| | <i>attributeList</i> | Attribute list handle. |
| | <i>attribute</i> | Reference to Attribute definition. |
| out | <i>float32Value</i> | Returned value of the attribute. |

Returns

OTF2_SUCCESS if successful, an error code if an error occurs.

J.3.3.29 `OTF2_ErrorCode OTF2_AttributeList_GetGroupRef (const
OTF2_AttributeList * attributeList, OTF2_AttributeRef attribute,
OTF2_GroupRef * groupRef)`

Get an OTF2_TYPE_GROUP attribute from an attribute list by attribute ID.

Convenient function around *OTF2_AttributeList_GetAttributeByID*.

APPENDIX J. FILE DOCUMENTATION

Parameters

| | | |
|-----|----------------------|------------------------------------|
| | <i>attributeList</i> | Attribute list handle. |
| | <i>attribute</i> | Reference to attribute definition. |
| out | <i>groupRef</i> | Returned group value. |

Returns

OTF2_SUCCESS if successful, an error code if an error occurs.

J.3.3.30 `OTF2_ErrorCode OTF2_AttributeList_GetInt16 (const OTF2_AttributeList * attributeList, OTF2_AttributeRef attribute, int16_t * int16Value)`

Get an OTF2_TYPE_INT16 attribute from an attribute list by attribute ID.

Convenient function around *OTF2_AttributeList_GetAttributeByID*.

Parameters

| | | |
|-----|----------------------|------------------------------------|
| | <i>attributeList</i> | Attribute list handle. |
| | <i>attribute</i> | Reference to Attribute definition. |
| out | <i>int16Value</i> | Returned value of the attribute. |

Returns

OTF2_SUCCESS if successful, an error code if an error occurs.

J.3.3.31 `OTF2_ErrorCode OTF2_AttributeList_GetInt32 (const OTF2_AttributeList * attributeList, OTF2_AttributeRef attribute, int32_t * int32Value)`

Get an OTF2_TYPE_INT32 attribute from an attribute list by attribute ID.

Convenient function around *OTF2_AttributeList_GetAttributeByID*.

Parameters

| | | |
|-----|----------------------|------------------------------------|
| | <i>attributeList</i> | Attribute list handle. |
| | <i>attribute</i> | Reference to Attribute definition. |
| out | <i>int32Value</i> | Returned value of the attribute. |

Returns

OTF2_SUCCESS if successful, an error code if an error occurs.

J.3 OTF2_AttributeList.h File Reference

J.3.3.32 `OTF2_ErrorCode OTF2_AttributeList.GetInt64 (const OTF2_AttributeList * attributeList, OTF2_AttributeRef attribute, int64_t * int64Value)`

Get an OTF2_TYPE_INT64 attribute from an attribute list by attribute ID.

Convenient function around *OTF2_AttributeList_GetAttributeByID*.

Parameters

| | | |
|-----|----------------------|------------------------------------|
| | <i>attributeList</i> | Attribute list handle. |
| | <i>attribute</i> | Reference to Attribute definition. |
| out | <i>int64Value</i> | Returned value of the attribute. |

Returns

OTF2_SUCCESS if successful, an error code if an error occurs.

J.3.3.33 `OTF2_ErrorCode OTF2_AttributeList.GetInt8 (const OTF2_AttributeList * attributeList, OTF2_AttributeRef attribute, int8_t * int8Value)`

Get an OTF2_TYPE_INT8 attribute from an attribute list by attribute ID.

Convenient function around *OTF2_AttributeList_GetAttributeByID*.

Parameters

| | | |
|-----|----------------------|------------------------------------|
| | <i>attributeList</i> | Attribute list handle. |
| | <i>attribute</i> | Reference to Attribute definition. |
| out | <i>int8Value</i> | Returned value of the attribute. |

Returns

OTF2_SUCCESS if successful, an error code if an error occurs.

J.3.3.34 `OTF2_ErrorCode OTF2_AttributeList.GetLocationRef (const OTF2_AttributeList * attributeList, OTF2_AttributeRef attribute, OTF2_LocationRef * locationRef)`

Get an OTF2_TYPE_LOCATION attribute from an attribute list by attribute ID.

Convenient function around *OTF2_AttributeList_GetAttributeByID*.

Parameters

| | | |
|--|----------------------|------------------------|
| | <i>attributeList</i> | Attribute list handle. |
|--|----------------------|------------------------|

APPENDIX J. FILE DOCUMENTATION

| | | |
|-----|--------------------|------------------------------------|
| | <i>attribute</i> | Reference to attribute definition. |
| out | <i>locationRef</i> | Returned location value. |

Returns

[*OTF2_SUCCESS*](#) if successful, an error code if an error occurs.

J.3.3.35 `OTF2_ErrorCode OTF2_AttributeList_GetMetricRef (const
OTF2_AttributeList * attributeList, OTF2_AttributeRef attribute,
OTF2_MetricRef * metricRef)`

Get an OTF2_TYPE_METRIC attribute from an attribute list by attribute ID.

Convenient function around *OTF2_AttributeList_GetAttributeByID*.

Parameters

| | | |
|-----|----------------------|------------------------------------|
| | <i>attributeList</i> | Attribute list handle. |
| | <i>attribute</i> | Reference to attribute definition. |
| out | <i>metricRef</i> | Returned metric value. |

Returns

[*OTF2_SUCCESS*](#) if successful, an error code if an error occurs.

J.3.3.36 `uint32_t OTF2_AttributeList_GetNumberOfElements (const
OTF2_AttributeList * attributeList)`

Get the number of entries in an attribute list.

Parameters

| | |
|----------------------|------------------------|
| <i>attributeList</i> | Attribute list handle. |
|----------------------|------------------------|

Returns

Returns the number of elements in the list. Returns zero if the list does not exist.

J.3 OTF2_AttributeList.h File Reference

J.3.3.37 `OTF2_ErrorCode OTF2_AttributeList_GetParameterRef (const
OTF2_AttributeList * attributeList, OTF2_AttributeRef attribute,
OTF2_ParameterRef * parameterRef)`

Get an OTF2_TYPE_PARAMETER attribute from an attribute list by attribute ID.

Convenient function around `OTF2_AttributeList_GetAttributeByID`.

Parameters

| | | |
|-----|----------------------|------------------------------------|
| | <i>attributeList</i> | Attribute list handle. |
| | <i>attribute</i> | Reference to attribute definition. |
| out | <i>parameter-Ref</i> | Returned parameter value. |

Returns

[*OTF2_SUCCESS*](#) if successful, an error code if an error occurs.

J.3.3.38 `OTF2_ErrorCode OTF2_AttributeList_GetRegionRef (const
OTF2_AttributeList * attributeList, OTF2_AttributeRef attribute,
OTF2_RegionRef * regionRef)`

Get an OTF2_TYPE_REGION attribute from an attribute list by attribute ID.

Convenient function around `OTF2_AttributeList_GetAttributeByID`.

Parameters

| | | |
|-----|----------------------|------------------------------------|
| | <i>attributeList</i> | Attribute list handle. |
| | <i>attribute</i> | Reference to attribute definition. |
| out | <i>regionRef</i> | Returned region value. |

Returns

[*OTF2_SUCCESS*](#) if successful, an error code if an error occurs.

J.3.3.39 `OTF2_ErrorCode OTF2_AttributeList_GetRmaWinRef (const
OTF2_AttributeList * attributeList, OTF2_AttributeRef attribute,
OTF2_RmaWinRef * rmaWinRef)`

Get an OTF2_TYPE_RMA_WIN attribute from an attribute list by attribute ID.

Convenient function around `OTF2_AttributeList_GetAttributeByID`.

APPENDIX J. FILE DOCUMENTATION

Parameters

| | | |
|-----|----------------------|------------------------------------|
| | <i>attributeList</i> | Attribute list handle. |
| | <i>attribute</i> | Reference to attribute definition. |
| out | <i>rmaWinRef</i> | Returned rmaWin value. |

Returns

OTF2_SUCCESS if successful, an error code if an error occurs.

J.3.3.40 `OTF2_StatusCode OTF2_AttributeList_GetString (const
OTF2_AttributeList * attributeList, OTF2_AttributeRef attribute,
OTF2_StringRef * stringRef)`

Add an OTF2_STRING attribute to an attribute list.

Deprecated

Use *OTF2_AttributeList_GetStringRef()* instead.

Convenient function around *OTF2_AttributeList_AddAttribute*.

Parameters

| | | |
|-----|----------------------|------------------------------------|
| | <i>attributeList</i> | Attribute list handle. |
| | <i>attribute</i> | Reference to attribute definition. |
| out | <i>stringRef</i> | Returned string value. |

Returns

OTF2_SUCCESS if successful, an error code if an error occurs.

J.3.3.41 `OTF2_StatusCode OTF2_AttributeList_GetStringRef (const
OTF2_AttributeList * attributeList, OTF2_AttributeRef attribute,
OTF2_StringRef * stringRef)`

Get an OTF2_TYPE_STRING attribute from an attribute list by attribute ID.

Convenient function around *OTF2_AttributeList_GetAttributeByID*.

Parameters

| | | |
|-----|----------------------|------------------------------------|
| | <i>attributeList</i> | Attribute list handle. |
| | <i>attribute</i> | Reference to attribute definition. |
| out | <i>stringRef</i> | Returned string value. |

J.3 OTF2_AttributeList.h File Reference

Returns

OTF2_SUCCESS if successful, an error code if an error occurs.

J.3.3.42 `OTF2_StatusCode OTF2_AttributeList_GetUint16 (const
OTF2_AttributeList * attributeList, OTF2_AttributeRef attribute,
uint16_t * uint16Value)`

Get an OTF2_TYPE_UINT16 attribute from an attribute list by attribute ID.

Convenient function around *OTF2_AttributeList_GetAttributeByID*.

Parameters

| | | |
|-----|----------------------|------------------------------------|
| | <i>attributeList</i> | Attribute list handle. |
| | <i>attribute</i> | Reference to Attribute definition. |
| out | <i>uint16Value</i> | Returned value of the attribute. |

Returns

OTF2_SUCCESS if successful, an error code if an error occurs.

J.3.3.43 `OTF2_StatusCode OTF2_AttributeList_GetUint32 (const
OTF2_AttributeList * attributeList, OTF2_AttributeRef attribute,
uint32_t * uint32Value)`

Get an OTF2_TYPE_UINT32 attribute from an attribute list by attribute ID.

Convenient function around *OTF2_AttributeList_GetAttributeByID*.

Parameters

| | | |
|-----|----------------------|------------------------------------|
| | <i>attributeList</i> | Attribute list handle. |
| | <i>attribute</i> | Reference to Attribute definition. |
| out | <i>uint32Value</i> | Returned value of the attribute. |

Returns

OTF2_SUCCESS if successful, an error code if an error occurs.

APPENDIX J. FILE DOCUMENTATION

J.3.3.44 `OTF2_ErrorCode OTF2_AttributeList_GetUint64 (const
OTF2_AttributeList * attributeList, OTF2_AttributeRef attribute,
uint64_t * uint64Value)`

Get an OTF2_TYPE_UINT64 attribute from an attribute list by attribute ID.
Convenient function around *OTF2_AttributeList_GetAttributeByID*.

Parameters

| | | |
|-----|----------------------|------------------------------------|
| | <i>attributeList</i> | Attribute list handle. |
| | <i>attribute</i> | Reference to Attribute definition. |
| out | <i>uint64Value</i> | Returned value of the attribute. |

Returns

OTF2_SUCCESS if successful, an error code if an error occurs.

J.3.3.45 `OTF2_ErrorCode OTF2_AttributeList_GetUint8 (const
OTF2_AttributeList * attributeList, OTF2_AttributeRef attribute, uint8_t
* uint8Value)`

Get an OTF2_TYPE_UINT8 attribute from an attribute list by attribute ID.
Convenient function around *OTF2_AttributeList_GetAttributeByID*.

Parameters

| | | |
|-----|----------------------|------------------------------------|
| | <i>attributeList</i> | Attribute list handle. |
| | <i>attribute</i> | Reference to Attribute definition. |
| out | <i>uint8Value</i> | Returned value of the attribute. |

Returns

OTF2_SUCCESS if successful, an error code if an error occurs.

J.3.3.46 `OTF2_AttributeList* OTF2_AttributeList_New (void)`

Create a new attribute list handle.

Returns

Returns a handle to the attribute list if successful, NULL otherwise.

J.3 OTF2_AttributeList.h File Reference

J.3.3.47 `OTF2_ErrorCode OTF2_AttributeList.PopAttribute (OTF2_AttributeList * attributeList, OTF2_AttributeRef * attribute, OTF2_Type * type, OTF2_AttributeValue * attributeValue)`

Get first attribute from an attribute list and remove it.

Returns the first entry in the attribute list and removes it from the list.

Parameters

| | | |
|-----|------------------------|----------------------------------|
| | <i>attributeList</i> | Attribute list handle. |
| out | <i>attribute</i> | Returned attribute reference. |
| out | <i>type</i> | Returned type of the attribute. |
| out | <i>attribute-Value</i> | Returned value of the attribute. |

Returns

[*OTF2_SUCCESS*](#) if successful, an error code if an error occurs.

J.3.3.48 `OTF2_ErrorCode OTF2_AttributeList.RemoveAllAttributes (OTF2_AttributeList * attributeList)`

Remove all attributes from an attribute list.

Parameters

| | |
|----------------------|------------------------|
| <i>attributeList</i> | Attribute list handle. |
|----------------------|------------------------|

Returns

[*OTF2_SUCCESS*](#) if successful, an error code if an error occurs.

J.3.3.49 `OTF2_ErrorCode OTF2_AttributeList.RemoveAttribute (OTF2_AttributeList * attributeList, OTF2_AttributeRef attribute)`

Remove an attribute from an attribute list.

Parameters

| | |
|----------------------|------------------------------------|
| <i>attributeList</i> | Attribute list handle. |
| <i>attribute</i> | Reference to Attribute definition. |

Returns

[OTF2_SUCCESS](#) if successful, an error code if an error occurs.

J.3.3.50 `bool OTF2_AttributeList_TestAttributeByID (const OTF2_AttributeList * attributeList, OTF2_AttributeRef attribute)`

Test if an attribute is in the attribute list.

Parameters

| | |
|----------------------|------------------------------------|
| <i>attributeList</i> | Attribute list handle. |
| <i>attribute</i> | Reference to Attribute definition. |

Returns

True if the id is in the list, else false.

J.4 OTF2_Callbacks.h File Reference

This header file provides all user callbacks.

```
#include <stdio.h>
#include <stdbool.h>
#include <otf2/OTF2_ErrorCodes.h>
#include <otf2/OTF2_GeneralDefinitions.h>
```

Data Structures

- struct [OTF2_FileSionCallbacks](#)
Structure holding the SION callbacks.
- struct [OTF2_FlushCallbacks](#)
Structure holding the flush callbacks.
- struct [OTF2_MemoryCallbacks](#)
Structure holding the memory callbacks.

J.4 OTF2_Callbacks.h File Reference

Typedefs

- typedef int(* [OTF2_FileSionClose](#))(void *userData, [OTF2_FileType](#) fileType, [OTF2_LocationRef](#) location, int sid)
Callbacks to wrap `sion_parclose_mpi()` for the OTF2 SION substrate.
- typedef [OTF2_ErrorCode](#)(* [OTF2_FileSionGetRank](#))(void *userData, [OTF2_FileType](#) fileType, [OTF2_LocationRef](#) location, int32_t *rank)
Provides location->rank translation, when using the SION substrate.
- typedef int(* [OTF2_FileSionOpen](#))(void *userData, [OTF2_FileType](#) fileType, [OTF2_LocationRef](#) location, const char *fname, const char *fileMode, long long int *chunkSize, int *fsblkSize, FILE **filePtr)
Callbacks to wrap `sion_paropen_mpi()` for the OTF2 SION substrate. Every parameter that can be given by OTF2 is named equally like the the according parameter of `sion_paropen_mpi()`. Therefore, these given parameters MUST be given to SION.
- typedef void *(* [OTF2_MemoryAllocate](#))(void *userData, [OTF2_FileType](#) fileType, [OTF2_LocationRef](#) location, void **perBufferData, uint64_t chunkSize)
Function pointer for allocating memory for chunks.
- typedef void(* [OTF2_MemoryFreeAll](#))(void *userData, [OTF2_FileType](#) fileType, [OTF2_LocationRef](#) location, void **perBufferData, bool final)
Function pointer to release all allocated chunks.
- typedef [OTF2_TimeStamp](#)(* [OTF2_PostFlushCallback](#))(void *userData, [OTF2_FileType](#) fileType, [OTF2_LocationRef](#) location)
Definition for the post flush callback.
- typedef [OTF2_FlushType](#)(* [OTF2_PreFlushCallback](#))(void *userData, [OTF2_FileType](#) fileType, [OTF2_LocationRef](#) location, void *callerData, bool final)
Definition for the pre flush callback.

J.4.1 Detailed Description

This header file provides all user callbacks.

Maintainer:

Michael Wagner <michael.wagner@zih.tu-dresden.de>

APPENDIX J. FILE DOCUMENTATION

Authors

Dominic Eschweiler <d.eschweiler@fz-juelich.de>, Michael Wagner <michael.wagner@zih.tu-dresden.de>

J.4.2 Typedef Documentation

J.4.2.1 `typedef int (* OTF2_FileSionClose)(void *userData, OTF2_FileType fileType, OTF2_LocationRef location, int sid)`

Callbacks to wrap `sion_parclose_mpi()` for the OTF2 SION substrate.

Parameters

| | |
|-----------------|---|
| <i>userData</i> | Data passed to the call OTF2_Archive_SetFileSionCallbacks . |
| <i>fileType</i> | The file type for which the file close is called. |
| <i>location</i> | The location ID of the writer for which the flush has happened (for file types without an ID this is OTF2_UNDEFINED_LOCATION). |
| <i>sid</i> | Sion file handle. |

Returns

Return value of `sion_parclose_mpi()`

J.4.2.2 `typedef OTF2_ErrorCode (* OTF2_FileSionGetRank)(void *userData, OTF2_FileType fileType, OTF2_LocationRef location, int32_t *rank)`

Provides `location->rank` translation, when using the SION substrate.

In case no `OTF2_FileSionOpen` and no `OTF2_FileSionClose` callback is given, the SION substrate still needs information what rank the current location has.

Parameters

| | | |
|-----|-----------------|---|
| | <i>userData</i> | Data passed to the call OTF2_Archive_SetFileSionCallbacks . |
| | <i>fileType</i> | The file type for which the file close is called. |
| | <i>location</i> | The location ID of the writer for which the flush has happened (for file types without an ID this is OTF2_UNDEFINED_LOCATION). |
| out | <i>rank</i> | The associated MPI rank for the <code>location</code> . |

Returns

[OTF2_SUCCESS](#), or error code.

J.4 OTF2_Callbacks.h File Reference

J.4.2.3 `typedef int(* OTF2_FileSionOpen)(void *userData, OTF2_FileType fileType, OTF2_LocationRef location, const char *fname, const char *fileMode, long long int *chunkSize, int *fsblkSize, FILE **filePtr)`

Callbacks to wrap `sion_paropen_mpi()` for the OTF2 SION substrate. Every parameter that can be given by OTF2 is named equally like the the according parameter of `sion_paropen_mpi()`. Therefore, these given parameters MUST be given to SION.

Parameters

| | | |
|---------|------------------|---|
| | <i>userData</i> | Data passed to the call OTF2_Archive_SetFileSionCallbacks . |
| | <i>fileType</i> | The file type for which the file open is called. |
| | <i>location</i> | The location ID of the writer for which the flush has happened (for file types without an ID this is OTF2_UNDEFINED_LOCATION). |
| | <i>fname</i> | Name of file, should equal on all tasks. |
| | <i>fileMode</i> | Like the type parameter of <code>fopen</code> . |
| in, out | <i>chunkSize</i> | Requested space for this task. |
| in, out | <i>fsblkSize</i> | Blocksize of filesystem, must be equal on all processors. |
| out | <i>filePtr</i> | Filepointer for this task. |

Returns

sion file handle integer (0, ...) -1 if error occurred

J.4.2.4 `typedef void*(* OTF2_MemoryAllocate)(void *userData, OTF2_FileType fileType, OTF2_LocationRef location, void **perBufferData, uint64_t chunkSize)`

Function pointer for allocating memory for chunks.

Please note: Do not use this feature if you do not really understand it. The OTF2 library is not able to do any kind of checks to validate if your memory management works properly. If you do not use it correctly OTF2's behaviour is undefined including dead locks and all that nasty stuff.

This function must return a pointer to a valid allocated memory location (just like `malloc`). This memory location must be of exact same size as the parameter 'chunkSize' provided with [OTF2_Archive_Open\(\)](#).

Parameters

| | | |
|--|-----------------|---|
| | <i>userData</i> | Data passed to the call OTF2_Archive_SetMemoryCallbacks . |
| | <i>fileType</i> | The file type for which the chunk is requested. |
| | <i>location</i> | The location ID of the writer for which the flush has happened (for file types without an ID this is OTF2_UNDEFINED_LOCATION). |

APPENDIX J. FILE DOCUMENTATION

| | |
|----------------------|---|
| <i>perBufferData</i> | A writeable pointer to store callee data. For the first call this will be NULL. |
| <i>chunkSize</i> | The size of the requested chunk. |

Returns

Returns a the allocated memory on success, NULL if an error occurs.

J.4.2.5 `typedef void(* OTF2_MemoryFreeAll)(void *userData, OTF2_FileType fileType, OTF2_LocationRef location, void **perBufferData, bool final)`

Function pointer to release all allocated chunks.

Please note: Do not use this feature if you do not really understand it. The OTF2 library is not able to do any kind of checks to validate if your memory management works properly. If you do not use it correctly OTF2's behaviour is undefined including dead locks and all that nasty stuff.

This function must free all those memory locations that were allocated for a buffer handle with the according allocate function. Please note: This is different from a posix free(). You must free *_all_* memory locations for that were allocated for exactly this buffer handle.

Parameters

| | |
|----------------------|---|
| <i>userData</i> | Data passed to the call OTF2_Archive_SetMemoryCallbacks . |
| <i>fileType</i> | The file type for which free is requested. |
| <i>location</i> | The location ID of the writer for which the flush has happened (for file types without an ID this is OTF2_UNDEFINED_LOCATION). |
| <i>perBufferData</i> | A writeable pointer to store callee data. For the first call this will be NULL. |
| <i>final</i> | Indicates whether this is the final free when closing the writer objects. <i>perBufferData</i> should be handled than. |

J.4.2.6 `typedef OTF2_TimeStamp(* OTF2_PostFlushCallback)(void *userData, OTF2_FileType fileType, OTF2_LocationRef location)`

Definition for the post flush callback.

This callback is triggered right after flushing the recorded data into file when running out of memory. The main function of this callback is to provide a timestamp for the end of flushing data into a file. So an according record can be written correctly.

J.5 OTF2_Definitions.h File Reference

Parameters

| | |
|-----------------|---|
| <i>userData</i> | Data passed to the call OTF2_Archive_SetFlushCallbacks . |
| <i>fileType</i> | The file type for which the flush has happened. |
| <i>location</i> | The location ID of the writer for which the flush has happened (for file types without an ID this is OTF2_UNDEFINED_LOCATION). |

Returns

Returns a timestamp for the end of flushing data into a file.

J.4.2.7 `typedef OTF2_FlushType(* OTF2_PreFlushCallback)(void *userData, OTF2_FileType fileType, OTF2_LocationRef location, void *callerData, bool final)`

Definition for the pre flush callback.

This callback is triggered right before flushing the recorded data into file when running out of memory.

Parameters

| | |
|-------------------|--|
| <i>userData</i> | Data passed to the call OTF2_Archive_SetFlushCallbacks . |
| <i>fileType</i> | The type of file for what this buffer holds data. |
| <i>location</i> | The location id for what this buffer holds data. This is only valid for files of type OTF2_FILETYPE_LOCAL_DEFS or OTF2_FILETYPE_EVENTS . For other files this is OTF2_UNDEFINED_LOCATION . A special case exists for files of type OTF2_FILETYPE_EVENTS in writing mode. The location ID may still be OTF2_UNDEFINED_LOCATION . In this case if the application wants to write the data from the buffer into the file, the application needs to provide a valid location ID via a call to OTF2_EvtWriter_SetLocationID() and utilizing the <i>callerData</i> argument. |
| <i>callerData</i> | Depending of the fileType, this can be an OTF2_EvtWriter , OTF2_GlobalDefWriter , OTF2_DefWriter . |
| <i>final</i> | Indicates whether this is the final flush when closing the writer objects. |

Returns

Returns [OTF2_FLUSH](#) or [OTF2_NO_FLUSH](#).

J.5 OTF2_Definitions.h File Reference

Data types used in the definition records.

APPENDIX J. FILE DOCUMENTATION

```
#include <otf2/OTF2_ErrorCodes.h>
#include <otf2/OTF2_GeneralDefinitions.h>
```

Typedefs

- typedef uint32_t [OTF2_GroupFlag](#)
Wrapper for enum [OTF2_GroupFlag_enum](#).
- typedef uint8_t [OTF2_GroupType](#)
Wrapper for enum [OTF2_GroupType_enum](#).
- typedef uint8_t [OTF2_LocationGroupType](#)
Wrapper for enum [OTF2_LocationGroupType_enum](#).
- typedef uint8_t [OTF2_LocationType](#)
Wrapper for enum [OTF2_LocationType_enum](#).
- typedef uint8_t [OTF2_MetricBase](#)
Wrapper for enum [OTF2_MetricBase_enum](#).
- typedef uint8_t [OTF2_MetricMode](#)
Wrapper for enum [OTF2_MetricMode_enum](#).
- typedef uint8_t [OTF2_MetricOccurrence](#)
Wrapper for enum [OTF2_MetricOccurrence_enum](#).
- typedef uint8_t [OTF2_MetricScope](#)
Wrapper for enum [OTF2_MetricScope_enum](#).
- typedef uint8_t [OTF2_MetricTiming](#)
Wrapper for enum [OTF2_MetricTiming_enum](#).
- typedef uint8_t [OTF2_MetricType](#)
Wrapper for enum [OTF2_MetricType_enum](#).
- typedef uint8_t [OTF2_MetricValueProperty](#)
Wrapper for enum [OTF2_MetricValueProperty_enum](#).
- typedef uint8_t [OTF2_ParameterType](#)
Wrapper for enum [OTF2_ParameterType_enum](#).

J.5 OTF2_Definitions.h File Reference

- typedef uint8_t [OTF2_RecorderKind](#)
Wrapper for enum [OTF2_RecorderKind_enum](#).
- typedef uint32_t [OTF2_RegionFlag](#)
Wrapper for enum [OTF2_RegionFlag_enum](#).
- typedef uint8_t [OTF2_RegionRole](#)
Wrapper for enum [OTF2_RegionRole_enum](#).
- typedef uint8_t [OTF2_SystemTreeDomain](#)
Wrapper for enum [OTF2_SystemTreeDomain_enum](#).

Enumerations

- enum [OTF2_GroupFlag_enum](#) {
[OTF2_GROUP_FLAG_NONE](#) = 0,
[OTF2_GROUP_FLAG_GLOBAL_MEMBERS](#) = (1 << 0) }
List of possible flags to specify special characteristics of a Group.
- enum [OTF2_GroupType_enum](#) {
[OTF2_GROUP_TYPE_UNKNOWN](#) = 0,
[OTF2_GROUP_TYPE_LOCATIONS](#) = 1,
[OTF2_GROUP_TYPE_REGIONS](#) = 2,
[OTF2_GROUP_TYPE_METRIC](#) = 3,
[OTF2_GROUP_TYPE_COMM_LOCATIONS](#) = 4,
[OTF2_GROUP_TYPE_COMM_GROUP](#) = 5,
[OTF2_GROUP_TYPE_COMM_SELF](#) = 6 }
• enum [OTF2_LocationGroupType_enum](#) {
[OTF2_LOCATION_GROUP_TYPE_UNKNOWN](#) = 0,
[OTF2_LOCATION_GROUP_TYPE_PROCESS](#) = 1 }
List of possible definitions of type LocationGroup.
- enum [OTF2_LocationType_enum](#) {
[OTF2_LOCATION_TYPE_UNKNOWN](#) = 0,
[OTF2_LOCATION_TYPE_CPU_THREAD](#) = 1,
[OTF2_LOCATION_TYPE_GPU](#) = 2,
[OTF2_LOCATION_TYPE_METRIC](#) = 3 }

APPENDIX J. FILE DOCUMENTATION

List of possible definitions of type Location.

- enum `OTF2_MetricBase_enum` {
 `OTF2_BASE_BINARY` = 0,
 `OTF2_BASE_DECIMAL` = 1 }

Metric base types.

- enum `OTF2_MetricMode_enum` {
 `OTF2_METRIC_ACCUMULATED_START` = `OTF2_METRIC_VALUE_-`
 `ACCUMULATED` | `OTF2_METRIC_TIMING_START`,
 `OTF2_METRIC_ACCUMULATED_POINT` = `OTF2_METRIC_VALUE_-`
 `ACCUMULATED` | `OTF2_METRIC_TIMING_POINT`,
 `OTF2_METRIC_ACCUMULATED_LAST` = `OTF2_METRIC_VALUE_ACCUMULATED`
 | `OTF2_METRIC_TIMING_LAST`,
 `OTF2_METRIC_ACCUMULATED_NEXT` = `OTF2_METRIC_VALUE_-`
 `ACCUMULATED` | `OTF2_METRIC_TIMING_NEXT`,
 `OTF2_METRIC_ABSOLUTE_POINT` = `OTF2_METRIC_VALUE_ABSOLUTE`
 | `OTF2_METRIC_TIMING_POINT`,
 `OTF2_METRIC_ABSOLUTE_LAST` = `OTF2_METRIC_VALUE_ABSOLUTE`
 | `OTF2_METRIC_TIMING_LAST`,
 `OTF2_METRIC_ABSOLUTE_NEXT` = `OTF2_METRIC_VALUE_ABSOLUTE`
 | `OTF2_METRIC_TIMING_NEXT`,
 `OTF2_METRIC_RELATIVE_POINT` = `OTF2_METRIC_VALUE_RELATIVE`
 | `OTF2_METRIC_TIMING_POINT`,
 `OTF2_METRIC_RELATIVE_LAST` = `OTF2_METRIC_VALUE_RELATIVE`
 | `OTF2_METRIC_TIMING_LAST`,
 `OTF2_METRIC_RELATIVE_NEXT` = `OTF2_METRIC_VALUE_RELATIVE`
 | `OTF2_METRIC_TIMING_NEXT` }

Metric mode is a combination of value property and timing information.

- enum `OTF2_MetricOccurrence_enum` {
 `OTF2_METRIC_SYNCHRONOUS_STRICT` = 0,
 `OTF2_METRIC_SYNCHRONOUS` = 1,
 `OTF2_METRIC_ASYNCHRONOUS` = 2 }

Metric occurrence.

- enum `OTF2_MetricScope_enum` {
 `OTF2_SCOPE_LOCATION` = 0,

J.5 OTF2_Definitions.h File Reference

```
OTF2_SCOPE_LOCATION_GROUP = 1,  
OTF2_SCOPE_SYSTEM_TREE_NODE = 2,  
OTF2_SCOPE_GROUP = 3 }
```

- enum OTF2_MetricTiming_enum {
OTF2_METRIC_TIMING_START = 0,
OTF2_METRIC_TIMING_POINT = 1 << 4,
OTF2_METRIC_TIMING_LAST = 2 << 4,
OTF2_METRIC_TIMING_NEXT = 3 << 4,
OTF2_METRIC_TIMING_MASK = 240 }

Determines when the values have been collected or for which interval of time they are valid. Used for the upper half-byte of OTF2_MetricMode.

- enum OTF2_MetricType_enum {
OTF2_METRIC_TYPE_OTHER = 0,
OTF2_METRIC_TYPE_PAPI = 1,
OTF2_METRIC_TYPE_RUSAGE = 2,
OTF2_METRIC_TYPE_USER = 3 }
- enum OTF2_MetricValueProperty_enum {
OTF2_METRIC_VALUE_ACCUMULATED = 0,
OTF2_METRIC_VALUE_ABSOLUTE = 1,
OTF2_METRIC_VALUE_RELATIVE = 2,
OTF2_METRIC_VALUE_MASK = 15 }

Information about whether the metric value is accumulated, absolute, or relative. Used for the lower half-byte of OTF2_MetricMode.

- enum OTF2_ParameterType_enum {
OTF2_PARAMETER_TYPE_STRING = 0,
OTF2_PARAMETER_TYPE_INT64 = 1,
OTF2_PARAMETER_TYPE_UINT64 = 2 }

List of possible for definitions of type Parameter.

- enum OTF2_RecorderKind_enum {
OTF2_RECORDER_KIND_UNKNOWN = 0,
OTF2_RECORDER_KIND_ABSTRACT = 1,
OTF2_RECORDER_KIND_CPU = 2,
OTF2_RECORDER_KIND_GPU = 3 }

APPENDIX J. FILE DOCUMENTATION

List of possible kinds a MetricClass can be recorded by.

- enum OTF2_RegionFlag_enum {
OTF2_REGION_FLAG_NONE = 0,
OTF2_REGION_FLAG_DYNAMIC = (1 << 0),
OTF2_REGION_FLAG_PHASE = (1 << 1) }
List of possible flags to specify special characteristics of a Region.
- enum OTF2_RegionRole_enum {
OTF2_REGION_ROLE_UNKNOWN = 0,
OTF2_REGION_ROLE_FUNCTION = 1,
OTF2_REGION_ROLE_WRAPPER = 2,
OTF2_REGION_ROLE_LOOP = 3,
OTF2_REGION_ROLE_CODE = 4,
OTF2_REGION_ROLE_PARALLEL = 5,
OTF2_REGION_ROLE_SECTIONS = 6,
OTF2_REGION_ROLE_SECTION = 7,
OTF2_REGION_ROLE_WORKSHARE = 8,
OTF2_REGION_ROLE_SINGLE = 9,
OTF2_REGION_ROLE_SINGLE_SBLOCK = 10,
OTF2_REGION_ROLE_MASTER = 11,
OTF2_REGION_ROLE_CRITICAL = 12,
OTF2_REGION_ROLE_CRITICAL_SBLOCK = 13,
OTF2_REGION_ROLE_ATOMIC = 14,
OTF2_REGION_ROLE_BARRIER = 15,
OTF2_REGION_ROLE_IMPLICIT_BARRIER = 16,
OTF2_REGION_ROLE_FLUSH = 17,
OTF2_REGION_ROLE_ORDERED = 18,
OTF2_REGION_ROLE_ORDERED_SBLOCK = 19,
OTF2_REGION_ROLE_TASK = 20,
OTF2_REGION_ROLE_TASK_CREATE = 21,
OTF2_REGION_ROLE_TASK_WAIT = 22,
OTF2_REGION_ROLE_COLL_ONE2ALL = 23,
OTF2_REGION_ROLE_COLL_ALL2ONE = 24,

J.5 OTF2_Definitions.h File Reference

```
OTF2_REGION_ROLE_COLL_ALL2ALL = 25,  
OTF2_REGION_ROLE_COLL_OTHER = 26,  
OTF2_REGION_ROLE_FILE_IO = 27,  
OTF2_REGION_ROLE_POINT2POINT = 28,  
OTF2_REGION_ROLE_RMA = 29,  
OTF2_REGION_ROLE_DATA_TRANSFER = 30,  
OTF2_REGION_ROLE_ARTIFICIAL = 31 }
```

List of possible roles of a Region.

- enum OTF2_SystemTreeDomain_enum {
OTF2_SYSTEM_TREE_DOMAIN_MACHINE = 0,
OTF2_SYSTEM_TREE_DOMAIN_SHARED_MEMORY = 1,
OTF2_SYSTEM_TREE_DOMAIN_NUMA = 2,
OTF2_SYSTEM_TREE_DOMAIN_SOCKET = 3,
OTF2_SYSTEM_TREE_DOMAIN_CACHE = 4,
OTF2_SYSTEM_TREE_DOMAIN_CORE = 5,
OTF2_SYSTEM_TREE_DOMAIN_PU = 6 }

J.5.1 Detailed Description

Data types used in the definition records.

Source Template:

templates/OTF2_Definitions.tmpl.h

Maintainer:

Dominic Eschweiler <d.eschweiler@fz-juelich.de>

Authors

Dominic Eschweiler <d.eschweiler@fz-juelich.de>, Michael Wagner <michael.wagner@zih.tu-dresden.de>

J.5.2 Enumeration Type Documentation

J.5.2.1 enum OTF2_GroupFlag_enum

List of possible flags to specify special characteristics of a Group.

Since

Version 1.2

Enumerator:

OTF2_GROUP_FLAG_NONE A group without special characterization.

OTF2_GROUP_FLAG_GLOBAL_MEMBERS No translation needs to be done when a group of type *OTF2_GROUP_TYPE_COMM_GROUP* has this flag.

J.5.2.2 enum OTF2_GroupType_enum

Since

Version 1.2

Enumerator:

OTF2_GROUP_TYPE_UNKNOWN Group of unknown type.

OTF2_GROUP_TYPE_LOCATIONS Group of locations.

OTF2_GROUP_TYPE_REGIONS Group of regions.

OTF2_GROUP_TYPE_METRIC Group of metrics.

OTF2_GROUP_TYPE_COMM_LOCATIONS List of location IDs, which are MPI ranks. The size of this group should match the size of *MPI_COMM_WORLD*. Each entry in the list is a location ID, where the index of the entry is equal to the rank in *MPI_COMM_WORLD*. (Ie. rank *i* corresponds to location members[*i*])

Also, if this definition is present, the location group ids of locations with type *OTF2_LOCATION_TYPE_CPU_THREAD* should match The MPI rank.

This group needs to be defined, before any group of type *OTF2_GROUP_TYPE_MPI_GROUP*.

Note: This does not makes sense in local definitions.

OTF2_GROUP_TYPE_COMM_GROUP MPI group.

OTF2_GROUP_TYPE_COMM_SELF Special group type to efficiently handle MPI self-like communicators.

J.5.2.3 enum OTF2_LocationGroupType_enum

List of possible definitions of type LocationGroup.

J.5 OTF2_Definitions.h File Reference

Since

Version 1.0

Enumerator:

OTF2_LOCATION_GROUP_TYPE_UNKNOWN A location group of unknown type.

OTF2_LOCATION_GROUP_TYPE_PROCESS A process.

J.5.2.4 enum OTF2_LocationType_enum

List of possible definitions of type Location.

Since

Version 1.0

Enumerator:

OTF2_LOCATION_TYPE_UNKNOWN A location of unknown type.

OTF2_LOCATION_TYPE_CPU_THREAD A CPU thread.

OTF2_LOCATION_TYPE_GPU A GPU location.

OTF2_LOCATION_TYPE_METRIC A metric only location e.g. an external device.

J.5.2.5 enum OTF2_MetricBase_enum

Metric base types.

Since

Version 1.0

Enumerator:

OTF2_BASE_BINARY Binary base.

OTF2_BASE_DECIMAL Decimal base.

J.5.2.6 enum **OTF2_MetricMode_enum**

Metric mode is a combination of value property and timing information.

Since

Version 1.0

Enumerator:

- OTF2_METRIC_ACCUMULATED_START* Accumulated metric, 'START' timing.
- OTF2_METRIC_ACCUMULATED_POINT* Accumulated metric, 'POINT' timing.
- OTF2_METRIC_ACCUMULATED_LAST* Accumulated metric, 'LAST' timing.
- OTF2_METRIC_ACCUMULATED_NEXT* Accumulated metric, 'NEXT' timing.
- OTF2_METRIC_ABSOLUTE_POINT* Absolute metric, 'POINT' timing.
- OTF2_METRIC_ABSOLUTE_LAST* Absolute metric, 'LAST' timing.
- OTF2_METRIC_ABSOLUTE_NEXT* Absolute metric, 'NEXT' timing.
- OTF2_METRIC_RELATIVE_POINT* Relative metric, 'POINT' timing.
- OTF2_METRIC_RELATIVE_LAST* Relative metric, 'LAST' timing.
- OTF2_METRIC_RELATIVE_NEXT* Relative metric, 'NEXT' timing.

J.5.2.7 enum **OTF2_MetricOccurrence_enum**

Metric occurrence.

Since

Version 1.0

Enumerator:

- OTF2_METRIC_SYNCHRONOUS_STRICT* Metric occurs at every region enter and leave.
- OTF2_METRIC_SYNCHRONOUS* Metric occurs only at a region enter and leave, but does not need to occur at every enter/leave.
- OTF2_METRIC_ASYNCHRONOUS* Metric can occur at any place i.e. it is not related to region enter and leaves.

J.5 OTF2_Definitions.h File Reference

J.5.2.8 enum OTF2_MetricScope_enum

Since

Version 1.0

Enumerator:

OTF2_SCOPE_LOCATION Scope of a metric is another location.

OTF2_SCOPE_LOCATION_GROUP Scope of a metric is a location group.

OTF2_SCOPE_SYSTEM_TREE_NODE Scope of a metric is a system tree node.

OTF2_SCOPE_GROUP Scope of a metric is a generic group of locations.

J.5.2.9 enum OTF2_MetricTiming_enum

Determines when the values have been collected or for which interval of time they are valid. Used for the upper half-byte of OTF2_MetricMode.

Since

Version 1.0

Enumerator:

OTF2_METRIC_TIMING_START Metric value belongs to the time interval since the beginning of the measurement.

OTF2_METRIC_TIMING_POINT Metric value is only valid at a point in time but not necessarily for any interval of time.

OTF2_METRIC_TIMING_LAST Metric value is related to the time interval since the last counter sample of the same metric, i.e. the immediate past.

OTF2_METRIC_TIMING_NEXT Metric value is valid from now until the next counter sample, i.e. the future right ahead.

OTF2_METRIC_TIMING_MASK This mask can be used to get the upper half-byte in OTF2_MetricMode that is used to indicate metric timing information.

J.5.2.10 enum OTF2_MetricType_enum

Since

Version 1.0

Enumerator:

OTF2_METRIC_TYPE_OTHER Any metric of a type not explicitly listed below.

OTF2_METRIC_TYPE_PAPI PAPI counter.

OTF2_METRIC_TYPE_RUSAGE Resource usage counter.

OTF2_METRIC_TYPE_USER User metrics.

J.5.2.11 enum OTF2_MetricValueProperty_enum

Information about whether the metric value is accumulated, absolute, or relative. Used for the lower half-byte of OTF2_MetricMode.

Since

Version 1.0

Enumerator:

OTF2_METRIC_VALUE_ACCUMULATED Accumulated metric is monotonously increasing (i.e., PAPI counter for number of executed floating point operations).

OTF2_METRIC_VALUE_ABSOLUTE Absolute metric (i.e., temperature, rate, mean value, etc.).

OTF2_METRIC_VALUE_RELATIVE Relative metric.

OTF2_METRIC_VALUE_MASK This mask can be used to get lower half-byte in OTF2_MetricMode that is used to indicate metric value property.

J.5.2.12 enum OTF2_ParameterType_enum

List of possible for definitions of type Parameter.

Since

Version 1.0

J.5 OTF2_Definitions.h File Reference

Enumerator:

OTF2_PARAMETER_TYPE_STRING Parameter is of type string.

OTF2_PARAMETER_TYPE_INT64 Parameter is of type signed 8-byte integer.

OTF2_PARAMETER_TYPE_UINT64 Parameter is of type unsigned 8-byte integer.

J.5.2.13 enum OTF2_RecorderKind_enum

List of possible kinds a MetricClass can be recorded by.

Since

Version 1.2

Enumerator:

OTF2_RECORDER_KIND_UNKNOWN No specific kind of recorder.

OTF2_RECORDER_KIND_ABSTRACT Only *MetricInstances* will record this metric class.

OTF2_RECORDER_KIND_CPU This metric class will only be recorded by locations of type [*OTF2_LOCATION_TYPE_CPU_THREAD*](#).

OTF2_RECORDER_KIND_GPU This metric class will only be recorded by locations of type [*OTF2_LOCATION_TYPE_GPU*](#).

J.5.2.14 enum OTF2_RegionFlag_enum

List of possible flags to specify special characteristics of a Region.

Since

Version 1.1

Enumerator:

OTF2_REGION_FLAG_NONE A region without special characterization.

OTF2_REGION_FLAG_DYNAMIC Each time this region is entered it will get an individual call path in the profile.

OTF2_REGION_FLAG_PHASE Each time this region is entered it will get an individual root node in the profile.

J.5.2.15 enum OTF2_RegionRole_enum

List of possible roles of a Region.

Since

Version 1.1

Enumerator:

- OTF2_REGION_ROLE_UNKNOWN* A region of unknown role.
- OTF2_REGION_ROLE_FUNCTION* An entire function/subroutine.
- OTF2_REGION_ROLE_WRAPPER* An API function wrapped by Score-P.
- OTF2_REGION_ROLE_LOOP* A loop in the code.
- OTF2_REGION_ROLE_CODE* An arbitrary section of code.
- OTF2_REGION_ROLE_PARALLEL* E.g. OpenMP "parallel" construct (structured block)
- OTF2_REGION_ROLE_SECTIONS* E.g. OpenMP "sections" construct.
- OTF2_REGION_ROLE_SECTION* Individual "section" inside an OpenMP "sections" construct.
- OTF2_REGION_ROLE_WORKSHARE* E.g. OpenMP "workshare" construct.
- OTF2_REGION_ROLE_SINGLE* E.g. OpenMP "single" construct.
- OTF2_REGION_ROLE_SINGLE_SBLOCK* E.g. OpenMP "single" construct (structured block)
- OTF2_REGION_ROLE_MASTER* E.g. OpenMP "master" construct.
- OTF2_REGION_ROLE_CRITICAL* E.g. OpenMP "critical" construct.
- OTF2_REGION_ROLE_CRITICAL_SBLOCK* E.g. OpenMP "critical" construct (structured block)
- OTF2_REGION_ROLE_ATOMIC* E.g. OpenMP "atomic" construct.
- OTF2_REGION_ROLE_BARRIER* Explicit barrier.
- OTF2_REGION_ROLE_IMPLICIT_BARRIER* Implicit barrier.
- OTF2_REGION_ROLE_FLUSH* E.g. OpenMP "flush" construct.
- OTF2_REGION_ROLE_ORDERED* E.g. OpenMP "ordered" construct.
- OTF2_REGION_ROLE_ORDERED_SBLOCK* E.g. OpenMP "ordered" construct (structured block)
- OTF2_REGION_ROLE_TASK* "task" construct (structured block)
- OTF2_REGION_ROLE_TASK_CREATE* "task" construct (creation)

J.5 OTF2_Definitions.h File Reference

OTF2_REGION_ROLE_TASK_WAIT "taskwait" construct

OTF2_REGION_ROLE_COLL_ONE2ALL Collective 1:N communication operation.

OTF2_REGION_ROLE_COLL_ALL2ONE Collective N:1 communication operation.

OTF2_REGION_ROLE_COLL_ALL2ALL Collective N:N communication operation.

OTF2_REGION_ROLE_COLL_OTHER Collective M:N communication operation.

OTF2_REGION_ROLE_FILE_IO Any file I/O operation.

OTF2_REGION_ROLE_POINT2POINT A point-to-point communication function.

OTF2_REGION_ROLE_RMA A remote memory access communication operation.

OTF2_REGION_ROLE_DATA_TRANSFER A data transfer operation in memory.

OTF2_REGION_ROLE_ARTIFICIAL An artificial region, mostly used by the monitor software.

Since

Version 1.2.

J.5.2.16 enum OTF2_SystemTreeDomain_enum

Since

Version 1.2

Enumerator:

OTF2_SYSTEM_TREE_DOMAIN_MACHINE All nodes below a node with this attribute encompass a tightly coupled HPC system.

OTF2_SYSTEM_TREE_DOMAIN_SHARED_MEMORY All nodes below a node with this attribute encompass a system where processes can communicate via hardware shared memory.

OTF2_SYSTEM_TREE_DOMAIN_NUMA A numa domain. A set of processors around memory which the processors can directly access.

OTF2_SYSTEM_TREE_DOMAIN_SOCKET Socket, physical package, or chip. In the physical meaning, i.e. that you can add or remove physically.

OTF2_SYSTEM_TREE_DOMAIN_CACHE Cache. Can be L1i, L1d, L2, L3, ...

OTF2_SYSTEM_TREE_DOMAIN_CORE Core. A computation unit (may be shared by several logical processors).

OTF2_SYSTEM_TREE_DOMAIN_PU Processing Unit (An non-shared ALU, FPU, ...)

J.6 OTF2_DefReader.h File Reference

This is the local definition reader, which reads location dependend definitions, and can also be used to get the mapping information from the local definition file. Local definitions are always assigned to a location.

```
#include <stdint.h>
#include <otf2/OTF2_ErrorCodes.h>
#include <otf2/OTF2_Definitions.h>
#include <otf2/OTF2_DefReaderCallbacks.h>
```

Functions

- [OTF2_ErrorCode OTF2_DefReader_GetLocationID](#) (const [OTF2_DefReader](#) *reader, [OTF2_LocationRef](#) *location)
Get the location ID of this reader object.
- [OTF2_ErrorCode OTF2_DefReader_ReadDefinitions](#) ([OTF2_DefReader](#) *reader, [uint64_t](#) recordsToRead, [uint64_t](#) *recordsRead)
Reads the given number of records from the definition reader.
- [OTF2_ErrorCode OTF2_DefReader_SetCallbacks](#) ([OTF2_DefReader](#) *reader, const [OTF2_DefReaderCallbacks](#) *callbacks, void *userData)
Sets the callback functions for the given reader object. Everytime when OTF2 reads a record, a callback function is called and the records data is passed to this function. Therefore the programmer needs to set function pointers at the "callbacks" struct for the record type he wants to read.

J.6.1 Detailed Description

This is the local definition reader, which reads location dependend definitions, and can also be used to get the mapping information from the local definition file. Local definitions are always assigned to a location.

J.6 OTF2_DefReader.h File Reference

Maintainer:

Dominic Eschweiler <d.eschweiler@fz-juelich.de>

Authors

Dominic Eschweiler <d.eschweiler@fz-juelich.de>, Michael Wagner <michael.wagner@zih.tu-dresden.de>

J.6.2 Function Documentation

J.6.2.1 OTF2_ErrorCode OTF2_DefReader.GetLocationID (const OTF2_DefReader * reader, OTF2_LocationRef * location)

Get the location ID of this reader object.

Parameters

| | |
|-----------------|---|
| <i>reader</i> | This given reader object will be deleted. |
| <i>location</i> | Pointer to the variable where the location ID is returned in. |

Returns

OTF2_SUCCESS if successful, an error code if an error occurs.

J.6.2.2 OTF2_ErrorCode OTF2_DefReader.ReadDefinitions (OTF2_DefReader * reader, uint64_t recordsToRead, uint64_t * recordsRead)

Reads the given number of records from the definition reader.

Parameters

| | | |
|-----|----------------------|--|
| | <i>reader</i> | The records of this reader will be read when the function is issued. |
| | <i>recordsToRead</i> | This variable tells the reader how much records it has to read. |
| out | <i>recordsRead</i> | This is a pointer to variable where the amount of actually read records is returned. This may differ to the given <i>recordsToRead</i> if there are no more records left in the trace. In this case the programmer can easily check that the reader has finished his job by checking <i>recordsRead</i> < <i>recordsToRead</i> . |

Returns

OTF2_SUCCESS if successful

APPENDIX J. FILE DOCUMENTATION

OTF2_ERROR_INTERRUPTED_BY_CALLBACK if an user supplied callback returned `OTF2_CALLBACK_INTERRUPT`

OTF2_ERROR_DUPLICATE_MAPPING_TABLE if an duplicate mapping table definition was read

otherwise the error code

J.6.2.3 `OTF2_ErrorCode OTF2_DefReader_SetCallbacks (OTF2_DefReader * reader, const OTF2_DefReaderCallbacks * callbacks, void * userData)`

Sets the callback functions for the given reader object. Everytime when OTF2 reads a record, a callback function is called and the records data is passed to this function. Therefore the programmer needs to set function pointers at the "callbacks" struct for the record type he wants to read.

Parameters

| | |
|------------------|---|
| <i>reader</i> | This given reader object will be setted up with new callback functions. |
| <i>callbacks</i> | Struct which holds a function pointer for each record type. OTF2_DefReaderCallbacks_New . |
| <i>userData</i> | Data passed as argument <i>userData</i> to the record callbacks. |

Returns

OTF2_SUCCESS if successful, an error code if an error occurs.

J.7 OTF2_DefReaderCallbacks.h File Reference

This defines the callbacks for the definition reader.

```
#include <stdint.h>
#include <otf2/OTF2_ErrorCodes.h>
#include <otf2/OTF2_GeneralDefinitions.h>
#include <otf2/OTF2_Definitions.h>
#include <otf2/OTF2_IdMap.h>
```

Typedefs

- typedef `OTF2_CallbackCode(* OTF2_DefReaderCallback_Attribute)(void *userData, OTF2_AttributeRef self, OTF2_StringRef name, OTF2_Type type)`

J.7 OTF2_DefReaderCallbacks.h File Reference

Function pointer definition for the callback which is triggered by a [Attribute](#) definition record.

- typedef [OTF2_CallbackCode](#)(* [OTF2_DefReaderCallback_Callpath](#))(void *userData, [OTF2_CallpathRef](#) self, [OTF2_CallpathRef](#) parent, [OTF2_RegionRef](#) region)

Function pointer definition for the callback which is triggered by a [Callpath](#) definition record.

- typedef [OTF2_CallbackCode](#)(* [OTF2_DefReaderCallback_Callsite](#))(void *userData, [OTF2_CallsiteRef](#) self, [OTF2_StringRef](#) sourceFile, [uint32_t](#) lineNumber, [OTF2_RegionRef](#) enteredRegion, [OTF2_RegionRef](#) leftRegion)

Function pointer definition for the callback which is triggered by a [Callsite](#) definition record.

- typedef [OTF2_CallbackCode](#)(* [OTF2_DefReaderCallback_ClockOffset](#))(void *userData, [OTF2_TimeStamp](#) time, [int64_t](#) offset, double standardDeviation)

Function pointer definition for the callback which is triggered by a [ClockOffset](#) definition record.

- typedef [OTF2_CallbackCode](#)(* [OTF2_DefReaderCallback_Comm](#))(void *userData, [OTF2_CommRef](#) self, [OTF2_StringRef](#) name, [OTF2_GroupRef](#) group, [OTF2_CommRef](#) parent)

Function pointer definition for the callback which is triggered by a [Comm](#) definition record.

- typedef [OTF2_CallbackCode](#)(* [OTF2_DefReaderCallback_Group](#))(void *userData, [OTF2_GroupRef](#) self, [OTF2_StringRef](#) name, [OTF2_GroupType](#) groupType, [OTF2_Paradigm](#) paradigm, [OTF2_GroupFlag](#) groupFlags, [uint32_t](#) numberOfMembers, const [uint64_t](#) *members)

Function pointer definition for the callback which is triggered by a [Group](#) definition record.

- typedef [OTF2_CallbackCode](#)(* [OTF2_DefReaderCallback_Location](#))(void *userData, [OTF2_LocationRef](#) self, [OTF2_StringRef](#) name, [OTF2_LocationType](#) locationType, [uint64_t](#) numberOfEvents, [OTF2_LocationGroupRef](#) locationGroup)

Function pointer definition for the callback which is triggered by a [Location](#) definition record.

- typedef [OTF2_CallbackCode](#)(* [OTF2_DefReaderCallback_LocationGroup](#))(void *userData, [OTF2_LocationGroupRef](#) self, [OTF2_StringRef](#) name, [OTF2_](#)

APPENDIX J. FILE DOCUMENTATION

[LocationGroupType](#) locationGroupType, [OTF2_SystemTreeNodeRef](#) systemTreeParent)

Function pointer definition for the callback which is triggered by a [LocationGroup](#) definition record.

- typedef [OTF2_CallbackCode](#)(* [OTF2_DefReaderCallback_MappingTable](#))(void *userData, [OTF2_MappingType](#) mappingType, const [OTF2_IdMap](#) *idMap)

Function pointer definition for the callback which is triggered by a [MappingTable](#) definition record.

- typedef [OTF2_CallbackCode](#)(* [OTF2_DefReaderCallback_MetricClass](#))(void *userData, [OTF2_MetricRef](#) self, uint8_t numberOfMetrics, const [OTF2_MetricMemberRef](#) *metricMembers, [OTF2_MetricOccurrence](#) metricOccurrence, [OTF2_RecorderKind](#) recorderKind)

Function pointer definition for the callback which is triggered by a [MetricClass](#) definition record.

- typedef [OTF2_CallbackCode](#)(* [OTF2_DefReaderCallback_MetricClassRecorder](#))(void *userData, [OTF2_MetricRef](#) metricClass, [OTF2_LocationRef](#) recorder)

Function pointer definition for the callback which is triggered by a [MetricClassRecorder](#) definition record.

- typedef [OTF2_CallbackCode](#)(* [OTF2_DefReaderCallback_MetricInstance](#))(void *userData, [OTF2_MetricRef](#) self, [OTF2_MetricRef](#) metricClass, [OTF2_LocationRef](#) recorder, [OTF2_MetricScope](#) metricScope, uint64_t scope)

Function pointer definition for the callback which is triggered by a [MetricInstance](#) definition record.

- typedef [OTF2_CallbackCode](#)(* [OTF2_DefReaderCallback_MetricMember](#))(void *userData, [OTF2_MetricMemberRef](#) self, [OTF2_StringRef](#) name, [OTF2_StringRef](#) description, [OTF2_MetricType](#) metricType, [OTF2_MetricMode](#) metricMode, [OTF2_Type](#) valueType, [OTF2_MetricBase](#) metricBase, int64_t exponent, [OTF2_StringRef](#) unit)

Function pointer definition for the callback which is triggered by a [MetricMember](#) definition record.

- typedef [OTF2_CallbackCode](#)(* [OTF2_DefReaderCallback_Parameter](#))(void *userData, [OTF2_ParameterRef](#) self, [OTF2_StringRef](#) name, [OTF2_ParameterType](#) parameterType)

Function pointer definition for the callback which is triggered by a [Parameter](#) definition record.

J.7 OTF2_DefReaderCallbacks.h File Reference

- typedef `OTF2_CallbackCode(* OTF2_DefReaderCallback_Region)`(void *userData, `OTF2_RegionRef` self, `OTF2_StringRef` name, `OTF2_StringRef` canonicalName, `OTF2_StringRef` description, `OTF2_RegionRole` regionRole, `OTF2_Paradigm` paradigm, `OTF2_RegionFlag` regionFlags, `OTF2_StringRef` sourceFile, `uint32_t` beginLineNumber, `uint32_t` endLineNumber)
Function pointer definition for the callback which is triggered by a [Region](#) definition record.
- typedef `OTF2_CallbackCode(* OTF2_DefReaderCallback_RmaWin)`(void *userData, `OTF2_RmaWinRef` self, `OTF2_StringRef` name, `OTF2_CommRef` comm)
Function pointer definition for the callback which is triggered by a [RmaWin](#) definition record.
- typedef `OTF2_CallbackCode(* OTF2_DefReaderCallback_String)`(void *userData, `OTF2_StringRef` self, const char *string)
Function pointer definition for the callback which is triggered by a [String](#) definition record.
- typedef `OTF2_CallbackCode(* OTF2_DefReaderCallback_SystemTreeNode)`(void *userData, `OTF2_SystemTreeNodeRef` self, `OTF2_StringRef` name, `OTF2_StringRef` className, `OTF2_SystemTreeNodeRef` parent)
Function pointer definition for the callback which is triggered by a [SystemTreeNode](#) definition record.
- typedef `OTF2_CallbackCode(* OTF2_DefReaderCallback_SystemTreeNodeDomain)`(void *userData, `OTF2_SystemTreeNodeRef` systemTreeNode, `OTF2_SystemTreeDomain` systemTreeDomain)
Function pointer definition for the callback which is triggered by a [SystemTreeNodeDomain](#) definition record.
- typedef `OTF2_CallbackCode(* OTF2_DefReaderCallback_SystemTreeNodeProperty)`(void *userData, `OTF2_SystemTreeNodeRef` systemTreeNode, `OTF2_StringRef` name, `OTF2_StringRef` value)
Function pointer definition for the callback which is triggered by a [SystemTreeNodeProperty](#) definition record.
- typedef `OTF2_CallbackCode(* OTF2_DefReaderCallback_Unknown)`(void *userData)
Function pointer definition for the callback which is triggered for an unknown definition.

APPENDIX J. FILE DOCUMENTATION

- typedef struct OTF2_DefReaderCallbacks_struct [OTF2_DefReaderCallbacks](#)

Opaque struct which holds all definition record callbacks.

Functions

- void [OTF2_DefReaderCallbacks_Clear](#) ([OTF2_DefReaderCallbacks](#) *defReaderCallbacks)

Clears a struct for the definition callbacks.

- void [OTF2_DefReaderCallbacks_Delete](#) ([OTF2_DefReaderCallbacks](#) *defReaderCallbacks)

Deallocates a struct for the definition callbacks.

- [OTF2_DefReaderCallbacks](#) * [OTF2_DefReaderCallbacks_New](#) (void)

Allocates a new struct for the definition callbacks.

- [OTF2_ErrorCode](#) [OTF2_DefReaderCallbacks_SetAttributeCallback](#) ([OTF2_DefReaderCallbacks](#) *defReaderCallbacks, [OTF2_DefReaderCallback_Attribute](#) attributeCallback)

*Registers the callback for the *Attribute* definition.*

- [OTF2_ErrorCode](#) [OTF2_DefReaderCallbacks_SetCallpathCallback](#) ([OTF2_DefReaderCallbacks](#) *defReaderCallbacks, [OTF2_DefReaderCallback_Callpath](#) callpathCallback)

*Registers the callback for the *Callpath* definition.*

- [OTF2_ErrorCode](#) [OTF2_DefReaderCallbacks_SetCallsiteCallback](#) ([OTF2_DefReaderCallbacks](#) *defReaderCallbacks, [OTF2_DefReaderCallback_Callsite](#) callsiteCallback)

*Registers the callback for the *Callsite* definition.*

- [OTF2_ErrorCode](#) [OTF2_DefReaderCallbacks_SetClockOffsetCallback](#) ([OTF2_DefReaderCallbacks](#) *defReaderCallbacks, [OTF2_DefReaderCallback_ClockOffset](#) clockOffsetCallback)

*Registers the callback for the *ClockOffset* definition.*

- [OTF2_ErrorCode](#) [OTF2_DefReaderCallbacks_SetCommCallback](#) ([OTF2_DefReaderCallbacks](#) *defReaderCallbacks, [OTF2_DefReaderCallback_Comm](#) commCallback)

*Registers the callback for the *Comm* definition.*

J.7 OTF2_DefReaderCallbacks.h File Reference

- [OTF2_ErrorCode](#) [OTF2_DefReaderCallbacks_SetGroupCallback](#) ([OTF2_DefReaderCallbacks](#) *defReaderCallbacks, [OTF2_DefReaderCallback_Group](#) groupCallback)
Registers the callback for the [Group](#) definition.
- [OTF2_ErrorCode](#) [OTF2_DefReaderCallbacks_SetLocationCallback](#) ([OTF2_DefReaderCallbacks](#) *defReaderCallbacks, [OTF2_DefReaderCallback_Location](#) locationCallback)
Registers the callback for the [Location](#) definition.
- [OTF2_ErrorCode](#) [OTF2_DefReaderCallbacks_SetLocationGroupCallback](#) ([OTF2_DefReaderCallbacks](#) *defReaderCallbacks, [OTF2_DefReaderCallback_LocationGroup](#) locationGroupCallback)
Registers the callback for the [LocationGroup](#) definition.
- [OTF2_ErrorCode](#) [OTF2_DefReaderCallbacks_SetMappingTableCallback](#) ([OTF2_DefReaderCallbacks](#) *defReaderCallbacks, [OTF2_DefReaderCallback_MappingTable](#) mappingTableCallback)
Registers the callback for the [MappingTable](#) definition.
- [OTF2_ErrorCode](#) [OTF2_DefReaderCallbacks_SetMetricClassCallback](#) ([OTF2_DefReaderCallbacks](#) *defReaderCallbacks, [OTF2_DefReaderCallback_MetricClass](#) metricClassCallback)
Registers the callback for the [MetricClass](#) definition.
- [OTF2_ErrorCode](#) [OTF2_DefReaderCallbacks_SetMetricClassRecorderCallback](#) ([OTF2_DefReaderCallbacks](#) *defReaderCallbacks, [OTF2_DefReaderCallback_MetricClassRecorder](#) metricClassRecorderCallback)
Registers the callback for the [MetricClassRecorder](#) definition.
- [OTF2_ErrorCode](#) [OTF2_DefReaderCallbacks_SetMetricInstanceCallback](#) ([OTF2_DefReaderCallbacks](#) *defReaderCallbacks, [OTF2_DefReaderCallback_MetricInstance](#) metricInstanceCallback)
Registers the callback for the [MetricInstance](#) definition.
- [OTF2_ErrorCode](#) [OTF2_DefReaderCallbacks_SetMetricMemberCallback](#) ([OTF2_DefReaderCallbacks](#) *defReaderCallbacks, [OTF2_DefReaderCallback_MetricMember](#) metricMemberCallback)
Registers the callback for the [MetricMember](#) definition.

APPENDIX J. FILE DOCUMENTATION

- [OTF2_ErrorCode](#) [OTF2_DefReaderCallbacks_SetParameterCallback](#) ([OTF2_DefReaderCallbacks](#) *defReaderCallbacks, [OTF2_DefReaderCallback_Parameter](#) parameterCallback)
Registers the callback for the [Parameter](#) definition.
- [OTF2_ErrorCode](#) [OTF2_DefReaderCallbacks_SetRegionCallback](#) ([OTF2_DefReaderCallbacks](#) *defReaderCallbacks, [OTF2_DefReaderCallback_Region](#) regionCallback)
Registers the callback for the [Region](#) definition.
- [OTF2_ErrorCode](#) [OTF2_DefReaderCallbacks_SetRmaWinCallback](#) ([OTF2_DefReaderCallbacks](#) *defReaderCallbacks, [OTF2_DefReaderCallback_RmaWin](#) rmaWinCallback)
Registers the callback for the [RmaWin](#) definition.
- [OTF2_ErrorCode](#) [OTF2_DefReaderCallbacks_SetStringCallback](#) ([OTF2_DefReaderCallbacks](#) *defReaderCallbacks, [OTF2_DefReaderCallback_String](#) stringCallback)
Registers the callback for the [String](#) definition.
- [OTF2_ErrorCode](#) [OTF2_DefReaderCallbacks_SetSystemTreeNodeCallback](#) ([OTF2_DefReaderCallbacks](#) *defReaderCallbacks, [OTF2_DefReaderCallback_SystemTreeNode](#) systemTreeNodeCallback)
Registers the callback for the [SystemTreeNode](#) definition.
- [OTF2_ErrorCode](#) [OTF2_DefReaderCallbacks_SetSystemTreeNodeDomainCallback](#) ([OTF2_DefReaderCallbacks](#) *defReaderCallbacks, [OTF2_DefReaderCallback_SystemTreeNodeDomain](#) systemTreeNodeDomainCallback)
Registers the callback for the [SystemTreeNodeDomain](#) definition.
- [OTF2_ErrorCode](#) [OTF2_DefReaderCallbacks_SetSystemTreeNodePropertyCallback](#) ([OTF2_DefReaderCallbacks](#) *defReaderCallbacks, [OTF2_DefReaderCallback_SystemTreeNodeProperty](#) systemTreeNodePropertyCallback)
Registers the callback for the [SystemTreeNodeProperty](#) definition.
- [OTF2_ErrorCode](#) [OTF2_DefReaderCallbacks_SetUnknownCallback](#) ([OTF2_DefReaderCallbacks](#) *defReaderCallbacks, [OTF2_DefReaderCallback_Unknown](#) unknownCallback)
Registers the callback for an unknown definition.

J.7.1 Detailed Description

This defines the callbacks for the definition reader.

J.7 OTF2_DefReaderCallbacks.h File Reference

Source Template:

templates/OTF2_DefReaderCallbacks.tmpl.h

Maintainer:

Dominic Eschweiler <d.eschweiler@fz-juelich.de>

Authors

Dominic Eschweiler <d.eschweiler@fz-juelich.de>, Michael Wagner <michael.wagner@zih.tu-dresden.de>

J.7.2 Typedef Documentation

J.7.2.1 `typedef OTF2_CallbackCode(* OTF2_DefReaderCallback_
Attribute)(void *userData, OTF2_AttributeRef self, OTF2_StringRef
name, OTF2_Type type)`

Function pointer definition for the callback which is triggered by a [Attribute](#) definition record.

Parameters

| | |
|-----------------|---|
| <i>userData</i> | User data as set by OTF2_Reader_RegisterDefCallbacks or OTF2_DefReader_SetCallbacks . |
| <i>self</i> | The unique identifier for this Attribute definition. |
| <i>name</i> | Name of the attribute. References a String definition. |
| <i>type</i> | Type of the attribute value. |

Since

Version 1.0

Returns

[OTF2_CALLBACK_SUCCESS](#) or [OTF2_CALLBACK_INTERRUPT](#).

J.7.2.2 `typedef OTF2_CallbackCode(* OTF2_DefReaderCallback_
Callpath)(void *userData, OTF2_CallpathRef self, OTF2_CallpathRef
parent, OTF2_RegionRef region)`

Function pointer definition for the callback which is triggered by a [Callpath](#) definition record.

APPENDIX J. FILE DOCUMENTATION

Parameters

| | |
|-----------------|---|
| <i>userData</i> | User data as set by OTF2_Reader_RegisterDefCallbacks or OTF2_DefReader_SetCallbacks . |
| <i>self</i> | The unique identifier for this Callpath definition. |
| <i>parent</i> | References a Callpath definition. |
| <i>region</i> | References a Region definition. |

Since

Version 1.0

Returns

[OTF2_CALLBACK_SUCCESS](#) or [OTF2_CALLBACK_INTERRUPT](#).

J.7.2.3 `typedef OTF2_CallbackCode(* OTF2_DefReaderCallback_ -
Callsite)(void *userData, OTF2_CallsiteRef self, OTF2_StringRef
sourceFile, uint32_t lineNumber, OTF2_RegionRef enteredRegion,
OTF2_RegionRef leftRegion)`

Function pointer definition for the callback which is triggered by a [Callsite](#) definition record.

Parameters

| | |
|----------------------|---|
| <i>userData</i> | User data as set by OTF2_Reader_RegisterDefCallbacks or OTF2_DefReader_SetCallbacks . |
| <i>self</i> | The unique identifier for this Callsite definition. |
| <i>sourceFile</i> | The source file where this call was made. References a String definition. |
| <i>lineNumber</i> | Line number in the source file where this call was made. |
| <i>enteredRegion</i> | The region which was called. References a Region definition. |
| <i>leftRegion</i> | The region which made the call. References a Region definition. |

Since

Version 1.0

Returns

[OTF2_CALLBACK_SUCCESS](#) or [OTF2_CALLBACK_INTERRUPT](#).

J.7 OTF2_DefReaderCallbacks.h File Reference

J.7.2.4 `typedef OTF2_CallbackCode(* OTF2_DefReaderCallback_
ClockOffset)(void *userData, OTF2_TimeStamp time, int64_t offset, double
standardDeviation)`

Function pointer definition for the callback which is triggered by a [ClockOffset](#) definition record.

Clock offsets are used for clock corrections.

Parameters

| | |
|---------------------------|---|
| <i>userData</i> | User data as set by OTF2_Reader_RegisterDefCallbacks or OTF2_DefReader_SetCallbacks . |
| <i>time</i> | Time when this offset was determined. |
| <i>offset</i> | The offset to the global clock which was determined at <i>time</i> . |
| <i>standard-Deviation</i> | A possible standard deviation, which can be used as a metric for the quality of the offset. |

Since

Version 1.0

Returns

[OTF2_CALLBACK_SUCCESS](#) or [OTF2_CALLBACK_INTERRUPT](#).

J.7.2.5 `typedef OTF2_CallbackCode(* OTF2_DefReaderCallback_
Comm)(void *userData, OTF2_CommRef self, OTF2_StringRef name,
OTF2_GroupRef group, OTF2_CommRef parent)`

Function pointer definition for the callback which is triggered by a [Comm](#) definition record.

Parameters

| | |
|-----------------|---|
| <i>userData</i> | User data as set by OTF2_Reader_RegisterDefCallbacks or OTF2_DefReader_SetCallbacks . |
| <i>self</i> | The unique identifier for this Comm definition. |
| <i>name</i> | The name given by calling <code>MPI_Comm_set_name</code> on this communicator. Or the empty name to indicate that no name was given. References a String definition. |
| <i>group</i> | The describing MPI group of this MPI communicator The group needs to be of type <code>OTF2_GROUP_TYPE_MPI_GROUP</code> or <code>OTF2_GROUP_TYPE_MPI_COMM_SELF</code> . References a Group definition. |
| <i>parent</i> | The parent MPI communicator from which this communicator was created, if any. Use OTF2_UNDEFINED_COMM to indicate no parent. |
| | References a Comm definition. |

Since

Version 1.0

Returns

OTF2_CALLBACK_SUCCESS or *OTF2_CALLBACK_INTERRUPT*.

J.7.2.6 `typedef OTF2_CallbackCode(* OTF2_DefReaderCallback_ -
Group)(void *userData, OTF2_GroupRef self, OTF2_StringRef
name, OTF2_GroupType groupType, OTF2_Paradigm paradigm,
OTF2_GroupFlag groupFlags, uint32_t numberOfMembers, const uint64_t
*members)`

Function pointer definition for the callback which is triggered by a **Group** definition record.

Parameters

| | |
|------------------------|---|
| <i>userData</i> | User data as set by OTF2_Reader_RegisterDefCallbacks or OTF2_DefReader_SetCallbacks . |
| <i>self</i> | The unique identifier for this Group definition. |
| <i>name</i> | Name of this group References a String definition. |
| <i>groupType</i> | The type of this group. Since version 1.2. |
| <i>paradigm</i> | The paradigm of this communication group. Since version 1.2. |
| <i>groupFlags</i> | Flags for this group. Since version 1.2. |
| <i>numberOfMembers</i> | The number of members in this group. |
| <i>members</i> | The identifiers of the group members. |

Since

Version 1.0

Returns

OTF2_CALLBACK_SUCCESS or *OTF2_CALLBACK_INTERRUPT*.

J.7 OTF2_DefReaderCallbacks.h File Reference

J.7.2.7 `typedef OTF2_CallbackCode(* OTF2_DefReaderCallback_ - Location)(void *userData, OTF2_LocationRef self, OTF2_StringRef name, OTF2_LocationType locationType, uint64_t numberOfEvents, OTF2_LocationGroupRef locationGroup)`

Function pointer definition for the callback which is triggered by a [Location](#) definition record.

Parameters

| | |
|-----------------------|---|
| <i>userData</i> | User data as set by OTF2_Reader_RegisterDefCallbacks or OTF2_DefReader_SetCallbacks . |
| <i>self</i> | The unique identifier for this Location definition. |
| <i>name</i> | Name of the location References a String definition. |
| <i>location-Type</i> | Location type. |
| <i>numberOfEvents</i> | Number of events this location has recorded. |
| <i>location-Group</i> | Location group which includes this location. References a Location-Group definition. |

Since

Version 1.0

Returns

[OTF2_CALLBACK_SUCCESS](#) or [OTF2_CALLBACK_INTERRUPT](#).

J.7.2.8 `typedef OTF2_CallbackCode(* OTF2_DefReaderCallback_ - LocationGroup)(void *userData, OTF2_LocationGroupRef self, OTF2_StringRef name, OTF2_LocationGroupType locationGroupType, OTF2_SystemTreeNodeRef systemTreeParent)`

Function pointer definition for the callback which is triggered by a [LocationGroup](#) definition record.

Parameters

| | |
|---------------------------|---|
| <i>userData</i> | User data as set by OTF2_Reader_RegisterDefCallbacks or OTF2_DefReader_SetCallbacks . |
| <i>self</i> | The unique identifier for this LocationGroup definition. |
| <i>name</i> | Name of the group. References a String definition. |
| <i>location-GroupType</i> | Type of this group. |

APPENDIX J. FILE DOCUMENTATION

| | |
|-------------------------------------|---|
| <i>sys- temTreePar- ent</i> | Parent of this location group in the system tree. References a SystemTreeNode definition. |
|-------------------------------------|---|

Since

Version 1.0

Returns

[OTF2_CALLBACK_SUCCESS](#) or [OTF2_CALLBACK_INTERRUPT](#).

J.7.2.9 `typedef OTF2_CallbackCode(* OTF2_DefReaderCallback_
MappingTable)(void *userData, OTF2_MappingType mappingType, const
OTF2_IdMap *idMap)`

Function pointer definition for the callback which is triggered by a [MappingTable](#) definition record.

Mapping tables are needed for situations where an ID is not globally known at measurement time. They are applied automatically at reading.

Parameters

| | |
|--------------------------|---|
| <i>userData</i> | User data as set by OTF2_Reader_RegisterDefCallbacks or OTF2_DefReader_SetCallbacks . |
| <i>mapping- Type</i> | Says to what type of ID the mapping table has to be applied. |
| <i>idMap</i> | Mapping table. |

Since

Version 1.0

Returns

[OTF2_CALLBACK_SUCCESS](#) or [OTF2_CALLBACK_INTERRUPT](#).

J.7 OTF2_DefReaderCallbacks.h File Reference

J.7.2.10 `typedef OTF2_CallbackCode(* OTF2_DefReaderCallback_MetricClass)(void *userData, OTF2_MetricRef self, uint8_t numberOfMetrics, const OTF2_MetricMemberRef *metricMembers, OTF2_MetricOccurrence metricOccurrence, OTF2_RecorderKind recorderKind)`

Function pointer definition for the callback which is triggered by a [MetricClass](#) definition record.

For a metric class it is implicitly given that the event stream that records the metric is also the scope. A metric class can contain multiple different metrics.

Parameters

| | |
|-------------------------|--|
| <i>userData</i> | User data as set by OTF2_Reader_RegisterDefCallbacks or OTF2_DefReader_SetCallbacks . |
| <i>self</i> | The unique identifier for this MetricClass definition. |
| <i>numberOfMetrics</i> | Number of metrics within the set. |
| <i>metricMembers</i> | List of metric members. References a MetricMember definition. |
| <i>metricOccurrence</i> | Defines occurrence of a metric set. |
| <i>recorderKind</i> | What kind of locations will record this metric class, or will this metric class only be recorded by metric instances. Since version 1.2. |

Since

Version 1.0

Returns

[OTF2_CALLBACK_SUCCESS](#) or [OTF2_CALLBACK_INTERRUPT](#).

J.7.2.11 `typedef OTF2_CallbackCode(* OTF2_DefReaderCallback_MetricClassRecorder)(void *userData, OTF2_MetricRef metricClass, OTF2_LocationRef recorder)`

Function pointer definition for the callback which is triggered by a [MetricClassRecorder](#) definition record.

Parameters

| | |
|-----------------|---|
| <i>userData</i> | User data as set by OTF2_Reader_RegisterDefCallbacks or OTF2_DefReader_SetCallbacks . |
|-----------------|---|

APPENDIX J. FILE DOCUMENTATION

| | |
|--------------------|---|
| <i>metricClass</i> | Parent MetricClass definition to which this one is a supplementary definition. References a MetricClass definition. |
| <i>recorder</i> | The location which recorded the referenced metric class. References a Location definition. |

Since

Version 1.2

Returns

[OTF2_CALLBACK_SUCCESS](#) or [OTF2_CALLBACK_INTERRUPT](#).

J.7.2.12 `typedef OTF2_CallbackCode(* OTF2_DefReaderCallback_ -
MetricInstance)(void *userData, OTF2_MetricRef self,
OTF2_MetricRef metricClass, OTF2_LocationRef recorder,
OTF2_MetricScope metricScope, uint64_t scope)`

Function pointer definition for the callback which is triggered by a [MetricInstance](#) definition record.

A metric instance is used to define metrics that are recorded at one location for multiple locations or for another location. The occurrence of a metric instance is implicitly of type [OTF2_METRIC_ASYNCHRONOUS](#).

Parameters

| | |
|---------------------|--|
| <i>userData</i> | User data as set by OTF2_Reader_RegisterDefCallbacks or OTF2_DefReader_SetCallbacks . |
| <i>self</i> | The unique identifier for this MetricClass definition. |
| <i>metricClass</i> | The instanced MetricClass . This metric class must be of kind OTF2_RECORDER_KIND_ABSTRACT . References a MetricClass definition. |
| <i>recorder</i> | Recorder of the metric: location ID. References a Location definition. |
| <i>metric-Scope</i> | Defines type of scope: location, location group, system tree node, or a generic group of locations. |
| <i>scope</i> | Scope of metric: ID of a location, location group, system tree node, or a generic group of locations. |

Since

Version 1.0

Returns

[OTF2_CALLBACK_SUCCESS](#) or [OTF2_CALLBACK_INTERRUPT](#).

J.7 OTF2_DefReaderCallbacks.h File Reference

J.7.2.13 `typedef OTF2_CallbackCode(* OTF2_DefReaderCallback_MetricMember)(void *userData, OTF2_MetricMemberRef self, OTF2_StringRef name, OTF2_StringRef description, OTF2_MetricType metricType, OTF2_MetricMode metricMode, OTF2_Type valueType, OTF2_MetricBase metricBase, int64_t exponent, OTF2_StringRef unit)`

Function pointer definition for the callback which is triggered by a [MetricMember](#) definition record.

A metric is defined by a metric member definition. A metric member is always a member of a metric class. Therefore, a single metric is a special case of a metric class with only one member. It is not allowed to reference a metric member id in a metric event, but only metric class IDs.

Parameters

| | |
|--------------------|---|
| <i>userData</i> | User data as set by OTF2_Reader_RegisterDefCallbacks or OTF2_DefReader_SetCallbacks . |
| <i>self</i> | The unique identifier for this MetricMember definition. |
| <i>name</i> | Name of the metric. References a String definition. |
| <i>description</i> | Description of the metric. References a String definition. |
| <i>metricType</i> | Metric type: PAPI, etc. |
| <i>metricMode</i> | Metric mode: accumulative, fix, relative, etc. |
| <i>valueType</i> | Type of the value: int64_t, uint64_t, or double. |
| <i>metricBase</i> | The recorded values should be handled in this given base, either binary or decimal. This information can be used if the value needs to be scaled. |
| <i>exponent</i> | The values inside the Metric events should be scaled by the factor $\text{base}^{\text{exponent}}$, to get the value in its base unit. For example, if the metric values come in as KiBi, than the base should be OTF2_BASE_BINARY and the exponent 10. Than the writer does not need to scale the values up to bytes, but can directly write the KiBi values into the Metric event. At reading time, the reader can apply the scaling factor to get the value in its base unit, ie. in bytes. |
| <i>unit</i> | Unit of the metric. This needs to be the scale free base unit, ie. "bytes", "operations", or "seconds". In particular this unit should not have any scale prefix. References a String definition. |

Since

Version 1.0

Returns

[OTF2_CALLBACK_SUCCESS](#) or [OTF2_CALLBACK_INTERRUPT](#).

J.7.2.14 `typedef OTF2_CallbackCode(* OTF2_DefReaderCallback_ -
Parameter)(void *userData, OTF2_ParameterRef self, OTF2_StringRef
name, OTF2_ParameterType parameterType)`

Function pointer definition for the callback which is triggered by a [Parameter](#) definition record.

Parameters

| | |
|----------------------------|---|
| <i>userData</i> | User data as set by OTF2_Reader_RegisterDefCallbacks or OTF2_DefReader_SetCallbacks . |
| <i>self</i> | The unique identifier for this Parameter definition. |
| <i>name</i> | Name of the parameter (variable name etc.) References a String definition. |
| <i>parameter- Type</i> | Type of the parameter, OTF2_ParameterType for possible types. |

Since

Version 1.0

Returns

[OTF2_CALLBACK_SUCCESS](#) or [OTF2_CALLBACK_INTERRUPT](#).

J.7.2.15 `typedef OTF2_CallbackCode(* OTF2_DefReaderCallback_ -
Region)(void *userData, OTF2_RegionRef self, OTF2_StringRef
name, OTF2_StringRef canonicalName, OTF2_StringRef description,
OTF2_RegionRole regionRole, OTF2_Paradigm paradigm,
OTF2_RegionFlag regionFlags, OTF2_StringRef sourceFile, uint32_t
beginLineNumber, uint32_t endLineNumber)`

Function pointer definition for the callback which is triggered by a [Region](#) definition record.

Parameters

| | |
|----------------------------|--|
| <i>userData</i> | User data as set by OTF2_Reader_RegisterDefCallbacks or OTF2_DefReader_SetCallbacks . |
| <i>self</i> | The unique identifier for this Region definition. |
| <i>name</i> | Name of the region (demangled name if available). References a String definition. |
| <i>canonical- Name</i> | Alternative name of the region (e.g. mangled name). References a String definition. Since version 1.1. |

J.7 OTF2_DefReaderCallbacks.h File Reference

| | |
|------------------------|---|
| <i>description</i> | A more detailed description of this region. References a String definition. |
| <i>regionRole</i> | Region role. Since version 1.1. |
| <i>paradigm</i> | Paradigm. Since version 1.1. |
| <i>regionFlags</i> | Region flags. Since version 1.1. |
| <i>sourceFile</i> | The source file where this region was declared. References a String definition. |
| <i>beginLineNumber</i> | Starting line number of this region in the source file. |
| <i>endLineNumber</i> | Ending line number of this region in the source file. |

Since

Version 1.0

Returns

[OTF2_CALLBACK_SUCCESS](#) or [OTF2_CALLBACK_INTERRUPT](#).

J.7.2.16 `typedef OTF2_CallbackCode(* OTF2_DefReaderCallback_
RmaWin)(void *userData, OTF2_RmaWinRef self, OTF2_StringRef
name, OTF2_CommRef comm)`

Function pointer definition for the callback which is triggered by a [RmaWin](#) definition record.

A window defines the communication context for any remote-memory access operation.

Parameters

| | |
|-----------------|---|
| <i>userData</i> | User data as set by OTF2_Reader_RegisterDefCallbacks or OTF2_DefReader_SetCallbacks . |
| <i>self</i> | The unique identifier for this RmaWin definition. |
| <i>name</i> | Name, e.g. 'GASPI Queue 1', 'NVidia Card 2', etc.. References a String definition. |
| <i>comm</i> | Communicator object used to create the window. References a Comm definition. |

Since

Version 1.2

Returns

OTF2_CALLBACK_SUCCESS or *OTF2_CALLBACK_INTERRUPT*.

J.7.2.17 `typedef OTF2_CallbackCode(* OTF2_DefReaderCallback_
String)(void *userData, OTF2_StringRef self, const char
*string)`

Function pointer definition for the callback which is triggered by a [String](#) definition record.

Parameters

| | |
|-----------------|---|
| <i>userData</i> | User data as set by OTF2_Reader_RegisterDefCallbacks or OTF2_DefReader_SetCallbacks . |
| <i>self</i> | The unique identifier for this String definition. |
| <i>string</i> | The string, null terminated. |

Since

Version 1.0

Returns

OTF2_CALLBACK_SUCCESS or *OTF2_CALLBACK_INTERRUPT*.

J.7.2.18 `typedef OTF2_CallbackCode(* OTF2_DefReaderCallback_
SystemTreeNode)(void *userData, OTF2_SystemTreeNodeRef
self, OTF2_StringRef name, OTF2_StringRef className,
OTF2_SystemTreeNodeRef parent)`

Function pointer definition for the callback which is triggered by a [SystemTreeNode](#) definition record.

Parameters

| | |
|------------------|---|
| <i>userData</i> | User data as set by OTF2_Reader_RegisterDefCallbacks or OTF2_DefReader_SetCallbacks . |
| <i>self</i> | The unique identifier for this SystemTreeNode definition. |
| <i>name</i> | Free form instance name of this node. References a String definition. |
| <i>className</i> | Free form class name of this node References a String definition. |
| <i>parent</i> | Parent id of this node. May be OTF2_UNDEFINED_SYSTEM_TREE_NODE to indicate that there is no parent. References a SystemTreeNode definition. |

J.7 OTF2_DefReaderCallbacks.h File Reference

Since

Version 1.0

Returns

[OTF2_CALLBACK_SUCCESS](#) or [OTF2_CALLBACK_INTERRUPT](#).

J.7.2.19 `typedef OTF2_CallbackCode(* OTF2_DefReaderCallback_ - SystemTreeNodeDomain)(void *userData, OTF2_SystemTreeNodeRef systemTreeNode, OTF2_SystemTreeDomain systemTreeDomain)`

Function pointer definition for the callback which is triggered by a [SystemTreeNodeDomain](#) definition record.

Parameters

| | |
|-----------------------|---|
| <i>userData</i> | User data as set by OTF2_Reader_RegisterDefCallbacks or OTF2_DefReader_SetCallbacks . |
| <i>systemTreeNode</i> | Parent SystemTreeNode definition to which this one is a supplementary definition. References a SystemTreeNode definition. |

Since

Version 1.2

Returns

[OTF2_CALLBACK_SUCCESS](#) or [OTF2_CALLBACK_INTERRUPT](#).

J.7.2.20 `typedef OTF2_CallbackCode(* OTF2_DefReaderCallback_ - SystemTreeNodeProperty)(void *userData, OTF2_SystemTreeNodeRef systemTreeNode, OTF2_StringRef name, OTF2_StringRef value)`

Function pointer definition for the callback which is triggered by a [SystemTreeNodeProperty](#) definition record.

Parameters

| | |
|-----------------------|---|
| <i>userData</i> | User data as set by OTF2_Reader_RegisterDefCallbacks or OTF2_DefReader_SetCallbacks . |
| <i>systemTreeNode</i> | Parent SystemTreeNode definition to which this one is a supplementary definition. References a SystemTreeNode definition. |

APPENDIX J. FILE DOCUMENTATION

| | |
|--------------|---|
| <i>name</i> | Name of the property. References a String definition. |
| <i>value</i> | Property value. References a String definition. |

Since

Version 1.2

Returns

[OTF2_CALLBACK_SUCCESS](#) or [OTF2_CALLBACK_INTERRUPT](#).

J.7.2.21 `typedef OTF2_CallbackCode(* OTF2_DefReaderCallback_Unknown)(void *userData)`

Function pointer definition for the callback which is triggered for an unknown definition.

Parameters

| | |
|-----------------|---|
| <i>userData</i> | User data as set by OTF2_Reader_RegisterDefCallbacks or OTF2_DefReader_SetCallbacks . |
|-----------------|---|

Returns

[OTF2_CALLBACK_SUCCESS](#) or [OTF2_CALLBACK_INTERRUPT](#).

J.7.3 Function Documentation

J.7.3.1 `void OTF2_DefReaderCallbacks.Clear (OTF2_DefReaderCallbacks * defReaderCallbacks)`

Clears a struct for the definition callbacks.

Parameters

| | |
|----------------------------|--|
| <i>defReader-Callbacks</i> | Handle to a struct previously allocated with OTF2_DefReaderCallbacks_New . |
|----------------------------|--|

J.7.3.2 `void OTF2_DefReaderCallbacks.Delete (OTF2_DefReaderCallbacks * defReaderCallbacks)`

Deallocates a struct for the definition callbacks.

J.7 OTF2_DefReaderCallbacks.h File Reference

Parameters

| | |
|----------------------------|--|
| <i>defReader-Callbacks</i> | Handle to a struct previously allocated with OTF2_DefReaderCallbacks_New . |
|----------------------------|--|

J.7.3.3 OTF2_DefReaderCallbacks* OTF2_DefReaderCallbacks.New (void)

Allocates a new struct for the definition callbacks.

Returns

A newly allocated struct of type [OTF2_DefReaderCallbacks](#).

J.7.3.4 OTF2_ErrorCode OTF2_DefReaderCallbacks.SetAttributeCallback (OTF2_DefReaderCallbacks * defReaderCallbacks, OTF2_DefReaderCallback_Attribute attributeCallback)

Registers the callback for the [Attribute](#) definition.

Parameters

| | |
|----------------------------|--|
| <i>defReader-Callbacks</i> | Struct for all callbacks. |
| <i>attribute-Callback</i> | Function which should be called for all Attribute definitions. |

Returns

[OTF2_SUCCESS](#) if successful

[OTF2_ERROR_INVALID_ARGUMENT](#) for an invalid `defReaderCallbacks` argument

J.7.3.5 OTF2_ErrorCode OTF2_DefReaderCallbacks.SetCallpathCallback (OTF2_DefReaderCallbacks * defReaderCallbacks, OTF2_DefReaderCallback_Callpath callpathCallback)

Registers the callback for the [Callpath](#) definition.

Parameters

| | |
|----------------------------|---------------------------|
| <i>defReader-Callbacks</i> | Struct for all callbacks. |
|----------------------------|---------------------------|

APPENDIX J. FILE DOCUMENTATION

| | |
|--------------------------|---|
| <i>callpath-Callback</i> | Function which should be called for all Callpath definitions. |
|--------------------------|---|

Returns

[OTF2_SUCCESS](#) if successful

[OTF2_ERROR_INVALID_ARGUMENT](#) for an invalid `defReaderCallbacks` argument

J.7.3.6 `OTF2_ErrorCode OTF2_DefReaderCallbacks_SetCallsiteCallback (OTF2_DefReaderCallbacks * defReaderCallbacks, OTF2_DefReaderCallback_Callsite callsiteCallback)`

Registers the callback for the [Callsite](#) definition.

Parameters

| | |
|----------------------------|---|
| <i>defReader-Callbacks</i> | Struct for all callbacks. |
| <i>callsite-Callback</i> | Function which should be called for all Callsite definitions. |

Returns

[OTF2_SUCCESS](#) if successful

[OTF2_ERROR_INVALID_ARGUMENT](#) for an invalid `defReaderCallbacks` argument

J.7.3.7 `OTF2_ErrorCode OTF2_DefReaderCallbacks_SetClockOffsetCallback (OTF2_DefReaderCallbacks * defReaderCallbacks, OTF2_DefReaderCallback_ClockOffset clockOffsetCallback)`

Registers the callback for the [ClockOffset](#) definition.

Parameters

| | |
|-----------------------------|--|
| <i>defReader-Callbacks</i> | Struct for all callbacks. |
| <i>clockOffset-Callback</i> | Function which should be called for all ClockOffset definitions. |

J.7 OTF2_DefReaderCallbacks.h File Reference

Returns

OTF2_SUCCESS if successful

OTF2_ERROR_INVALID_ARGUMENT for an invalid `defReaderCallbacks` argument

J.7.3.8 OTF2_ErrorCode OTF2_DefReaderCallbacks_SetCommCallback (OTF2_DefReaderCallbacks * *defReaderCallbacks*, OTF2_DefReaderCallback_Comm *commCallback*)

Registers the callback for the `Comm` definition.

Parameters

| | |
|----------------------------|--|
| <i>defReader-Callbacks</i> | Struct for all callbacks. |
| <i>commCallback</i> | Function which should be called for all <code>Comm</code> definitions. |

Returns

OTF2_SUCCESS if successful

OTF2_ERROR_INVALID_ARGUMENT for an invalid `defReaderCallbacks` argument

J.7.3.9 OTF2_ErrorCode OTF2_DefReaderCallbacks_SetGroupCallback (OTF2_DefReaderCallbacks * *defReaderCallbacks*, OTF2_DefReaderCallback_Group *groupCallback*)

Registers the callback for the `Group` definition.

Parameters

| | |
|----------------------------|---|
| <i>defReader-Callbacks</i> | Struct for all callbacks. |
| <i>groupCallback</i> | Function which should be called for all <code>Group</code> definitions. |

Returns

OTF2_SUCCESS if successful

OTF2_ERROR_INVALID_ARGUMENT for an invalid `defReaderCallbacks` argument

APPENDIX J. FILE DOCUMENTATION

J.7.3.10 **OTF2_StatusCode** **OTF2_DefReaderCallbacks_SetLocationCallback**
(**OTF2_DefReaderCallbacks** * *defReaderCallbacks*,
OTF2_DefReaderCallback_Location *locationCallback*)

Registers the callback for the [Location](#) definition.

Parameters

| | |
|----------------------------|---|
| <i>defReader-Callbacks</i> | Struct for all callbacks. |
| <i>location-Callback</i> | Function which should be called for all Location definitions. |

Returns

[OTF2_SUCCESS](#) if successful

[OTF2_ERROR_INVALID_ARGUMENT](#) for an invalid *defReaderCallbacks* argument

J.7.3.11 **OTF2_StatusCode** **OTF2_DefReaderCallbacks_SetLocationGroupCallback**
(**OTF2_DefReaderCallbacks** * *defReaderCallbacks*,
OTF2_DefReaderCallback_LocationGroup *locationGroupCallback*)

Registers the callback for the [LocationGroup](#) definition.

Parameters

| | |
|-------------------------------|--|
| <i>defReader-Callbacks</i> | Struct for all callbacks. |
| <i>location-GroupCallback</i> | Function which should be called for all LocationGroup definitions. |

Returns

[OTF2_SUCCESS](#) if successful

[OTF2_ERROR_INVALID_ARGUMENT](#) for an invalid *defReaderCallbacks* argument

J.7 OTF2_DefReaderCallbacks.h File Reference

J.7.3.12 `OTF2_ErrorCode OTF2_DefReaderCallbacks_SetMappingTableCallback (OTF2_DefReaderCallbacks * defReaderCallbacks, OTF2_DefReaderCallback_MappingTable mappingTableCallback)`

Registers the callback for the [MappingTable](#) definition.

Parameters

| | |
|-------------------------------|---|
| <i>defReader-Callbacks</i> | Struct for all callbacks. |
| <i>map-pingTable-Callback</i> | Function which should be called for all MappingTable definitions. |

Returns

[OTF2_SUCCESS](#) if successful

[OTF2_ERROR_INVALID_ARGUMENT](#) for an invalid `defReaderCallbacks` argument

J.7.3.13 `OTF2_ErrorCode OTF2_DefReaderCallbacks_SetMetricClassCallback (OTF2_DefReaderCallbacks * defReaderCallbacks, OTF2_DefReaderCallback_MetricClass metricClassCallback)`

Registers the callback for the [MetricClass](#) definition.

Parameters

| | |
|------------------------------|--|
| <i>defReader-Callbacks</i> | Struct for all callbacks. |
| <i>metric-ClassCall-back</i> | Function which should be called for all MetricClass definitions. |

Returns

[OTF2_SUCCESS](#) if successful

[OTF2_ERROR_INVALID_ARGUMENT](#) for an invalid `defReaderCallbacks` argument

APPENDIX J. FILE DOCUMENTATION

J.7.3.14 `OTF2_ErrorCode OTF2_DefReaderCallbacks_SetMetricClassRecorderCallback (OTF2_DefReaderCallbacks * defReaderCallbacks, OTF2_DefReaderCallback_MetricClassRecorder metricClassRecorderCallback)`

Registers the callback for the [MetricClassRecorder](#) definition.

Parameters

| | |
|---------------------------------------|--|
| <i>defReader-Callbacks</i> | Struct for all callbacks. |
| <i>metric-Class-Recorder-Callback</i> | Function which should be called for all MetricClassRecorder definitions. |

Returns

[OTF2_SUCCESS](#) if successful

[OTF2_ERROR_INVALID_ARGUMENT](#) for an invalid `defReaderCallbacks` argument

J.7.3.15 `OTF2_ErrorCode OTF2_DefReaderCallbacks_SetMetricInstanceCallback (OTF2_DefReaderCallbacks * defReaderCallbacks, OTF2_DefReaderCallback_MetricInstance metricInstanceCallback)`

Registers the callback for the [MetricInstance](#) definition.

Parameters

| | |
|-------------------------------|---|
| <i>defReader-Callbacks</i> | Struct for all callbacks. |
| <i>metricInstanceCallback</i> | Function which should be called for all MetricInstance definitions. |

Returns

[OTF2_SUCCESS](#) if successful

[OTF2_ERROR_INVALID_ARGUMENT](#) for an invalid `defReaderCallbacks` argument

J.7 OTF2_DefReaderCallbacks.h File Reference

J.7.3.16 `OTF2_ErrorCode OTF2_DefReaderCallbacks_SetMetricMemberCallback (OTF2_DefReaderCallbacks * defReaderCallbacks, OTF2_DefReaderCallback_MetricMember metricMemberCallback)`

Registers the callback for the [MetricMember](#) definition.

Parameters

| | |
|-----------------------------|---|
| <i>defReader-Callbacks</i> | Struct for all callbacks. |
| <i>metricMemberCallback</i> | Function which should be called for all MetricMember definitions. |

Returns

[OTF2_SUCCESS](#) if successful
[OTF2_ERROR_INVALID_ARGUMENT](#) for an invalid `defReaderCallbacks` argument

J.7.3.17 `OTF2_ErrorCode OTF2_DefReaderCallbacks_SetParameterCallback (OTF2_DefReaderCallbacks * defReaderCallbacks, OTF2_DefReaderCallback_Parameter parameterCallback)`

Registers the callback for the [Parameter](#) definition.

Parameters

| | |
|----------------------------|--|
| <i>defReader-Callbacks</i> | Struct for all callbacks. |
| <i>parameterCallback</i> | Function which should be called for all Parameter definitions. |

Returns

[OTF2_SUCCESS](#) if successful
[OTF2_ERROR_INVALID_ARGUMENT](#) for an invalid `defReaderCallbacks` argument

J.7.3.18 `OTF2_ErrorCode OTF2_DefReaderCallbacks_SetRegionCallback (OTF2_DefReaderCallbacks * defReaderCallbacks, OTF2_DefReaderCallback_Region regionCallback)`

Registers the callback for the [Region](#) definition.

APPENDIX J. FILE DOCUMENTATION

Parameters

| | |
|---------------------------|---|
| <i>defReaderCallbacks</i> | Struct for all callbacks. |
| <i>regionCallback</i> | Function which should be called for all Region definitions. |

Returns

[OTF2_SUCCESS](#) if successful

[OTF2_ERROR_INVALID_ARGUMENT](#) for an invalid `defReaderCallbacks` argument

J.7.3.19 `OTF2_StatusCode OTF2_DefReaderCallbacks_SetRmaWinCallback (OTF2_DefReaderCallbacks * defReaderCallbacks, OTF2_DefReaderCallback_RmaWin rmaWinCallback)`

Registers the callback for the [RmaWin](#) definition.

Parameters

| | |
|---------------------------|---|
| <i>defReaderCallbacks</i> | Struct for all callbacks. |
| <i>rmaWinCallback</i> | Function which should be called for all RmaWin definitions. |

Returns

[OTF2_SUCCESS](#) if successful

[OTF2_ERROR_INVALID_ARGUMENT](#) for an invalid `defReaderCallbacks` argument

J.7.3.20 `OTF2_StatusCode OTF2_DefReaderCallbacks_SetStringCallback (OTF2_DefReaderCallbacks * defReaderCallbacks, OTF2_DefReaderCallback_String stringCallback)`

Registers the callback for the [String](#) definition.

Parameters

| | |
|---------------------------|---|
| <i>defReaderCallbacks</i> | Struct for all callbacks. |
| <i>stringCallback</i> | Function which should be called for all String definitions. |

J.7 OTF2_DefReaderCallbacks.h File Reference

Returns

OTF2_SUCCESS if successful

OTF2_ERROR_INVALID_ARGUMENT for an invalid `defReaderCallbacks` argument

J.7.3.21 **OTF2_ErrorCode** `OTF2_DefReaderCallbacks_SetSystemTreeNodeCallback`
(**OTF2_DefReaderCallbacks** * *defReaderCallbacks*,
OTF2_DefReaderCallback_SystemTreeNode *systemTreeNodeCallback*)

Registers the callback for the [SystemTreeNode](#) definition.

Parameters

| | |
|-------------------------------|---|
| <i>defReader-Callbacks</i> | Struct for all callbacks. |
| <i>systemTreeNodeCallback</i> | Function which should be called for all SystemTreeNode definitions. |

Returns

OTF2_SUCCESS if successful

OTF2_ERROR_INVALID_ARGUMENT for an invalid `defReaderCallbacks` argument

J.7.3.22 **OTF2_ErrorCode** `OTF2_DefReaderCallbacks_SetSystemTreeNodeDomainCallback`
(**OTF2_DefReaderCallbacks**
* *defReaderCallbacks*, **OTF2_DefReaderCallback_SystemTreeNodeDomain** *systemTreeNodeDomainCallback*
)

Registers the callback for the [SystemTreeNodeDomain](#) definition.

Parameters

| | |
|-------------------------------------|---|
| <i>defReader-Callbacks</i> | Struct for all callbacks. |
| <i>systemTreeNodeDomainCallback</i> | Function which should be called for all SystemTreeNodeDomain definitions. |

APPENDIX J. FILE DOCUMENTATION

Returns

OTF2_SUCCESS if successful

OTF2_ERROR_INVALID_ARGUMENT for an invalid `defReaderCallbacks` argument

J.7.3.23 **OTF2_ErrorCode** **OTF2_DefReaderCallbacks_**
SetSystemTreeNodePropertyCallback (**OTF2_DefReaderCallbacks**
*** *defReaderCallbacks***, **OTF2_DefReaderCallback_**
SystemTreeNodeProperty ***systemTreeNodePropertyCallback***
)

Registers the callback for the `SystemTreeNodeProperty` definition.

Parameters

| | |
|---|--|
| <i>defReader- Callbacks</i> | Struct for all callbacks. |
| <i>sys- temTreeN- odeProper- tyCallback</i> | Function which should be called for all <code>SystemTreeNodeProperty</code> definitions. |

Returns

OTF2_SUCCESS if successful

OTF2_ERROR_INVALID_ARGUMENT for an invalid `defReaderCallbacks` argument

J.7.3.24 **OTF2_ErrorCode** **OTF2_DefReaderCallbacks_**
SetUnknownCallback
(**OTF2_DefReaderCallbacks** * ***defReaderCallbacks***,
OTF2_DefReaderCallback_Unknown ***unknownCallback***)

Registers the callback for an unknown definition.

Parameters

| | |
|---------------------------------|--|
| <i>defReader- Callbacks</i> | Struct for all callbacks. |
| <i>unknown- Callback</i> | Function which should be called for all unknown definitions. |

J.8 OTF2_DefWriter.h File Reference

Returns

OTF2_SUCCESS if successful

OTF2_ERROR_INVALID_ARGUMENT for an invalid defReaderCallbacks argument

J.8 OTF2_DefWriter.h File Reference

This file provides all routines that write definition records of a single location.

```
#include <stdint.h>
#include <otf2/OTF2_ErrorCodes.h>
#include <otf2/OTF2_Definitions.h>
#include <otf2/OTF2_IdMap.h>
```

Typedefs

- typedef struct OTF2_DefWriter_struct **OTF2_DefWriter**
Handle definition for the external definition writer.

Functions

- **OTF2_ErrorCode OTF2_DefWriter_GetLocationID** (const **OTF2_DefWriter** *writer, **OTF2_LocationRef** *location)
Returns the location ID of the location which is related to the writer object.
- **OTF2_ErrorCode OTF2_DefWriter_WriteAttribute** (**OTF2_DefWriter** *writer, **OTF2_AttributeRef** self, **OTF2_StringRef** name, **OTF2_Type** type)
Writes a Attribute definition record into the DefWriter.
- **OTF2_ErrorCode OTF2_DefWriter_WriteCallpath** (**OTF2_DefWriter** *writer, **OTF2_CallpathRef** self, **OTF2_CallpathRef** parent, **OTF2_RegionRef** region)
Writes a Callpath definition record into the DefWriter.
- **OTF2_ErrorCode OTF2_DefWriter_WriteCallsite** (**OTF2_DefWriter** *writer, **OTF2_CallsiteRef** self, **OTF2_StringRef** sourceFile, **uint32_t** lineNumber, **OTF2_RegionRef** enteredRegion, **OTF2_RegionRef** leftRegion)
Writes a Callsite definition record into the DefWriter.

APPENDIX J. FILE DOCUMENTATION

- [OTF2_ErrorCode](#) [OTF2_DefWriter_WriteClockOffset](#) ([OTF2_DefWriter](#) *writer, [OTF2_TimeStamp](#) time, [int64_t](#) offset, double standardDeviation)

Writes a ClockOffset definition record into the DefWriter.

- [OTF2_ErrorCode](#) [OTF2_DefWriter_WriteComm](#) ([OTF2_DefWriter](#) *writer, [OTF2_CommRef](#) self, [OTF2_StringRef](#) name, [OTF2_GroupRef](#) group, [OTF2_CommRef](#) parent)

Writes a Comm definition record into the DefWriter.

- [OTF2_ErrorCode](#) [OTF2_DefWriter_WriteGroup](#) ([OTF2_DefWriter](#) *writer, [OTF2_GroupRef](#) self, [OTF2_StringRef](#) name, [OTF2_GroupType](#) groupType, [OTF2_Paradigm](#) paradigm, [OTF2_GroupFlag](#) groupFlags, [uint32_t](#) numberOfMembers, [const uint64_t](#) *members)

Writes a Group definition record into the DefWriter.

- [OTF2_ErrorCode](#) [OTF2_DefWriter_WriteLocation](#) ([OTF2_DefWriter](#) *writer, [OTF2_LocationRef](#) self, [OTF2_StringRef](#) name, [OTF2_LocationType](#) locationType, [uint64_t](#) numberOfEvents, [OTF2_LocationGroupRef](#) locationGroup)

Writes a Location definition record into the DefWriter.

- [OTF2_ErrorCode](#) [OTF2_DefWriter_WriteLocationGroup](#) ([OTF2_DefWriter](#) *writer, [OTF2_LocationGroupRef](#) self, [OTF2_StringRef](#) name, [OTF2_LocationGroupType](#) locationGroupType, [OTF2_SystemTreeNodeRef](#) systemTreeParent)

Writes a LocationGroup definition record into the DefWriter.

- [OTF2_ErrorCode](#) [OTF2_DefWriter_WriteMappingTable](#) ([OTF2_DefWriter](#) *writer, [OTF2_MappingType](#) mappingType, [const OTF2_IdMap](#) *idMap)

Writes a MappingTable definition record into the DefWriter.

- [OTF2_ErrorCode](#) [OTF2_DefWriter_WriteMetricClass](#) ([OTF2_DefWriter](#) *writer, [OTF2_MetricRef](#) self, [uint8_t](#) numberOfMetrics, [const OTF2_MetricMemberRef](#) *metricMembers, [OTF2_MetricOccurrence](#) metricOccurrence, [OTF2_RecorderKind](#) recorderKind)

Writes a MetricClass definition record into the DefWriter.

- [OTF2_ErrorCode](#) [OTF2_DefWriter_WriteMetricClassRecorder](#) ([OTF2_DefWriter](#) *writer, [OTF2_MetricRef](#) metricClass, [OTF2_LocationRef](#) recorder)

Writes a MetricClassRecorder definition record into the DefWriter.

J.8 OTF2_DefWriter.h File Reference

- [OTF2_ErrorCode](#) [OTF2_DefWriter_WriteMetricInstance](#) ([OTF2_DefWriter](#) *writer, [OTF2_MetricRef](#) self, [OTF2_MetricRef](#) metricClass, [OTF2_LocationRef](#) recorder, [OTF2_MetricScope](#) metricScope, [uint64_t](#) scope)
Writes a MetricInstance definition record into the DefWriter.
- [OTF2_ErrorCode](#) [OTF2_DefWriter_WriteMetricMember](#) ([OTF2_DefWriter](#) *writer, [OTF2_MetricMemberRef](#) self, [OTF2_StringRef](#) name, [OTF2_StringRef](#) description, [OTF2_MetricType](#) metricType, [OTF2_MetricMode](#) metricMode, [OTF2_Type](#) valueType, [OTF2_MetricBase](#) metricBase, [int64_t](#) exponent, [OTF2_StringRef](#) unit)
Writes a MetricMember definition record into the DefWriter.
- [OTF2_ErrorCode](#) [OTF2_DefWriter_WriteParameter](#) ([OTF2_DefWriter](#) *writer, [OTF2_ParameterRef](#) self, [OTF2_StringRef](#) name, [OTF2_ParameterType](#) parameterType)
Writes a Parameter definition record into the DefWriter.
- [OTF2_ErrorCode](#) [OTF2_DefWriter_WriteRegion](#) ([OTF2_DefWriter](#) *writer, [OTF2_RegionRef](#) self, [OTF2_StringRef](#) name, [OTF2_StringRef](#) canonicalName, [OTF2_StringRef](#) description, [OTF2_RegionRole](#) regionRole, [OTF2_Paradigm](#) paradigm, [OTF2_RegionFlag](#) regionFlags, [OTF2_StringRef](#) sourceFile, [uint32_t](#) beginLineNumber, [uint32_t](#) endLineNumber)
Writes a Region definition record into the DefWriter.
- [OTF2_ErrorCode](#) [OTF2_DefWriter_WriteRmaWin](#) ([OTF2_DefWriter](#) *writer, [OTF2_RmaWinRef](#) self, [OTF2_StringRef](#) name, [OTF2_CommRef](#) comm)
Writes a RmaWin definition record into the DefWriter.
- [OTF2_ErrorCode](#) [OTF2_DefWriter_WriteString](#) ([OTF2_DefWriter](#) *writer, [OTF2_StringRef](#) self, [const char](#) *string)
Writes a String definition record into the DefWriter.
- [OTF2_ErrorCode](#) [OTF2_DefWriter_WriteSystemTreeNode](#) ([OTF2_DefWriter](#) *writer, [OTF2_SystemTreeNodeRef](#) self, [OTF2_StringRef](#) name, [OTF2_StringRef](#) className, [OTF2_SystemTreeNodeRef](#) parent)
Writes a SystemTreeNode definition record into the DefWriter.
- [OTF2_ErrorCode](#) [OTF2_DefWriter_WriteSystemTreeNodeDomain](#) ([OTF2_DefWriter](#) *writer, [OTF2_SystemTreeNodeRef](#) systemTreeNode, [OTF2_SystemTreeDomain](#) systemTreeDomain)
Writes a SystemTreeNodeDomain definition record into the DefWriter.

APPENDIX J. FILE DOCUMENTATION

- [OTF2_ErrorCode](#) [OTF2_DefWriter_WriteSystemTreeNodeProperty](#) ([OTF2_DefWriter](#) *writer, [OTF2_SystemTreeNodeRef](#) systemTreeNode, [OTF2_StringRef](#) name, [OTF2_StringRef](#) value)

Writes a SystemTreeNodeProperty definition record into the DefWriter.

J.8.1 Detailed Description

This file provides all routines that write definition records of a single location.

Source Template:

templates/OTF2_DefWriter.templ.h

J.8.2 Function Documentation

- J.8.2.1** [OTF2_ErrorCode](#) [OTF2_DefWriter_GetLocationID](#) ([const](#) [OTF2_DefWriter](#) * writer, [OTF2_LocationRef](#) * location)

Returns the location ID of the location which is related to the writer object.

Parameters

| | |
|-----------------|----------------------------|
| <i>writer</i> | Writer object. |
| <i>location</i> | Return location reference. |

Returns

[OTF2_SUCCESS](#) if successful, an error code if an error occurs.

- J.8.2.2** [OTF2_ErrorCode](#) [OTF2_DefWriter_WriteAttribute](#) ([OTF2_DefWriter](#) * writer, [OTF2_AttributeRef](#) self, [OTF2_StringRef](#) name, [OTF2_Type](#) type)

Writes a Attribute definition record into the DefWriter.

Parameters

| | |
|---------------|--|
| <i>writer</i> | Writer object. |
| <i>self</i> | The unique identifier for this Attribute definition. |
| <i>name</i> | Name of the attribute. References a String definition. |
| <i>type</i> | Type of the attribute value. |

J.8 OTF2_DefWriter.h File Reference

Since

Version 1.0

Returns

[OTF2_SUCCESS](#) if successful, an error code if an error occurs.

J.8.2.3 **OTF2_ErrorCode** **OTF2_DefWriter_WriteCallpath** (**OTF2_DefWriter** * *writer*, **OTF2_CallpathRef** *self*, **OTF2_CallpathRef** *parent*, **OTF2_RegionRef** *region*)

Writes a Callpath definition record into the DefWriter.

Parameters

| | |
|---------------|---|
| <i>writer</i> | Writer object. |
| <i>self</i> | The unique identifier for this Callpath definition. |
| <i>parent</i> | References a Callpath definition. |
| <i>region</i> | References a Region definition. |

Since

Version 1.0

Returns

[OTF2_SUCCESS](#) if successful, an error code if an error occurs.

J.8.2.4 **OTF2_ErrorCode** **OTF2_DefWriter_WriteCallsite** (**OTF2_DefWriter** * *writer*, **OTF2_CallsiteRef** *self*, **OTF2_StringRef** *sourceFile*, **uint32_t** *lineNumber*, **OTF2_RegionRef** *enteredRegion*, **OTF2_RegionRef** *leftRegion*)

Writes a Callsite definition record into the DefWriter.

Parameters

| | |
|----------------------|---|
| <i>writer</i> | Writer object. |
| <i>self</i> | The unique identifier for this Callsite definition. |
| <i>sourceFile</i> | The source file where this call was made. References a String definition. |
| <i>lineNumber</i> | Line number in the source file where this call was made. |
| <i>enteredRegion</i> | The region which was called. References a Region definition. |
| <i>leftRegion</i> | The region which made the call. References a Region definition. |

Since

Version 1.0

Returns

[OTF2_SUCCESS](#) if successful, an error code if an error occurs.

J.8.2.5 `OTF2_ErrorCode OTF2_DefWriter_WriteClockOffset (OTF2_DefWriter * writer, OTF2_TimeStamp time, int64_t offset, double standardDeviation)`

Writes a ClockOffset definition record into the DefWriter.

Clock offsets are used for clock corrections.

Parameters

| | |
|---------------------------|---|
| <i>writer</i> | Writer object. |
| <i>time</i> | Time when this offset was determined. |
| <i>offset</i> | The offset to the global clock which was determined at <i>time</i> . |
| <i>standard-Deviation</i> | A possible standard deviation, which can be used as a metric for the quality of the offset. |

Since

Version 1.0

Returns

[OTF2_SUCCESS](#) if successful, an error code if an error occurs.

J.8.2.6 `OTF2_ErrorCode OTF2_DefWriter_WriteComm (OTF2_DefWriter * writer, OTF2_CommRef self, OTF2_StringRef name, OTF2_GroupRef group, OTF2_CommRef parent)`

Writes a Comm definition record into the DefWriter.

Parameters

| | |
|---------------|--|
| <i>writer</i> | Writer object. |
| <i>self</i> | The unique identifier for this Comm definition. |
| <i>name</i> | The name given by calling <code>MPI_Comm_set_name</code> on this communicator. Or the empty name to indicate that no name was given. References a String definition. |

J.8 OTF2_DefWriter.h File Reference

| | |
|---------------|---|
| <i>group</i> | The describing MPI group of this MPI communicator The group needs to be of type <i>OTF2_GROUP_TYPE_MPI_GROUP</i> or <i>OTF2_GROUP_TYPE_MPI_COMM_SELF</i> . References a Group definition. |
| <i>parent</i> | The parent MPI communicator from which this communicator was created, if any. Use <i>OTF2_UNDEFINED_COMM</i> to indicate no parent. References a Comm definition. |

Since

Version 1.0

Returns

OTF2_SUCCESS if successful, an error code if an error occurs.

J.8.2.7 OTF2_ErrorCode OTF2_DefWriter_WriteGroup (OTF2_DefWriter * *writer*, OTF2_GroupRef *self*, OTF2_StringRef *name*, OTF2_GroupType *groupType*, OTF2_Paradigm *paradigm*, OTF2_GroupFlag *groupFlags*, uint32_t *numberOfMembers*, const uint64_t * *members*)

Writes a Group definition record into the DefWriter.

Parameters

| | |
|------------------------|--|
| <i>writer</i> | Writer object. |
| <i>self</i> | The unique identifier for this Group definition. |
| <i>name</i> | Name of this group References a String definition. |
| <i>groupType</i> | The type of this group. Since version 1.2. |
| <i>paradigm</i> | The paradigm of this communication group. Since version 1.2. |
| <i>groupFlags</i> | Flags for this group. Since version 1.2. |
| <i>numberOfMembers</i> | The number of members in this group. |
| <i>members</i> | The identifiers of the group members. |

Since

Version 1.0

Returns

OTF2_SUCCESS if successful, an error code if an error occurs.

APPENDIX J. FILE DOCUMENTATION

J.8.2.8 **OTF2_ErrorCode** **OTF2.DefWriter_WriteLocation** (**OTF2_DefWriter**
* *writer*, **OTF2_LocationRef** *self*, **OTF2_StringRef** *name*,
OTF2_LocationType *locationType*, **uint64.t** *numberOfEvents*,
OTF2_LocationGroupRef *locationGroup*)

Writes a Location definition record into the DefWriter.

Parameters

| | |
|-----------------------------|--|
| <i>writer</i> | Writer object. |
| <i>self</i> | The unique identifier for this Location definition. |
| <i>name</i> | Name of the location References a String definition. |
| <i>location- Type</i> | Location type. |
| <i>numberO- fEvents</i> | Number of events this location has recorded. |
| <i>location- Group</i> | Location group which includes this location. References a Location-Group definition. |

Since

Version 1.0

Returns

[OTF2_SUCCESS](#) if successful, an error code if an error occurs.

J.8.2.9 **OTF2_ErrorCode** **OTF2.DefWriter_WriteLocationGroup** (**OTF2_DefWriter**
* *writer*, **OTF2_LocationGroupRef** *self*, **OTF2_StringRef**
name, **OTF2_LocationGroupType** *locationGroupType*,
OTF2_SystemTreeNodeRef *systemTreeParent*)

Writes a LocationGroup definition record into the DefWriter.

Parameters

| | |
|-------------------------------------|--|
| <i>writer</i> | Writer object. |
| <i>self</i> | The unique identifier for this LocationGroup definition. |
| <i>name</i> | Name of the group. References a String definition. |
| <i>location- GroupType</i> | Type of this group. |
| <i>sys- temTreePar- ent</i> | Parent of this location group in the system tree. References a Sys-temTreeNode definition. |

J.8 OTF2_DefWriter.h File Reference

Since

Version 1.0

Returns

[*OTF2_SUCCESS*](#) if successful, an error code if an error occurs.

J.8.2.10 `OTF2_StatusCode OTF2_DefWriter_WriteMappingTable (OTF2_DefWriter * writer, OTF2_MappingType mappingType, const OTF2_IdMap * idMap)`

Writes a MappingTable definition record into the DefWriter.

Mapping tables are needed for situations where an ID is not globally known at measurement time. They are applied automatically at reading.

Parameters

| | |
|---------------------|--|
| <i>writer</i> | Writer object. |
| <i>mapping-Type</i> | Says to what type of ID the mapping table has to be applied. |
| <i>idMap</i> | Mapping table. |

Since

Version 1.0

Returns

[*OTF2_SUCCESS*](#) if successful, an error code if an error occurs.

J.8.2.11 `OTF2_StatusCode OTF2_DefWriter_WriteMetricClass (OTF2_DefWriter * writer, OTF2_MetricRef self, uint8_t numberOfMetrics, const OTF2_MetricMemberRef * metricMembers, OTF2_MetricOccurrence metricOccurrence, OTF2_RecorderKind recorderKind)`

Writes a MetricClass definition record into the DefWriter.

For a metric class it is implicitly given that the event stream that records the metric is also the scope. A metric class can contain multiple different metrics.

Parameters

| | |
|---------------|----------------|
| <i>writer</i> | Writer object. |
|---------------|----------------|

APPENDIX J. FILE DOCUMENTATION

| | |
|-------------------------|--|
| <i>self</i> | The unique identifier for this MetricClass definition. |
| <i>numberOfMetrics</i> | Number of metrics within the set. |
| <i>metricMembers</i> | List of metric members. References a MetricMember definition. |
| <i>metricOccurrence</i> | Defines occurrence of a metric set. |
| <i>recorderKind</i> | What kind of locations will record this metric class, or will this metric class only be recorded by metric instances. Since version 1.2. |

Since

Version 1.0

Returns

[OTF2_SUCCESS](#) if successful, an error code if an error occurs.

J.8.2.12 [OTF2_ErrorCode](#) [OTF2_DefWriter_WriteMetricClassRecorder](#)
([OTF2_DefWriter](#) * *writer*, [OTF2_MetricRef](#) *metricClass*,
[OTF2_LocationRef](#) *recorder*)

Writes a MetricClassRecorder definition record into the DefWriter.

Parameters

| | |
|--------------------|---|
| <i>writer</i> | Writer object. |
| <i>metricClass</i> | Parent MetricClass definition to which this one is a supplementary definition. References a MetricClass definition. |
| <i>recorder</i> | The location which recorded the referenced metric class. References a Location definition. |

Since

Version 1.2

Returns

[OTF2_SUCCESS](#) if successful, an error code if an error occurs.

J.8 OTF2_DefWriter.h File Reference

J.8.2.13 `OTF2_ErrorCode OTF2_DefWriter_WriteMetricInstance (OTF2_DefWriter * writer, OTF2_MetricRef self, OTF2_MetricRef metricClass, OTF2_LocationRef recorder, OTF2_MetricScope metricScope, uint64_t scope)`

Writes a MetricInstance definition record into the DefWriter.

A metric instance is used to define metrics that are recorded at one location for multiple locations or for another location. The occurrence of a metric instance is implicitly of type [OTF2_METRIC_ASYNCHRONOUS](#).

Parameters

| | |
|--------------------------|--|
| <i>writer</i> | Writer object. |
| <i>self</i> | The unique identifier for this MetricClass definition. |
| <i>metricClass</i> | The instanced MetricClass . This metric class must be of kind OTF2_RECORDER_KIND_ABSTRACT . References a MetricClass definition. |
| <i>recorder</i> | Recorder of the metric: location ID. References a Location definition. |
| <i>metric- Scope</i> | Defines type of scope: location, location group, system tree node, or a generic group of locations. |
| <i>scope</i> | Scope of metric: ID of a location, location group, system tree node, or a generic group of locations. |

Since

Version 1.0

Returns

[OTF2_SUCCESS](#) if successful, an error code if an error occurs.

J.8.2.14 `OTF2_ErrorCode OTF2_DefWriter_WriteMetricMember (OTF2_DefWriter * writer, OTF2_MetricMemberRef self, OTF2_StringRef name, OTF2_StringRef description, OTF2_MetricType metricType, OTF2_MetricMode metricMode, OTF2_Type valueType, OTF2_MetricBase metricBase, int64_t exponent, OTF2_StringRef unit)`

Writes a MetricMember definition record into the DefWriter.

A metric is defined by a metric member definition. A metric member is always a member of a metric class. Therefore, a single metric is a special case of a metric class with only one member. It is not allowed to reference a metric member id in a metric event, but only metric class IDs.

Parameters

APPENDIX J. FILE DOCUMENTATION

| | |
|--------------------|---|
| <i>writer</i> | Writer object. |
| <i>self</i> | The unique identifier for this MetricMember definition. |
| <i>name</i> | Name of the metric. References a String definition. |
| <i>description</i> | Description of the metric. References a String definition. |
| <i>metricType</i> | Metric type: PAPI, etc. |
| <i>metricMode</i> | Metric mode: accumulative, fix, relative, etc. |
| <i>valueType</i> | Type of the value: int64_t, uint64_t, or double. |
| <i>metricBase</i> | The recorded values should be handled in this given base, either binary or decimal. This information can be used if the value needs to be scaled. |
| <i>exponent</i> | The values inside the Metric events should be scaled by the factor $base^{exponent}$, to get the value in its base unit. For example, if the metric values come in as KiBi, than the base should be OTF2_BASE_BINARY and the exponent 10. Than the writer does not need to scale the values up to bytes, but can directly write the KiBi values into the Metric event. At reading time, the reader can apply the scaling factor to get the value in its base unit, ie. in bytes. |
| <i>unit</i> | Unit of the metric. This needs to be the scale free base unit, ie. "bytes", "operations", or "seconds". In particular this unit should not have any scale prefix. References a String definition. |

Since

Version 1.0

Returns

[OTF2_SUCCESS](#) if successful, an error code if an error occurs.

J.8.2.15 `OTF2_StatusCode OTF2_DefWriter_WriteParameter (OTF2_DefWriter * writer, OTF2_ParameterRef self, OTF2_StringRef name, OTF2_ParameterType parameterType)`

Writes a Parameter definition record into the DefWriter.

Parameters

| | |
|-----------------------|--|
| <i>writer</i> | Writer object. |
| <i>self</i> | The unique identifier for this Parameter definition. |
| <i>name</i> | Name of the parameter (variable name etc.) References a String definition. |
| <i>parameter-Type</i> | Type of the parameter, OTF2_ParameterType for possible types. |

J.8 OTF2_DefWriter.h File Reference

Since

Version 1.0

Returns

[OTF2_SUCCESS](#) if successful, an error code if an error occurs.

J.8.2.16 `OTF2_ErrorCode OTF2_DefWriter_WriteRegion (OTF2_DefWriter *
writer, OTF2_RegionRef self, OTF2_StringRef name, OTF2_StringRef
canonicalName, OTF2_StringRef description, OTF2_RegionRole
regionRole, OTF2_Paradigm paradigm, OTF2_RegionFlag regionFlags,
OTF2_StringRef sourceFile, uint32_t beginLineNumber, uint32_t
endLineNumber)`

Writes a Region definition record into the DefWriter.

Parameters

| | |
|------------------------------|--|
| <i>writer</i> | Writer object. |
| <i>self</i> | The unique identifier for this Region definition. |
| <i>name</i> | Name of the region (demangled name if available). References a String definition. |
| <i>canonical-Name</i> | Alternative name of the region (e.g. mangled name). References a String definition. Since version 1.1. |
| <i>description</i> | A more detailed description of this region. References a String definition. |
| <i>regionRole</i> | Region role. Since version 1.1. |
| <i>paradigm</i> | Paradigm. Since version 1.1. |
| <i>regionFlags</i> | Region flags. Since version 1.1. |
| <i>sourceFile</i> | The source file where this region was declared. References a String definition. |
| <i>beginLine- Number</i> | Starting line number of this region in the source file. |
| <i>endLi- neNumber</i> | Ending line number of this region in the source file. |

Since

Version 1.0

Returns

[OTF2_SUCCESS](#) if successful, an error code if an error occurs.

APPENDIX J. FILE DOCUMENTATION

J.8.2.17 `OTF2_ErrorCode OTF2_DefWriter_WriteRmaWin (OTF2_DefWriter * writer, OTF2_RmaWinRef self, OTF2_StringRef name, OTF2_CommRef comm)`

Writes a RmaWin definition record into the DefWriter.

A window defines the communication context for any remote-memory access operation.

Parameters

| | |
|---------------|--|
| <i>writer</i> | Writer object. |
| <i>self</i> | The unique identifier for this RmaWin definition. |
| <i>name</i> | Name, e.g. 'GASPI Queue 1', 'NVidia Card 2', etc.. References a String definition. |
| <i>comm</i> | Communicator object used to create the window. References a Comm definition. |

Since

Version 1.2

Returns

[OTF2_SUCCESS](#) if successful, an error code if an error occurs.

J.8.2.18 `OTF2_ErrorCode OTF2_DefWriter_WriteString (OTF2_DefWriter * writer, OTF2_StringRef self, const char * string)`

Writes a String definition record into the DefWriter.

Parameters

| | |
|---------------|---|
| <i>writer</i> | Writer object. |
| <i>self</i> | The unique identifier for this String definition. |
| <i>string</i> | The string, null terminated. |

Since

Version 1.0

Returns

[OTF2_SUCCESS](#) if successful, an error code if an error occurs.

J.8 OTF2_DefWriter.h File Reference

J.8.2.19 `OTF2_ErrorCode OTF2_DefWriter_WriteSystemTreeNode (OTF2_DefWriter * writer, OTF2_SystemTreeNodeRef self, OTF2_StringRef name, OTF2_StringRef className, OTF2_SystemTreeNodeRef parent)`

Writes a SystemTreeNode definition record into the DefWriter.

Parameters

| | |
|------------------|---|
| <i>writer</i> | Writer object. |
| <i>self</i> | The unique identifier for this SystemTreeNode definition. |
| <i>name</i> | Free form instance name of this node. References a String definition. |
| <i>className</i> | Free form class name of this node References a String definition. |
| <i>parent</i> | Parent id of this node. May be OTF2_UNDEFINED_SYSTEM_TREE_NODE to indicate that there is no parent. References a SystemTreeNode definition. |

Since

Version 1.0

Returns

[OTF2_SUCCESS](#) if successful, an error code if an error occurs.

J.8.2.20 `OTF2_ErrorCode OTF2_DefWriter_WriteSystemTreeNodeDomain (OTF2_DefWriter * writer, OTF2_SystemTreeNodeRef systemTreeNode, OTF2_SystemTreeDomain systemTreeDomain)`

Writes a SystemTreeNodeDomain definition record into the DefWriter.

Parameters

| | |
|-----------------------|---|
| <i>writer</i> | Writer object. |
| <i>systemTreeNode</i> | Parent SystemTreeNode definition to which this one is a supplementary definition. References a SystemTreeNode definition. |

Since

Version 1.2

Returns

[OTF2_SUCCESS](#) if successful, an error code if an error occurs.

J.8.2.21 `OTF2_ErrorCode` `OTF2_DefWriter_WriteSystemTreeNodeProperty` (
`OTF2_DefWriter * writer`, `OTF2_SystemTreeNodeRef systemTreeNode`,
`OTF2_StringRef name`, `OTF2_StringRef value`)

Writes a SystemTreeNodeProperty definition record into the DefWriter.

Parameters

| | |
|-----------------------|---|
| <i>writer</i> | Writer object. |
| <i>systemTreeNode</i> | Parent SystemTreeNode definition to which this one is a supplementary definition. References a SystemTreeNode definition. |
| <i>name</i> | Name of the property. References a String definition. |
| <i>value</i> | Property value. References a String definition. |

Since

Version 1.2

Returns

[OTF2_SUCCESS](#) if successful, an error code if an error occurs.

J.9 OTF2_ErrorCodes.h File Reference

Error codes and error handling.

```
#include <errno.h>
#include <stdint.h>
#include <stdarg.h>
```

Typedefs

- typedef `OTF2_ErrorCode`(* `OTF2_ErrorCallback`)(void *userData, const char *file, uint64_t line, const char *function, `OTF2_ErrorCode` errorCode, const char *msgFormatString, va_list va)

Enumerations

- enum `OTF2_ErrorCode` {
[OTF2_DEPRECATED](#) = -3,
[OTF2_ABORT](#) = -2,

J.9 OTF2_ErrorCodes.h File Reference

OTF2_WARNING = -1,
OTF2_SUCCESS = 0,
OTF2_ERROR_INVALID = 1,
OTF2_ERROR_E2BIG,
OTF2_ERROR_EACCES,
OTF2_ERROR_EADDRNOTAVAIL,
OTF2_ERROR_EAFNOSUPPORT,
OTF2_ERROR_EAGAIN,
OTF2_ERROR_EALREADY,
OTF2_ERROR_EBADF,
OTF2_ERROR_EBADMSG,
OTF2_ERROR_EBUSY,
OTF2_ERROR_ECANCELED,
OTF2_ERROR_ECHILD,
OTF2_ERROR_ECONNREFUSED,
OTF2_ERROR_ECONNRESET,
OTF2_ERROR_EDEADLK,
OTF2_ERROR_EDESTADDRREQ,
OTF2_ERROR_EDOM,
OTF2_ERROR_EDQUOT,
OTF2_ERROR_EEXIST,
OTF2_ERROR_EFAULT,
OTF2_ERROR_EFBIG,
OTF2_ERROR_EINPROGRESS,
OTF2_ERROR_EINTR,
OTF2_ERROR_EINVAL,
OTF2_ERROR_EIO,
OTF2_ERROR_EISCONN,
OTF2_ERROR_EISDIR,
OTF2_ERROR_ELOOP,
OTF2_ERROR_EMFILE,
OTF2_ERROR_EMLINK,
OTF2_ERROR EMSGSIZE,

APPENDIX J. FILE DOCUMENTATION

OTF2_ERROR_EMULTIHOP,
OTF2_ERROR_ENAMETOOLONG,
OTF2_ERROR_ENETDOWN,
OTF2_ERROR_ENETRESET,
OTF2_ERROR_ENETUNREACH,
OTF2_ERROR_ENFILE,
OTF2_ERROR_ENOBUFS,
OTF2_ERROR_ENODATA,
OTF2_ERROR_ENODEV,
OTF2_ERROR_ENOENT,
OTF2_ERROR_ENOEXEC,
OTF2_ERROR_ENOLCK,
OTF2_ERROR_ENOLINK,
OTF2_ERROR_ENOMEM,
OTF2_ERROR_ENOMSG,
OTF2_ERROR_ENOPROTOOPT,
OTF2_ERROR_ENOSPC,
OTF2_ERROR_ENOSR,
OTF2_ERROR_ENOSTR,
OTF2_ERROR_ENOSYS,
OTF2_ERROR_ENOTCONN,
OTF2_ERROR_ENOTDIR,
OTF2_ERROR_ENOTEMPTY,
OTF2_ERROR_ENOTSOCK,
OTF2_ERROR_ENOTSUP,
OTF2_ERROR_ENOTTY,
OTF2_ERROR_ENXIO,
OTF2_ERROR_EOPNOTSUPP,
OTF2_ERROR_EOVERFLOW,
OTF2_ERROR_EPERM,
OTF2_ERROR_EPIPE,
OTF2_ERROR_EPROTO,
OTF2_ERROR_EPROTONOSUPPORT,

J.9 OTF2_ErrorCodes.h File Reference

OTF2_ERROR_EPROTOTYPE,
OTF2_ERROR_ERANGE,
OTF2_ERROR_EROFS,
OTF2_ERROR_ESPIPE,
OTF2_ERROR_ESRCH,
OTF2_ERROR_ESTALE,
OTF2_ERROR_ETIME,
OTF2_ERROR_ETIMEDOUT,
OTF2_ERROR_ETXTBSY,
OTF2_ERROR_EWOULDBLOCK,
OTF2_ERROR_EXDEV,
OTF2_ERROR_END_OF_FUNCTION,
OTF2_ERROR_INVALID_CALL,
OTF2_ERROR_INVALID_ARGUMENT,
OTF2_ERROR_INVALID_RECORD,
OTF2_ERROR_INVALID_DATA,
OTF2_ERROR_INVALID_SIZE_GIVEN,
OTF2_ERROR_UNKNOWN_TYPE,
OTF2_ERROR_INTEGRITY_FAULT,
OTF2_ERROR_MEM_FAULT,
OTF2_ERROR_MEM_ALLOC_FAILED,
OTF2_ERROR_PROCESSED_WITH_FAULTS,
OTF2_ERROR_INDEX_OUT_OF_BOUNDS,
OTF2_ERROR_INVALID_LINENO,
OTF2_ERROR_END_OF_BUFFER,
OTF2_ERROR_FILE_INTERACTION,
OTF2_ERROR_FILE_CAN_NOT_OPEN,
OTF2_ERROR_INTERRUPTED_BY_CALLBACK,
OTF2_ERROR_PROPERTY_NAME_INVALID,
OTF2_ERROR_PROPERTY_EXISTS,
OTF2_ERROR_PROPERTY_NOT_FOUND,
OTF2_ERROR_PROPERTY_VALUE_INVALID,
OTF2_ERROR_FILE_COMPRESSION_NOT_SUPPORTED,
OTF2_ERROR_DUPLICATE_MAPPING_TABLE,
OTF2_ERROR_INVALID_FILE_MODE_TRANSITION }

Functions

- `const char * OTF2_Error_GetDescription (OTF2_ErrorCode errorCode)`
- `const char * OTF2_Error_GetName (OTF2_ErrorCode errorCode)`
- `OTF2_ErrorCallback OTF2_Error_RegisterCallback (OTF2_ErrorCallback errorCallbackIn, void *userData)`

J.9.1 Detailed Description

Error codes and error handling.

Maintainer:

Daniel Lorenz <d.lorenz@fz-juelich.de>

File Status:

ALPHA

Author

Dominic Eschweiler <d.eschweiler@fz-juelich.de>

J.9.2 Typedef Documentation

J.9.2.1 `typedef OTF2_ErrorCode(* OTF2_ErrorCallback)(void *userData, const char *file, uint64_t line, const char *function, OTF2_ErrorCode errorCode, const char *msgFormatString, va_list va)`

Signature of error handler callback functions. The error handler can be set with [OTF2_Error_RegisterCallback](#).

Parameters

| | |
|------------------------|---|
| <i>userData</i> | : Data passed to this function as given by the registry call. |
| <i>file</i> | : Name of the source-code file where the error appeared |
| <i>line</i> | : Line number in the source-code where the error appeared |
| <i>function</i> | : Name of the function where the error appeared |
| <i>errorCode</i> | : Error Code |
| <i>msgFormatString</i> | : Format string like it is used at the printf family. |
| <i>va</i> | : Variable argument list |

J.9 OTF2_ErrorCodes.h File Reference

Returns

Should return the errorCode

J.9.3 Enumeration Type Documentation

J.9.3.1 enum OTF2_ErrorCode

This is the list of error codes for OTF2.

Enumerator:

OTF2_DEPRECATED Special marker for error messages which indicates an deprecation.

OTF2_ABORT Special marker when the application will be aborted.

OTF2_WARNING Special marker for error messages which are only warnings.

OTF2_SUCCESS Operation successful

OTF2_ERROR_INVALID Invalid error code

Should only be used internally and not as an actual error code.

OTF2_ERROR_E2BIG The list of arguments is too long

OTF2_ERROR_EACCES Not enough rights

OTF2_ERROR_EADDRNOTAVAIL Address is not available

OTF2_ERROR_EAFNOSUPPORT Address family is not supported

OTF2_ERROR_EAGAIN Resource temporarily not available

OTF2_ERROR_EALREADY Connection is already processed

OTF2_ERROR_EBADF Invalid file pointer

OTF2_ERROR_EBADMSG Invalid message

OTF2_ERROR_EBUSY Resource or device is busy

OTF2_ERROR_ECANCELED Operation was aborted

OTF2_ERROR_ECHILD No child process available

OTF2_ERROR_ECONNREFUSED Connection was refused

OTF2_ERROR_ECONNRESET Connection was reset

OTF2_ERROR_EDEADLK Resolved deadlock

OTF2_ERROR_EDESTADDRREQ Destination address was expected

OTF2_ERROR_EDOM Domain error

OTF2_ERROR_EDQUOT Reserved

OTF2_ERROR_EEXIST File does already exist

APPENDIX J. FILE DOCUMENTATION

OTF2_ERROR_EFAULT Invalid Address
OTF2_ERROR_EFBIG File is to big
OTF2_ERROR_EINPROGRESS Operation is work in progress
OTF2_ERROR_EINTR Interruption of an operating system call
OTF2_ERROR_EINVAL Invalid argument
OTF2_ERROR_EIO Generic I/O error
OTF2_ERROR_EISCONN Socket is already connected
OTF2_ERROR_EISDIR Target is a directory
OTF2_ERROR_ELOOP To many layers of symbolic links
OTF2_ERROR_EMFILE To many opened files
OTF2_ERROR_EMLINK To many links
OTF2_ERROR EMSGSIZE Message buffer is to small
OTF2_ERROR_EMULTIHOP Reserved
OTF2_ERROR_ENAMETOOLONG Filename is to long
OTF2_ERROR_ENETDOWN Network is down
OTF2_ERROR_ENETRESET Connection was reset from the network
OTF2_ERROR_ENETUNREACH Network is not reachable
OTF2_ERROR_ENFILE To much opened files
OTF2_ERROR_ENOBUFS No buffer space available
OTF2_ERROR_ENODATA No more data left in the queue
OTF2_ERROR_ENODEV This device does not support this function
OTF2_ERROR_ENOENT File or Directory does not exist
OTF2_ERROR_ENOEXEC Can not execute binary
OTF2_ERROR_ENOLCK Locking failed
OTF2_ERROR_ENOLINK Reserved
OTF2_ERROR_ENOMEM Not enough main memory available
OTF2_ERROR_ENOMSG Message has not the expected type
OTF2_ERROR_ENOPROTOOPT This protocol is not available
OTF2_ERROR_ENOSPC No space left on device
OTF2_ERROR_ENOSR No stream available
OTF2_ERROR_ENOSTR This is not a stream
OTF2_ERROR_ENOSYS Requested function is not implemented
OTF2_ERROR_ENOTCONN Socket is not connected
OTF2_ERROR_ENOTDIR This is not an directory

J.9 OTF2_ErrorCodes.h File Reference

OTF2_ERROR_ENOTEMPTY This directory is not empty

OTF2_ERROR_ENOTSOCK No socket

OTF2_ERROR_ENOTSUP This operation is not supported

OTF2_ERROR_ENOTTY This IOCTL is not supported by the device

OTF2_ERROR_ENXIO Device is not yet configured

OTF2_ERROR_EOPNOTSUPP Operation is not supported by this socket

OTF2_ERROR_EOVERFLOW Value is too long for the datatype

OTF2_ERROR_EPERM Operation is not permitted

OTF2_ERROR_EPIPE Broken pipe

OTF2_ERROR_EPROTO Protocol error

OTF2_ERROR_EPROTONOSUPPORT Protocol is not supported

OTF2_ERROR_EPROTOTYPE Wrong protocol type for this socket

OTF2_ERROR_ERANGE Value is out of range

OTF2_ERROR_EROFS Filesystem is read only

OTF2_ERROR_ESPIPE This seek is not allowed

OTF2_ERROR_ESRCH No matching process found

OTF2_ERROR_ESTALE Reserved

OTF2_ERROR_ETIME Timeout in file stream or IOCTL

OTF2_ERROR_ETIMEDOUT Connection timed out

OTF2_ERROR_ETXTBSY File couldn't be executed while it is opened

OTF2_ERROR_EWOULDBLOCK Operation would be blocking

OTF2_ERROR_EXDEV Invalid link between devices

OTF2_ERROR_END_OF_FUNCTION Unintentional reached end of function

OTF2_ERROR_INVALID_CALL Function call not allowed in current state

OTF2_ERROR_INVALID_ARGUMENT Parameter value out of range

OTF2_ERROR_INVALID_RECORD Invalid definition or event record

OTF2_ERROR_INVALID_DATA Invalid or inconsistent record data

OTF2_ERROR_INVALID_SIZE_GIVEN The given size can not be used

OTF2_ERROR_UNKNOWN_TYPE The given type is not known

OTF2_ERROR_INTEGRITY_FAULT The structural integrity is not given

OTF2_ERROR_MEM_FAULT This could not be done with the given memory

OTF2_ERROR_MEM_ALLOC_FAILED Memory allocation failed

APPENDIX J. FILE DOCUMENTATION

- OTF2_ERROR_PROCESSED_WITH_FAULTS*** An error appeared when data was processed
- OTF2_ERROR_INDEX_OUT_OF_BOUNDS*** Index out of bounds
- OTF2_ERROR_INVALID_LINENO*** Invalid source code line number
- OTF2_ERROR_END_OF_BUFFER*** End of buffer/file reached
- OTF2_ERROR_FILE_INTERACTION*** Invalid file operation
- OTF2_ERROR_FILE_CAN_NOT_OPEN*** Unable to open file
- OTF2_ERROR_INTERRUPTED_BY_CALLBACK*** Record reading interrupted by reader callback
- OTF2_ERROR_PROPERTY_NAME_INVALID*** Property name does not conform to the naming scheme
- OTF2_ERROR_PROPERTY_EXISTS*** Property already exists
- OTF2_ERROR_PROPERTY_NOT_FOUND*** Property not found found in this archive
- OTF2_ERROR_PROPERTY_VALUE_INVALID*** Property value does not have the expected value
- OTF2_ERROR_FILE_COMPRESSION_NOT_SUPPORTED*** Missing library support for requested compression mode
- OTF2_ERROR_DUPLICATE_MAPPING_TABLE*** Multiple definitions for the same mapping type
- OTF2_ERROR_INVALID_FILE_MODE_TRANSITION*** File mode transition not permitted

J.9.4 Function Documentation

J.9.4.1 `const char* OTF2_Error_GetDescription (OTF2_ErrorCode errorCode)`

Returns the description of an error code.

Parameters

| | |
|------------------|--------------|
| <i>errorCode</i> | : Error Code |
|------------------|--------------|

Returns

Returns the description of a known error code.

J.10 OTF2_Events.h File Reference

J.9.4.2 `const char* OTF2_Error_GetName (OTF2_ErrorCode errorCode)`

Returns the name of an error code.

Parameters

| | |
|------------------|--------------|
| <i>errorCode</i> | : Error Code |
|------------------|--------------|

Returns

Returns the name of a known error code, and "INVALID_ERROR" for invalid or unknown error IDs.

J.9.4.3 `OTF2_ErrorCallback OTF2_Error_RegisterCallback (OTF2_ErrorCallback errorCallbackIn, void * userData)`

Register a programmers callback function for error handling.

Parameters

| | |
|------------------------|--|
| <i>errorCallbackIn</i> | : Function will be called instead of printing a default message to standard error. |
| <i>userData</i> | : Data pointer passed to the callback. |

Returns

Function pointer to the former error handling function.

J.10 OTF2_Events.h File Reference

Enums and types used in event records.

```
#include <otf2/OTF2_ErrorCodes.h>
```

```
#include <otf2/OTF2_GeneralDefinitions.h>
```

Data Structures

- union [OTF2_MetricValue](#)

Metric value.

Typedefs

- typedef uint8_t `OTF2_CollectiveOp`
Wrapper for enum `OTF2_CollectiveOp_enum`.
- typedef uint8_t `OTF2_LockType`
Wrapper for enum `OTF2_LockType_enum`.
- typedef uint8_t `OTF2_MeasurementMode`
Wrapper for enum `OTF2_MeasurementMode_enum`.
- typedef uint8_t `OTF2_RmaAtomicType`
Wrapper for enum `OTF2_RmaAtomicType_enum`.
- typedef uint32_t `OTF2_RmaSyncLevel`
Wrapper for enum `OTF2_RmaSyncLevel_enum`.
- typedef uint8_t `OTF2_RmaSyncType`
Wrapper for enum `OTF2_RmaSyncType_enum`.

Enumerations

- enum `OTF2_CollectiveOp_enum` { ,
`OTF2_COLLECTIVE_OP_CREATE_HANDLE` = 17,
`OTF2_COLLECTIVE_OP_DESTROY_HANDLE` = 18,
`OTF2_COLLECTIVE_OP_ALLOCATE` = 19,
`OTF2_COLLECTIVE_OP_DEALLOCATE` = 20,
`OTF2_COLLECTIVE_OP_CREATE_HANDLE_AND_ALLOCATE` = 21,
`OTF2_COLLECTIVE_OP_DESTROY_HANDLE_AND_DEALLOCATE` =
22 }
Types of collective operations.
- enum `OTF2_LockType_enum` {
`OTF2_LOCK_EXCLUSIVE` = 0,
`OTF2_LOCK_SHARED` = 1 }
General Lock Type.

J.10 OTF2_Events.h File Reference

- enum `OTF2_MeasurementMode_enum` {
`OTF2_MEASUREMENT_ON` = 1,
`OTF2_MEASUREMENT_OFF` = 2 }
Types for use in the MeasurementOnOff event.
- enum `OTF2_RmaAtomicType_enum`
RMA Atomic Operation Type.
- enum `OTF2_RmaSyncLevel_enum` {
`OTF2_RMA_SYNC_LEVEL_NONE` = 0,
`OTF2_RMA_SYNC_LEVEL_PROCESS` = (1 << 0),
`OTF2_RMA_SYNC_LEVEL_MEMORY` = (1 << 1) }
Synchronization level used in RMA synchronization records.
- enum `OTF2_RmaSyncType_enum` {
`OTF2_RMA_SYNC_TYPE_MEMORY` = 0,
`OTF2_RMA_SYNC_TYPE_NOTIFY_IN` = 1,
`OTF2_RMA_SYNC_TYPE_NOTIFY_OUT` = 2 }
Type of direct RMA synchronization call.

J.10.1 Detailed Description

Enums and types used in event records.

Source Template:

templates/OTF2_Events.tmpl.h

Maintainer:

Dominic Eschweiler <d.eschweiler@fz-juelich.de>

Authors

Dominic Eschweiler <d.eschweiler@fz-juelich.de>, Michael Wagner <michael.wagner@zih.tu-dresden.de>

J.10.2 Enumeration Type Documentation

J.10.2.1 enum OTF2_CollectiveOp_enum

Types of collective operations.

Since

Version 1.0

Enumerator:

OTF2_COLLECTIVE_OP_CREATE_HANDLE Collectively create a handle (ie. MPI_Win, MPI_Comm, MPI_File).

OTF2_COLLECTIVE_OP_DESTROY_HANDLE Collectively destroy a handle.

OTF2_COLLECTIVE_OP_ALLOCATE Collectively allocate memory.

OTF2_COLLECTIVE_OP_DEALLOCATE Collectively deallocate memory.

OTF2_COLLECTIVE_OP_CREATE_HANDLE_AND_ALLOCATE Collectively create a handle and allocate memory.

OTF2_COLLECTIVE_OP_DESTROY_HANDLE_AND_DEALLOCATE Collectively destroy a handle and deallocate memory.

J.10.2.2 enum OTF2_LockType_enum

General Lock Type.

Since

Version 1.2

Enumerator:

OTF2_LOCK_EXCLUSIVE Exclusive lock. No other lock will be granted.

OTF2_LOCK_SHARED Shared lock. Other shared locks will be granted, but no exclusive locks.

J.10 OTF2_Events.h File Reference

J.10.2.3 enum OTF2_MeasurementMode_enum

Types for use in the MeasurementOnOff event.

Since

Version 1.0

Enumerator:

OTF2_MEASUREMENT_ON The measurement resumed with event recording.

OTF2_MEASUREMENT_OFF The measurement suspended with event recording.

J.10.2.4 enum OTF2_RmaAtomicType_enum

RMA Atomic Operation Type.

Since

Version 1.2

J.10.2.5 enum OTF2_RmaSyncLevel_enum

Synchronization level used in RMA synchronization records.

Since

Version 1.2

Enumerator:

OTF2_RMA_SYNC_LEVEL_NONE No process synchronization or access completion (e.g., MPI_Win_post, MPI_Win_start).

OTF2_RMA_SYNC_LEVEL_PROCESS Synchronize processes (e.g., MPI_Win_create/free).

OTF2_RMA_SYNC_LEVEL_MEMORY Complete memory accesses (e.g., MPI_Win_complete, MPI_Win_wait).

J.10.2.6 enum OTF2_RmaSyncType_enum

Type of direct RMA synchronization call.

Since

Version 1.2

Enumerator:

- OTF2_RMA_SYNC_TYPE_MEMORY** Synchronize memory copy.
- OTF2_RMA_SYNC_TYPE_NOTIFY_IN** Incoming remote notification.
- OTF2_RMA_SYNC_TYPE_NOTIFY_OUT** Outgoing remote notification.

J.11 OTF2_EvtReader.h File Reference

This is the local event reader, which reads events from one location.

```
#include <stdint.h>
#include <otf2/OTF2_ErrorCodes.h>
#include <otf2/OTF2_Events.h>
#include <otf2/OTF2_Definitions.h>
#include <otf2/OTF2_AttributeList.h>
#include <otf2/OTF2_EvtReaderCallbacks.h>
```

Functions

- [OTF2_ErrorCode OTF2_EvtReader_ApplyClockOffsets](#) ([OTF2_EvtReader *reader](#), bool action)
Enable or disable applying of the clock offset to event timestamps read from this event reader.
- [OTF2_ErrorCode OTF2_EvtReader_ApplyMappingTables](#) ([OTF2_EvtReader *reader](#), bool action)
Enable or disable applying of the mapping tables to events read from this event reader.
- [OTF2_ErrorCode OTF2_EvtReader_GetLocationID](#) (const [OTF2_EvtReader *reader](#), [OTF2_LocationRef *location](#))
Return the location ID of the reading related location.

J.11 OTF2_EvtReader.h File Reference

- [OTF2_ErrorCode OTF2_EvtReader_GetPos](#) ([OTF2_EvtReader](#) *reader, [uint64_t](#) *position)

The following function can be used to get the position (number of the event in the stream) of last read event.

- [OTF2_ErrorCode OTF2_EvtReader_ReadEvents](#) ([OTF2_EvtReader](#) *reader, [uint64_t](#) recordsToRead, [uint64_t](#) *recordsRead)

After callback registration, the local events could be read with the following function. Readn reads recordsToRead records. The reader indicates that it reached the end of the trace by just reading less records than requested.

- [OTF2_ErrorCode OTF2_EvtReader_ReadEventsBackward](#) ([OTF2_EvtReader](#) *reader, [uint64_t](#) recordsToRead, [uint64_t](#) *recordsRead)

This functions reads recordsRead events backwards from the current position.

- [OTF2_ErrorCode OTF2_EvtReader_Seek](#) ([OTF2_EvtReader](#) *reader, [uint64_t](#) position)

Seek jumps to an event position.

- [OTF2_ErrorCode OTF2_EvtReader_SetCallbacks](#) ([OTF2_EvtReader](#) *reader, [const OTF2_EvtReaderCallbacks](#) *callbacks, [void](#) *userData)

Sets the callback functions for the given reader object. Everytime when OTF2 reads a record, a callback function is called and the records data is passed to this function. Therefore the programmer needs to set function pointers at the "callbacks" struct for the record type he wants to read.

- [OTF2_ErrorCode OTF2_EvtReader_TimeStampRewrite](#) ([OTF2_EvtReader](#) *reader, [OTF2_TimeStamp](#) time)

The following function rewrites the timestamp from the event on the actual reading position if the buffer is in `OTF2_BUFFER_MODIFY` mode. It also modifies the timestamp for all other events in the same timestamp bundle. This function also has to keep track that not only the last timestamp, but all records equal to the last timestamp has to be modified. This is done by a position list, if there has no seek appeared before. In this case a position list can be easily generated because of that the reader has seen all related timestamps before. This not the case if there has a seek appeared before. In this case the related timestamp positions are generated by a linear search.

J.11.1 Detailed Description

This is the local event reader, which reads events from one location.

Maintainer:

Dominic Eschweiler <d.eschweiler@fz-juelich.de>

Authors

Dominic Eschweiler <d.eschweiler@fz-juelich.de>, Michael Wagner <michael.wagner@zih.tu-dresden.de>

J.11.2 Function Documentation

J.11.2.1 OTF2_ErrorCode OTF2_EvtReader.ApplyClockOffsets (OTF2_EvtReader * reader, bool action)

Enable or disable applying of the clock offset to event timestamps read from this event reader.

This setting has no effect if the eventes are read by an global event reader.

Parameters

| | |
|---------------|---|
| <i>reader</i> | Reader object. |
| <i>action</i> | Truth value whether the clock offsets should be applied or not. |

Returns

OTF2_SUCCESS if successful, an error code if an error occurs.

J.11.2.2 OTF2_ErrorCode OTF2_EvtReader.ApplyMappingTables (OTF2_EvtReader * reader, bool action)

Enable or disable applying of the mapping tabes to events read from this event reader.

This setting has no effect if the eventes are read by an global event reader.

Parameters

| | |
|---------------|--|
| <i>reader</i> | Reader object. |
| <i>action</i> | Truth value whether the mappings should be applied or not. |

Returns

OTF2_SUCCESS if successful, an error code if an error occurs.

J.11 OTF2_EvtReader.h File Reference

J.11.2.3 `OTF2_StatusCode OTF2_EvtReader_GetLocationID (const
OTF2_EvtReader * reader, OTF2_LocationRef * location)`

Return the location ID of the reading related location.

Parameters

| | | |
|-----|-----------------|---|
| | <i>reader</i> | Reader object which reads the events from its buffer. |
| out | <i>location</i> | ID of the location. |

Returns

[*OTF2_SUCCESS*](#) if successful, an error code if an error occurs.

J.11.2.4 `OTF2_StatusCode OTF2_EvtReader_GetPos (OTF2_EvtReader * reader,
uint64_t * position)`

The following function can be used to get the position (number of the event in the stream) of last read event.

Parameters

| | | |
|-----|-----------------|---|
| | <i>reader</i> | Reader object which reads the events from its buffer. |
| out | <i>position</i> | Number of the event in the stream. |

Returns

[*OTF2_SUCCESS*](#) if successful, an error code if an error occurs.

J.11.2.5 `OTF2_StatusCode OTF2_EvtReader_ReadEvents (OTF2_EvtReader *
reader, uint64_t recordsToRead, uint64_t * recordsRead)`

After callback registration, the local events could be read with the following function. `Readn` reads *recordsToRead* records. The reader indicates that it reached the end of the trace by just reading less records than requested.

Parameters

| | | |
|-----|----------------------|---|
| | <i>reader</i> | Reader object which reads the events from its buffer. |
| | <i>recordsToRead</i> | How many records can be read next. |
| out | <i>recordsRead</i> | Return how many records were really read. |

Returns

OTF2_SUCCESS if successful, an error code if an error occurs.

J.11.2.6 *OTF2_StatusCode* **OTF2_EvtReader_ReadEventsBackward** (*OTF2_EvtReader* * *reader*, *uint64_t* *recordsToRead*, *uint64_t* * *recordsRead*)

This function reads *recordsRead* events backwards from the current position.

Parameters

| | | |
|-----|----------------------|---|
| | <i>reader</i> | Reader object which reads the events from its buffer. |
| | <i>recordsToRead</i> | How many records can be read next. |
| out | <i>recordsRead</i> | Return how many records were really read. |

Returns

OTF2_SUCCESS if successful, an error code if an error occurs.

J.11.2.7 *OTF2_StatusCode* **OTF2_EvtReader_Seek** (*OTF2_EvtReader* * *reader*, *uint64_t* *position*)

Seek jumps to an event position.

Parameters

| | |
|-----------------|---|
| <i>reader</i> | Reader object which reads the events from its buffer. |
| <i>position</i> | Number of the event, where the reader has to jump. |

Returns

OTF2_SUCCESS if successful, an error code if an error occurs.

J.11.2.8 *OTF2_StatusCode* **OTF2_EvtReader_SetCallbacks** (*OTF2_EvtReader* * *reader*, *const OTF2_EvtReaderCallbacks* * *callbacks*, *void* * *userData*)

Sets the callback functions for the given reader object. Everytime when OTF2 reads a record, a callback function is called and the records data is passed to this function. Therefore the programmer needs to set function pointers at the "callbacks" struct for the record type he wants to read.

J.12 OTF2_EvtReaderCallbacks.h File Reference

These callbacks are ignored, if the events are read by an global event reader.

Parameters

| | |
|------------------|---|
| <i>reader</i> | Reader object which reads the events from its buffer. |
| <i>callbacks</i> | Struct which holds a function pointer for each record type. OTF2_EvtReaderCallbacks_New . |
| <i>userData</i> | Data passed as argument <i>userData</i> to the record callbacks. |

Returns

[OTF2_SUCCESS](#) if successful, an error code if an error occurs.

J.11.2.9 OTF2_ErrorCode OTF2_EvtReader_TimeStampRewrite (OTF2_EvtReader * reader, OTF2_TimeStamp time)

The following function rewrites the timestamp from the event on the actual reading position if the buffer is in OTF2_BUFFER_MODIFY mode. It also modifies the timestamp for all other events in the same timestamp bundle. This function also has to keep track that not only the last timestamp, but all records equal to the last timestamp has to be modified. This is done by a position list, if there has no seek appeared before. In this case a position list can be easily generated because of that the reader has seen all related timestamps before. This not the case if there has a seek appeared before. In this case the related timestamp positions are generated by a linear search.

Parameters

| | |
|---------------|---|
| <i>reader</i> | Reader object which reads the events from its buffer. |
| <i>time</i> | New timestamp |

Returns

[OTF2_SUCCESS](#) if successful, an error code if an error occurs.

J.12 OTF2_EvtReaderCallbacks.h File Reference

This defines the callbacks for the event reader.

```
#include <stdint.h>
#include <otf2/OTF2_ErrorCodes.h>
#include <otf2/OTF2_GeneralDefinitions.h>
```

APPENDIX J. FILE DOCUMENTATION

```
#include <otf2/OTF2_AttributeList.h>
```

```
#include <otf2/OTF2_Events.h>
```

Typedefs

- typedef [OTF2_CallbackCode](#)(* [OTF2_EvtReaderCallback_BufferFlush](#))([OTF2_LocationRef](#) location, [OTF2_TimeStamp](#) time, uint64_t eventPosition, void *userData, [OTF2_AttributeList](#) *attributeList, [OTF2_TimeStamp](#) stopTime)

Callback for the BufferFlush event record.

- typedef [OTF2_CallbackCode](#)(* [OTF2_EvtReaderCallback_Enter](#))([OTF2_LocationRef](#) location, [OTF2_TimeStamp](#) time, uint64_t eventPosition, void *userData, [OTF2_AttributeList](#) *attributeList, [OTF2_RegionRef](#) region)

Callback for the Enter event record.

- typedef [OTF2_CallbackCode](#)(* [OTF2_EvtReaderCallback_Leave](#))([OTF2_LocationRef](#) location, [OTF2_TimeStamp](#) time, uint64_t eventPosition, void *userData, [OTF2_AttributeList](#) *attributeList, [OTF2_RegionRef](#) region)

Callback for the Leave event record.

- typedef [OTF2_CallbackCode](#)(* [OTF2_EvtReaderCallback_MeasurementOnOff](#))([OTF2_LocationRef](#) location, [OTF2_TimeStamp](#) time, uint64_t eventPosition, void *userData, [OTF2_AttributeList](#) *attributeList, [OTF2_MeasurementMode](#) measurementMode)

Callback for the MeasurementOnOff event record.

- typedef [OTF2_CallbackCode](#)(* [OTF2_EvtReaderCallback_Metric](#))([OTF2_LocationRef](#) location, [OTF2_TimeStamp](#) time, uint64_t eventPosition, void *userData, [OTF2_AttributeList](#) *attributeList, [OTF2_MetricRef](#) metric, uint8_t numberOfMetrics, const [OTF2_Type](#) *typeIDs, const [OTF2_MetricValue](#) *metricValues)

Callback for the Metric event record.

- typedef [OTF2_CallbackCode](#)(* [OTF2_EvtReaderCallback_MpiCollectiveBegin](#))([OTF2_LocationRef](#) location, [OTF2_TimeStamp](#) time, uint64_t eventPosition, void *userData, [OTF2_AttributeList](#) *attributeList)

Callback for the MpiCollectiveBegin event record.

- typedef [OTF2_CallbackCode](#)(* [OTF2_EvtReaderCallback_MpiCollectiveEnd](#))([OTF2_LocationRef](#) location, [OTF2_TimeStamp](#) time, uint64_t eventPosition, void *userData, [OTF2_AttributeList](#) *attributeList, [OTF2_CollectiveOp](#)

J.12 OTF2_EvtReaderCallbacks.h File Reference

collectiveOp, [OTF2_CommRef](#) communicator, uint32_t root, uint64_t sizeSent, uint64_t sizeReceived)

Callback for the `MpiCollectiveEnd` event record.

- typedef [OTF2_CallbackCode](#)(* [OTF2_EvtReaderCallback_MpiIrecv](#))([OTF2_LocationRef](#) location, [OTF2_TimeStamp](#) time, uint64_t eventPosition, void *userData, [OTF2_AttributeList](#) *attributeList, uint32_t sender, [OTF2_CommRef](#) communicator, uint32_t msgTag, uint64_t msgLength, uint64_t requestID)

Callback for the `MpiIrecv` event record.

- typedef [OTF2_CallbackCode](#)(* [OTF2_EvtReaderCallback_MpiIrecvRequest](#))([OTF2_LocationRef](#) location, [OTF2_TimeStamp](#) time, uint64_t eventPosition, void *userData, [OTF2_AttributeList](#) *attributeList, uint64_t requestID)

Callback for the `MpiIrecvRequest` event record.

- typedef [OTF2_CallbackCode](#)(* [OTF2_EvtReaderCallback_MpiIsend](#))([OTF2_LocationRef](#) location, [OTF2_TimeStamp](#) time, uint64_t eventPosition, void *userData, [OTF2_AttributeList](#) *attributeList, uint32_t receiver, [OTF2_CommRef](#) communicator, uint32_t msgTag, uint64_t msgLength, uint64_t requestID)

Callback for the `MpiIsend` event record.

- typedef [OTF2_CallbackCode](#)(* [OTF2_EvtReaderCallback_MpiIsendComplete](#))([OTF2_LocationRef](#) location, [OTF2_TimeStamp](#) time, uint64_t eventPosition, void *userData, [OTF2_AttributeList](#) *attributeList, uint64_t requestID)

Callback for the `MpiIsendComplete` event record.

- typedef [OTF2_CallbackCode](#)(* [OTF2_EvtReaderCallback_MpiRecv](#))([OTF2_LocationRef](#) location, [OTF2_TimeStamp](#) time, uint64_t eventPosition, void *userData, [OTF2_AttributeList](#) *attributeList, uint32_t sender, [OTF2_CommRef](#) communicator, uint32_t msgTag, uint64_t msgLength)

Callback for the `MpiRecv` event record.

- typedef [OTF2_CallbackCode](#)(* [OTF2_EvtReaderCallback_MpiRequestCancelled](#))([OTF2_LocationRef](#) location, [OTF2_TimeStamp](#) time, uint64_t eventPosition, void *userData, [OTF2_AttributeList](#) *attributeList, uint64_t requestID)

Callback for the `MpiRequestCancelled` event record.

- typedef [OTF2_CallbackCode](#)(* [OTF2_EvtReaderCallback_MpiRequestTest](#))([OTF2_LocationRef](#) location, [OTF2_TimeStamp](#) time, uint64_t eventPosition,

APPENDIX J. FILE DOCUMENTATION

tion, void *userData, [OTF2_AttributeList](#) *attributeList, uint64_t requestID)

Callback for the `MpiRequestTest` event record.

- typedef [OTF2_CallbackCode](#)(* [OTF2_EvtReaderCallback_MpiSend](#))([OTF2_LocationRef](#) location, [OTF2_TimeStamp](#) time, uint64_t eventPosition, void *userData, [OTF2_AttributeList](#) *attributeList, uint32_t receiver, [OTF2_CommRef](#) communicator, uint32_t msgTag, uint64_t msgLength)

Callback for the `MpiSend` event record.

- typedef [OTF2_CallbackCode](#)(* [OTF2_EvtReaderCallback_OmpAcquireLock](#))([OTF2_LocationRef](#) location, [OTF2_TimeStamp](#) time, uint64_t eventPosition, void *userData, [OTF2_AttributeList](#) *attributeList, uint32_t lockID, uint32_t acquisitionOrder)

Callback for the `OmpAcquireLock` event record.

- typedef [OTF2_CallbackCode](#)(* [OTF2_EvtReaderCallback_OmpFork](#))([OTF2_LocationRef](#) location, [OTF2_TimeStamp](#) time, uint64_t eventPosition, void *userData, [OTF2_AttributeList](#) *attributeList, uint32_t numberOfRequestedThreads)

Callback for the `OmpFork` event record.

- typedef [OTF2_CallbackCode](#)(* [OTF2_EvtReaderCallback_OmpJoin](#))([OTF2_LocationRef](#) location, [OTF2_TimeStamp](#) time, uint64_t eventPosition, void *userData, [OTF2_AttributeList](#) *attributeList)

Callback for the `OmpJoin` event record.

- typedef [OTF2_CallbackCode](#)(* [OTF2_EvtReaderCallback_OmpReleaseLock](#))([OTF2_LocationRef](#) location, [OTF2_TimeStamp](#) time, uint64_t eventPosition, void *userData, [OTF2_AttributeList](#) *attributeList, uint32_t lockID, uint32_t acquisitionOrder)

Callback for the `OmpReleaseLock` event record.

- typedef [OTF2_CallbackCode](#)(* [OTF2_EvtReaderCallback_OmpTaskComplete](#))([OTF2_LocationRef](#) location, [OTF2_TimeStamp](#) time, uint64_t eventPosition, void *userData, [OTF2_AttributeList](#) *attributeList, uint64_t taskID)

Callback for the `OmpTaskComplete` event record.

- typedef [OTF2_CallbackCode](#)(* [OTF2_EvtReaderCallback_OmpTaskCreate](#))([OTF2_LocationRef](#) location, [OTF2_TimeStamp](#) time, uint64_t eventPosition, void *userData, [OTF2_AttributeList](#) *attributeList, uint64_t taskID)

Callback for the `OmpTaskCreate` event record.

J.12 OTF2_EvtReaderCallbacks.h File Reference

- typedef OTF2_CallbackCode(* OTF2_EvtReaderCallback_OmpTaskSwitch)(OTF2_LocationRef location, OTF2_TimeStamp time, uint64_t eventPosition, void *userData, OTF2_AttributeList *attributeList, uint64_t taskID)
Callback for the OmpTaskSwitch event record.
- typedef OTF2_CallbackCode(* OTF2_EvtReaderCallback_ParameterInt)(OTF2_LocationRef location, OTF2_TimeStamp time, uint64_t eventPosition, void *userData, OTF2_AttributeList *attributeList, OTF2_ParameterRef parameter, int64_t value)
Callback for the ParameterInt event record.
- typedef OTF2_CallbackCode(* OTF2_EvtReaderCallback_ParameterString)(OTF2_LocationRef location, OTF2_TimeStamp time, uint64_t eventPosition, void *userData, OTF2_AttributeList *attributeList, OTF2_ParameterRef parameter, OTF2_StringRef string)
Callback for the ParameterString event record.
- typedef OTF2_CallbackCode(* OTF2_EvtReaderCallback_ParameterUnsignedInt)(OTF2_LocationRef location, OTF2_TimeStamp time, uint64_t eventPosition, void *userData, OTF2_AttributeList *attributeList, OTF2_ParameterRef parameter, uint64_t value)
Callback for the ParameterUnsignedInt event record.
- typedef OTF2_CallbackCode(* OTF2_EvtReaderCallback_RmaAcquireLock)(OTF2_LocationRef location, OTF2_TimeStamp time, uint64_t eventPosition, void *userData, OTF2_AttributeList *attributeList, OTF2_RmaWinRef win, uint32_t remote, uint64_t lockId, OTF2_LockType lockType)
Callback for the RmaAcquireLock event record.
- typedef OTF2_CallbackCode(* OTF2_EvtReaderCallback_RmaAtomic)(OTF2_LocationRef location, OTF2_TimeStamp time, uint64_t eventPosition, void *userData, OTF2_AttributeList *attributeList, OTF2_RmaWinRef win, uint32_t remote, OTF2_RmaAtomicType type, uint64_t bytesSent, uint64_t bytesReceived, uint64_t matchingId)
Callback for the RmaAtomic event record.
- typedef OTF2_CallbackCode(* OTF2_EvtReaderCallback_RmaCollectiveBegin)(OTF2_LocationRef location, OTF2_TimeStamp time, uint64_t eventPosition, void *userData, OTF2_AttributeList *attributeList)
Callback for the RmaCollectiveBegin event record.

APPENDIX J. FILE DOCUMENTATION

- typedef OTF2_CallbackCode(* OTF2_EvtReaderCallback_RmaCollectiveEnd)(OTF2_LocationRef location, OTF2_TimeStamp time, uint64_t eventPosition, void *userData, OTF2_AttributeList *attributeList, OTF2_CollectiveOp collectiveOp, OTF2_RmaSyncLevel syncLevel, OTF2_RmaWinRef win, uint32_t root, uint64_t bytesSent, uint64_t bytesReceived)
Callback for the RmaCollectiveEnd event record.
- typedef OTF2_CallbackCode(* OTF2_EvtReaderCallback_RmaGet)(OTF2_LocationRef location, OTF2_TimeStamp time, uint64_t eventPosition, void *userData, OTF2_AttributeList *attributeList, OTF2_RmaWinRef win, uint32_t remote, uint64_t bytes, uint64_t matchingId)
Callback for the RmaGet event record.
- typedef OTF2_CallbackCode(* OTF2_EvtReaderCallback_RmaGroupSync)(OTF2_LocationRef location, OTF2_TimeStamp time, uint64_t eventPosition, void *userData, OTF2_AttributeList *attributeList, OTF2_RmaSyncLevel syncLevel, OTF2_RmaWinRef win, OTF2_GroupRef group)
Callback for the RmaGroupSync event record.
- typedef OTF2_CallbackCode(* OTF2_EvtReaderCallback_RmaOpCompleteBlocking)(OTF2_LocationRef location, OTF2_TimeStamp time, uint64_t eventPosition, void *userData, OTF2_AttributeList *attributeList, OTF2_RmaWinRef win, uint64_t matchingId)
Callback for the RmaOpCompleteBlocking event record.
- typedef OTF2_CallbackCode(* OTF2_EvtReaderCallback_RmaOpCompleteNonBlocking)(OTF2_LocationRef location, OTF2_TimeStamp time, uint64_t eventPosition, void *userData, OTF2_AttributeList *attributeList, OTF2_RmaWinRef win, uint64_t matchingId)
Callback for the RmaOpCompleteNonBlocking event record.
- typedef OTF2_CallbackCode(* OTF2_EvtReaderCallback_RmaOpCompleteRemote)(OTF2_LocationRef location, OTF2_TimeStamp time, uint64_t eventPosition, void *userData, OTF2_AttributeList *attributeList, OTF2_RmaWinRef win, uint64_t matchingId)
Callback for the RmaOpCompleteRemote event record.
- typedef OTF2_CallbackCode(* OTF2_EvtReaderCallback_RmaOpTest)(OTF2_LocationRef location, OTF2_TimeStamp time, uint64_t eventPosition, void *userData, OTF2_AttributeList *attributeList, OTF2_RmaWinRef win, uint64_t matchingId)
Callback for the RmaOpTest event record.

J.12 OTF2_EvtReaderCallbacks.h File Reference

- typedef `OTF2_CallbackCode(* OTF2_EvtReaderCallback_RmaPut)(OTF2_LocationRef location, OTF2_TimeStamp time, uint64_t eventPosition, void *userData, OTF2_AttributeList *attributeList, OTF2_RmaWinRef win, uint32_t remote, uint64_t bytes, uint64_t matchingId)`
Callback for the RmaPut event record.
- typedef `OTF2_CallbackCode(* OTF2_EvtReaderCallback_RmaReleaseLock)(OTF2_LocationRef location, OTF2_TimeStamp time, uint64_t eventPosition, void *userData, OTF2_AttributeList *attributeList, OTF2_RmaWinRef win, uint32_t remote, uint64_t lockId)`
Callback for the RmaReleaseLock event record.
- typedef `OTF2_CallbackCode(* OTF2_EvtReaderCallback_RmaRequestLock)(OTF2_LocationRef location, OTF2_TimeStamp time, uint64_t eventPosition, void *userData, OTF2_AttributeList *attributeList, OTF2_RmaWinRef win, uint32_t remote, uint64_t lockId, OTF2_LockType lockType)`
Callback for the RmaRequestLock event record.
- typedef `OTF2_CallbackCode(* OTF2_EvtReaderCallback_RmaSync)(OTF2_LocationRef location, OTF2_TimeStamp time, uint64_t eventPosition, void *userData, OTF2_AttributeList *attributeList, OTF2_RmaWinRef win, uint32_t remote, OTF2_RmaSyncType syncType)`
Callback for the RmaSync event record.
- typedef `OTF2_CallbackCode(* OTF2_EvtReaderCallback_RmaTryLock)(OTF2_LocationRef location, OTF2_TimeStamp time, uint64_t eventPosition, void *userData, OTF2_AttributeList *attributeList, OTF2_RmaWinRef win, uint32_t remote, uint64_t lockId, OTF2_LockType lockType)`
Callback for the RmaTryLock event record.
- typedef `OTF2_CallbackCode(* OTF2_EvtReaderCallback_RmaWaitChange)(OTF2_LocationRef location, OTF2_TimeStamp time, uint64_t eventPosition, void *userData, OTF2_AttributeList *attributeList, OTF2_RmaWinRef win)`
Callback for the RmaWaitChange event record.
- typedef `OTF2_CallbackCode(* OTF2_EvtReaderCallback_RmaWinCreate)(OTF2_LocationRef location, OTF2_TimeStamp time, uint64_t eventPosition, void *userData, OTF2_AttributeList *attributeList, OTF2_RmaWinRef win)`
Callback for the RmaWinCreate event record.

- `typedef OTF2_CallbackCode(* OTF2_EvtReaderCallback_RmaWinDestroy)(OTF2_LocationRef location, OTF2_TimeStamp time, uint64_t eventPosition, void *userData, OTF2_AttributeList *attributeList, OTF2_RmaWinRef win)`
Callback for the RmaWinDestroy event record.
- `typedef OTF2_CallbackCode(* OTF2_EvtReaderCallback_ThreadAcquireLock)(OTF2_LocationRef location, OTF2_TimeStamp time, uint64_t eventPosition, void *userData, OTF2_AttributeList *attributeList, OTF2_Paradigm model, uint32_t lockID, uint32_t acquisitionOrder)`
Callback for the ThreadAcquireLock event record.
- `typedef OTF2_CallbackCode(* OTF2_EvtReaderCallback_ThreadFork)(OTF2_LocationRef location, OTF2_TimeStamp time, uint64_t eventPosition, void *userData, OTF2_AttributeList *attributeList, OTF2_Paradigm model, uint32_t numberOfRequestedThreads)`
Callback for the ThreadFork event record.
- `typedef OTF2_CallbackCode(* OTF2_EvtReaderCallback_ThreadJoin)(OTF2_LocationRef location, OTF2_TimeStamp time, uint64_t eventPosition, void *userData, OTF2_AttributeList *attributeList, OTF2_Paradigm model)`
Callback for the ThreadJoin event record.
- `typedef OTF2_CallbackCode(* OTF2_EvtReaderCallback_ThreadReleaseLock)(OTF2_LocationRef location, OTF2_TimeStamp time, uint64_t eventPosition, void *userData, OTF2_AttributeList *attributeList, OTF2_Paradigm model, uint32_t lockID, uint32_t acquisitionOrder)`
Callback for the ThreadReleaseLock event record.
- `typedef OTF2_CallbackCode(* OTF2_EvtReaderCallback_ThreadTaskComplete)(OTF2_LocationRef location, OTF2_TimeStamp time, uint64_t eventPosition, void *userData, OTF2_AttributeList *attributeList, OTF2_CommRef threadTeam, uint32_t creatingThread, uint32_t generationNumber)`
Callback for the ThreadTaskComplete event record.
- `typedef OTF2_CallbackCode(* OTF2_EvtReaderCallback_ThreadTaskCreate)(OTF2_LocationRef location, OTF2_TimeStamp time, uint64_t eventPosition, void *userData, OTF2_AttributeList *attributeList, OTF2_CommRef threadTeam, uint32_t creatingThread, uint32_t generationNumber)`
Callback for the ThreadTaskCreate event record.

J.12 OTF2_EvtReaderCallbacks.h File Reference

- typedef OTF2_CallbackCode(* OTF2_EvtReaderCallback_ThreadTaskSwitch)(OTF2_LocationRef location, OTF2_TimeStamp time, uint64_t eventPosition, void *userData, OTF2_AttributeList *attributeList, OTF2_CommRef threadTeam, uint32_t creatingThread, uint32_t generationNumber)

Callback for the ThreadTaskSwitch event record.

- typedef OTF2_CallbackCode(* OTF2_EvtReaderCallback_ThreadTeamBegin)(OTF2_LocationRef location, OTF2_TimeStamp time, uint64_t eventPosition, void *userData, OTF2_AttributeList *attributeList, OTF2_CommRef threadTeam)

Callback for the ThreadTeamBegin event record.

- typedef OTF2_CallbackCode(* OTF2_EvtReaderCallback_ThreadTeamEnd)(OTF2_LocationRef location, OTF2_TimeStamp time, uint64_t eventPosition, void *userData, OTF2_AttributeList *attributeList, OTF2_CommRef threadTeam)

Callback for the ThreadTeamEnd event record.

- typedef OTF2_CallbackCode(* OTF2_EvtReaderCallback_Unknown)(OTF2_LocationRef location, OTF2_TimeStamp time, uint64_t eventPosition, void *userData, OTF2_AttributeList *attributeList)

Callback for an unknown event record.

- typedef struct OTF2_EvtReaderCallbacks_struct OTF2_EvtReaderCallbacks

Opaque struct which holds all event record callbacks.

Functions

- void OTF2_EvtReaderCallbacks_Clear (OTF2_EvtReaderCallbacks *evtReaderCallbacks)

Clears a struct for the event callbacks.

- void OTF2_EvtReaderCallbacks_Delete (OTF2_EvtReaderCallbacks *evtReaderCallbacks)

Deallocates a struct for the event callbacks.

- OTF2_EvtReaderCallbacks * OTF2_EvtReaderCallbacks_New (void)

Allocates a new struct for the event callbacks.

APPENDIX J. FILE DOCUMENTATION

- [OTF2_ErrorCode](#) [OTF2_EvtReaderCallbacks_SetBufferFlushCallback](#) ([OTF2_EvtReaderCallbacks](#) *[evtReaderCallbacks](#), [OTF2_EvtReaderCallback_BufferFlush](#) [bufferFlushCallback](#))
Registers the callback for the BufferFlush event.
- [OTF2_ErrorCode](#) [OTF2_EvtReaderCallbacks_SetEnterCallback](#) ([OTF2_EvtReaderCallbacks](#) *[evtReaderCallbacks](#), [OTF2_EvtReaderCallback_Enter](#) [enterCallback](#))
Registers the callback for the Enter event.
- [OTF2_ErrorCode](#) [OTF2_EvtReaderCallbacks_SetLeaveCallback](#) ([OTF2_EvtReaderCallbacks](#) *[evtReaderCallbacks](#), [OTF2_EvtReaderCallback_Leave](#) [leaveCallback](#))
Registers the callback for the Leave event.
- [OTF2_ErrorCode](#) [OTF2_EvtReaderCallbacks_SetMeasurementOnOffCallback](#) ([OTF2_EvtReaderCallbacks](#) *[evtReaderCallbacks](#), [OTF2_EvtReaderCallback_MeasurementOnOff](#) [measurementOnOffCallback](#))
Registers the callback for the MeasurementOnOff event.
- [OTF2_ErrorCode](#) [OTF2_EvtReaderCallbacks_SetMetricCallback](#) ([OTF2_EvtReaderCallbacks](#) *[evtReaderCallbacks](#), [OTF2_EvtReaderCallback_Metric](#) [metricCallback](#))
Registers the callback for the Metric event.
- [OTF2_ErrorCode](#) [OTF2_EvtReaderCallbacks_SetMpiCollectiveBeginCallback](#) ([OTF2_EvtReaderCallbacks](#) *[evtReaderCallbacks](#), [OTF2_EvtReaderCallback_MpiCollectiveBegin](#) [mpiCollectiveBeginCallback](#))
Registers the callback for the MpiCollectiveBegin event.
- [OTF2_ErrorCode](#) [OTF2_EvtReaderCallbacks_SetMpiCollectiveEndCallback](#) ([OTF2_EvtReaderCallbacks](#) *[evtReaderCallbacks](#), [OTF2_EvtReaderCallback_MpiCollectiveEnd](#) [mpiCollectiveEndCallback](#))
Registers the callback for the MpiCollectiveEnd event.
- [OTF2_ErrorCode](#) [OTF2_EvtReaderCallbacks_SetMpiIrecvCallback](#) ([OTF2_EvtReaderCallbacks](#) *[evtReaderCallbacks](#), [OTF2_EvtReaderCallback_MpiIrecv](#) [mpiIrecvCallback](#))
Registers the callback for the MpiIrecv event.
- [OTF2_ErrorCode](#) [OTF2_EvtReaderCallbacks_SetMpiIrecvRequestCallback](#) ([OTF2_EvtReaderCallbacks](#) *[evtReaderCallbacks](#), [OTF2_EvtReaderCallback_MpiIrecvRequest](#) [mpiIrecvRequestCallback](#))
Registers the callback for the MpiIrecvRequest event.

J.12 OTF2_EvtReaderCallbacks.h File Reference

- [OTF2_ErrorCode](#) [OTF2_EvtReaderCallbacks_SetMpiIsendCallback](#) ([OTF2_EvtReaderCallbacks](#) *[evtReaderCallbacks](#), [OTF2_EvtReaderCallback_MpiIsend](#) [mpiIsendCallback](#))

Registers the callback for the MpiIsend event.

- [OTF2_ErrorCode](#) [OTF2_EvtReaderCallbacks_SetMpiIsendCompleteCallback](#) ([OTF2_EvtReaderCallbacks](#) *[evtReaderCallbacks](#), [OTF2_EvtReaderCallback_MpiIsendComplete](#) [mpiIsendCompleteCallback](#))

Registers the callback for the MpiIsendComplete event.

- [OTF2_ErrorCode](#) [OTF2_EvtReaderCallbacks_SetMpiRecvCallback](#) ([OTF2_EvtReaderCallbacks](#) *[evtReaderCallbacks](#), [OTF2_EvtReaderCallback_MpiRecv](#) [mpiRecvCallback](#))

Registers the callback for the MpiRecv event.

- [OTF2_ErrorCode](#) [OTF2_EvtReaderCallbacks_SetMpiRequestCancelledCallback](#) ([OTF2_EvtReaderCallbacks](#) *[evtReaderCallbacks](#), [OTF2_EvtReaderCallback_MpiRequestCancelled](#) [mpiRequestCancelledCallback](#))

Registers the callback for the MpiRequestCancelled event.

- [OTF2_ErrorCode](#) [OTF2_EvtReaderCallbacks_SetMpiRequestTestCallback](#) ([OTF2_EvtReaderCallbacks](#) *[evtReaderCallbacks](#), [OTF2_EvtReaderCallback_MpiRequestTest](#) [mpiRequestTestCallback](#))

Registers the callback for the MpiRequestTest event.

- [OTF2_ErrorCode](#) [OTF2_EvtReaderCallbacks_SetMpiSendCallback](#) ([OTF2_EvtReaderCallbacks](#) *[evtReaderCallbacks](#), [OTF2_EvtReaderCallback_MpiSend](#) [mpiSendCallback](#))

Registers the callback for the MpiSend event.

- [OTF2_ErrorCode](#) [OTF2_EvtReaderCallbacks_SetOmpAcquireLockCallback](#) ([OTF2_EvtReaderCallbacks](#) *[evtReaderCallbacks](#), [OTF2_EvtReaderCallback_OmpAcquireLock](#) [ompAcquireLockCallback](#))

Registers the callback for the OmpAcquireLock event.

- [OTF2_ErrorCode](#) [OTF2_EvtReaderCallbacks_SetOmpForkCallback](#) ([OTF2_EvtReaderCallbacks](#) *[evtReaderCallbacks](#), [OTF2_EvtReaderCallback_OmpFork](#) [ompForkCallback](#))

Registers the callback for the OmpFork event.

APPENDIX J. FILE DOCUMENTATION

- [OTF2_ErrorCode](#) [OTF2_EvtReaderCallbacks_SetOmpJoinCallback](#) ([OTF2_EvtReaderCallbacks](#) *evtReaderCallbacks, [OTF2_EvtReaderCallback_OmpJoin](#) ompJoinCallback)
Registers the callback for the OmpJoin event.
- [OTF2_ErrorCode](#) [OTF2_EvtReaderCallbacks_SetOmpReleaseLockCallback](#) ([OTF2_EvtReaderCallbacks](#) *evtReaderCallbacks, [OTF2_EvtReaderCallback_OmpReleaseLock](#) ompReleaseLockCallback)
Registers the callback for the OmpReleaseLock event.
- [OTF2_ErrorCode](#) [OTF2_EvtReaderCallbacks_SetOmpTaskCompleteCallback](#) ([OTF2_EvtReaderCallbacks](#) *evtReaderCallbacks, [OTF2_EvtReaderCallback_OmpTaskComplete](#) ompTaskCompleteCallback)
Registers the callback for the OmpTaskComplete event.
- [OTF2_ErrorCode](#) [OTF2_EvtReaderCallbacks_SetOmpTaskCreateCallback](#) ([OTF2_EvtReaderCallbacks](#) *evtReaderCallbacks, [OTF2_EvtReaderCallback_OmpTaskCreate](#) ompTaskCreateCallback)
Registers the callback for the OmpTaskCreate event.
- [OTF2_ErrorCode](#) [OTF2_EvtReaderCallbacks_SetOmpTaskSwitchCallback](#) ([OTF2_EvtReaderCallbacks](#) *evtReaderCallbacks, [OTF2_EvtReaderCallback_OmpTaskSwitch](#) ompTaskSwitchCallback)
Registers the callback for the OmpTaskSwitch event.
- [OTF2_ErrorCode](#) [OTF2_EvtReaderCallbacks_SetParameterIntCallback](#) ([OTF2_EvtReaderCallbacks](#) *evtReaderCallbacks, [OTF2_EvtReaderCallback_ParameterInt](#) parameterIntCallback)
Registers the callback for the ParameterInt event.
- [OTF2_ErrorCode](#) [OTF2_EvtReaderCallbacks_SetParameterStringCallback](#) ([OTF2_EvtReaderCallbacks](#) *evtReaderCallbacks, [OTF2_EvtReaderCallback_ParameterString](#) parameterStringCallback)
Registers the callback for the ParameterString event.
- [OTF2_ErrorCode](#) [OTF2_EvtReaderCallbacks_SetParameterUnsignedIntCallback](#) ([OTF2_EvtReaderCallbacks](#) *evtReaderCallbacks, [OTF2_EvtReaderCallback_ParameterUnsignedInt](#) parameterUnsignedIntCallback)
Registers the callback for the ParameterUnsignedInt event.
- [OTF2_ErrorCode](#) [OTF2_EvtReaderCallbacks_SetRmaAcquireLockCallback](#) ([OTF2_EvtReaderCallbacks](#) *evtReaderCallbacks, [OTF2_EvtReaderCallback_RmaAcquireLock](#) rmaAcquireLockCallback)

J.12 OTF2_EvtReaderCallbacks.h File Reference

Registers the callback for the RmaAcquireLock event.

- [OTF2_StatusCode OTF2_EvtReaderCallbacks_SetRmaAtomicCallback](#) ([OTF2_EvtReaderCallbacks](#) *evtReaderCallbacks, [OTF2_EvtReaderCallback_RmaAtomic](#) rmaAtomicCallback)

Registers the callback for the RmaAtomic event.

- [OTF2_StatusCode OTF2_EvtReaderCallbacks_SetRmaCollectiveBeginCallback](#) ([OTF2_EvtReaderCallbacks](#) *evtReaderCallbacks, [OTF2_EvtReaderCallback_RmaCollectiveBegin](#) rmaCollectiveBeginCallback)

Registers the callback for the RmaCollectiveBegin event.

- [OTF2_StatusCode OTF2_EvtReaderCallbacks_SetRmaCollectiveEndCallback](#) ([OTF2_EvtReaderCallbacks](#) *evtReaderCallbacks, [OTF2_EvtReaderCallback_RmaCollectiveEnd](#) rmaCollectiveEndCallback)

Registers the callback for the RmaCollectiveEnd event.

- [OTF2_StatusCode OTF2_EvtReaderCallbacks_SetRmaGetCallback](#) ([OTF2_EvtReaderCallbacks](#) *evtReaderCallbacks, [OTF2_EvtReaderCallback_RmaGet](#) rmaGetCallback)

Registers the callback for the RmaGet event.

- [OTF2_StatusCode OTF2_EvtReaderCallbacks_SetRmaGroupSyncCallback](#) ([OTF2_EvtReaderCallbacks](#) *evtReaderCallbacks, [OTF2_EvtReaderCallback_RmaGroupSync](#) rmaGroupSyncCallback)

Registers the callback for the RmaGroupSync event.

- [OTF2_StatusCode OTF2_EvtReaderCallbacks_SetRmaOpCompleteBlockingCallback](#) ([OTF2_EvtReaderCallbacks](#) *evtReaderCallbacks, [OTF2_EvtReaderCallback_RmaOpCompleteBlocking](#) rmaOpCompleteBlockingCallback)

Registers the callback for the RmaOpCompleteBlocking event.

- [OTF2_StatusCode OTF2_EvtReaderCallbacks_SetRmaOpCompleteNonBlockingCallback](#) ([OTF2_EvtReaderCallbacks](#) *evtReaderCallbacks, [OTF2_EvtReaderCallback_RmaOpCompleteNonBlocking](#) rmaOpCompleteNonBlockingCallback)

Registers the callback for the RmaOpCompleteNonBlocking event.

- [OTF2_StatusCode OTF2_EvtReaderCallbacks_SetRmaOpCompleteRemoteCallback](#) ([OTF2_EvtReaderCallbacks](#) *evtReaderCallbacks, [OTF2_EvtReaderCallback_RmaOpCompleteRemote](#) rmaOpCompleteRemoteCallback)

Registers the callback for the RmaOpCompleteRemote event.

APPENDIX J. FILE DOCUMENTATION

- [OTF2_ErrorCode](#) [OTF2_EvtReaderCallbacks_SetRmaOpTestCallback](#) ([OTF2_EvtReaderCallbacks](#) *[evtReaderCallbacks](#), [OTF2_EvtReaderCallback_RmaOpTest](#) [rmaOpTestCallback](#))
Registers the callback for the RmaOpTest event.
- [OTF2_ErrorCode](#) [OTF2_EvtReaderCallbacks_SetRmaPutCallback](#) ([OTF2_EvtReaderCallbacks](#) *[evtReaderCallbacks](#), [OTF2_EvtReaderCallback_RmaPut](#) [rmaPutCallback](#))
Registers the callback for the RmaPut event.
- [OTF2_ErrorCode](#) [OTF2_EvtReaderCallbacks_SetRmaReleaseLockCallback](#) ([OTF2_EvtReaderCallbacks](#) *[evtReaderCallbacks](#), [OTF2_EvtReaderCallback_RmaReleaseLock](#) [rmaReleaseLockCallback](#))
Registers the callback for the RmaReleaseLock event.
- [OTF2_ErrorCode](#) [OTF2_EvtReaderCallbacks_SetRmaRequestLockCallback](#) ([OTF2_EvtReaderCallbacks](#) *[evtReaderCallbacks](#), [OTF2_EvtReaderCallback_RmaRequestLock](#) [rmaRequestLockCallback](#))
Registers the callback for the RmaRequestLock event.
- [OTF2_ErrorCode](#) [OTF2_EvtReaderCallbacks_SetRmaSyncCallback](#) ([OTF2_EvtReaderCallbacks](#) *[evtReaderCallbacks](#), [OTF2_EvtReaderCallback_RmaSync](#) [rmaSyncCallback](#))
Registers the callback for the RmaSync event.
- [OTF2_ErrorCode](#) [OTF2_EvtReaderCallbacks_SetRmaTryLockCallback](#) ([OTF2_EvtReaderCallbacks](#) *[evtReaderCallbacks](#), [OTF2_EvtReaderCallback_RmaTryLock](#) [rmaTryLockCallback](#))
Registers the callback for the RmaTryLock event.
- [OTF2_ErrorCode](#) [OTF2_EvtReaderCallbacks_SetRmaWaitChangeCallback](#) ([OTF2_EvtReaderCallbacks](#) *[evtReaderCallbacks](#), [OTF2_EvtReaderCallback_RmaWaitChange](#) [rmaWaitChangeCallback](#))
Registers the callback for the RmaWaitChange event.
- [OTF2_ErrorCode](#) [OTF2_EvtReaderCallbacks_SetRmaWinCreateCallback](#) ([OTF2_EvtReaderCallbacks](#) *[evtReaderCallbacks](#), [OTF2_EvtReaderCallback_RmaWinCreate](#) [rmaWinCreateCallback](#))
Registers the callback for the RmaWinCreate event.
- [OTF2_ErrorCode](#) [OTF2_EvtReaderCallbacks_SetRmaWinDestroyCallback](#) ([OTF2_EvtReaderCallbacks](#) *[evtReaderCallbacks](#), [OTF2_EvtReaderCallback_RmaWinDestroy](#) [rmaWinDestroyCallback](#))

J.12 OTF2_EvtReaderCallbacks.h File Reference

Registers the callback for the RmaWinDestroy event.

- [OTF2_ErrorCode OTF2_EvtReaderCallbacks_SetThreadAcquireLockCallback](#) ([OTF2_EvtReaderCallbacks *evtReaderCallbacks](#), [OTF2_EvtReaderCallback_ThreadAcquireLock threadAcquireLockCallback](#))

Registers the callback for the ThreadAcquireLock event.

- [OTF2_ErrorCode OTF2_EvtReaderCallbacks_SetThreadForkCallback](#) ([OTF2_EvtReaderCallbacks *evtReaderCallbacks](#), [OTF2_EvtReaderCallback_ThreadFork threadForkCallback](#))

Registers the callback for the ThreadFork event.

- [OTF2_ErrorCode OTF2_EvtReaderCallbacks_SetThreadJoinCallback](#) ([OTF2_EvtReaderCallbacks *evtReaderCallbacks](#), [OTF2_EvtReaderCallback_ThreadJoin threadJoinCallback](#))

Registers the callback for the ThreadJoin event.

- [OTF2_ErrorCode OTF2_EvtReaderCallbacks_SetThreadReleaseLockCallback](#) ([OTF2_EvtReaderCallbacks *evtReaderCallbacks](#), [OTF2_EvtReaderCallback_ThreadReleaseLock threadReleaseLockCallback](#))

Registers the callback for the ThreadReleaseLock event.

- [OTF2_ErrorCode OTF2_EvtReaderCallbacks_SetThreadTaskCompleteCallback](#) ([OTF2_EvtReaderCallbacks *evtReaderCallbacks](#), [OTF2_EvtReaderCallback_ThreadTaskComplete threadTaskCompleteCallback](#))

Registers the callback for the ThreadTaskComplete event.

- [OTF2_ErrorCode OTF2_EvtReaderCallbacks_SetThreadTaskCreateCallback](#) ([OTF2_EvtReaderCallbacks *evtReaderCallbacks](#), [OTF2_EvtReaderCallback_ThreadTaskCreate threadTaskCreateCallback](#))

Registers the callback for the ThreadTaskCreate event.

- [OTF2_ErrorCode OTF2_EvtReaderCallbacks_SetThreadTaskSwitchCallback](#) ([OTF2_EvtReaderCallbacks *evtReaderCallbacks](#), [OTF2_EvtReaderCallback_ThreadTaskSwitch threadTaskSwitchCallback](#))

Registers the callback for the ThreadTaskSwitch event.

- [OTF2_ErrorCode OTF2_EvtReaderCallbacks_SetThreadTeamBeginCallback](#) ([OTF2_EvtReaderCallbacks *evtReaderCallbacks](#), [OTF2_EvtReaderCallback_ThreadTeamBegin threadTeamBeginCallback](#))

Registers the callback for the ThreadTeamBegin event.

APPENDIX J. FILE DOCUMENTATION

- [OTF2_ErrorCode OTF2_EvtReaderCallbacks_SetThreadTeamEndCallback](#) ([OTF2_EvtReaderCallbacks *evtReaderCallbacks](#), [OTF2_EvtReaderCallback_ThreadTeamEnd threadTeamEndCallback](#))
Registers the callback for the ThreadTeamEnd event.
- [OTF2_ErrorCode OTF2_EvtReaderCallbacks_SetUnknownCallback](#) ([OTF2_EvtReaderCallbacks *evtReaderCallbacks](#), [OTF2_EvtReaderCallback_Unknown unknownCallback](#))
Registers the callback for the Unknown event.

J.12.1 Detailed Description

This defines the callbacks for the event reader.

Source Template:

templates/OTF2_EvtReaderCallbacks.tmpl.h

Maintainer:

Dominic Eschweiler <d.eschweiler@fz-juelich.de>

Authors

Dominic Eschweiler <d.eschweiler@fz-juelich.de>, Michael Wagner <michael.wagner@zih.tu-dresden.de>

J.12.2 Typedef Documentation

J.12.2.1 `typedef OTF2_CallbackCode(* OTF2_EvtReaderCallback_ - BufferFlush)(OTF2_LocationRef location, OTF2_TimeStamp time, uint64_t eventPosition, void *userData, OTF2_AttributeList *attributeList, OTF2_TimeStamp stopTime)`

Callback for the BufferFlush event record.

This event signals that the internal buffer was flushed at the given time.

Parameters

| | |
|----------------------|---|
| <i>location</i> | The location where this event happened. |
| <i>time</i> | The time when this event happened. |
| <i>eventPosition</i> | The event position of this event in the trace. Starting with 1. |

J.12 OTF2_EvtReaderCallbacks.h File Reference

| | |
|----------------------|---|
| <i>userData</i> | User data as set by OTF2_Reader_RegisterEvtCallbacks or OTF2_EvtReader_SetCallbacks . |
| <i>attributeList</i> | Additional attributes for this event. |
| <i>stopTime</i> | The time the buffer flush finished. |

Since

Version 1.0

Returns

[OTF2_CALLBACK_SUCCESS](#) or [OTF2_CALLBACK_INTERRUPT](#).

J.12.2.2 `typedef OTF2_CallbackCode(* OTF2_EvtReaderCallback_Enter)(OTF2_LocationRef location, OTF2_TimeStamp time, uint64_t eventPosition, void *userData, OTF2_AttributeList *attributeList, OTF2_RegionRef region)`

Callback for the Enter event record.

An enter record indicates that the program enters a code region.

Parameters

| | |
|----------------------|--|
| <i>location</i> | The location where this event happened. |
| <i>time</i> | The time when this event happened. |
| <i>eventPosition</i> | The event position of this event in the trace. Starting with 1. |
| <i>userData</i> | User data as set by OTF2_Reader_RegisterEvtCallbacks or OTF2_EvtReader_SetCallbacks . |
| <i>attributeList</i> | Additional attributes for this event. |
| <i>region</i> | Needs to be defined in a definition record References a Region definition and will be mapped to the global definition if a mapping table of type OTF2_MAPPING_REGION is available. |

Since

Version 1.0

Returns

[OTF2_CALLBACK_SUCCESS](#) or [OTF2_CALLBACK_INTERRUPT](#).

APPENDIX J. FILE DOCUMENTATION

J.12.2.3 typedef OTF2_CallbackCode(* OTF2_EvtReaderCallback_Leave)(OTF2_LocationRef location, OTF2_TimeStamp time, uint64.t eventPosition, void *userData, OTF2_AttributeList *attributeList, OTF2_RegionRef region)

Callback for the Leave event record.

A leave record indicates that the program leaves a code region.

Parameters

| | |
|----------------------|--|
| <i>location</i> | The location where this event happened. |
| <i>time</i> | The time when this event happened. |
| <i>eventPosition</i> | The event position of this event in the trace. Starting with 1. |
| <i>userData</i> | User data as set by OTF2_Reader_RegisterEvtCallbacks or OTF2_EvtReader_SetCallbacks . |
| <i>attributeList</i> | Additional attributes for this event. |
| <i>region</i> | Needs to be defined in a definition record References a Region definition and will be mapped to the global definition if a mapping table of type OTF2_MAPPING_REGION is available. |

Since

Version 1.0

Returns

[OTF2_CALLBACK_SUCCESS](#) or [OTF2_CALLBACK_INTERRUPT](#).

J.12.2.4 typedef OTF2_CallbackCode(* OTF2_EvtReaderCallback_MeasurementOnOff)(OTF2_LocationRef location, OTF2_TimeStamp time, uint64.t eventPosition, void *userData, OTF2_AttributeList *attributeList, OTF2_MeasurementMode measurementMode)

Callback for the MeasurementOnOff event record.

This event signals where the measurement system turned measurement on or off.

Parameters

| | |
|----------------------|---|
| <i>location</i> | The location where this event happened. |
| <i>time</i> | The time when this event happened. |
| <i>eventPosition</i> | The event position of this event in the trace. Starting with 1. |

J.12 OTF2_EvtReaderCallbacks.h File Reference

| | |
|------------------------|---|
| <i>userData</i> | User data as set by OTF2_Reader_RegisterEvtCallbacks or OTF2_EvtReader_SetCallbacks . |
| <i>attributeList</i> | Additional attributes for this event. |
| <i>measurementMode</i> | Is the measurement turned on (OTF2_MEASUREMENT_ON) or off (OTF2_MEASUREMENT_OFF)? |

Since

Version 1.0

Returns

[OTF2_CALLBACK_SUCCESS](#) or [OTF2_CALLBACK_INTERRUPT](#).

J.12.2.5 `typedef OTF2_CallbackCode(* OTF2_EvtReaderCallback_Metric)(OTF2_LocationRef location, OTF2_TimeStamp time, uint64_t eventPosition, void *userData, OTF2_AttributeList *attributeList, OTF2_MetricRef metric, uint8_t numberOfMetrics, const OTF2_Type *typeIDs, const OTF2_MetricValue *metricValues)`

Callback for the Metric event record.

A metric event is always stored at the location that recorded the metric. A metric event can reference a metric class or metric instance. Therefore, metric classes and instances share same ID space. Synchronous metrics are always located right before the according enter and leave event.

Parameters

| | |
|------------------------|--|
| <i>location</i> | The location where this event happened. |
| <i>time</i> | The time when this event happened. |
| <i>eventPosition</i> | The event position of this event in the trace. Starting with 1. |
| <i>userData</i> | User data as set by OTF2_Reader_RegisterEvtCallbacks or OTF2_EvtReader_SetCallbacks . |
| <i>attributeList</i> | Additional attributes for this event. |
| <i>metric</i> | Could be a metric class or a metric instance. References a MetricClass , or a MetricInstance definition and will be mapped to the global definition if a mapping table of type OTF2_MAPPING_METRIC is available. |
| <i>numberOfMetrics</i> | Number of metrics with in the set. |
| <i>typeIDs</i> | List of metric types. |
| <i>metricValues</i> | List of metric values. |

Since

Version 1.0

Returns

OTF2_CALLBACK_SUCCESS or *OTF2_CALLBACK_INTERRUPT*.

J.12.2.6 `typedef OTF2_CallbackCode(* OTF2_EvtReaderCallback_ -
MpiCollectiveBegin)(OTF2_LocationRef location, OTF2_TimeStamp
time, uint64_t eventPosition, void *userData, OTF2_AttributeList
*attributeList)`

Callback for the MpiCollectiveBegin event record.

A MpiCollectiveBegin record marks the begin of an MPI collective operation (MPI_GATHER, MPI_SCATTER etc.).

Parameters

| | |
|----------------------|---|
| <i>location</i> | The location where this event happened. |
| <i>time</i> | The time when this event happened. |
| <i>eventPosition</i> | The event position of this event in the trace. Starting with 1. |
| <i>userData</i> | User data as set by OTF2_Reader_RegisterEvtCallbacks or OTF2_EvtReader_SetCallbacks . |
| <i>attributeList</i> | Additional attributes for this event. |

Since

Version 1.0

Returns

OTF2_CALLBACK_SUCCESS or *OTF2_CALLBACK_INTERRUPT*.

J.12.2.7 `typedef OTF2_CallbackCode(* OTF2_EvtReaderCallback_ -
MpiCollectiveEnd)(OTF2_LocationRef location, OTF2_TimeStamp
time, uint64_t eventPosition, void *userData, OTF2_AttributeList
*attributeList, OTF2_CollectiveOp collectiveOp, OTF2_CommRef
communicator, uint32_t root, uint64_t sizeSent, uint64_t sizeReceived)`

Callback for the MpiCollectiveEnd event record.

A MpiCollectiveEnd record marks the end of an MPI collective operation (MPI_GATHER, MPI_SCATTER etc.). It keeps the necessary information for this event:

J.12 OTF2_EvtReaderCallbacks.h File Reference

type of collective operation, communicator, the root of this collective operation. You can optionally add further information like sent and received bytes.

Parameters

| | |
|----------------------|--|
| <i>location</i> | The location where this event happened. |
| <i>time</i> | The time when this event happened. |
| <i>eventPosition</i> | The event position of this event in the trace. Starting with 1. |
| <i>userData</i> | User data as set by OTF2_Reader_RegisterEvtCallbacks or OTF2_EvtReader_SetCallbacks . |
| <i>attributeList</i> | Additional attributes for this event. |
| <i>collectiveOp</i> | Determines which collective operation it is. |
| <i>communicator</i> | Communicator References a Comm definition and will be mapped to the global definition if a mapping table of type OTF2_MAPPING_COMM is available. |
| <i>root</i> | MPI rank of root in <i>communicator</i> . |
| <i>sizeSent</i> | Size of the sent message. |
| <i>sizeReceived</i> | Size of the received message. |

Since

Version 1.0

Returns

[OTF2_CALLBACK_SUCCESS](#) or [OTF2_CALLBACK_INTERRUPT](#).

J.12.2.8 `typedef OTF2_CallbackCode(* OTF2_EvtReaderCallback_MpiIrecv)(OTF2_LocationRef location, OTF2_TimeStamp time, uint64_t eventPosition, void *userData, OTF2_AttributeList *attributeList, uint32_t sender, OTF2_CommRef communicator, uint32_t msgTag, uint64_t msgLength, uint64_t requestID)`

Callback for the MpiIrecv event record.

A MpiIrecv record indicates that a MPI message was received (MPI_IRecv). It keeps the necessary information for this event: sender of the message, communicator, and the message tag. You can optionally add further information like the message length (size of the receive buffer).

Parameters

APPENDIX J. FILE DOCUMENTATION

| | |
|----------------------|--|
| <i>location</i> | The location where this event happened. |
| <i>time</i> | The time when this event happened. |
| <i>eventPosition</i> | The event position of this event in the trace. Starting with 1. |
| <i>userData</i> | User data as set by OTF2_Reader_RegisterEvtCallbacks or OTF2_EvtReader_SetCallbacks . |
| <i>attributeList</i> | Additional attributes for this event. |
| <i>sender</i> | MPI rank of sender in <i>communicator</i> . |
| <i>communicator</i> | Communicator ID. References a Comm definition and will be mapped to the global definition if a mapping table of type OTF2_MAPPING_COMM is available. |
| <i>msgTag</i> | Message tag |
| <i>msgLength</i> | Message length |
| <i>requestID</i> | ID of the related request |

Since

Version 1.0

Returns

[OTF2_CALLBACK_SUCCESS](#) or [OTF2_CALLBACK_INTERRUPT](#).

J.12.2.9 `typedef OTF2_CallbackCode(* OTF2_EvtReaderCallback_MpiIrecvRequest)(OTF2_LocationRef location, OTF2_TimeStamp time, uint64_t eventPosition, void *userData, OTF2_AttributeList *attributeList, uint64_t requestID)`

Callback for the `MpiIrecvRequest` event record.

Signals the request of an receive, which can be completed later.

Parameters

| | |
|----------------------|---|
| <i>location</i> | The location where this event happened. |
| <i>time</i> | The time when this event happened. |
| <i>eventPosition</i> | The event position of this event in the trace. Starting with 1. |
| <i>userData</i> | User data as set by OTF2_Reader_RegisterEvtCallbacks or OTF2_EvtReader_SetCallbacks . |
| <i>attributeList</i> | Additional attributes for this event. |
| <i>requestID</i> | ID of the requested receive |

J.12 OTF2_EvtReaderCallbacks.h File Reference

Since

Version 1.0

Returns

[OTF2_CALLBACK_SUCCESS](#) or [OTF2_CALLBACK_INTERRUPT](#).

J.12.2.10 `typedef OTF2_CallbackCode(* OTF2_EvtReaderCallback_
MpiIsend)(OTF2_LocationRef location, OTF2_TimeStamp time,
uint64_t eventPosition, void *userData, OTF2_AttributeList *attributeList,
uint32_t receiver, OTF2_CommRef communicator, uint32_t msgTag, uint64_t
msgLength, uint64_t requestID)`

Callback for the MpiIsend event record.

A MpiIsend record indicates that a MPI message send process was initiated (MPI_ISEND). It keeps the necessary information for this event: receiver of the message, communicator, and the message tag. You can optionally add further information like the message length (size of the send buffer).

Parameters

| | |
|----------------------|--|
| <i>location</i> | The location where this event happened. |
| <i>time</i> | The time when this event happened. |
| <i>eventPosition</i> | The event position of this event in the trace. Starting with 1. |
| <i>userData</i> | User data as set by OTF2_Reader_RegisterEvtCallbacks or OTF2_EvtReader_SetCallbacks . |
| <i>attributeList</i> | Additional attributes for this event. |
| <i>receiver</i> | MPI rank of receiver in <i>communicator</i> . |
| <i>communicator</i> | Communicator ID. References a Comm definition and will be mapped to the global definition if a mapping table of type OTF2_MAPPING_COMM is available. |
| <i>msgTag</i> | Message tag |
| <i>msgLength</i> | Message length |
| <i>requestID</i> | ID of the related request |

Since

Version 1.0

Returns

[OTF2_CALLBACK_SUCCESS](#) or [OTF2_CALLBACK_INTERRUPT](#).

APPENDIX J. FILE DOCUMENTATION

J.12.2.11 `typedef OTF2_CallbackCode(* OTF2_EvtReaderCallback_-
MpiIsendComplete)(OTF2_LocationRef location, OTF2_TimeStamp
time, uint64_t eventPosition, void *userData, OTF2_AttributeList
*attributeList, uint64_t requestID)`

Callback for the MpiIsendComplete event record.

Signals the completion of non-blocking send request.

Parameters

| | |
|----------------------|--|
| <i>location</i> | The location where this event happened. |
| <i>time</i> | The time when this event happened. |
| <i>eventPosition</i> | The event position of this event in the trace. Starting with 1. |
| <i>userData</i> | User data as set by OTF2_Reader_RegisterEvtCallbacks or OTF2_-EvtReader_SetCallbacks . |
| <i>attributeList</i> | Additional attributes for this event. |
| <i>requestID</i> | ID of the related request |

Since

Version 1.0

Returns

[OTF2_CALLBACK_SUCCESS](#) or [OTF2_CALLBACK_INTERRUPT](#).

J.12.2.12 `typedef OTF2_CallbackCode(* OTF2_EvtReaderCallback_-
MpiRecv)(OTF2_LocationRef location, OTF2_TimeStamp time,
uint64_t eventPosition, void *userData, OTF2_AttributeList *attributeList,
uint32_t sender, OTF2_CommRef communicator, uint32_t msgTag, uint64_t
msgLength)`

Callback for the MpiRecv event record.

A MpiRecv record indicates that a MPI message was received (MPI_RECV). It keeps the necessary information for this event: sender of the message, communicator, and the message tag. You can optionally add further information like the message length (size of the receive buffer).

Parameters

| | |
|-----------------|---|
| <i>location</i> | The location where this event happened. |
| <i>time</i> | The time when this event happened. |

J.12 OTF2_EvtReaderCallbacks.h File Reference

| | |
|----------------------|--|
| <i>eventPosition</i> | The event position of this event in the trace. Starting with 1. |
| <i>userData</i> | User data as set by OTF2_Reader_RegisterEvtCallbacks or OTF2_EvtReader_SetCallbacks . |
| <i>attributeList</i> | Additional attributes for this event. |
| <i>sender</i> | MPI rank of sender in <i>communicator</i> . |
| <i>communicator</i> | Communicator ID. References a Comm definition and will be mapped to the global definition if a mapping table of type OTF2_MAPPING_COMM is available. |
| <i>msgTag</i> | Message tag |
| <i>msgLength</i> | Message length |

Since

Version 1.0

Returns

[OTF2_CALLBACK_SUCCESS](#) or [OTF2_CALLBACK_INTERRUPT](#).

J.12.2.13 `typedef OTF2_CallbackCode(* OTF2_EvtReaderCallback_MpiRequestCancelled)(OTF2_LocationRef location, OTF2_TimeStamp time, uint64_t eventPosition, void *userData, OTF2_AttributeList *attributeList, uint64_t requestID)`

Callback for the MpiRequestCancelled event record.

This events appears if the program canceled a request.

Parameters

| | |
|----------------------|---|
| <i>location</i> | The location where this event happened. |
| <i>time</i> | The time when this event happened. |
| <i>eventPosition</i> | The event position of this event in the trace. Starting with 1. |
| <i>userData</i> | User data as set by OTF2_Reader_RegisterEvtCallbacks or OTF2_EvtReader_SetCallbacks . |
| <i>attributeList</i> | Additional attributes for this event. |
| <i>requestID</i> | ID of the related request |

Since

Version 1.0

Returns

OTF2_CALLBACK_SUCCESS or *OTF2_CALLBACK_INTERRUPT*.

J.12.2.14 `typedef OTF2_CallbackCode(* OTF2_EvtReaderCallback_-
MpiRequestTest)(OTF2_LocationRef location, OTF2_TimeStamp
time, uint64_t eventPosition, void *userData, OTF2_AttributeList
*attributeList, uint64_t requestID)`

Callback for the MpiRequestTest event record.

This events appears if the program tests if a request has already completed but the test failed.

Parameters

| | |
|----------------------|---|
| <i>location</i> | The location where this event happened. |
| <i>time</i> | The time when this event happened. |
| <i>eventPosition</i> | The event position of this event in the trace. Starting with 1. |
| <i>userData</i> | User data as set by OTF2_Reader_RegisterEvtCallbacks or OTF2_EvtReader_SetCallbacks . |
| <i>attributeList</i> | Additional attributes for this event. |
| <i>requestID</i> | ID of the related request |

Since

Version 1.0

Returns

OTF2_CALLBACK_SUCCESS or *OTF2_CALLBACK_INTERRUPT*.

J.12.2.15 `typedef OTF2_CallbackCode(* OTF2_EvtReaderCallback_-
MpiSend)(OTF2_LocationRef location, OTF2_TimeStamp time,
uint64_t eventPosition, void *userData, OTF2_AttributeList *attributeList,
uint32_t receiver, OTF2_CommRef communicator, uint32_t msgTag, uint64_t
msgLength)`

Callback for the MpiSend event record.

A MpiSend record indicates that a MPI message send process was initiated (MPI_SEND). It keeps the necessary information for this event: receiver of the message, communicator, and the message tag. You can optionally add further information like the message length (size of the send buffer).

J.12 OTF2_EvtReaderCallbacks.h File Reference

Parameters

| | |
|----------------------|--|
| <i>location</i> | The location where this event happened. |
| <i>time</i> | The time when this event happened. |
| <i>eventPosition</i> | The event position of this event in the trace. Starting with 1. |
| <i>userData</i> | User data as set by OTF2_Reader_RegisterEvtCallbacks or OTF2_EvtReader_SetCallbacks . |
| <i>attributeList</i> | Additional attributes for this event. |
| <i>receiver</i> | MPI rank of receiver in <i>communicator</i> . |
| <i>communicator</i> | Communicator ID. References a Comm definition and will be mapped to the global definition if a mapping table of type OTF2_MAPPING_COMM is available. |
| <i>msgTag</i> | Message tag |
| <i>msgLength</i> | Message length |

Since

Version 1.0

Returns

[OTF2_CALLBACK_SUCCESS](#) or [OTF2_CALLBACK_INTERRUPT](#).

J.12.2.16 `typedef OTF2_CallbackCode(* OTF2_EvtReaderCallback_OmpAcquireLock)(OTF2_LocationRef location, OTF2_TimeStamp time, uint64_t eventPosition, void *userData, OTF2_AttributeList *attributeList, uint32_t lockID, uint32_t acquisitionOrder)`

Callback for the `OmpAcquireLock` event record.

An `OmpAcquireLock` record marks that a thread acquires an OpenMP lock.

This event record is superseded by the [ThreadAcquireLock](#) event record and should not be used when the [ThreadAcquireLock](#) event record is in use record.

Parameters

| | |
|----------------------|---|
| <i>location</i> | The location where this event happened. |
| <i>time</i> | The time when this event happened. |
| <i>eventPosition</i> | The event position of this event in the trace. Starting with 1. |
| <i>userData</i> | User data as set by OTF2_Reader_RegisterEvtCallbacks or OTF2_EvtReader_SetCallbacks . |
| <i>attributeList</i> | Additional attributes for this event. |

APPENDIX J. FILE DOCUMENTATION

| | |
|-------------------------|---|
| <i>lockID</i> | ID of the lock. |
| <i>acquisitionOrder</i> | A monotonically increasing number to determine the order of lock acquisitions (with unsynchronized clocks this is otherwise not possible). Corresponding acquire-release events have same number. |

Since

Version 1.0

Returns

[OTF2_CALLBACK_SUCCESS](#) or [OTF2_CALLBACK_INTERRUPT](#).

J.12.2.17 `typedef OTF2_CallbackCode(* OTF2_EvtReaderCallback_
OmpFork)(OTF2_LocationRef location, OTF2_TimeStamp time,
uint64_t eventPosition, void *userData, OTF2_AttributeList *attributeList,
uint32_t numberOfRequestedThreads)`

Callback for the OmpFork event record.

An OmpFork record marks that an OpenMP Thread forks a thread team.

This event record is superseded by the [ThreadFork](#) event record and should not be used when the [ThreadFork](#) event record is in use.

Parameters

| | |
|---------------------------------|---|
| <i>location</i> | The location where this event happened. |
| <i>time</i> | The time when this event happened. |
| <i>eventPosition</i> | The event position of this event in the trace. Starting with 1. |
| <i>userData</i> | User data as set by OTF2_Reader_RegisterEvtCallbacks or OTF2_EvtReader_SetCallbacks . |
| <i>attributeList</i> | Additional attributes for this event. |
| <i>numberOfRequestedThreads</i> | Requested size of the team. |

Since

Version 1.0

Returns

[OTF2_CALLBACK_SUCCESS](#) or [OTF2_CALLBACK_INTERRUPT](#).

J.12 OTF2_EvtReaderCallbacks.h File Reference

J.12.2.18 `typedef OTF2_CallbackCode(* OTF2_EvtReaderCallback_-
OmpJoin)(OTF2_LocationRef location, OTF2_TimeStamp time,
uint64_t eventPosition, void *userData, OTF2_AttributeList *attributeList)`

Callback for the OmpJoin event record.

An OmpJoin record marks that a team of threads is joint and only the master thread continues execution.

This event record is superseded by the *ThreadJoin* event record and should not be used when the *ThreadJoin* event record is in use.

Parameters

| | |
|----------------------|---|
| <i>location</i> | The location where this event happened. |
| <i>time</i> | The time when this event happened. |
| <i>eventPosition</i> | The event position of this event in the trace. Starting with 1. |
| <i>userData</i> | User data as set by OTF2_Reader_RegisterEvtCallbacks or OTF2_EvtReader_SetCallbacks . |
| <i>attributeList</i> | Additional attributes for this event. |

Since

Version 1.0

Returns

[OTF2_CALLBACK_SUCCESS](#) or [OTF2_CALLBACK_INTERRUPT](#).

J.12.2.19 `typedef OTF2_CallbackCode(* OTF2_EvtReaderCallback_-
OmpReleaseLock)(OTF2_LocationRef location, OTF2_TimeStamp
time, uint64_t eventPosition, void *userData, OTF2_AttributeList
*attributeList, uint32_t lockID, uint32_t acquisitionOrder)`

Callback for the OmpReleaseLock event record.

An OmpReleaseLock record marks that a thread releases an OpenMP lock.

This event record is superseded by the *ThreadReleaseLock* event record and should not be used when the *ThreadReleaseLock* event record is in use.

Parameters

| | |
|-----------------|---|
| <i>location</i> | The location where this event happened. |
| <i>time</i> | The time when this event happened. |

APPENDIX J. FILE DOCUMENTATION

| | |
|-------------------------|---|
| <i>eventPosition</i> | The event position of this event in the trace. Starting with 1. |
| <i>userData</i> | User data as set by OTF2_Reader_RegisterEvtCallbacks or OTF2_EvtReader_SetCallbacks . |
| <i>attributeList</i> | Additional attributes for this event. |
| <i>lockID</i> | ID of the lock. |
| <i>acquisitionOrder</i> | A monotonically increasing number to determine the order of lock acquisitions (with unsynchronized clocks this is otherwise not possible). Corresponding acquire-release events have same number. |

Since

Version 1.0

Returns

[OTF2_CALLBACK_SUCCESS](#) or [OTF2_CALLBACK_INTERRUPT](#).

J.12.2.20 `typedef OTF2_CallbackCode(* OTF2_EvtReaderCallback_OmpTaskComplete)(OTF2_LocationRef location, OTF2_TimeStamp time, uint64_t eventPosition, void *userData, OTF2_AttributeList *attributeList, uint64_t taskID)`

Callback for the OmpTaskComplete event record.

An OmpTaskComplete record indicates that the execution of an OpenMP task has finished.

This event record is superseded by the [ThreadTaskComplete](#) event record and should not be used when the [ThreadTaskComplete](#) event record is in use.

Parameters

| | |
|----------------------|---|
| <i>location</i> | The location where this event happened. |
| <i>time</i> | The time when this event happened. |
| <i>eventPosition</i> | The event position of this event in the trace. Starting with 1. |
| <i>userData</i> | User data as set by OTF2_Reader_RegisterEvtCallbacks or OTF2_EvtReader_SetCallbacks . |
| <i>attributeList</i> | Additional attributes for this event. |
| <i>taskID</i> | Identifier of the completed task instance. |

J.12 OTF2_EvtReaderCallbacks.h File Reference

Since

Version 1.0

Returns

[OTF2_CALLBACK_SUCCESS](#) or [OTF2_CALLBACK_INTERRUPT](#).

J.12.2.21 `typedef OTF2_CallbackCode(* OTF2_EvtReaderCallback_
OmpTaskCreate)(OTF2_LocationRef location, OTF2_TimeStamp
time, uint64_t eventPosition, void *userData, OTF2_AttributeList
*attributeList, uint64_t taskID)`

Callback for the OmpTaskCreate event record.

An OmpTaskCreate record marks that an OpenMP Task was/will be created in the current region.

This event record is superseded by the [ThreadTaskCreate](#) event record and should not be used when the [ThreadTaskCreate](#) event record is in use.

Parameters

| | |
|----------------------|---|
| <i>location</i> | The location where this event happened. |
| <i>time</i> | The time when this event happened. |
| <i>eventPosition</i> | The event position of this event in the trace. Starting with 1. |
| <i>userData</i> | User data as set by OTF2_Reader_RegisterEvtCallbacks or OTF2_EvtReader_SetCallbacks . |
| <i>attributeList</i> | Additional attributes for this event. |
| <i>taskID</i> | Identifier of the newly created task instance. |

Since

Version 1.0

Returns

[OTF2_CALLBACK_SUCCESS](#) or [OTF2_CALLBACK_INTERRUPT](#).

J.12.2.22 `typedef OTF2_CallbackCode(* OTF2_EvtReaderCallback_
OmpTaskSwitch)(OTF2_LocationRef location, OTF2_TimeStamp
time, uint64_t eventPosition, void *userData, OTF2_AttributeList
*attributeList, uint64_t taskID)`

Callback for the OmpTaskSwitch event record.

APPENDIX J. FILE DOCUMENTATION

An `OmpTaskSwitch` record indicates that the execution of the current task will be suspended and another task starts/restarts its execution. Please note that this may change the current call stack of the executing location.

This event record is superseded by the [ThreadTaskSwitch](#) event record and should not be used when the [ThreadTaskSwitch](#) event record is in use.

Parameters

| | |
|----------------------|---|
| <i>location</i> | The location where this event happened. |
| <i>time</i> | The time when this event happened. |
| <i>eventPosition</i> | The event position of this event in the trace. Starting with 1. |
| <i>userData</i> | User data as set by OTF2_Reader_RegisterEvtCallbacks or OTF2_EvtReader_SetCallbacks . |
| <i>attributeList</i> | Additional attributes for this event. |
| <i>taskID</i> | Identifier of the now active task instance. |

Since

Version 1.0

Returns

[OTF2_CALLBACK_SUCCESS](#) or [OTF2_CALLBACK_INTERRUPT](#).

J.12.2.23 `typedef OTF2_CallbackCode(* OTF2_EvtReaderCallback_ParameterInt)(OTF2_LocationRef location, OTF2_TimeStamp time, uint64_t eventPosition, void *userData, OTF2_AttributeList *attributeList, OTF2_ParameterRef parameter, int64_t value)`

Callback for the `ParameterInt` event record.

A `ParameterInt` record marks that in the current region, the specified integer parameter has the specified value.

Parameters

| | |
|----------------------|---|
| <i>location</i> | The location where this event happened. |
| <i>time</i> | The time when this event happened. |
| <i>eventPosition</i> | The event position of this event in the trace. Starting with 1. |
| <i>userData</i> | User data as set by OTF2_Reader_RegisterEvtCallbacks or OTF2_EvtReader_SetCallbacks . |
| <i>attributeList</i> | Additional attributes for this event. |

J.12 OTF2_EvtReaderCallbacks.h File Reference

| | |
|------------------|---|
| <i>parameter</i> | Parameter ID. References a Parameter definition and will be mapped to the global definition if a mapping table of type OTF2_MAPPING_PARAMETER is available. |
| <i>value</i> | Value of the recorded parameter. |

Since

Version 1.0

Returns

[OTF2_CALLBACK_SUCCESS](#) or [OTF2_CALLBACK_INTERRUPT](#).

J.12.2.24 `typedef OTF2_CallbackCode(* OTF2_EvtReaderCallback_
ParameterString)(OTF2_LocationRef location, OTF2_TimeStamp
time, uint64_t eventPosition, void *userData, OTF2_AttributeList
*attributeList, OTF2_ParameterRef parameter, OTF2_StringRef string)`

Callback for the ParameterString event record.

A ParameterString record marks that in the current region, the specified string parameter has the specified value.

Parameters

| | |
|----------------------|--|
| <i>location</i> | The location where this event happened. |
| <i>time</i> | The time when this event happened. |
| <i>eventPosition</i> | The event position of this event in the trace. Starting with 1. |
| <i>userData</i> | User data as set by OTF2_Reader_RegisterEvtCallbacks or OTF2_EvtReader_SetCallbacks . |
| <i>attributeList</i> | Additional attributes for this event. |
| <i>parameter</i> | Parameter ID. References a Parameter definition and will be mapped to the global definition if a mapping table of type OTF2_MAPPING_PARAMETER is available. |
| <i>string</i> | Value: Handle of a string definition References a String definition and will be mapped to the global definition if a mapping table of type OTF2_MAPPING_STRING is available. |

Since

Version 1.0

APPENDIX J. FILE DOCUMENTATION

Returns

[OTF2_CALLBACK_SUCCESS](#) or [OTF2_CALLBACK_INTERRUPT](#).

J.12.2.25 `typedef OTF2_CallbackCode(* OTF2_EvtReaderCallback_
ParameterUnsignedInt)(OTF2_LocationRef location,
OTF2_TimeStamp time, uint64_t eventPosition, void *userData,
OTF2_AttributeList *attributeList, OTF2_ParameterRef parameter,
uint64_t value)`

Callback for the ParameterUnsignedInt event record.

A ParameterUnsignedInt record marks that in the current region, the specified unsigned integer parameter has the specified value.

Parameters

| | |
|----------------------|---|
| <i>location</i> | The location where this event happened. |
| <i>time</i> | The time when this event happened. |
| <i>eventPosition</i> | The event position of this event in the trace. Starting with 1. |
| <i>userData</i> | User data as set by OTF2_Reader_RegisterEvtCallbacks or OTF2_EvtReader_SetCallbacks . |
| <i>attributeList</i> | Additional attributes for this event. |
| <i>parameter</i> | Parameter ID. References a Parameter definition and will be mapped to the global definition if a mapping table of type OTF2_MAPPING_PARAMETER is available. |
| <i>value</i> | Value of the recorded parameter. |

Since

Version 1.0

Returns

[OTF2_CALLBACK_SUCCESS](#) or [OTF2_CALLBACK_INTERRUPT](#).

J.12.2.26 `typedef OTF2_CallbackCode(* OTF2_EvtReaderCallback_
RmaAcquireLock)(OTF2_LocationRef location, OTF2_TimeStamp
time, uint64_t eventPosition, void *userData, OTF2_AttributeList
*attributeList, OTF2_RmaWinRef win, uint32_t remote, uint64_t lockId,
OTF2_LockType lockType)`

Callback for the RmaAcquireLock event record.

J.12 OTF2_EvtReaderCallbacks.h File Reference

An RmaAcquireLock record denotes the time a lock was acquired by the process.

Parameters

| | |
|----------------------|--|
| <i>location</i> | The location where this event happened. |
| <i>time</i> | The time when this event happened. |
| <i>eventPosition</i> | The event position of this event in the trace. Starting with 1. |
| <i>userData</i> | User data as set by OTF2_Reader_RegisterEvtCallbacks or OTF2_EvtReader_SetCallbacks . |
| <i>attributeList</i> | Additional attributes for this event. |
| <i>win</i> | ID of the window used for this operation. References a RmaWin definition and will be mapped to the global definition if a mapping table of type OTF2_MAPPING_RMA_WIN is available. |
| <i>remote</i> | Rank of the locked remote process. |
| <i>lockId</i> | ID of the lock acquired, if multiple locks are defined on a window. |
| <i>lockType</i> | Type of lock acquired. |

Since

Version 1.2

Returns

[OTF2_CALLBACK_SUCCESS](#) or [OTF2_CALLBACK_INTERRUPT](#).

J.12.2.27 **typedef OTF2_CallbackCode(* OTF2_EvtReaderCallback_
RmaAtomic)(OTF2_LocationRef location, OTF2_TimeStamp time,
uint64_t eventPosition, void *userData, OTF2_AttributeList *attributeList,
OTF2_RmaWinRef win, uint32_t remote, OTF2_RmaAtomicType type,
uint64_t bytesSent, uint64_t bytesReceived, uint64_t matchingId)**

Callback for the RmaAtomic event record.

An RmaAtomic record denotes the time a atomic operation was issued.

Parameters

| | |
|----------------------|---|
| <i>location</i> | The location where this event happened. |
| <i>time</i> | The time when this event happened. |
| <i>eventPosition</i> | The event position of this event in the trace. Starting with 1. |
| <i>userData</i> | User data as set by OTF2_Reader_RegisterEvtCallbacks or OTF2_EvtReader_SetCallbacks . |
| <i>attributeList</i> | Additional attributes for this event. |

APPENDIX J. FILE DOCUMENTATION

| | |
|----------------------|--|
| <i>win</i> | ID of the window used for this operation. References a RmaWin definition and will be mapped to the global definition if a mapping table of type OTF2_MAPPING_RMA_WIN is available. |
| <i>remote</i> | Rank of the target process. |
| <i>type</i> | Type of atomic operation. |
| <i>bytesSent</i> | Bytes sent to target. |
| <i>bytesReceived</i> | Bytes received from target. |
| <i>matchingId</i> | ID used for matching the appropriate completion record. |

Since

Version 1.2

Returns

[OTF2_CALLBACK_SUCCESS](#) or [OTF2_CALLBACK_INTERRUPT](#).

J.12.2.28 `typedef OTF2_CallbackCode(* OTF2_EvtReaderCallback_
RmaCollectiveBegin)(OTF2_LocationRef location, OTF2_TimeStamp
time, uint64_t eventPosition, void *userData, OTF2_AttributeList
*attributeList)`

Callback for the RmaCollectiveBegin event record.

An RmaCollectiveBegin record denotes the beginning of a collective RMA operation.

Parameters

| | |
|----------------------|---|
| <i>location</i> | The location where this event happened. |
| <i>time</i> | The time when this event happened. |
| <i>eventPosition</i> | The event position of this event in the trace. Starting with 1. |
| <i>userData</i> | User data as set by OTF2_Reader_RegisterEvtCallbacks or OTF2_EvtReader_SetCallbacks . |
| <i>attributeList</i> | Additional attributes for this event. |

Since

Version 1.2

Returns

[OTF2_CALLBACK_SUCCESS](#) or [OTF2_CALLBACK_INTERRUPT](#).

J.12 OTF2_EvtReaderCallbacks.h File Reference

J.12.2.29 `typedef OTF2_CallbackCode(* OTF2_EvtReaderCallback_-
RmaCollectiveEnd)(OTF2_LocationRef location, OTF2_TimeStamp
time, uint64_t eventPosition, void *userData, OTF2_AttributeList
*attributeList, OTF2_CollectiveOp collectiveOp, OTF2_RmaSyncLevel
syncLevel, OTF2_RmaWinRef win, uint32_t root, uint64_t bytesSent, uint64_t
bytesReceived)`

Callback for the RmaCollectiveEnd event record.

"An RmaCollectiveEnd record denotes the end of a collective RMA operation.

Parameters

| | |
|----------------------|--|
| <i>location</i> | The location where this event happened. |
| <i>time</i> | The time when this event happened. |
| <i>eventPosition</i> | The event position of this event in the trace. Starting with 1. |
| <i>userData</i> | User data as set by OTF2_Reader_RegisterEvtCallbacks or OTF2_EvtReader_SetCallbacks . |
| <i>attributeList</i> | Additional attributes for this event. |
| <i>collectiveOp</i> | Determines which collective operation it is. |
| <i>syncLevel</i> | Synchronization level of this collective operation. |
| <i>win</i> | ID of the window used for this operation. References a RmaWin definition and will be mapped to the global definition if a mapping table of type OTF2_MAPPING_RMA_WIN is available. |
| <i>root</i> | Root process for this operation. |
| <i>bytesSent</i> | Bytes sent in operation. |
| <i>bytesReceived</i> | Bytes receives in operation. |

Since

Version 1.2

Returns

[OTF2_CALLBACK_SUCCESS](#) or [OTF2_CALLBACK_INTERRUPT](#).

J.12.2.30 `typedef OTF2_CallbackCode(* OTF2_EvtReaderCallback_-
RmaGet)(OTF2_LocationRef location, OTF2_TimeStamp time,
uint64_t eventPosition, void *userData, OTF2_AttributeList *attributeList,
OTF2_RmaWinRef win, uint32_t remote, uint64_t bytes, uint64_t matchingId)`

Callback for the RmaGet event record.

APPENDIX J. FILE DOCUMENTATION

An RmaGet record denotes the time a put operation was issued.

Parameters

| | |
|----------------------|--|
| <i>location</i> | The location where this event happened. |
| <i>time</i> | The time when this event happened. |
| <i>eventPosition</i> | The event position of this event in the trace. Starting with 1. |
| <i>userData</i> | User data as set by OTF2_Reader_RegisterEvtCallbacks or OTF2_EvtReader_SetCallbacks . |
| <i>attributeList</i> | Additional attributes for this event. |
| <i>win</i> | ID of the window used for this operation. References a RmaWin definition and will be mapped to the global definition if a mapping table of type OTF2_MAPPING_RMA_WIN is available. |
| <i>remote</i> | Rank of the target process. |
| <i>bytes</i> | Bytes received from target. |
| <i>matchingId</i> | ID used for matching the appropriate completion record. |

Since

Version 1.2

Returns

[OTF2_CALLBACK_SUCCESS](#) or [OTF2_CALLBACK_INTERRUPT](#).

J.12.231 `typedef OTF2_CallbackCode(* OTF2_EvtReaderCallback_
RmaGroupSync)(OTF2_LocationRef location, OTF2_TimeStamp
time, uint64_t eventPosition, void *userData, OTF2_AttributeList
*attributeList, OTF2_RmaSyncLevel syncLevel, OTF2_RmaWinRef win,
OTF2_GroupRef group)`

Callback for the RmaGroupSync event record.

An RmaGroupSync record denotes the synchronization with a subgroup of processes on a window.

Parameters

| | |
|----------------------|---|
| <i>location</i> | The location where this event happened. |
| <i>time</i> | The time when this event happened. |
| <i>eventPosition</i> | The event position of this event in the trace. Starting with 1. |
| <i>userData</i> | User data as set by OTF2_Reader_RegisterEvtCallbacks or OTF2_EvtReader_SetCallbacks . |

J.12 OTF2_EvtReaderCallbacks.h File Reference

| | |
|----------------------|--|
| <i>attributeList</i> | Additional attributes for this event. |
| <i>syncLevel</i> | Synchronization level of this collective operation. |
| <i>win</i> | ID of the window used for this operation. References a RmaWin definition and will be mapped to the global definition if a mapping table of type OTF2_MAPPING_RMA_WIN is available. |
| <i>group</i> | Group of remote processes involved in synchronization. References a Group definition and will be mapped to the global definition if a mapping table of type OTF2_MAPPING_GROUP is available. |

Since

Version 1.2

Returns

[OTF2_CALLBACK_SUCCESS](#) or [OTF2_CALLBACK_INTERRUPT](#).

J.12.2.32 `typedef OTF2_CallbackCode(* OTF2_EvtReaderCallback_ -
RmaOpCompleteBlocking)(OTF2_LocationRef location,
OTF2_TimeStamp time, uint64_t eventPosition, void *userData,
OTF2_AttributeList *attributeList, OTF2_RmaWinRef win, uint64_t
matchingId)`

Callback for the RmaOpCompleteBlocking event record.

An RmaOpCompleteBlocking record denotes the local completion of a blocking RMA operation.

Parameters

| | |
|----------------------|--|
| <i>location</i> | The location where this event happened. |
| <i>time</i> | The time when this event happened. |
| <i>eventPosition</i> | The event position of this event in the trace. Starting with 1. |
| <i>userData</i> | User data as set by OTF2_Reader_RegisterEvtCallbacks or OTF2_EvtReader_SetCallbacks . |
| <i>attributeList</i> | Additional attributes for this event. |
| <i>win</i> | ID of the window used for this operation. References a RmaWin definition and will be mapped to the global definition if a mapping table of type OTF2_MAPPING_RMA_WIN is available. |
| <i>matchingId</i> | ID used for matching the appropriate completion record. |

Since

Version 1.2

Returns

OTF2_CALLBACK_SUCCESS or *OTF2_CALLBACK_INTERRUPT*.

J.12.2.33 typedef OTF2_CallbackCode(* OTF2_EvtReaderCallback_
RmaOpCompleteNonBlocking)(OTF2_LocationRef location,
OTF2_TimeStamp time, uint64_t eventPosition, void *userData,
OTF2_AttributeList *attributeList, OTF2_RmaWinRef win, uint64_t
matchingId)

Callback for the RmaOpCompleteNonBlocking event record.

An RmaOpCompleteNonBlocking record denotes the local completion of a non-blocking RMA operation.

Parameters

| | |
|----------------------|--|
| <i>location</i> | The location where this event happened. |
| <i>time</i> | The time when this event happened. |
| <i>eventPosition</i> | The event position of this event in the trace. Starting with 1. |
| <i>userData</i> | User data as set by OTF2_Reader_RegisterEvtCallbacks or OTF2_EvtReader_SetCallbacks . |
| <i>attributeList</i> | Additional attributes for this event. |
| <i>win</i> | ID of the window used for this operation. References a RmaWin definition and will be mapped to the global definition if a mapping table of type OTF2_MAPPING_RMA_WIN is available. |
| <i>matchingId</i> | ID used for matching the appropriate completion record. |

Since

Version 1.2

Returns

OTF2_CALLBACK_SUCCESS or *OTF2_CALLBACK_INTERRUPT*.

J.12 OTF2_EvtReaderCallbacks.h File Reference

J.12.2.34 `typedef OTF2_CallbackCode(* OTF2_EvtReaderCallback_-RmaOpCompleteRemote)(OTF2_LocationRef location, OTF2_TimeStamp time, uint64_t eventPosition, void *userData, OTF2_AttributeList *attributeList, OTF2_RmaWinRef win, uint64_t matchingId)`

Callback for the RmaOpCompleteRemote event record.

An RmaOpCompleteRemote record denotes the local completion of an RMA operation.

Parameters

| | |
|----------------------|--|
| <i>location</i> | The location where this event happened. |
| <i>time</i> | The time when this event happened. |
| <i>eventPosition</i> | The event position of this event in the trace. Starting with 1. |
| <i>userData</i> | User data as set by OTF2_Reader_RegisterEvtCallbacks or OTF2_EvtReader_SetCallbacks . |
| <i>attributeList</i> | Additional attributes for this event. |
| <i>win</i> | ID of the window used for this operation. References a RmaWin definition and will be mapped to the global definition if a mapping table of type OTF2_MAPPING_RMA_WIN is available. |
| <i>matchingId</i> | ID used for matching the appropriate completion record. |

Since

Version 1.2

Returns

[OTF2_CALLBACK_SUCCESS](#) or [OTF2_CALLBACK_INTERRUPT](#).

J.12.2.35 `typedef OTF2_CallbackCode(* OTF2_EvtReaderCallback_-RmaOpTest)(OTF2_LocationRef location, OTF2_TimeStamp time, uint64_t eventPosition, void *userData, OTF2_AttributeList *attributeList, OTF2_RmaWinRef win, uint64_t matchingId)`

Callback for the RmaOpTest event record.

An RmaOpTest record denotes that a non-blocking RMA operation has been tested for completion unsuccessfully.

Parameters

APPENDIX J. FILE DOCUMENTATION

| | |
|----------------------|--|
| <i>location</i> | The location where this event happened. |
| <i>time</i> | The time when this event happened. |
| <i>eventPosition</i> | The event position of this event in the trace. Starting with 1. |
| <i>userData</i> | User data as set by OTF2_Reader_RegisterEvtCallbacks or OTF2_EvtReader_SetCallbacks . |
| <i>attributeList</i> | Additional attributes for this event. |
| <i>win</i> | ID of the window used for this operation. References a RmaWin definition and will be mapped to the global definition if a mapping table of type OTF2_MAPPING_RMA_WIN is available. |
| <i>matchingId</i> | ID used for matching the appropriate completion record. |

Since

Version 1.2

Returns

[OTF2_CALLBACK_SUCCESS](#) or [OTF2_CALLBACK_INTERRUPT](#).

J.12.2.36 `typedef OTF2_CallbackCode(* OTF2_EvtReaderCallback_RmaPut)(OTF2_LocationRef location, OTF2_TimeStamp time, uint64_t eventPosition, void *userData, OTF2_AttributeList *attributeList, OTF2_RmaWinRef win, uint32_t remote, uint64_t bytes, uint64_t matchingId)`

Callback for the RmaPut event record.

An RmaPut record denotes the time a put operation was issued.

Parameters

| | |
|----------------------|--|
| <i>location</i> | The location where this event happened. |
| <i>time</i> | The time when this event happened. |
| <i>eventPosition</i> | The event position of this event in the trace. Starting with 1. |
| <i>userData</i> | User data as set by OTF2_Reader_RegisterEvtCallbacks or OTF2_EvtReader_SetCallbacks . |
| <i>attributeList</i> | Additional attributes for this event. |
| <i>win</i> | ID of the window used for this operation. References a RmaWin definition and will be mapped to the global definition if a mapping table of type OTF2_MAPPING_RMA_WIN is available. |
| <i>remote</i> | Rank of the target process. |
| <i>bytes</i> | Bytes sent to target. |
| <i>matchingId</i> | ID used for matching the appropriate completion record. |

J.12 OTF2_EvtReaderCallbacks.h File Reference

Since

Version 1.2

Returns

[OTF2_CALLBACK_SUCCESS](#) or [OTF2_CALLBACK_INTERRUPT](#).

J.12.2.37 `typedef OTF2_CallbackCode(* OTF2_EvtReaderCallback_
RmaReleaseLock)(OTF2_LocationRef location, OTF2_TimeStamp
time, uint64_t eventPosition, void *userData, OTF2_AttributeList
*attributeList, OTF2_RmaWinRef win, uint32_t remote, uint64_t lockId)`

Callback for the RmaReleaseLock event record.

An RmaReleaseLock record denotes the time the lock was released.

Parameters

| | |
|----------------------|--|
| <i>location</i> | The location where this event happened. |
| <i>time</i> | The time when this event happened. |
| <i>eventPosition</i> | The event position of this event in the trace. Starting with 1. |
| <i>userData</i> | User data as set by OTF2_Reader_RegisterEvtCallbacks or OTF2_EvtReader_SetCallbacks . |
| <i>attributeList</i> | Additional attributes for this event. |
| <i>win</i> | ID of the window used for this operation. References a RmaWin definition and will be mapped to the global definition if a mapping table of type OTF2_MAPPING_RMA_WIN is available. |
| <i>remote</i> | Rank of the locked remote process. |
| <i>lockId</i> | ID of the lock released, if multiple locks are defined on a window. |

Since

Version 1.2

Returns

[OTF2_CALLBACK_SUCCESS](#) or [OTF2_CALLBACK_INTERRUPT](#).

J.12.2.38 `typedef OTF2_CallbackCode(* OTF2_EvtReaderCallback_
RmaRequestLock)(OTF2_LocationRef location, OTF2_TimeStamp
time, uint64_t eventPosition, void *userData, OTF2_AttributeList
*attributeList, OTF2_RmaWinRef win, uint32_t remote, uint64_t lockId,
OTF2_LockType lockType)`

Callback for the RmaRequestLock event record.

An RmaRequestLock record denotes the time a lock was requested and with it the earliest time it could have been granted. It is used to mark (possibly) non-blocking lock request, as defined by the MPI standard.

Parameters

| | |
|----------------------|--|
| <i>location</i> | The location where this event happened. |
| <i>time</i> | The time when this event happened. |
| <i>eventPosition</i> | The event position of this event in the trace. Starting with 1. |
| <i>userData</i> | User data as set by OTF2_Reader_RegisterEvtCallbacks or OTF2_EvtReader_SetCallbacks . |
| <i>attributeList</i> | Additional attributes for this event. |
| <i>win</i> | ID of the window used for this operation. References a RmaWin definition and will be mapped to the global definition if a mapping table of type OTF2_MAPPING_RMA_WIN is available. |
| <i>remote</i> | Rank of the locked remote process. |
| <i>lockId</i> | ID of the lock acquired, if multiple locks are defined on a window. |
| <i>lockType</i> | Type of lock acquired. |

Since

Version 1.2

Returns

[OTF2_CALLBACK_SUCCESS](#) or [OTF2_CALLBACK_INTERRUPT](#).

J.12.2.39 `typedef OTF2_CallbackCode(* OTF2_EvtReaderCallback_
RmaSync)(OTF2_LocationRef location, OTF2_TimeStamp time,
uint64_t eventPosition, void *userData, OTF2_AttributeList *attributeList,
OTF2_RmaWinRef win, uint32_t remote, OTF2_RmaSyncType
syncType)`

Callback for the RmaSync event record.

An RmaSync record denotes the direct synchronization with a possibly remote process.

J.12 OTF2_EvtReaderCallbacks.h File Reference

Parameters

| | |
|----------------------|--|
| <i>location</i> | The location where this event happened. |
| <i>time</i> | The time when this event happened. |
| <i>eventPosition</i> | The event position of this event in the trace. Starting with 1. |
| <i>userData</i> | User data as set by OTF2_Reader_RegisterEvtCallbacks or OTF2_EvtReader_SetCallbacks . |
| <i>attributeList</i> | Additional attributes for this event. |
| <i>win</i> | ID of the window used for this operation. References a RmaWin definition and will be mapped to the global definition if a mapping table of type OTF2_MAPPING_RMA_WIN is available. |
| <i>remote</i> | Rank of the locked remote process. |
| <i>syncType</i> | Type of synchronization. |

Since

Version 1.2

Returns

[OTF2_CALLBACK_SUCCESS](#) or [OTF2_CALLBACK_INTERRUPT](#).

J.12.2.40 `typedef OTF2_CallbackCode(* OTF2_EvtReaderCallback_
RmaTryLock)(OTF2_LocationRef location, OTF2_TimeStamp time,
uint64_t eventPosition, void *userData, OTF2_AttributeList *attributeList,
OTF2_RmaWinRef win, uint32_t remote, uint64_t lockId, OTF2_LockType
lockType)`

Callback for the RmaTryLock event record.

An RmaTryLock record denotes the time of an unsuccessful attempt to acquire the lock.

Parameters

| | |
|----------------------|--|
| <i>location</i> | The location where this event happened. |
| <i>time</i> | The time when this event happened. |
| <i>eventPosition</i> | The event position of this event in the trace. Starting with 1. |
| <i>userData</i> | User data as set by OTF2_Reader_RegisterEvtCallbacks or OTF2_EvtReader_SetCallbacks . |
| <i>attributeList</i> | Additional attributes for this event. |
| <i>win</i> | ID of the window used for this operation. References a RmaWin definition and will be mapped to the global definition if a mapping table of type OTF2_MAPPING_RMA_WIN is available. |

APPENDIX J. FILE DOCUMENTATION

| | |
|-----------------|---|
| <i>remote</i> | Rank of the locked remote process. |
| <i>lockId</i> | ID of the lock acquired, if multiple locks are defined on a window. |
| <i>lockType</i> | Type of lock acquired. |

Since

Version 1.2

Returns

[OTF2_CALLBACK_SUCCESS](#) or [OTF2_CALLBACK_INTERRUPT](#).

J.12.2.41 `typedef OTF2_CallbackCode(* OTF2_EvtReaderCallback_
RmaWaitChange)(OTF2_LocationRef location, OTF2_TimeStamp
time, uint64_t eventPosition, void *userData, OTF2_AttributeList
*attributeList, OTF2_RmaWinRef win)`

Callback for the RmaWaitChange event record.

An RmaWaitChange record denotes the change of a window that was waited for.

Parameters

| | |
|----------------------|--|
| <i>location</i> | The location where this event happened. |
| <i>time</i> | The time when this event happened. |
| <i>eventPosition</i> | The event position of this event in the trace. Starting with 1. |
| <i>userData</i> | User data as set by OTF2_Reader_RegisterEvtCallbacks or OTF2_EvtReader_SetCallbacks . |
| <i>attributeList</i> | Additional attributes for this event. |
| <i>win</i> | ID of the window used for this operation. References a RmaWin definition and will be mapped to the global definition if a mapping table of type OTF2_MAPPING_RMA_WIN is available. |

Since

Version 1.2

Returns

[OTF2_CALLBACK_SUCCESS](#) or [OTF2_CALLBACK_INTERRUPT](#).

J.12 OTF2_EvtReaderCallbacks.h File Reference

J.12.2.42 `typedef OTF2_CallbackCode(* OTF2_EvtReaderCallback_
RmaWinCreate)(OTF2_LocationRef location, OTF2_TimeStamp time,
uint64_t eventPosition, void *userData, OTF2_AttributeList *attributeList,
OTF2_RmaWinRef win)`

Callback for the RmaWinCreate event record.

An RmaWinCreate record denotes the creation of an RMA window.

Parameters

| | |
|----------------------|--|
| <i>location</i> | The location where this event happened. |
| <i>time</i> | The time when this event happened. |
| <i>eventPosition</i> | The event position of this event in the trace. Starting with 1. |
| <i>userData</i> | User data as set by OTF2_Reader_RegisterEvtCallbacks or OTF2_EvtReader_SetCallbacks . |
| <i>attributeList</i> | Additional attributes for this event. |
| <i>win</i> | ID of the window created. References a RmaWin definition and will be mapped to the global definition if a mapping table of type OTF2_MAPPING_RMA_WIN is available. |

Since

Version 1.2

Returns

[OTF2_CALLBACK_SUCCESS](#) or [OTF2_CALLBACK_INTERRUPT](#).

J.12.2.43 `typedef OTF2_CallbackCode(* OTF2_EvtReaderCallback_
RmaWinDestroy)(OTF2_LocationRef location, OTF2_TimeStamp
time, uint64_t eventPosition, void *userData, OTF2_AttributeList
*attributeList, OTF2_RmaWinRef win)`

Callback for the RmaWinDestroy event record.

An RmaWinDestroy record denotes the destruction of an RMA window.

Parameters

| | |
|----------------------|---|
| <i>location</i> | The location where this event happened. |
| <i>time</i> | The time when this event happened. |
| <i>eventPosition</i> | The event position of this event in the trace. Starting with 1. |

APPENDIX J. FILE DOCUMENTATION

| | |
|----------------------|---|
| <i>userData</i> | User data as set by OTF2_Reader_RegisterEvtCallbacks or OTF2_EvtReader_SetCallbacks . |
| <i>attributeList</i> | Additional attributes for this event. |
| <i>win</i> | ID of the window destructed. References a RmaWin definition and will be mapped to the global definition if a mapping table of type OTF2_MAPPING_RMA_WIN is available. |

Since

Version 1.2

Returns

[OTF2_CALLBACK_SUCCESS](#) or [OTF2_CALLBACK_INTERRUPT](#).

J.12.2.44 `typedef OTF2_CallbackCode(* OTF2_EvtReaderCallback_ThreadAcquireLock)(OTF2_LocationRef location, OTF2_TimeStamp time, uint64_t eventPosition, void *userData, OTF2_AttributeList *attributeList, OTF2_Paradigm model, uint32_t lockID, uint32_t acquisitionOrder)`

Callback for the ThreadAcquireLock event record.

An ThreadAcquireLock record marks that a thread acquires an lock.

Parameters

| | |
|-------------------------|---|
| <i>location</i> | The location where this event happened. |
| <i>time</i> | The time when this event happened. |
| <i>eventPosition</i> | The event position of this event in the trace. Starting with 1. |
| <i>userData</i> | User data as set by OTF2_Reader_RegisterEvtCallbacks or OTF2_EvtReader_SetCallbacks . |
| <i>attributeList</i> | Additional attributes for this event. |
| <i>lockID</i> | ID of the lock. |
| <i>acquisitionOrder</i> | A monotonically increasing number to determine the order of lock acquisitions (with unsynchronized clocks this is otherwise not possible). Corresponding acquire-release events have same number. |

Since

Version 1.2

J.12 OTF2_EvtReaderCallbacks.h File Reference

Returns

[OTF2_CALLBACK_SUCCESS](#) or [OTF2_CALLBACK_INTERRUPT](#).

J.12.2.45 `typedef OTF2_CallbackCode(* OTF2_EvtReaderCallback_ - ThreadFork)(OTF2_LocationRef location, OTF2_TimeStamp time, uint64_t eventPosition, void *userData, OTF2_AttributeList *attributeList, OTF2_Paradigm model, uint32_t numberOfRequestedThreads)`

Callback for the ThreadFork event record.

An ThreadFork record marks that an thread forks a thread team.

Parameters

| | |
|---------------------------------|---|
| <i>location</i> | The location where this event happened. |
| <i>time</i> | The time when this event happened. |
| <i>eventPosition</i> | The event position of this event in the trace. Starting with 1. |
| <i>userData</i> | User data as set by OTF2_Reader_RegisterEvtCallbacks or OTF2_EvtReader_SetCallbacks . |
| <i>attributeList</i> | Additional attributes for this event. |
| <i>numberOfRequestedThreads</i> | Requested size of the team. |

Since

Version 1.2

Returns

[OTF2_CALLBACK_SUCCESS](#) or [OTF2_CALLBACK_INTERRUPT](#).

J.12.2.46 `typedef OTF2_CallbackCode(* OTF2_EvtReaderCallback_ - ThreadJoin)(OTF2_LocationRef location, OTF2_TimeStamp time, uint64_t eventPosition, void *userData, OTF2_AttributeList *attributeList, OTF2_Paradigm model)`

Callback for the ThreadJoin event record.

An ThreadJoin record marks that a team of threads is joint and only the master thread continues execution.

APPENDIX J. FILE DOCUMENTATION

Parameters

| | |
|----------------------|--|
| <i>location</i> | The location where this event happened. |
| <i>time</i> | The time when this event happened. |
| <i>eventPosition</i> | The event position of this event in the trace. Starting with 1. |
| <i>userData</i> | User data as set by OTF2_Reader_RegisterEvtCallbacks or OTF2_-EvtReader_SetCallbacks . |
| <i>attributeList</i> | Additional attributes for this event. |

Since

Version 1.2

Returns

[OTF2_CALLBACK_SUCCESS](#) or [OTF2_CALLBACK_INTERRUPT](#).

J.12.2.47 `typedef OTF2_CallbackCode(* OTF2_EvtReaderCallback_ - ThreadReleaseLock)(OTF2_LocationRef location, OTF2_TimeStamp time, uint64_t eventPosition, void *userData, OTF2_AttributeList *attributeList, OTF2_Paradigm model, uint32_t lockID, uint32_t acquisitionOrder)`

Callback for the ThreadReleaseLock event record.

An ThreadReleaseLock record marks that a thread releases an lock.

Parameters

| | |
|-------------------------|---|
| <i>location</i> | The location where this event happened. |
| <i>time</i> | The time when this event happened. |
| <i>eventPosition</i> | The event position of this event in the trace. Starting with 1. |
| <i>userData</i> | User data as set by OTF2_Reader_RegisterEvtCallbacks or OTF2_-EvtReader_SetCallbacks . |
| <i>attributeList</i> | Additional attributes for this event. |
| <i>lockID</i> | ID of the lock. |
| <i>acquisitionOrder</i> | A monotonically increasing number to determine the order of lock acquisitions (with unsynchronized clocks this is otherwise not possible). Corresponding acquire-release events have same number. |

Since

Version 1.2

J.12 OTF2_EvtReaderCallbacks.h File Reference

Returns

[OTF2_CALLBACK_SUCCESS](#) or [OTF2_CALLBACK_INTERRUPT](#).

J.12.2.48 typedef OTF2_CallbackCode(* OTF2_EvtReaderCallback_
ThreadTaskComplete)(OTF2_LocationRef location,
OTF2_TimeStamp time, uint64_t eventPosition, void *userData,
OTF2_AttributeList *attributeList, OTF2_CommRef threadTeam, uint32_t
creatingThread, uint32_t generationNumber)

Callback for the ThreadTaskComplete event record.

An ThreadTaskComplete record indicates that the execution of an OpenMP task has finished.

Parameters

| | |
|-------------------------|---|
| <i>location</i> | The location where this event happened. |
| <i>time</i> | The time when this event happened. |
| <i>eventPosition</i> | The event position of this event in the trace. Starting with 1. |
| <i>userData</i> | User data as set by OTF2_Reader_RegisterEvtCallbacks or OTF2_EvtReader_SetCallbacks . |
| <i>attributeList</i> | Additional attributes for this event. |
| <i>threadTeam</i> | Thread team References a Comm definition and will be mapped to the global definition if a mapping table of type OTF2_MAPPING_COMM is available. |
| <i>creatingThread</i> | Creating thread of this task. |
| <i>generationNumber</i> | Thread-private generation number of task's creating thread. |

Since

Version 1.2

Returns

[OTF2_CALLBACK_SUCCESS](#) or [OTF2_CALLBACK_INTERRUPT](#).

APPENDIX J. FILE DOCUMENTATION

J.12.2.49 `typedef OTF2_CallbackCode(* OTF2_EvtReaderCallback_ - ThreadTaskCreate)(OTF2_LocationRef location, OTF2_TimeStamp time, uint64_t eventPosition, void *userData, OTF2_AttributeList *attributeList, OTF2_CommRef threadTeam, uint32_t creatingThread, uint32_t generationNumber)`

Callback for the ThreadTaskCreate event record.

An ThreadTaskCreate record marks that an task in was/will be created and will be processed by the specified thread team.

Parameters

| | |
|-------------------------|---|
| <i>location</i> | The location where this event happened. |
| <i>time</i> | The time when this event happened. |
| <i>eventPosition</i> | The event position of this event in the trace. Starting with 1. |
| <i>userData</i> | User data as set by OTF2_Reader_RegisterEvtCallbacks or OTF2_EvtReader_SetCallbacks . |
| <i>attributeList</i> | Additional attributes for this event. |
| <i>threadTeam</i> | Thread team References a Comm definition and will be mapped to the global definition if a mapping table of type OTF2_MAPPING_COMM is available. |
| <i>creatingThread</i> | Creating thread of this task. (This is redundant, remove?) |
| <i>generationNumber</i> | Thread-private generation number of task's creating thread. |

Since

Version 1.2

Returns

[OTF2_CALLBACK_SUCCESS](#) or [OTF2_CALLBACK_INTERRUPT](#).

J.12.2.50 `typedef OTF2_CallbackCode(* OTF2_EvtReaderCallback_ - ThreadTaskSwitch)(OTF2_LocationRef location, OTF2_TimeStamp time, uint64_t eventPosition, void *userData, OTF2_AttributeList *attributeList, OTF2_CommRef threadTeam, uint32_t creatingThread, uint32_t generationNumber)`

Callback for the ThreadTaskSwitch event record.

J.12 OTF2_EvtReaderCallbacks.h File Reference

An ThreadTaskSwitch record indicates that the execution of the current task will be suspended and another task starts/restarts its execution. Please note that this may change the current call stack of the executing location.

Parameters

| | |
|-------------------------|---|
| <i>location</i> | The location where this event happened. |
| <i>time</i> | The time when this event happened. |
| <i>eventPosition</i> | The event position of this event in the trace. Starting with 1. |
| <i>userData</i> | User data as set by OTF2_Reader_RegisterEvtCallbacks or OTF2_EvtReader_SetCallbacks . |
| <i>attributeList</i> | Additional attributes for this event. |
| <i>threadTeam</i> | Thread team References a Comm definition and will be mapped to the global definition if a mapping table of type OTF2_MAPPING_COMM is available. |
| <i>creatingThread</i> | Creating thread of this task. |
| <i>generationNumber</i> | Thread-private generation number of task's creating thread. |

Since

Version 1.2

Returns

[OTF2_CALLBACK_SUCCESS](#) or [OTF2_CALLBACK_INTERRUPT](#).

J.12.2.51 `typedef OTF2_CallbackCode(* OTF2_EvtReaderCallback_ - ThreadTeamBegin)(OTF2_LocationRef location, OTF2_TimeStamp time, uint64_t eventPosition, void *userData, OTF2_AttributeList *attributeList, OTF2_CommRef threadTeam)`

Callback for the ThreadTeamBegin event record.

Parameters

| | |
|----------------------|---|
| <i>location</i> | The location where this event happened. |
| <i>time</i> | The time when this event happened. |
| <i>eventPosition</i> | The event position of this event in the trace. Starting with 1. |
| <i>userData</i> | User data as set by OTF2_Reader_RegisterEvtCallbacks or OTF2_EvtReader_SetCallbacks . |

APPENDIX J. FILE DOCUMENTATION

| | |
|----------------------|---|
| <i>attributeList</i> | Additional attributes for this event. |
| <i>threadTeam</i> | Thread team References a Comm definition and will be mapped to the global definition if a mapping table of type OTF2_MAPPING_COMM is available. |

Since

Version 1.2

Returns

[OTF2_CALLBACK_SUCCESS](#) or [OTF2_CALLBACK_INTERRUPT](#).

J.12.2.52 `typedef OTF2_CallbackCode(* OTF2_EvtReaderCallback_ -
ThreadTeamEnd)(OTF2_LocationRef location, OTF2_TimeStamp
time, uint64_t eventPosition, void *userData, OTF2_AttributeList
*attributeList, OTF2_CommRef threadTeam)`

Callback for the ThreadTeamEnd event record.

Parameters

| | |
|----------------------|---|
| <i>location</i> | The location where this event happened. |
| <i>time</i> | The time when this event happened. |
| <i>eventPosition</i> | The event position of this event in the trace. Starting with 1. |
| <i>userData</i> | User data as set by OTF2_Reader_RegisterEvtCallbacks or OTF2_- EvtReader_SetCallbacks . |
| <i>attributeList</i> | Additional attributes for this event. |
| <i>threadTeam</i> | Thread team References a Comm definition and will be mapped to the global definition if a mapping table of type OTF2_MAPPING_COMM is available. |

Since

Version 1.2

Returns

[OTF2_CALLBACK_SUCCESS](#) or [OTF2_CALLBACK_INTERRUPT](#).

J.12 OTF2_EvtReaderCallbacks.h File Reference

J.12.2.53 `typedef OTF2_CallbackCode(* OTF2_EvtReaderCallback_Unknown)(OTF2_LocationRef location, OTF2_TimeStamp time, uint64_t eventPosition, void *userData, OTF2_AttributeList *attributeList)`

Callback for an unknown event record.

Parameters

| | |
|----------------------|---|
| <i>location</i> | The location where this event happened. |
| <i>time</i> | The time when this event happened. |
| <i>eventPosition</i> | The event position of this event in the trace. Starting with 1. |
| <i>userData</i> | User data as set by OTF2_Reader_RegisterEvtCallbacks or OTF2_EvtReader_SetCallbacks . |
| <i>attributeList</i> | Additional attributes for this event. |

Returns

[OTF2_CALLBACK_SUCCESS](#) or [OTF2_CALLBACK_INTERRUPT](#).

J.12.3 Function Documentation

J.12.3.1 `void OTF2_EvtReaderCallbacks_Clear (OTF2_EvtReaderCallbacks * evtReaderCallbacks)`

Clears a struct for the event callbacks.

Parameters

| | |
|---------------------------|--|
| <i>evtReaderCallbacks</i> | Handle to a struct previously allocated with OTF2_EvtReaderCallbacks_New . |
|---------------------------|--|

J.12.3.2 `void OTF2_EvtReaderCallbacks_Delete (OTF2_EvtReaderCallbacks * evtReaderCallbacks)`

Deallocates a struct for the event callbacks.

Parameters

| | |
|---------------------------|--|
| <i>evtReaderCallbacks</i> | Handle to a struct previously allocated with OTF2_EvtReaderCallbacks_New . |
|---------------------------|--|

APPENDIX J. FILE DOCUMENTATION

J.12.3.3 `OTF2_EvtReaderCallbacks*` `OTF2.EvtReaderCallbacks_New (void)`

Allocates a new struct for the event callbacks.

Returns

A newly allocated struct of type `OTF2_EvtReaderCallbacks`.

J.12.3.4 `OTF2_ErrorCode` `OTF2_EvtReaderCallbacks_SetBufferFlushCallback` (`OTF2_EvtReaderCallbacks * evtReaderCallbacks`, `OTF2_EvtReaderCallback_BufferFlush bufferFlushCallback`)

Registers the callback for the BufferFlush event.

Parameters

| | |
|-----------------------------|---|
| <i>evtReader-Callbacks</i> | Struct for all callbacks. |
| <i>buffer-FlushCallback</i> | Function which should be called for all BufferFlush events. |

Returns

`OTF2_SUCCESS` if successful

`OTF2_ERROR_INVALID_ARGUMENT` for an invalid `defReaderCallbacks` argument

J.12.3.5 `OTF2_ErrorCode` `OTF2_EvtReaderCallbacks_SetEnterCallback` (`OTF2_EvtReaderCallbacks * evtReaderCallbacks`, `OTF2_EvtReaderCallback_Enter enterCallback`)

Registers the callback for the Enter event.

Parameters

| | |
|----------------------------|---|
| <i>evtReader-Callbacks</i> | Struct for all callbacks. |
| <i>enterCallback</i> | Function which should be called for all Enter events. |

J.12 OTF2_EvtReaderCallbacks.h File Reference

Returns

OTF2_SUCCESS if successful

OTF2_ERROR_INVALID_ARGUMENT for an invalid `defReaderCallbacks` argument

J.12.3.6 **OTF2_ErrorCode** `OTF2_EvtReaderCallbacks_SetLeaveCallback`
(**OTF2_EvtReaderCallbacks** * *evtReaderCallbacks*,
OTF2_EvtReaderCallback_Leave *leaveCallback*)

Registers the callback for the Leave event.

Parameters

| | |
|----------------------------|---|
| <i>evtReader-Callbacks</i> | Struct for all callbacks. |
| <i>leaveCall-back</i> | Function which should be called for all Leave events. |

Returns

OTF2_SUCCESS if successful

OTF2_ERROR_INVALID_ARGUMENT for an invalid `defReaderCallbacks` argument

J.12.3.7 **OTF2_ErrorCode** `OTF2_EvtReaderCallbacks_SetMeasurementOnOffCallback`
(**OTF2_EvtReaderCallbacks** * *evtReaderCallbacks*, **OTF2_-**
EvtReaderCallback_MeasurementOnOff *measurementOnOffCallback*
)

Registers the callback for the MeasurementOnOff event.

Parameters

| | |
|----------------------------------|--|
| <i>evtReader-Callbacks</i> | Struct for all callbacks. |
| <i>measurementOnOff-Callback</i> | Function which should be called for all MeasurementOnOff events. |

Returns

OTF2_SUCCESS if successful

APPENDIX J. FILE DOCUMENTATION

OTF2_ERROR_INVALID_ARGUMENT for an invalid `defReaderCallbacks` argument

J.12.3.8 **OTF2_ErrorCode** `OTF2_EvtReaderCallbacks_SetMetricCallback`
(`OTF2_EvtReaderCallbacks * evtReaderCallbacks`,
`OTF2_EvtReaderCallback_Metric metricCallback`)

Registers the callback for the Metric event.

Parameters

| | |
|----------------------------|--|
| <i>evtReader-Callbacks</i> | Struct for all callbacks. |
| <i>metricCallback</i> | Function which should be called for all Metric events. |

Returns

OTF2_SUCCESS if successful

OTF2_ERROR_INVALID_ARGUMENT for an invalid `defReaderCallbacks` argument

J.12.3.9 **OTF2_ErrorCode** `OTF2_EvtReaderCallbacks_SetMpiCollectiveBeginCallback`
(`OTF2_EvtReaderCallbacks * evtReaderCallbacks`, `OTF2_-`
`EvtReaderCallback_MpiCollectiveBegin mpiCollectiveBeginCallback`
)

Registers the callback for the MpiCollectiveBegin event.

Parameters

| | |
|-----------------------------------|--|
| <i>evtReader-Callbacks</i> | Struct for all callbacks. |
| <i>mpiCollectiveBeginCallback</i> | Function which should be called for all MpiCollectiveBegin events. |

Returns

OTF2_SUCCESS if successful

OTF2_ERROR_INVALID_ARGUMENT for an invalid `defReaderCallbacks` argument

J.12 OTF2_EvtReaderCallbacks.h File Reference

J.12.3.10 **OTF2_ErrorCode** **OTF2_EvtReaderCallbacks.SetMpiCollectiveEndCallback**
(**OTF2_EvtReaderCallbacks** * *evtReaderCallbacks*, **OTF2_-**
EvtReaderCallback_MpiCollectiveEnd *mpiCollectiveEndCallback*
)

Registers the callback for the MpiCollectiveEnd event.

Parameters

| | |
|---|--|
| <i>evtReader- Callbacks</i> | Struct for all callbacks. |
| <i>mpiCollec- tiveEnd- Callback</i> | Function which should be called for all MpiCollectiveEnd events. |

Returns

OTF2_SUCCESS if successful

OTF2_ERROR_INVALID_ARGUMENT for an invalid *defReaderCallbacks*
argument

J.12.3.11 **OTF2_ErrorCode** **OTF2_EvtReaderCallbacks.SetMpiIrecvCallback**
(**OTF2_EvtReaderCallbacks** * *evtReaderCallbacks*,
OTF2_EvtReaderCallback_MpiIrecv *mpiIrecvCallback*)

Registers the callback for the MpiIrecv event.

Parameters

| | |
|---------------------------------|--|
| <i>evtReader- Callbacks</i> | Struct for all callbacks. |
| <i>mpiIrecv- Callback</i> | Function which should be called for all MpiIrecv events. |

Returns

OTF2_SUCCESS if successful

OTF2_ERROR_INVALID_ARGUMENT for an invalid *defReaderCallbacks*
argument

J.12.3.12 `OTF2_ErrorCode OTF2_EvtReaderCallbacks.SetMpiIrecvRequestCallback (OTF2_EvtReaderCallbacks * evtReaderCallbacks, OTF2_EvtReaderCallback_MpiIrecvRequest mpilrecvRequestCallback)`

Registers the callback for the `MpiIrecvRequest` event.

Parameters

| | |
|--------------------------------|--|
| <i>evtReaderCallbacks</i> | Struct for all callbacks. |
| <i>mpilrecvRequestCallback</i> | Function which should be called for all <code>MpiIrecvRequest</code> events. |

Returns

`OTF2_SUCCESS` if successful
`OTF2_ERROR_INVALID_ARGUMENT` for an invalid `defReaderCallbacks` argument

J.12.3.13 `OTF2_ErrorCode OTF2_EvtReaderCallbacks.SetMpisendCallback (OTF2_EvtReaderCallbacks * evtReaderCallbacks, OTF2_EvtReaderCallback_MpiSend mpisendCallback)`

Registers the callback for the `MpiSend` event.

Parameters

| | |
|---------------------------|--|
| <i>evtReaderCallbacks</i> | Struct for all callbacks. |
| <i>mpisendCallback</i> | Function which should be called for all <code>MpiSend</code> events. |

Returns

`OTF2_SUCCESS` if successful
`OTF2_ERROR_INVALID_ARGUMENT` for an invalid `defReaderCallbacks` argument

J.12 OTF2_EvtReaderCallbacks.h File Reference

J.12.3.14 **OTF2_ErrorCode** **OTF2_EvtReaderCallbacks.SetMpiIsendCompleteCallback**
(**OTF2_EvtReaderCallbacks** * *evtReaderCallbacks*,
OTF2_EvtReaderCallback_MpiIsendComplete
mpiIsendCompleteCallback)

Registers the callback for the MpiIsendComplete event.

Parameters

| | |
|-----------------------------------|--|
| <i>evtReader-Callbacks</i> | Struct for all callbacks. |
| <i>mpiIsend-Complete-Callback</i> | Function which should be called for all MpiIsendComplete events. |

Returns

OTF2_SUCCESS if successful

OTF2_ERROR_INVALID_ARGUMENT for an invalid *defReaderCallbacks* argument

J.12.3.15 **OTF2_ErrorCode** **OTF2_EvtReaderCallbacks.SetMpiRecvCallback**
(**OTF2_EvtReaderCallbacks** * *evtReaderCallbacks*,
OTF2_EvtReaderCallback_MpiRecv *mpiRecvCallback*)

Registers the callback for the MpiRecv event.

Parameters

| | |
|----------------------------|---|
| <i>evtReader-Callbacks</i> | Struct for all callbacks. |
| <i>mpiRecv-Callback</i> | Function which should be called for all MpiRecv events. |

Returns

OTF2_SUCCESS if successful

OTF2_ERROR_INVALID_ARGUMENT for an invalid *defReaderCallbacks* argument

APPENDIX J. FILE DOCUMENTATION

J.12.3.16 **OTF2_ErrorCode** **OTF2_EvtReaderCallbacks_**-
SetMpiRequestCancelledCallback (**OTF2_EvtReaderCallbacks**
***** *evtReaderCallbacks*, **OTF2_EvtReaderCallback_**-
MpiRequestCancelled *mpiRequestCancelledCallback*
)

Registers the callback for the MpiRequestCancelled event.

Parameters

| | |
|--|---|
| <i>evtReader- Callbacks</i> | Struct for all callbacks. |
| <i>mpiRe- questCan- celledCall- back</i> | Function which should be called for all MpiRequestCancelled events. |

Returns

OTF2_SUCCESS if successful

OTF2_ERROR_INVALID_ARGUMENT for an invalid `defReaderCallbacks` argument

J.12.3.17 **OTF2_ErrorCode** **OTF2_EvtReaderCallbacks_****SetMpiRequestTestCallback**
(**OTF2_EvtReaderCallbacks** * *evtReaderCallbacks*,
OTF2_EvtReaderCallback_**MpiRequestTest** *mpiRequestTestCallback*)

Registers the callback for the MpiRequestTest event.

Parameters

| | |
|---|--|
| <i>evtReader- Callbacks</i> | Struct for all callbacks. |
| <i>mpiRe- questTest- Callback</i> | Function which should be called for all MpiRequestTest events. |

Returns

OTF2_SUCCESS if successful

OTF2_ERROR_INVALID_ARGUMENT for an invalid `defReaderCallbacks` argument

J.12 OTF2_EvtReaderCallbacks.h File Reference

J.12.3.18 `OTF2_ErrorCode OTF2_EvtReaderCallbacks.SetMpiSendCallback (OTF2_EvtReaderCallbacks * evtReaderCallbacks, OTF2_EvtReaderCallback_MpiSend mpiSendCallback)`

Registers the callback for the MpiSend event.

Parameters

| | |
|----------------------------|---|
| <i>evtReader-Callbacks</i> | Struct for all callbacks. |
| <i>mpiSend-Callback</i> | Function which should be called for all MpiSend events. |

Returns

`OTF2_SUCCESS` if successful

`OTF2_ERROR_INVALID_ARGUMENT` for an invalid `defReaderCallbacks` argument

J.12.3.19 `OTF2_ErrorCode OTF2_EvtReaderCallbacks.SetOmpAcquireLockCallback (OTF2_EvtReaderCallbacks * evtReaderCallbacks, OTF2_-EvtReaderCallback_OmpAcquireLock ompAcquireLockCallback)`

Registers the callback for the OmpAcquireLock event.

Parameters

| | |
|--------------------------------|--|
| <i>evtReader-Callbacks</i> | Struct for all callbacks. |
| <i>ompAcquireLock-Callback</i> | Function which should be called for all OmpAcquireLock events. |

Returns

`OTF2_SUCCESS` if successful

`OTF2_ERROR_INVALID_ARGUMENT` for an invalid `defReaderCallbacks` argument

APPENDIX J. FILE DOCUMENTATION

J.12.3.20 **OTF2_ErrorCode** **OTF2_EvtReaderCallbacks.SetOmpForkCallback**
(**OTF2_EvtReaderCallbacks** * *evtReaderCallbacks*,
OTF2_EvtReaderCallback_OmpFork *ompForkCallback*)

Registers the callback for the OmpFork event.

Parameters

| | |
|----------------------------|---|
| <i>evtReader-Callbacks</i> | Struct for all callbacks. |
| <i>ompFork-Callback</i> | Function which should be called for all OmpFork events. |

Returns

OTF2_SUCCESS if successful

OTF2_ERROR_INVALID_ARGUMENT for an invalid *defReaderCallbacks* argument

J.12.3.21 **OTF2_ErrorCode** **OTF2_EvtReaderCallbacks.SetOmpJoinCallback**
(**OTF2_EvtReaderCallbacks** * *evtReaderCallbacks*,
OTF2_EvtReaderCallback_OmpJoin *ompJoinCallback*)

Registers the callback for the OmpJoin event.

Parameters

| | |
|----------------------------|---|
| <i>evtReader-Callbacks</i> | Struct for all callbacks. |
| <i>ompJoin-Callback</i> | Function which should be called for all OmpJoin events. |

Returns

OTF2_SUCCESS if successful

OTF2_ERROR_INVALID_ARGUMENT for an invalid *defReaderCallbacks* argument

J.12 OTF2_EvtReaderCallbacks.h File Reference

J.12.3.22 `OTF2_ErrorCode OTF2_EvtReaderCallbacks_SetOmpReleaseLockCallback (OTF2_EvtReaderCallbacks * evtReaderCallbacks, OTF2_EvtReaderCallback_OmpReleaseLock ompReleaseLockCallback)`

Registers the callback for the OmpReleaseLock event.

Parameters

| | |
|-------------------------------|--|
| <i>evtReaderCallbacks</i> | Struct for all callbacks. |
| <i>ompReleaseLockCallback</i> | Function which should be called for all OmpReleaseLock events. |

Returns

[*OTF2_SUCCESS*](#) if successful

[*OTF2_ERROR_INVALID_ARGUMENT*](#) for an invalid `defReaderCallbacks` argument

J.12.3.23 `OTF2_ErrorCode OTF2_EvtReaderCallbacks_SetOmpTaskCompleteCallback (OTF2_EvtReaderCallbacks * evtReaderCallbacks, OTF2_EvtReaderCallback_OmpTaskComplete ompTaskCompleteCallback)`

Registers the callback for the OmpTaskComplete event.

Parameters

| | |
|--------------------------------|---|
| <i>evtReaderCallbacks</i> | Struct for all callbacks. |
| <i>ompTaskCompleteCallback</i> | Function which should be called for all OmpTaskComplete events. |

Returns

[*OTF2_SUCCESS*](#) if successful

[*OTF2_ERROR_INVALID_ARGUMENT*](#) for an invalid `defReaderCallbacks` argument

APPENDIX J. FILE DOCUMENTATION

J.12.3.24 **OTF2_ErrorCode** **OTF2_EvtReaderCallbacks.SetOmpTaskCreateCallback**
(**OTF2_EvtReaderCallbacks** * *evtReaderCallbacks*,
OTF2_EvtReaderCallback_OmpTaskCreate *ompTaskCreateCallback*)

Registers the callback for the OmpTaskCreate event.

Parameters

| | |
|--------------------------------|---|
| <i>evtReader-Callbacks</i> | Struct for all callbacks. |
| <i>omp-TaskCreate-Callback</i> | Function which should be called for all OmpTaskCreate events. |

Returns

OTF2_SUCCESS if successful

OTF2_ERROR_INVALID_ARGUMENT for an invalid `defReaderCallbacks` argument

J.12.3.25 **OTF2_ErrorCode** **OTF2_EvtReaderCallbacks.SetOmpTaskSwitchCallback**
(**OTF2_EvtReaderCallbacks** * *evtReaderCallbacks*,
OTF2_EvtReaderCallback_OmpTaskSwitch *ompTaskSwitchCallback*)

Registers the callback for the OmpTaskSwitch event.

Parameters

| | |
|--------------------------------|---|
| <i>evtReader-Callbacks</i> | Struct for all callbacks. |
| <i>omp-TaskSwitch-Callback</i> | Function which should be called for all OmpTaskSwitch events. |

Returns

OTF2_SUCCESS if successful

OTF2_ERROR_INVALID_ARGUMENT for an invalid `defReaderCallbacks` argument

J.12 OTF2_EvtReaderCallbacks.h File Reference

J.12.3.26 `OTF2_StatusCode OTF2_EvtReaderCallbacks_SetParameterIntCallback (OTF2_EvtReaderCallbacks * evtReaderCallbacks, OTF2_EvtReaderCallback_ParameterInt parameterIntCallback)`

Registers the callback for the ParameterInt event.

Parameters

| | |
|------------------------------|--|
| <i>evtReader-Callbacks</i> | Struct for all callbacks. |
| <i>parameter-IntCallback</i> | Function which should be called for all ParameterInt events. |

Returns

`OTF2_SUCCESS` if successful

`OTF2_ERROR_INVALID_ARGUMENT` for an invalid `defReaderCallbacks` argument

J.12.3.27 `OTF2_StatusCode OTF2_EvtReaderCallbacks_SetParameterStringCallback (OTF2_EvtReaderCallbacks * evtReaderCallbacks, OTF2_EvtReaderCallback_ParameterString parameterStringCallback)`

Registers the callback for the ParameterString event.

Parameters

| | |
|---------------------------------|---|
| <i>evtReader-Callbacks</i> | Struct for all callbacks. |
| <i>parameter-StringCallback</i> | Function which should be called for all ParameterString events. |

Returns

`OTF2_SUCCESS` if successful

`OTF2_ERROR_INVALID_ARGUMENT` for an invalid `defReaderCallbacks` argument

APPENDIX J. FILE DOCUMENTATION

J.12.3.28 **OTF2_ErrorCode** **OTF2_EvtReaderCallbacks** **SetParameterUnsignedIntCallback** (**OTF2_EvtReaderCallbacks**
* *evtReaderCallbacks*, **OTF2_EvtReaderCallback** **ParameterUnsignedInt** *parameterUnsignedIntCallback*
)

Registers the callback for the ParameterUnsignedInt event.

Parameters

| | |
|--------------------------------------|--|
| <i>evtReader-Callbacks</i> | Struct for all callbacks. |
| <i>parameterUnsignedInt-Callback</i> | Function which should be called for all ParameterUnsignedInt events. |

Returns

OTF2_SUCCESS if successful

OTF2_ERROR_INVALID_ARGUMENT for an invalid `defReaderCallbacks` argument

J.12.3.29 **OTF2_ErrorCode** **OTF2_EvtReaderCallbacks** **SetRmaAcquireLockCallback**
(**OTF2_EvtReaderCallbacks** * *evtReaderCallbacks*,
OTF2_EvtReaderCallback **RmaAcquireLock** *rmaAcquireLockCallback*
)

Registers the callback for the RmaAcquireLock event.

Parameters

| | |
|--------------------------------|--|
| <i>evtReader-Callbacks</i> | Struct for all callbacks. |
| <i>rmaAcquireLock-Callback</i> | Function which should be called for all RmaAcquireLock events. |

Returns

OTF2_SUCCESS if successful

OTF2_ERROR_INVALID_ARGUMENT for an invalid `defReaderCallbacks` argument

J.12 OTF2_EvtReaderCallbacks.h File Reference

J.12.3.30 `OTF2_ErrorCode OTF2_EvtReaderCallbacks_SetRmaAtomicCallback (OTF2_EvtReaderCallbacks * evtReaderCallbacks, OTF2_EvtReaderCallback_RmaAtomic rmaAtomicCallback)`

Registers the callback for the RmaAtomic event.

Parameters

| | |
|----------------------------|---|
| <i>evtReader-Callbacks</i> | Struct for all callbacks. |
| <i>rmaAtomic-Callback</i> | Function which should be called for all RmaAtomic events. |

Returns

`OTF2_SUCCESS` if successful

`OTF2_ERROR_INVALID_ARGUMENT` for an invalid `defReaderCallbacks` argument

J.12.3.31 `OTF2_ErrorCode OTF2_EvtReaderCallbacks_SetRmaCollectiveBeginCallback (OTF2_EvtReaderCallbacks * evtReaderCallbacks, OTF2_EvtReaderCallback_RmaCollectiveBegin rmaCollectiveBeginCallback)`

Registers the callback for the RmaCollectiveBegin event.

Parameters

| | |
|------------------------------------|--|
| <i>evtReader-Callbacks</i> | Struct for all callbacks. |
| <i>rmaCollectiveBegin-Callback</i> | Function which should be called for all RmaCollectiveBegin events. |

Returns

`OTF2_SUCCESS` if successful

`OTF2_ERROR_INVALID_ARGUMENT` for an invalid `defReaderCallbacks` argument

APPENDIX J. FILE DOCUMENTATION

J.12.3.32 **OTF2_ErrorCode** **OTF2_EvtReaderCallbacks.SetRmaCollectiveEndCallback**
(**OTF2_EvtReaderCallbacks** * *evtReaderCallbacks*, **OTF2_-**
EvtReaderCallback_RmaCollectiveEnd *rmaCollectiveEndCallback*
)

Registers the callback for the RmaCollectiveEnd event.

Parameters

| | |
|---|--|
| <i>evtReader- Callbacks</i> | Struct for all callbacks. |
| <i>rmaCollec- tiveEnd- Callback</i> | Function which should be called for all RmaCollectiveEnd events. |

Returns

OTF2_SUCCESS if successful

OTF2_ERROR_INVALID_ARGUMENT for an invalid *defReaderCallbacks*
argument

J.12.3.33 **OTF2_ErrorCode** **OTF2_EvtReaderCallbacks.SetRmaGetCallback**
(**OTF2_EvtReaderCallbacks** * *evtReaderCallbacks*,
OTF2_EvtReaderCallback_RmaGet *rmaGetCallback*)

Registers the callback for the RmaGet event.

Parameters

| | |
|---------------------------------|--|
| <i>evtReader- Callbacks</i> | Struct for all callbacks. |
| <i>rmaGet- Callback</i> | Function which should be called for all RmaGet events. |

Returns

OTF2_SUCCESS if successful

OTF2_ERROR_INVALID_ARGUMENT for an invalid *defReaderCallbacks*
argument

J.12 OTF2_EvtReaderCallbacks.h File Reference

J.12.3.34 `OTF2_ErrorCode OTF2_EvtReaderCallbacks_SetRmaGroupSyncCallback (OTF2_EvtReaderCallbacks * evtReaderCallbacks, OTF2_EvtReaderCallback_RmaGroupSync rmaGroupSyncCallback)`

Registers the callback for the RmaGroupSync event.

Parameters

| | |
|-------------------------------|--|
| <i>evtReader-Callbacks</i> | Struct for all callbacks. |
| <i>rmaGroup-SyncCall-back</i> | Function which should be called for all RmaGroupSync events. |

Returns

[*OTF2_SUCCESS*](#) if successful

[*OTF2_ERROR_INVALID_ARGUMENT*](#) for an invalid `defReaderCallbacks` argument

J.12.3.35 `OTF2_ErrorCode OTF2_EvtReaderCallbacks_SetRmaOpCompleteBlockingCallback (OTF2_EvtReaderCallbacks * evtReaderCallbacks, OTF2_EvtReaderCallback_RmaOpCompleteBlocking rmaOpCompleteBlockingCallback)`

Registers the callback for the RmaOpCompleteBlocking event.

Parameters

| | |
|---|---|
| <i>evtReader-Callbacks</i> | Struct for all callbacks. |
| <i>rmaOp-Complete-Blocking-Callback</i> | Function which should be called for all RmaOpCompleteBlocking events. |

Returns

[*OTF2_SUCCESS*](#) if successful

[*OTF2_ERROR_INVALID_ARGUMENT*](#) for an invalid `defReaderCallbacks` argument

APPENDIX J. FILE DOCUMENTATION

J.12.3.36 **OTF2_ErrorCode** **OTF2_EvtReaderCallbacks_-**
SetRmaOpCompleteNonBlockingCallback (**OTF2_EvtReaderCallbacks**
*** *evtReaderCallbacks*, **OTF2_EvtReaderCallback_-****
RmaOpCompleteNonBlocking *rmaOpCompleteNonBlockingCallback*
)

Registers the callback for the RmaOpCompleteNonBlocking event.

Parameters

| | |
|---|--|
| <i>evtReader- Callbacks</i> | Struct for all callbacks. |
| <i>rmaOp- Com- pleteNon- Blocking- Callback</i> | Function which should be called for all RmaOpCompleteNonBlocking events. |

Returns

OTF2_SUCCESS if successful

OTF2_ERROR_INVALID_ARGUMENT for an invalid `defReaderCallbacks` argument

J.12.3.37 **OTF2_ErrorCode** **OTF2_EvtReaderCallbacks_-**
SetRmaOpCompleteRemoteCallback (**OTF2_EvtReaderCallbacks**
*** *evtReaderCallbacks*, **OTF2_EvtReaderCallback_-****
RmaOpCompleteRemote *rmaOpCompleteRemoteCallback*
)

Registers the callback for the RmaOpCompleteRemote event.

Parameters

| | |
|--|---|
| <i>evtReader- Callbacks</i> | Struct for all callbacks. |
| <i>rmaOp- CompleteR- emoteCall- back</i> | Function which should be called for all RmaOpCompleteRemote events. |

Returns

OTF2_SUCCESS if successful

J.12 OTF2_EvtReaderCallbacks.h File Reference

OTF2_ERROR_INVALID_ARGUMENT for an invalid `defReaderCallbacks` argument

J.12.3.38 **OTF2_StatusCode** `OTF2_EvtReaderCallbacks.SetRmaOpTestCallback`
(**OTF2_EvtReaderCallbacks** * *evtReaderCallbacks*,
OTF2_EvtReaderCallback_RmaOpTest *rmaOpTestCallback*)

Registers the callback for the RmaOpTest event.

Parameters

| | |
|----------------------------|---|
| <i>evtReader-Callbacks</i> | Struct for all callbacks. |
| <i>rmaOpTest-Callback</i> | Function which should be called for all RmaOpTest events. |

Returns

OTF2_SUCCESS if successful

OTF2_ERROR_INVALID_ARGUMENT for an invalid `defReaderCallbacks` argument

J.12.3.39 **OTF2_StatusCode** `OTF2_EvtReaderCallbacks.SetRmaPutCallback`
(**OTF2_EvtReaderCallbacks** * *evtReaderCallbacks*,
OTF2_EvtReaderCallback_RmaPut *rmaPutCallback*)

Registers the callback for the RmaPut event.

Parameters

| | |
|----------------------------|--|
| <i>evtReader-Callbacks</i> | Struct for all callbacks. |
| <i>rmaPut-Callback</i> | Function which should be called for all RmaPut events. |

Returns

OTF2_SUCCESS if successful

OTF2_ERROR_INVALID_ARGUMENT for an invalid `defReaderCallbacks` argument

APPENDIX J. FILE DOCUMENTATION

J.12.3.40 `OTF2_ErrorCode` `OTF2_EvtReaderCallbacks_SetRmaReleaseLockCallback`
(`OTF2_EvtReaderCallbacks` * `evtReaderCallbacks`,
`OTF2_EvtReaderCallback_RmaReleaseLock` `rmaReleaseLockCallback`
)

Registers the callback for the RmaReleaseLock event.

Parameters

| | |
|--------------------------------|--|
| <i>evtReader-Callbacks</i> | Struct for all callbacks. |
| <i>rmaReleaseLock-Callback</i> | Function which should be called for all RmaReleaseLock events. |

Returns

`OTF2_SUCCESS` if successful

`OTF2_ERROR_INVALID_ARGUMENT` for an invalid `defReaderCallbacks` argument

J.12.3.41 `OTF2_ErrorCode` `OTF2_EvtReaderCallbacks_SetRmaRequestLockCallback`
(`OTF2_EvtReaderCallbacks` * `evtReaderCallbacks`,
`OTF2_EvtReaderCallback_RmaRequestLock` `rmaRequestLockCallback`
)

Registers the callback for the RmaRequestLock event.

Parameters

| | |
|--------------------------------|--|
| <i>evtReader-Callbacks</i> | Struct for all callbacks. |
| <i>rmaRequestLock-Callback</i> | Function which should be called for all RmaRequestLock events. |

Returns

`OTF2_SUCCESS` if successful

`OTF2_ERROR_INVALID_ARGUMENT` for an invalid `defReaderCallbacks` argument

J.12 OTF2_EvtReaderCallbacks.h File Reference

J.12.3.42 `OTF2_ErrorCode OTF2_EvtReaderCallbacks.SetRmaSyncCallback (OTF2_EvtReaderCallbacks * evtReaderCallbacks, OTF2_EvtReaderCallback_RmaSync rmaSyncCallback)`

Registers the callback for the RmaSync event.

Parameters

| | |
|----------------------------|---|
| <i>evtReader-Callbacks</i> | Struct for all callbacks. |
| <i>rmaSync-Callback</i> | Function which should be called for all RmaSync events. |

Returns

OTF2_SUCCESS if successful

OTF2_ERROR_INVALID_ARGUMENT for an invalid `defReaderCallbacks` argument

J.12.3.43 `OTF2_ErrorCode OTF2_EvtReaderCallbacks.SetRmaTryLockCallback (OTF2_EvtReaderCallbacks * evtReaderCallbacks, OTF2_EvtReaderCallback_RmaTryLock rmaTryLockCallback)`

Registers the callback for the RmaTryLock event.

Parameters

| | |
|-----------------------------|--|
| <i>evtReader-Callbacks</i> | Struct for all callbacks. |
| <i>rmaTry-LockCall-back</i> | Function which should be called for all RmaTryLock events. |

Returns

OTF2_SUCCESS if successful

OTF2_ERROR_INVALID_ARGUMENT for an invalid `defReaderCallbacks` argument

APPENDIX J. FILE DOCUMENTATION

J.12.3.44 **OTF2_ErrorCode** **OTF2_EvtReaderCallbacks.SetRmaWaitChangeCallback**
(**OTF2_EvtReaderCallbacks** * *evtReaderCallbacks*,
OTF2_EvtReaderCallback_RmaWaitChange *rmaWaitChangeCallback*)

Registers the callback for the RmaWaitChange event.

Parameters

| | |
|--------------------------------|---|
| <i>evtReader-Callbacks</i> | Struct for all callbacks. |
| <i>rmaWait-Change-Callback</i> | Function which should be called for all RmaWaitChange events. |

Returns

OTF2_SUCCESS if successful

OTF2_ERROR_INVALID_ARGUMENT for an invalid *defReaderCallbacks* argument

J.12.3.45 **OTF2_ErrorCode** **OTF2_EvtReaderCallbacks.SetRmaWinCreateCallback**
(**OTF2_EvtReaderCallbacks** * *evtReaderCallbacks*,
OTF2_EvtReaderCallback_RmaWinCreate *rmaWinCreateCallback*)

Registers the callback for the RmaWinCreate event.

Parameters

| | |
|-------------------------------|--|
| <i>evtReader-Callbacks</i> | Struct for all callbacks. |
| <i>rmaWin-CreateCall-back</i> | Function which should be called for all RmaWinCreate events. |

Returns

OTF2_SUCCESS if successful

OTF2_ERROR_INVALID_ARGUMENT for an invalid *defReaderCallbacks* argument

J.12 OTF2_EvtReaderCallbacks.h File Reference

J.12.3.46 `OTF2_ErrorCode OTF2_EvtReaderCallbacks.SetRmaWinDestroyCallback (OTF2_EvtReaderCallbacks * evtReaderCallbacks, OTF2_EvtReaderCallback_RmaWinDestroy rmaWinDestroyCallback)`

Registers the callback for the RmaWinDestroy event.

Parameters

| | |
|------------------------------|---|
| <i>evtReaderCallbacks</i> | Struct for all callbacks. |
| <i>rmaWinDestroyCallback</i> | Function which should be called for all RmaWinDestroy events. |

Returns

`OTF2_SUCCESS` if successful

`OTF2_ERROR_INVALID_ARGUMENT` for an invalid `defReaderCallbacks` argument

J.12.3.47 `OTF2_ErrorCode OTF2_EvtReaderCallbacks.SetThreadAcquireLockCallback (OTF2_EvtReaderCallbacks * evtReaderCallbacks, OTF2_EvtReaderCallback_ThreadAcquireLock threadAcquireLockCallback)`

Registers the callback for the ThreadAcquireLock event.

Parameters

| | |
|----------------------------------|---|
| <i>evtReaderCallbacks</i> | Struct for all callbacks. |
| <i>threadAcquireLockCallback</i> | Function which should be called for all ThreadAcquireLock events. |

Returns

`OTF2_SUCCESS` if successful

`OTF2_ERROR_INVALID_ARGUMENT` for an invalid `defReaderCallbacks` argument

APPENDIX J. FILE DOCUMENTATION

J.12.3.48 **OTF2_ErrorCode** **OTF2_EvtReaderCallbacks.SetThreadForkCallback**
(**OTF2_EvtReaderCallbacks** * *evtReaderCallbacks*,
OTF2_EvtReaderCallback_ThreadFork *threadForkCallback*)

Registers the callback for the ThreadFork event.

Parameters

| | |
|----------------------------|--|
| <i>evtReader-Callbacks</i> | Struct for all callbacks. |
| <i>threadFork-Callback</i> | Function which should be called for all ThreadFork events. |

Returns

OTF2_SUCCESS if successful

OTF2_ERROR_INVALID_ARGUMENT for an invalid *defReaderCallbacks* argument

J.12.3.49 **OTF2_ErrorCode** **OTF2_EvtReaderCallbacks.SetThreadJoinCallback**
(**OTF2_EvtReaderCallbacks** * *evtReaderCallbacks*,
OTF2_EvtReaderCallback_ThreadJoin *threadJoinCallback*)

Registers the callback for the ThreadJoin event.

Parameters

| | |
|----------------------------|--|
| <i>evtReader-Callbacks</i> | Struct for all callbacks. |
| <i>threadJoin-Callback</i> | Function which should be called for all ThreadJoin events. |

Returns

OTF2_SUCCESS if successful

OTF2_ERROR_INVALID_ARGUMENT for an invalid *defReaderCallbacks* argument

J.12 OTF2_EvtReaderCallbacks.h File Reference

J.12.3.50 **OTF2_StatusCode** **OTF2_EvtReaderCallbacks_SetThreadReleaseLockCallback**
(**OTF2_EvtReaderCallbacks** * *evtReaderCallbacks*,
OTF2_EvtReaderCallback_ThreadReleaseLock
threadReleaseLockCallback)

Registers the callback for the ThreadReleaseLock event.

Parameters

| | |
|-------------------------------------|---|
| <i>evtReader-Callbacks</i> | Struct for all callbacks. |
| <i>thread-Release-LockCall-back</i> | Function which should be called for all ThreadReleaseLock events. |

Returns

OTF2_SUCCESS if successful

OTF2_ERROR_INVALID_ARGUMENT for an invalid *defReaderCallbacks* argument

J.12.3.51 **OTF2_StatusCode** **OTF2_EvtReaderCallbacks_SetThreadTaskCompleteCallback** (**OTF2_EvtReaderCallbacks** *
evtReaderCallbacks, **OTF2_EvtReaderCallback_ThreadTaskComplete**
threadTaskCompleteCallback)

Registers the callback for the ThreadTaskComplete event.

Parameters

| | |
|-------------------------------------|--|
| <i>evtReader-Callbacks</i> | Struct for all callbacks. |
| <i>thread-TaskCompleteCall-back</i> | Function which should be called for all ThreadTaskComplete events. |

Returns

OTF2_SUCCESS if successful

OTF2_ERROR_INVALID_ARGUMENT for an invalid *defReaderCallbacks* argument

APPENDIX J. FILE DOCUMENTATION

J.12.3.52 **OTF2_StatusCode** **OTF2_EvtReaderCallbacks_SetThreadTaskCreateCallback**
(**OTF2_EvtReaderCallbacks** * *evtReaderCallbacks*, **OTF2_**
EvtReaderCallback_ThreadTaskCreate *threadTaskCreateCallback*
)

Registers the callback for the ThreadTaskCreate event.

Parameters

| | |
|---|--|
| <i>evtReader- Callbacks</i> | Struct for all callbacks. |
| <i>thread- TaskCreate- Callback</i> | Function which should be called for all ThreadTaskCreate events. |

Returns

OTF2_SUCCESS if successful

OTF2_ERROR_INVALID_ARGUMENT for an invalid *defReaderCallbacks*
argument

J.12.3.53 **OTF2_StatusCode** **OTF2_EvtReaderCallbacks_SetThreadTaskSwitchCallback**
(**OTF2_EvtReaderCallbacks** * *evtReaderCallbacks*, **OTF2_**
EvtReaderCallback_ThreadTaskSwitch *threadTaskSwitchCallback*
)

Registers the callback for the ThreadTaskSwitch event.

Parameters

| | |
|---|--|
| <i>evtReader- Callbacks</i> | Struct for all callbacks. |
| <i>thread- TaskSwitch- Callback</i> | Function which should be called for all ThreadTaskSwitch events. |

Returns

OTF2_SUCCESS if successful

OTF2_ERROR_INVALID_ARGUMENT for an invalid *defReaderCallbacks*
argument

J.12 OTF2_EvtReaderCallbacks.h File Reference

J.12.3.54 **OTF2_StatusCode** **OTF2_EvtReaderCallbacks.SetThreadTeamBeginCallback**
(**OTF2_EvtReaderCallbacks** * *evtReaderCallbacks*, **OTF2_**
EvtReaderCallback_ThreadTeamBegin *threadTeamBeginCallback*
)

Registers the callback for the ThreadTeamBegin event.

Parameters

| | |
|--|---|
| <i>evtReader- Callbacks</i> | Struct for all callbacks. |
| <i>thread- TeamBegin- Callback</i> | Function which should be called for all ThreadTeamBegin events. |

Returns

OTF2_SUCCESS if successful

OTF2_ERROR_INVALID_ARGUMENT for an invalid `defReaderCallbacks`
argument

J.12.3.55 **OTF2_StatusCode** **OTF2_EvtReaderCallbacks.SetThreadTeamEndCallback**
(**OTF2_EvtReaderCallbacks** * *evtReaderCallbacks*,
OTF2_EvtReaderCallback_ThreadTeamEnd *threadTeamEndCallback*)

Registers the callback for the ThreadTeamEnd event.

Parameters

| | |
|--|---|
| <i>evtReader- Callbacks</i> | Struct for all callbacks. |
| <i>threadTea- mEndCall- back</i> | Function which should be called for all ThreadTeamEnd events. |

Returns

OTF2_SUCCESS if successful

OTF2_ERROR_INVALID_ARGUMENT for an invalid `defReaderCallbacks`
argument

J.12.3.56 `OTF2_ErrorCode OTF2_EvtReaderCallbacks.SetUnknownCallback`
 (`OTF2_EvtReaderCallbacks * evtReaderCallbacks,`
`OTF2_EvtReaderCallback_Unknown unknownCallback`)

Registers the callback for the Unknown event.

Parameters

| | |
|----------------------------|---|
| <i>evtReader-Callbacks</i> | Struct for all callbacks. |
| <i>unknown-Callback</i> | Function which should be called for all unknown events. |

Returns

`OTF2_SUCCESS` if successful
`OTF2_ERROR_INVALID_ARGUMENT` for an invalid `defReaderCallbacks` argument

J.13 OTF2_EvtWriter.h File Reference

This lowest user-visible layer provides write routines to write event data of a single location.

```
#include <stdint.h>
#include <otf2/OTF2_ErrorCodes.h>
#include <otf2/OTF2_Events.h>
#include <otf2/OTF2_AttributeList.h>
```

Typedefs

- typedef struct `OTF2_EvtWriter_struct` [OTF2_EvtWriter](#)
Keeps all necessary information about the event writer. See OTF2_EvtWriter_struct for detailed information.

Functions

- `OTF2_ErrorCode OTF2_EvtWriter_BufferFlush` (`OTF2_EvtWriter *writer,`
`OTF2_AttributeList *attributeList, OTF2_TimeStamp time, OTF2_TimeStamp stopTime`)

J.13 OTF2_EvtWriter.h File Reference

Records an BufferFlush event.

- [OTF2_ErrorCode OTF2_EvtWriter_ClearRewindPoint](#) (OTF2_EvtWriter *writer, uint32_t rewindId)

Please give me a documantation.

- [OTF2_ErrorCode OTF2_EvtWriter_Enter](#) (OTF2_EvtWriter *writer, OTF2_AttributeList *attributeList, OTF2_TimeStamp time, OTF2_RegionRef region)

Records an Enter event.

- [OTF2_ErrorCode OTF2_EvtWriter_GetLocationID](#) (const OTF2_EvtWriter *writer, OTF2_LocationRef *locationID)

Function to get the location ID of a writer object.

- [OTF2_ErrorCode OTF2_EvtWriter_GetNumberOfEvents](#) (OTF2_EvtWriter *writer, uint64_t *numberOfEvents)

Get the number of events.

- [OTF2_ErrorCode OTF2_EvtWriter_GetUserData](#) (const OTF2_EvtWriter *writer, void **userData)

Function to get the location of a writer object.

- [OTF2_ErrorCode OTF2_EvtWriter_Leave](#) (OTF2_EvtWriter *writer, OTF2_AttributeList *attributeList, OTF2_TimeStamp time, OTF2_RegionRef region)

Records an Leave event.

- [OTF2_ErrorCode OTF2_EvtWriter_MeasurementOnOff](#) (OTF2_EvtWriter *writer, OTF2_AttributeList *attributeList, OTF2_TimeStamp time, OTF2_MeasurementMode measurementMode)

Records an MeasurementOnOff event.

- [OTF2_ErrorCode OTF2_EvtWriter_Metric](#) (OTF2_EvtWriter *writer, OTF2_AttributeList *attributeList, OTF2_TimeStamp time, OTF2_MetricRef metric, uint8_t numberOfMetrics, const OTF2_Type *typeIDs, const OTF2_MetricValue *metricValues)

Records an Metric event.

- [OTF2_ErrorCode OTF2_EvtWriter_MpiCollectiveBegin](#) (OTF2_EvtWriter *writer, OTF2_AttributeList *attributeList, OTF2_TimeStamp time)

Records an MpiCollectiveBegin event.

APPENDIX J. FILE DOCUMENTATION

- `OTF2_ErrorCode OTF2_EvtWriter_MpiCollectiveEnd` (`OTF2_EvtWriter *writer`, `OTF2_AttributeList *attributeList`, `OTF2_TimeStamp` time, `OTF2_CollectiveOp` collectiveOp, `OTF2_CommRef` communicator, `uint32_t` root, `uint64_t` sizeSent, `uint64_t` sizeReceived)
Records an MpiCollectiveEnd event.
- `OTF2_ErrorCode OTF2_EvtWriter_MpiIrecv` (`OTF2_EvtWriter *writer`, `OTF2_AttributeList *attributeList`, `OTF2_TimeStamp` time, `uint32_t` sender, `OTF2_CommRef` communicator, `uint32_t` msgTag, `uint64_t` msgLength, `uint64_t` requestID)
Records an MpiIrecv event.
- `OTF2_ErrorCode OTF2_EvtWriter_MpiIrecvRequest` (`OTF2_EvtWriter *writer`, `OTF2_AttributeList *attributeList`, `OTF2_TimeStamp` time, `uint64_t` requestID)
Records an MpiIrecvRequest event.
- `OTF2_ErrorCode OTF2_EvtWriter_MpiIsend` (`OTF2_EvtWriter *writer`, `OTF2_AttributeList *attributeList`, `OTF2_TimeStamp` time, `uint32_t` receiver, `OTF2_CommRef` communicator, `uint32_t` msgTag, `uint64_t` msgLength, `uint64_t` requestID)
Records an MpiIsend event.
- `OTF2_ErrorCode OTF2_EvtWriter_MpiIsendComplete` (`OTF2_EvtWriter *writer`, `OTF2_AttributeList *attributeList`, `OTF2_TimeStamp` time, `uint64_t` requestID)
Records an MpiIsendComplete event.
- `OTF2_ErrorCode OTF2_EvtWriter_MpiRecv` (`OTF2_EvtWriter *writer`, `OTF2_AttributeList *attributeList`, `OTF2_TimeStamp` time, `uint32_t` sender, `OTF2_CommRef` communicator, `uint32_t` msgTag, `uint64_t` msgLength)
Records an MpiRecv event.
- `OTF2_ErrorCode OTF2_EvtWriter_MpiRequestCancelled` (`OTF2_EvtWriter *writer`, `OTF2_AttributeList *attributeList`, `OTF2_TimeStamp` time, `uint64_t` requestID)
Records an MpiRequestCancelled event.
- `OTF2_ErrorCode OTF2_EvtWriter_MpiRequestTest` (`OTF2_EvtWriter *writer`, `OTF2_AttributeList *attributeList`, `OTF2_TimeStamp` time, `uint64_t` requestID)

J.13 OTF2_EvtWriter.h File Reference

Records an MpiRequestTest event.

- [OTF2_ErrorCode](#) [OTF2_EvtWriter_MpiSend](#) ([OTF2_EvtWriter](#) *writer, [OTF2_AttributeList](#) *attributeList, [OTF2_TimeStamp](#) time, [uint32_t](#) receiver, [OTF2_CommRef](#) communicator, [uint32_t](#) msgTag, [uint64_t](#) msgLength)

Records an MpiSend event.

- [OTF2_ErrorCode](#) [OTF2_EvtWriter_OmpAcquireLock](#) ([OTF2_EvtWriter](#) *writer, [OTF2_AttributeList](#) *attributeList, [OTF2_TimeStamp](#) time, [uint32_t](#) lockID, [uint32_t](#) acquisitionOrder)

Records an OmpAcquireLock event.

- [OTF2_ErrorCode](#) [OTF2_EvtWriter_OmpFork](#) ([OTF2_EvtWriter](#) *writer, [OTF2_AttributeList](#) *attributeList, [OTF2_TimeStamp](#) time, [uint32_t](#) numberOfRequestedThreads)

Records an OmpFork event.

- [OTF2_ErrorCode](#) [OTF2_EvtWriter_OmpJoin](#) ([OTF2_EvtWriter](#) *writer, [OTF2_AttributeList](#) *attributeList, [OTF2_TimeStamp](#) time)

Records an OmpJoin event.

- [OTF2_ErrorCode](#) [OTF2_EvtWriter_OmpReleaseLock](#) ([OTF2_EvtWriter](#) *writer, [OTF2_AttributeList](#) *attributeList, [OTF2_TimeStamp](#) time, [uint32_t](#) lockID, [uint32_t](#) acquisitionOrder)

Records an OmpReleaseLock event.

- [OTF2_ErrorCode](#) [OTF2_EvtWriter_OmpTaskComplete](#) ([OTF2_EvtWriter](#) *writer, [OTF2_AttributeList](#) *attributeList, [OTF2_TimeStamp](#) time, [uint64_t](#) taskID)

Records an OmpTaskComplete event.

- [OTF2_ErrorCode](#) [OTF2_EvtWriter_OmpTaskCreate](#) ([OTF2_EvtWriter](#) *writer, [OTF2_AttributeList](#) *attributeList, [OTF2_TimeStamp](#) time, [uint64_t](#) taskID)

Records an OmpTaskCreate event.

- [OTF2_ErrorCode](#) [OTF2_EvtWriter_OmpTaskSwitch](#) ([OTF2_EvtWriter](#) *writer, [OTF2_AttributeList](#) *attributeList, [OTF2_TimeStamp](#) time, [uint64_t](#) taskID)

Records an OmpTaskSwitch event.

APPENDIX J. FILE DOCUMENTATION

- [OTF2_ErrorCode](#) [OTF2_EvtWriter_ParameterInt](#) ([OTF2_EvtWriter](#) *writer, [OTF2_AttributeList](#) *attributeList, [OTF2_TimeStamp](#) time, [OTF2_ParameterRef](#) parameter, [int64_t](#) value)
Records an ParameterInt event.
- [OTF2_ErrorCode](#) [OTF2_EvtWriter_ParameterString](#) ([OTF2_EvtWriter](#) *writer, [OTF2_AttributeList](#) *attributeList, [OTF2_TimeStamp](#) time, [OTF2_ParameterRef](#) parameter, [OTF2_StringRef](#) string)
Records an ParameterString event.
- [OTF2_ErrorCode](#) [OTF2_EvtWriter_ParameterUnsignedInt](#) ([OTF2_EvtWriter](#) *writer, [OTF2_AttributeList](#) *attributeList, [OTF2_TimeStamp](#) time, [OTF2_ParameterRef](#) parameter, [uint64_t](#) value)
Records an ParameterUnsignedInt event.
- [OTF2_ErrorCode](#) [OTF2_EvtWriter_Rewind](#) ([OTF2_EvtWriter](#) *writer, [uint32_t](#) rewindId)
Please give me a documantation.
- [OTF2_ErrorCode](#) [OTF2_EvtWriter_RmaAcquireLock](#) ([OTF2_EvtWriter](#) *writer, [OTF2_AttributeList](#) *attributeList, [OTF2_TimeStamp](#) time, [OTF2_RmaWinRef](#) win, [uint32_t](#) remote, [uint64_t](#) lockId, [OTF2_LockType](#) lockType)
Records an RmaAcquireLock event.
- [OTF2_ErrorCode](#) [OTF2_EvtWriter_RmaAtomic](#) ([OTF2_EvtWriter](#) *writer, [OTF2_AttributeList](#) *attributeList, [OTF2_TimeStamp](#) time, [OTF2_RmaWinRef](#) win, [uint32_t](#) remote, [OTF2_RmaAtomicType](#) type, [uint64_t](#) bytesSent, [uint64_t](#) bytesReceived, [uint64_t](#) matchingId)
Records an RmaAtomic event.
- [OTF2_ErrorCode](#) [OTF2_EvtWriter_RmaCollectiveBegin](#) ([OTF2_EvtWriter](#) *writer, [OTF2_AttributeList](#) *attributeList, [OTF2_TimeStamp](#) time)
Records an RmaCollectiveBegin event.
- [OTF2_ErrorCode](#) [OTF2_EvtWriter_RmaCollectiveEnd](#) ([OTF2_EvtWriter](#) *writer, [OTF2_AttributeList](#) *attributeList, [OTF2_TimeStamp](#) time, [OTF2_CollectiveOp](#) collectiveOp, [OTF2_RmaSyncLevel](#) syncLevel, [OTF2_RmaWinRef](#) win, [uint32_t](#) root, [uint64_t](#) bytesSent, [uint64_t](#) bytesReceived)
Records an RmaCollectiveEnd event.
- [OTF2_ErrorCode](#) [OTF2_EvtWriter_RmaGet](#) ([OTF2_EvtWriter](#) *writer, [OTF2_AttributeList](#) *attributeList, [OTF2_TimeStamp](#) time, [OTF2_RmaWinRef](#) win, [uint32_t](#) remote, [uint64_t](#) bytes, [uint64_t](#) matchingId)

J.13 OTF2_EvtWriter.h File Reference

Records an RmaGet event.

- [OTF2_ErrorCode](#) [OTF2_EvtWriter_RmaGroupSync](#) ([OTF2_EvtWriter](#) *writer, [OTF2_AttributeList](#) *attributeList, [OTF2_TimeStamp](#) time, [OTF2_RmaSyncLevel](#) syncLevel, [OTF2_RmaWinRef](#) win, [OTF2_GroupRef](#) group)

Records an RmaGroupSync event.

- [OTF2_ErrorCode](#) [OTF2_EvtWriter_RmaOpCompleteBlocking](#) ([OTF2_EvtWriter](#) *writer, [OTF2_AttributeList](#) *attributeList, [OTF2_TimeStamp](#) time, [OTF2_-RmaWinRef](#) win, [uint64_t](#) matchingId)

Records an RmaOpCompleteBlocking event.

- [OTF2_ErrorCode](#) [OTF2_EvtWriter_RmaOpCompleteNonBlocking](#) ([OTF2_-EvtWriter](#) *writer, [OTF2_AttributeList](#) *attributeList, [OTF2_TimeStamp](#) time, [OTF2_-RmaWinRef](#) win, [uint64_t](#) matchingId)

Records an RmaOpCompleteNonBlocking event.

- [OTF2_ErrorCode](#) [OTF2_EvtWriter_RmaOpCompleteRemote](#) ([OTF2_EvtWriter](#) *writer, [OTF2_AttributeList](#) *attributeList, [OTF2_TimeStamp](#) time, [OTF2_-RmaWinRef](#) win, [uint64_t](#) matchingId)

Records an RmaOpCompleteRemote event.

- [OTF2_ErrorCode](#) [OTF2_EvtWriter_RmaOpTest](#) ([OTF2_EvtWriter](#) *writer, [OTF2_AttributeList](#) *attributeList, [OTF2_TimeStamp](#) time, [OTF2_RmaWinRef](#) win, [uint64_t](#) matchingId)

Records an RmaOpTest event.

- [OTF2_ErrorCode](#) [OTF2_EvtWriter_RmaPut](#) ([OTF2_EvtWriter](#) *writer, [OTF2_-AttributeList](#) *attributeList, [OTF2_TimeStamp](#) time, [OTF2_RmaWinRef](#) win, [uint32_t](#) remote, [uint64_t](#) bytes, [uint64_t](#) matchingId)

Records an RmaPut event.

- [OTF2_ErrorCode](#) [OTF2_EvtWriter_RmaReleaseLock](#) ([OTF2_EvtWriter](#) *writer, [OTF2_AttributeList](#) *attributeList, [OTF2_TimeStamp](#) time, [OTF2_RmaWinRef](#) win, [uint32_t](#) remote, [uint64_t](#) lockId)

Records an RmaReleaseLock event.

- [OTF2_ErrorCode](#) [OTF2_EvtWriter_RmaRequestLock](#) ([OTF2_EvtWriter](#) *writer, [OTF2_AttributeList](#) *attributeList, [OTF2_TimeStamp](#) time, [OTF2_RmaWinRef](#) win, [uint32_t](#) remote, [uint64_t](#) lockId, [OTF2_LockType](#) lockType)

Records an RmaRequestLock event.

APPENDIX J. FILE DOCUMENTATION

- [OTF2_ErrorCode](#) [OTF2_EvtWriter_RmaSync](#) ([OTF2_EvtWriter](#) *writer, [OTF2_AttributeList](#) *attributeList, [OTF2_TimeStamp](#) time, [OTF2_RmaWinRef](#) win, [uint32_t](#) remote, [OTF2_RmaSyncType](#) syncType)
Records an RmaSync event.
- [OTF2_ErrorCode](#) [OTF2_EvtWriter_RmaTryLock](#) ([OTF2_EvtWriter](#) *writer, [OTF2_AttributeList](#) *attributeList, [OTF2_TimeStamp](#) time, [OTF2_RmaWinRef](#) win, [uint32_t](#) remote, [uint64_t](#) lockId, [OTF2_LockType](#) lockType)
Records an RmaTryLock event.
- [OTF2_ErrorCode](#) [OTF2_EvtWriter_RmaWaitChange](#) ([OTF2_EvtWriter](#) *writer, [OTF2_AttributeList](#) *attributeList, [OTF2_TimeStamp](#) time, [OTF2_RmaWinRef](#) win)
Records an RmaWaitChange event.
- [OTF2_ErrorCode](#) [OTF2_EvtWriter_RmaWinCreate](#) ([OTF2_EvtWriter](#) *writer, [OTF2_AttributeList](#) *attributeList, [OTF2_TimeStamp](#) time, [OTF2_RmaWinRef](#) win)
Records an RmaWinCreate event.
- [OTF2_ErrorCode](#) [OTF2_EvtWriter_RmaWinDestroy](#) ([OTF2_EvtWriter](#) *writer, [OTF2_AttributeList](#) *attributeList, [OTF2_TimeStamp](#) time, [OTF2_RmaWinRef](#) win)
Records an RmaWinDestroy event.
- [OTF2_ErrorCode](#) [OTF2_EvtWriter_SetLocationID](#) ([OTF2_EvtWriter](#) *writer, [OTF2_LocationRef](#) location)
The location ID is not always known on measurment start, and only needed on the first buffer flush to generate the file name. This function enables setting of the location ID after generating the buffer object.
- [OTF2_ErrorCode](#) [OTF2_EvtWriter_SetUserData](#) ([OTF2_EvtWriter](#) *writer, [void](#) *userData)
Function to set user defined data to a writer object.
- [OTF2_ErrorCode](#) [OTF2_EvtWriter_StoreRewindPoint](#) ([OTF2_EvtWriter](#) *writer, [uint32_t](#) rewindId)
Please give me a documantation.
- [OTF2_ErrorCode](#) [OTF2_EvtWriter_ThreadAcquireLock](#) ([OTF2_EvtWriter](#) *writer, [OTF2_AttributeList](#) *attributeList, [OTF2_TimeStamp](#) time, [OTF2_Paradigm](#) model, [uint32_t](#) lockID, [uint32_t](#) acquisitionOrder)

J.13 OTF2_EvtWriter.h File Reference

Records an ThreadAcquireLock event.

- [OTF2_ErrorCode](#) [OTF2_EvtWriter_ThreadFork](#) ([OTF2_EvtWriter](#) *writer, [OTF2_AttributeList](#) *attributeList, [OTF2_TimeStamp](#) time, [OTF2_Paradigm](#) model, [uint32_t](#) numberOfRequestedThreads)

Records an ThreadFork event.

- [OTF2_ErrorCode](#) [OTF2_EvtWriter_ThreadJoin](#) ([OTF2_EvtWriter](#) *writer, [OTF2_AttributeList](#) *attributeList, [OTF2_TimeStamp](#) time, [OTF2_Paradigm](#) model)

Records an ThreadJoin event.

- [OTF2_ErrorCode](#) [OTF2_EvtWriter_ThreadReleaseLock](#) ([OTF2_EvtWriter](#) *writer, [OTF2_AttributeList](#) *attributeList, [OTF2_TimeStamp](#) time, [OTF2_Paradigm](#) model, [uint32_t](#) lockID, [uint32_t](#) acquisitionOrder)

Records an ThreadReleaseLock event.

- [OTF2_ErrorCode](#) [OTF2_EvtWriter_ThreadTaskComplete](#) ([OTF2_EvtWriter](#) *writer, [OTF2_AttributeList](#) *attributeList, [OTF2_TimeStamp](#) time, [OTF2_CommRef](#) threadTeam, [uint32_t](#) creatingThread, [uint32_t](#) generationNumber)

Records an ThreadTaskComplete event.

- [OTF2_ErrorCode](#) [OTF2_EvtWriter_ThreadTaskCreate](#) ([OTF2_EvtWriter](#) *writer, [OTF2_AttributeList](#) *attributeList, [OTF2_TimeStamp](#) time, [OTF2_CommRef](#) threadTeam, [uint32_t](#) creatingThread, [uint32_t](#) generationNumber)

Records an ThreadTaskCreate event.

- [OTF2_ErrorCode](#) [OTF2_EvtWriter_ThreadTaskSwitch](#) ([OTF2_EvtWriter](#) *writer, [OTF2_AttributeList](#) *attributeList, [OTF2_TimeStamp](#) time, [OTF2_CommRef](#) threadTeam, [uint32_t](#) creatingThread, [uint32_t](#) generationNumber)

Records an ThreadTaskSwitch event.

- [OTF2_ErrorCode](#) [OTF2_EvtWriter_ThreadTeamBegin](#) ([OTF2_EvtWriter](#) *writer, [OTF2_AttributeList](#) *attributeList, [OTF2_TimeStamp](#) time, [OTF2_CommRef](#) threadTeam)

Records an ThreadTeamBegin event.

- [OTF2_ErrorCode](#) [OTF2_EvtWriter_ThreadTeamEnd](#) ([OTF2_EvtWriter](#) *writer, [OTF2_AttributeList](#) *attributeList, [OTF2_TimeStamp](#) time, [OTF2_CommRef](#) threadTeam)

Records an ThreadTeamEnd event.

J.13.1 Detailed Description

This lowest user-visible layer provides write routines to write event data of a single location.

Source Template:

templates/OTF2_EvtWriter.tmpl.h

Maintainer:

Dominic Eschweiler <d.eschweiler@fz-juelich.de>

Authors

Dominic Eschweiler <d.eschweiler@fz-juelich.de>, Michael Wagner <michael.wagner@zih.tu-dresden.de>

J.13.2 Function Documentation

J.13.2.1 `OTF2_ErrorCode OTF2_EvtWriter.BufferFlush (OTF2_EvtWriter * writer, OTF2_AttributeList * attributeList, OTF2_TimeStamp time, OTF2_TimeStamp stopTime)`

Records an BufferFlush event.

This event signals that the internal buffer was flushed at the given time.

Parameters

| | |
|----------------------|-------------------------------------|
| <i>writer</i> | Writer object. |
| <i>attributeList</i> | Generic attributes for the event. |
| <i>time</i> | The time for this event. |
| <i>stopTime</i> | The time the buffer flush finished. |

Since

Version 1.0

Returns

OTF2_SUCCESS if successful, an error code if an error occurs.

J.13 OTF2_EvtWriter.h File Reference

J.13.2.2 `OTF2_ErrorCode OTF2_EvtWriter_ClearRewindPoint (OTF2_EvtWriter * writer, uint32_t rewindId)`

Please give me a documentantation.

Parameters

| | |
|-----------------|-----------------------------------|
| <i>writer</i> | Writer object. |
| <i>rewindId</i> | Generic attributes for the event. |

Since

Version 1.1

Returns

[*OTF2_SUCCESS*](#) if successful, an error code if an error occurs.

J.13.2.3 `OTF2_ErrorCode OTF2_EvtWriter_Enter (OTF2_EvtWriter * writer, OTF2_AttributeList * attributeList, OTF2_TimeStamp time, OTF2_RegionRef region)`

Records an Enter event.

An enter record indicates that the program enters a code region.

Parameters

| | |
|----------------------|--|
| <i>writer</i> | Writer object. |
| <i>attributeList</i> | Generic attributes for the event. |
| <i>time</i> | The time for this event. |
| <i>region</i> | Needs to be defined in a definition record References a Region definition and will be mapped to the global definition if a mapping table of type OTF2_MAPPING_REGION is available. |

Since

Version 1.0

Returns

[*OTF2_SUCCESS*](#) if successful, an error code if an error occurs.

APPENDIX J. FILE DOCUMENTATION

J.13.2.4 `OTF2_ErrorCode OTF2_EvtWriter_GetLocationID (const OTF2_EvtWriter * writer, OTF2_LocationRef * locationID)`

Function to get the location ID of a writer object.

Parameters

| | |
|-------------------|---|
| <i>writer</i> | Writer object which has to be deleted |
| <i>locationID</i> | Pointer to a variable where the ID is returned in |

Returns

[*OTF2_SUCCESS*](#) if successful, an error code if an error occurs.

J.13.2.5 `OTF2_ErrorCode OTF2_EvtWriter_GetNumberOfEvents (OTF2_EvtWriter * writer, uint64_t * numberOfEvents)`

Get the number of events.

Get the number of events written with this event writer. You should call this function right before closing the event writer to get the correct number of stored event records.

Parameters

| | | |
|-----|-----------------------|---|
| | <i>writer</i> | Writer object. |
| out | <i>numberOfEvents</i> | Return pointer to the number of events. |

Returns

[*OTF2_SUCCESS*](#) if successful, an error code if an error occurs.

J.13.2.6 `OTF2_ErrorCode OTF2_EvtWriter_GetUserData (const OTF2_EvtWriter * writer, void ** userData)`

Function to get the location of a writer object.

Parameters

| | | |
|-----|-----------------|---|
| | <i>writer</i> | Writer object. |
| out | <i>userData</i> | Pointer to a variable where the pointer to the location is returned in. |

J.13 OTF2_EvtWriter.h File Reference

Returns

[OTF2_SUCCESS](#) if successful, an error code if an error occurs.

J.13.2.7 `OTF2_StatusCode OTF2_EvtWriter_Leave (OTF2_EvtWriter *
writer, OTF2_AttributeList * attributeList, OTF2_TimeStamp time,
OTF2_RegionRef region)`

Records an Leave event.

A leave record indicates that the program leaves a code region.

Parameters

| | |
|----------------------|--|
| <i>writer</i> | Writer object. |
| <i>attributeList</i> | Generic attributes for the event. |
| <i>time</i> | The time for this event. |
| <i>region</i> | Needs to be defined in a definition record References a Region definition and will be mapped to the global definition if a mapping table of type OTF2_MAPPING_REGION is available. |

Since

Version 1.0

Returns

[OTF2_SUCCESS](#) if successful, an error code if an error occurs.

J.13.2.8 `OTF2_StatusCode OTF2_EvtWriter_MeasurementOnOff (OTF2_EvtWriter
* writer, OTF2_AttributeList * attributeList, OTF2_TimeStamp time,
OTF2_MeasurementMode measurementMode)`

Records an MeasurementOnOff event.

This event signals where the measurement system turned measurement on or off.

Parameters

| | |
|------------------------------|---|
| <i>writer</i> | Writer object. |
| <i>attributeList</i> | Generic attributes for the event. |
| <i>time</i> | The time for this event. |
| <i>measure- mentMode</i> | Is the measurement turned on (OTF2_MEASUREMENT_ON) or off (OTF2_MEASUREMENT_OFF)? |

Since

Version 1.0

Returns

[OTF2_SUCCESS](#) if successful, an error code if an error occurs.

**J.13.2.9 OTF2_ErrorCode OTF2_EvtWriter.Metric (OTF2_EvtWriter *
writer, OTF2_AttributeList * attributeList, OTF2_TimeStamp time,
OTF2_MetricRef metric, uint8_t numberOfMetrics, const OTF2_Type *
typeIDs, const OTF2.MetricValue * metricValues)**

Records an Metric event.

A metric event is always stored at the location that recorded the metric. A metric event can reference a metric class or metric instance. Therefore, metric classes and instances share same ID space. Synchronous metrics are always located right before the according enter and leave event.

Parameters

| | |
|------------------------|--|
| <i>writer</i> | Writer object. |
| <i>attributeList</i> | Generic attributes for the event. |
| <i>time</i> | The time for this event. |
| <i>metric</i> | Could be a metric class or a metric instance. References a MetricClass , or a MetricInstance definition and will be mapped to the global definition if a mapping table of type OTF2_MAPPING_METRIC is available. |
| <i>numberOfMetrics</i> | Number of metrics with in the set. |
| <i>typeIDs</i> | List of metric types. |
| <i>metricValues</i> | List of metric values. |

Since

Version 1.0

Returns

[OTF2_SUCCESS](#) if successful, an error code if an error occurs.

J.13 OTF2_EvtWriter.h File Reference

J.13.2.10 `OTF2_ErrorCode OTF2_EvtWriter_MpiCollectiveBegin (OTF2_EvtWriter * writer, OTF2_AttributeList * attributeList, OTF2_TimeStamp time)`

Records an MpiCollectiveBegin event.

A MpiCollectiveBegin record marks the begin of an MPI collective operation (MPI_GATHER, MPI_SCATTER etc.).

Parameters

| | |
|----------------------|-----------------------------------|
| <i>writer</i> | Writer object. |
| <i>attributeList</i> | Generic attributes for the event. |
| <i>time</i> | The time for this event. |

Since

Version 1.0

Returns

[OTF2_SUCCESS](#) if successful, an error code if an error occurs.

J.13.2.11 `OTF2_ErrorCode OTF2_EvtWriter_MpiCollectiveEnd (OTF2_EvtWriter * writer, OTF2_AttributeList * attributeList, OTF2_TimeStamp time, OTF2_CollectiveOp collectiveOp, OTF2_CommRef communicator, uint32_t root, uint64_t sizeSent, uint64_t sizeReceived)`

Records an MpiCollectiveEnd event.

A MpiCollectiveEnd record marks the end of an MPI collective operation (MPI_GATHER, MPI_SCATTER etc.). It keeps the necessary information for this event: type of collective operation, communicator, the root of this collective operation. You can optionally add further information like sent and received bytes.

Parameters

| | |
|----------------------|--|
| <i>writer</i> | Writer object. |
| <i>attributeList</i> | Generic attributes for the event. |
| <i>time</i> | The time for this event. |
| <i>collectiveOp</i> | Determines which collective operation it is. |
| <i>communicator</i> | Communicator References a Comm definition and will be mapped to the global definition if a mapping table of type OTF2_MAPPING_COMM is available. |
| <i>root</i> | MPI rank of root in <i>communicator</i> . |

APPENDIX J. FILE DOCUMENTATION

| | |
|---------------------|-------------------------------|
| <i>sizeSent</i> | Size of the sent message. |
| <i>sizeReceived</i> | Size of the received message. |

Since

Version 1.0

Returns

[OTF2_SUCCESS](#) if successful, an error code if an error occurs.

J.13.2.12 **OTF2_ErrorCode** **OTF2_EvtWriter.Mpilrecv** (**OTF2_EvtWriter** * *writer*, **OTF2_AttributeList** * *attributeList*, **OTF2_TimeStamp** *time*, **uint32_t** *sender*, **OTF2_CommRef** *communicator*, **uint32_t** *msgTag*, **uint64_t** *msgLength*, **uint64_t** *requestID*)

Records an Mpilrecv event.

A Mpilrecv record indicates that a MPI message was received (MPI_IRecv). It keeps the necessary information for this event: sender of the message, communicator, and the message tag. You can optionally add further information like the message length (size of the receive buffer).

Parameters

| | |
|----------------------|--|
| <i>writer</i> | Writer object. |
| <i>attributeList</i> | Generic attributes for the event. |
| <i>time</i> | The time for this event. |
| <i>sender</i> | MPI rank of sender in <i>communicator</i> . |
| <i>communicator</i> | Communicator ID. References a Comm definition and will be mapped to the global definition if a mapping table of type OTF2_MAPPING_COMM is available. |
| <i>msgTag</i> | Message tag |
| <i>msgLength</i> | Message length |
| <i>requestID</i> | ID of the related request |

Since

Version 1.0

Returns

[OTF2_SUCCESS](#) if successful, an error code if an error occurs.

J.13 OTF2_EvtWriter.h File Reference

J.13.2.13 `OTF2_ErrorCode OTF2_EvtWriter.MpiIrecvRequest (OTF2_EvtWriter * writer, OTF2_AttributeList * attributeList, OTF2_TimeStamp time, uint64_t requestID)`

Records an MpiIrecvRequest event.

Signals the request of an receive, which can be completed later.

Parameters

| | |
|----------------------|-----------------------------------|
| <i>writer</i> | Writer object. |
| <i>attributeList</i> | Generic attributes for the event. |
| <i>time</i> | The time for this event. |
| <i>requestID</i> | ID of the requested receive |

Since

Version 1.0

Returns

[*OTF2_SUCCESS*](#) if successful, an error code if an error occurs.

J.13.2.14 `OTF2_ErrorCode OTF2_EvtWriter.MpIsend (OTF2_EvtWriter * writer, OTF2_AttributeList * attributeList, OTF2_TimeStamp time, uint32_t receiver, OTF2_CommRef communicator, uint32_t msgTag, uint64_t msgLength, uint64_t requestID)`

Records an MpIsend event.

A MpIsend record indicates that a MPI message send process was initiated (MPI_ISEND). It keeps the necessary information for this event: receiver of the message, communicator, and the message tag. You can optionally add further information like the message length (size of the send buffer).

Parameters

| | |
|----------------------|--|
| <i>writer</i> | Writer object. |
| <i>attributeList</i> | Generic attributes for the event. |
| <i>time</i> | The time for this event. |
| <i>receiver</i> | MPI rank of receiver in <i>communicator</i> . |
| <i>communicator</i> | Communicator ID. References a Comm definition and will be mapped to the global definition if a mapping table of type OTF2_MAPPING_COMM is available. |
| <i>msgTag</i> | Message tag |
| <i>msgLength</i> | Message length |
| <i>requestID</i> | ID of the related request |

Since

Version 1.0

Returns

OTF2_SUCCESS if successful, an error code if an error occurs.

J.13.2.15 `OTF2_ErrorCode OTF2_EvtWriter_MpiIsendComplete (OTF2_EvtWriter * writer, OTF2_AttributeList * attributeList, OTF2_TimeStamp time, uint64_t requestID)`

Records an MpiIsendComplete event.

Signals the completion of non-blocking send request.

Parameters

| | |
|----------------------|-----------------------------------|
| <i>writer</i> | Writer object. |
| <i>attributeList</i> | Generic attributes for the event. |
| <i>time</i> | The time for this event. |
| <i>requestID</i> | ID of the related request |

Since

Version 1.0

Returns

OTF2_SUCCESS if successful, an error code if an error occurs.

J.13.2.16 `OTF2_ErrorCode OTF2_EvtWriter_MpiRecv (OTF2_EvtWriter * writer, OTF2_AttributeList * attributeList, OTF2_TimeStamp time, uint32_t sender, OTF2_CommRef communicator, uint32_t msgTag, uint64_t msgLength)`

Records an MpiRecv event.

A MpiRecv record indicates that a MPI message was received (MPI_RECV). It keeps the necessary information for this event: sender of the message, communicator, and the message tag. You can optionally add further information like the message length (size of the receive buffer).

Parameters

J.13 OTF2_EvtWriter.h File Reference

| | |
|----------------------|--|
| <i>writer</i> | Writer object. |
| <i>attributeList</i> | Generic attributes for the event. |
| <i>time</i> | The time for this event. |
| <i>sender</i> | MPI rank of sender in <i>communicator</i> . |
| <i>communicator</i> | Communicator ID. References a Comm definition and will be mapped to the global definition if a mapping table of type OTF2_MAPPING_COMM is available. |
| <i>msgTag</i> | Message tag |
| <i>msgLength</i> | Message length |

Since

Version 1.0

Returns

[OTF2_SUCCESS](#) if successful, an error code if an error occurs.

J.13.2.17 [OTF2_ErrorCode](#) [OTF2_EvtWriter_MpiRequestCancelled](#) (
[OTF2_EvtWriter](#) * *writer*, [OTF2_AttributeList](#) * *attributeList*,
[OTF2_TimeStamp](#) *time*, [uint64_t](#) *requestID*)

Records an `MpiRequestCancelled` event.

This events appears if the program canceled a request.

Parameters

| | |
|----------------------|-----------------------------------|
| <i>writer</i> | Writer object. |
| <i>attributeList</i> | Generic attributes for the event. |
| <i>time</i> | The time for this event. |
| <i>requestID</i> | ID of the related request |

Since

Version 1.0

Returns

[OTF2_SUCCESS](#) if successful, an error code if an error occurs.

APPENDIX J. FILE DOCUMENTATION

J.13.2.18 `OTF2_ErrorCode OTF2_EvtWriter.MpiRequestTest (OTF2_EvtWriter * writer, OTF2_AttributeList * attributeList, OTF2_TimeStamp time, uint64_t requestID)`

Records an MpiRequestTest event.

This events appears if the program tests if a request has already completed but the test failed.

Parameters

| | |
|----------------------|-----------------------------------|
| <i>writer</i> | Writer object. |
| <i>attributeList</i> | Generic attributes for the event. |
| <i>time</i> | The time for this event. |
| <i>requestID</i> | ID of the related request |

Since

Version 1.0

Returns

[*OTF2_SUCCESS*](#) if successful, an error code if an error occurs.

J.13.2.19 `OTF2_ErrorCode OTF2_EvtWriter.MpiSend (OTF2_EvtWriter * writer, OTF2_AttributeList * attributeList, OTF2_TimeStamp time, uint32_t receiver, OTF2_CommRef communicator, uint32_t msgTag, uint64_t msgLength)`

Records an MpiSend event.

A MpiSend record indicates that a MPI message send process was initiated (MPI_SEND). It keeps the necessary information for this event: receiver of the message, communicator, and the message tag. You can optionally add further information like the message length (size of the send buffer).

Parameters

| | |
|----------------------|--|
| <i>writer</i> | Writer object. |
| <i>attributeList</i> | Generic attributes for the event. |
| <i>time</i> | The time for this event. |
| <i>receiver</i> | MPI rank of receiver in <i>communicator</i> . |
| <i>communicator</i> | Communicator ID. References a Comm definition and will be mapped to the global definition if a mapping table of type OTF2_MAPPING_COMM is available. |
| <i>msgTag</i> | Message tag |
| <i>msgLength</i> | Message length |

J.13 OTF2_EvtWriter.h File Reference

Since

Version 1.0

Returns

[OTF2_SUCCESS](#) if successful, an error code if an error occurs.

J.13.2.20 `OTF2_ErrorCode OTF2_EvtWriter_OmpAcquireLock (OTF2_EvtWriter * writer, OTF2_AttributeList * attributeList, OTF2_TimeStamp time, uint32_t lockID, uint32_t acquisitionOrder)`

Records an OmpAcquireLock event.

An OmpAcquireLock record marks that a thread acquires an OpenMP lock.

This event record is superseded by the [ThreadAcquireLock](#) event record and should not be used when the [ThreadAcquireLock](#) event record is in use record.

Parameters

| | |
|-------------------------|---|
| <i>writer</i> | Writer object. |
| <i>attributeList</i> | Generic attributes for the event. |
| <i>time</i> | The time for this event. |
| <i>lockID</i> | ID of the lock. |
| <i>acquisitionOrder</i> | A monotonically increasing number to determine the order of lock acquisitions (with unsynchronized clocks this is otherwise not possible). Corresponding acquire-release events have same number. |

Since

Version 1.0

Deprecated

In version 1.2

Returns

[OTF2_SUCCESS](#) if successful, an error code if an error occurs.

J.13.2.21 `OTF2_ErrorCode OTF2_EvtWriter_OmpFork (OTF2_EvtWriter * writer, OTF2_AttributeList * attributeList, OTF2_TimeStamp time, uint32_t numberOfRequestedThreads)`

Records an OmpFork event.

APPENDIX J. FILE DOCUMENTATION

An OmpFork record marks that an OpenMP Thread forks a thread team.

This event record is superseded by the *ThreadFork* event record and should not be used when the *ThreadFork* event record is in use.

Parameters

| | |
|------------------------------------|-----------------------------------|
| <i>writer</i> | Writer object. |
| <i>attributeList</i> | Generic attributes for the event. |
| <i>time</i> | The time for this event. |
| <i>num-berOfRe-quest-edThreads</i> | Requested size of the team. |

Since

Version 1.0

Deprecated

In version 1.2

Returns

OTF2_SUCCESS if successful, an error code if an error occurs.

J.13.2.22 *OTF2_ErrorCode* *OTF2_EvtWriter_OmpJoin* (*OTF2_EvtWriter* * *writer*,
OTF2_AttributeList * *attributeList*, *OTF2_TimeStamp* *time*)

Records an OmpJoin event.

An OmpJoin record marks that a team of threads is joint and only the master thread continues execution.

This event record is superseded by the *ThreadJoin* event record and should not be used when the *ThreadJoin* event record is in use.

Parameters

| | |
|----------------------|-----------------------------------|
| <i>writer</i> | Writer object. |
| <i>attributeList</i> | Generic attributes for the event. |
| <i>time</i> | The time for this event. |

Since

Version 1.0

J.13 OTF2_EvtWriter.h File Reference

Deprecated

In version 1.2

Returns

OTF2_SUCCESS if successful, an error code if an error occurs.

J.13.2.23 `OTF2_ErrorCode OTF2_EvtWriter.OmpReleaseLock (OTF2_EvtWriter * writer, OTF2_AttributeList * attributeList, OTF2_TimeStamp time, uint32_t lockID, uint32_t acquisitionOrder)`

Records an OmpReleaseLock event.

An OmpReleaseLock record marks that a thread releases an OpenMP lock.

This event record is superseded by the *ThreadReleaseLock* event record and should not be used when the *ThreadReleaseLock* event record is in use.

Parameters

| | |
|-------------------------|---|
| <i>writer</i> | Writer object. |
| <i>attributeList</i> | Generic attributes for the event. |
| <i>time</i> | The time for this event. |
| <i>lockID</i> | ID of the lock. |
| <i>acquisitionOrder</i> | A monotonically increasing number to determine the order of lock acquisitions (with unsynchronized clocks this is otherwise not possible). Corresponding acquire-release events have same number. |

Since

Version 1.0

Deprecated

In version 1.2

Returns

OTF2_SUCCESS if successful, an error code if an error occurs.

J.13.2.24 `OTF2_ErrorCode OTF2_EvtWriter.OmpTaskComplete (OTF2_EvtWriter * writer, OTF2_AttributeList * attributeList, OTF2_TimeStamp time, uint64_t taskID)`

Records an OmpTaskComplete event.

APPENDIX J. FILE DOCUMENTATION

An `OmpTaskComplete` record indicates that the execution of an OpenMP task has finished.

This event record is superseded by the [ThreadTaskComplete](#) event record and should not be used when the [ThreadTaskComplete](#) event record is in use.

Parameters

| | |
|----------------------|--|
| <i>writer</i> | Writer object. |
| <i>attributeList</i> | Generic attributes for the event. |
| <i>time</i> | The time for this event. |
| <i>taskID</i> | Identifier of the completed task instance. |

Since

Version 1.0

Deprecated

In version 1.2

Returns

[OTF2_SUCCESS](#) if successful, an error code if an error occurs.

J.13.2.25 `OTF2_ErrorCode OTF2_EvtWriter_OmpTaskCreate (OTF2_EvtWriter * writer, OTF2_AttributeList * attributeList, OTF2_TimeStamp time, uint64_t taskID)`

Records an `OmpTaskCreate` event.

An `OmpTaskCreate` record marks that an OpenMP Task was/will be created in the current region.

This event record is superseded by the [ThreadTaskCreate](#) event record and should not be used when the [ThreadTaskCreate](#) event record is in use.

Parameters

| | |
|----------------------|--|
| <i>writer</i> | Writer object. |
| <i>attributeList</i> | Generic attributes for the event. |
| <i>time</i> | The time for this event. |
| <i>taskID</i> | Identifier of the newly created task instance. |

Since

Version 1.0

J.13 OTF2_EvtWriter.h File Reference

Deprecated

In version 1.2

Returns

OTF2_SUCCESS if successful, an error code if an error occurs.

J.13.2.26 `OTF2_ErrorCode OTF2_EvtWriter_OmpTaskSwitch (OTF2_EvtWriter * writer, OTF2_AttributeList * attributeList, OTF2_TimeStamp time, uint64_t taskID)`

Records an OmpTaskSwitch event.

An OmpTaskSwitch record indicates that the execution of the current task will be suspended and another task starts/restarts its execution. Please note that this may change the current call stack of the executing location.

This event record is superseded by the *ThreadTaskSwitch* event record and should not be used when the *ThreadTaskSwitch* event record is in use.

Parameters

| | |
|----------------------|---|
| <i>writer</i> | Writer object. |
| <i>attributeList</i> | Generic attributes for the event. |
| <i>time</i> | The time for this event. |
| <i>taskID</i> | Identifier of the now active task instance. |

Since

Version 1.0

Deprecated

In version 1.2

Returns

OTF2_SUCCESS if successful, an error code if an error occurs.

J.13.2.27 `OTF2_ErrorCode OTF2_EvtWriter_ParameterInt (OTF2_EvtWriter * writer, OTF2_AttributeList * attributeList, OTF2_TimeStamp time, OTF2_ParameterRef parameter, int64_t value)`

Records an ParameterInt event.

APPENDIX J. FILE DOCUMENTATION

A ParameterInt record marks that in the current region, the specified integer parameter has the specified value.

Parameters

| | |
|----------------------|---|
| <i>writer</i> | Writer object. |
| <i>attributeList</i> | Generic attributes for the event. |
| <i>time</i> | The time for this event. |
| <i>parameter</i> | Parameter ID. References a Parameter definition and will be mapped to the global definition if a mapping table of type OTF2_MAPPING_PARAMETER is available. |
| <i>value</i> | Value of the recorded parameter. |

Since

Version 1.0

Returns

[OTF2_SUCCESS](#) if successful, an error code if an error occurs.

J.13.2.28 `OTF2_ErrorCode OTF2_EvtWriter.ParameterString (OTF2_EvtWriter * writer, OTF2_AttributeList * attributeList, OTF2_TimeStamp time, OTF2_ParameterRef parameter, OTF2_StringRef string)`

Records an ParameterString event.

A ParameterString record marks that in the current region, the specified string parameter has the specified value.

Parameters

| | |
|----------------------|--|
| <i>writer</i> | Writer object. |
| <i>attributeList</i> | Generic attributes for the event. |
| <i>time</i> | The time for this event. |
| <i>parameter</i> | Parameter ID. References a Parameter definition and will be mapped to the global definition if a mapping table of type OTF2_MAPPING_PARAMETER is available. |
| <i>string</i> | Value: Handle of a string definition References a String definition and will be mapped to the global definition if a mapping table of type OTF2_MAPPING_STRING is available. |

Since

Version 1.0

J.13 OTF2_EvtWriter.h File Reference

Returns

[*OTF2_SUCCESS*](#) if successful, an error code if an error occurs.

J.13.2.29 `OTF2_StatusCode OTF2_EvtWriter_ParameterUnsignedInt (OTF2_EvtWriter * writer, OTF2_AttributeList * attributeList, OTF2_TimeStamp time, OTF2_ParameterRef parameter, uint64_t value)`

Records an ParameterUnsignedInt event.

A ParameterUnsignedInt record marks that in the current region, the specified unsigned integer parameter has the specified value.

Parameters

| | |
|----------------------|---|
| <i>writer</i> | Writer object. |
| <i>attributeList</i> | Generic attributes for the event. |
| <i>time</i> | The time for this event. |
| <i>parameter</i> | Parameter ID. References a Parameter definition and will be mapped to the global definition if a mapping table of type OTF2_MAPPING_PARAMETER is available. |
| <i>value</i> | Value of the recorded parameter. |

Since

Version 1.0

Returns

[*OTF2_SUCCESS*](#) if successful, an error code if an error occurs.

J.13.2.30 `OTF2_StatusCode OTF2_EvtWriter_Rewind (OTF2_EvtWriter * writer, uint32_t rewindId)`

Please give me a documantation.

Parameters

| | |
|-----------------|-----------------------------------|
| <i>writer</i> | Writer object. |
| <i>rewindId</i> | Generic attributes for the event. |

Since

Version 1.1

Returns

OTF2_SUCCESS if successful, an error code if an error occurs.

J.13.2.31 `OTF2_StatusCode OTF2_EvtWriter_RmaAcquireLock (OTF2_EvtWriter * writer, OTF2_AttributeList * attributeList, OTF2_TimeStamp time, OTF2_RmaWinRef win, uint32_t remote, uint64_t lockId, OTF2_LockType lockType)`

Records an RmaAcquireLock event.

An RmaAcquireLock record denotes the time a lock was acquired by the process.

Parameters

| | |
|----------------------|--|
| <i>writer</i> | Writer object. |
| <i>attributeList</i> | Generic attributes for the event. |
| <i>time</i> | The time for this event. |
| <i>win</i> | ID of the window used for this operation. References a RmaWin definition and will be mapped to the global definition if a mapping table of type OTF2_MAPPING_RMA_WIN is available. |
| <i>remote</i> | Rank of the locked remote process. |
| <i>lockId</i> | ID of the lock acquired, if multiple locks are defined on a window. |
| <i>lockType</i> | Type of lock acquired. |

Since

Version 1.2

Returns

OTF2_SUCCESS if successful, an error code if an error occurs.

J.13.2.32 `OTF2_StatusCode OTF2_EvtWriter_RmaAtomic (OTF2_EvtWriter * writer, OTF2_AttributeList * attributeList, OTF2_TimeStamp time, OTF2_RmaWinRef win, uint32_t remote, OTF2_RmaAtomicType type, uint64_t bytesSent, uint64_t bytesReceived, uint64_t matchingId)`

Records an RmaAtomic event.

An RmaAtomic record denotes the time a atomic operation was issued.

J.13 OTF2_EvtWriter.h File Reference

Parameters

| | |
|----------------------|--|
| <i>writer</i> | Writer object. |
| <i>attributeList</i> | Generic attributes for the event. |
| <i>time</i> | The time for this event. |
| <i>win</i> | ID of the window used for this operation. References a RmaWin definition and will be mapped to the global definition if a mapping table of type OTF2_MAPPING_RMA_WIN is available. |
| <i>remote</i> | Rank of the target process. |
| <i>type</i> | Type of atomic operation. |
| <i>bytesSent</i> | Bytes sent to target. |
| <i>bytesReceived</i> | Bytes received from target. |
| <i>matchingId</i> | ID used for matching the appropriate completion record. |

Since

Version 1.2

Returns

[OTF2_SUCCESS](#) if successful, an error code if an error occurs.

J.13.2.33 `OTF2_ErrorCode OTF2_EvtWriter_RmaCollectiveBegin (OTF2_EvtWriter * writer, OTF2_AttributeList * attributeList, OTF2_TimeStamp time)`

Records an RmaCollectiveBegin event.

An RmaCollectiveBegin record denotes the beginning of a collective RMA operation.

Parameters

| | |
|----------------------|-----------------------------------|
| <i>writer</i> | Writer object. |
| <i>attributeList</i> | Generic attributes for the event. |
| <i>time</i> | The time for this event. |

Since

Version 1.2

Returns

[OTF2_SUCCESS](#) if successful, an error code if an error occurs.

APPENDIX J. FILE DOCUMENTATION

J.13.2.34 `OTF2_ErrorCode OTF2_EvtWriter.RmaCollectiveEnd (OTF2_EvtWriter * writer, OTF2_AttributeList * attributeList, OTF2_TimeStamp time, OTF2_CollectiveOp collectiveOp, OTF2_RmaSyncLevel syncLevel, OTF2_RmaWinRef win, uint32_t root, uint64_t bytesSent, uint64_t bytesReceived)`

Records an RmaCollectiveEnd event.

"An RmaCollectiveEnd record denotes the end of a collective RMA operation.

Parameters

| | |
|----------------------|--|
| <i>writer</i> | Writer object. |
| <i>attributeList</i> | Generic attributes for the event. |
| <i>time</i> | The time for this event. |
| <i>collectiveOp</i> | Determines which collective operation it is. |
| <i>syncLevel</i> | Synchronization level of this collective operation. |
| <i>win</i> | ID of the window used for this operation. References a RmaWin definition and will be mapped to the global definition if a mapping table of type OTF2_MAPPING_RMA_WIN is available. |
| <i>root</i> | Root process for this operation. |
| <i>bytesSent</i> | Bytes sent in operation. |
| <i>bytesReceived</i> | Bytes receives in operation. |

Since

Version 1.2

Returns

[OTF2_SUCCESS](#) if successful, an error code if an error occurs.

J.13.2.35 `OTF2_ErrorCode OTF2_EvtWriter.RmaGet (OTF2_EvtWriter * writer, OTF2_AttributeList * attributeList, OTF2_TimeStamp time, OTF2_RmaWinRef win, uint32_t remote, uint64_t bytes, uint64_t matchingId)`

Records an RmaGet event.

An RmaGet record denotes the time a put operation was issued.

Parameters

J.13 OTF2_EvtWriter.h File Reference

| | |
|----------------------|--|
| <i>writer</i> | Writer object. |
| <i>attributeList</i> | Generic attributes for the event. |
| <i>time</i> | The time for this event. |
| <i>win</i> | ID of the window used for this operation. References a RmaWin definition and will be mapped to the global definition if a mapping table of type OTF2_MAPPING_RMA_WIN is available. |
| <i>remote</i> | Rank of the target process. |
| <i>bytes</i> | Bytes received from target. |
| <i>matchingId</i> | ID used for matching the appropriate completion record. |

Since

Version 1.2

Returns

[OTF2_SUCCESS](#) if successful, an error code if an error occurs.

J.13.2.36 `OTF2_ErrorCode OTF2_EvtWriter_RmaGroupSync (OTF2_EvtWriter * writer, OTF2_AttributeList * attributeList, OTF2_TimeStamp time, OTF2_RmaSyncLevel syncLevel, OTF2_RmaWinRef win, OTF2_GroupRef group)`

Records an RmaGroupSync event.

An RmaGroupSync record denotes the synchronization with a subgroup of processes on a window.

Parameters

| | |
|----------------------|--|
| <i>writer</i> | Writer object. |
| <i>attributeList</i> | Generic attributes for the event. |
| <i>time</i> | The time for this event. |
| <i>syncLevel</i> | Synchronization level of this collective operation. |
| <i>win</i> | ID of the window used for this operation. References a RmaWin definition and will be mapped to the global definition if a mapping table of type OTF2_MAPPING_RMA_WIN is available. |
| <i>group</i> | Group of remote processes involved in synchronization. References a Group definition and will be mapped to the global definition if a mapping table of type OTF2_MAPPING_GROUP is available. |

Since

Version 1.2

Returns

OTF2_SUCCESS if successful, an error code if an error occurs.

J.13.2.37 `OTF2_StatusCode OTF2_EvtWriter.RmaOpCompleteBlocking (OTF2_EvtWriter * writer, OTF2_AttributeList * attributeList, OTF2_TimeStamp time, OTF2_RmaWinRef win, uint64_t matchingId)`

Records an RmaOpCompleteBlocking event.

An RmaOpCompleteBlocking record denotes the local completion of a blocking RMA operation.

Parameters

| | |
|----------------------|--|
| <i>writer</i> | Writer object. |
| <i>attributeList</i> | Generic attributes for the event. |
| <i>time</i> | The time for this event. |
| <i>win</i> | ID of the window used for this operation. References a RmaWin definition and will be mapped to the global definition if a mapping table of type OTF2_MAPPING_RMA_WIN is available. |
| <i>matchingId</i> | ID used for matching the appropriate completion record. |

Since

Version 1.2

Returns

OTF2_SUCCESS if successful, an error code if an error occurs.

J.13.2.38 `OTF2_StatusCode OTF2_EvtWriter.RmaOpCompleteNonBlocking (OTF2_EvtWriter * writer, OTF2_AttributeList * attributeList, OTF2_TimeStamp time, OTF2_RmaWinRef win, uint64_t matchingId)`

Records an RmaOpCompleteNonBlocking event.

An RmaOpCompleteNonBlocking record denotes the local completion of a non-blocking RMA operation.

Parameters

| | |
|----------------------|-----------------------------------|
| <i>writer</i> | Writer object. |
| <i>attributeList</i> | Generic attributes for the event. |
| <i>time</i> | The time for this event. |

J.13 OTF2_EvtWriter.h File Reference

| | |
|-------------------|--|
| <i>win</i> | ID of the window used for this operation. References a RmaWin definition and will be mapped to the global definition if a mapping table of type OTF2_MAPPING_RMA_WIN is available. |
| <i>matchingId</i> | ID used for matching the appropriate completion record. |

Since

Version 1.2

Returns

[OTF2_SUCCESS](#) if successful, an error code if an error occurs.

J.13.2.39 OTF2_ErrorCode OTF2_EvtWriter.RmaOpCompleteRemote (OTF2_EvtWriter * *writer*, OTF2_AttributeList * *attributeList*, OTF2_TimeStamp *time*, OTF2_RmaWinRef *win*, uint64_t *matchingId*)

Records an RmaOpCompleteRemote event.

An RmaOpCompleteRemote record denotes the local completion of an RMA operation.

Parameters

| | |
|----------------------|--|
| <i>writer</i> | Writer object. |
| <i>attributeList</i> | Generic attributes for the event. |
| <i>time</i> | The time for this event. |
| <i>win</i> | ID of the window used for this operation. References a RmaWin definition and will be mapped to the global definition if a mapping table of type OTF2_MAPPING_RMA_WIN is available. |
| <i>matchingId</i> | ID used for matching the appropriate completion record. |

Since

Version 1.2

Returns

[OTF2_SUCCESS](#) if successful, an error code if an error occurs.

APPENDIX J. FILE DOCUMENTATION

J.13.2.40 **OTF2_ErrorCode** **OTF2_EvtWriter.RmaOpTest** (**OTF2_EvtWriter** * *writer*, **OTF2_AttributeList** * *attributeList*, **OTF2_TimeStamp** *time*, **OTF2_RmaWinRef** *win*, **uint64_t** *matchingId*)

Records an RmaOpTest event.

An RmaOpTest record denotes that a non-blocking RMA operation has been tested for completion unsuccessfully.

Parameters

| | |
|----------------------|--|
| <i>writer</i> | Writer object. |
| <i>attributeList</i> | Generic attributes for the event. |
| <i>time</i> | The time for this event. |
| <i>win</i> | ID of the window used for this operation. References a RmaWin definition and will be mapped to the global definition if a mapping table of type OTF2_MAPPING_RMA_WIN is available. |
| <i>matchingId</i> | ID used for matching the appropriate completion record. |

Since

Version 1.2

Returns

[OTF2_SUCCESS](#) if successful, an error code if an error occurs.

J.13.2.41 **OTF2_ErrorCode** **OTF2_EvtWriter.RmaPut** (**OTF2_EvtWriter** * *writer*, **OTF2_AttributeList** * *attributeList*, **OTF2_TimeStamp** *time*, **OTF2_RmaWinRef** *win*, **uint32_t** *remote*, **uint64_t** *bytes*, **uint64_t** *matchingId*)

Records an RmaPut event.

An RmaPut record denotes the time a put operation was issued.

Parameters

| | |
|----------------------|--|
| <i>writer</i> | Writer object. |
| <i>attributeList</i> | Generic attributes for the event. |
| <i>time</i> | The time for this event. |
| <i>win</i> | ID of the window used for this operation. References a RmaWin definition and will be mapped to the global definition if a mapping table of type OTF2_MAPPING_RMA_WIN is available. |
| <i>remote</i> | Rank of the target process. |
| <i>bytes</i> | Bytes sent to target. |
| <i>matchingId</i> | ID used for matching the appropriate completion record. |

J.13 OTF2_EvtWriter.h File Reference

Since

Version 1.2

Returns

[OTF2_SUCCESS](#) if successful, an error code if an error occurs.

J.13.2.42 `OTF2_ErrorCode OTF2_EvtWriter_RmaReleaseLock (OTF2_EvtWriter *
writer, OTF2_AttributeList * attributeList, OTF2_TimeStamp time,
OTF2_RmaWinRef win, uint32_t remote, uint64_t lockId)`

Records an RmaReleaseLock event.

An RmaReleaseLock record denotes the time the lock was released.

Parameters

| | |
|----------------------|--|
| <i>writer</i> | Writer object. |
| <i>attributeList</i> | Generic attributes for the event. |
| <i>time</i> | The time for this event. |
| <i>win</i> | ID of the window used for this operation. References a RmaWin definition and will be mapped to the global definition if a mapping table of type OTF2_MAPPING_RMA_WIN is available. |
| <i>remote</i> | Rank of the locked remote process. |
| <i>lockId</i> | ID of the lock released, if multiple locks are defined on a window. |

Since

Version 1.2

Returns

[OTF2_SUCCESS](#) if successful, an error code if an error occurs.

J.13.2.43 `OTF2_ErrorCode OTF2_EvtWriter_RmaRequestLock (OTF2_EvtWriter
* writer, OTF2_AttributeList * attributeList, OTF2_TimeStamp
time, OTF2_RmaWinRef win, uint32_t remote, uint64_t lockId,
OTF2_LockType lockType)`

Records an RmaRequestLock event.

An RmaRequestLock record denotes the time a lock was requested and with it the earliest time it could have been granted. It is used to mark (possibly) non-blocking lock request, as defined by the MPI standard.

APPENDIX J. FILE DOCUMENTATION

Parameters

| | |
|----------------------|--|
| <i>writer</i> | Writer object. |
| <i>attributeList</i> | Generic attributes for the event. |
| <i>time</i> | The time for this event. |
| <i>win</i> | ID of the window used for this operation. References a RmaWin definition and will be mapped to the global definition if a mapping table of type OTF2_MAPPING_RMA_WIN is available. |
| <i>remote</i> | Rank of the locked remote process. |
| <i>lockId</i> | ID of the lock acquired, if multiple locks are defined on a window. |
| <i>lockType</i> | Type of lock acquired. |

Since

Version 1.2

Returns

[OTF2_SUCCESS](#) if successful, an error code if an error occurs.

J.13.2.44 `OTF2_StatusCode OTF2_EvtWriter.RmaSync (OTF2_EvtWriter *
writer, OTF2_AttributeList * attributeList, OTF2_TimeStamp time,
OTF2_RmaWinRef win, uint32_t remote, OTF2_RmaSyncType
syncType)`

Records an RmaSync event.

An RmaSync record denotes the direct synchronization with a possibly remote process.

Parameters

| | |
|----------------------|--|
| <i>writer</i> | Writer object. |
| <i>attributeList</i> | Generic attributes for the event. |
| <i>time</i> | The time for this event. |
| <i>win</i> | ID of the window used for this operation. References a RmaWin definition and will be mapped to the global definition if a mapping table of type OTF2_MAPPING_RMA_WIN is available. |
| <i>remote</i> | Rank of the locked remote process. |
| <i>syncType</i> | Type of synchronization. |

Since

Version 1.2

J.13 OTF2_EvtWriter.h File Reference

Returns

[*OTF2_SUCCESS*](#) if successful, an error code if an error occurs.

J.13.2.45 `OTF2_StatusCode OTF2_EvtWriter.RmaTryLock (OTF2_EvtWriter * writer, OTF2_AttributeList * attributeList, OTF2_TimeStamp time, OTF2_RmaWinRef win, uint32_t remote, uint64_t lockId, OTF2_LockType lockType)`

Records an RmaTryLock event.

An RmaTryLock record denotes the time of an unsuccessful attempt to acquire the lock.

Parameters

| | |
|----------------------|--|
| <i>writer</i> | Writer object. |
| <i>attributeList</i> | Generic attributes for the event. |
| <i>time</i> | The time for this event. |
| <i>win</i> | ID of the window used for this operation. References a RmaWin definition and will be mapped to the global definition if a mapping table of type OTF2_MAPPING_RMA_WIN is available. |
| <i>remote</i> | Rank of the locked remote process. |
| <i>lockId</i> | ID of the lock acquired, if multiple locks are defined on a window. |
| <i>lockType</i> | Type of lock acquired. |

Since

Version 1.2

Returns

[*OTF2_SUCCESS*](#) if successful, an error code if an error occurs.

J.13.2.46 `OTF2_StatusCode OTF2_EvtWriter.RmaWaitChange (OTF2_EvtWriter * writer, OTF2_AttributeList * attributeList, OTF2_TimeStamp time, OTF2_RmaWinRef win)`

Records an RmaWaitChange event.

An RmaWaitChange record denotes the change of a window that was waited for.

Parameters

| | |
|---------------|----------------|
| <i>writer</i> | Writer object. |
|---------------|----------------|

APPENDIX J. FILE DOCUMENTATION

| | |
|----------------------|--|
| <i>attributeList</i> | Generic attributes for the event. |
| <i>time</i> | The time for this event. |
| <i>win</i> | ID of the window used for this operation. References a RmaWin definition and will be mapped to the global definition if a mapping table of type OTF2_MAPPING_RMA_WIN is available. |

Since

Version 1.2

Returns

[OTF2_SUCCESS](#) if successful, an error code if an error occurs.

J.13.2.47 `OTF2_ErrorCode OTF2_EvtWriter.RmaWinCreate (OTF2_EvtWriter *
writer, OTF2_AttributeList * attributeList, OTF2_TimeStamp time,
OTF2_RmaWinRef win)`

Records an RmaWinCreate event.

An RmaWinCreate record denotes the creation of an RMA window.

Parameters

| | |
|----------------------|--|
| <i>writer</i> | Writer object. |
| <i>attributeList</i> | Generic attributes for the event. |
| <i>time</i> | The time for this event. |
| <i>win</i> | ID of the window created. References a RmaWin definition and will be mapped to the global definition if a mapping table of type OTF2_MAPPING_RMA_WIN is available. |

Since

Version 1.2

Returns

[OTF2_SUCCESS](#) if successful, an error code if an error occurs.

J.13.2.48 `OTF2_ErrorCode OTF2_EvtWriter.RmaWinDestroy (OTF2_EvtWriter *
writer, OTF2_AttributeList * attributeList, OTF2_TimeStamp time,
OTF2_RmaWinRef win)`

Records an RmaWinDestroy event.

J.13 OTF2_EvtWriter.h File Reference

An RmaWinDestroy record denotes the destruction of an RMA window.

Parameters

| | |
|----------------------|---|
| <i>writer</i> | Writer object. |
| <i>attributeList</i> | Generic attributes for the event. |
| <i>time</i> | The time for this event. |
| <i>win</i> | ID of the window destroyed. References a RmaWin definition and will be mapped to the global definition if a mapping table of type OTF2_-MAPPING_RMA_WIN is available. |

Since

Version 1.2

Returns

[OTF2_SUCCESS](#) if successful, an error code if an error occurs.

J.13.2.49 OTF2_ErrorCode OTF2_EvtWriter_SetLocationID (OTF2_EvtWriter * *writer*, OTF2_LocationRef *location*)

The location ID is not always known on measurement start, and only needed on the first buffer flush to generate the file name. This function enables setting of the location ID after generating the buffer object.

Parameters

| | |
|-----------------|----------------|
| <i>writer</i> | Writer object. |
| <i>location</i> | Location ID. |

Returns

[OTF2_SUCCESS](#) if successful, an error code if an error occurs.

J.13.2.50 OTF2_ErrorCode OTF2_EvtWriter_SetUserData (OTF2_EvtWriter * *writer*, void * *userData*)

Function to set user defined data to a writer object.

Parameters

| | |
|-----------------|---|
| <i>writer</i> | Writer object. |
| <i>userData</i> | User provided data. Can be queried with OTF2_EvtWriter_-GetUserData . |

Returns

OTF2_SUCCESS if successful, an error code if an error occurs.

J.13.2.51 `OTF2_StatusCode OTF2_EvtWriter_StoreRewindPoint (OTF2_EvtWriter * writer, uint32_t rewindId)`

Please give me a documantation.

Parameters

| | |
|-----------------|-----------------------------------|
| <i>writer</i> | Writer object. |
| <i>rewindId</i> | Generic attributes for the event. |

Since

Version 1.1

Returns

OTF2_SUCCESS if successful, an error code if an error occurs.

J.13.2.52 `OTF2_StatusCode OTF2_EvtWriter_ThreadAcquireLock (OTF2_EvtWriter * writer, OTF2_AttributeList * attributeList, OTF2_TimeStamp time, OTF2_Paradigm model, uint32_t lockID, uint32_t acquisitionOrder)`

Records an ThreadAcquireLock event.

An ThreadAcquireLock record marks that a thread acquires an lock.

Parameters

| | |
|-------------------------|---|
| <i>writer</i> | Writer object. |
| <i>attributeList</i> | Generic attributes for the event. |
| <i>time</i> | The time for this event. |
| <i>lockID</i> | ID of the lock. |
| <i>acquisitionOrder</i> | A monotonically increasing number to determine the order of lock acquisitions (with unsynchronized clocks this is otherwise not possible). Corresponding acquire-release events have same number. |

Since

Version 1.2

J.13 OTF2_EvtWriter.h File Reference

Returns

[*OTF2_SUCCESS*](#) if successful, an error code if an error occurs.

J.13.2.53 `OTF2_StatusCode OTF2_EvtWriter.ThreadFork (OTF2_EvtWriter *
writer, OTF2_AttributeList * attributeList, OTF2_TimeStamp time,
OTF2_Paradigm model, uint32_t numberOfRequestedThreads)`

Records an ThreadFork event.

An ThreadFork record marks that an thread forks a thread team.

Parameters

| | |
|---|-----------------------------------|
| <i>writer</i> | Writer object. |
| <i>attributeList</i> | Generic attributes for the event. |
| <i>time</i> | The time for this event. |
| <i>num- berOfRe- quest- edThreads</i> | Requested size of the team. |

Since

Version 1.2

Returns

[*OTF2_SUCCESS*](#) if successful, an error code if an error occurs.

J.13.2.54 `OTF2_StatusCode OTF2_EvtWriter.ThreadJoin (OTF2_EvtWriter *
writer, OTF2_AttributeList * attributeList, OTF2_TimeStamp time,
OTF2_Paradigm model)`

Records an ThreadJoin event.

An ThreadJoin record marks that a team of threads is joint and only the master thread continues execution.

Parameters

| | |
|----------------------|-----------------------------------|
| <i>writer</i> | Writer object. |
| <i>attributeList</i> | Generic attributes for the event. |
| <i>time</i> | The time for this event. |

Since

Version 1.2

Returns

OTF2_SUCCESS if successful, an error code if an error occurs.

J.13.2.55 `OTF2_ErrorCode OTF2_EvtWriter_ThreadReleaseLock (OTF2_EvtWriter * writer, OTF2_AttributeList * attributeList, OTF2_TimeStamp time, OTF2_Paradigm model, uint32_t lockID, uint32_t acquisitionOrder)`

Records an ThreadReleaseLock event.

An ThreadReleaseLock record marks that a thread releases an lock.

Parameters

| | |
|-------------------------|---|
| <i>writer</i> | Writer object. |
| <i>attributeList</i> | Generic attributes for the event. |
| <i>time</i> | The time for this event. |
| <i>lockID</i> | ID of the lock. |
| <i>acquisitionOrder</i> | A monotonically increasing number to determine the order of lock acquisitions (with unsynchronized clocks this is otherwise not possible). Corresponding acquire-release events have same number. |

Since

Version 1.2

Returns

OTF2_SUCCESS if successful, an error code if an error occurs.

J.13.2.56 `OTF2_ErrorCode OTF2_EvtWriter_ThreadTaskComplete (OTF2_EvtWriter * writer, OTF2_AttributeList * attributeList, OTF2_TimeStamp time, OTF2_CommRef threadTeam, uint32_t creatingThread, uint32_t generationNumber)`

Records an ThreadTaskComplete event.

An ThreadTaskComplete record indicates that the execution of an OpenMP task has finished.

Parameters

J.13 OTF2_EvtWriter.h File Reference

| | |
|-------------------------|---|
| <i>writer</i> | Writer object. |
| <i>attributeList</i> | Generic attributes for the event. |
| <i>time</i> | The time for this event. |
| <i>threadTeam</i> | Thread team References a Comm definition and will be mapped to the global definition if a mapping table of type OTF2_MAPPING_COMM is available. |
| <i>creatingThread</i> | Creating thread of this task. |
| <i>generationNumber</i> | Thread-private generation number of task's creating thread. |

Since

Version 1.2

Returns

[OTF2_SUCCESS](#) if successful, an error code if an error occurs.

J.13.2.57 `OTF2_StatusCode OTF2_EvtWriter.ThreadTaskCreate (OTF2_EvtWriter * writer, OTF2_AttributeList * attributeList, OTF2_TimeStamp time, OTF2_CommRef threadTeam, uint32_t creatingThread, uint32_t generationNumber)`

Records an ThreadTaskCreate event.

An ThreadTaskCreate record marks that an task in was/will be created and will be processed by the specified thread team.

Parameters

| | |
|-------------------------|---|
| <i>writer</i> | Writer object. |
| <i>attributeList</i> | Generic attributes for the event. |
| <i>time</i> | The time for this event. |
| <i>threadTeam</i> | Thread team References a Comm definition and will be mapped to the global definition if a mapping table of type OTF2_MAPPING_COMM is available. |
| <i>creatingThread</i> | Creating thread of this task. (This is redundant, remove?) |
| <i>generationNumber</i> | Thread-private generation number of task's creating thread. |

Since

Version 1.2

Returns

OTF2_SUCCESS if successful, an error code if an error occurs.

J.13.2.58 **OTF2_ErrorCode** **OTF2_EvtWriter.ThreadTaskSwitch** (**OTF2_EvtWriter** * *writer*, **OTF2_AttributeList** * *attributeList*, **OTF2_TimeStamp** *time*, **OTF2_CommRef** *threadTeam*, **uint32_t** *creatingThread*, **uint32_t** *generationNumber*)

Records an ThreadTaskSwitch event.

An ThreadTaskSwitch record indicates that the execution of the current task will be suspended and another task starts/restarts its execution. Please note that this may change the current call stack of the executing location.

Parameters

| | |
|-------------------------|---|
| <i>writer</i> | Writer object. |
| <i>attributeList</i> | Generic attributes for the event. |
| <i>time</i> | The time for this event. |
| <i>threadTeam</i> | Thread team References a Comm definition and will be mapped to the global definition if a mapping table of type OTF2_MAPPING_COMM is available. |
| <i>creatingThread</i> | Creating thread of this task. |
| <i>generationNumber</i> | Thread-private generation number of task's creating thread. |

Since

Version 1.2

Returns

OTF2_SUCCESS if successful, an error code if an error occurs.

J.13.2.59 **OTF2_ErrorCode** **OTF2_EvtWriter.ThreadTeamBegin** (**OTF2_EvtWriter** * *writer*, **OTF2_AttributeList** * *attributeList*, **OTF2_TimeStamp** *time*, **OTF2_CommRef** *threadTeam*)

Records an ThreadTeamBegin event.

J.14 OTF2_GeneralDefinitions.h File Reference

Parameters

| | |
|----------------------|---|
| <i>writer</i> | Writer object. |
| <i>attributeList</i> | Generic attributes for the event. |
| <i>time</i> | The time for this event. |
| <i>threadTeam</i> | Thread team References a Comm definition and will be mapped to the global definition if a mapping table of type OTF2_MAPPING_COMM is available. |

Since

Version 1.2

Returns

[OTF2_SUCCESS](#) if successful, an error code if an error occurs.

J.13.2.60 `OTF2_StatusCode OTF2_EvtWriter_ThreadTeamEnd (OTF2_EvtWriter *
writer, OTF2_AttributeList * attributeList, OTF2_TimeStamp time,
OTF2_CommRef threadTeam)`

Records an ThreadTeamEnd event.

Parameters

| | |
|----------------------|---|
| <i>writer</i> | Writer object. |
| <i>attributeList</i> | Generic attributes for the event. |
| <i>time</i> | The time for this event. |
| <i>threadTeam</i> | Thread team References a Comm definition and will be mapped to the global definition if a mapping table of type OTF2_MAPPING_COMM is available. |

Since

Version 1.2

Returns

[OTF2_SUCCESS](#) if successful, an error code if an error occurs.

J.14 OTF2_GeneralDefinitions.h File Reference

This header file provides general definitions which should be accessible in all internal and external modules.

APPENDIX J. FILE DOCUMENTATION

```
#include <stdint.h>
#include <otf2/OTF2_ErrorCodes.h>
```

Defines

- #define [OTF2_CHUNK_SIZE_MAX](#) (uint64_t)(1024 * 1024 * 16)
Defines the maximum size of a chunk.
- #define [OTF2_CHUNK_SIZE_MIN](#) (uint64_t)(256 * 1024)
Defines the minimum size of a chunk.
- #define [OTF2_UNDEFINED_ATTRIBUTE](#) (([OTF2_AttributeRef](#))OTF2_UNDEFINED_UINT32)
The invalid value for a reference to a [Attribute](#) definition.
- #define [OTF2_UNDEFINED_CALLPATH](#) (([OTF2_CallpathRef](#))OTF2_UNDEFINED_UINT32)
The invalid value for a reference to a [Callpath](#) definition.
- #define [OTF2_UNDEFINED_CALLSITE](#) (([OTF2_CallsiteRef](#))OTF2_UNDEFINED_UINT32)
The invalid value for a reference to a [Callsite](#) definition.
- #define [OTF2_UNDEFINED_COMM](#) (([OTF2_CommRef](#))OTF2_UNDEFINED_UINT32)
The invalid value for a reference to a [Comm](#) definition.
- #define [OTF2_UNDEFINED_GROUP](#) (([OTF2_GroupRef](#))OTF2_UNDEFINED_UINT32)
The invalid value for a reference to a [Group](#) definition.
- #define [OTF2_UNDEFINED_LOCATION](#) (([OTF2_LocationRef](#))OTF2_UNDEFINED_UINT64)
The invalid value for a reference to a [Location](#) definition.
- #define [OTF2_UNDEFINED_LOCATION_GROUP](#) (([OTF2_LocationGroupRef](#))OTF2_UNDEFINED_UINT32)
The invalid value for a reference to a [LocationGroup](#) definition.
- #define [OTF2_UNDEFINED_METRIC](#) (([OTF2_MetricRef](#))OTF2_UNDEFINED_UINT32)

J.14 OTF2_GeneralDefinitions.h File Reference

The invalid value for a reference to a [MetricClass](#), or a [MetricInstance](#) definition.

- #define [OTF2_UNDEFINED_METRIC_MEMBER](#) (([OTF2_MetricMemberRef](#))OTF2_UNDEFINED_UINT32)

The invalid value for a reference to a [MetricMember](#) definition.

- #define [OTF2_UNDEFINED_PARAMETER](#) (([OTF2_ParameterRef](#))OTF2_UNDEFINED_UINT32)

The invalid value for a reference to a [Parameter](#) definition.

- #define [OTF2_UNDEFINED_REGION](#) (([OTF2_RegionRef](#))OTF2_UNDEFINED_UINT32)

The invalid value for a reference to a [Region](#) definition.

- #define [OTF2_UNDEFINED_RMA_WIN](#) (([OTF2_RmaWinRef](#))OTF2_UNDEFINED_UINT32)

The invalid value for a reference to a [RmaWin](#) definition.

- #define [OTF2_UNDEFINED_STRING](#) (([OTF2_StringRef](#))OTF2_UNDEFINED_UINT32)

The invalid value for a reference to a [String](#) definition.

- #define [OTF2_UNDEFINED_SYSTEM_TREE_NODE](#) (([OTF2_SystemTreeNodeRef](#))OTF2_UNDEFINED_UINT32)

The invalid value for a reference to a [SystemTreeNode](#) definition.

- #define [OTF2_UNDEFINED_TYPE](#) OTF2_UNDEFINED_UINT8

OTF2 library version.

- #define [OTF2_VERSION_MAJOR](#) 1
- #define [OTF2_VERSION_MINOR](#) 2
- #define [OTF2_VERSION_BUGFIX](#) 0
- #define [OTF2_VERSION_SUFFIX](#) ""
- #define [OTF2_VERSION](#) "1.2"

Standard undefined values for basic data types.

- #define [OTF2_UNDEFINED_UINT8](#) ((uint8_t)(~((uint8_t)0u)))
- #define [OTF2_UNDEFINED_UINT16](#) ((uint16_t)(~((uint16_t)0u)))

- `#define OTF2_UNDEFINED_UINT32 ((uint32_t)(~((uint32_t)0u)))`
- `#define OTF2_UNDEFINED_UINT64 ((uint64_t)(~((uint64_t)0u)))`

Typedefs

- typedef uint32_t [OTF2_AttributeRef](#)
Type used to indicate a reference to a [Attribute](#) definition.
- typedef uint32_t [OTF2_CallpathRef](#)
Type used to indicate a reference to a [Callpath](#) definition.
- typedef uint32_t [OTF2_CallsiteRef](#)
Type used to indicate a reference to a [Callsite](#) definition.
- typedef uint32_t [OTF2_CommRef](#)
Type used to indicate a reference to a [Comm](#) definition.
- typedef uint8_t [OTF2_Compression](#)
Defines which compression is used. Please see [OTF2_Compression_enum](#) for a detailed description.
- typedef struct OTF2_DefReader_struct [OTF2_DefReader](#)
OTF2 local definition reader handle.
- typedef struct OTF2_EvtReader_struct [OTF2_EvtReader](#)
OTF2 local event reader handle.
- typedef uint8_t [OTF2_FileMode](#)
Defines how to interact with files. Please see [OTF2_FileMode_enum](#) for a detailed description.
- typedef uint8_t [OTF2_FileSubstrate](#)
Defines which file substrate is used. Please see [OTF2_FileSubstrate_enum](#) for a detailed description.
- typedef uint8_t [OTF2_FileType](#)
Defines which file type is used. Please see [OTF2_FileType_enum](#) for a detailed description.
- typedef uint8_t [OTF2_FlushType](#)

J.14 OTF2_GeneralDefinitions.h File Reference

Defines whether the recorded data is flushed to a file or not. Please see [OTF2_FlushType_enum](#) for a detailed description.

- typedef struct OTF2_GlobalDefReader_struct [OTF2_GlobalDefReader](#)
OTF2 global definition reader handle.
- typedef struct OTF2_GlobalEvtReader_struct [OTF2_GlobalEvtReader](#)
OTF2 global event reader handle.
- typedef struct OTF2_GlobalSnapReader_struct [OTF2_GlobalSnapReader](#)
OTF2 global snap reader handle.
- typedef uint32_t [OTF2_GroupRef](#)
Type used to indicate a reference to a [Group](#) definition.
- typedef uint32_t [OTF2_LocationGroupRef](#)
Type used to indicate a reference to a [LocationGroup](#) definition.
- typedef uint64_t [OTF2_LocationRef](#)
Type used to indicate a reference to a [Location](#) definition.
- typedef uint8_t [OTF2_MappingType](#)
Wrapper for enum [OTF2_MappingType_enum](#).
- typedef struct OTF2_MarkerReader_struct [OTF2_MarkerReader](#)
OTF2 marker reader handle.
- typedef uint32_t [OTF2_MetricMemberRef](#)
Type used to indicate a reference to a [MetricMember](#) definition.
- typedef uint32_t [OTF2_MetricRef](#)
Type used to indicate a reference to a [MetricClass](#), or a [MetricInstance](#) definition.
- typedef uint8_t [OTF2_Paradigm](#)
Wrapper for enum [OTF2_Paradigm_enum](#).
- typedef uint32_t [OTF2_ParameterRef](#)
Type used to indicate a reference to a [Parameter](#) definition.
- typedef uint32_t [OTF2_RegionRef](#)
Type used to indicate a reference to a [Region](#) definition.

- typedef uint32_t [OTF2_RmaWinRef](#)
Type used to indicate a reference to a [RmaWin](#) definition.
- typedef struct OTF2_SnapReader_struct [OTF2_SnapReader](#)
OTF2 local snap reader handle.
- typedef uint32_t [OTF2_StringRef](#)
Type used to indicate a reference to a [String](#) definition.
- typedef uint32_t [OTF2_SystemTreeNodeRef](#)
Type used to indicate a reference to a [SystemTreeNode](#) definition.
- typedef uint8_t [OTF2_ThumbnailType](#)
Wrapper for enum [OTF2_ThumbnailType_enum](#).
- typedef uint64_t [OTF2_TimeStamp](#)
OTF2 time stamp.
- typedef uint8_t [OTF2_Type](#)
Wrapper for enum [OTF2_Type_enum](#).

Enumerations

- enum [OTF2_CallbackCode](#) {
 [OTF2_CALLBACK_SUCCESS](#) = 0,
 [OTF2_CALLBACK_INTERRUPT](#) = ![OTF2_CALLBACK_SUCCESS](#) }
Return value to indicate that the record reading should be interrupted.
- enum [OTF2_Compression_enum](#) {
 [OTF2_COMPRESSION_UNDEFINED](#) = 0,
 [OTF2_COMPRESSION_NONE](#) = 1,
 [OTF2_COMPRESSION_ZLIB](#) = 2 }
Defines which compression is used.
- enum [OTF2_FileMode_enum](#) {
 [OTF2_FILEMODE_WRITE](#) = 0,
 [OTF2_FILEMODE_READ](#) = 1,
 [OTF2_FILEMODE_MODIFY](#) = 2 }
Defines which file mode is used.

J.14 OTF2_GeneralDefinitions.h File Reference

Defines how to interact with files.

- enum `OTF2_FileSubstrate_enum` {
 `OTF2_SUBSTRATE_UNDEFINED` = 0,
 `OTF2_SUBSTRATE_POSIX` = 1,
 `OTF2_SUBSTRATE_SION` = 2,
 `OTF2_SUBSTRATE_NONE` = 3 }

Defines which file substrate is used. Please note: At the moment only the posix and none interfaces are implemented.

- enum `OTF2_FileType_enum` {
 `OTF2_FILETYPE_ANCHOR` = 0,
 `OTF2_FILETYPE_GLOBAL_DEFS` = 1,
 `OTF2_FILETYPE_LOCAL_DEFS` = 2,
 `OTF2_FILETYPE_EVENTS` = 3,
 `OTF2_FILETYPE_SNAPSHOTS` = 4,
 `OTF2_FILETYPE_THUMBNAIL` = 5,
 `OTF2_FILETYPE_MARKER` = 6 }

Defines which file type is used.

- enum `OTF2_FlushType_enum` {
 `OTF2_NO_FLUSH` = 0,
 `OTF2_FLUSH` = 1 }

Defines whether the recorded data is flushed to a file or not.

- enum `OTF2_MappingType_enum` {
 `OTF2_MAPPING_STRING` = 0,
 `OTF2_MAPPING_ATTRIBUTE` = 1,
 `OTF2_MAPPING_LOCATION` = 2,
 `OTF2_MAPPING_REGION` = 3,
 `OTF2_MAPPING_GROUP` = 4,
 `OTF2_MAPPING_METRIC` = 5,
 `OTF2_MAPPING_COMM` = 6,
 `OTF2_MAPPING_PARAMETER` = 7,
 `OTF2_MAPPING_RMA_WIN` = 8,
 `OTF2_MAPPING_MAX` = 9 }

APPENDIX J. FILE DOCUMENTATION

Possible mappings from local to global identifiers.

- enum `OTF2_Paradigm_enum` {
 `OTF2_PARADIGM_UNKNOWN` = 0,
 `OTF2_PARADIGM_USER` = 1,
 `OTF2_PARADIGM_COMPILER` = 2,
 `OTF2_PARADIGM_OPENMP` = 3,
 `OTF2_PARADIGM_MPI` = 4,
 `OTF2_PARADIGM_CUDA` = 5,
 `OTF2_PARADIGM_MEASUREMENT_SYSTEM` = 6 }

List of known paradigms.

- enum `OTF2_ThumbnailType_enum` {
 `OTF2_THUMBNAIL_TYPE_REGION` = 0,
 `OTF2_THUMBNAIL_TYPE_METRIC` = 1,
 `OTF2_THUMBNAIL_TYPE_ATTRIBUTES` = 2 }

Type of definitions used as metric in an thumbnail.

- enum `OTF2_Type_enum` {
 `OTF2_TYPE_NONE` = 0,
 `OTF2_TYPE_UINT8` = 1,
 `OTF2_TYPE_UINT16` = 2,
 `OTF2_TYPE_UINT32` = 3,
 `OTF2_TYPE_UINT64` = 4,
 `OTF2_TYPE_INT8` = 5,
 `OTF2_TYPE_INT16` = 6,
 `OTF2_TYPE_INT32` = 7,
 `OTF2_TYPE_INT64` = 8,
 `OTF2_TYPE_FLOAT` = 9,
 `OTF2_TYPE_DOUBLE` = 10 }

OTF2 basic data types.

J.14 OTF2_GeneralDefinitions.h File Reference

J.14.1 Detailed Description

This header file provides general definitions which should be accessible in all internal and external modules.

Source Template:

templates/OTF2_GeneralDefinitions.templ.h

Maintainer:

Michael Wagner <michael.wagner@zih.tu-dresden.de>

Authors

Dominic Eschweiler <d.eschweiler@fz-juelich.de>, Michael Wagner <michael.wagner@zih.tu-dresden.de>

J.14.2 Define Documentation

J.14.2.1 `#define OTF2_UNDEFINED_TYPE OTF2_UNDEFINED_UINT8`

Undefined value for enums

J.14.3 Enumeration Type Documentation

J.14.3.1 `enum OTF2_CallbackCode`

Return value to indicate that the record reading should be interrupted.

Returning *OTF2_CALLBACK_INTERRUPT* will stop reading more events, if functions like:

- [OTF2_Reader_ReadLocalEvents](#)
- [OTF2_Reader_ReadAllLocalEvents](#)
- [OTF2_Reader_ReadLocalEventsBackward](#)
- [OTF2_Reader_ReadGlobalEvents](#)
- [OTF2_Reader_ReadAllGlobalEvents](#)
- [OTF2_Reader_ReadLocalDefinitions](#)
- [OTF2_Reader_ReadAllLocalDefinitions](#)

- [OTF2_Reader_ReadGlobalDefinitions](#)
- [OTF2_Reader_ReadAllGlobalDefinitions](#) where called. The return value for these functions is [OTF2_ERROR_INTERRUPTED_BY_CALLBACK](#) in this case. It is valid to call any reader functions in such a condition again.

Enumerator:

OTF2_CALLBACK_SUCCESS Record reading can continue.

OTF2_CALLBACK_INTERRUPT Interrupt record reading. Control returns to the caller of the read function with error *OTF2_ERROR_INTERRUPTED_BY_CALLBACK* to signal this. The actual value can be any except *OTF2_CALLBACK_SUCCESS*.

J.14.3.2 enum OTF2_Compression_enum

Defines which compression is used.

Enumerator:

OTF2_COMPRESSION_UNDEFINED Undefined.

OTF2_COMPRESSION_NONE No compression is used.

OTF2_COMPRESSION_ZLIB Use zlib compression.

J.14.3.3 enum OTF2_FileMode_enum

Defines how to interact with files.

Enumerator:

OTF2_FILEMODE_WRITE Open a file in write-only mode.

OTF2_FILEMODE_READ Open a file in read-only mode.

OTF2_FILEMODE_MODIFY Open a file in write-read mode.

J.14.3.4 enum OTF2_FileSubstrate_enum

Defines which file substrate is used. Please note: At the moment only the posix and none interfaces are implemented.

Enumerator:

OTF2_SUBSTRATE_UNDEFINED Undefined.

J.14 OTF2_GeneralDefinitions.h File Reference

OTF2_SUBSTRATE_POSIX Use standard posix file interface.

OTF2_SUBSTRATE_SION Use the interface of the sionlib to write many logical files into few physical files.

OTF2_SUBSTRATE_NONE Do not use any file interface. No data is written to a file.

J.14.3.5 enum OTF2_FileType_enum

Defines which file type is used.

Enumerator:

OTF2_FILETYPE_ANCHOR Represents the type for the anchor file (.otf2). Does has a undefined location ID.

OTF2_FILETYPE_GLOBAL_DEFS Represents the type for the global definition file (.def). Does has a undefined location ID.

OTF2_FILETYPE_LOCAL_DEFS Represents the type for a local definition file (.def).

OTF2_FILETYPE_EVENTS Represents the type for a event file (.evt).

OTF2_FILETYPE_SNAPSHOTS Represents the type for a snapshot file (.snap).

OTF2_FILETYPE_THUMBNAIL Represents the type for a thumb file (.thumb).

OTF2_FILETYPE_MARKER Represents the type for a marker file (.marker).

J.14.3.6 enum OTF2_FlushType_enum

Defines whether the recorded data is flushed to a file or not.

Enumerator:

OTF2_NO_FLUSH Flushing will be suppressed when running out of memory.

OTF2_FLUSH Recorded data is flushed when running out of memory.

J.14.3.7 enum *OTF2_MappingType_enum*

Possible mappings from local to global identifiers.

Since

Version 1.0

Enumerator:

- OTF2_MAPPING_STRING* Mapping of string identifiers.
- OTF2_MAPPING_ATTRIBUTE* Mapping of attribute identifiers.
- OTF2_MAPPING_LOCATION* Mapping of location identifiers.
- OTF2_MAPPING_REGION* Mapping of region identifiers.
- OTF2_MAPPING_GROUP* Mapping of group identifiers.
- OTF2_MAPPING_METRIC* Mapping of metric identifiers.
- OTF2_MAPPING_COMM* Mapping of MPI communicator identifiers.
- OTF2_MAPPING_PARAMETER* Mapping of parameter identifiers.
- OTF2_MAPPING_RMA_WIN* Mapping of RMA window identifiers.
- OTF2_MAPPING_MAX* Max entry.

J.14.3.8 enum *OTF2_Paradigm_enum*

List of known paradigms.

Since

Version 1.1

Enumerator:

- OTF2_PARADIGM_UNKNOWN* An unknown paradigm.
- OTF2_PARADIGM_USER* Regions generated through user instrumentation.

- OTF2_PARADIGM_COMPILER* Regions generated through compiler instrumentation.
- OTF2_PARADIGM_OPENMP* Regions referring to OpenMP directives and API functions.
- OTF2_PARADIGM_MPI* Regions referring to MPI functions.
- OTF2_PARADIGM_CUDA* Regions referring to CUDA API functions.

J.14 OTF2_GeneralDefinitions.h File Reference

OTF2_PARADIGM_MEASUREMENT_SYSTEM Regions used by the measurement software.

Since

Version 1.2.

J.14.3.9 enum OTF2_ThumbnailType_enum

Type of definitions used as metric in an thumbnail.

Since

Version 1.2

Enumerator:

OTF2_THUMBNAIL_TYPE_REGION The referenced definitions are of type *Region*.

OTF2_THUMBNAIL_TYPE_METRIC The referenced definitions are of type *MetricMember*.

OTF2_THUMBNAIL_TYPE_ATTRIBUTES The referenced definitions are of type *Attribute*.

J.14.3.10 enum OTF2_Type_enum

OTF2 basic data types.

Since

Version 1.0

Enumerator:

OTF2_TYPE_NONE Undefined type.

OTF2_TYPE_UINT8 Unsigned 8-bit integer.

OTF2_TYPE_UINT16 Unsigned 16-bit integer.

OTF2_TYPE_UINT32 Unsigned 32-bit integer.

OTF2_TYPE_UINT64 Unsigned 64-bit integer.

OTF2_TYPE_INT8 Signed 8-bit integer.

OTF2_TYPE_INT16 Signed 16-bit integer.

OTF2_TYPE_INT32 Signed 32-bit integer.

OTF2_TYPE_INT64 Signed 64-bit integer.

OTF2_TYPE_FLOAT 32-bit floating point value.

OTF2_TYPE_DOUBLE 64-bit floating point value.

J.15 OTF2_GlobalDefReader.h File Reference

This is the definition reader.

```
#include <stddef.h>
#include <stdint.h>
#include <otf2/OTF2_ErrorCodes.h>
#include <otf2/OTF2_Definitions.h>
#include <otf2/OTF2_GlobalDefReaderCallbacks.h>
```

Functions

- [OTF2_ErrorCode OTF2_GlobalDefReader_ReadDefinitions](#) ([OTF2_GlobalDefReader](#) *reader, uint64_t recordsToRead, uint64_t *recordsRead)

Reads the given number of records from the global definition reader.

- [OTF2_ErrorCode OTF2_GlobalDefReader_SetCallbacks](#) ([OTF2_GlobalDefReader](#) *reader, const [OTF2_GlobalDefReaderCallbacks](#) *callbacks, void *userData)

Sets the callback functions for the given reader object. Everytime when OTF2 reads a record, a callback function is called and the records data is passed to this function. Therefore the programmer needs to set function pointers at the "callbacks" struct for the record type he wants to read.

J.15.1 Detailed Description

This is the definition reader.

Maintainer:

Dominic Eschweiler <d.eschweiler@fz-juelich.de>

Authors

Dominic Eschweiler <d.eschweiler@fz-juelich.de>, Michael Wagner <michael.wagner@zih.tu-dresden.de>

J.15 OTF2_GlobalDefReader.h File Reference

J.15.2 Function Documentation

J.15.2.1 `OTF2_ErrorCode OTF2_GlobalDefReader_ReadDefinitions (OTF2_GlobalDefReader * reader, uint64_t recordsToRead, uint64_t * recordsRead)`

Reads the given number of records from the global definition reader.

Parameters

| | | |
|-----|----------------------|--|
| | <i>reader</i> | The records of this reader will be read when the function is issued. |
| | <i>recordsToRead</i> | This variable tells the reader how much records it has to read. |
| out | <i>recordsRead</i> | This is a pointer to variable where the amount of actually read records is returned. This may differ to the given recordsToRead if there are no more records left in the trace. In this case the programmer can easily check that the reader has finished his job by checking recordsRead < recordsToRead. |

Returns

[*OTF2_SUCCESS*](#) if successful, an error code if an error occurs.

J.15.2.2 `OTF2_ErrorCode OTF2_GlobalDefReader_SetCallbacks (OTF2_GlobalDefReader * reader, const OTF2_GlobalDefReaderCallbacks * callbacks, void * userData)`

Sets the callback functions for the given reader object. Everytime when OTF2 reads a record, a callback function is called and the records data is passed to this function. Therefore the programmer needs to set function pointers at the "callbacks" struct for the record type he wants to read.

Parameters

| | |
|------------------|--|
| <i>reader</i> | This given reader object will be setted up with new callback functions. |
| <i>callbacks</i> | Struct which holds a function pointer for each record type. <i>OTF2_GlobalDefReaderCallbacks_New</i> . |
| <i>userData</i> | Data passed as argument <i>userData</i> to the record callbacks. |

Returns

[*OTF2_SUCCESS*](#) if successful, an error code if an error occurs.

J.16 OTF2_GlobalDefReaderCallbacks.h File Reference

This defines the callbacks for the global definition reader.

```
#include <stdint.h>
#include <otf2/OTF2_ErrorCodes.h>
#include <otf2/OTF2_GeneralDefinitions.h>
#include <otf2/OTF2_Definitions.h>
```

Typedefs

- typedef [OTF2_CallbackCode](#)(* [OTF2_GlobalDefReaderCallback_Attribute](#))(void *userData, [OTF2_AttributeRef](#) self, [OTF2_StringRef](#) name, [OTF2_Type](#) type)

Function pointer definition for the callback which is triggered by a [Attribute](#) definition record.
- typedef [OTF2_CallbackCode](#)(* [OTF2_GlobalDefReaderCallback_Callpath](#))(void *userData, [OTF2_CallpathRef](#) self, [OTF2_CallpathRef](#) parent, [OTF2_RegionRef](#) region)

Function pointer definition for the callback which is triggered by a [Callpath](#) definition record.
- typedef [OTF2_CallbackCode](#)(* [OTF2_GlobalDefReaderCallback_Callsite](#))(void *userData, [OTF2_CallsiteRef](#) self, [OTF2_StringRef](#) sourceFile, [uint32_t](#) lineNumber, [OTF2_RegionRef](#) enteredRegion, [OTF2_RegionRef](#) leftRegion)

Function pointer definition for the callback which is triggered by a [Callsite](#) definition record.
- typedef [OTF2_CallbackCode](#)(* [OTF2_GlobalDefReaderCallback_ClockProperties](#))(void *userData, [uint64_t](#) timerResolution, [uint64_t](#) globalOffset, [uint64_t](#) traceLength)

Function pointer definition for the callback which is triggered by a [ClockProperties](#) definition record.
- typedef [OTF2_CallbackCode](#)(* [OTF2_GlobalDefReaderCallback_Comm](#))(void *userData, [OTF2_CommRef](#) self, [OTF2_StringRef](#) name, [OTF2_GroupRef](#) group, [OTF2_CommRef](#) parent)

Function pointer definition for the callback which is triggered by a [Comm](#) definition record.

J.16 OTF2_GlobalDefReaderCallbacks.h File Reference

- typedef OTF2_CallbackCode(* OTF2_GlobalDefReaderCallback_Group)(void *userData, OTF2_GroupRef self, OTF2_StringRef name, OTF2_GroupType groupType, OTF2_Paradigm paradigm, OTF2_GroupFlag groupFlags, uint32_t numberOfMembers, const uint64_t *members)
Function pointer definition for the callback which is triggered by a [Group](#) definition record.
- typedef OTF2_CallbackCode(* OTF2_GlobalDefReaderCallback_Location)(void *userData, OTF2_LocationRef self, OTF2_StringRef name, OTF2_LocationType locationType, uint64_t numberOfEvents, OTF2_LocationGroupRef locationGroup)
Function pointer definition for the callback which is triggered by a [Location](#) definition record.
- typedef OTF2_CallbackCode(* OTF2_GlobalDefReaderCallback_LocationGroup)(void *userData, OTF2_LocationGroupRef self, OTF2_StringRef name, OTF2_LocationGroupType locationGroupType, OTF2_SystemTreeNodeRef systemTreeParent)
Function pointer definition for the callback which is triggered by a [Location-Group](#) definition record.
- typedef OTF2_CallbackCode(* OTF2_GlobalDefReaderCallback_MetricClass)(void *userData, OTF2_MetricRef self, uint8_t numberOfMetrics, const OTF2_MetricMemberRef *metricMembers, OTF2_MetricOccurrence metricOccurrence, OTF2_RecorderKind recorderKind)
Function pointer definition for the callback which is triggered by a [MetricClass](#) definition record.
- typedef OTF2_CallbackCode(* OTF2_GlobalDefReaderCallback_MetricClassRecorder)(void *userData, OTF2_MetricRef metricClass, OTF2_LocationRef recorder)
Function pointer definition for the callback which is triggered by a [MetricClass-Recorder](#) definition record.
- typedef OTF2_CallbackCode(* OTF2_GlobalDefReaderCallback_MetricInstance)(void *userData, OTF2_MetricRef self, OTF2_MetricRef metricClass, OTF2_LocationRef recorder, OTF2_MetricScope metricScope, uint64_t scope)
Function pointer definition for the callback which is triggered by a [MetricInstance](#) definition record.
- typedef OTF2_CallbackCode(* OTF2_GlobalDefReaderCallback_MetricMember)(void *userData, OTF2_MetricMemberRef self, OTF2_StringRef name, OTF2_StringRef description, OTF2_MetricType metricType, OTF2_MetricMode

APPENDIX J. FILE DOCUMENTATION

metricMode, [OTF2_Type](#) valueType, [OTF2_MetricBase](#) metricBase, int64_t exponent, [OTF2_StringRef](#) unit)

Function pointer definition for the callback which is triggered by a [MetricMember](#) definition record.

- typedef [OTF2_CallbackCode](#)(* [OTF2_GlobalDefReaderCallback_Parameter](#))(void *userData, [OTF2_ParameterRef](#) self, [OTF2_StringRef](#) name, [OTF2_ParameterType](#) parameterType)

Function pointer definition for the callback which is triggered by a [Parameter](#) definition record.

- typedef [OTF2_CallbackCode](#)(* [OTF2_GlobalDefReaderCallback_Region](#))(void *userData, [OTF2_RegionRef](#) self, [OTF2_StringRef](#) name, [OTF2_StringRef](#) canonicalName, [OTF2_StringRef](#) description, [OTF2_RegionRole](#) regionRole, [OTF2_Paradigm](#) paradigm, [OTF2_RegionFlag](#) regionFlags, [OTF2_StringRef](#) sourceFile, uint32_t beginLineNumber, uint32_t endLineNumber)

Function pointer definition for the callback which is triggered by a [Region](#) definition record.

- typedef [OTF2_CallbackCode](#)(* [OTF2_GlobalDefReaderCallback_RmaWin](#))(void *userData, [OTF2_RmaWinRef](#) self, [OTF2_StringRef](#) name, [OTF2_CommRef](#) comm)

Function pointer definition for the callback which is triggered by a [RmaWin](#) definition record.

- typedef [OTF2_CallbackCode](#)(* [OTF2_GlobalDefReaderCallback_String](#))(void *userData, [OTF2_StringRef](#) self, const char *string)

Function pointer definition for the callback which is triggered by a [String](#) definition record.

- typedef [OTF2_CallbackCode](#)(* [OTF2_GlobalDefReaderCallback_SystemTreeNode](#))(void *userData, [OTF2_SystemTreeNodeRef](#) self, [OTF2_StringRef](#) name, [OTF2_StringRef](#) className, [OTF2_SystemTreeNodeRef](#) parent)

Function pointer definition for the callback which is triggered by a [SystemTreeNode](#) definition record.

- typedef [OTF2_CallbackCode](#)(* [OTF2_GlobalDefReaderCallback_SystemTreeNodeDomain](#))(void *userData, [OTF2_SystemTreeNodeRef](#) systemTreeNode, [OTF2_SystemTreeDomain](#) systemTreeDomain)

Function pointer definition for the callback which is triggered by a [SystemTreeNodeDomain](#) definition record.

J.16 OTF2_GlobalDefReaderCallbacks.h File Reference

- typedef [OTF2_CallbackCode](#)(* [OTF2_GlobalDefReaderCallback_SystemTreeNodeProperty](#))(void *userData, [OTF2_SystemTreeNodeRef](#) systemTreeNode, [OTF2_StringRef](#) name, [OTF2_StringRef](#) value)
Function pointer definition for the callback which is triggered by a [SystemTreeNodeProperty](#) definition record.
- typedef [OTF2_CallbackCode](#)(* [OTF2_GlobalDefReaderCallback_Unknown](#))(void *userData)
Function pointer definition for the callback which is triggered by an unknown definition record.
- typedef struct [OTF2_GlobalDefReaderCallbacks_struct](#) [OTF2_GlobalDefReaderCallbacks](#)
Opaque struct which holds all global definition record callbacks.

Functions

- void [OTF2_GlobalDefReaderCallbacks_Clear](#) ([OTF2_GlobalDefReaderCallbacks](#) *globalDefReaderCallbacks)
Clears a struct for the global definition callbacks.
- void [OTF2_GlobalDefReaderCallbacks_Delete](#) ([OTF2_GlobalDefReaderCallbacks](#) *globalDefReaderCallbacks)
Deallocates a struct for the global definition callbacks.
- [OTF2_GlobalDefReaderCallbacks](#) * [OTF2_GlobalDefReaderCallbacks_New](#) (void)
Allocates a new struct for the global definition callbacks.
- [OTF2_ErrorCode](#) [OTF2_GlobalDefReaderCallbacks_SetAttributeCallback](#) ([OTF2_GlobalDefReaderCallbacks](#) *globalDefReaderCallbacks, [OTF2_GlobalDefReaderCallback_Attribute](#) attributeCallback)
Registers the callback for the [Attribute](#) definition.
- [OTF2_ErrorCode](#) [OTF2_GlobalDefReaderCallbacks_SetCallpathCallback](#) ([OTF2_GlobalDefReaderCallbacks](#) *globalDefReaderCallbacks, [OTF2_GlobalDefReaderCallback_Callpath](#) callpathCallback)
Registers the callback for the [Callpath](#) definition.
- [OTF2_ErrorCode](#) [OTF2_GlobalDefReaderCallbacks_SetCallsiteCallback](#) ([OTF2_GlobalDefReaderCallbacks](#) *globalDefReaderCallbacks, [OTF2_GlobalDefReaderCallback_Callsite](#) callsiteCallback)

APPENDIX J. FILE DOCUMENTATION

Registers the callback for the [Callsite](#) definition.

- [OTF2_ErrorCode](#) [OTF2_GlobalDefReaderCallbacks_SetClockPropertiesCallback](#) ([OTF2_GlobalDefReaderCallbacks](#) *globalDefReaderCallbacks, [OTF2_GlobalDefReaderCallback_ClockProperties](#) clockPropertiesCallback)

Registers the callback for the [ClockProperties](#) definition.

- [OTF2_ErrorCode](#) [OTF2_GlobalDefReaderCallbacks_SetCommCallback](#) ([OTF2_GlobalDefReaderCallbacks](#) *globalDefReaderCallbacks, [OTF2_GlobalDefReaderCallback_Comm](#) commCallback)

Registers the callback for the [Comm](#) definition.

- [OTF2_ErrorCode](#) [OTF2_GlobalDefReaderCallbacks_SetGroupCallback](#) ([OTF2_GlobalDefReaderCallbacks](#) *globalDefReaderCallbacks, [OTF2_GlobalDefReaderCallback_Group](#) groupCallback)

Registers the callback for the [Group](#) definition.

- [OTF2_ErrorCode](#) [OTF2_GlobalDefReaderCallbacks_SetLocationCallback](#) ([OTF2_GlobalDefReaderCallbacks](#) *globalDefReaderCallbacks, [OTF2_GlobalDefReaderCallback_Location](#) locationCallback)

Registers the callback for the [Location](#) definition.

- [OTF2_ErrorCode](#) [OTF2_GlobalDefReaderCallbacks_SetLocationGroupCallback](#) ([OTF2_GlobalDefReaderCallbacks](#) *globalDefReaderCallbacks, [OTF2_GlobalDefReaderCallback_LocationGroup](#) locationGroupCallback)

Registers the callback for the [LocationGroup](#) definition.

- [OTF2_ErrorCode](#) [OTF2_GlobalDefReaderCallbacks_SetMetricClassCallback](#) ([OTF2_GlobalDefReaderCallbacks](#) *globalDefReaderCallbacks, [OTF2_GlobalDefReaderCallback_MetricClass](#) metricClassCallback)

Registers the callback for the [MetricClass](#) definition.

- [OTF2_ErrorCode](#) [OTF2_GlobalDefReaderCallbacks_SetMetricClassRecorderCallback](#) ([OTF2_GlobalDefReaderCallbacks](#) *globalDefReaderCallbacks, [OTF2_GlobalDefReaderCallback_MetricClassRecorder](#) metricClassRecorderCallback)

Registers the callback for the [MetricClassRecorder](#) definition.

- [OTF2_ErrorCode](#) [OTF2_GlobalDefReaderCallbacks_SetMetricInstanceCallback](#) ([OTF2_GlobalDefReaderCallbacks](#) *globalDefReaderCallbacks, [OTF2_GlobalDefReaderCallback_MetricInstance](#) metricInstanceCallback)

Registers the callback for the [MetricInstance](#) definition.

J.16 OTF2_GlobalDefReaderCallbacks.h File Reference

- [OTF2_ErrorCode OTF2_GlobalDefReaderCallbacks_SetMetricMemberCallback](#)
([OTF2_GlobalDefReaderCallbacks *globalDefReaderCallbacks](#), [OTF2_GlobalDefReaderCallback_MetricMember metricMemberCallback](#))
Registers the callback for the [MetricMember](#) definition.
- [OTF2_ErrorCode OTF2_GlobalDefReaderCallbacks_SetParameterCallback](#)
([OTF2_GlobalDefReaderCallbacks *globalDefReaderCallbacks](#), [OTF2_GlobalDefReaderCallback_Parameter parameterCallback](#))
Registers the callback for the [Parameter](#) definition.
- [OTF2_ErrorCode OTF2_GlobalDefReaderCallbacks_SetRegionCallback](#) ([OTF2_GlobalDefReaderCallbacks *globalDefReaderCallbacks](#), [OTF2_GlobalDefReaderCallback_Region regionCallback](#))
Registers the callback for the [Region](#) definition.
- [OTF2_ErrorCode OTF2_GlobalDefReaderCallbacks_SetRmaWinCallback](#) ([OTF2_GlobalDefReaderCallbacks *globalDefReaderCallbacks](#), [OTF2_GlobalDefReaderCallback_RmaWin rmaWinCallback](#))
Registers the callback for the [RmaWin](#) definition.
- [OTF2_ErrorCode OTF2_GlobalDefReaderCallbacks_SetStringCallback](#) ([OTF2_GlobalDefReaderCallbacks *globalDefReaderCallbacks](#), [OTF2_GlobalDefReaderCallback_String stringCallback](#))
Registers the callback for the [String](#) definition.
- [OTF2_ErrorCode OTF2_GlobalDefReaderCallbacks_SetSystemTreeNodeCallback](#)
([OTF2_GlobalDefReaderCallbacks *globalDefReaderCallbacks](#), [OTF2_GlobalDefReaderCallback_SystemTreeNode systemTreeNodeCallback](#))
Registers the callback for the [SystemTreeNode](#) definition.
- [OTF2_ErrorCode OTF2_GlobalDefReaderCallbacks_SetSystemTreeNodeDomainCallback](#)
([OTF2_GlobalDefReaderCallbacks *globalDefReaderCallbacks](#), [OTF2_GlobalDefReaderCallback_SystemTreeNodeDomain systemTreeNodeDomainCallback](#))
Registers the callback for the [SystemTreeNodeDomain](#) definition.
- [OTF2_ErrorCode OTF2_GlobalDefReaderCallbacks_SetSystemTreeNodePropertyCallback](#)
([OTF2_GlobalDefReaderCallbacks *globalDefReaderCallbacks](#), [OTF2_GlobalDefReaderCallback_SystemTreeNodeProperty systemTreeNodePropertyCallback](#))
Registers the callback for the [SystemTreeNodeProperty](#) definition.
- [OTF2_ErrorCode OTF2_GlobalDefReaderCallbacks_SetUnknownCallback](#)
([OTF2_GlobalDefReaderCallbacks *globalDefReaderCallbacks](#), [OTF2_GlobalDefReaderCallback_Unknown unknownCallback](#))

Registers the callback for an unknown definition.

J.16.1 Detailed Description

This defines the callbacks for the global definition reader.

Source Template:

templates/OTF2_GlobalDefReaderCallbacks.tmpl.h

Maintainer:

Dominic Eschweiler <d.eschweiler@fz-juelich.de>

Authors

Dominic Eschweiler <d.eschweiler@fz-juelich.de>, Michael Wagner <michael.wagner@zih.tu-dresden.de>

J.16.2 Typedef Documentation

J.16.2.1 `typedef OTF2_CallbackCode(* OTF2_GlobalDefReaderCallback_Attribute)(void *userData, OTF2_AttributeRef self, OTF2_StringRef name, OTF2_Type type)`

Function pointer definition for the callback which is triggered by a [Attribute](#) definition record.

Parameters

| | |
|-----------------|---|
| <i>userData</i> | User data as set by OTF2_Reader_RegisterGlobalDefCallbacks or OTF2_GlobalDefReader_SetCallbacks . |
| <i>self</i> | The unique identifier for this Attribute definition. |
| <i>name</i> | Name of the attribute. References a String definition. |
| <i>type</i> | Type of the attribute value. |

Since

Version 1.0

Returns

[OTF2_CALLBACK_SUCCESS](#) or [OTF2_CALLBACK_INTERRUPT](#).

J.16 OTF2_GlobalDefReaderCallbacks.h File Reference

J.16.2.2 `typedef OTF2_CallbackCode(* OTF2_GlobalDefReaderCallback - Callpath)(void *userData, OTF2_CallpathRef self, OTF2_CallpathRef parent, OTF2_RegionRef region)`

Function pointer definition for the callback which is triggered by a [Callpath](#) definition record.

Parameters

| | |
|-----------------|---|
| <i>userData</i> | User data as set by OTF2_Reader_RegisterGlobalDefCallbacks or OTF2_GlobalDefReader_SetCallbacks . |
| <i>self</i> | The unique identifier for this Callpath definition. |
| <i>parent</i> | References a Callpath definition. |
| <i>region</i> | References a Region definition. |

Since

Version 1.0

Returns

[OTF2_CALLBACK_SUCCESS](#) or [OTF2_CALLBACK_INTERRUPT](#).

J.16.2.3 `typedef OTF2_CallbackCode(* OTF2_GlobalDefReaderCallback - Callsite)(void *userData, OTF2_CallsiteRef self, OTF2_StringRef sourceFile, uint32_t lineNumber, OTF2_RegionRef enteredRegion, OTF2_RegionRef leftRegion)`

Function pointer definition for the callback which is triggered by a [Callsite](#) definition record.

Parameters

| | |
|----------------------|---|
| <i>userData</i> | User data as set by OTF2_Reader_RegisterGlobalDefCallbacks or OTF2_GlobalDefReader_SetCallbacks . |
| <i>self</i> | The unique identifier for this Callsite definition. |
| <i>sourceFile</i> | The source file where this call was made. References a String definition. |
| <i>lineNumber</i> | Line number in the source file where this call was made. |
| <i>enteredRegion</i> | The region which was called. References a Region definition. |
| <i>leftRegion</i> | The region which made the call. References a Region definition. |

Since

Version 1.0

Returns

OTF2_CALLBACK_SUCCESS or *OTF2_CALLBACK_INTERRUPT*.

J.16.2.4 `typedef OTF2_CallbackCode(* OTF2_GlobalDefReaderCallback_ -
ClockProperties)(void *userData, uint64_t timerResolution, uint64_t
globalOffset, uint64_t traceLength)`

Function pointer definition for the callback which is triggered by a [ClockProperties](#) definition record.

Defines the timer resolution and time range of this trace. There will be no event with a timestamp less than *globalOffset*, and no event with timestamp greater than (*globalOffset* + *traceLength*).

Parameters

| | |
|------------------------|---|
| <i>userData</i> | User data as set by OTF2_Reader_RegisterGlobalDefCallbacks or OTF2_GlobalDefReader_SetCallbacks . |
| <i>timerResolution</i> | Ticks per seconds. |
| <i>globalOffset</i> | A timestamp smaller than all event timestamps. |
| <i>traceLength</i> | A timespan which includes the timespan between the smallest and greatest timestamp of all event timestamps. |

Since

Version 1.0

Returns

OTF2_CALLBACK_SUCCESS or *OTF2_CALLBACK_INTERRUPT*.

J.16.2.5 `typedef OTF2_CallbackCode(* OTF2_GlobalDefReaderCallback_ -
Comm)(void *userData, OTF2_CommRef self, OTF2_StringRef name,
OTF2_GroupRef group, OTF2_CommRef parent)`

Function pointer definition for the callback which is triggered by a [Comm](#) definition record.

Parameters

| | |
|-----------------|---|
| <i>userData</i> | User data as set by OTF2_Reader_RegisterGlobalDefCallbacks or OTF2_GlobalDefReader_SetCallbacks . |
|-----------------|---|

J.16 OTF2_GlobalDefReaderCallbacks.h File Reference

| | |
|---------------|---|
| <i>self</i> | The unique identifier for this Comm definition. |
| <i>name</i> | The name given by calling <code>MPI_Comm_set_name</code> on this communicator. Or the empty name to indicate that no name was given. References a String definition. |
| <i>group</i> | The describing MPI group of this MPI communicator The group needs to be of type <code>OTF2_GROUP_TYPE_MPI_GROUP</code> or <code>OTF2_GROUP_TYPE_MPI_COMM_SELF</code> . References a Group definition. |
| <i>parent</i> | The parent MPI communicator from which this communicator was created, if any. Use <code>OTF2_UNDEFINED_COMM</code> to indicate no parent. References a Comm definition. |

Since

Version 1.0

Returns

[OTF2_CALLBACK_SUCCESS](#) or [OTF2_CALLBACK_INTERRUPT](#).

J.16.2.6 `typedef OTF2_CallbackCode(* OTF2_GlobalDefReaderCallback_ - Group)(void *userData, OTF2_GroupRef self, OTF2_StringRef name, OTF2_GroupType groupType, OTF2_Paradigm paradigm, OTF2_GroupFlag groupFlags, uint32_t numberOfMembers, const uint64_t *members)`

Function pointer definition for the callback which is triggered by a [Group](#) definition record.

Parameters

| | |
|------------------------|---|
| <i>userData</i> | User data as set by OTF2_Reader_RegisterGlobalDefCallbacks or OTF2_GlobalDefReader_SetCallbacks . |
| <i>self</i> | The unique identifier for this Group definition. |
| <i>name</i> | Name of this group References a String definition. |
| <i>groupType</i> | The type of this group. Since version 1.2. |
| <i>paradigm</i> | The paradigm of this communication group. Since version 1.2. |
| <i>groupFlags</i> | Flags for this group. Since version 1.2. |
| <i>numberOfMembers</i> | The number of members in this group. |
| <i>members</i> | The identifiers of the group members. |

Since

Version 1.0

Returns

OTF2_CALLBACK_SUCCESS or *OTF2_CALLBACK_INTERRUPT*.

J.16.2.7 `typedef OTF2_CallbackCode(* OTF2_GlobalDefReaderCallback_ - Location)(void *userData, OTF2_LocationRef self, OTF2_StringRef name, OTF2_LocationType locationType, uint64_t numberOfEvents, OTF2_LocationGroupRef locationGroup)`

Function pointer definition for the callback which is triggered by a [Location](#) definition record.

Parameters

| | |
|-----------------------|---|
| <i>userData</i> | User data as set by OTF2_Reader_RegisterGlobalDefCallbacks or OTF2_GlobalDefReader_SetCallbacks . |
| <i>self</i> | The unique identifier for this Location definition. |
| <i>name</i> | Name of the location References a String definition. |
| <i>location-Type</i> | Location type. |
| <i>numberOfEvents</i> | Number of events this location has recorded. |
| <i>location-Group</i> | Location group which includes this location. References a Location-Group definition. |

Since

Version 1.0

Returns

OTF2_CALLBACK_SUCCESS or *OTF2_CALLBACK_INTERRUPT*.

J.16.2.8 `typedef OTF2_CallbackCode(* OTF2_GlobalDefReaderCallback_ - LocationGroup)(void *userData, OTF2_LocationGroupRef self, OTF2_StringRef name, OTF2_LocationGroupType locationGroupType, OTF2_SystemTreeNodeRef systemTreeParent)`

Function pointer definition for the callback which is triggered by a [LocationGroup](#) definition record.

J.16 OTF2_GlobalDefReaderCallbacks.h File Reference

Parameters

| | |
|---------------------------|---|
| <i>userData</i> | User data as set by OTF2_Reader_RegisterGlobalDefCallbacks or OTF2_GlobalDefReader_SetCallbacks . |
| <i>self</i> | The unique identifier for this LocationGroup definition. |
| <i>name</i> | Name of the group. References a String definition. |
| <i>location-GroupType</i> | Type of this group. |
| <i>systemTreeParent</i> | Parent of this location group in the system tree. References a SystemTreeNode definition. |

Since

Version 1.0

Returns

[OTF2_CALLBACK_SUCCESS](#) or [OTF2_CALLBACK_INTERRUPT](#).

J.16.2.9 `typedef OTF2_CallbackCode(* OTF2_GlobalDefReaderCallback_ - MetricClass)(void *userData, OTF2_MetricRef self, uint8_t numberOfMetrics, const OTF2_MetricMemberRef *metricMembers, OTF2_MetricOccurrence metricOccurrence, OTF2_RecorderKind recorderKind)`

Function pointer definition for the callback which is triggered by a [MetricClass](#) definition record.

For a metric class it is implicitly given that the event stream that records the metric is also the scope. A metric class can contain multiple different metrics.

Parameters

| | |
|-------------------------|--|
| <i>userData</i> | User data as set by OTF2_Reader_RegisterGlobalDefCallbacks or OTF2_GlobalDefReader_SetCallbacks . |
| <i>self</i> | The unique identifier for this MetricClass definition. |
| <i>numberOfMetrics</i> | Number of metrics within the set. |
| <i>metricMembers</i> | List of metric members. References a MetricMember definition. |
| <i>metricOccurrence</i> | Defines occurrence of a metric set. |
| <i>recorderKind</i> | What kind of locations will record this metric class, or will this metric class only be recorded by metric instances. Since version 1.2. |

Since

Version 1.0

Returns

OTF2_CALLBACK_SUCCESS or *OTF2_CALLBACK_INTERRUPT*.

J.16.2.10 `typedef OTF2_CallbackCode(* OTF2_GlobalDefReaderCallback_ - MetricClassRecorder)(void *userData, OTF2_MetricRef metricClass, OTF2_LocationRef recorder)`

Function pointer definition for the callback which is triggered by a [MetricClassRecorder](#) definition record.

Parameters

| | |
|--------------------|---|
| <i>userData</i> | User data as set by OTF2_Reader_RegisterGlobalDefCallbacks or OTF2_GlobalDefReader_SetCallbacks . |
| <i>metricClass</i> | Parent MetricClass definition to which this one is a supplementary definition. References a MetricClass definition. |
| <i>recorder</i> | The location which recorded the referenced metric class. References a Location definition. |

Since

Version 1.2

Returns

OTF2_CALLBACK_SUCCESS or *OTF2_CALLBACK_INTERRUPT*.

J.16.2.11 `typedef OTF2_CallbackCode(* OTF2_GlobalDefReaderCallback_ - MetricInstance)(void *userData, OTF2_MetricRef self, OTF2_MetricRef metricClass, OTF2_LocationRef recorder, OTF2_MetricScope metricScope, uint64_t scope)`

Function pointer definition for the callback which is triggered by a [MetricInstance](#) definition record.

A metric instance is used to define metrics that are recorded at one location for multiple locations or for another location. The occurrence of a metric instance is implicitly of type *OTF2_METRIC_ASYNCHRONOUS*.

J.16 OTF2_GlobalDefReaderCallbacks.h File Reference

Parameters

| | |
|---------------------|--|
| <i>userData</i> | User data as set by OTF2_Reader_RegisterGlobalDefCallbacks or OTF2_GlobalDefReader_SetCallbacks . |
| <i>self</i> | The unique identifier for this MetricClass definition. |
| <i>metricClass</i> | The instanced MetricClass . This metric class must be of kind OTF2_RECORDER_KIND_ABSTRACT . References a MetricClass definition. |
| <i>recorder</i> | Recorder of the metric: location ID. References a Location definition. |
| <i>metric-Scope</i> | Defines type of scope: location, location group, system tree node, or a generic group of locations. |
| <i>scope</i> | Scope of metric: ID of a location, location group, system tree node, or a generic group of locations. |

Since

Version 1.0

Returns

[OTF2_CALLBACK_SUCCESS](#) or [OTF2_CALLBACK_INTERRUPT](#).

```
J.16.2.12 typedef OTF2_CallbackCode( * OTF2_GlobalDefReaderCallback_  
MetricMember)(void *userData, OTF2_MetricMemberRef  
self, OTF2_StringRef name, OTF2_StringRef description,  
OTF2_MetricType metricType, OTF2_MetricMode metricMode,  
OTF2_Type valueType, OTF2_MetricBase metricBase, int64_t exponent,  
OTF2_StringRef unit)
```

Function pointer definition for the callback which is triggered by a [MetricMember](#) definition record.

A metric is defined by a metric member definition. A metric member is always a member of a metric class. Therefore, a single metric is a special case of a metric class with only one member. It is not allowed to reference a metric member id in a metric event, but only metric class IDs.

Parameters

| | |
|--------------------|---|
| <i>userData</i> | User data as set by OTF2_Reader_RegisterGlobalDefCallbacks or OTF2_GlobalDefReader_SetCallbacks . |
| <i>self</i> | The unique identifier for this MetricMember definition. |
| <i>name</i> | Name of the metric. References a String definition. |
| <i>description</i> | Description of the metric. References a String definition. |
| <i>metricType</i> | Metric type: PAPI, etc. |
| <i>metricMode</i> | Metric mode: accumulative, fix, relative, etc. |

APPENDIX J. FILE DOCUMENTATION

| | |
|-------------------|---|
| <i>valueType</i> | Type of the value: int64_t, uint64_t, or double. |
| <i>metricBase</i> | The recorded values should be handled in this given base, either binary or decimal. This information can be used if the value needs to be scaled. |
| <i>exponent</i> | The values inside the Metric events should be scaled by the factor $\text{base}^{\text{exponent}}$, to get the value in its base unit. For example, if the metric values come in as KiBi, then the base should be OTF2_BASE_BINARY and the exponent 10. Then the writer does not need to scale the values up to bytes, but can directly write the KiBi values into the Metric event. At reading time, the reader can apply the scaling factor to get the value in its base unit, ie. in bytes. |
| <i>unit</i> | Unit of the metric. This needs to be the scale free base unit, ie. "bytes", "operations", or "seconds". In particular this unit should not have any scale prefix. References a String definition. |

Since

Version 1.0

Returns

[OTF2_CALLBACK_SUCCESS](#) or [OTF2_CALLBACK_INTERRUPT](#).

J.16.2.13 `typedef OTF2_CallbackCode(* OTF2_GlobalDefReaderCallback_ -
Parameter)(void *userData, OTF2_ParameterRef self, OTF2_StringRef
name, OTF2_ParameterType parameterType)`

Function pointer definition for the callback which is triggered by a [Parameter](#) definition record.

Parameters

| | |
|----------------------------|---|
| <i>userData</i> | User data as set by OTF2_Reader_RegisterGlobalDefCallbacks or OTF2_GlobalDefReader_SetCallbacks . |
| <i>self</i> | The unique identifier for this Parameter definition. |
| <i>name</i> | Name of the parameter (variable name etc.) References a String definition. |
| <i>parameter- Type</i> | Type of the parameter, OTF2_ParameterType for possible types. |

Since

Version 1.0

J.16 OTF2_GlobalDefReaderCallbacks.h File Reference

Returns

[OTF2_CALLBACK_SUCCESS](#) or [OTF2_CALLBACK_INTERRUPT](#).

J.16.2.14 `typedef OTF2_CallbackCode(* OTF2_GlobalDefReaderCallback_Region)(void *userData, OTF2_RegionRef self, OTF2_StringRef name, OTF2_StringRef canonicalName, OTF2_StringRef description, OTF2_RegionRole regionRole, OTF2_Paradigm paradigm, OTF2_RegionFlag regionFlags, OTF2_StringRef sourceFile, uint32_t beginLineNumber, uint32_t endLineNumber)`

Function pointer definition for the callback which is triggered by a [Region](#) definition record.

Parameters

| | |
|------------------------|---|
| <i>userData</i> | User data as set by OTF2_Reader_RegisterGlobalDefCallbacks or OTF2_GlobalDefReader_SetCallbacks . |
| <i>self</i> | The unique identifier for this Region definition. |
| <i>name</i> | Name of the region (demangled name if available). References a String definition. |
| <i>canonical-Name</i> | Alternative name of the region (e.g. mangled name). References a String definition. Since version 1.1. |
| <i>description</i> | A more detailed description of this region. References a String definition. |
| <i>regionRole</i> | Region role. Since version 1.1. |
| <i>paradigm</i> | Paradigm. Since version 1.1. |
| <i>regionFlags</i> | Region flags. Since version 1.1. |
| <i>sourceFile</i> | The source file where this region was declared. References a String definition. |
| <i>beginLineNumber</i> | Starting line number of this region in the source file. |
| <i>endLineNumber</i> | Ending line number of this region in the source file. |

Since

Version 1.0

Returns

[OTF2_CALLBACK_SUCCESS](#) or [OTF2_CALLBACK_INTERRUPT](#).

APPENDIX J. FILE DOCUMENTATION

J.16.2.15 `typedef OTF2_CallbackCode(* OTF2_GlobalDefReaderCallback_
RmaWin)(void *userData, OTF2_RmaWinRef self, OTF2_StringRef
name, OTF2_CommRef comm)`

Function pointer definition for the callback which is triggered by a [RmaWin](#) definition record.

A window defines the communication context for any remote-memory access operation.

Parameters

| | |
|-----------------|---|
| <i>userData</i> | User data as set by OTF2_Reader_RegisterGlobalDefCallbacks or OTF2_GlobalDefReader_SetCallbacks . |
| <i>self</i> | The unique identifier for this RmaWin definition. |
| <i>name</i> | Name, e.g. 'GASPI Queue 1', 'Nvidia Card 2', etc.. References a String definition. |
| <i>comm</i> | Communicator object used to create the window. References a Comm definition. |

Since

Version 1.2

Returns

[OTF2_CALLBACK_SUCCESS](#) or [OTF2_CALLBACK_INTERRUPT](#).

J.16.2.16 `typedef OTF2_CallbackCode(* OTF2_GlobalDefReaderCallback_
String)(void *userData, OTF2_StringRef self, const char
*string)`

Function pointer definition for the callback which is triggered by a [String](#) definition record.

Parameters

| | |
|-----------------|---|
| <i>userData</i> | User data as set by OTF2_Reader_RegisterGlobalDefCallbacks or OTF2_GlobalDefReader_SetCallbacks . |
| <i>self</i> | The unique identifier for this String definition. |
| <i>string</i> | The string, null terminated. |

Since

Version 1.0

J.16 OTF2_GlobalDefReaderCallbacks.h File Reference

Returns

[OTF2_CALLBACK_SUCCESS](#) or [OTF2_CALLBACK_INTERRUPT](#).

J.16.2.17 `typedef OTF2_CallbackCode(* OTF2_GlobalDefReaderCallback_
SystemTreeNode)(void *userData, OTF2_SystemTreeNodeRef
self, OTF2_StringRef name, OTF2_StringRef className,
OTF2_SystemTreeNodeRef parent)`

Function pointer definition for the callback which is triggered by a [SystemTreeNode](#) definition record.

Parameters

| | |
|------------------|---|
| <i>userData</i> | User data as set by OTF2_Reader_RegisterGlobalDefCallbacks or OTF2_GlobalDefReader_SetCallbacks . |
| <i>self</i> | The unique identifier for this SystemTreeNode definition. |
| <i>name</i> | Free form instance name of this node. References a String definition. |
| <i>className</i> | Free form class name of this node References a String definition. |
| <i>parent</i> | Parent id of this node. May be OTF2_UNDEFINED_SYSTEM_TREE_NODE to indicate that there is no parent. References a SystemTreeNode definition. |

Since

Version 1.0

Returns

[OTF2_CALLBACK_SUCCESS](#) or [OTF2_CALLBACK_INTERRUPT](#).

J.16.2.18 `typedef OTF2_CallbackCode(* OTF2_GlobalDefReaderCallback_
SystemTreeNodeDomain)(void *userData, OTF2_SystemTreeNodeRef
systemTreeNode, OTF2_SystemTreeNodeDomain systemTreeDomain)`

Function pointer definition for the callback which is triggered by a [SystemTreeNodeDomain](#) definition record.

Parameters

| | |
|-----------------------|---|
| <i>userData</i> | User data as set by OTF2_Reader_RegisterGlobalDefCallbacks or OTF2_GlobalDefReader_SetCallbacks . |
| <i>systemTreeNode</i> | Parent SystemTreeNode definition to which this one is a supplementary definition. References a SystemTreeNode definition. |

Since

Version 1.2

Returns

OTF2_CALLBACK_SUCCESS or *OTF2_CALLBACK_INTERRUPT*.

J.16.2.19 `typedef OTF2_CallbackCode(* OTF2_GlobalDefReaderCallback_SystemTreeNodeProperty)(void *userData, OTF2_SystemTreeNodeRef systemTreeNode, OTF2_StringRef name, OTF2_StringRef value)`

Function pointer definition for the callback which is triggered by a [SystemTreeNodeProperty](#) definition record.

Parameters

| | |
|-----------------------|---|
| <i>userData</i> | User data as set by OTF2_Reader_RegisterGlobalDefCallbacks or OTF2_GlobalDefReader_SetCallbacks . |
| <i>systemTreeNode</i> | Parent SystemTreeNode definition to which this one is a supplementary definition. References a SystemTreeNode definition. |
| <i>name</i> | Name of the property. References a String definition. |
| <i>value</i> | Property value. References a String definition. |

Since

Version 1.2

Returns

OTF2_CALLBACK_SUCCESS or *OTF2_CALLBACK_INTERRUPT*.

J.16.2.20 `typedef OTF2_CallbackCode(* OTF2_GlobalDefReaderCallback_Unknown)(void *userData)`

Function pointer definition for the callback which is triggered by an unknown definition record.

Parameters

| | |
|-----------------|---|
| <i>userData</i> | User data as set by OTF2_Reader_RegisterGlobalDefCallbacks or OTF2_GlobalDefReader_SetCallbacks . |
|-----------------|---|

J.16 OTF2_GlobalDefReaderCallbacks.h File Reference

Returns

[OTF2_CALLBACK_SUCCESS](#) or [OTF2_CALLBACK_INTERRUPT](#).

J.16.3 Function Documentation

J.16.3.1 void [OTF2_GlobalDefReaderCallbacks_Clear](#) ([OTF2_GlobalDefReaderCallbacks](#) * *globalDefReaderCallbacks*)

Clears a struct for the global definition callbacks.

Parameters

| | |
|---------------------------------|--|
| <i>globalDefReaderCallbacks</i> | Handle to a struct previously allocated with OTF2_GlobalDefReaderCallbacks_New . |
|---------------------------------|--|

J.16.3.2 void [OTF2_GlobalDefReaderCallbacks_Delete](#) ([OTF2_GlobalDefReaderCallbacks](#) * *globalDefReaderCallbacks*)

Deallocates a struct for the global definition callbacks.

Parameters

| | |
|---------------------------------|--|
| <i>globalDefReaderCallbacks</i> | Handle to a struct previously allocated with OTF2_GlobalDefReaderCallbacks_New . |
|---------------------------------|--|

J.16.3.3 [OTF2_GlobalDefReaderCallbacks*](#) [OTF2_GlobalDefReaderCallbacks_New](#) (void)

Allocates a new struct for the global definition callbacks.

Returns

A newly allocated struct of type [OTF2_GlobalDefReaderCallbacks](#).

APPENDIX J. FILE DOCUMENTATION

J.16.3.4 `OTF2_ErrorCode OTF2_GlobalDefReaderCallbacks_SetAttributeCallback (OTF2_GlobalDefReaderCallbacks * globalDefReaderCallbacks, OTF2_GlobalDefReaderCallback_Attribute attributeCallback)`

Registers the callback for the [Attribute](#) definition.

Parameters

| | |
|-----------------------------------|--|
| <i>globalDef-Reader-Callbacks</i> | Struct for all callbacks. |
| <i>attribute-Callback</i> | Function which should be called for all Attribute definitions. |

Returns

[OTF2_SUCCESS](#) if successful

[OTF2_ERROR_INVALID_ARGUMENT](#) for an invalid `defReaderCallbacks` argument

J.16.3.5 `OTF2_ErrorCode OTF2_GlobalDefReaderCallbacks_SetCallpathCallback (OTF2_GlobalDefReaderCallbacks * globalDefReaderCallbacks, OTF2_GlobalDefReaderCallback_Callpath callpathCallback)`

Registers the callback for the [Callpath](#) definition.

Parameters

| | |
|-----------------------------------|---|
| <i>globalDef-Reader-Callbacks</i> | Struct for all callbacks. |
| <i>callpath-Callback</i> | Function which should be called for all Callpath definitions. |

Returns

[OTF2_SUCCESS](#) if successful

[OTF2_ERROR_INVALID_ARGUMENT](#) for an invalid `defReaderCallbacks` argument

J.16 OTF2_GlobalDefReaderCallbacks.h File Reference

J.16.3.6 `OTF2_ErrorCode OTF2_GlobalDefReaderCallbacks_SetCallsiteCallback (OTF2_GlobalDefReaderCallbacks * globalDefReaderCallbacks, OTF2_GlobalDefReaderCallback_Callsite callsiteCallback)`

Registers the callback for the [Callsite](#) definition.

Parameters

| | |
|-----------------------------------|---|
| <i>globalDef-Reader-Callbacks</i> | Struct for all callbacks. |
| <i>callsite-Callback</i> | Function which should be called for all Callsite definitions. |

Returns

[OTF2_SUCCESS](#) if successful

[OTF2_ERROR_INVALID_ARGUMENT](#) for an invalid `defReaderCallbacks` argument

J.16.3.7 `OTF2_ErrorCode OTF2_GlobalDefReaderCallbacks_SetClockPropertiesCallback (OTF2_GlobalDefReaderCallbacks * globalDefReaderCallbacks, OTF2_GlobalDefReaderCallback_ClockProperties clockPropertiesCallback)`

Registers the callback for the [ClockProperties](#) definition.

Parameters

| | |
|-----------------------------------|--|
| <i>globalDef-Reader-Callbacks</i> | Struct for all callbacks. |
| <i>clockPropertiesCallback</i> | Function which should be called for all ClockProperties definitions. |

Returns

[OTF2_SUCCESS](#) if successful

[OTF2_ERROR_INVALID_ARGUMENT](#) for an invalid `defReaderCallbacks` argument

APPENDIX J. FILE DOCUMENTATION

J.16.3.8 `OTF2_ErrorCode OTF2_GlobalDefReaderCallbacks_SetCommCallback (OTF2_GlobalDefReaderCallbacks * globalDefReaderCallbacks, OTF2_GlobalDefReaderCallback_Comm commCallback)`

Registers the callback for the [Comm](#) definition.

Parameters

| | |
|-----------------------------------|---|
| <i>globalDef-Reader-Callbacks</i> | Struct for all callbacks. |
| <i>commCallback</i> | Function which should be called for all Comm definitions. |

Returns

[OTF2_SUCCESS](#) if successful

[OTF2_ERROR_INVALID_ARGUMENT](#) for an invalid `defReaderCallbacks` argument

J.16.3.9 `OTF2_ErrorCode OTF2_GlobalDefReaderCallbacks_SetGroupCallback (OTF2_GlobalDefReaderCallbacks * globalDefReaderCallbacks, OTF2_GlobalDefReaderCallback_Group groupCallback)`

Registers the callback for the [Group](#) definition.

Parameters

| | |
|-----------------------------------|--|
| <i>globalDef-Reader-Callbacks</i> | Struct for all callbacks. |
| <i>groupCallback</i> | Function which should be called for all Group definitions. |

Returns

[OTF2_SUCCESS](#) if successful

[OTF2_ERROR_INVALID_ARGUMENT](#) for an invalid `defReaderCallbacks` argument

J.16 OTF2_GlobalDefReaderCallbacks.h File Reference

J.16.3.10 **OTF2_ErrorCode** **OTF2_GlobalDefReaderCallbacks_SetLocationCallback**
(**OTF2_GlobalDefReaderCallbacks** * *globalDefReaderCallbacks*,
OTF2_GlobalDefReaderCallback_Location *locationCallback*)

Registers the callback for the [Location](#) definition.

Parameters

| | |
|-----------------------------------|---|
| <i>globalDef-Reader-Callbacks</i> | Struct for all callbacks. |
| <i>location-Callback</i> | Function which should be called for all Location definitions. |

Returns

[OTF2_SUCCESS](#) if successful

[OTF2_ERROR_INVALID_ARGUMENT](#) for an invalid `defReaderCallbacks` argument

J.16.3.11 **OTF2_ErrorCode** **OTF2_GlobalDefReaderCallbacks_-SetLocationGroupCallback**
(**OTF2_GlobalDefReaderCallbacks** *
globalDefReaderCallbacks, **OTF2_GlobalDefReaderCallback_-LocationGroup** *locationGroupCallback*)

Registers the callback for the [LocationGroup](#) definition.

Parameters

| | |
|-----------------------------------|--|
| <i>globalDef-Reader-Callbacks</i> | Struct for all callbacks. |
| <i>location-GroupCallback</i> | Function which should be called for all LocationGroup definitions. |

Returns

[OTF2_SUCCESS](#) if successful

[OTF2_ERROR_INVALID_ARGUMENT](#) for an invalid `defReaderCallbacks` argument

APPENDIX J. FILE DOCUMENTATION

J.16.3.12 `OTF2_StatusCode OTF2_GlobalDefReaderCallbacks_SetMetricClassCallback (OTF2_GlobalDefReaderCallbacks * globalDefReaderCallbacks, OTF2_GlobalDefReaderCallback_MetricClass metricClassCallback)`

Registers the callback for the [MetricClass](#) definition.

Parameters

| | |
|-----------------------------------|--|
| <i>globalDef-Reader-Callbacks</i> | Struct for all callbacks. |
| <i>metric-Class-Callback</i> | Function which should be called for all MetricClass definitions. |

Returns

[OTF2_SUCCESS](#) if successful

[OTF2_ERROR_INVALID_ARGUMENT](#) for an invalid `defReaderCallbacks` argument

J.16.3.13 `OTF2_StatusCode OTF2_GlobalDefReaderCallbacks_-SetMetricClassRecorderCallback (OTF2_GlobalDefReaderCallbacks * globalDefReaderCallbacks, OTF2_GlobalDefReaderCallback_-MetricClassRecorder metricClassRecorderCallback)`

Registers the callback for the [MetricClassRecorder](#) definition.

Parameters

| | |
|---------------------------------------|--|
| <i>globalDef-Reader-Callbacks</i> | Struct for all callbacks. |
| <i>metric-Class-Recorder-Callback</i> | Function which should be called for all MetricClassRecorder definitions. |

Returns

[OTF2_SUCCESS](#) if successful

[OTF2_ERROR_INVALID_ARGUMENT](#) for an invalid `defReaderCallbacks` argument

J.16 OTF2_GlobalDefReaderCallbacks.h File Reference

J.16.3.14 **OTF2_**`ErrorCode` **OTF2_GlobalDefReaderCallbacks_**
SetMetricInstanceCallback (**OTF2_GlobalDefReaderCallbacks** *
globalDefReaderCallbacks, **OTF2_GlobalDefReaderCallback_**
MetricInstance *metricInstanceCallback*)

Registers the callback for the [MetricInstance](#) definition.

Parameters

| | |
|---|---|
| <i>globalDef- Reader- Callbacks</i> | Struct for all callbacks. |
| <i>metricIn- stanceCall- back</i> | Function which should be called for all MetricInstance definitions. |

Returns

[OTF2_SUCCESS](#) if successful

[OTF2_ERROR_INVALID_ARGUMENT](#) for an invalid `defReaderCallbacks` argument

J.16.3.15 **OTF2_**`ErrorCode` **OTF2_GlobalDefReaderCallbacks_**
SetMetricMemberCallback (**OTF2_GlobalDefReaderCallbacks** *
globalDefReaderCallbacks, **OTF2_GlobalDefReaderCallback_**
MetricMember *metricMemberCallback*)

Registers the callback for the [MetricMember](#) definition.

Parameters

| | |
|---|---|
| <i>globalDef- Reader- Callbacks</i> | Struct for all callbacks. |
| <i>metricMem- berCallback</i> | Function which should be called for all MetricMember definitions. |

Returns

[OTF2_SUCCESS](#) if successful

[OTF2_ERROR_INVALID_ARGUMENT](#) for an invalid `defReaderCallbacks` argument

APPENDIX J. FILE DOCUMENTATION

J.16.3.16 `OTF2_ErrorCode` `OTF2_GlobalDefReaderCallbacks_SetParameterCallback`
(`OTF2_GlobalDefReaderCallbacks` * `globalDefReaderCallbacks`,
`OTF2_GlobalDefReaderCallback_Parameter` `parameterCallback`)

Registers the callback for the [Parameter](#) definition.

Parameters

| | |
|-----------------------------------|--|
| <i>globalDef-Reader-Callbacks</i> | Struct for all callbacks. |
| <i>parameter-Callback</i> | Function which should be called for all Parameter definitions. |

Returns

[OTF2_SUCCESS](#) if successful

[OTF2_ERROR_INVALID_ARGUMENT](#) for an invalid `defReaderCallbacks` argument

J.16.3.17 `OTF2_ErrorCode` `OTF2_GlobalDefReaderCallbacks_SetRegionCallback`
(`OTF2_GlobalDefReaderCallbacks` * `globalDefReaderCallbacks`,
`OTF2_GlobalDefReaderCallback_Region` `regionCallback`)

Registers the callback for the [Region](#) definition.

Parameters

| | |
|-----------------------------------|---|
| <i>globalDef-Reader-Callbacks</i> | Struct for all callbacks. |
| <i>regionCallback</i> | Function which should be called for all Region definitions. |

Returns

[OTF2_SUCCESS](#) if successful

[OTF2_ERROR_INVALID_ARGUMENT](#) for an invalid `defReaderCallbacks` argument

J.16 OTF2_GlobalDefReaderCallbacks.h File Reference

J.16.3.18 `OTF2_ErrorCode OTF2_GlobalDefReaderCallbacks_SetRmaWinCallback (OTF2_GlobalDefReaderCallbacks * globalDefReaderCallbacks, OTF2_GlobalDefReaderCallback_RmaWin rmaWinCallback)`

Registers the callback for the [RmaWin](#) definition.

Parameters

| | |
|-----------------------------------|---|
| <i>globalDef-Reader-Callbacks</i> | Struct for all callbacks. |
| <i>rmaWin-Callback</i> | Function which should be called for all RmaWin definitions. |

Returns

[OTF2_SUCCESS](#) if successful

[OTF2_ERROR_INVALID_ARGUMENT](#) for an invalid `defReaderCallbacks` argument

J.16.3.19 `OTF2_ErrorCode OTF2_GlobalDefReaderCallbacks_SetStringCallback (OTF2_GlobalDefReaderCallbacks * globalDefReaderCallbacks, OTF2_GlobalDefReaderCallback_String stringCallback)`

Registers the callback for the [String](#) definition.

Parameters

| | |
|-----------------------------------|---|
| <i>globalDef-Reader-Callbacks</i> | Struct for all callbacks. |
| <i>stringCallback</i> | Function which should be called for all String definitions. |

Returns

[OTF2_SUCCESS](#) if successful

[OTF2_ERROR_INVALID_ARGUMENT](#) for an invalid `defReaderCallbacks` argument

APPENDIX J. FILE DOCUMENTATION

J.16.3.20 **OTF2_ErrorCode** **OTF2_GlobalDefReaderCallbacks_-SetSystemTreeNodeCallback** (**OTF2_GlobalDefReaderCallbacks** * *globalDefReaderCallbacks*, **OTF2_GlobalDefReaderCallback_-SystemTreeNode** *systemTreeNodeCallback*)

Registers the callback for the [SystemTreeNode](#) definition.

Parameters

| | |
|-----------------------------------|---|
| <i>globalDef-Reader-Callbacks</i> | Struct for all callbacks. |
| <i>systemTreeNodeCallback</i> | Function which should be called for all SystemTreeNode definitions. |

Returns

OTF2_SUCCESS if successful

OTF2_ERROR_INVALID_ARGUMENT for an invalid `defReaderCallbacks` argument

J.16.3.21 **OTF2_ErrorCode** **OTF2_GlobalDefReaderCallbacks_-SetSystemTreeNodeDomainCallback** (**OTF2_GlobalDefReaderCallbacks** * *globalDefReaderCallbacks*, **OTF2_GlobalDefReaderCallback_-SystemTreeNodeDomain** *systemTreeNodeDomainCallback*)

Registers the callback for the [SystemTreeNodeDomain](#) definition.

Parameters

| | |
|-------------------------------------|---|
| <i>globalDef-Reader-Callbacks</i> | Struct for all callbacks. |
| <i>systemTreeNodeDomainCallback</i> | Function which should be called for all SystemTreeNodeDomain definitions. |

J.16 OTF2_GlobalDefReaderCallbacks.h File Reference

Returns

OTF2_SUCCESS if successful

OTF2_ERROR_INVALID_ARGUMENT for an invalid `defReaderCallbacks` argument

J.16.3.22 **OTF2_StatusCode** **OTF2_GlobalDefReaderCallbacks_SetSystemTreeNodePropertyCallback** (**OTF2_GlobalDefReaderCallbacks** * *globalDefReaderCallbacks*, **OTF2_GlobalDefReaderCallback_SystemTreeNodeProperty** *systemTreeNodePropertyCallback*)

Registers the callback for the `SystemTreeNodeProperty` definition.

Parameters

| | |
|---------------------------------------|--|
| <i>globalDefReaderCallbacks</i> | Struct for all callbacks. |
| <i>systemTreeNodePropertyCallback</i> | Function which should be called for all <code>SystemTreeNodeProperty</code> definitions. |

Returns

OTF2_SUCCESS if successful

OTF2_ERROR_INVALID_ARGUMENT for an invalid `defReaderCallbacks` argument

J.16.3.23 **OTF2_StatusCode** **OTF2_GlobalDefReaderCallbacks_SetUnknownCallback** (**OTF2_GlobalDefReaderCallbacks** * *globalDefReaderCallbacks*, **OTF2_GlobalDefReaderCallback_Unknown** *unknownCallback*)

Registers the callback for an unknown definition.

Parameters

| | |
|---------------------------------|--|
| <i>globalDefReaderCallbacks</i> | Struct for all callbacks. |
| <i>unknownCallback</i> | Function which should be called for all Unknown definitions. |

Returns

[OTF2_SUCCESS](#) if successful

[OTF2_ERROR_INVALID_ARGUMENT](#) for an invalid `defReaderCallbacks` argument

J.17 OTF2_GlobalDefWriter.h File Reference

This layer always writes globally defined OTF2 definition records and is used to write either the global definitions in addition to local definitions or write all definitions as globally valid in combination with `OTF2_GlobalEventWriter`. Global definitions are stored in one global definition file, which makes it nearly impossible to write them in a distributed manner. It is therefore only allowed to get such a writer from an `OTF2_ArchiveHandler` which is marked as `OTF2_MASTER`.

```
#include <stdint.h>
#include <otf2/OTF2_ErrorCodes.h>
#include <otf2/OTF2_Definitions.h>
```

Typedefs

- typedef struct `OTF2_GlobalDefWriter_struct` [OTF2_GlobalDefWriter](#)
Typedef of the struct which keeps all necessary information of a global definition writer. Can be used to reference these structs from external.

Functions

- [OTF2_ErrorCode](#) [OTF2_GlobalDefWriter_GetNumberOfDefinitions](#) ([OTF2_GlobalDefWriter](#) *writerHandle, uint64_t *numberOfDefinitions)
Returns the current number of written definitions of a global definition writer.
- [OTF2_ErrorCode](#) [OTF2_GlobalDefWriter_GetNumberOfLocations](#) ([OTF2_GlobalDefWriter](#) *writerHandle, uint64_t *numberOfLocations)
Returns the current number of written location definitions of a global definition writer.
- [OTF2_ErrorCode](#) [OTF2_GlobalDefWriter_WriteAttribute](#) ([OTF2_GlobalDefWriter](#) *writerHandle, [OTF2_AttributeRef](#) self, [OTF2_StringRef](#) name, [OTF2_Type](#) type)
Writes a [Attribute](#) definition record into the [GlobalDefWriter](#).

J.17 OTF2_GlobalDefWriter.h File Reference

- [OTF2_ErrorCode OTF2_GlobalDefWriter_WriteCallpath](#) ([OTF2_GlobalDefWriter](#) *writerHandle, [OTF2_CallpathRef](#) self, [OTF2_CallpathRef](#) parent, [OTF2_RegionRef](#) region)
Writes a [Callpath](#) definition record into the [GlobalDefWriter](#).
- [OTF2_ErrorCode OTF2_GlobalDefWriter_WriteCallsite](#) ([OTF2_GlobalDefWriter](#) *writerHandle, [OTF2_CallsiteRef](#) self, [OTF2_StringRef](#) sourceFile, [uint32_t](#) lineNumber, [OTF2_RegionRef](#) enteredRegion, [OTF2_RegionRef](#) leftRegion)
Writes a [Callsite](#) definition record into the [GlobalDefWriter](#).
- [OTF2_ErrorCode OTF2_GlobalDefWriter_WriteClockProperties](#) ([OTF2_GlobalDefWriter](#) *writerHandle, [uint64_t](#) timerResolution, [uint64_t](#) globalOffset, [uint64_t](#) traceLength)
Writes a [ClockProperties](#) definition record into the [GlobalDefWriter](#).
- [OTF2_ErrorCode OTF2_GlobalDefWriter_WriteComm](#) ([OTF2_GlobalDefWriter](#) *writerHandle, [OTF2_CommRef](#) self, [OTF2_StringRef](#) name, [OTF2_GroupRef](#) group, [OTF2_CommRef](#) parent)
Writes a [Comm](#) definition record into the [GlobalDefWriter](#).
- [OTF2_ErrorCode OTF2_GlobalDefWriter_WriteGroup](#) ([OTF2_GlobalDefWriter](#) *writerHandle, [OTF2_GroupRef](#) self, [OTF2_StringRef](#) name, [OTF2_GroupType](#) groupType, [OTF2_Paradigm](#) paradigm, [OTF2_GroupFlag](#) groupFlags, [uint32_t](#) numberOfMembers, [const uint64_t](#) *members)
Writes a [Group](#) definition record into the [GlobalDefWriter](#).
- [OTF2_ErrorCode OTF2_GlobalDefWriter_WriteLocation](#) ([OTF2_GlobalDefWriter](#) *writerHandle, [OTF2_LocationRef](#) self, [OTF2_StringRef](#) name, [OTF2_LocationType](#) locationType, [uint64_t](#) numberOfEvents, [OTF2_LocationGroupRef](#) locationGroup)
Writes a [Location](#) definition record into the [GlobalDefWriter](#).
- [OTF2_ErrorCode OTF2_GlobalDefWriter_WriteLocationGroup](#) ([OTF2_GlobalDefWriter](#) *writerHandle, [OTF2_LocationGroupRef](#) self, [OTF2_StringRef](#) name, [OTF2_LocationGroupType](#) locationGroupType, [OTF2_SystemTreeNodeRef](#) systemTreeParent)
Writes a [LocationGroup](#) definition record into the [GlobalDefWriter](#).
- [OTF2_ErrorCode OTF2_GlobalDefWriter_WriteMetricClass](#) ([OTF2_GlobalDefWriter](#) *writerHandle, [OTF2_MetricRef](#) self, [uint8_t](#) numberOfMetrics, [const OTF2_](#)

APPENDIX J. FILE DOCUMENTATION

[MetricMemberRef](#) *metricMembers, [OTF2_MetricOccurrence](#) metricOccurrence, [OTF2_RecorderKind](#) recorderKind)

Writes a [MetricClass](#) definition record into the [GlobalDefWriter](#).

- [OTF2_ErrorCode](#) [OTF2_GlobalDefWriter_WriteMetricClassRecorder](#) ([OTF2_GlobalDefWriter](#) *writerHandle, [OTF2_MetricRef](#) metricClass, [OTF2_LocationRef](#) recorder)

Writes a [MetricClassRecorder](#) definition record into the [GlobalDefWriter](#).

- [OTF2_ErrorCode](#) [OTF2_GlobalDefWriter_WriteMetricInstance](#) ([OTF2_GlobalDefWriter](#) *writerHandle, [OTF2_MetricRef](#) self, [OTF2_MetricRef](#) metricClass, [OTF2_LocationRef](#) recorder, [OTF2_MetricScope](#) metricScope, [uint64_t](#) scope)

Writes a [MetricInstance](#) definition record into the [GlobalDefWriter](#).

- [OTF2_ErrorCode](#) [OTF2_GlobalDefWriter_WriteMetricMember](#) ([OTF2_GlobalDefWriter](#) *writerHandle, [OTF2_MetricMemberRef](#) self, [OTF2_StringRef](#) name, [OTF2_StringRef](#) description, [OTF2_MetricType](#) metricType, [OTF2_MetricMode](#) metricMode, [OTF2_Type](#) valueType, [OTF2_MetricBase](#) metricBase, [int64_t](#) exponent, [OTF2_StringRef](#) unit)

Writes a [MetricMember](#) definition record into the [GlobalDefWriter](#).

- [OTF2_ErrorCode](#) [OTF2_GlobalDefWriter_WriteParameter](#) ([OTF2_GlobalDefWriter](#) *writerHandle, [OTF2_ParameterRef](#) self, [OTF2_StringRef](#) name, [OTF2_ParameterType](#) parameterType)

Writes a [Parameter](#) definition record into the [GlobalDefWriter](#).

- [OTF2_ErrorCode](#) [OTF2_GlobalDefWriter_WriteRegion](#) ([OTF2_GlobalDefWriter](#) *writerHandle, [OTF2_RegionRef](#) self, [OTF2_StringRef](#) name, [OTF2_StringRef](#) canonicalName, [OTF2_StringRef](#) description, [OTF2_RegionRole](#) regionRole, [OTF2_Paradigm](#) paradigm, [OTF2_RegionFlag](#) regionFlags, [OTF2_StringRef](#) sourceFile, [uint32_t](#) beginLineNumber, [uint32_t](#) endLineNumber)

Writes a [Region](#) definition record into the [GlobalDefWriter](#).

- [OTF2_ErrorCode](#) [OTF2_GlobalDefWriter_WriteRmaWin](#) ([OTF2_GlobalDefWriter](#) *writerHandle, [OTF2_RmaWinRef](#) self, [OTF2_StringRef](#) name, [OTF2_CommRef](#) comm)

Writes a [RmaWin](#) definition record into the [GlobalDefWriter](#).

- [OTF2_ErrorCode](#) [OTF2_GlobalDefWriter_WriteString](#) ([OTF2_GlobalDefWriter](#) *writerHandle, [OTF2_StringRef](#) self, [const char](#) *string)

Writes a [String](#) definition record into the [GlobalDefWriter](#).

J.17 OTF2_GlobalDefWriter.h File Reference

- `OTF2_ErrorCode OTF2_GlobalDefWriter_WriteSystemTreeNode` (`OTF2_GlobalDefWriter *writerHandle`, `OTF2_SystemTreeNodeRef self`, `OTF2_StringRef name`, `OTF2_StringRef className`, `OTF2_SystemTreeNodeRef parent`)
Writes a `SystemTreeNode` definition record into the `GlobalDefWriter`.
- `OTF2_ErrorCode OTF2_GlobalDefWriter_WriteSystemTreeNodeDomain` (`OTF2_GlobalDefWriter *writerHandle`, `OTF2_SystemTreeNodeRef systemTreeNode`, `OTF2_SystemTreeDomain systemTreeDomain`)
Writes a `SystemTreeNodeDomain` definition record into the `GlobalDefWriter`.
- `OTF2_ErrorCode OTF2_GlobalDefWriter_WriteSystemTreeNodeProperty` (`OTF2_GlobalDefWriter *writerHandle`, `OTF2_SystemTreeNodeRef systemTreeNode`, `OTF2_StringRef name`, `OTF2_StringRef value`)
Writes a `SystemTreeNodeProperty` definition record into the `GlobalDefWriter`.

J.17.1 Detailed Description

This layer always writes globally defined OTF2 definition records and is used to write either the global definitions in addition to local definitions or write all definitions as globally valid in combination with `OTF2_GlobalEventWriter`. Global definitions are stored in one global definition file, which makes it nearly impossible to write them in a distributed manner. It is therefore only allowed to get such a writer from an `OTF2_ArchiveHandler` which is marked as `OTF2_MASTER`.

Source Template:

`templates/OTF2_GlobalDefWriter.templ.h`

Maintainer:

Dominic Eschweiler <d.eschweiler@fz-juelich.de>

Authors

Dominic Eschweiler <d.eschweiler@fz-juelich.de>, Michael Wagner <michael.wagner@zih.tu-dresden.de>

J.17.2 Function Documentation

J.17.2.1 `OTF2_ErrorCode OTF2_GlobalDefWriter_GetNumberOfDefinitions` (`OTF2_GlobalDefWriter * writerHandle`, `uint64_t * numberOfDefinitions`)

Returns the current number of written definitions of a global definition writer.

APPENDIX J. FILE DOCUMENTATION

Parameters

| | | |
|-----|----------------------------|---|
| | <i>writerHandle</i> | Handle to the global definition writer. |
| out | <i>numberOfDefinitions</i> | Storage for the number of definitions. |

Returns

[OTF2_SUCCESS](#) if successful, an error code if an error occurs.

J.17.2.2 `OTF2_ErrorCode OTF2_GlobalDefWriter_GetNumberOfLocations (OTF2_GlobalDefWriter * writerHandle, uint64_t * numberOfLocations)`

Returns the current number of written location definitions of a global definition writer.

Parameters

| | | |
|-----|--------------------------|---|
| | <i>writerHandle</i> | Handle to the global definition writer. |
| out | <i>numberOfLocations</i> | Storage for the number of locations. |

Returns

[OTF2_SUCCESS](#) if successful, an error code if an error occurs.

J.17.2.3 `OTF2_ErrorCode OTF2_GlobalDefWriter_WriteAttribute (OTF2_GlobalDefWriter * writerHandle, OTF2_AttributeRef self, OTF2_StringRef name, OTF2_Type type)`

Writes a [Attribute](#) definition record into the GlobalDefWriter.

Parameters

| | |
|---------------------|--|
| <i>writerHandle</i> | The writer handle. |
| <i>self</i> | The unique identifier for this Attribute definition. |
| <i>name</i> | Name of the attribute. References a String definition. |
| <i>type</i> | Type of the attribute value. |

J.17 OTF2_GlobalDefWriter.h File Reference

Since

Version 1.0

Returns

[OTF2_SUCCESS](#) if successful, an error code if an error occurs.

J.17.2.4 `OTF2_StatusCode OTF2_GlobalDefWriter_WriteCallpath (`
`OTF2_GlobalDefWriter * writerHandle, OTF2_CallpathRef self,`
`OTF2_CallpathRef parent, OTF2_RegionRef region)`

Writes a [Callpath](#) definition record into the GlobalDefWriter.

Parameters

| | |
|---------------------|---|
| <i>writerHandle</i> | The writer handle. |
| <i>self</i> | The unique identifier for this Callpath definition. |
| <i>parent</i> | References a Callpath definition. |
| <i>region</i> | References a Region definition. |

Since

Version 1.0

Returns

[OTF2_SUCCESS](#) if successful, an error code if an error occurs.

J.17.2.5 `OTF2_StatusCode OTF2_GlobalDefWriter_WriteCallsite (`
`OTF2_GlobalDefWriter * writerHandle, OTF2_CallsiteRef self,`
`OTF2_StringRef sourceFile, uint32_t lineNumber, OTF2_RegionRef`
`enteredRegion, OTF2_RegionRef leftRegion)`

Writes a [Callsite](#) definition record into the GlobalDefWriter.

Parameters

| | |
|---------------------|---|
| <i>writerHandle</i> | The writer handle. |
| <i>self</i> | The unique identifier for this Callsite definition. |
| <i>sourceFile</i> | The source file where this call was made. References a String definition. |
| <i>lineNumber</i> | Line number in the source file where this call was made. |

APPENDIX J. FILE DOCUMENTATION

| | |
|----------------------|---|
| <i>enteredRegion</i> | The region which was called. References a Region definition. |
| <i>leftRegion</i> | The region which made the call. References a Region definition. |

Since

Version 1.0

Returns

[OTF2_SUCCESS](#) if successful, an error code if an error occurs.

J.17.2.6 `OTF2_StatusCode OTF2_GlobalDefWriter_WriteClockProperties (OTF2_GlobalDefWriter * writerHandle, uint64_t timerResolution, uint64_t globalOffset, uint64_t traceLength)`

Writes a [ClockProperties](#) definition record into the GlobalDefWriter.

Defines the timer resolution and time range of this trace. There will be no event with a timestamp less than *globalOffset*, and no event with timestamp greater than (*globalOffset* + *traceLength*).

Parameters

| | |
|------------------------|---|
| <i>writerHandle</i> | The writer handle. |
| <i>timerResolution</i> | Ticks per seconds. |
| <i>globalOffset</i> | A timestamp smaller than all event timestamps. |
| <i>traceLength</i> | A timespan which includes the timespan between the smallest and greatest timestamp of all event timestamps. |

Since

Version 1.0

Returns

[OTF2_SUCCESS](#) if successful, an error code if an error occurs.

J.17 OTF2_GlobalDefWriter.h File Reference

J.17.2.7 `OTF2_ErrorCode OTF2_GlobalDefWriter_WriteComm (OTF2_GlobalDefWriter * writerHandle, OTF2_CommRef self, OTF2_StringRef name, OTF2_GroupRef group, OTF2_CommRef parent)`

Writes a [Comm](#) definition record into the GlobalDefWriter.

Parameters

| | |
|---------------------|---|
| <i>writerHandle</i> | The writer handle. |
| <i>self</i> | The unique identifier for this Comm definition. |
| <i>name</i> | The name given by calling <code>MPI_Comm_set_name</code> on this communicator. Or the empty name to indicate that no name was given. References a String definition. |
| <i>group</i> | The describing MPI group of this MPI communicator The group needs to be of type <code>OTF2_GROUP_TYPE_MPI_GROUP</code> or <code>OTF2_GROUP_TYPE_MPI_COMM_SELF</code> . References a Group definition. |
| <i>parent</i> | The parent MPI communicator from which this communicator was created, if any. Use <code>OTF2_UNDEFINED_COMM</code> to indicate no parent. References a Comm definition. |

Since

Version 1.0

Returns

[OTF2_SUCCESS](#) if successful, an error code if an error occurs.

J.17.2.8 `OTF2_ErrorCode OTF2_GlobalDefWriter_WriteGroup (OTF2_GlobalDefWriter * writerHandle, OTF2_GroupRef self, OTF2_StringRef name, OTF2_GroupType groupType, OTF2_Paradigm paradigm, OTF2_GroupFlag groupFlags, uint32_t numberOfMembers, const uint64_t * members)`

Writes a [Group](#) definition record into the GlobalDefWriter.

Parameters

| | |
|---------------------|--|
| <i>writerHandle</i> | The writer handle. |
| <i>self</i> | The unique identifier for this Group definition. |
| <i>name</i> | Name of this group References a String definition. |

APPENDIX J. FILE DOCUMENTATION

| | |
|------------------------|--|
| <i>groupType</i> | The type of this group. Since version 1.2. |
| <i>paradigm</i> | The paradigm of this communication group. Since version 1.2. |
| <i>groupFlags</i> | Flags for this group. Since version 1.2. |
| <i>numberOfMembers</i> | The number of members in this group. |
| <i>members</i> | The identifiers of the group members. |

Since

Version 1.0

Returns

[OTF2_SUCCESS](#) if successful, an error code if an error occurs.

J.17.2.9 `OTF2_StatusCode OTF2_GlobalDefWriter_WriteLocation (`
`OTF2_GlobalDefWriter * writerHandle, OTF2_LocationRef self,`
`OTF2_StringRef name, OTF2_LocationType locationType, uint64_t`
`numberOfEvents, OTF2_LocationGroupRef locationGroup)`

Writes a [Location](#) definition record into the GlobalDefWriter.

Parameters

| | |
|-----------------------|--|
| <i>writerHandle</i> | The writer handle. |
| <i>self</i> | The unique identifier for this Location definition. |
| <i>name</i> | Name of the location References a String definition. |
| <i>locationType</i> | Location type. |
| <i>numberOfEvents</i> | Number of events this location has recorded. |
| <i>locationGroup</i> | Location group which includes this location. References a Location-Group definition. |

Since

Version 1.0

Returns

[OTF2_SUCCESS](#) if successful, an error code if an error occurs.

J.17 OTF2_GlobalDefWriter.h File Reference

J.17.2.10 `OTF2_ErrorCode OTF2_GlobalDefWriter_WriteLocationGroup (OTF2_GlobalDefWriter * writerHandle, OTF2_LocationGroupRef self, OTF2_StringRef name, OTF2_LocationGroupType locationGroupType, OTF2_SystemTreeNodeRef systemTreeParent)`

Writes a [LocationGroup](#) definition record into the GlobalDefWriter.

Parameters

| | |
|--------------------------|---|
| <i>writerHandle</i> | The writer handle. |
| <i>self</i> | The unique identifier for this LocationGroup definition. |
| <i>name</i> | Name of the group. References a String definition. |
| <i>locationGroupType</i> | Type of this group. |
| <i>systemTreeParent</i> | Parent of this location group in the system tree. References a SystemTreeNode definition. |

Since

Version 1.0

Returns

[OTF2_SUCCESS](#) if successful, an error code if an error occurs.

J.17.2.11 `OTF2_ErrorCode OTF2_GlobalDefWriter_WriteMetricClass (OTF2_GlobalDefWriter * writerHandle, OTF2_MetricRef self, uint8_t numberOfMetrics, const OTF2_MetricMemberRef * metricMembers, OTF2_MetricOccurrence metricOccurrence, OTF2_RecorderKind recorderKind)`

Writes a [MetricClass](#) definition record into the GlobalDefWriter.

For a metric class it is implicitly given that the event stream that records the metric is also the scope. A metric class can contain multiple different metrics.

Parameters

| | |
|------------------------|--|
| <i>writerHandle</i> | The writer handle. |
| <i>self</i> | The unique identifier for this MetricClass definition. |
| <i>numberOfMetrics</i> | Number of metrics within the set. |

APPENDIX J. FILE DOCUMENTATION

| | |
|-------------------------|--|
| <i>metricMembers</i> | List of metric members. References a MetricMember definition. |
| <i>metricOccurrence</i> | Defines occurrence of a metric set. |
| <i>recorderKind</i> | What kind of locations will record this metric class, or will this metric class only be recorded by metric instances. Since version 1.2. |

Since

Version 1.0

Returns

[OTF2_SUCCESS](#) if successful, an error code if an error occurs.

J.17.2.12 `OTF2_StatusCode OTF2_GlobalDefWriter_WriteMetricClassRecorder (OTF2_GlobalDefWriter * writerHandle, OTF2_MetricRef metricClass, OTF2_LocationRef recorder)`

Writes a [MetricClassRecorder](#) definition record into the GlobalDefWriter.

Parameters

| | |
|---------------------|---|
| <i>writerHandle</i> | The writer handle. |
| <i>metricClass</i> | Parent MetricClass definition to which this one is a supplementary definition. References a MetricClass definition. |
| <i>recorder</i> | The location which recorded the referenced metric class. References a Location definition. |

Since

Version 1.2

Returns

[OTF2_SUCCESS](#) if successful, an error code if an error occurs.

J.17.2.13 `OTF2_StatusCode OTF2_GlobalDefWriter_WriteMetricInstance (OTF2_GlobalDefWriter * writerHandle, OTF2_MetricRef self, OTF2_MetricRef metricClass, OTF2_LocationRef recorder, OTF2_MetricScope metricScope, uint64_t scope)`

Writes a [MetricInstance](#) definition record into the GlobalDefWriter.

J.17 OTF2_GlobalDefWriter.h File Reference

A metric instance is used to define metrics that are recorded at one location for multiple locations or for another location. The occurrence of a metric instance is implicitly of type *OTF2_METRIC_ASYNCHRONOUS*.

Parameters

| | |
|---------------------|---|
| <i>writerHandle</i> | The writer handle. |
| <i>self</i> | The unique identifier for this <i>MetricClass</i> definition. |
| <i>metricClass</i> | The instanced <i>MetricClass</i> . This metric class must be of kind <i>OTF2_RECORDER_KIND_ABSTRACT</i> . References a <i>MetricClass</i> definition. |
| <i>recorder</i> | Recorder of the metric: location ID. References a <i>Location</i> definition. |
| <i>metricScope</i> | Defines type of scope: location, location group, system tree node, or a generic group of locations. |
| <i>scope</i> | Scope of metric: ID of a location, location group, system tree node, or a generic group of locations. |

Since

Version 1.0

Returns

OTF2_SUCCESS if successful, an error code if an error occurs.

J.17.2.14 *OTF2_*ErrorCode *OTF2_GlobalDefWriter_WriteMetricMember* (
OTF2_GlobalDefWriter * *writerHandle*, *OTF2_MetricMemberRef*
self, *OTF2_StringRef* *name*, *OTF2_StringRef* *description*,
OTF2_MetricType *metricType*, *OTF2_MetricMode* *metricMode*,
OTF2_Type *valueType*, *OTF2_MetricBase* *metricBase*, int64.t *exponent*,
OTF2_StringRef *unit*)

Writes a *MetricMember* definition record into the GlobalDefWriter.

A metric is defined by a metric member definition. A metric member is always a member of a metric class. Therefore, a single metric is a special case of a metric class with only one member. It is not allowed to reference a metric member id in a metric event, but only metric class IDs.

Parameters

| | |
|---------------------|--|
| <i>writerHandle</i> | The writer handle. |
| <i>self</i> | The unique identifier for this <i>MetricMember</i> definition. |
| <i>name</i> | Name of the metric. References a <i>String</i> definition. |

APPENDIX J. FILE DOCUMENTATION

| | |
|--------------------|---|
| <i>description</i> | Description of the metric. References a String definition. |
| <i>metricType</i> | Metric type: PAPI, etc. |
| <i>metricMode</i> | Metric mode: accumulative, fix, relative, etc. |
| <i>valueType</i> | Type of the value: int64_t, uint64_t, or double. |
| <i>metricBase</i> | The recorded values should be handled in this given base, either binary or decimal. This information can be used if the value needs to be scaled. |
| <i>exponent</i> | The values inside the Metric events should be scaled by the factor $\text{base}^{\text{exponent}}$, to get the value in its base unit. For example, if the metric values come in as KiBi, than the base should be OTF2_BASE_BINARY and the exponent 10. Than the writer does not need to scale the values up to bytes, but can directly write the KiBi values into the Metric event. At reading time, the reader can apply the scaling factor to get the value in its base unit, ie. in bytes. |
| <i>unit</i> | Unit of the metric. This needs to be the scale free base unit, ie. "bytes", "operations", or "seconds". In particular this unit should not have any scale prefix. References a String definition. |

Since

Version 1.0

Returns

[OTF2_SUCCESS](#) if successful, an error code if an error occurs.

J.17.2.15 [OTF2_ErrorCode](#) [OTF2_GlobalDefWriter_WriteParameter](#) (
[OTF2_GlobalDefWriter](#) * *writerHandle*, [OTF2_ParameterRef](#) *self*,
[OTF2_StringRef](#) *name*, [OTF2_ParameterType](#) *parameterType*)

Writes a [Parameter](#) definition record into the GlobalDefWriter.

Parameters

| | |
|----------------------|--|
| <i>writerHandle</i> | The writer handle. |
| <i>self</i> | The unique identifier for this Parameter definition. |
| <i>name</i> | Name of the parameter (variable name etc.) References a String definition. |
| <i>parameterType</i> | Type of the parameter, OTF2_ParameterType for possible types. |

J.17 OTF2_GlobalDefWriter.h File Reference

Since

Version 1.0

Returns

[OTF2_SUCCESS](#) if successful, an error code if an error occurs.

J.17.2.16 `OTF2_ErrorCode OTF2_GlobalDefWriter_WriteRegion (OTF2_GlobalDefWriter * writerHandle, OTF2_RegionRef self, OTF2_StringRef name, OTF2_StringRef canonicalName, OTF2_StringRef description, OTF2_RegionRole regionRole, OTF2_Paradigm paradigm, OTF2_RegionFlag regionFlags, OTF2_StringRef sourceFile, uint32_t beginLineNumber, uint32_t endLineNumber)`

Writes a [Region](#) definition record into the GlobalDefWriter.

Parameters

| | |
|------------------------|--|
| <i>writerHandle</i> | The writer handle. |
| <i>self</i> | The unique identifier for this Region definition. |
| <i>name</i> | Name of the region (demangled name if available). References a String definition. |
| <i>canonicalName</i> | Alternative name of the region (e.g. mangled name). References a String definition. Since version 1.1. |
| <i>description</i> | A more detailed description of this region. References a String definition. |
| <i>regionRole</i> | Region role. Since version 1.1. |
| <i>paradigm</i> | Paradigm. Since version 1.1. |
| <i>regionFlags</i> | Region flags. Since version 1.1. |
| <i>sourceFile</i> | The source file where this region was declared. References a String definition. |
| <i>beginLineNumber</i> | Starting line number of this region in the source file. |
| <i>endLineNumber</i> | Ending line number of this region in the source file. |

Since

Version 1.0

Returns

[OTF2_SUCCESS](#) if successful, an error code if an error occurs.

J.17.2.17 `OTF2_ErrorCode OTF2_GlobalDefWriter_WriteRmaWin (OTF2_GlobalDefWriter * writerHandle, OTF2_RmaWinRef self, OTF2_StringRef name, OTF2_CommRef comm)`

Writes a [RmaWin](#) definition record into the GlobalDefWriter.

A window defines the communication context for any remote-memory access operation.

Parameters

| | |
|---------------------|--|
| <i>writerHandle</i> | The writer handle. |
| <i>self</i> | The unique identifier for this RmaWin definition. |
| <i>name</i> | Name, e.g. 'GASPI Queue 1', 'NVidia Card 2', etc.. References a String definition. |
| <i>comm</i> | Communicator object used to create the window. References a Comm definition. |

Since

Version 1.2

Returns

[OTF2_SUCCESS](#) if successful, an error code if an error occurs.

J.17.2.18 `OTF2_ErrorCode OTF2_GlobalDefWriter_WriteString (OTF2_GlobalDefWriter * writerHandle, OTF2_StringRef self, const char * string)`

Writes a [String](#) definition record into the GlobalDefWriter.

Parameters

| | |
|---------------------|---|
| <i>writerHandle</i> | The writer handle. |
| <i>self</i> | The unique identifier for this String definition. |
| <i>string</i> | The string, null terminated. |

J.17 OTF2_GlobalDefWriter.h File Reference

Since

Version 1.0

Returns

[OTF2_SUCCESS](#) if successful, an error code if an error occurs.

J.17.2.19 `OTF2_ErrorCode OTF2_GlobalDefWriter_WriteSystemTreeNode (OTF2_GlobalDefWriter * writerHandle, OTF2_SystemTreeNodeRef self, OTF2_StringRef name, OTF2_StringRef className, OTF2_SystemTreeNodeRef parent)`

Writes a [SystemTreeNode](#) definition record into the GlobalDefWriter.

Parameters

| | |
|---------------------|---|
| <i>writerHandle</i> | The writer handle. |
| <i>self</i> | The unique identifier for this SystemTreeNode definition. |
| <i>name</i> | Free form instance name of this node. References a String definition. |
| <i>className</i> | Free form class name of this node. References a String definition. |
| <i>parent</i> | Parent id of this node. May be OTF2_UNDEFINED_SYSTEM_TREE_NODE to indicate that there is no parent. References a SystemTreeNode definition. |

Since

Version 1.0

Returns

[OTF2_SUCCESS](#) if successful, an error code if an error occurs.

J.17.2.20 `OTF2_ErrorCode OTF2_GlobalDefWriter_WriteSystemTreeNodeDomain (OTF2_GlobalDefWriter * writerHandle, OTF2_SystemTreeNodeRef systemTreeNode, OTF2_SystemTreeDomain systemTreeDomain)`

Writes a [SystemTreeNodeDomain](#) definition record into the GlobalDefWriter.

Parameters

| | |
|---------------------|--------------------|
| <i>writerHandle</i> | The writer handle. |
|---------------------|--------------------|

APPENDIX J. FILE DOCUMENTATION

| | |
|-----------------------|---|
| <i>systemTreeNode</i> | Parent SystemTreeNode definition to which this one is a supplementary definition. References a SystemTreeNode definition. |
|-----------------------|---|

Since

Version 1.2

Returns

[OTF2_SUCCESS](#) if successful, an error code if an error occurs.

J.17.2.21 `OTF2_StatusCode OTF2_GlobalDefWriter_WriteSystemTreeNodeProperty (OTF2_GlobalDefWriter * writerHandle, OTF2_SystemTreeNodeRef systemTreeNode, OTF2_StringRef name, OTF2_StringRef value)`

Writes a [SystemTreeNodeProperty](#) definition record into the GlobalDefWriter.

Parameters

| | |
|-----------------------|---|
| <i>writerHandle</i> | The writer handle. |
| <i>systemTreeNode</i> | Parent SystemTreeNode definition to which this one is a supplementary definition. References a SystemTreeNode definition. |
| <i>name</i> | Name of the property. References a String definition. |
| <i>value</i> | Property value. References a String definition. |

Since

Version 1.2

Returns

[OTF2_SUCCESS](#) if successful, an error code if an error occurs.

J.18 OTF2_GlobalEvtReader.h File Reference

This is the global event reader.

```
#include <stdint.h>
#include <otf2/OTF2_ErrorCodes.h>
#include <otf2/OTF2_EvtReader.h>
```

J.18 OTF2_GlobalEvtReader.h File Reference

```
#include <otf2/OTF2_GlobalEvtReaderCallbacks.h>
```

Functions

- [OTF2_ErrorCode OTF2_GlobalEvtReader_HasEvent](#) (OTF2_GlobalEvtReader *reader, int *flag)
Has more events.
- [OTF2_ErrorCode OTF2_GlobalEvtReader_ReadEvent](#) (OTF2_GlobalEvtReader *reader)
Triggers the callback for the next event record.
- [OTF2_ErrorCode OTF2_GlobalEvtReader_ReadEvents](#) (OTF2_GlobalEvtReader *reader, uint64_t recordsToRead, uint64_t *recordsRead)
Reads the given number of records from the global event reader.
- [OTF2_ErrorCode OTF2_GlobalEvtReader_SetCallbacks](#) (OTF2_GlobalEvtReader *reader, const OTF2_GlobalEvtReaderCallbacks *callbacks, void *userData)

Sets the callback functions for the given reader object. Everytime when OTF2 reads a record, a callback function is called and the records data is passed to this function. Therefore the programmer needs to set function pointers at the "callbacks" struct for the record type he wants to read.

J.18.1 Detailed Description

This is the global event reader.

Maintainer:

Michael Wagner <michael.wagner@zih.tu-dresden.de>

Authors

Dominic Eschweiler <d.eschweiler@fz-juelich.de>, Michael Wagner <michael.wagner@zih.tu-dresden.de>

Used to read from multiple local event readers, and provide them in a timely ordered sequence.

APPENDIX J. FILE DOCUMENTATION

J.18.2 Function Documentation

J.18.2.1 `OTF2_ErrorCode OTF2_GlobalEvtReader_HasEvent (OTF2_GlobalEvtReader * reader, int * flag)`

Has more events.

Parameters

| | | |
|-----|---------------|--|
| | <i>reader</i> | Global event reader handle. |
| out | <i>flag</i> | In case of success, the flag will be set to 1 when there is at least more more event to read. To 0 if not. Otherwise the value is undefined. |

Returns

[*OTF2_SUCCESS*](#) if successful, an error code if an error occurs.

J.18.2.2 `OTF2_ErrorCode OTF2_GlobalEvtReader_ReadEvent (OTF2_GlobalEvtReader * reader)`

Triggers the callback for the next event record.

Parameters

| | | |
|--|---------------|---|
| | <i>reader</i> | Reader object which reads the events from its buffer. |
|--|---------------|---|

Returns

[*OTF2_SUCCESS*](#) if successful, an error code if an error occurs.

J.18.2.3 `OTF2_ErrorCode OTF2_GlobalEvtReader_ReadEvents (OTF2_GlobalEvtReader * reader, uint64.t recordsToRead, uint64.t * recordsRead)`

Reads the given number of records from the global event reader.

Parameters

| | | |
|--|----------------------|--|
| | <i>reader</i> | The records of this reader will be read when the function is issued. |
| | <i>recordsToRead</i> | This variable tells the reader how much records it has to read. |

J.19 OTF2_GlobalEvtReaderCallbacks.h File Reference

| | | |
|-----|--------------------|---|
| out | <i>recordsRead</i> | This is a pointer to variable where the amount of actually read records is returned. This may differ to the given recordsToRead if there are no more records left in the trace. In this case the programmer can easily check that the reader has finished his job by checking <code>recordsRead < recordsToRead</code> . |
|-----|--------------------|---|

Returns

[OTF2_SUCCESS](#) if successful, an error code if an error occurs.

J.18.2.4 `OTF2_ErrorCode OTF2_GlobalEvtReader_SetCallbacks (OTF2_GlobalEvtReader * reader, const OTF2_GlobalEvtReaderCallbacks * callbacks, void * userData)`

Sets the callback functions for the given reader object. Everytime when OTF2 reads a record, a callback function is called and the records data is passed to this function. Therefore the programmer needs to set function pointers at the "callbacks" struct for the record type he wants to read.

Parameters

| | |
|------------------|---|
| <i>reader</i> | Reader object which reads the events from its buffer. |
| <i>callbacks</i> | Struct which holds a function pointer for each record type. OTF2_GlobalEvtReaderCallbacks_New . |
| <i>userData</i> | Data passed as argument <i>userData</i> to the record callbacks. |

Returns

[OTF2_SUCCESS](#) if successful, an error code if an error occurs.

J.19 OTF2_GlobalEvtReaderCallbacks.h File Reference

This defines the callbacks for the global event reader.

```
#include <stdint.h>
#include <otf2/OTF2_ErrorCodes.h>
#include <otf2/OTF2_GeneralDefinitions.h>
#include <otf2/OTF2_AttributeList.h>
#include <otf2/OTF2_Events.h>
```

Typedefs

- typedef OTF2_CallbackCode(* OTF2_GlobalEvtReaderCallback_BufferFlush)(OTF2_LocationRef locationID, OTF2_TimeStamp time, void *userData, OTF2_AttributeList *attributeList, OTF2_TimeStamp stopTime)
Callback for the BufferFlush event record.
- typedef OTF2_CallbackCode(* OTF2_GlobalEvtReaderCallback_Enter)(OTF2_LocationRef locationID, OTF2_TimeStamp time, void *userData, OTF2_AttributeList *attributeList, OTF2_RegionRef region)
Callback for the Enter event record.
- typedef OTF2_CallbackCode(* OTF2_GlobalEvtReaderCallback_Leave)(OTF2_LocationRef locationID, OTF2_TimeStamp time, void *userData, OTF2_AttributeList *attributeList, OTF2_RegionRef region)
Callback for the Leave event record.
- typedef OTF2_CallbackCode(* OTF2_GlobalEvtReaderCallback_MeasurementOnOff)(OTF2_LocationRef locationID, OTF2_TimeStamp time, void *userData, OTF2_AttributeList *attributeList, OTF2_MeasurementMode measurementMode)
Callback for the MeasurementOnOff event record.
- typedef OTF2_CallbackCode(* OTF2_GlobalEvtReaderCallback_Metric)(OTF2_LocationRef locationID, OTF2_TimeStamp time, void *userData, OTF2_AttributeList *attributeList, OTF2_MetricRef metric, uint8_t numberOfMetrics, const OTF2_Type *typeIDs, const OTF2_MetricValue *metricValues)
Callback for the Metric event record.
- typedef OTF2_CallbackCode(* OTF2_GlobalEvtReaderCallback_MpiCollectiveBegin)(OTF2_LocationRef locationID, OTF2_TimeStamp time, void *userData, OTF2_AttributeList *attributeList)
Callback for the MpiCollectiveBegin event record.
- typedef OTF2_CallbackCode(* OTF2_GlobalEvtReaderCallback_MpiCollectiveEnd)(OTF2_LocationRef locationID, OTF2_TimeStamp time, void *userData, OTF2_AttributeList *attributeList, OTF2_CollectiveOp collectiveOp, OTF2_CommRef communicator, uint32_t root, uint64_t sizeSent, uint64_t sizeReceived)
Callback for the MpiCollectiveEnd event record.

J.19 OTF2_GlobalEvtReaderCallbacks.h File Reference

- typedef OTF2_CallbackCode(* OTF2_GlobalEvtReaderCallback_MpiIrecv)(OTF2_LocationRef locationID, OTF2_TimeStamp time, void *userData, OTF2_AttributeList *attributeList, uint32_t sender, OTF2_CommRef communicator, uint32_t msgTag, uint64_t msgLength, uint64_t requestID)
Callback for the MpiIrecv event record.
- typedef OTF2_CallbackCode(* OTF2_GlobalEvtReaderCallback_MpiIrecvRequest)(OTF2_LocationRef locationID, OTF2_TimeStamp time, void *userData, OTF2_AttributeList *attributeList, uint64_t requestID)
Callback for the MpiIrecvRequest event record.
- typedef OTF2_CallbackCode(* OTF2_GlobalEvtReaderCallback_MpiIsend)(OTF2_LocationRef locationID, OTF2_TimeStamp time, void *userData, OTF2_AttributeList *attributeList, uint32_t receiver, OTF2_CommRef communicator, uint32_t msgTag, uint64_t msgLength, uint64_t requestID)
Callback for the MpiIsend event record.
- typedef OTF2_CallbackCode(* OTF2_GlobalEvtReaderCallback_MpiIsendComplete)(OTF2_LocationRef locationID, OTF2_TimeStamp time, void *userData, OTF2_AttributeList *attributeList, uint64_t requestID)
Callback for the MpiIsendComplete event record.
- typedef OTF2_CallbackCode(* OTF2_GlobalEvtReaderCallback_MpiRecv)(OTF2_LocationRef locationID, OTF2_TimeStamp time, void *userData, OTF2_AttributeList *attributeList, uint32_t sender, OTF2_CommRef communicator, uint32_t msgTag, uint64_t msgLength)
Callback for the MpiRecv event record.
- typedef OTF2_CallbackCode(* OTF2_GlobalEvtReaderCallback_MpiRequestCancelled)(OTF2_LocationRef locationID, OTF2_TimeStamp time, void *userData, OTF2_AttributeList *attributeList, uint64_t requestID)
Callback for the MpiRequestCancelled event record.
- typedef OTF2_CallbackCode(* OTF2_GlobalEvtReaderCallback_MpiRequestTest)(OTF2_LocationRef locationID, OTF2_TimeStamp time, void *userData, OTF2_AttributeList *attributeList, uint64_t requestID)
Callback for the MpiRequestTest event record.
- typedef OTF2_CallbackCode(* OTF2_GlobalEvtReaderCallback_MpiSend)(OTF2_LocationRef locationID, OTF2_TimeStamp time, void *userData, OTF2_AttributeList *attributeList, uint32_t receiver, OTF2_CommRef communicator, uint32_t msgTag, uint64_t msgLength)

APPENDIX J. FILE DOCUMENTATION

Callback for the `MpiSend` event record.

- typedef `OTF2_CallbackCode(* OTF2_GlobalEvtReaderCallback_OmpAcquireLock)`(`OTF2_LocationRef` locationID, `OTF2_TimeStamp` time, void *userData, `OTF2_AttributeList` *attributeList, `uint32_t` lockID, `uint32_t` acquisitionOrder)

Callback for the `OmpAcquireLock` event record.

- typedef `OTF2_CallbackCode(* OTF2_GlobalEvtReaderCallback_OmpFork)`(`OTF2_LocationRef` locationID, `OTF2_TimeStamp` time, void *userData, `OTF2_AttributeList` *attributeList, `uint32_t` numberOfRequestedThreads)

Callback for the `OmpFork` event record.

- typedef `OTF2_CallbackCode(* OTF2_GlobalEvtReaderCallback_OmpJoin)`(`OTF2_LocationRef` locationID, `OTF2_TimeStamp` time, void *userData, `OTF2_AttributeList` *attributeList)

Callback for the `OmpJoin` event record.

- typedef `OTF2_CallbackCode(* OTF2_GlobalEvtReaderCallback_OmpReleaseLock)`(`OTF2_LocationRef` locationID, `OTF2_TimeStamp` time, void *userData, `OTF2_AttributeList` *attributeList, `uint32_t` lockID, `uint32_t` acquisitionOrder)

Callback for the `OmpReleaseLock` event record.

- typedef `OTF2_CallbackCode(* OTF2_GlobalEvtReaderCallback_OmpTaskComplete)`(`OTF2_LocationRef` locationID, `OTF2_TimeStamp` time, void *userData, `OTF2_AttributeList` *attributeList, `uint64_t` taskID)

Callback for the `OmpTaskComplete` event record.

- typedef `OTF2_CallbackCode(* OTF2_GlobalEvtReaderCallback_OmpTaskCreate)`(`OTF2_LocationRef` locationID, `OTF2_TimeStamp` time, void *userData, `OTF2_AttributeList` *attributeList, `uint64_t` taskID)

Callback for the `OmpTaskCreate` event record.

- typedef `OTF2_CallbackCode(* OTF2_GlobalEvtReaderCallback_OmpTaskSwitch)`(`OTF2_LocationRef` locationID, `OTF2_TimeStamp` time, void *userData, `OTF2_AttributeList` *attributeList, `uint64_t` taskID)

Callback for the `OmpTaskSwitch` event record.

- typedef `OTF2_CallbackCode(* OTF2_GlobalEvtReaderCallback_ParameterInt)`(`OTF2_LocationRef` locationID, `OTF2_TimeStamp` time, void *userData, `OTF2_AttributeList` *attributeList, `OTF2_ParameterRef` parameter, `int64_t` value)

J.19 OTF2_GlobalEvtReaderCallbacks.h File Reference

Callback for the ParameterInt event record.

- typedef OTF2_CallbackCode(* OTF2_GlobalEvtReaderCallback_ParameterString)(OTF2_LocationRef locationID, OTF2_TimeStamp time, void *userData, OTF2_AttributeList *attributeList, OTF2_ParameterRef parameter, OTF2_StringRef string)

Callback for the ParameterString event record.

- typedef OTF2_CallbackCode(* OTF2_GlobalEvtReaderCallback_ParameterUnsignedInt)(OTF2_LocationRef locationID, OTF2_TimeStamp time, void *userData, OTF2_AttributeList *attributeList, OTF2_ParameterRef parameter, uint64_t value)

Callback for the ParameterUnsignedInt event record.

- typedef OTF2_CallbackCode(* OTF2_GlobalEvtReaderCallback_RmaAcquireLock)(OTF2_LocationRef locationID, OTF2_TimeStamp time, void *userData, OTF2_AttributeList *attributeList, OTF2_RmaWinRef win, uint32_t remote, uint64_t lockId, OTF2_LockType lockType)

Callback for the RmaAcquireLock event record.

- typedef OTF2_CallbackCode(* OTF2_GlobalEvtReaderCallback_RmaAtomic)(OTF2_LocationRef locationID, OTF2_TimeStamp time, void *userData, OTF2_AttributeList *attributeList, OTF2_RmaWinRef win, uint32_t remote, OTF2_RmaAtomicType type, uint64_t bytesSent, uint64_t bytesReceived, uint64_t matchingId)

Callback for the RmaAtomic event record.

- typedef OTF2_CallbackCode(* OTF2_GlobalEvtReaderCallback_RmaCollectiveBegin)(OTF2_LocationRef locationID, OTF2_TimeStamp time, void *userData, OTF2_AttributeList *attributeList)

Callback for the RmaCollectiveBegin event record.

- typedef OTF2_CallbackCode(* OTF2_GlobalEvtReaderCallback_RmaCollectiveEnd)(OTF2_LocationRef locationID, OTF2_TimeStamp time, void *userData, OTF2_AttributeList *attributeList, OTF2_CollectiveOp collectiveOp, OTF2_RmaSyncLevel syncLevel, OTF2_RmaWinRef win, uint32_t root, uint64_t bytesSent, uint64_t bytesReceived)

Callback for the RmaCollectiveEnd event record.

- typedef OTF2_CallbackCode(* OTF2_GlobalEvtReaderCallback_RmaGet)(OTF2_LocationRef locationID, OTF2_TimeStamp time, void *userData, OTF2_AttributeList *attributeList, OTF2_RmaWinRef win, uint32_t remote, uint64_t bytes, uint64_t matchingId)

APPENDIX J. FILE DOCUMENTATION

Callback for the RmaGet event record.

- typedef OTF2_CallbackCode(* OTF2_GlobalEvtReaderCallback_RmaGroupSync)(OTF2_LocationRef locationID, OTF2_TimeStamp time, void *userData, OTF2_AttributeList *attributeList, OTF2_RmaSyncLevel syncLevel, OTF2_RmaWinRef win, OTF2_GroupRef group)

Callback for the RmaGroupSync event record.

- typedef OTF2_CallbackCode(* OTF2_GlobalEvtReaderCallback_RmaOpCompleteBlocking)(OTF2_LocationRef locationID, OTF2_TimeStamp time, void *userData, OTF2_AttributeList *attributeList, OTF2_RmaWinRef win, uint64_t matchingId)

Callback for the RmaOpCompleteBlocking event record.

- typedef OTF2_CallbackCode(* OTF2_GlobalEvtReaderCallback_RmaOpCompleteNonBlocking)(OTF2_LocationRef locationID, OTF2_TimeStamp time, void *userData, OTF2_AttributeList *attributeList, OTF2_RmaWinRef win, uint64_t matchingId)

Callback for the RmaOpCompleteNonBlocking event record.

- typedef OTF2_CallbackCode(* OTF2_GlobalEvtReaderCallback_RmaOpCompleteRemote)(OTF2_LocationRef locationID, OTF2_TimeStamp time, void *userData, OTF2_AttributeList *attributeList, OTF2_RmaWinRef win, uint64_t matchingId)

Callback for the RmaOpCompleteRemote event record.

- typedef OTF2_CallbackCode(* OTF2_GlobalEvtReaderCallback_RmaOpTest)(OTF2_LocationRef locationID, OTF2_TimeStamp time, void *userData, OTF2_AttributeList *attributeList, OTF2_RmaWinRef win, uint64_t matchingId)

Callback for the RmaOpTest event record.

- typedef OTF2_CallbackCode(* OTF2_GlobalEvtReaderCallback_RmaPut)(OTF2_LocationRef locationID, OTF2_TimeStamp time, void *userData, OTF2_AttributeList *attributeList, OTF2_RmaWinRef win, uint32_t remote, uint64_t bytes, uint64_t matchingId)

Callback for the RmaPut event record.

- typedef OTF2_CallbackCode(* OTF2_GlobalEvtReaderCallback_RmaReleaseLock)(OTF2_LocationRef locationID, OTF2_TimeStamp time, void *userData, OTF2_AttributeList *attributeList, OTF2_RmaWinRef win, uint32_t remote, uint64_t lockId)

J.19 OTF2_GlobalEvtReaderCallbacks.h File Reference

Callback for the RmaReleaseLock event record.

- typedef OTF2_CallbackCode(* OTF2_GlobalEvtReaderCallback_RmaRequestLock)(OTF2_LocationRef locationID, OTF2_TimeStamp time, void *userData, OTF2_AttributeList *attributeList, OTF2_RmaWinRef win, uint32_t remote, uint64_t lockId, OTF2_LockType lockType)

Callback for the RmaRequestLock event record.

- typedef OTF2_CallbackCode(* OTF2_GlobalEvtReaderCallback_RmaSync)(OTF2_LocationRef locationID, OTF2_TimeStamp time, void *userData, OTF2_AttributeList *attributeList, OTF2_RmaWinRef win, uint32_t remote, OTF2_RmaSyncType syncType)

Callback for the RmaSync event record.

- typedef OTF2_CallbackCode(* OTF2_GlobalEvtReaderCallback_RmaTryLock)(OTF2_LocationRef locationID, OTF2_TimeStamp time, void *userData, OTF2_AttributeList *attributeList, OTF2_RmaWinRef win, uint32_t remote, uint64_t lockId, OTF2_LockType lockType)

Callback for the RmaTryLock event record.

- typedef OTF2_CallbackCode(* OTF2_GlobalEvtReaderCallback_RmaWaitChange)(OTF2_LocationRef locationID, OTF2_TimeStamp time, void *userData, OTF2_AttributeList *attributeList, OTF2_RmaWinRef win)

Callback for the RmaWaitChange event record.

- typedef OTF2_CallbackCode(* OTF2_GlobalEvtReaderCallback_RmaWinCreate)(OTF2_LocationRef locationID, OTF2_TimeStamp time, void *userData, OTF2_AttributeList *attributeList, OTF2_RmaWinRef win)

Callback for the RmaWinCreate event record.

- typedef OTF2_CallbackCode(* OTF2_GlobalEvtReaderCallback_RmaWinDestroy)(OTF2_LocationRef locationID, OTF2_TimeStamp time, void *userData, OTF2_AttributeList *attributeList, OTF2_RmaWinRef win)

Callback for the RmaWinDestroy event record.

- typedef OTF2_CallbackCode(* OTF2_GlobalEvtReaderCallback_ThreadAcquireLock)(OTF2_LocationRef locationID, OTF2_TimeStamp time, void *userData, OTF2_AttributeList *attributeList, OTF2_Paradigm model, uint32_t lockID, uint32_t acquisitionOrder)

Callback for the ThreadAcquireLock event record.

APPENDIX J. FILE DOCUMENTATION

- typedef OTF2_CallbackCode(* OTF2_GlobalEvtReaderCallback_ThreadFork)(OTF2_LocationRef locationID, OTF2_TimeStamp time, void *userData, OTF2_AttributeList *attributeList, OTF2_Paradigm model, uint32_t numberOfRequestedThreads)
Callback for the ThreadFork event record.
- typedef OTF2_CallbackCode(* OTF2_GlobalEvtReaderCallback_ThreadJoin)(OTF2_LocationRef locationID, OTF2_TimeStamp time, void *userData, OTF2_AttributeList *attributeList, OTF2_Paradigm model)
Callback for the ThreadJoin event record.
- typedef OTF2_CallbackCode(* OTF2_GlobalEvtReaderCallback_ThreadReleaseLock)(OTF2_LocationRef locationID, OTF2_TimeStamp time, void *userData, OTF2_AttributeList *attributeList, OTF2_Paradigm model, uint32_t lockID, uint32_t acquisitionOrder)
Callback for the ThreadReleaseLock event record.
- typedef OTF2_CallbackCode(* OTF2_GlobalEvtReaderCallback_ThreadTaskComplete)(OTF2_LocationRef locationID, OTF2_TimeStamp time, void *userData, OTF2_AttributeList *attributeList, OTF2_CommRef threadTeam, uint32_t creatingThread, uint32_t generationNumber)
Callback for the ThreadTaskComplete event record.
- typedef OTF2_CallbackCode(* OTF2_GlobalEvtReaderCallback_ThreadTaskCreate)(OTF2_LocationRef locationID, OTF2_TimeStamp time, void *userData, OTF2_AttributeList *attributeList, OTF2_CommRef threadTeam, uint32_t creatingThread, uint32_t generationNumber)
Callback for the ThreadTaskCreate event record.
- typedef OTF2_CallbackCode(* OTF2_GlobalEvtReaderCallback_ThreadTaskSwitch)(OTF2_LocationRef locationID, OTF2_TimeStamp time, void *userData, OTF2_AttributeList *attributeList, OTF2_CommRef threadTeam, uint32_t creatingThread, uint32_t generationNumber)
Callback for the ThreadTaskSwitch event record.
- typedef OTF2_CallbackCode(* OTF2_GlobalEvtReaderCallback_ThreadTeamBegin)(OTF2_LocationRef locationID, OTF2_TimeStamp time, void *userData, OTF2_AttributeList *attributeList, OTF2_CommRef threadTeam)
Callback for the ThreadTeamBegin event record.
- typedef OTF2_CallbackCode(* OTF2_GlobalEvtReaderCallback_ThreadTeamEnd)(OTF2_LocationRef locationID, OTF2_TimeStamp time, void *userData, OTF2_AttributeList *attributeList, OTF2_CommRef threadTeam)

J.19 OTF2_GlobalEvtReaderCallbacks.h File Reference

Callback for the ThreadTeamEnd event record.

- typedef OTF2_CallbackCode(* OTF2_GlobalEvtReaderCallback_Unknown)(OTF2_LocationRef locationID, OTF2_TimeStamp time, void *userData, OTF2_AttributeList *attributeList)

Callback for an unknown event record.

- typedef struct OTF2_GlobalEvtReaderCallbacks_struct OTF2_GlobalEvtReaderCallbacks

Opaque struct which holds all event record callbacks.

Functions

- void OTF2_GlobalEvtReaderCallbacks_Clear (OTF2_GlobalEvtReaderCallbacks *globalEvtReaderCallbacks)
Clears a struct for the global event callbacks.
- void OTF2_GlobalEvtReaderCallbacks_Delete (OTF2_GlobalEvtReaderCallbacks *globalEvtReaderCallbacks)
Deallocates a struct for the global event callbacks.
- OTF2_GlobalEvtReaderCallbacks * OTF2_GlobalEvtReaderCallbacks_New (void)
Allocates a new struct for the event callbacks.
- OTF2_ErrorCode OTF2_GlobalEvtReaderCallbacks_SetBufferFlushCallback (OTF2_GlobalEvtReaderCallbacks *globalEvtReaderCallbacks, OTF2_GlobalEvtReaderCallback_BufferFlush bufferFlushCallback)
Registers the callback for the BufferFlush event.
- OTF2_ErrorCode OTF2_GlobalEvtReaderCallbacks_SetEnterCallback (OTF2_GlobalEvtReaderCallbacks *globalEvtReaderCallbacks, OTF2_GlobalEvtReaderCallback_Enter enterCallback)
Registers the callback for the Enter event.
- OTF2_ErrorCode OTF2_GlobalEvtReaderCallbacks_SetLeaveCallback (OTF2_GlobalEvtReaderCallbacks *globalEvtReaderCallbacks, OTF2_GlobalEvtReaderCallback_Leave leaveCallback)
Registers the callback for the Leave event.

APPENDIX J. FILE DOCUMENTATION

- [OTF2_ErrorCode OTF2_GlobalEvtReaderCallbacks_SetMeasurementOnOffCallback](#)
([OTF2_GlobalEvtReaderCallbacks *globalEvtReaderCallbacks](#), [OTF2_GlobalEvtReaderCallback_-MeasurementOnOff](#) measurementOnOffCallback)
Registers the callback for the MeasurementOnOff event.
- [OTF2_ErrorCode OTF2_GlobalEvtReaderCallbacks_SetMetricCallback](#) ([OTF2_-GlobalEvtReaderCallbacks *globalEvtReaderCallbacks](#), [OTF2_GlobalEvtReaderCallback_-Metric](#) metricCallback)
Registers the callback for the Metric event.
- [OTF2_ErrorCode OTF2_GlobalEvtReaderCallbacks_SetMpiCollectiveBeginCallback](#)
([OTF2_GlobalEvtReaderCallbacks *globalEvtReaderCallbacks](#), [OTF2_GlobalEvtReaderCallback_-MpiCollectiveBegin](#) mpiCollectiveBeginCallback)
Registers the callback for the MpiCollectiveBegin event.
- [OTF2_ErrorCode OTF2_GlobalEvtReaderCallbacks_SetMpiCollectiveEndCallback](#)
([OTF2_GlobalEvtReaderCallbacks *globalEvtReaderCallbacks](#), [OTF2_GlobalEvtReaderCallback_-MpiCollectiveEnd](#) mpiCollectiveEndCallback)
Registers the callback for the MpiCollectiveEnd event.
- [OTF2_ErrorCode OTF2_GlobalEvtReaderCallbacks_SetMpiIrecvCallback](#) ([OTF2_-GlobalEvtReaderCallbacks *globalEvtReaderCallbacks](#), [OTF2_GlobalEvtReaderCallback_-MpiIrecv](#) mpiIrecvCallback)
Registers the callback for the MpiIrecv event.
- [OTF2_ErrorCode OTF2_GlobalEvtReaderCallbacks_SetMpiIrecvRequestCallback](#)
([OTF2_GlobalEvtReaderCallbacks *globalEvtReaderCallbacks](#), [OTF2_GlobalEvtReaderCallback_-MpiIrecvRequest](#) mpiIrecvRequestCallback)
Registers the callback for the MpiIrecvRequest event.
- [OTF2_ErrorCode OTF2_GlobalEvtReaderCallbacks_SetMpiIsendCallback](#)
([OTF2_GlobalEvtReaderCallbacks *globalEvtReaderCallbacks](#), [OTF2_GlobalEvtReaderCallback_-MpiIsend](#) mpiIsendCallback)
Registers the callback for the MpiIsend event.
- [OTF2_ErrorCode OTF2_GlobalEvtReaderCallbacks_SetMpiIsendCompleteCallback](#)
([OTF2_GlobalEvtReaderCallbacks *globalEvtReaderCallbacks](#), [OTF2_GlobalEvtReaderCallback_-MpiIsendComplete](#) mpiIsendCompleteCallback)
Registers the callback for the MpiIsendComplete event.
- [OTF2_ErrorCode OTF2_GlobalEvtReaderCallbacks_SetMpiRecvCallback](#) ([OTF2_-GlobalEvtReaderCallbacks *globalEvtReaderCallbacks](#), [OTF2_GlobalEvtReaderCallback_-MpiRecv](#) mpiRecvCallback)

J.19 OTF2_GlobalEvtReaderCallbacks.h File Reference

Registers the callback for the `MpiRecv` event.

- [OTF2_ErrorCode OTF2_GlobalEvtReaderCallbacks_SetMpiRequestCancelledCallback](#)
([OTF2_GlobalEvtReaderCallbacks](#) *globalEvtReaderCallbacks, [OTF2_GlobalEvtReaderCallback_-MpiRequestCancelled](#) mpiRequestCancelledCallback)

Registers the callback for the `MpiRequestCancelled` event.

- [OTF2_ErrorCode OTF2_GlobalEvtReaderCallbacks_SetMpiRequestTestCallback](#)
([OTF2_GlobalEvtReaderCallbacks](#) *globalEvtReaderCallbacks, [OTF2_GlobalEvtReaderCallback_-MpiRequestTest](#) mpiRequestTestCallback)

Registers the callback for the `MpiRequestTest` event.

- [OTF2_ErrorCode OTF2_GlobalEvtReaderCallbacks_SetMpiSendCallback](#) ([OTF2_GlobalEvtReaderCallbacks](#) *globalEvtReaderCallbacks, [OTF2_GlobalEvtReaderCallback_-MpiSend](#) mpiSendCallback)

Registers the callback for the `MpiSend` event.

- [OTF2_ErrorCode OTF2_GlobalEvtReaderCallbacks_SetOmpAcquireLockCallback](#)
([OTF2_GlobalEvtReaderCallbacks](#) *globalEvtReaderCallbacks, [OTF2_GlobalEvtReaderCallback_-OmpAcquireLock](#) ompAcquireLockCallback)

Registers the callback for the `OmpAcquireLock` event.

- [OTF2_ErrorCode OTF2_GlobalEvtReaderCallbacks_SetOmpForkCallback](#)
([OTF2_GlobalEvtReaderCallbacks](#) *globalEvtReaderCallbacks, [OTF2_GlobalEvtReaderCallback_-OmpFork](#) ompForkCallback)

Registers the callback for the `OmpFork` event.

- [OTF2_ErrorCode OTF2_GlobalEvtReaderCallbacks_SetOmpJoinCallback](#) ([OTF2_GlobalEvtReaderCallbacks](#) *globalEvtReaderCallbacks, [OTF2_GlobalEvtReaderCallback_-OmpJoin](#) ompJoinCallback)

Registers the callback for the `OmpJoin` event.

- [OTF2_ErrorCode OTF2_GlobalEvtReaderCallbacks_SetOmpReleaseLockCallback](#)
([OTF2_GlobalEvtReaderCallbacks](#) *globalEvtReaderCallbacks, [OTF2_GlobalEvtReaderCallback_-OmpReleaseLock](#) ompReleaseLockCallback)

Registers the callback for the `OmpReleaseLock` event.

- [OTF2_ErrorCode OTF2_GlobalEvtReaderCallbacks_SetOmpTaskCompleteCallback](#)
([OTF2_GlobalEvtReaderCallbacks](#) *globalEvtReaderCallbacks, [OTF2_GlobalEvtReaderCallback_-OmpTaskComplete](#) ompTaskCompleteCallback)

Registers the callback for the `OmpTaskComplete` event.

APPENDIX J. FILE DOCUMENTATION

- [OTF2_ErrorCode OTF2_GlobalEvtReaderCallbacks_SetOmpTaskCreateCallback](#)
([OTF2_GlobalEvtReaderCallbacks](#) *globalEvtReaderCallbacks, [OTF2_GlobalEvtReaderCallback_-OmpTaskCreate](#) ompTaskCreateCallback)
Registers the callback for the OmpTaskCreate event.
- [OTF2_ErrorCode OTF2_GlobalEvtReaderCallbacks_SetOmpTaskSwitchCallback](#)
([OTF2_GlobalEvtReaderCallbacks](#) *globalEvtReaderCallbacks, [OTF2_GlobalEvtReaderCallback_-OmpTaskSwitch](#) ompTaskSwitchCallback)
Registers the callback for the OmpTaskSwitch event.
- [OTF2_ErrorCode OTF2_GlobalEvtReaderCallbacks_SetParameterIntCallback](#)
([OTF2_GlobalEvtReaderCallbacks](#) *globalEvtReaderCallbacks, [OTF2_GlobalEvtReaderCallback_-ParameterInt](#) parameterIntCallback)
Registers the callback for the ParameterInt event.
- [OTF2_ErrorCode OTF2_GlobalEvtReaderCallbacks_SetParameterStringCallback](#)
([OTF2_GlobalEvtReaderCallbacks](#) *globalEvtReaderCallbacks, [OTF2_GlobalEvtReaderCallback_-ParameterString](#) parameterStringCallback)
Registers the callback for the ParameterString event.
- [OTF2_ErrorCode OTF2_GlobalEvtReaderCallbacks_SetParameterUnsignedIntCallback](#)
([OTF2_GlobalEvtReaderCallbacks](#) *globalEvtReaderCallbacks, [OTF2_GlobalEvtReaderCallback_-ParameterUnsignedInt](#) parameterUnsignedIntCallback)
Registers the callback for the ParameterUnsignedInt event.
- [OTF2_ErrorCode OTF2_GlobalEvtReaderCallbacks_SetRmaAcquireLockCallback](#)
([OTF2_GlobalEvtReaderCallbacks](#) *globalEvtReaderCallbacks, [OTF2_GlobalEvtReaderCallback_-RmaAcquireLock](#) rmaAcquireLockCallback)
Registers the callback for the RmaAcquireLock event.
- [OTF2_ErrorCode OTF2_GlobalEvtReaderCallbacks_SetRmaAtomicCallback](#)
([OTF2_GlobalEvtReaderCallbacks](#) *globalEvtReaderCallbacks, [OTF2_GlobalEvtReaderCallback_-RmaAtomic](#) rmaAtomicCallback)
Registers the callback for the RmaAtomic event.
- [OTF2_ErrorCode OTF2_GlobalEvtReaderCallbacks_SetRmaCollectiveBeginCallback](#)
([OTF2_GlobalEvtReaderCallbacks](#) *globalEvtReaderCallbacks, [OTF2_GlobalEvtReaderCallback_-RmaCollectiveBegin](#) rmaCollectiveBeginCallback)
Registers the callback for the RmaCollectiveBegin event.
- [OTF2_ErrorCode OTF2_GlobalEvtReaderCallbacks_SetRmaCollectiveEndCallback](#)
([OTF2_GlobalEvtReaderCallbacks](#) *globalEvtReaderCallbacks, [OTF2_GlobalEvtReaderCallback_-RmaCollectiveEnd](#) rmaCollectiveEndCallback)

J.19 OTF2_GlobalEvtReaderCallbacks.h File Reference

Registers the callback for the RmaCollectiveEnd event.

- [OTF2_ErrorCode OTF2_GlobalEvtReaderCallbacks_SetRmaGetCallback](#) ([OTF2_GlobalEvtReaderCallbacks *globalEvtReaderCallbacks](#), [OTF2_GlobalEvtReaderCallback_RmaGet](#) [rmaGetCallback](#))

Registers the callback for the RmaGet event.

- [OTF2_ErrorCode OTF2_GlobalEvtReaderCallbacks_SetRmaGroupSyncCallback](#) ([OTF2_GlobalEvtReaderCallbacks *globalEvtReaderCallbacks](#), [OTF2_GlobalEvtReaderCallback_RmaGroupSync](#) [rmaGroupSyncCallback](#))

Registers the callback for the RmaGroupSync event.

- [OTF2_ErrorCode OTF2_GlobalEvtReaderCallbacks_SetRmaOpCompleteBlockingCallback](#) ([OTF2_GlobalEvtReaderCallbacks *globalEvtReaderCallbacks](#), [OTF2_GlobalEvtReaderCallback_RmaOpCompleteBlocking](#) [rmaOpCompleteBlockingCallback](#))

Registers the callback for the RmaOpCompleteBlocking event.

- [OTF2_ErrorCode OTF2_GlobalEvtReaderCallbacks_SetRmaOpCompleteNonBlockingCallback](#) ([OTF2_GlobalEvtReaderCallbacks *globalEvtReaderCallbacks](#), [OTF2_GlobalEvtReaderCallback_RmaOpCompleteNonBlocking](#) [rmaOpCompleteNonBlockingCallback](#))

Registers the callback for the RmaOpCompleteNonBlocking event.

- [OTF2_ErrorCode OTF2_GlobalEvtReaderCallbacks_SetRmaOpCompleteRemoteCallback](#) ([OTF2_GlobalEvtReaderCallbacks *globalEvtReaderCallbacks](#), [OTF2_GlobalEvtReaderCallback_RmaOpCompleteRemote](#) [rmaOpCompleteRemoteCallback](#))

Registers the callback for the RmaOpCompleteRemote event.

- [OTF2_ErrorCode OTF2_GlobalEvtReaderCallbacks_SetRmaOpTestCallback](#) ([OTF2_GlobalEvtReaderCallbacks *globalEvtReaderCallbacks](#), [OTF2_GlobalEvtReaderCallback_RmaOpTest](#) [rmaOpTestCallback](#))

Registers the callback for the RmaOpTest event.

- [OTF2_ErrorCode OTF2_GlobalEvtReaderCallbacks_SetRmaPutCallback](#) ([OTF2_GlobalEvtReaderCallbacks *globalEvtReaderCallbacks](#), [OTF2_GlobalEvtReaderCallback_RmaPut](#) [rmaPutCallback](#))

Registers the callback for the RmaPut event.

- [OTF2_ErrorCode OTF2_GlobalEvtReaderCallbacks_SetRmaReleaseLockCallback](#) ([OTF2_GlobalEvtReaderCallbacks *globalEvtReaderCallbacks](#), [OTF2_GlobalEvtReaderCallback_RmaReleaseLock](#) [rmaReleaseLockCallback](#))

Registers the callback for the RmaReleaseLock event.

APPENDIX J. FILE DOCUMENTATION

- [OTF2_ErrorCode OTF2_GlobalEvtReaderCallbacks_SetRmaRequestLockCallback](#)
([OTF2_GlobalEvtReaderCallbacks](#) *globalEvtReaderCallbacks, [OTF2_GlobalEvtReaderCallback_-RmaRequestLock](#) rmaRequestLockCallback)
Registers the callback for the RmaRequestLock event.
- [OTF2_ErrorCode OTF2_GlobalEvtReaderCallbacks_SetRmaSyncCallback](#)
([OTF2_GlobalEvtReaderCallbacks](#) *globalEvtReaderCallbacks, [OTF2_GlobalEvtReaderCallback_-RmaSync](#) rmaSyncCallback)
Registers the callback for the RmaSync event.
- [OTF2_ErrorCode OTF2_GlobalEvtReaderCallbacks_SetRmaTryLockCallback](#)
([OTF2_GlobalEvtReaderCallbacks](#) *globalEvtReaderCallbacks, [OTF2_GlobalEvtReaderCallback_-RmaTryLock](#) rmaTryLockCallback)
Registers the callback for the RmaTryLock event.
- [OTF2_ErrorCode OTF2_GlobalEvtReaderCallbacks_SetRmaWaitChangeCallback](#)
([OTF2_GlobalEvtReaderCallbacks](#) *globalEvtReaderCallbacks, [OTF2_GlobalEvtReaderCallback_-RmaWaitChange](#) rmaWaitChangeCallback)
Registers the callback for the RmaWaitChange event.
- [OTF2_ErrorCode OTF2_GlobalEvtReaderCallbacks_SetRmaWinCreateCallback](#)
([OTF2_GlobalEvtReaderCallbacks](#) *globalEvtReaderCallbacks, [OTF2_GlobalEvtReaderCallback_-RmaWinCreate](#) rmaWinCreateCallback)
Registers the callback for the RmaWinCreate event.
- [OTF2_ErrorCode OTF2_GlobalEvtReaderCallbacks_SetRmaWinDestroyCallback](#)
([OTF2_GlobalEvtReaderCallbacks](#) *globalEvtReaderCallbacks, [OTF2_GlobalEvtReaderCallback_-RmaWinDestroy](#) rmaWinDestroyCallback)
Registers the callback for the RmaWinDestroy event.
- [OTF2_ErrorCode OTF2_GlobalEvtReaderCallbacks_SetThreadAcquireLockCallback](#)
([OTF2_GlobalEvtReaderCallbacks](#) *globalEvtReaderCallbacks, [OTF2_GlobalEvtReaderCallback_-ThreadAcquireLock](#) threadAcquireLockCallback)
Registers the callback for the ThreadAcquireLock event.
- [OTF2_ErrorCode OTF2_GlobalEvtReaderCallbacks_SetThreadForkCallback](#)
([OTF2_GlobalEvtReaderCallbacks](#) *globalEvtReaderCallbacks, [OTF2_GlobalEvtReaderCallback_-ThreadFork](#) threadForkCallback)
Registers the callback for the ThreadFork event.
- [OTF2_ErrorCode OTF2_GlobalEvtReaderCallbacks_SetThreadJoinCallback](#)
([OTF2_GlobalEvtReaderCallbacks](#) *globalEvtReaderCallbacks, [OTF2_GlobalEvtReaderCallback_-ThreadJoin](#) threadJoinCallback)

J.19 OTF2_GlobalEvtReaderCallbacks.h File Reference

Registers the callback for the ThreadJoin event.

- [OTF2_StatusCode OTF2_GlobalEvtReaderCallbacks_SetThreadReleaseLockCallback](#)
([OTF2_GlobalEvtReaderCallbacks *globalEvtReaderCallbacks](#), [OTF2_GlobalEvtReaderCallback_ThreadReleaseLock](#) threadReleaseLockCallback)

Registers the callback for the ThreadReleaseLock event.

- [OTF2_StatusCode OTF2_GlobalEvtReaderCallbacks_SetThreadTaskCompleteCallback](#)
([OTF2_GlobalEvtReaderCallbacks *globalEvtReaderCallbacks](#), [OTF2_GlobalEvtReaderCallback_ThreadTaskComplete](#) threadTaskCompleteCallback)

Registers the callback for the ThreadTaskComplete event.

- [OTF2_StatusCode OTF2_GlobalEvtReaderCallbacks_SetThreadTaskCreateCallback](#)
([OTF2_GlobalEvtReaderCallbacks *globalEvtReaderCallbacks](#), [OTF2_GlobalEvtReaderCallback_ThreadTaskCreate](#) threadTaskCreateCallback)

Registers the callback for the ThreadTaskCreate event.

- [OTF2_StatusCode OTF2_GlobalEvtReaderCallbacks_SetThreadTaskSwitchCallback](#)
([OTF2_GlobalEvtReaderCallbacks *globalEvtReaderCallbacks](#), [OTF2_GlobalEvtReaderCallback_ThreadTaskSwitch](#) threadTaskSwitchCallback)

Registers the callback for the ThreadTaskSwitch event.

- [OTF2_StatusCode OTF2_GlobalEvtReaderCallbacks_SetThreadTeamBeginCallback](#)
([OTF2_GlobalEvtReaderCallbacks *globalEvtReaderCallbacks](#), [OTF2_GlobalEvtReaderCallback_ThreadTeamBegin](#) threadTeamBeginCallback)

Registers the callback for the ThreadTeamBegin event.

- [OTF2_StatusCode OTF2_GlobalEvtReaderCallbacks_SetThreadTeamEndCallback](#)
([OTF2_GlobalEvtReaderCallbacks *globalEvtReaderCallbacks](#), [OTF2_GlobalEvtReaderCallback_ThreadTeamEnd](#) threadTeamEndCallback)

Registers the callback for the ThreadTeamEnd event.

- [OTF2_StatusCode OTF2_GlobalEvtReaderCallbacks_SetUnknownCallback](#)
([OTF2_GlobalEvtReaderCallbacks *globalEvtReaderCallbacks](#), [OTF2_GlobalEvtReaderCallback_Unknown](#) unknownCallback)

Registers the callback for unknown events.

J.19.1 Detailed Description

This defines the callbacks for the global event reader.

Source Template:

templates/OTF2_GlobalEvtReaderCallbacks.tmpl.h

Maintainer:

Dominic Eschweiler <d.eschweiler@fz-juelich.de>

Authors

Dominic Eschweiler <d.eschweiler@fz-juelich.de>, Michael Wagner <michael.wagner@zih.tu-dresden.de>

J.19.2 Typedef Documentation

J.19.2.1 `typedef OTF2_CallbackCode(* OTF2_GlobalEvtReaderCallback_ - BufferFlush)(OTF2_LocationRef locationID, OTF2_TimeStamp time, void *userData, OTF2_AttributeList *attributeList, OTF2_TimeStamp stopTime)`

Callback for the BufferFlush event record.

This event signals that the internal buffer was flushed at the given time.

Parameters

| | |
|----------------------|---|
| <i>locationID</i> | The location where this event happened. |
| <i>time</i> | The time when this event happened. |
| <i>userData</i> | User data as set by OTF2_Reader_RegisterGlobalEvtCallbacks or OTF2_GlobalEvtReader_SetCallbacks . |
| <i>attributeList</i> | Additional attributes for this event. |
| <i>stopTime</i> | The time the buffer flush finished. |

Since

Version 1.0

Returns

[OTF2_CALLBACK_SUCCESS](#) or [OTF2_CALLBACK_INTERRUPT](#).

J.19.2.2 `typedef OTF2_CallbackCode(* OTF2_GlobalEvtReaderCallback_ - Enter)(OTF2_LocationRef locationID, OTF2_TimeStamp time, void *userData, OTF2_AttributeList *attributeList, OTF2_RegionRef region)`

Callback for the Enter event record.

J.19 OTF2_GlobalEvtReaderCallbacks.h File Reference

An enter record indicates that the program enters a code region.

Parameters

| | |
|----------------------|--|
| <i>locationID</i> | The location where this event happened. |
| <i>time</i> | The time when this event happened. |
| <i>userData</i> | User data as set by OTF2_Reader_RegisterGlobalEvtCallbacks or OTF2_GlobalEvtReader_SetCallbacks . |
| <i>attributeList</i> | Additional attributes for this event. |
| <i>region</i> | Needs to be defined in a definition record References a Region definition and will be mapped to the global definition if a mapping table of type OTF2_MAPPING_REGION is available. |

Since

Version 1.0

Returns

[OTF2_CALLBACK_SUCCESS](#) or [OTF2_CALLBACK_INTERRUPT](#).

J.19.2.3 `typedef OTF2_CallbackCode(* OTF2_GlobalEvtReaderCallback_Leave)(OTF2_LocationRef locationID, OTF2_TimeStamp time, void *userData, OTF2_AttributeList *attributeList, OTF2_RegionRef region)`

Callback for the Leave event record.

A leave record indicates that the program leaves a code region.

Parameters

| | |
|----------------------|--|
| <i>locationID</i> | The location where this event happened. |
| <i>time</i> | The time when this event happened. |
| <i>userData</i> | User data as set by OTF2_Reader_RegisterGlobalEvtCallbacks or OTF2_GlobalEvtReader_SetCallbacks . |
| <i>attributeList</i> | Additional attributes for this event. |
| <i>region</i> | Needs to be defined in a definition record References a Region definition and will be mapped to the global definition if a mapping table of type OTF2_MAPPING_REGION is available. |

Since

Version 1.0

APPENDIX J. FILE DOCUMENTATION

Returns

[*OTF2_CALLBACK_SUCCESS*](#) or [*OTF2_CALLBACK_INTERRUPT*](#).

J.19.2.4 `typedef OTF2_CallbackCode(* OTF2_GlobalEvtReaderCallback_ -
MeasurementOnOff)(OTF2_LocationRef locationID,
OTF2_TimeStamp time, void *userData, OTF2_AttributeList
*attributeList, OTF2_MeasurementMode measurementMode)`

Callback for the MeasurementOnOff event record.

This event signals where the measurement system turned measurement on or off.

Parameters

| | |
|------------------------|---|
| <i>locationID</i> | The location where this event happened. |
| <i>time</i> | The time when this event happened. |
| <i>userData</i> | User data as set by <i>OTF2_Reader_RegisterGlobalEvtCallbacks</i> or <i>OTF2_GlobalEvtReader_SetCallbacks</i> . |
| <i>attributeList</i> | Additional attributes for this event. |
| <i>measurementMode</i> | Is the measurement turned on (<i>OTF2_MEASUREMENT_ON</i>) or off (<i>OTF2_MEASUREMENT_OFF</i>)? |

Since

Version 1.0

Returns

[*OTF2_CALLBACK_SUCCESS*](#) or [*OTF2_CALLBACK_INTERRUPT*](#).

J.19.2.5 `typedef OTF2_CallbackCode(* OTF2_GlobalEvtReaderCallback_ -
Metric)(OTF2_LocationRef locationID, OTF2_TimeStamp time, void
*userData, OTF2_AttributeList *attributeList, OTF2_MetricRef metric,
uint8_t numberOfMetrics, const OTF2_Type *typeIDs, const OTF2_MetricValue
*metricValues)`

Callback for the Metric event record.

A metric event is always stored at the location that recorded the metric. A metric event can reference a metric class or metric instance. Therefore, metric classes and instances share same ID space. Synchronous metrics are always located right before the according enter and leave event.

J.19 OTF2_GlobalEvtReaderCallbacks.h File Reference

Parameters

| | |
|------------------------|--|
| <i>locationID</i> | The location where this event happened. |
| <i>time</i> | The time when this event happened. |
| <i>userData</i> | User data as set by OTF2_Reader_RegisterGlobalEvtCallbacks or OTF2_GlobalEvtReader_SetCallbacks . |
| <i>attributeList</i> | Additional attributes for this event. |
| <i>metric</i> | Could be a metric class or a metric instance. References a MetricClass , or a MetricInstance definition and will be mapped to the global definition if a mapping table of type OTF2_MAPPING_METRIC is available. |
| <i>numberOfMetrics</i> | Number of metrics with in the set. |
| <i>typeIDs</i> | List of metric types. |
| <i>metricValues</i> | List of metric values. |

Since

Version 1.0

Returns

[OTF2_CALLBACK_SUCCESS](#) or [OTF2_CALLBACK_INTERRUPT](#).

J.19.2.6 `typedef OTF2_CallbackCode(* OTF2_GlobalEvtReaderCallback -
MpiCollectiveBegin)(OTF2_LocationRef locationID, OTF2_TimeStamp
time, void *userData, OTF2_AttributeList *attributeList)`

Callback for the MpiCollectiveBegin event record.

A MpiCollectiveBegin record marks the begin of an MPI collective operation (MPI_GATHER, MPI_SCATTER etc.).

Parameters

| | |
|----------------------|---|
| <i>locationID</i> | The location where this event happened. |
| <i>time</i> | The time when this event happened. |
| <i>userData</i> | User data as set by OTF2_Reader_RegisterGlobalEvtCallbacks or OTF2_GlobalEvtReader_SetCallbacks . |
| <i>attributeList</i> | Additional attributes for this event. |

Since

Version 1.0

Returns

OTF2_CALLBACK_SUCCESS or *OTF2_CALLBACK_INTERRUPT*.

J.19.2.7 typedef OTF2_CallbackCode(* OTF2_GlobalEvtReaderCallback_
-
MpiCollectiveEnd)(OTF2_LocationRef locationID, OTF2_TimeStamp
time, void *userData, OTF2_AttributeList *attributelist,
OTF2_CollectiveOp collectiveOp, OTF2_CommRef communicator, uint32_t
root, uint64_t sizeSent, uint64_t sizeReceived)

Callback for the MpiCollectiveEnd event record.

A MpiCollectiveEnd record marks the end of an MPI collective operation (MPI_GATHER, MPI_SCATTER etc.). It keeps the necessary information for this event: type of collective operation, communicator, the root of this collective operation. You can optionally add further information like sent and received bytes.

Parameters

| | |
|----------------------|--|
| <i>locationID</i> | The location where this event happened. |
| <i>time</i> | The time when this event happened. |
| <i>userData</i> | User data as set by OTF2_Reader_RegisterGlobalEvtCallbacks or OTF2_GlobalEvtReader_SetCallbacks . |
| <i>attributeList</i> | Additional attributes for this event. |
| <i>collectiveOp</i> | Determines which collective operation it is. |
| <i>communicator</i> | Communicator References a Comm definition and will be mapped to the global definition if a mapping table of type OTF2_MAPPING_COMM is available. |
| <i>root</i> | MPI rank of root in <i>communicator</i> . |
| <i>sizeSent</i> | Size of the sent message. |
| <i>sizeReceived</i> | Size of the received message. |

Since

Version 1.0

Returns

OTF2_CALLBACK_SUCCESS or *OTF2_CALLBACK_INTERRUPT*.

J.19 OTF2_GlobalEvtReaderCallbacks.h File Reference

J.19.2.8 `typedef OTF2_CallbackCode(* OTF2_GlobalEvtReaderCallback_
MpiIrecv)(OTF2_LocationRef locationID, OTF2_TimeStamp time,
void *userData, OTF2_AttributeList *attributeList, uint32_t sender,
OTF2_CommRef communicator, uint32_t msgTag, uint64_t msgLength, uint64_t
requestID)`

Callback for the MpiIrecv event record.

A MpiIrecv record indicates that a MPI message was received (MPI_IRECV). It keeps the necessary information for this event: sender of the message, communicator, and the message tag. You can optionally add further information like the message length (size of the receive buffer).

Parameters

| | |
|----------------------|--|
| <i>locationID</i> | The location where this event happened. |
| <i>time</i> | The time when this event happened. |
| <i>userData</i> | User data as set by OTF2_Reader_RegisterGlobalEvtCallbacks or OTF2_GlobalEvtReader_SetCallbacks . |
| <i>attributeList</i> | Additional attributes for this event. |
| <i>sender</i> | MPI rank of sender in <i>communicator</i> . |
| <i>communicator</i> | Communicator ID. References a Comm definition and will be mapped to the global definition if a mapping table of type OTF2_MAPPING_COMM is available. |
| <i>msgTag</i> | Message tag |
| <i>msgLength</i> | Message length |
| <i>requestID</i> | ID of the related request |

Since

Version 1.0

Returns

[OTF2_CALLBACK_SUCCESS](#) or [OTF2_CALLBACK_INTERRUPT](#).

J.19.2.9 `typedef OTF2_CallbackCode(* OTF2_GlobalEvtReaderCallback_
MpiIrecvRequest)(OTF2_LocationRef locationID, OTF2_TimeStamp
time, void *userData, OTF2_AttributeList *attributeList, uint64_t requestID)`

Callback for the MpiIrecvRequest event record.

Signals the request of an receive, which can be completed later.

Parameters

APPENDIX J. FILE DOCUMENTATION

| | |
|----------------------|---|
| <i>locationID</i> | The location where this event happened. |
| <i>time</i> | The time when this event happened. |
| <i>userData</i> | User data as set by OTF2_Reader_RegisterGlobalEvtCallbacks or OTF2_GlobalEvtReader_SetCallbacks . |
| <i>attributeList</i> | Additional attributes for this event. |
| <i>requestID</i> | ID of the requested receive |

Since

Version 1.0

Returns

[OTF2_CALLBACK_SUCCESS](#) or [OTF2_CALLBACK_INTERRUPT](#).

```
J.19.2.10 typedef OTF2_CallbackCode( * OTF2_GlobalEvtReaderCallback_  
MpiIsend)(OTF2_LocationRef locationID, OTF2_TimeStamp time,  
void *userData, OTF2_AttributeList *attributeList, uint32_t receiver,  
OTF2_CommRef communicator, uint32_t msgTag, uint64_t msgLength,  
uint64_t requestID)
```

Callback for the MpiIsend event record.

A MpiIsend record indicates that a MPI message send process was initiated (MPI_ISEND). It keeps the necessary information for this event: receiver of the message, communicator, and the message tag. You can optionally add further information like the message length (size of the send buffer).

Parameters

| | |
|---------------------------|--|
| <i>locationID</i> | The location where this event happened. |
| <i>time</i> | The time when this event happened. |
| <i>userData</i> | User data as set by OTF2_Reader_RegisterGlobalEvtCallbacks or OTF2_GlobalEvtReader_SetCallbacks . |
| <i>attributeList</i> | Additional attributes for this event. |
| <i>receiver</i> | MPI rank of receiver in <i>communicator</i> . |
| <i>communi- cator</i> | Communicator ID. References a Comm definition and will be mapped to the global definition if a mapping table of type OTF2_MAPPING_- COMM is available. |
| <i>msgTag</i> | Message tag |
| <i>msgLength</i> | Message length |
| <i>requestID</i> | ID of the related request |

J.19 OTF2_GlobalEvtReaderCallbacks.h File Reference

Since

Version 1.0

Returns

[OTF2_CALLBACK_SUCCESS](#) or [OTF2_CALLBACK_INTERRUPT](#).

J.19.2.11 `typedef OTF2_CallbackCode(* OTF2_GlobalEvtReaderCallback_
MpiIsendComplete)(OTF2_LocationRef locationID,
OTF2_TimeStamp time, void *userData, OTF2_AttributeList
*attributeList, uint64_t requestID)`

Callback for the MpiIsendComplete event record.

Signals the completion of non-blocking send request.

Parameters

| | |
|----------------------|---|
| <i>locationID</i> | The location where this event happened. |
| <i>time</i> | The time when this event happened. |
| <i>userData</i> | User data as set by OTF2_Reader_RegisterGlobalEvtCallbacks or OTF2_GlobalEvtReader_SetCallbacks . |
| <i>attributeList</i> | Additional attributes for this event. |
| <i>requestID</i> | ID of the related request |

Since

Version 1.0

Returns

[OTF2_CALLBACK_SUCCESS](#) or [OTF2_CALLBACK_INTERRUPT](#).

J.19.2.12 `typedef OTF2_CallbackCode(* OTF2_GlobalEvtReaderCallback_
MpiRecv)(OTF2_LocationRef locationID, OTF2_TimeStamp time,
void *userData, OTF2_AttributeList *attributeList, uint32_t sender,
OTF2_CommRef communicator, uint32_t msgTag, uint64_t msgLength)`

Callback for the MpiRecv event record.

A MpiRecv record indicates that a MPI message was received (MPI_RECV). It keeps the necessary information for this event: sender of the message, communicator, and the message tag. You can optionally add further information like the message length (size of the receive buffer).

APPENDIX J. FILE DOCUMENTATION

Parameters

| | |
|----------------------|---|
| <i>locationID</i> | The location where this event happened. |
| <i>time</i> | The time when this event happened. |
| <i>userData</i> | User data as set by OTF2_Reader_RegisterGlobalEvtCallbacks or OTF2_GlobalEvtReader_SetCallbacks . |
| <i>attributeList</i> | Additional attributes for this event. |
| <i>sender</i> | MPI rank of sender in <i>communicator</i> . |
| <i>communicator</i> | Communicator ID. References a Comm definition and will be mapped to the global definition if a mapping table of type OTF2_MAPPING_-COMM is available. |
| <i>msgTag</i> | Message tag |
| <i>msgLength</i> | Message length |

Since

Version 1.0

Returns

[OTF2_CALLBACK_SUCCESS](#) or [OTF2_CALLBACK_INTERRUPT](#).

```
J.19.2.13 typedef OTF2_CallbackCode( * OTF2_GlobalEvtReaderCallback_  
MpiRequestCancelled)(OTF2_LocationRef locationID,  
OTF2_TimeStamp time, void *userData, OTF2_AttributeList  
*attributeList, uint64_t requestID)
```

Callback for the MpiRequestCancelled event record.

This events appears if the program canceled a request.

Parameters

| | |
|----------------------|---|
| <i>locationID</i> | The location where this event happened. |
| <i>time</i> | The time when this event happened. |
| <i>userData</i> | User data as set by OTF2_Reader_RegisterGlobalEvtCallbacks or OTF2_GlobalEvtReader_SetCallbacks . |
| <i>attributeList</i> | Additional attributes for this event. |
| <i>requestID</i> | ID of the related request |

Since

Version 1.0

J.19 OTF2_GlobalEvtReaderCallbacks.h File Reference

Returns

[OTF2_CALLBACK_SUCCESS](#) or [OTF2_CALLBACK_INTERRUPT](#).

J.19.2.14 `typedef OTF2_CallbackCode(* OTF2_GlobalEvtReaderCallback_-
MpiRequestTest)(OTF2_LocationRef locationID, OTF2_TimeStamp
time, void *userData, OTF2_AttributeList *attributeList, uint64_t requestID)`

Callback for the MpiRequestTest event record.

This events appears if the program tests if a request has already completed but the test failed.

Parameters

| | |
|----------------------|---|
| <i>locationID</i> | The location where this event happened. |
| <i>time</i> | The time when this event happened. |
| <i>userData</i> | User data as set by OTF2_Reader_RegisterGlobalEvtCallbacks or OTF2_GlobalEvtReader_SetCallbacks . |
| <i>attributeList</i> | Additional attributes for this event. |
| <i>requestID</i> | ID of the related request |

Since

Version 1.0

Returns

[OTF2_CALLBACK_SUCCESS](#) or [OTF2_CALLBACK_INTERRUPT](#).

J.19.2.15 `typedef OTF2_CallbackCode(* OTF2_GlobalEvtReaderCallback_-
MpiSend)(OTF2_LocationRef locationID, OTF2_TimeStamp time,
void *userData, OTF2_AttributeList *attributeList, uint32_t receiver,
OTF2_CommRef communicator, uint32_t msgTag, uint64_t msgLength)`

Callback for the MpiSend event record.

A MpiSend record indicates that a MPI message send process was initiated (MPI_SEND). It keeps the necessary information for this event: receiver of the message, communicator, and the message tag. You can optionally add further information like the message length (size of the send buffer).

Parameters

| | |
|-------------------|---|
| <i>locationID</i> | The location where this event happened. |
|-------------------|---|

APPENDIX J. FILE DOCUMENTATION

| | |
|----------------------|---|
| <i>time</i> | The time when this event happened. |
| <i>userData</i> | User data as set by OTF2_Reader_RegisterGlobalEvtCallbacks or OTF2_GlobalEvtReader_SetCallbacks . |
| <i>attributeList</i> | Additional attributes for this event. |
| <i>receiver</i> | MPI rank of receiver in <i>communicator</i> . |
| <i>communicator</i> | Communicator ID. References a Comm definition and will be mapped to the global definition if a mapping table of type OTF2_MAPPING_-COMM is available. |
| <i>msgTag</i> | Message tag |
| <i>msgLength</i> | Message length |

Since

Version 1.0

Returns

[OTF2_CALLBACK_SUCCESS](#) or [OTF2_CALLBACK_INTERRUPT](#).

J.19.2.16 `typedef OTF2_CallbackCode(* OTF2_GlobalEvtReaderCallback_OmpAcquireLock)(OTF2_LocationRef locationID, OTF2_TimeStamp time, void *userData, OTF2_AttributeList *attributeList, uint32_t lockID, uint32_t acquisitionOrder)`

Callback for the OmpAcquireLock event record.

An OmpAcquireLock record marks that a thread acquires an OpenMP lock.

This event record is superseded by the [ThreadAcquireLock](#) event record and should not be used when the [ThreadAcquireLock](#) event record is in use record.

Parameters

| | |
|-------------------------|---|
| <i>locationID</i> | The location where this event happened. |
| <i>time</i> | The time when this event happened. |
| <i>userData</i> | User data as set by OTF2_Reader_RegisterGlobalEvtCallbacks or OTF2_GlobalEvtReader_SetCallbacks . |
| <i>attributeList</i> | Additional attributes for this event. |
| <i>lockID</i> | ID of the lock. |
| <i>acquisitionOrder</i> | A monotonically increasing number to determine the order of lock acquisitions (with unsynchronized clocks this is otherwise not possible). Corresponding acquire-release events have same number. |

J.19 OTF2_GlobalEvtReaderCallbacks.h File Reference

Since

Version 1.0

Returns

[OTF2_CALLBACK_SUCCESS](#) or [OTF2_CALLBACK_INTERRUPT](#).

J.19.2.17 `typedef OTF2_CallbackCode(* OTF2_GlobalEvtReaderCallback_
OmpFork)(OTF2_LocationRef locationID, OTF2_TimeStamp
time, void *userData, OTF2_AttributeList *attributeList, uint32_t
numberOfRequestedThreads)`

Callback for the OmpFork event record.

An OmpFork record marks that an OpenMP Thread forks a thread team.

This event record is superseded by the [ThreadFork](#) event record and should not be used when the [ThreadFork](#) event record is in use.

Parameters

| | |
|---|---|
| <i>locationID</i> | The location where this event happened. |
| <i>time</i> | The time when this event happened. |
| <i>userData</i> | User data as set by OTF2_Reader_RegisterGlobalEvtCallbacks or OTF2_GlobalEvtReader_SetCallbacks . |
| <i>attributeList</i> | Additional attributes for this event. |
| <i>num- berOfRe- quest- edThreads</i> | Requested size of the team. |

Since

Version 1.0

Returns

[OTF2_CALLBACK_SUCCESS](#) or [OTF2_CALLBACK_INTERRUPT](#).

J.19.2.18 `typedef OTF2_CallbackCode(* OTF2_GlobalEvtReaderCallback_
OmpJoin)(OTF2_LocationRef locationID, OTF2_TimeStamp time, void
*userData, OTF2_AttributeList *attributeList)`

Callback for the OmpJoin event record.

APPENDIX J. FILE DOCUMENTATION

An `OmpJoin` record marks that a team of threads is joint and only the master thread continues execution.

This event record is superseded by the [ThreadJoin](#) event record and should not be used when the [ThreadJoin](#) event record is in use.

Parameters

| | |
|----------------------|---|
| <i>locationID</i> | The location where this event happened. |
| <i>time</i> | The time when this event happened. |
| <i>userData</i> | User data as set by OTF2_Reader_RegisterGlobalEvtCallbacks or OTF2_GlobalEvtReader_SetCallbacks . |
| <i>attributeList</i> | Additional attributes for this event. |

Since

Version 1.0

Returns

[OTF2_CALLBACK_SUCCESS](#) or [OTF2_CALLBACK_INTERRUPT](#).

J.19.2.19 `typedef OTF2_CallbackCode(* OTF2_GlobalEvtReaderCallback_ - OmpReleaseLock)(OTF2_LocationRef locationID, OTF2_TimeStamp time, void *userData, OTF2_AttributeList *attributeList, uint32_t lockID, uint32_t acquisitionOrder)`

Callback for the `OmpReleaseLock` event record.

An `OmpReleaseLock` record marks that a thread releases an OpenMP lock.

This event record is superseded by the [ThreadReleaseLock](#) event record and should not be used when the [ThreadReleaseLock](#) event record is in use.

Parameters

| | |
|-------------------------|---|
| <i>locationID</i> | The location where this event happened. |
| <i>time</i> | The time when this event happened. |
| <i>userData</i> | User data as set by OTF2_Reader_RegisterGlobalEvtCallbacks or OTF2_GlobalEvtReader_SetCallbacks . |
| <i>attributeList</i> | Additional attributes for this event. |
| <i>lockID</i> | ID of the lock. |
| <i>acquisitionOrder</i> | A monotonically increasing number to determine the order of lock acquisitions (with unsynchronized clocks this is otherwise not possible). Corresponding acquire-release events have same number. |

J.19 OTF2_GlobalEvtReaderCallbacks.h File Reference

Since

Version 1.0

Returns

OTF2_CALLBACK_SUCCESS or *OTF2_CALLBACK_INTERRUPT*.

J.19.2.20 `typedef OTF2_CallbackCode(* OTF2_GlobalEvtReaderCallback_
OmpTaskComplete)(OTF2_LocationRef locationID,
OTF2_TimeStamp time, void *userData, OTF2_AttributeList
*attributeList, uint64_t taskID)`

Callback for the OmpTaskComplete event record.

An OmpTaskComplete record indicates that the execution of an OpenMP task has finished.

This event record is superseded by the *ThreadTaskComplete* event record and should not be used when the *ThreadTaskComplete* event record is in use.

Parameters

| | |
|----------------------|---|
| <i>locationID</i> | The location where this event happened. |
| <i>time</i> | The time when this event happened. |
| <i>userData</i> | User data as set by OTF2_Reader_RegisterGlobalEvtCallbacks or OTF2_GlobalEvtReader_SetCallbacks . |
| <i>attributeList</i> | Additional attributes for this event. |
| <i>taskID</i> | Identifier of the completed task instance. |

Since

Version 1.0

Returns

OTF2_CALLBACK_SUCCESS or *OTF2_CALLBACK_INTERRUPT*.

J.19.2.21 `typedef OTF2_CallbackCode(* OTF2_GlobalEvtReaderCallback_
OmpTaskCreate)(OTF2_LocationRef locationID, OTF2_TimeStamp
time, void *userData, OTF2_AttributeList *attributeList, uint64_t taskID)`

Callback for the OmpTaskCreate event record.

An OmpTaskCreate record marks that an OpenMP Task was/will be created in the current region.

APPENDIX J. FILE DOCUMENTATION

This event record is superseded by the *ThreadTaskCreate* event record and should not be used when the *ThreadTaskCreate* event record is in use.

Parameters

| | |
|----------------------|---|
| <i>locationID</i> | The location where this event happened. |
| <i>time</i> | The time when this event happened. |
| <i>userData</i> | User data as set by OTF2_Reader_RegisterGlobalEvtCallbacks or OTF2_GlobalEvtReader_SetCallbacks . |
| <i>attributeList</i> | Additional attributes for this event. |
| <i>taskID</i> | Identifier of the newly created task instance. |

Since

Version 1.0

Returns

[OTF2_CALLBACK_SUCCESS](#) or [OTF2_CALLBACK_INTERRUPT](#).

J.19.22 `typedef OTF2_CallbackCode(* OTF2_GlobalEvtReaderCallback_
OmpTaskSwitch)(OTF2_LocationRef locationID, OTF2_TimeStamp
time, void *userData, OTF2_AttributeList *attributeList, uint64_t taskID)`

Callback for the OmpTaskSwitch event record.

An OmpTaskSwitch record indicates that the execution of the current task will be suspended and another task starts/restarts its execution. Please note that this may change the current call stack of the executing location.

This event record is superseded by the *ThreadTaskSwitch* event record and should not be used when the *ThreadTaskSwitch* event record is in use.

Parameters

| | |
|----------------------|---|
| <i>locationID</i> | The location where this event happened. |
| <i>time</i> | The time when this event happened. |
| <i>userData</i> | User data as set by OTF2_Reader_RegisterGlobalEvtCallbacks or OTF2_GlobalEvtReader_SetCallbacks . |
| <i>attributeList</i> | Additional attributes for this event. |
| <i>taskID</i> | Identifier of the now active task instance. |

Since

Version 1.0

J.19 OTF2_GlobalEvtReaderCallbacks.h File Reference

Returns

[OTF2_CALLBACK_SUCCESS](#) or [OTF2_CALLBACK_INTERRUPT](#).

J.19.2.23 `typedef OTF2_CallbackCode(* OTF2_GlobalEvtReaderCallback_ - ParameterInt)(OTF2_LocationRef locationID, OTF2_TimeStamp time, void *userData, OTF2_AttributeList *attributeList, OTF2_ParameterRef parameter, int64_t value)`

Callback for the ParameterInt event record.

A ParameterInt record marks that in the current region, the specified integer parameter has the specified value.

Parameters

| | |
|----------------------|--|
| <i>locationID</i> | The location where this event happened. |
| <i>time</i> | The time when this event happened. |
| <i>userData</i> | User data as set by OTF2_Reader_RegisterGlobalEvtCallbacks or OTF2_GlobalEvtReader_SetCallbacks . |
| <i>attributeList</i> | Additional attributes for this event. |
| <i>parameter</i> | Parameter ID. References a Parameter definition and will be mapped to the global definition if a mapping table of type OTF2_MAPPING_-PARAMETER is available. |
| <i>value</i> | Value of the recorded parameter. |

Since

Version 1.0

Returns

[OTF2_CALLBACK_SUCCESS](#) or [OTF2_CALLBACK_INTERRUPT](#).

J.19.2.24 `typedef OTF2_CallbackCode(* OTF2_GlobalEvtReaderCallback_ - ParameterString)(OTF2_LocationRef locationID, OTF2_TimeStamp time, void *userData, OTF2_AttributeList *attributeList, OTF2_ParameterRef parameter, OTF2_StringRef string)`

Callback for the ParameterString event record.

A ParameterString record marks that in the current region, the specified string parameter has the specified value.

APPENDIX J. FILE DOCUMENTATION

Parameters

| | |
|----------------------|--|
| <i>locationID</i> | The location where this event happened. |
| <i>time</i> | The time when this event happened. |
| <i>userData</i> | User data as set by OTF2_Reader_RegisterGlobalEvtCallbacks or OTF2_GlobalEvtReader_SetCallbacks . |
| <i>attributeList</i> | Additional attributes for this event. |
| <i>parameter</i> | Parameter ID. References a Parameter definition and will be mapped to the global definition if a mapping table of type OTF2_MAPPING_PARAMETER is available. |
| <i>string</i> | Value: Handle of a string definition References a String definition and will be mapped to the global definition if a mapping table of type OTF2_MAPPING_STRING is available. |

Since

Version 1.0

Returns

[OTF2_CALLBACK_SUCCESS](#) or [OTF2_CALLBACK_INTERRUPT](#).

J.19.2.25 `typedef OTF2_CallbackCode(* OTF2_GlobalEvtReaderCallback_
ParameterUnsignedInt)(OTF2_LocationRef locationID,
OTF2_TimeStamp time, void *userData, OTF2_AttributeList
*attributeList, OTF2_ParameterRef parameter, uint64_t value)`

Callback for the `ParameterUnsignedInt` event record.

A `ParameterUnsignedInt` record marks that in the current region, the specified unsigned integer parameter has the specified value.

Parameters

| | |
|----------------------|---|
| <i>locationID</i> | The location where this event happened. |
| <i>time</i> | The time when this event happened. |
| <i>userData</i> | User data as set by OTF2_Reader_RegisterGlobalEvtCallbacks or OTF2_GlobalEvtReader_SetCallbacks . |
| <i>attributeList</i> | Additional attributes for this event. |
| <i>parameter</i> | Parameter ID. References a Parameter definition and will be mapped to the global definition if a mapping table of type OTF2_MAPPING_PARAMETER is available. |
| <i>value</i> | Value of the recorded parameter. |

J.19 OTF2_GlobalEvtReaderCallbacks.h File Reference

Since

Version 1.0

Returns

[OTF2_CALLBACK_SUCCESS](#) or [OTF2_CALLBACK_INTERRUPT](#).

J.19.2.26 typedef OTF2_CallbackCode(* OTF2_GlobalEvtReaderCallback_
RmaAcquireLock)(OTF2_LocationRef locationID, OTF2_TimeStamp
time, void *userData, OTF2_AttributeList *attributeList,
OTF2_RmaWinRef win, uint32_t remote, uint64_t lockId, OTF2_LockType
lockType)

Callback for the RmaAcquireLock event record.

An RmaAcquireLock record denotes the time a lock was acquired by the process.

Parameters

| | |
|----------------------|--|
| <i>locationID</i> | The location where this event happened. |
| <i>time</i> | The time when this event happened. |
| <i>userData</i> | User data as set by OTF2_Reader_RegisterGlobalEvtCallbacks or OTF2_GlobalEvtReader_SetCallbacks . |
| <i>attributeList</i> | Additional attributes for this event. |
| <i>win</i> | ID of the window used for this operation. References a RmaWin definition and will be mapped to the global definition if a mapping table of type OTF2_MAPPING_RMA_WIN is available. |
| <i>remote</i> | Rank of the locked remote process. |
| <i>lockId</i> | ID of the lock acquired, if multiple locks are defined on a window. |
| <i>lockType</i> | Type of lock acquired. |

Since

Version 1.2

Returns

[OTF2_CALLBACK_SUCCESS](#) or [OTF2_CALLBACK_INTERRUPT](#).

J.19.2.27 `typedef OTF2_CallbackCode(* OTF2_GlobalEvtReaderCallback_
RmaAtomic)(OTF2_LocationRef locationID, OTF2_TimeStamp time,
void *userData, OTF2_AttributeList *attributeList, OTF2_RmaWinRef
win, uint32_t remote, OTF2_RmaAtomicType type, uint64_t bytesSent,
uint64_t bytesReceived, uint64_t matchingId)`

Callback for the RmaAtomic event record.

An RmaAtomic record denotes the time a atomic operation was issued.

Parameters

| | |
|----------------------|--|
| <i>locationID</i> | The location where this event happened. |
| <i>time</i> | The time when this event happened. |
| <i>userData</i> | User data as set by OTF2_Reader_RegisterGlobalEvtCallbacks or OTF2_GlobalEvtReader_SetCallbacks . |
| <i>attributeList</i> | Additional attributes for this event. |
| <i>win</i> | ID of the window used for this operation. References a RmaWin definition and will be mapped to the global definition if a mapping table of type OTF2_MAPPING_RMA_WIN is available. |
| <i>remote</i> | Rank of the target process. |
| <i>type</i> | Type of atomic operation. |
| <i>bytesSent</i> | Bytes sent to target. |
| <i>bytesReceived</i> | Bytes received from target. |
| <i>matchingId</i> | ID used for matching the appropriate completion record. |

Since

Version 1.2

Returns

[OTF2_CALLBACK_SUCCESS](#) or [OTF2_CALLBACK_INTERRUPT](#).

J.19.2.28 `typedef OTF2_CallbackCode(* OTF2_GlobalEvtReaderCallback_
RmaCollectiveBegin)(OTF2_LocationRef locationID,
OTF2_TimeStamp time, void *userData, OTF2_AttributeList
*attributeList)`

Callback for the RmaCollectiveBegin event record.

An RmaCollectiveBegin record denotes the beginnig of a collective RMA operation.

J.19 OTF2_GlobalEvtReaderCallbacks.h File Reference

Parameters

| | |
|----------------------|---|
| <i>locationID</i> | The location where this event happened. |
| <i>time</i> | The time when this event happened. |
| <i>userData</i> | User data as set by OTF2_Reader_RegisterGlobalEvtCallbacks or OTF2_GlobalEvtReader_SetCallbacks . |
| <i>attributeList</i> | Additional attributes for this event. |

Since

Version 1.2

Returns

[OTF2_CALLBACK_SUCCESS](#) or [OTF2_CALLBACK_INTERRUPT](#).

J.19.2.29 `typedef OTF2_CallbackCode(* OTF2_GlobalEvtReaderCallback_ - RmaCollectiveEnd)(OTF2_LocationRef locationID, OTF2_TimeStamp time, void *userData, OTF2_AttributeList *attributeList, OTF2_CollectiveOp collectiveOp, OTF2_RmaSyncLevel syncLevel, OTF2_RmaWinRef win, uint32_t root, uint64_t bytesSent, uint64_t bytesReceived)`

Callback for the RmaCollectiveEnd event record.

"An RmaCollectiveEnd record denotes the end of a collective RMA operation.

Parameters

| | |
|----------------------|--|
| <i>locationID</i> | The location where this event happened. |
| <i>time</i> | The time when this event happened. |
| <i>userData</i> | User data as set by OTF2_Reader_RegisterGlobalEvtCallbacks or OTF2_GlobalEvtReader_SetCallbacks . |
| <i>attributeList</i> | Additional attributes for this event. |
| <i>collectiveOp</i> | Determines which collective operation it is. |
| <i>syncLevel</i> | Synchronization level of this collective operation. |
| <i>win</i> | ID of the window used for this operation. References a RmaWin definition and will be mapped to the global definition if a mapping table of type OTF2_MAPPING_RMA_WIN is available. |
| <i>root</i> | Root process for this operation. |
| <i>bytesSent</i> | Bytes sent in operation. |
| <i>bytesReceived</i> | Bytes receives in operation. |

Since

Version 1.2

Returns

OTF2_CALLBACK_SUCCESS or *OTF2_CALLBACK_INTERRUPT*.

J.19.2.30 `typedef OTF2_CallbackCode(* OTF2_GlobalEvtReaderCallback_
RmaGet)(OTF2_LocationRef locationID, OTF2_TimeStamp time, void
*userData, OTF2_AttributeList *attributeList, OTF2_RmaWinRef win,
uint32_t remote, uint64_t bytes, uint64_t matchingId)`

Callback for the RmaGet event record.

An RmaGet record denotes the time a put operation was issued.

Parameters

| | |
|----------------------|--|
| <i>locationID</i> | The location where this event happened. |
| <i>time</i> | The time when this event happened. |
| <i>userData</i> | User data as set by OTF2_Reader_RegisterGlobalEvtCallbacks or OTF2_GlobalEvtReader_SetCallbacks . |
| <i>attributeList</i> | Additional attributes for this event. |
| <i>win</i> | ID of the window used for this operation. References a RmaWin definition and will be mapped to the global definition if a mapping table of type OTF2_MAPPING_RMA_WIN is available. |
| <i>remote</i> | Rank of the target process. |
| <i>bytes</i> | Bytes received from target. |
| <i>matchingId</i> | ID used for matching the appropriate completion record. |

Since

Version 1.2

Returns

OTF2_CALLBACK_SUCCESS or *OTF2_CALLBACK_INTERRUPT*.

J.19 OTF2_GlobalEvtReaderCallbacks.h File Reference

J.19.2.31 `typedef OTF2_CallbackCode(* OTF2_GlobalEvtReaderCallback_
RmaGroupSync)(OTF2_LocationRef locationID, OTF2_TimeStamp
time, void *userData, OTF2_AttributeList *attributeList,
OTF2_RmaSyncLevel syncLevel, OTF2_RmaWinRef win,
OTF2_GroupRef group)`

Callback for the RmaGroupSync event record.

An RmaGroupSync record denotes the synchronization with a subgroup of processes on a window.

Parameters

| | |
|----------------------|--|
| <i>locationID</i> | The location where this event happened. |
| <i>time</i> | The time when this event happened. |
| <i>userData</i> | User data as set by OTF2_Reader_RegisterGlobalEvtCallbacks or OTF2_GlobalEvtReader_SetCallbacks . |
| <i>attributeList</i> | Additional attributes for this event. |
| <i>syncLevel</i> | Synchronization level of this collective operation. |
| <i>win</i> | ID of the window used for this operation. References a RmaWin definition and will be mapped to the global definition if a mapping table of type OTF2_MAPPING_RMA_WIN is available. |
| <i>group</i> | Group of remote processes involved in synchronization. References a Group definition and will be mapped to the global definition if a mapping table of type OTF2_MAPPING_GROUP is available. |

Since

Version 1.2

Returns

[OTF2_CALLBACK_SUCCESS](#) or [OTF2_CALLBACK_INTERRUPT](#).

J.19.2.32 `typedef OTF2_CallbackCode(* OTF2_GlobalEvtReaderCallback_
RmaOpCompleteBlocking)(OTF2_LocationRef locationID,
OTF2_TimeStamp time, void *userData, OTF2_AttributeList
*attributeList, OTF2_RmaWinRef win, uint64_t matchingId)`

Callback for the RmaOpCompleteBlocking event record.

An RmaOpCompleteBlocking record denotes the local completion of a blocking RMA operation.

Parameters

APPENDIX J. FILE DOCUMENTATION

| | |
|----------------------|--|
| <i>locationID</i> | The location where this event happened. |
| <i>time</i> | The time when this event happened. |
| <i>userData</i> | User data as set by OTF2_Reader_RegisterGlobalEvtCallbacks or OTF2_GlobalEvtReader_SetCallbacks . |
| <i>attributeList</i> | Additional attributes for this event. |
| <i>win</i> | ID of the window used for this operation. References a RmaWin definition and will be mapped to the global definition if a mapping table of type OTF2_MAPPING_RMA_WIN is available. |
| <i>matchingId</i> | ID used for matching the appropriate completion record. |

Since

Version 1.2

Returns

[OTF2_CALLBACK_SUCCESS](#) or [OTF2_CALLBACK_INTERRUPT](#).

J.19.2.33 `typedef OTF2_CallbackCode(* OTF2_GlobalEvtReaderCallback_
RmaOpCompleteNonBlocking)(OTF2_LocationRef locationID,
OTF2_TimeStamp time, void *userData, OTF2_AttributeList
*attributeList, OTF2_RmaWinRef win, uint64_t matchingId)`

Callback for the RmaOpCompleteNonBlocking event record.

An RmaOpCompleteNonBlocking record denotes the local completion of a non-blocking RMA operation.

Parameters

| | |
|----------------------|--|
| <i>locationID</i> | The location where this event happened. |
| <i>time</i> | The time when this event happened. |
| <i>userData</i> | User data as set by OTF2_Reader_RegisterGlobalEvtCallbacks or OTF2_GlobalEvtReader_SetCallbacks . |
| <i>attributeList</i> | Additional attributes for this event. |
| <i>win</i> | ID of the window used for this operation. References a RmaWin definition and will be mapped to the global definition if a mapping table of type OTF2_MAPPING_RMA_WIN is available. |
| <i>matchingId</i> | ID used for matching the appropriate completion record. |

Since

Version 1.2

J.19 OTF2_GlobalEvtReaderCallbacks.h File Reference

Returns

[OTF2_CALLBACK_SUCCESS](#) or [OTF2_CALLBACK_INTERRUPT](#).

J.19.2.34 `typedef OTF2_CallbackCode(* OTF2_GlobalEvtReaderCallback_
RmaOpCompleteRemote)(OTF2_LocationRef locationID,
OTF2_TimeStamp time, void *userData, OTF2_AttributeList
*attributeList, OTF2_RmaWinRef win, uint64_t matchingId)`

Callback for the RmaOpCompleteRemote event record.

An RmaOpCompleteRemote record denotes the local completion of an RMA operation.

Parameters

| | |
|----------------------|--|
| <i>locationID</i> | The location where this event happened. |
| <i>time</i> | The time when this event happened. |
| <i>userData</i> | User data as set by OTF2_Reader_RegisterGlobalEvtCallbacks or OTF2_GlobalEvtReader_SetCallbacks . |
| <i>attributeList</i> | Additional attributes for this event. |
| <i>win</i> | ID of the window used for this operation. References a RmaWin definition and will be mapped to the global definition if a mapping table of type OTF2_MAPPING_RMA_WIN is available. |
| <i>matchingId</i> | ID used for matching the appropriate completion record. |

Since

Version 1.2

Returns

[OTF2_CALLBACK_SUCCESS](#) or [OTF2_CALLBACK_INTERRUPT](#).

J.19.2.35 `typedef OTF2_CallbackCode(* OTF2_GlobalEvtReaderCallback_
RmaOpTest)(OTF2_LocationRef locationID, OTF2_TimeStamp time,
void *userData, OTF2_AttributeList *attributeList, OTF2_RmaWinRef
win, uint64_t matchingId)`

Callback for the RmaOpTest event record.

An RmaOpTest record denotes that a non-blocking RMA operation has been tested for completion unsuccessfully.

APPENDIX J. FILE DOCUMENTATION

Parameters

| | |
|----------------------|--|
| <i>locationID</i> | The location where this event happened. |
| <i>time</i> | The time when this event happened. |
| <i>userData</i> | User data as set by OTF2_Reader_RegisterGlobalEvtCallbacks or OTF2_GlobalEvtReader_SetCallbacks . |
| <i>attributeList</i> | Additional attributes for this event. |
| <i>win</i> | ID of the window used for this operation. References a RmaWin definition and will be mapped to the global definition if a mapping table of type OTF2_MAPPING_RMA_WIN is available. |
| <i>matchingId</i> | ID used for matching the appropriate completion record. |

Since

Version 1.2

Returns

[OTF2_CALLBACK_SUCCESS](#) or [OTF2_CALLBACK_INTERRUPT](#).

J.19.2.36 `typedef OTF2_CallbackCode(* OTF2_GlobalEvtReaderCallback_ - RmaPut)(OTF2_LocationRef locationID, OTF2_TimeStamp time, void *userData, OTF2_AttributeList *attributeList, OTF2_RmaWinRef win, uint32_t remote, uint64_t bytes, uint64_t matchingId)`

Callback for the RmaPut event record.

An RmaPut record denotes the time a put operation was issued.

Parameters

| | |
|----------------------|--|
| <i>locationID</i> | The location where this event happened. |
| <i>time</i> | The time when this event happened. |
| <i>userData</i> | User data as set by OTF2_Reader_RegisterGlobalEvtCallbacks or OTF2_GlobalEvtReader_SetCallbacks . |
| <i>attributeList</i> | Additional attributes for this event. |
| <i>win</i> | ID of the window used for this operation. References a RmaWin definition and will be mapped to the global definition if a mapping table of type OTF2_MAPPING_RMA_WIN is available. |
| <i>remote</i> | Rank of the target process. |
| <i>bytes</i> | Bytes sent to target. |
| <i>matchingId</i> | ID used for matching the appropriate completion record. |

J.19 OTF2_GlobalEvtReaderCallbacks.h File Reference

Since

Version 1.2

Returns

[OTF2_CALLBACK_SUCCESS](#) or [OTF2_CALLBACK_INTERRUPT](#).

J.19.2.37 `typedef OTF2_CallbackCode(* OTF2_GlobalEvtReaderCallback_
RmaReleaseLock)(OTF2_LocationRef locationID, OTF2_TimeStamp
time, void *userData, OTF2_AttributeList *attributeList,
OTF2_RmaWinRef win, uint32_t remote, uint64_t lockId)`

Callback for the RmaReleaseLock event record.

An RmaReleaseLock record denotes the time the lock was released.

Parameters

| | |
|----------------------|--|
| <i>locationID</i> | The location where this event happened. |
| <i>time</i> | The time when this event happened. |
| <i>userData</i> | User data as set by OTF2_Reader_RegisterGlobalEvtCallbacks or OTF2_GlobalEvtReader_SetCallbacks . |
| <i>attributeList</i> | Additional attributes for this event. |
| <i>win</i> | ID of the window used for this operation. References a RmaWin definition and will be mapped to the global definition if a mapping table of type OTF2_MAPPING_RMA_WIN is available. |
| <i>remote</i> | Rank of the locked remote process. |
| <i>lockId</i> | ID of the lock released, if multiple locks are defined on a window. |

Since

Version 1.2

Returns

[OTF2_CALLBACK_SUCCESS](#) or [OTF2_CALLBACK_INTERRUPT](#).

J.19.2.38 `typedef OTF2_CallbackCode(* OTF2_GlobalEvtReaderCallback_
RmaRequestLock)(OTF2_LocationRef locationID, OTF2_TimeStamp
time, void *userData, OTF2_AttributeList *attributeList,
OTF2_RmaWinRef win, uint32_t remote, uint64_t lockId, OTF2_LockType
lockType)`

Callback for the RmaRequestLock event record.

APPENDIX J. FILE DOCUMENTATION

An `RmaRequestLock` record denotes the time a lock was requested and with it the earliest time it could have been granted. It is used to mark (possibly) non-blocking lock request, as defined by the MPI standard.

Parameters

| | |
|----------------------|--|
| <i>locationID</i> | The location where this event happened. |
| <i>time</i> | The time when this event happened. |
| <i>userData</i> | User data as set by OTF2_Reader_RegisterGlobalEvtCallbacks or OTF2_GlobalEvtReader_SetCallbacks . |
| <i>attributeList</i> | Additional attributes for this event. |
| <i>win</i> | ID of the window used for this operation. References a RmaWin definition and will be mapped to the global definition if a mapping table of type OTF2_MAPPING_RMA_WIN is available. |
| <i>remote</i> | Rank of the locked remote process. |
| <i>lockId</i> | ID of the lock aquired, if multiple locks are defined on a window. |
| <i>lockType</i> | Type of lock aquired. |

Since

Version 1.2

Returns

[OTF2_CALLBACK_SUCCESS](#) or [OTF2_CALLBACK_INTERRUPT](#).

```
J.19.2.39 typedef OTF2_CallbackCode( * OTF2_GlobalEvtReaderCallback_  
RmaSync)(OTF2_LocationRef locationID, OTF2_TimeStamp time, void  
*userData, OTF2_AttributeList *attributeList, OTF2_RmaWinRef win,  
uint32_t remote, OTF2_RmaSyncType syncType)
```

Callback for the `RmaSync` event record.

An `RmaSync` record denotes the direct synchronization with a possibly remote process.

Parameters

| | |
|----------------------|--|
| <i>locationID</i> | The location where this event happened. |
| <i>time</i> | The time when this event happened. |
| <i>userData</i> | User data as set by OTF2_Reader_RegisterGlobalEvtCallbacks or OTF2_GlobalEvtReader_SetCallbacks . |
| <i>attributeList</i> | Additional attributes for this event. |
| <i>win</i> | ID of the window used for this operation. References a RmaWin definition and will be mapped to the global definition if a mapping table of type OTF2_MAPPING_RMA_WIN is available. |

J.19 OTF2_GlobalEvtReaderCallbacks.h File Reference

| | |
|-----------------|------------------------------------|
| <i>remote</i> | Rank of the locked remote process. |
| <i>syncType</i> | Type of synchronization. |

Since

Version 1.2

Returns

[OTF2_CALLBACK_SUCCESS](#) or [OTF2_CALLBACK_INTERRUPT](#).

J.19.2.40 `typedef OTF2_CallbackCode(* OTF2_GlobalEvtReaderCallback_
RmaTryLock)(OTF2_LocationRef locationID, OTF2_TimeStamp time,
void *userData, OTF2_AttributeList *attributeList, OTF2_RmaWinRef
win, uint32_t remote, uint64_t lockId, OTF2_LockType lockType)`

Callback for the RmaTryLock event record.

An RmaTryLock record denotes the time of an unsuccessful attempt to acquire the lock.

Parameters

| | |
|----------------------|--|
| <i>locationID</i> | The location where this event happened. |
| <i>time</i> | The time when this event happened. |
| <i>userData</i> | User data as set by OTF2_Reader_RegisterGlobalEvtCallbacks or OTF2_GlobalEvtReader_SetCallbacks . |
| <i>attributeList</i> | Additional attributes for this event. |
| <i>win</i> | ID of the window used for this operation. References a RmaWin definition and will be mapped to the global definition if a mapping table of type OTF2_MAPPING_RMA_WIN is available. |
| <i>remote</i> | Rank of the locked remote process. |
| <i>lockId</i> | ID of the lock acquired, if multiple locks are defined on a window. |
| <i>lockType</i> | Type of lock acquired. |

Since

Version 1.2

Returns

[OTF2_CALLBACK_SUCCESS](#) or [OTF2_CALLBACK_INTERRUPT](#).

APPENDIX J. FILE DOCUMENTATION

J.19.2.41 `typedef OTF2_CallbackCode(* OTF2_GlobalEvtReaderCallback_
RmaWaitChange)(OTF2_LocationRef locationID, OTF2_TimeStamp
time, void *userData, OTF2_AttributeList *attributeList,
OTF2_RmaWinRef win)`

Callback for the RmaWaitChange event record.

An RmaWaitChange record denotes the change of a window that was waited for.

Parameters

| | |
|----------------------|--|
| <i>locationID</i> | The location where this event happened. |
| <i>time</i> | The time when this event happened. |
| <i>userData</i> | User data as set by OTF2_Reader_RegisterGlobalEvtCallbacks or OTF2_GlobalEvtReader_SetCallbacks . |
| <i>attributeList</i> | Additional attributes for this event. |
| <i>win</i> | ID of the window used for this operation. References a RmaWin definition and will be mapped to the global definition if a mapping table of type OTF2_MAPPING_RMA_WIN is available. |

Since

Version 1.2

Returns

[OTF2_CALLBACK_SUCCESS](#) or [OTF2_CALLBACK_INTERRUPT](#).

J.19.2.42 `typedef OTF2_CallbackCode(* OTF2_GlobalEvtReaderCallback_
RmaWinCreate)(OTF2_LocationRef locationID, OTF2_TimeStamp
time, void *userData, OTF2_AttributeList *attributeList,
OTF2_RmaWinRef win)`

Callback for the RmaWinCreate event record.

An RmaWinCreate record denotes the creation of an RMA window.

Parameters

| | |
|----------------------|--|
| <i>locationID</i> | The location where this event happened. |
| <i>time</i> | The time when this event happened. |
| <i>userData</i> | User data as set by OTF2_Reader_RegisterGlobalEvtCallbacks or OTF2_GlobalEvtReader_SetCallbacks . |
| <i>attributeList</i> | Additional attributes for this event. |
| <i>win</i> | ID of the window created. References a RmaWin definition and will be mapped to the global definition if a mapping table of type OTF2_MAPPING_RMA_WIN is available. |

J.19 OTF2_GlobalEvtReaderCallbacks.h File Reference

Since

Version 1.2

Returns

[OTF2_CALLBACK_SUCCESS](#) or [OTF2_CALLBACK_INTERRUPT](#).

J.19.2.43 `typedef OTF2_CallbackCode(* OTF2_GlobalEvtReaderCallback_ - RmaWinDestroy)(OTF2_LocationRef locationID, OTF2_TimeStamp time, void *userData, OTF2_AttributeList *attributeList, OTF2_RmaWinRef win)`

Callback for the RmaWinDestroy event record.

An RmaWinDestroy record denotes the destruction of an RMA window.

Parameters

| | |
|----------------------|---|
| <i>locationID</i> | The location where this event happened. |
| <i>time</i> | The time when this event happened. |
| <i>userData</i> | User data as set by OTF2_Reader_RegisterGlobalEvtCallbacks or OTF2_GlobalEvtReader_SetCallbacks . |
| <i>attributeList</i> | Additional attributes for this event. |
| <i>win</i> | ID of the window destroyed. References a RmaWin definition and will be mapped to the global definition if a mapping table of type OTF2_-MAPPING_RMA_WIN is available. |

Since

Version 1.2

Returns

[OTF2_CALLBACK_SUCCESS](#) or [OTF2_CALLBACK_INTERRUPT](#).

J.19.2.44 `typedef OTF2_CallbackCode(* OTF2_GlobalEvtReaderCallback_ - ThreadAcquireLock)(OTF2_LocationRef locationID, OTF2_TimeStamp time, void *userData, OTF2_AttributeList *attributeList, OTF2_Paradigm model, uint32_t lockID, uint32_t acquisitionOrder)`

Callback for the ThreadAcquireLock event record.

An ThreadAcquireLock record marks that a thread acquires an lock.

APPENDIX J. FILE DOCUMENTATION

Parameters

| | |
|-------------------------|---|
| <i>locationID</i> | The location where this event happened. |
| <i>time</i> | The time when this event happened. |
| <i>userData</i> | User data as set by OTF2_Reader_RegisterGlobalEvtCallbacks or OTF2_GlobalEvtReader_SetCallbacks . |
| <i>attributeList</i> | Additional attributes for this event. |
| <i>lockID</i> | ID of the lock. |
| <i>acquisitionOrder</i> | A monotonically increasing number to determine the order of lock acquisitions (with unsynchronized clocks this is otherwise not possible). Corresponding acquire-release events have same number. |

Since

Version 1.2

Returns

[OTF2_CALLBACK_SUCCESS](#) or [OTF2_CALLBACK_INTERRUPT](#).

J.19.2.45 `typedef OTF2_CallbackCode(* OTF2_GlobalEvtReaderCallback_ - ThreadFork)(OTF2_LocationRef locationID, OTF2_TimeStamp time, void *userData, OTF2_AttributeList *attributeList, OTF2_Paradigm model, uint32_t numberOfRequestedThreads)`

Callback for the ThreadFork event record.

An ThreadFork record marks that an thread forks a thread team.

Parameters

| | |
|---------------------------------|---|
| <i>locationID</i> | The location where this event happened. |
| <i>time</i> | The time when this event happened. |
| <i>userData</i> | User data as set by OTF2_Reader_RegisterGlobalEvtCallbacks or OTF2_GlobalEvtReader_SetCallbacks . |
| <i>attributeList</i> | Additional attributes for this event. |
| <i>numberOfRequestedThreads</i> | Requested size of the team. |

Since

Version 1.2

J.19 OTF2_GlobalEvtReaderCallbacks.h File Reference

Returns

[OTF2_CALLBACK_SUCCESS](#) or [OTF2_CALLBACK_INTERRUPT](#).

J.19.2.46 `typedef OTF2_CallbackCode(* OTF2_GlobalEvtReaderCallback_ - ThreadJoin)(OTF2_LocationRef locationID, OTF2_TimeStamp time, void *userData, OTF2_AttributeList *attributeList, OTF2_Paradigm model)`

Callback for the ThreadJoin event record.

An ThreadJoin record marks that a team of threads is joint and only the master thread continues execution.

Parameters

| | |
|----------------------|---|
| <i>locationID</i> | The location where this event happened. |
| <i>time</i> | The time when this event happened. |
| <i>userData</i> | User data as set by OTF2_Reader_RegisterGlobalEvtCallbacks or OTF2_GlobalEvtReader_SetCallbacks . |
| <i>attributeList</i> | Additional attributes for this event. |

Since

Version 1.2

Returns

[OTF2_CALLBACK_SUCCESS](#) or [OTF2_CALLBACK_INTERRUPT](#).

J.19.2.47 `typedef OTF2_CallbackCode(* OTF2_GlobalEvtReaderCallback_ - ThreadReleaseLock)(OTF2_LocationRef locationID, OTF2_TimeStamp time, void *userData, OTF2_AttributeList *attributeList, OTF2_Paradigm model, uint32_t lockID, uint32_t acquisitionOrder)`

Callback for the ThreadReleaseLock event record.

An ThreadReleaseLock record marks that a thread releases an lock.

Parameters

| | |
|-------------------|---|
| <i>locationID</i> | The location where this event happened. |
| <i>time</i> | The time when this event happened. |

APPENDIX J. FILE DOCUMENTATION

| | |
|-------------------------|---|
| <i>userData</i> | User data as set by OTF2_Reader_RegisterGlobalEvtCallbacks or OTF2_GlobalEvtReader_SetCallbacks . |
| <i>attributeList</i> | Additional attributes for this event. |
| <i>lockID</i> | ID of the lock. |
| <i>acquisitionOrder</i> | A monotonically increasing number to determine the order of lock acquisitions (with unsynchronized clocks this is otherwise not possible). Corresponding acquire-release events have same number. |

Since

Version 1.2

Returns

[OTF2_CALLBACK_SUCCESS](#) or [OTF2_CALLBACK_INTERRUPT](#).

J.19.2.48 `typedef OTF2_CallbackCode(* OTF2_GlobalEvtReaderCallback_ - ThreadTaskComplete)(OTF2_LocationRef locationID, OTF2_TimeStamp time, void *userData, OTF2_AttributeList *attributeList, OTF2_CommRef threadTeam, uint32_t creatingThread, uint32_t generationNumber)`

Callback for the ThreadTaskComplete event record.

An ThreadTaskComplete record indicates that the execution of an OpenMP task has finished.

Parameters

| | |
|-------------------------|---|
| <i>locationID</i> | The location where this event happened. |
| <i>time</i> | The time when this event happened. |
| <i>userData</i> | User data as set by OTF2_Reader_RegisterGlobalEvtCallbacks or OTF2_GlobalEvtReader_SetCallbacks . |
| <i>attributeList</i> | Additional attributes for this event. |
| <i>threadTeam</i> | Thread team References a Comm definition and will be mapped to the global definition if a mapping table of type OTF2_MAPPING_COMM is available. |
| <i>creatingThread</i> | Creating thread of this task. |
| <i>generationNumber</i> | Thread-private generation number of task's creating thread. |

J.19 OTF2_GlobalEvtReaderCallbacks.h File Reference

Since

Version 1.2

Returns

[OTF2_CALLBACK_SUCCESS](#) or [OTF2_CALLBACK_INTERRUPT](#).

J.19.2.49 `typedef OTF2_CallbackCode(* OTF2_GlobalEvtReaderCallback_ - ThreadTaskCreate)(OTF2_LocationRef locationID, OTF2_TimeStamp time, void *userData, OTF2_AttributeList *attributeList, OTF2_CommRef threadTeam, uint32_t creatingThread, uint32_t generationNumber)`

Callback for the ThreadTaskCreate event record.

An ThreadTaskCreate record marks that an task in was/will be created and will be processed by the specified thread team.

Parameters

| | |
|-------------------------|---|
| <i>locationID</i> | The location where this event happened. |
| <i>time</i> | The time when this event happened. |
| <i>userData</i> | User data as set by OTF2_Reader_RegisterGlobalEvtCallbacks or OTF2_GlobalEvtReader_SetCallbacks . |
| <i>attributeList</i> | Additional attributes for this event. |
| <i>threadTeam</i> | Thread team References a Comm definition and will be mapped to the global definition if a mapping table of type OTF2_MAPPING_COMM is available. |
| <i>creatingThread</i> | Creating thread of this task. (This is redundant, remove?) |
| <i>generationNumber</i> | Thread-private generation number of task's creating thread. |

Since

Version 1.2

Returns

[OTF2_CALLBACK_SUCCESS](#) or [OTF2_CALLBACK_INTERRUPT](#).

APPENDIX J. FILE DOCUMENTATION

J.19.2.50 `typedef OTF2_CallbackCode(* OTF2_GlobalEvtReaderCallback_ - ThreadTaskSwitch)(OTF2_LocationRef locationID, OTF2_TimeStamp time, void *userData, OTF2_AttributeList *attributeList, OTF2_CommRef threadTeam, uint32_t creatingThread, uint32_t generationNumber)`

Callback for the ThreadTaskSwitch event record.

An ThreadTaskSwitch record indicates that the execution of the current task will be suspended and another task starts/restarts its execution. Please note that this may change the current call stack of the executing location.

Parameters

| | |
|-------------------------|---|
| <i>locationID</i> | The location where this event happened. |
| <i>time</i> | The time when this event happened. |
| <i>userData</i> | User data as set by OTF2_Reader_RegisterGlobalEvtCallbacks or OTF2_GlobalEvtReader_SetCallbacks . |
| <i>attributeList</i> | Additional attributes for this event. |
| <i>threadTeam</i> | Thread team References a Comm definition and will be mapped to the global definition if a mapping table of type OTF2_MAPPING_COMM is available. |
| <i>creatingThread</i> | Creating thread of this task. |
| <i>generationNumber</i> | Thread-private generation number of task's creating thread. |

Since

Version 1.2

Returns

[OTF2_CALLBACK_SUCCESS](#) or [OTF2_CALLBACK_INTERRUPT](#).

J.19.2.51 `typedef OTF2_CallbackCode(* OTF2_GlobalEvtReaderCallback_ - ThreadTeamBegin)(OTF2_LocationRef locationID, OTF2_TimeStamp time, void *userData, OTF2_AttributeList *attributeList, OTF2_CommRef threadTeam)`

Callback for the ThreadTeamBegin event record.

Parameters

| | |
|-------------------|---|
| <i>locationID</i> | The location where this event happened. |
|-------------------|---|

J.19 OTF2_GlobalEvtReaderCallbacks.h File Reference

| | |
|----------------------|---|
| <i>time</i> | The time when this event happened. |
| <i>userData</i> | User data as set by OTF2_Reader_RegisterGlobalEvtCallbacks or OTF2_GlobalEvtReader_SetCallbacks . |
| <i>attributeList</i> | Additional attributes for this event. |
| <i>threadTeam</i> | Thread team References a Comm definition and will be mapped to the global definition if a mapping table of type OTF2_MAPPING_COMM is available. |

Since

Version 1.2

Returns

[OTF2_CALLBACK_SUCCESS](#) or [OTF2_CALLBACK_INTERRUPT](#).

J.19.252 `typedef OTF2_CallbackCode(* OTF2_GlobalEvtReaderCallback_ - ThreadTeamEnd)(OTF2_LocationRef locationID, OTF2_TimeStamp time, void *userData, OTF2_AttributeList *attributeList, OTF2_CommRef threadTeam)`

Callback for the ThreadTeamEnd event record.

Parameters

| | |
|----------------------|---|
| <i>locationID</i> | The location where this event happened. |
| <i>time</i> | The time when this event happened. |
| <i>userData</i> | User data as set by OTF2_Reader_RegisterGlobalEvtCallbacks or OTF2_GlobalEvtReader_SetCallbacks . |
| <i>attributeList</i> | Additional attributes for this event. |
| <i>threadTeam</i> | Thread team References a Comm definition and will be mapped to the global definition if a mapping table of type OTF2_MAPPING_COMM is available. |

Since

Version 1.2

Returns

[OTF2_CALLBACK_SUCCESS](#) or [OTF2_CALLBACK_INTERRUPT](#).

APPENDIX J. FILE DOCUMENTATION

J.19.2.53 `typedef OTF2_CallbackCode(* OTF2_GlobalEvtReaderCallback_Unknown)(OTF2_LocationRef locationID, OTF2_TimeStamp time, void *userData, OTF2_AttributeList *attributeList)`

Callback for an unknown event record.

Parameters

| | |
|----------------------|---|
| <i>locationID</i> | The location where this event happened. |
| <i>time</i> | The time when this event happened. |
| <i>userData</i> | User data as set by OTF2_Reader_RegisterGlobalEvtCallbacks or OTF2_GlobalEvtReader_SetCallbacks . |
| <i>attributeList</i> | Additional attributes for this event. |

Returns

[OTF2_CALLBACK_SUCCESS](#) or [OTF2_CALLBACK_INTERRUPT](#).

J.19.3 Function Documentation

J.19.3.1 `void OTF2_GlobalEvtReaderCallbacks_Clear (OTF2_GlobalEvtReaderCallbacks * globalEvtReaderCallbacks)`

Clears a struct for the global event callbacks.

Parameters

| | |
|---------------------------------|--|
| <i>globalEvtReaderCallbacks</i> | Handle to a struct previously allocated with OTF2_GlobalEvtReaderCallbacks_New . |
|---------------------------------|--|

J.19.3.2 `void OTF2_GlobalEvtReaderCallbacks_Delete (OTF2_GlobalEvtReaderCallbacks * globalEvtReaderCallbacks)`

Deallocates a struct for the global event callbacks.

Parameters

| | |
|---------------------------------|--|
| <i>globalEvtReaderCallbacks</i> | Handle to a struct previously allocated with OTF2_GlobalEvtReaderCallbacks_New . |
|---------------------------------|--|

J.19 OTF2_GlobalEvtReaderCallbacks.h File Reference

J.19.3.3 `OTF2_GlobalEvtReaderCallbacks* OTF2_GlobalEvtReaderCallbacks_New (void)`

Allocates a new struct for the event callbacks.

Returns

A newly allocated struct of type [OTF2_GlobalEvtReaderCallbacks](#).

J.19.3.4 `OTF2_ErrorCode OTF2_GlobalEvtReaderCallbacks_SetBufferFlushCallback (OTF2_GlobalEvtReaderCallbacks * globalEvtReaderCallbacks, OTF2_GlobalEvtReaderCallback_BufferFlush bufferFlushCallback)`

Registers the callback for the BufferFlush event.

Parameters

| | |
|---------------------------------|---|
| <i>globalEvtReaderCallbacks</i> | Struct for all callbacks. |
| <i>bufferFlushCallback</i> | Function which should be called for all BufferFlush events. |

Returns

[OTF2_SUCCESS](#) if successful

[OTF2_ERROR_INVALID_ARGUMENT](#) for an invalid `defReaderCallbacks` argument

J.19.3.5 `OTF2_ErrorCode OTF2_GlobalEvtReaderCallbacks_SetEnterCallback (OTF2_GlobalEvtReaderCallbacks * globalEvtReaderCallbacks, OTF2_GlobalEvtReaderCallback_Enter enterCallback)`

Registers the callback for the Enter event.

Parameters

| | |
|---------------------------------|---|
| <i>globalEvtReaderCallbacks</i> | Struct for all callbacks. |
| <i>enterCallback</i> | Function which should be called for all Enter events. |

APPENDIX J. FILE DOCUMENTATION

Returns

OTF2_SUCCESS if successful

OTF2_ERROR_INVALID_ARGUMENT for an invalid `defReaderCallbacks` argument

J.19.3.6 **OTF2_ErrorCode** **OTF2_GlobalEvtReaderCallbacks_SetLeaveCallback**
(**OTF2_GlobalEvtReaderCallbacks** * *globalEvtReaderCallbacks*,
OTF2_GlobalEvtReaderCallback_Leave *leaveCallback*)

Registers the callback for the Leave event.

Parameters

| | |
|---------------------------------|---|
| <i>globalEvtReaderCallbacks</i> | Struct for all callbacks. |
| <i>leaveCallback</i> | Function which should be called for all Leave events. |

Returns

OTF2_SUCCESS if successful

OTF2_ERROR_INVALID_ARGUMENT for an invalid `defReaderCallbacks` argument

J.19.3.7 **OTF2_ErrorCode** **OTF2_GlobalEvtReaderCallbacks_SetMeasurementOnOffCallback** (**OTF2_GlobalEvtReaderCallbacks**
* *globalEvtReaderCallbacks*, **OTF2_GlobalEvtReaderCallback_MeasurementOnOff** *measurementOnOffCallback*
)

Registers the callback for the MeasurementOnOff event.

Parameters

| | |
|---------------------------------|--|
| <i>globalEvtReaderCallbacks</i> | Struct for all callbacks. |
| <i>measurementOnOffCallback</i> | Function which should be called for all MeasurementOnOff events. |

J.19 OTF2_GlobalEvtReaderCallbacks.h File Reference

Returns

OTF2_SUCCESS if successful

OTF2_ERROR_INVALID_ARGUMENT for an invalid `defReaderCallbacks` argument

J.19.3.8 **OTF2_ErrorCode** **OTF2_GlobalEvtReaderCallbacks_SetMetricCallback** (**OTF2_GlobalEvtReaderCallbacks** * *globalEvtReaderCallbacks*, **OTF2_GlobalEvtReaderCallback_Metric** *metricCallback*)

Registers the callback for the Metric event.

Parameters

| | |
|---------------------------------|--|
| <i>globalEvtReaderCallbacks</i> | Struct for all callbacks. |
| <i>metricCallback</i> | Function which should be called for all Metric events. |

Returns

OTF2_SUCCESS if successful

OTF2_ERROR_INVALID_ARGUMENT for an invalid `defReaderCallbacks` argument

J.19.3.9 **OTF2_ErrorCode** **OTF2_GlobalEvtReaderCallbacks_SetMpiCollectiveBeginCallback** (**OTF2_GlobalEvtReaderCallbacks** * *globalEvtReaderCallbacks*, **OTF2_GlobalEvtReaderCallback_MpiCollectiveBegin** *mpiCollectiveBeginCallback*)

Registers the callback for the MpiCollectiveBegin event.

Parameters

| | |
|-----------------------------------|--|
| <i>globalEvtReaderCallbacks</i> | Struct for all callbacks. |
| <i>mpiCollectiveBeginCallback</i> | Function which should be called for all MpiCollectiveBegin events. |

APPENDIX J. FILE DOCUMENTATION

Returns

OTF2_SUCCESS if successful

OTF2_ERROR_INVALID_ARGUMENT for an invalid `defReaderCallbacks` argument

J.19.3.10 **OTF2_ErrorCode** **OTF2_GlobalEvtReaderCallbacks**.
SetMpiCollectiveEndCallback (**OTF2_GlobalEvtReaderCallbacks**
* **globalEvtReaderCallbacks**, **OTF2_GlobalEvtReaderCallback**_
MpiCollectiveEnd **mpiCollectiveEndCallback**)

Registers the callback for the `MpiCollectiveEnd` event.

Parameters

| | |
|---------------------------------|---|
| <i>globalEvtReaderCallbacks</i> | Struct for all callbacks. |
| <i>mpiCollectiveEndCallback</i> | Function which should be called for all <code>MpiCollectiveEnd</code> events. |

Returns

OTF2_SUCCESS if successful

OTF2_ERROR_INVALID_ARGUMENT for an invalid `defReaderCallbacks` argument

J.19.3.11 **OTF2_ErrorCode** **OTF2_GlobalEvtReaderCallbacks**.
SetMpiIrecvCallback (**OTF2_GlobalEvtReaderCallbacks** * **globalEvtReaderCallbacks**,
OTF2_GlobalEvtReaderCallback_
MpiIrecv **mpiIrecvCallback**)

Registers the callback for the `MpiIrecv` event.

Parameters

| | |
|---------------------------------|---|
| <i>globalEvtReaderCallbacks</i> | Struct for all callbacks. |
| <i>mpiIrecvCallback</i> | Function which should be called for all <code>MpiIrecv</code> events. |

J.19 OTF2_GlobalEvtReaderCallbacks.h File Reference

Returns

OTF2_SUCCESS if successful

OTF2_ERROR_INVALID_ARGUMENT for an invalid `defReaderCallbacks` argument

J.19.3.12 OTF2_ErrorCode OTF2_GlobalEvtReaderCallbacks.SetMpiIrecvRequestCallback (**OTF2_GlobalEvtReaderCallbacks** * *globalEvtReaderCallbacks*, **OTF2_GlobalEvtReaderCallback_MpiIrecvRequest** *mpiIrecvRequestCallback*)

Registers the callback for the `MpiIrecvRequest` event.

Parameters

| | |
|---------------------------------|--|
| <i>globalEvtReaderCallbacks</i> | Struct for all callbacks. |
| <i>mpiIrecvRequestCallback</i> | Function which should be called for all <code>MpiIrecvRequest</code> events. |

Returns

OTF2_SUCCESS if successful

OTF2_ERROR_INVALID_ARGUMENT for an invalid `defReaderCallbacks` argument

J.19.3.13 OTF2_ErrorCode OTF2_GlobalEvtReaderCallbacks.SetMpisendCallback (**OTF2_GlobalEvtReaderCallbacks** * *globalEvtReaderCallbacks*, **OTF2_GlobalEvtReaderCallback_MpiSend** *mpisendCallback*)

Registers the callback for the `MpiSend` event.

Parameters

| | |
|---------------------------------|--|
| <i>globalEvtReaderCallbacks</i> | Struct for all callbacks. |
| <i>mpisendCallback</i> | Function which should be called for all <code>MpiSend</code> events. |

APPENDIX J. FILE DOCUMENTATION

Returns

OTF2_SUCCESS if successful

OTF2_ERROR_INVALID_ARGUMENT for an invalid `defReaderCallbacks` argument

J.19.3.14 **OTF2_ErrorCode** **OTF2_GlobalEvtReaderCallbacks** .-
SetMpiSendCompleteCallback (**OTF2_GlobalEvtReaderCallbacks**
* *globalEvtReaderCallbacks*, **OTF2_GlobalEvtReaderCallback**_-
MpiSendComplete *mpiSendCompleteCallback*
)

Registers the callback for the `MpiSendComplete` event.

Parameters

| | |
|---------------------------------|--|
| <i>globalEvtReaderCallbacks</i> | Struct for all callbacks. |
| <i>mpiSendCompleteCallback</i> | Function which should be called for all <code>MpiSendComplete</code> events. |

Returns

OTF2_SUCCESS if successful

OTF2_ERROR_INVALID_ARGUMENT for an invalid `defReaderCallbacks` argument

J.19.3.15 **OTF2_ErrorCode** **OTF2_GlobalEvtReaderCallbacks** .**SetMpiRecvCallback**
(**OTF2_GlobalEvtReaderCallbacks** * *globalEvtReaderCallbacks*,
OTF2_GlobalEvtReaderCallback_**MpiRecv** *mpiRecvCallback*)

Registers the callback for the `MpiRecv` event.

Parameters

| | |
|---------------------------------|--|
| <i>globalEvtReaderCallbacks</i> | Struct for all callbacks. |
| <i>mpiRecvCallback</i> | Function which should be called for all <code>MpiRecv</code> events. |

J.19 OTF2_GlobalEvtReaderCallbacks.h File Reference

Returns

OTF2_SUCCESS if successful

OTF2_ERROR_INVALID_ARGUMENT for an invalid `defReaderCallbacks` argument

J.19.3.16 **OTF2_ErrorCode** **OTF2_GlobalEvtReaderCallbacks** -
SetMpiRequestCancelledCallback (**OTF2_GlobalEvtReaderCallbacks**
* *globalEvtReaderCallbacks*, **OTF2_GlobalEvtReaderCallback** -
MpiRequestCancelled *mpiRequestCancelledCallback*
)

Registers the callback for the `MpiRequestCancelled` event.

Parameters

| | |
|------------------------------------|--|
| <i>globalEvtReaderCallbacks</i> | Struct for all callbacks. |
| <i>mpiRequestCancelledCallback</i> | Function which should be called for all <code>MpiRequestCancelled</code> events. |

Returns

OTF2_SUCCESS if successful

OTF2_ERROR_INVALID_ARGUMENT for an invalid `defReaderCallbacks` argument

J.19.3.17 **OTF2_ErrorCode** **OTF2_GlobalEvtReaderCallbacks** -
SetMpiRequestTestCallback (**OTF2_GlobalEvtReaderCallbacks** *
globalEvtReaderCallbacks, **OTF2_GlobalEvtReaderCallback** -
MpiRequestTest *mpiRequestTestCallback*)

Registers the callback for the `MpiRequestTest` event.

Parameters

| | |
|---------------------------------|---------------------------|
| <i>globalEvtReaderCallbacks</i> | Struct for all callbacks. |
|---------------------------------|---------------------------|

APPENDIX J. FILE DOCUMENTATION

| | |
|--------------------------------|--|
| <i>mpiRequestTest-Callback</i> | Function which should be called for all MpiRequestTest events. |
|--------------------------------|--|

Returns

OTF2_SUCCESS if successful

OTF2_ERROR_INVALID_ARGUMENT for an invalid defReaderCallbacks argument

J.19.3.18 **OTF2_StatusCode** **OTF2_GlobalEvtReaderCallbacks.SetMpiSendCallback** (**OTF2_GlobalEvtReaderCallbacks** * *globalEvtReaderCallbacks*, **OTF2_GlobalEvtReaderCallback_MpiSend** *mpiSendCallback*)

Registers the callback for the MpiSend event.

Parameters

| | |
|---------------------------------|---|
| <i>globalEvtReaderCallbacks</i> | Struct for all callbacks. |
| <i>mpiSend-Callback</i> | Function which should be called for all MpiSend events. |

Returns

OTF2_SUCCESS if successful

OTF2_ERROR_INVALID_ARGUMENT for an invalid defReaderCallbacks argument

J.19.3.19 **OTF2_StatusCode** **OTF2_GlobalEvtReaderCallbacks.SetOmpAcquireLockCallback** (**OTF2_GlobalEvtReaderCallbacks** * *globalEvtReaderCallbacks*, **OTF2_GlobalEvtReaderCallback_OmpAcquireLock** *ompAcquireLockCallback*)

Registers the callback for the OmpAcquireLock event.

Parameters

| | |
|---------------------------------|---------------------------|
| <i>globalEvtReaderCallbacks</i> | Struct for all callbacks. |
|---------------------------------|---------------------------|

J.19 OTF2_GlobalEvtReaderCallbacks.h File Reference

| | |
|-------------------------------|--|
| <i>ompAcquireLockCallback</i> | Function which should be called for all OmpAcquireLock events. |
|-------------------------------|--|

Returns

OTF2_SUCCESS if successful

OTF2_ERROR_INVALID_ARGUMENT for an invalid `defReaderCallbacks` argument

J.19.3.20 **OTF2_ErrorCode** **OTF2_GlobalEvtReaderCallbacks_SetOmpForkCallback**
(**OTF2_GlobalEvtReaderCallbacks** * *globalEvtReaderCallbacks*,
OTF2_GlobalEvtReaderCallback_OmpFork *ompForkCallback*)

Registers the callback for the OmpFork event.

Parameters

| | |
|---------------------------------|---|
| <i>globalEvtReaderCallbacks</i> | Struct for all callbacks. |
| <i>ompForkCallback</i> | Function which should be called for all OmpFork events. |

Returns

OTF2_SUCCESS if successful

OTF2_ERROR_INVALID_ARGUMENT for an invalid `defReaderCallbacks` argument

J.19.3.21 **OTF2_ErrorCode** **OTF2_GlobalEvtReaderCallbacks_SetOmpJoinCallback**
(**OTF2_GlobalEvtReaderCallbacks** * *globalEvtReaderCallbacks*,
OTF2_GlobalEvtReaderCallback_OmpJoin *ompJoinCallback*)

Registers the callback for the OmpJoin event.

Parameters

| | |
|---------------------------------|---------------------------|
| <i>globalEvtReaderCallbacks</i> | Struct for all callbacks. |
|---------------------------------|---------------------------|

APPENDIX J. FILE DOCUMENTATION

| | |
|-------------------------|---|
| <i>ompJoin-Callback</i> | Function which should be called for all OmpJoin events. |
|-------------------------|---|

Returns

OTF2_SUCCESS if successful

OTF2_ERROR_INVALID_ARGUMENT for an invalid `defReaderCallbacks` argument

J.19.3.22 **OTF2_ErrorCode** **OTF2_GlobalEvtReaderCallbacks_-SetOmpReleaseLockCallback** (**OTF2_GlobalEvtReaderCallbacks** * **globalEvtReaderCallbacks**, **OTF2_GlobalEvtReaderCallback_-OmpReleaseLock** **ompReleaseLockCallback**)

Registers the callback for the OmpReleaseLock event.

Parameters

| | |
|---------------------------------|--|
| <i>globalEvtReaderCallbacks</i> | Struct for all callbacks. |
| <i>ompReleaseLock-Callback</i> | Function which should be called for all OmpReleaseLock events. |

Returns

OTF2_SUCCESS if successful

OTF2_ERROR_INVALID_ARGUMENT for an invalid `defReaderCallbacks` argument

J.19.3.23 **OTF2_ErrorCode** **OTF2_GlobalEvtReaderCallbacks_-SetOmpTaskCompleteCallback** (**OTF2_GlobalEvtReaderCallbacks** * **globalEvtReaderCallbacks**, **OTF2_GlobalEvtReaderCallback_-OmpTaskComplete** **ompTaskCompleteCallback**)

Registers the callback for the OmpTaskComplete event.

Parameters

J.19 OTF2_GlobalEvtReaderCallbacks.h File Reference

| | |
|---------------------------------|---|
| <i>globalEvtReaderCallbacks</i> | Struct for all callbacks. |
| <i>ompTaskCompleteCallback</i> | Function which should be called for all OmpTaskComplete events. |

Returns

OTF2_SUCCESS if successful

OTF2_ERROR_INVALID_ARGUMENT for an invalid `defReaderCallbacks` argument

J.19.3.24 OTF2_ErrorCode OTF2_GlobalEvtReaderCallbacks - SetOmpTaskCreateCallback (OTF2_GlobalEvtReaderCallbacks * globalEvtReaderCallbacks, OTF2_GlobalEvtReaderCallback_ - OmpTaskCreate ompTaskCreateCallback)

Registers the callback for the OmpTaskCreate event.

Parameters

| | |
|---------------------------------|---|
| <i>globalEvtReaderCallbacks</i> | Struct for all callbacks. |
| <i>ompTaskCreateCallback</i> | Function which should be called for all OmpTaskCreate events. |

Returns

OTF2_SUCCESS if successful

OTF2_ERROR_INVALID_ARGUMENT for an invalid `defReaderCallbacks` argument

APPENDIX J. FILE DOCUMENTATION

J.19.3.25 **OTF2_ErrorCode** **OTF2_GlobalEvtReaderCallbacks_-SetOmpTaskSwitchCallback** (**OTF2_GlobalEvtReaderCallbacks** * **globalEvtReaderCallbacks**, **OTF2_GlobalEvtReaderCallback_-OmpTaskSwitch** **ompTaskSwitchCallback**)

Registers the callback for the OmpTaskSwitch event.

Parameters

| | |
|---------------------------------|---|
| <i>globalEvtReaderCallbacks</i> | Struct for all callbacks. |
| <i>ompTaskSwitchCallback</i> | Function which should be called for all OmpTaskSwitch events. |

Returns

OTF2_SUCCESS if successful

OTF2_ERROR_INVALID_ARGUMENT for an invalid `defReaderCallbacks` argument

J.19.3.26 **OTF2_ErrorCode** **OTF2_GlobalEvtReaderCallbacks_SetParameterIntCallback** (**OTF2_GlobalEvtReaderCallbacks** * **globalEvtReaderCallbacks**, **OTF2_GlobalEvtReaderCallback_ParameterInt** **parameterIntCallback**)

Registers the callback for the ParameterInt event.

Parameters

| | |
|---------------------------------|--|
| <i>globalEvtReaderCallbacks</i> | Struct for all callbacks. |
| <i>parameterIntCallback</i> | Function which should be called for all ParameterInt events. |

Returns

OTF2_SUCCESS if successful

OTF2_ERROR_INVALID_ARGUMENT for an invalid `defReaderCallbacks` argument

J.19 OTF2_GlobalEvtReaderCallbacks.h File Reference

J.19.3.27 **OTF2_***ErrorCode* **OTF2_GlobalEvtReaderCallbacks_**-
SetParameterStringCallback (**OTF2_GlobalEvtReaderCallbacks** *
globalEvtReaderCallbacks, **OTF2_GlobalEvtReaderCallback_**-
ParameterString *parameterStringCallback*)

Registers the callback for the ParameterString event.

Parameters

| | |
|---------------------------------|---|
| <i>globalEvtReaderCallbacks</i> | Struct for all callbacks. |
| <i>parameterStringCallback</i> | Function which should be called for all ParameterString events. |

Returns

OTF2_SUCCESS if successful

OTF2_ERROR_INVALID_ARGUMENT for an invalid `defReaderCallbacks` argument

J.19.3.28 **OTF2_***ErrorCode* **OTF2_GlobalEvtReaderCallbacks_**-
SetParameterUnsignedIntCallback (**OTF2_GlobalEvtReaderCallbacks** *
globalEvtReaderCallbacks, **OTF2_GlobalEvtReaderCallback_**-
ParameterUnsignedInt *parameterUnsignedIntCallback*)

Registers the callback for the ParameterUnsignedInt event.

Parameters

| | |
|-------------------------------------|--|
| <i>globalEvtReaderCallbacks</i> | Struct for all callbacks. |
| <i>parameterUnsignedIntCallback</i> | Function which should be called for all ParameterUnsignedInt events. |

Returns

OTF2_SUCCESS if successful

OTF2_ERROR_INVALID_ARGUMENT for an invalid `defReaderCallbacks`

argument

J.19.3.29 **OTF2_ErrorCode** **OTF2_GlobalEvtReaderCallbacks** .-
SetRmaAcquireLockCallback (**OTF2_GlobalEvtReaderCallbacks**
* *globalEvtReaderCallbacks*, **OTF2_GlobalEvtReaderCallback**_-
RmaAcquireLock *rmaAcquireLockCallback*)

Registers the callback for the RmaAcquireLock event.

Parameters

| | |
|---------------------------------|--|
| <i>globalEvtReaderCallbacks</i> | Struct for all callbacks. |
| <i>rmaAcquireLockCallback</i> | Function which should be called for all RmaAcquireLock events. |

Returns

OTF2_SUCCESS if successful

OTF2_ERROR_INVALID_ARGUMENT for an invalid defReaderCallbacks argument

J.19.3.30 **OTF2_ErrorCode** **OTF2_GlobalEvtReaderCallbacks** .**SetRmaAtomicCallback**
(**OTF2_GlobalEvtReaderCallbacks** * *globalEvtReaderCallbacks*,
OTF2_GlobalEvtReaderCallback_RmaAtomic *rmaAtomicCallback*)

Registers the callback for the RmaAtomic event.

Parameters

| | |
|---------------------------------|---|
| <i>globalEvtReaderCallbacks</i> | Struct for all callbacks. |
| <i>rmaAtomicCallback</i> | Function which should be called for all RmaAtomic events. |

Returns

OTF2_SUCCESS if successful

OTF2_ERROR_INVALID_ARGUMENT for an invalid defReaderCallbacks

J.19 OTF2_GlobalEvtReaderCallbacks.h File Reference

argument

J.19.331 **OTF2_ErrorCode** **OTF2_GlobalEvtReaderCallbacks** -
SetRmaCollectiveBeginCallback (OTF2_GlobalEvtReaderCallbacks
*** globalEvtReaderCallbacks, OTF2_GlobalEvtReaderCallback_-**
RmaCollectiveBegin rmaCollectiveBeginCallback
)

Registers the callback for the RmaCollectiveBegin event.

Parameters

| | |
|-----------------------------------|--|
| <i>globalEvtReaderCallbacks</i> | Struct for all callbacks. |
| <i>rmaCollectiveBeginCallback</i> | Function which should be called for all RmaCollectiveBegin events. |

Returns

OTF2_SUCCESS if successful

OTF2_ERROR_INVALID_ARGUMENT for an invalid `defReaderCallbacks` argument

J.19.332 **OTF2_ErrorCode** **OTF2_GlobalEvtReaderCallbacks** -
SetRmaCollectiveEndCallback (OTF2_GlobalEvtReaderCallbacks
*** globalEvtReaderCallbacks, OTF2_GlobalEvtReaderCallback_-**
RmaCollectiveEnd rmaCollectiveEndCallback)

Registers the callback for the RmaCollectiveEnd event.

Parameters

| | |
|---------------------------------|--|
| <i>globalEvtReaderCallbacks</i> | Struct for all callbacks. |
| <i>rmaCollectiveEndCallback</i> | Function which should be called for all RmaCollectiveEnd events. |

APPENDIX J. FILE DOCUMENTATION

Returns

OTF2_SUCCESS if successful

OTF2_ERROR_INVALID_ARGUMENT for an invalid `defReaderCallbacks` argument

J.19.3.33 **OTF2_StatusCode** `OTF2_GlobalEvtReaderCallbacks_SetRmaGetCallback`
(**OTF2_GlobalEvtReaderCallbacks** * *globalEvtReaderCallbacks*,
OTF2_GlobalEvtReaderCallback_RmaGet *rmaGetCallback*)

Registers the callback for the RmaGet event.

Parameters

| | |
|---------------------------------|--|
| <i>globalEvtReaderCallbacks</i> | Struct for all callbacks. |
| <i>rmaGetCallback</i> | Function which should be called for all RmaGet events. |

Returns

OTF2_SUCCESS if successful

OTF2_ERROR_INVALID_ARGUMENT for an invalid `defReaderCallbacks` argument

J.19.3.34 **OTF2_StatusCode** `OTF2_GlobalEvtReaderCallbacks_SetRmaGroupSyncCallback`
(**OTF2_GlobalEvtReaderCallbacks** *
globalEvtReaderCallbacks, **OTF2_GlobalEvtReaderCallback_-RmaGroupSync** *rmaGroupSyncCallback*)

Registers the callback for the RmaGroupSync event.

Parameters

| | |
|---------------------------------|--|
| <i>globalEvtReaderCallbacks</i> | Struct for all callbacks. |
| <i>rmaGroupSyncCallback</i> | Function which should be called for all RmaGroupSync events. |

J.19 OTF2_GlobalEvtReaderCallbacks.h File Reference

Returns

OTF2_SUCCESS if successful

OTF2_ERROR_INVALID_ARGUMENT for an invalid `defReaderCallbacks` argument

J.19.35 **OTF2_StatusCode** **OTF2_GlobalEvtReaderCallbacks** -
SetRmaOpCompleteBlockingCallback (**OTF2_GlobalEvtReaderCallbacks**
* *globalEvtReaderCallbacks*, **OTF2_GlobalEvtReaderCallback** -
RmaOpCompleteBlocking *rmaOpCompleteBlockingCallback*
)

Registers the callback for the `RmaOpCompleteBlocking` event.

Parameters

| | |
|--------------------------------------|--|
| <i>globalEvtReaderCallbacks</i> | Struct for all callbacks. |
| <i>rmaOpCompleteBlockingCallback</i> | Function which should be called for all <code>RmaOpCompleteBlocking</code> events. |

Returns

OTF2_SUCCESS if successful

OTF2_ERROR_INVALID_ARGUMENT for an invalid `defReaderCallbacks` argument

J.19.36 **OTF2_StatusCode** **OTF2_GlobalEvtReaderCallbacks** -
SetRmaOpCompleteNonBlockingCallback (**OTF2** -
GlobalEvtReaderCallbacks * *globalEvtReaderCallbacks*,
OTF2_GlobalEvtReaderCallback_RmaOpCompleteNonBlocking
rmaOpCompleteNonBlockingCallback)

Registers the callback for the `RmaOpCompleteNonBlocking` event.

Parameters

| | |
|---------------------------------|---------------------------|
| <i>globalEvtReaderCallbacks</i> | Struct for all callbacks. |
|---------------------------------|---------------------------|

APPENDIX J. FILE DOCUMENTATION

| | |
|--|--|
| <i>rmaOp-CompleteNon-Blocking-Callback</i> | Function which should be called for all RmaOpCompleteNonBlocking events. |
|--|--|

Returns

OTF2_SUCCESS if successful

OTF2_ERROR_INVALID_ARGUMENT for an invalid `defReaderCallbacks` argument

J.19.3.37 **OTF2_StatusCode** **OTF2_GlobalEvtReaderCallbacks** **SetRmaOpCompleteRemoteCallback** (**OTF2_GlobalEvtReaderCallbacks** * **globalEvtReaderCallbacks**, **OTF2_GlobalEvtReaderCallback** * **RmaOpCompleteRemote** **rmaOpCompleteRemoteCallback**)

Registers the callback for the RmaOpCompleteRemote event.

Parameters

| | |
|--------------------------------------|---|
| <i>globalEvtReaderCallbacks</i> | Struct for all callbacks. |
| <i>rmaOp-CompleteRemote-Callback</i> | Function which should be called for all RmaOpCompleteRemote events. |

Returns

OTF2_SUCCESS if successful

OTF2_ERROR_INVALID_ARGUMENT for an invalid `defReaderCallbacks` argument

J.19.3.38 **OTF2_StatusCode** **OTF2_GlobalEvtReaderCallbacks** **SetRmaOpTestCallback** (**OTF2_GlobalEvtReaderCallbacks** * **globalEvtReaderCallbacks**, **OTF2_GlobalEvtReaderCallback** * **RmaOpTest** **rmaOpTestCallback**)

Registers the callback for the RmaOpTest event.

J.19 OTF2_GlobalEvtReaderCallbacks.h File Reference

Parameters

| | |
|---------------------------------|---|
| <i>globalEvtReaderCallbacks</i> | Struct for all callbacks. |
| <i>rmaOpTestCallback</i> | Function which should be called for all RmaOpTest events. |

Returns

OTF2_SUCCESS if successful

OTF2_ERROR_INVALID_ARGUMENT for an invalid `defReaderCallbacks` argument

J.19.3.39 **OTF2_StatusCode** `OTF2_GlobalEvtReaderCallbacks_SetRmaPutCallback (OTF2_GlobalEvtReaderCallbacks * globalEvtReaderCallbacks, OTF2_GlobalEvtReaderCallback_RmaPut rmaPutCallback)`

Registers the callback for the RmaPut event.

Parameters

| | |
|---------------------------------|--|
| <i>globalEvtReaderCallbacks</i> | Struct for all callbacks. |
| <i>rmaPutCallback</i> | Function which should be called for all RmaPut events. |

Returns

OTF2_SUCCESS if successful

OTF2_ERROR_INVALID_ARGUMENT for an invalid `defReaderCallbacks` argument

J.19.3.40 **OTF2_StatusCode** `OTF2_GlobalEvtReaderCallbacks_SetRmaReleaseLockCallback (OTF2_GlobalEvtReaderCallbacks * globalEvtReaderCallbacks, OTF2_GlobalEvtReaderCallback_RmaReleaseLock rmaReleaseLockCallback)`

Registers the callback for the RmaReleaseLock event.

Parameters

APPENDIX J. FILE DOCUMENTATION

| | |
|---------------------------------|--|
| <i>globalEvtReaderCallbacks</i> | Struct for all callbacks. |
| <i>rmaReleaseLockCallback</i> | Function which should be called for all RmaReleaseLock events. |

Returns

OTF2_SUCCESS if successful

OTF2_ERROR_INVALID_ARGUMENT for an invalid `defReaderCallbacks` argument

J.19.3.41 **OTF2_StatusCode** **OTF2_GlobalEvtReaderCallbacks_SetRmaRequestLockCallback** (**OTF2_GlobalEvtReaderCallbacks** * *globalEvtReaderCallbacks*, **OTF2_GlobalEvtReaderCallback_RmaRequestLock** *rmaRequestLockCallback*)

Registers the callback for the RmaRequestLock event.

Parameters

| | |
|---------------------------------|--|
| <i>globalEvtReaderCallbacks</i> | Struct for all callbacks. |
| <i>rmaRequestLockCallback</i> | Function which should be called for all RmaRequestLock events. |

Returns

OTF2_SUCCESS if successful

OTF2_ERROR_INVALID_ARGUMENT for an invalid `defReaderCallbacks` argument

J.19.3.42 **OTF2_StatusCode** **OTF2_GlobalEvtReaderCallbacks_SetRmaSyncCallback** (**OTF2_GlobalEvtReaderCallbacks** * *globalEvtReaderCallbacks*, **OTF2_GlobalEvtReaderCallback_RmaSync** *rmaSyncCallback*)

Registers the callback for the RmaSync event.

J.19 OTF2_GlobalEvtReaderCallbacks.h File Reference

Parameters

| | |
|---------------------------------|---|
| <i>globalEvtReaderCallbacks</i> | Struct for all callbacks. |
| <i>rmaSyncCallback</i> | Function which should be called for all RmaSync events. |

Returns

OTF2_SUCCESS if successful

OTF2_ERROR_INVALID_ARGUMENT for an invalid `defReaderCallbacks` argument

J.19.3.43 **OTF2_StatusCode** **OTF2_GlobalEvtReaderCallbacks_SetRmaTryLockCallback** (**OTF2_GlobalEvtReaderCallbacks** * *globalEvtReaderCallbacks*, **OTF2_GlobalEvtReaderCallback_RmaTryLock** *rmaTryLockCallback*)

Registers the callback for the RmaTryLock event.

Parameters

| | |
|---------------------------------|--|
| <i>globalEvtReaderCallbacks</i> | Struct for all callbacks. |
| <i>rmaTryLockCallback</i> | Function which should be called for all RmaTryLock events. |

Returns

OTF2_SUCCESS if successful

OTF2_ERROR_INVALID_ARGUMENT for an invalid `defReaderCallbacks` argument

J.19.3.44 **OTF2_StatusCode** **OTF2_GlobalEvtReaderCallbacks_SetRmaWaitChangeCallback** (**OTF2_GlobalEvtReaderCallbacks** * *globalEvtReaderCallbacks*, **OTF2_GlobalEvtReaderCallback_RmaWaitChange** *rmaWaitChangeCallback*)

Registers the callback for the RmaWaitChange event.

APPENDIX J. FILE DOCUMENTATION

Parameters

| | |
|---------------------------------|---|
| <i>globalEvtReaderCallbacks</i> | Struct for all callbacks. |
| <i>rmaWaitChangeCallback</i> | Function which should be called for all RmaWaitChange events. |

Returns

OTF2_SUCCESS if successful

OTF2_ERROR_INVALID_ARGUMENT for an invalid `defReaderCallbacks` argument

J.19.3.45 **OTF2_ErrorCode** **OTF2_GlobalEvtReaderCallbacks_**
**SetRmaWinCreateCallback (OTF2_GlobalEvtReaderCallbacks *
globalEvtReaderCallbacks, OTF2_GlobalEvtReaderCallback_ -
RmaWinCreate rmaWinCreateCallback)**

Registers the callback for the RmaWinCreate event.

Parameters

| | |
|---------------------------------|--|
| <i>globalEvtReaderCallbacks</i> | Struct for all callbacks. |
| <i>rmaWinCreateCallback</i> | Function which should be called for all RmaWinCreate events. |

Returns

OTF2_SUCCESS if successful

OTF2_ERROR_INVALID_ARGUMENT for an invalid `defReaderCallbacks` argument

J.19.3.46 **OTF2_ErrorCode** **OTF2_GlobalEvtReaderCallbacks_**
**SetRmaWinDestroyCallback (OTF2_GlobalEvtReaderCallbacks *
globalEvtReaderCallbacks, OTF2_GlobalEvtReaderCallback_ -
RmaWinDestroy rmaWinDestroyCallback)**

Registers the callback for the RmaWinDestroy event.

J.19 OTF2_GlobalEvtReaderCallbacks.h File Reference

Parameters

| | |
|---------------------------------|---|
| <i>globalEvtReaderCallbacks</i> | Struct for all callbacks. |
| <i>rmaWinDestroyCallback</i> | Function which should be called for all RmaWinDestroy events. |

Returns

OTF2_SUCCESS if successful

OTF2_ERROR_INVALID_ARGUMENT for an invalid `defReaderCallbacks` argument

J.19.3.47 **OTF2_ErrorCode** **OTF2_GlobalEvtReaderCallbacks_SetThreadAcquireLockCallback** (**OTF2_GlobalEvtReaderCallbacks** * *globalEvtReaderCallbacks*, **OTF2_GlobalEvtReaderCallback_ThreadAcquireLock** *threadAcquireLockCallback*)

Registers the callback for the ThreadAcquireLock event.

Parameters

| | |
|----------------------------------|---|
| <i>globalEvtReaderCallbacks</i> | Struct for all callbacks. |
| <i>threadAcquireLockCallback</i> | Function which should be called for all ThreadAcquireLock events. |

Returns

OTF2_SUCCESS if successful

OTF2_ERROR_INVALID_ARGUMENT for an invalid `defReaderCallbacks` argument

J.19.3.48 **OTF2_ErrorCode** **OTF2_GlobalEvtReaderCallbacks_SetThreadForkCallback** (**OTF2_GlobalEvtReaderCallbacks** * *globalEvtReaderCallbacks*, **OTF2_GlobalEvtReaderCallback_ThreadFork** *threadForkCallback*)

Registers the callback for the ThreadFork event.

APPENDIX J. FILE DOCUMENTATION

Parameters

| | |
|---------------------------------|--|
| <i>globalEvtReaderCallbacks</i> | Struct for all callbacks. |
| <i>threadForkCallback</i> | Function which should be called for all ThreadFork events. |

Returns

OTF2_SUCCESS if successful

OTF2_ERROR_INVALID_ARGUMENT for an invalid `defReaderCallbacks` argument

J.19.3.49 **OTF2_StatusCode** `OTF2_GlobalEvtReaderCallbacks.SetThreadJoinCallback (OTF2_GlobalEvtReaderCallbacks * globalEvtReaderCallbacks, OTF2_GlobalEvtReaderCallback_ThreadJoin threadJoinCallback)`

Registers the callback for the ThreadJoin event.

Parameters

| | |
|---------------------------------|--|
| <i>globalEvtReaderCallbacks</i> | Struct for all callbacks. |
| <i>threadJoinCallback</i> | Function which should be called for all ThreadJoin events. |

Returns

OTF2_SUCCESS if successful

OTF2_ERROR_INVALID_ARGUMENT for an invalid `defReaderCallbacks` argument

J.19.3.50 **OTF2_StatusCode** `OTF2_GlobalEvtReaderCallbacks.-SetThreadReleaseLockCallback (OTF2_GlobalEvtReaderCallbacks * globalEvtReaderCallbacks, OTF2_GlobalEvtReaderCallback_ThreadReleaseLock threadReleaseLockCallback)`

Registers the callback for the ThreadReleaseLock event.

J.19 OTF2_GlobalEvtReaderCallbacks.h File Reference

Parameters

| | |
|----------------------------------|---|
| <i>globalEvtReaderCallbacks</i> | Struct for all callbacks. |
| <i>threadReleaseLockCallback</i> | Function which should be called for all ThreadReleaseLock events. |

Returns

OTF2_SUCCESS if successful

OTF2_ERROR_INVALID_ARGUMENT for an invalid `defReaderCallbacks` argument

J.19.3.51 **OTF2_ErrorCode** **OTF2_GlobalEvtReaderCallbacks.-**
SetThreadTaskCompleteCallback (**OTF2_GlobalEvtReaderCallbacks**
*** *globalEvtReaderCallbacks*, OTF2_GlobalEvtReaderCallback_-**
ThreadTaskComplete *threadTaskCompleteCallback*
)

Registers the callback for the ThreadTaskComplete event.

Parameters

| | |
|-----------------------------------|--|
| <i>globalEvtReaderCallbacks</i> | Struct for all callbacks. |
| <i>threadTaskCompleteCallback</i> | Function which should be called for all ThreadTaskComplete events. |

Returns

OTF2_SUCCESS if successful

OTF2_ERROR_INVALID_ARGUMENT for an invalid `defReaderCallbacks` argument

APPENDIX J. FILE DOCUMENTATION

J.19.3.52 **OTF2_ErrorCode** **OTF2_GlobalEvtReaderCallbacks_-SetThreadTaskCreateCallback** (**OTF2_GlobalEvtReaderCallbacks** * **globalEvtReaderCallbacks**, **OTF2_GlobalEvtReaderCallback_-ThreadTaskCreate** **threadTaskCreateCallback**)

Registers the callback for the ThreadTaskCreate event.

Parameters

| | |
|---------------------------------|--|
| <i>globalEvtReaderCallbacks</i> | Struct for all callbacks. |
| <i>threadTaskCreateCallback</i> | Function which should be called for all ThreadTaskCreate events. |

Returns

OTF2_SUCCESS if successful

OTF2_ERROR_INVALID_ARGUMENT for an invalid defReaderCallbacks argument

J.19.3.53 **OTF2_ErrorCode** **OTF2_GlobalEvtReaderCallbacks_-SetThreadTaskSwitchCallback** (**OTF2_GlobalEvtReaderCallbacks** * **globalEvtReaderCallbacks**, **OTF2_GlobalEvtReaderCallback_-ThreadTaskSwitch** **threadTaskSwitchCallback**)

Registers the callback for the ThreadTaskSwitch event.

Parameters

| | |
|---------------------------------|--|
| <i>globalEvtReaderCallbacks</i> | Struct for all callbacks. |
| <i>threadTaskSwitchCallback</i> | Function which should be called for all ThreadTaskSwitch events. |

Returns

OTF2_SUCCESS if successful

OTF2_ERROR_INVALID_ARGUMENT for an invalid defReaderCallbacks argument

J.19 OTF2_GlobalEvtReaderCallbacks.h File Reference

J.19.3.54 OTF2_StatusCode OTF2_GlobalEvtReaderCallbacks - SetThreadTeamBeginCallback (OTF2_GlobalEvtReaderCallbacks * *globalEvtReaderCallbacks*, OTF2_GlobalEvtReaderCallback_ - ThreadTeamBegin *threadTeamBeginCallback*)

Registers the callback for the ThreadTeamBegin event.

Parameters

| | |
|---------------------------------|---|
| <i>globalEvtReaderCallbacks</i> | Struct for all callbacks. |
| <i>threadTeamBeginCallback</i> | Function which should be called for all ThreadTeamBegin events. |

Returns

OTF2_SUCCESS if successful

OTF2_ERROR_INVALID_ARGUMENT for an invalid *defReaderCallbacks* argument

J.19.3.55 OTF2_StatusCode OTF2_GlobalEvtReaderCallbacks - SetThreadTeamEndCallback (OTF2_GlobalEvtReaderCallbacks * *globalEvtReaderCallbacks*, OTF2_GlobalEvtReaderCallback_ - ThreadTeamEnd *threadTeamEndCallback*)

Registers the callback for the ThreadTeamEnd event.

Parameters

| | |
|---------------------------------|---|
| <i>globalEvtReaderCallbacks</i> | Struct for all callbacks. |
| <i>threadTeamEndCallback</i> | Function which should be called for all ThreadTeamEnd events. |

Returns

OTF2_SUCCESS if successful

OTF2_ERROR_INVALID_ARGUMENT for an invalid *defReaderCallbacks* argument

J.19.3.56 OTF2_StatusCode OTF2_GlobalEvtReaderCallbacks_SetUnknownCallback (OTF2_GlobalEvtReaderCallbacks * globalEvtReaderCallbacks, OTF2_GlobalEvtReaderCallback_Unknown unknownCallback)

Registers the callback for unknown events.

Parameters

| | |
|---------------------------------|---|
| <i>globalEvtReaderCallbacks</i> | Struct for all callbacks. |
| <i>unknownCallback</i> | Function which should be called for all unknown events. |

Returns

- OTF2_SUCCESS* if successful
- OTF2_ERROR_INVALID_ARGUMENT* for an invalid defReaderCallbacks argument

J.20 OTF2_GlobalSnapReader.h File Reference

This is the global snapshot event reader.

```
#include <stdint.h>
#include <otf2/OTF2_ErrorCodes.h>
#include <otf2/OTF2_SnapReader.h>
#include <otf2/OTF2_GlobalSnapReaderCallbacks.h>
```

Functions

- [OTF2_StatusCode OTF2_GlobalSnapReader_ReadSnapshots \(OTF2_GlobalSnapReader *reader, uint64_t recordsToRead, uint64_t *recordsRead\)](#)
Reads the given number of records from the global snap event reader.
- [OTF2_StatusCode OTF2_GlobalSnapReader_SetCallbacks \(OTF2_GlobalSnapReader *reader, const OTF2_GlobalSnapReaderCallbacks *callbacks, void *userData\)](#)

Sets the callback functions for the given reader object. Everytime when OTF2 reads a record, a callback function is called and the records data is passed to this function. Therefore the programmer needs to set function pointers at the "callbacks" struct for the record type he wants to read.

J.20 OTF2_GlobalSnapReader.h File Reference

J.20.1 Detailed Description

This is the global snapshot event reader.

Since

Version 1.2

Used to read from multiple local snap event readers, and provide them in a timely ordered sequence.

J.20.2 Function Documentation

J.20.2.1 OTF2_ErrorCode OTF2_GlobalSnapReader_ReadSnapshots (OTF2_GlobalSnapReader * reader, uint64_t recordsToRead, uint64_t * recordsRead)

Reads the given number of records from the global snap event reader.

Parameters

| | | |
|-----|----------------------|--|
| | <i>reader</i> | The records of this reader will be read when the function is issued. |
| | <i>recordsToRead</i> | This variable tells the reader how much records it has to read. |
| out | <i>recordsRead</i> | This is a pointer to variable where the amount of actually read records is returned. This may differ to the given recordsToRead if there are no more records left in the trace. In this case the programmer can easily check that the reader has finished his job by checking recordsRead < recordsToRead. |

Since

Version 1.2

Returns

OTF2_SUCCESS if successful, an error code if an error occurs.

J.20.2.2 OTF2_ErrorCode OTF2_GlobalSnapReader_SetCallbacks (OTF2_GlobalSnapReader * reader, const OTF2_GlobalSnapReaderCallbacks * callbacks, void * userData)

Sets the callback functions for the given reader object. Everytime when OTF2 reads a record, a callback function is called and the records data is passed to this function.

APPENDIX J. FILE DOCUMENTATION

Therefore the programmer needs to set function pointers at the "callbacks" struct for the record type he wants to read.

Parameters

| | |
|------------------|--|
| <i>reader</i> | Reader object which reads the snap events from its buffer. |
| <i>callbacks</i> | Struct which holds a function pointer for each record type. OTF2_GlobalSnapReaderCallbacks_New . |
| <i>userData</i> | Data passed as argument <i>userData</i> to the record callbacks. |

Since

Version 1.2

Returns

[OTF2_SUCCESS](#) if successful, an error code if an error occurs.

J.21 OTF2_GlobalSnapReaderCallbacks.h File Reference

This defines the callbacks for the global snap reader.

```
#include <stdint.h>
#include <otf2/OTF2_ErrorCodes.h>
#include <otf2/OTF2_GeneralDefinitions.h>
#include <otf2/OTF2_AttributeList.h>
#include <otf2/OTF2_Events.h>
```

Typedefs

- typedef [OTF2_CallbackCode](#)(* [OTF2_GlobalSnapReaderCallback_Enter](#))([OTF2_LocationRef](#) locationID, [OTF2_TimeStamp](#) snapTime, void *userData, [OTF2_AttributeList](#) *attributeList, [OTF2_TimeStamp](#) origEventTime, [OTF2_RegionRef](#) region)
Callback for the Enter snap record.
- typedef [OTF2_CallbackCode](#)(* [OTF2_GlobalSnapReaderCallback_MeasurementOnOff](#))([OTF2_LocationRef](#) locationID, [OTF2_TimeStamp](#) snapTime, void *userData, [OTF2_AttributeList](#) *attributeList, [OTF2_TimeStamp](#) origEventTime, [OTF2_MeasurementMode](#) measurementMode)
Callback for the MeasurementOnOff snap record.

J.21 OTF2_GlobalSnapReaderCallbacks.h File Reference

- typedef OTF2_CallbackCode(* OTF2_GlobalSnapReaderCallback_Metric)(OTF2_LocationRef locationID, OTF2_TimeStamp snapTime, void *userData, OTF2_AttributeList *attributeList, OTF2_TimeStamp origEventTime, OTF2_MetricRef metric, uint8_t numberOfMetrics, const OTF2_Type *typeIDs, const OTF2_MetricValue *metricValues)
Callback for the Metric snap record.
- typedef OTF2_CallbackCode(* OTF2_GlobalSnapReaderCallback_MpiCollectiveBegin)(OTF2_LocationRef locationID, OTF2_TimeStamp snapTime, void *userData, OTF2_AttributeList *attributeList, OTF2_TimeStamp origEventTime)
Callback for the MpiCollectiveBegin snap record.
- typedef OTF2_CallbackCode(* OTF2_GlobalSnapReaderCallback_MpiCollectiveEnd)(OTF2_LocationRef locationID, OTF2_TimeStamp snapTime, void *userData, OTF2_AttributeList *attributeList, OTF2_TimeStamp origEventTime, OTF2_CollectiveOp collectiveOp, OTF2_CommRef communicator, uint32_t root, uint64_t sizeSent, uint64_t sizeReceived)
Callback for the MpiCollectiveEnd snap record.
- typedef OTF2_CallbackCode(* OTF2_GlobalSnapReaderCallback_MpiIrecv)(OTF2_LocationRef locationID, OTF2_TimeStamp snapTime, void *userData, OTF2_AttributeList *attributeList, OTF2_TimeStamp origEventTime, uint32_t sender, OTF2_CommRef communicator, uint32_t msgTag, uint64_t msgLength, uint64_t requestID)
Callback for the MpiIrecv snap record.
- typedef OTF2_CallbackCode(* OTF2_GlobalSnapReaderCallback_MpiIrecvRequest)(OTF2_LocationRef locationID, OTF2_TimeStamp snapTime, void *userData, OTF2_AttributeList *attributeList, OTF2_TimeStamp origEventTime, uint64_t requestID)
Callback for the MpiIrecvRequest snap record.
- typedef OTF2_CallbackCode(* OTF2_GlobalSnapReaderCallback_MpiIsend)(OTF2_LocationRef locationID, OTF2_TimeStamp snapTime, void *userData, OTF2_AttributeList *attributeList, OTF2_TimeStamp origEventTime, uint32_t receiver, OTF2_CommRef communicator, uint32_t msgTag, uint64_t msgLength, uint64_t requestID)
Callback for the MpiIsend snap record.
- typedef OTF2_CallbackCode(* OTF2_GlobalSnapReaderCallback_MpiIsendComplete)(OTF2_LocationRef locationID, OTF2_TimeStamp snapTime, void *userData, OTF2_AttributeList *attributeList, OTF2_TimeStamp origEventTime, uint64_t requestID)

APPENDIX J. FILE DOCUMENTATION

Callback for the `MpiSendComplete` snap record.

- typedef `OTF2_CallbackCode(* OTF2_GlobalSnapReaderCallback_MpiRecv)`(`OTF2_LocationRef` locationID, `OTF2_TimeStamp` snapTime, void *userData, `OTF2_AttributeList` *attributeList, `OTF2_TimeStamp` origEventTime, uint32_t sender, `OTF2_CommRef` communicator, uint32_t msgTag, uint64_t msgLength)

Callback for the `MpiRecv` snap record.

- typedef `OTF2_CallbackCode(* OTF2_GlobalSnapReaderCallback_MpiSend)`(`OTF2_LocationRef` locationID, `OTF2_TimeStamp` snapTime, void *userData, `OTF2_AttributeList` *attributeList, `OTF2_TimeStamp` origEventTime, uint32_t receiver, `OTF2_CommRef` communicator, uint32_t msgTag, uint64_t msgLength)

Callback for the `MpiSend` snap record.

- typedef `OTF2_CallbackCode(* OTF2_GlobalSnapReaderCallback_OmpAcquireLock)`(`OTF2_LocationRef` locationID, `OTF2_TimeStamp` snapTime, void *userData, `OTF2_AttributeList` *attributeList, `OTF2_TimeStamp` origEventTime, uint32_t lockID, uint32_t acquisitionOrder)

Callback for the `OmpAcquireLock` snap record.

- typedef `OTF2_CallbackCode(* OTF2_GlobalSnapReaderCallback_OmpFork)`(`OTF2_LocationRef` locationID, `OTF2_TimeStamp` snapTime, void *userData, `OTF2_AttributeList` *attributeList, `OTF2_TimeStamp` origEventTime, uint32_t numberOfRequestedThreads)

Callback for the `OmpFork` snap record.

- typedef `OTF2_CallbackCode(* OTF2_GlobalSnapReaderCallback_OmpTaskCreate)`(`OTF2_LocationRef` locationID, `OTF2_TimeStamp` snapTime, void *userData, `OTF2_AttributeList` *attributeList, `OTF2_TimeStamp` origEventTime, uint64_t taskID)

Callback for the `OmpTaskCreate` snap record.

- typedef `OTF2_CallbackCode(* OTF2_GlobalSnapReaderCallback_OmpTaskSwitch)`(`OTF2_LocationRef` locationID, `OTF2_TimeStamp` snapTime, void *userData, `OTF2_AttributeList` *attributeList, `OTF2_TimeStamp` origEventTime, uint64_t taskID)

Callback for the `OmpTaskSwitch` snap record.

- typedef `OTF2_CallbackCode(* OTF2_GlobalSnapReaderCallback_ParameterInt)`(`OTF2_LocationRef` locationID, `OTF2_TimeStamp` snapTime, void *userData,

J.21 OTF2_GlobalSnapReaderCallbacks.h File Reference

[OTF2_AttributeList](#) *attributeList, [OTF2_TimeStamp](#) origEventTime, [OTF2_ParameterRef](#) parameter, int64_t value)

Callback for the ParameterInt snap record.

- typedef [OTF2_CallbackCode](#)(* [OTF2_GlobalSnapReaderCallback_ParameterString](#))([OTF2_LocationRef](#) locationID, [OTF2_TimeStamp](#) snapTime, void *userData, [OTF2_AttributeList](#) *attributeList, [OTF2_TimeStamp](#) origEventTime, [OTF2_ParameterRef](#) parameter, [OTF2_StringRef](#) string)

Callback for the ParameterString snap record.

- typedef [OTF2_CallbackCode](#)(* [OTF2_GlobalSnapReaderCallback_ParameterUnsignedInt](#))([OTF2_LocationRef](#) locationID, [OTF2_TimeStamp](#) snapTime, void *userData, [OTF2_AttributeList](#) *attributeList, [OTF2_TimeStamp](#) origEventTime, [OTF2_ParameterRef](#) parameter, uint64_t value)

Callback for the ParameterUnsignedInt snap record.

- typedef [OTF2_CallbackCode](#)(* [OTF2_GlobalSnapReaderCallback_SnapshotEnd](#))([OTF2_LocationRef](#) locationID, [OTF2_TimeStamp](#) snapTime, void *userData, [OTF2_AttributeList](#) *attributeList, uint64_t contReadPos)

Callback for the SnapshotEnd snap record.

- typedef [OTF2_CallbackCode](#)(* [OTF2_GlobalSnapReaderCallback_SnapshotStart](#))([OTF2_LocationRef](#) locationID, [OTF2_TimeStamp](#) snapTime, void *userData, [OTF2_AttributeList](#) *attributeList, uint64_t numberOfRecords)

Callback for the SnapshotStart snap record.

- typedef [OTF2_CallbackCode](#)(* [OTF2_GlobalSnapReaderCallback_Unknown](#))([OTF2_LocationRef](#) locationID, [OTF2_TimeStamp](#) snapTime, void *userData, [OTF2_AttributeList](#) *attributeList)

Callback for an unknown snap record.

- typedef struct [OTF2_GlobalSnapReaderCallbacks_struct](#) [OTF2_GlobalSnapReaderCallbacks](#)

Opaque struct which holds all snap record callbacks.

Functions

- void [OTF2_GlobalSnapReaderCallbacks_Clear](#) ([OTF2_GlobalSnapReaderCallbacks](#) *globalSnapReaderCallbacks)

Clears a struct for the global snap callbacks.

APPENDIX J. FILE DOCUMENTATION

- `void OTF2_GlobalSnapReaderCallbacks_Delete (OTF2_GlobalSnapReaderCallbacks *globalSnapReaderCallbacks)`
Deallocates a struct for the global snap callbacks.
- `OTF2_GlobalSnapReaderCallbacks * OTF2_GlobalSnapReaderCallbacks_New (void)`
Allocates a new struct for the snap callbacks.
- `OTF2_ErrorCode OTF2_GlobalSnapReaderCallbacks_SetEnterCallback (OTF2_GlobalSnapReaderCallbacks *globalSnapReaderCallbacks, OTF2_GlobalSnapReaderCallback_Enter enterCallback)`
Registers the callback for the Enter snap.
- `OTF2_ErrorCode OTF2_GlobalSnapReaderCallbacks_SetMeasurementOnOffCallback (OTF2_GlobalSnapReaderCallbacks *globalSnapReaderCallbacks, OTF2_GlobalSnapReaderCallback_MeasurementOnOff measurementOnOffCallback)`
Registers the callback for the MeasurementOnOff snap.
- `OTF2_ErrorCode OTF2_GlobalSnapReaderCallbacks_SetMetricCallback (OTF2_GlobalSnapReaderCallbacks *globalSnapReaderCallbacks, OTF2_GlobalSnapReaderCallback_Metric metricCallback)`
Registers the callback for the Metric snap.
- `OTF2_ErrorCode OTF2_GlobalSnapReaderCallbacks_SetMpiCollectiveBeginCallback (OTF2_GlobalSnapReaderCallbacks *globalSnapReaderCallbacks, OTF2_GlobalSnapReaderCallback_MpiCollectiveBegin mpiCollectiveBeginCallback)`
Registers the callback for the MpiCollectiveBegin snap.
- `OTF2_ErrorCode OTF2_GlobalSnapReaderCallbacks_SetMpiCollectiveEndCallback (OTF2_GlobalSnapReaderCallbacks *globalSnapReaderCallbacks, OTF2_GlobalSnapReaderCallback_MpiCollectiveEnd mpiCollectiveEndCallback)`
Registers the callback for the MpiCollectiveEnd snap.
- `OTF2_ErrorCode OTF2_GlobalSnapReaderCallbacks_SetMpiIrecvCallback (OTF2_GlobalSnapReaderCallbacks *globalSnapReaderCallbacks, OTF2_GlobalSnapReaderCallback_MpiIrecv mpiIrecvCallback)`
Registers the callback for the MpiIrecv snap.

J.21 OTF2_GlobalSnapReaderCallbacks.h File Reference

- [OTF2_ErrorCode OTF2_GlobalSnapReaderCallbacks_SetMpiIrecvRequestCallback](#)
([OTF2_GlobalSnapReaderCallbacks *globalSnapReaderCallbacks](#), [OTF2_GlobalSnapReaderCallback_MpiIrecvRequest](#) [mpiIrecvRequestCallback](#))
Registers the callback for the MpiIrecvRequest snap.
- [OTF2_ErrorCode OTF2_GlobalSnapReaderCallbacks_SetMpiIsendCallback](#)
([OTF2_GlobalSnapReaderCallbacks *globalSnapReaderCallbacks](#), [OTF2_GlobalSnapReaderCallback_MpiIsend](#) [mpiIsendCallback](#))
Registers the callback for the MpiIsend snap.
- [OTF2_ErrorCode OTF2_GlobalSnapReaderCallbacks_SetMpiIsendCompleteCallback](#)
([OTF2_GlobalSnapReaderCallbacks *globalSnapReaderCallbacks](#), [OTF2_GlobalSnapReaderCallback_MpiIsendComplete](#) [mpiIsendCompleteCallback](#))

Registers the callback for the MpiIsendComplete snap.
- [OTF2_ErrorCode OTF2_GlobalSnapReaderCallbacks_SetMpiRecvCallback](#)
([OTF2_GlobalSnapReaderCallbacks *globalSnapReaderCallbacks](#), [OTF2_GlobalSnapReaderCallback_MpiRecv](#) [mpiRecvCallback](#))
Registers the callback for the MpiRecv snap.
- [OTF2_ErrorCode OTF2_GlobalSnapReaderCallbacks_SetMpiSendCallback](#)
([OTF2_GlobalSnapReaderCallbacks *globalSnapReaderCallbacks](#), [OTF2_GlobalSnapReaderCallback_MpiSend](#) [mpiSendCallback](#))
Registers the callback for the MpiSend snap.
- [OTF2_ErrorCode OTF2_GlobalSnapReaderCallbacks_SetOmpAcquireLockCallback](#)
([OTF2_GlobalSnapReaderCallbacks *globalSnapReaderCallbacks](#), [OTF2_GlobalSnapReaderCallback_OmpAcquireLock](#) [ompAcquireLockCallback](#))
Registers the callback for the OmpAcquireLock snap.
- [OTF2_ErrorCode OTF2_GlobalSnapReaderCallbacks_SetOmpForkCallback](#)
([OTF2_GlobalSnapReaderCallbacks *globalSnapReaderCallbacks](#), [OTF2_GlobalSnapReaderCallback_OmpFork](#) [ompForkCallback](#))
Registers the callback for the OmpFork snap.
- [OTF2_ErrorCode OTF2_GlobalSnapReaderCallbacks_SetOmpTaskCreateCallback](#)
([OTF2_GlobalSnapReaderCallbacks *globalSnapReaderCallbacks](#), [OTF2_GlobalSnapReaderCallback_OmpTaskCreate](#) [ompTaskCreateCallback](#))
Registers the callback for the OmpTaskCreate snap.

APPENDIX J. FILE DOCUMENTATION

- [OTF2_ErrorCode](#) [OTF2_GlobalSnapReaderCallbacks_SetOmpTaskSwitchCallback](#)
([OTF2_GlobalSnapReaderCallbacks](#) *globalSnapReaderCallbacks, [OTF2_GlobalSnapReaderCallback_OmpTaskSwitch](#) ompTaskSwitchCallback)
Registers the callback for the OmpTaskSwitch snap.
- [OTF2_ErrorCode](#) [OTF2_GlobalSnapReaderCallbacks_SetParameterIntCallback](#)
([OTF2_GlobalSnapReaderCallbacks](#) *globalSnapReaderCallbacks, [OTF2_GlobalSnapReaderCallback_ParameterInt](#) parameterIntCallback)
Registers the callback for the ParameterInt snap.
- [OTF2_ErrorCode](#) [OTF2_GlobalSnapReaderCallbacks_SetParameterStringCallback](#)
([OTF2_GlobalSnapReaderCallbacks](#) *globalSnapReaderCallbacks, [OTF2_GlobalSnapReaderCallback_ParameterString](#) parameterStringCallback)
Registers the callback for the ParameterString snap.
- [OTF2_ErrorCode](#) [OTF2_GlobalSnapReaderCallbacks_SetParameterUnsignedIntCallback](#)
([OTF2_GlobalSnapReaderCallbacks](#) *globalSnapReaderCallbacks, [OTF2_GlobalSnapReaderCallback_ParameterUnsignedInt](#) parameterUnsignedIntCallback)
Registers the callback for the ParameterUnsignedInt snap.
- [OTF2_ErrorCode](#) [OTF2_GlobalSnapReaderCallbacks_SetSnapshotEndCallback](#)
([OTF2_GlobalSnapReaderCallbacks](#) *globalSnapReaderCallbacks, [OTF2_GlobalSnapReaderCallback_SnapshotEnd](#) snapshotEndCallback)
Registers the callback for the SnapshotEnd snap.
- [OTF2_ErrorCode](#) [OTF2_GlobalSnapReaderCallbacks_SetSnapshotStartCallback](#)
([OTF2_GlobalSnapReaderCallbacks](#) *globalSnapReaderCallbacks, [OTF2_GlobalSnapReaderCallback_SnapshotStart](#) snapshotStartCallback)
Registers the callback for the SnapshotStart snap.
- [OTF2_ErrorCode](#) [OTF2_GlobalSnapReaderCallbacks_SetUnknownCallback](#)
([OTF2_GlobalSnapReaderCallbacks](#) *globalSnapReaderCallbacks, [OTF2_GlobalSnapReaderCallback_Unknown](#) unknownCallback)
Registers the callback for unknown snaps.

J.21.1 Detailed Description

This defines the callbacks for the global snap reader.

J.21 OTF2_GlobalSnapReaderCallbacks.h File Reference

Source Template:

templates/OTF2_GlobalSnapReaderCallbacks.tmpl.h

J.21.2 Typedef Documentation

J.21.2.1 typedef OTF2_CallbackCode(* OTF2_GlobalSnapReaderCallback_Enter)(OTF2_LocationRef locationID, OTF2_TimeStamp snapTime, void *userData, OTF2_AttributeList *attributeList, OTF2_TimeStamp origEventTime, OTF2_RegionRef region)

Callback for the Enter snap record.

This record exists for each *Enter* event where the corresponding *Leave* event did not occur before the snapshot.

Parameters

| | |
|----------------------|--|
| <i>locationID</i> | The location where this snap happened. |
| <i>time</i> | The time of this snapshot. |
| <i>userData</i> | User data as set by OTF2_Reader_RegisterGlobalSnapCallbacks or OTF2_GlobalSnapReader_SetCallbacks . |
| <i>attributeList</i> | Additional attributes for this snap. |
| <i>origEventTime</i> | The original time this event happened. |
| <i>region</i> | Needs to be defined in a definition record References a Region definition and will be mapped to the global definition if a mapping table of type OTF2_MAPPING_REGION is available. |

Since

Version 1.2

Returns

[OTF2_CALLBACK_SUCCESS](#) or [OTF2_CALLBACK_INTERRUPT](#).

J.21.2.2 typedef OTF2_CallbackCode(* OTF2_GlobalSnapReaderCallback_MeasurementOnOff)(OTF2_LocationRef locationID, OTF2_TimeStamp snapTime, void *userData, OTF2_AttributeList *attributeList, OTF2_TimeStamp origEventTime, OTF2_MeasurementMode measurementMode)

Callback for the MeasurementOnOff snap record.

The last occurrence of an *MeasurementOnOff* event of this location, if any.

APPENDIX J. FILE DOCUMENTATION

Parameters

| | |
|------------------------|---|
| <i>locationID</i> | The location where this snap happened. |
| <i>time</i> | The time of this snapshot. |
| <i>userData</i> | User data as set by OTF2_Reader_RegisterGlobalSnapCallbacks or OTF2_GlobalSnapReader_SetCallbacks . |
| <i>attributeList</i> | Additional attributes for this snap. |
| <i>origEvent-Time</i> | The original time this event happened. |
| <i>measurementMode</i> | Is the measurement turned on (OTF2_MEASUREMENT_ON) or off (OTF2_MEASUREMENT_OFF)? |

Since

Version 1.2

Returns

[OTF2_CALLBACK_SUCCESS](#) or [OTF2_CALLBACK_INTERRUPT](#).

```
J.21.2.3 typedef OTF2_CallbackCode( * OTF2_GlobalSnapReaderCallback_ -  
Metric)(OTF2_LocationRef locationID, OTF2_TimeStamp snapTime,  
void *userData, OTF2_AttributeList *attributeList, OTF2_TimeStamp  
origEventTime, OTF2_MetricRef metric, uint8_t numberOfMetrics, const  
OTF2_Type *typeIDs, const OTF2_MetricValue *metricValues)
```

Callback for the Metric snap record.

This record exists for each referenced metric class or metric instance event this location recorded metrics before and provides the last known recorded metric values.

As an exception for metric classes where the metric mode detontes an [OTF2_-METRIC_VALUE_RELATIVE](#) mode the value indicates the accumulation of all previous metric values recorded.

Parameters

| | |
|-----------------------|--|
| <i>locationID</i> | The location where this snap happened. |
| <i>time</i> | The time of this snapshot. |
| <i>userData</i> | User data as set by OTF2_Reader_RegisterGlobalSnapCallbacks or OTF2_GlobalSnapReader_SetCallbacks . |
| <i>attributeList</i> | Additional attributes for this snap. |
| <i>origEvent-Time</i> | The original time this event happened. |
| <i>metric</i> | Could be a metric class or a metric instance. References a MetricClass , or a MetricInstance definition and will be mapped to the global definition if a mapping table of type OTF2_MAPPING_METRIC is available. |

J.21 OTF2_GlobalSnapReaderCallbacks.h File Reference

| | |
|------------------------|------------------------------------|
| <i>numberOfMetrics</i> | Number of metrics with in the set. |
| <i>typeIDs</i> | List of metric types. |
| <i>metricValues</i> | List of metric values. |

Since

Version 1.2

Returns

[OTF2_CALLBACK_SUCCESS](#) or [OTF2_CALLBACK_INTERRUPT](#).

J.21.2.4 `typedef OTF2_CallbackCode(* OTF2_GlobalSnapReaderCallback_MpiCollectiveBegin)(OTF2_LocationRef locationID, OTF2_TimeStamp snapTime, void *userData, OTF2_AttributeList *attributeList, OTF2_TimeStamp origEventTime)`

Callback for the MpiCollectiveBegin snap record.

Indicates that this location started a collective operation but not all of the participating locations completed the operation yet, including this location.

Parameters

| | |
|----------------------|---|
| <i>locationID</i> | The location where this snap happened. |
| <i>time</i> | The time of this snapshot. |
| <i>userData</i> | User data as set by OTF2_Reader_RegisterGlobalSnapCallbacks or OTF2_GlobalSnapReader_SetCallbacks . |
| <i>attributeList</i> | Additional attributes for this snap. |
| <i>origEventTime</i> | The original time this event happened. |

Since

Version 1.2

Returns

[OTF2_CALLBACK_SUCCESS](#) or [OTF2_CALLBACK_INTERRUPT](#).

APPENDIX J. FILE DOCUMENTATION

J.21.2.5 typedef OTF2_CallbackCode(* OTF2_GlobalSnapReaderCallback_
MpiCollectiveEnd)(OTF2_LocationRef locationID, OTF2_TimeStamp
snapTime, void *userData, OTF2_AttributeList *attributeList,
OTF2_TimeStamp origEventTime, OTF2_CollectiveOp collectiveOp,
OTF2_CommRef communicator, uint32_t root, uint64_t sizeSent, uint64_t
sizeReceived)

Callback for the MpiCollectiveEnd snap record.

Indicates that this location completed a collective operation locally but not all of the participating locations completed the operation yet. The corresponding *MpiCollectiveBeginSnaps* record is still in the snapshot though.

Parameters

| | |
|-----------------------|--|
| <i>locationID</i> | The location where this snap happened. |
| <i>time</i> | The time of this snapshot. |
| <i>userData</i> | User data as set by OTF2_Reader_RegisterGlobalSnapCallbacks or OTF2_GlobalSnapReader_SetCallbacks . |
| <i>attributeList</i> | Additional attributes for this snap. |
| <i>origEvent-Time</i> | The original time this event happened. |
| <i>collec-tiveOp</i> | Determines which collective operation it is. |
| <i>communi-cator</i> | Communicator References a Comm definition and will be mapped to the global definition if a mapping table of type OTF2_MAPPING_COMM is available. |
| <i>root</i> | MPI rank of root in <i>communicator</i> . |
| <i>sizeSent</i> | Size of the sent message. |
| <i>sizeRe-ceived</i> | Size of the received message. |

Since

Version 1.2

Returns

[OTF2_CALLBACK_SUCCESS](#) or [OTF2_CALLBACK_INTERRUPT](#).

J.21 OTF2_GlobalSnapReaderCallbacks.h File Reference

J.21.2.6 typedef OTF2_CallbackCode(* OTF2_GlobalSnapReaderCallback_
MpiIrecv)(OTF2_LocationRef locationID, OTF2_TimeStamp snapTime,
void *userData, OTF2_AttributeList *attributeList, OTF2_TimeStamp
origEventTime, uint32_t sender, OTF2_CommRef communicator, uint32_t
msgTag, uint64_t msgLength, uint64_t requestID)

Callback for the MpiIrecv snap record.

This record exists for each *MpiIrecv* event where the matching send message event did not occur on the remote location before the snapshot. This could either be an *MpiSend* or an *MpiSendComplete* event. Or an *MpiIrecvRequest* occurred before this event but the corresponding *MpiIrecv* event did not occur before this snapshot. In this case the message matching couldn't be performed yet, because the envelope of the ongoing *MpiIrecvRequest* is not yet known.

Parameters

| | |
|----------------------|--|
| <i>locationID</i> | The location where this snap happened. |
| <i>time</i> | The time of this snapshot. |
| <i>userData</i> | User data as set by OTF2_Reader_RegisterGlobalSnapCallbacks or OTF2_GlobalSnapReader_SetCallbacks . |
| <i>attributeList</i> | Additional attributes for this snap. |
| <i>origEventTime</i> | The original time this event happened. |
| <i>sender</i> | MPI rank of sender in <i>communicator</i> . |
| <i>communicator</i> | Communicator ID. References a Comm definition and will be mapped to the global definition if a mapping table of type OTF2_MAPPING_COMM is available. |
| <i>msgTag</i> | Message tag |
| <i>msgLength</i> | Message length |
| <i>requestID</i> | ID of the related request |

Since

Version 1.2

Returns

[OTF2_CALLBACK_SUCCESS](#) or [OTF2_CALLBACK_INTERRUPT](#).

J.21.2.7 `typedef OTF2_CallbackCode(* OTF2_GlobalSnapReaderCallback_ -
MpiIrecvRequest)(OTF2_LocationRef locationID, OTF2_TimeStamp
snapTime, void *userData, OTF2_AttributeList *attributeList,
OTF2_TimeStamp origEventTime, uint64_t requestID)`

Callback for the MpiIrecvRequest snap record.

This record exists for each *MpiIrecvRequest* event where an corresponding *MpiIrecv* or *MpiRequestCancelled* event did not occur on this location before the snapshot. Or the corresponding *MpiIrecv* did occurred (the *MpiIrecvSnap* record exists in the snapshot) but the matching receive message event did not occur on the remote location before the snapshot. This could either be an *MpiRecv* or an *MpiIrecv* event.

Parameters

| | |
|----------------------|---|
| <i>locationID</i> | The location where this snap happened. |
| <i>time</i> | The time of this snapshot. |
| <i>userData</i> | User data as set by OTF2_Reader_RegisterGlobalSnapCallbacks or OTF2_GlobalSnapReader_SetCallbacks . |
| <i>attributeList</i> | Additional attributes for this snap. |
| <i>origEventTime</i> | The original time this event happened. |
| <i>requestID</i> | ID of the requested receive |

Since

Version 1.2

Returns

[OTF2_CALLBACK_SUCCESS](#) or [OTF2_CALLBACK_INTERRUPT](#).

J.21.2.8 `typedef OTF2_CallbackCode(* OTF2_GlobalSnapReaderCallback_ -
MpiIsend)(OTF2_LocationRef locationID, OTF2_TimeStamp snapTime,
void *userData, OTF2_AttributeList *attributeList, OTF2_TimeStamp
origEventTime, uint32_t receiver, OTF2_CommRef communicator, uint32_t
msgTag, uint64_t msgLength, uint64_t requestID)`

Callback for the MpiIsend snap record.

This record exists for each *MpiIsend* event where an corresponding *MpiIsendComplete* or *MpiRequestCancelled* event did not occur on this location before the snapshot. Or the corresponding *MpiIsendComplete* did occurred (the *MpiIsendCompleteSnap* record exists in the snapshot) but the matching receive message event

J.21 OTF2_GlobalSnapReaderCallbacks.h File Reference

did not occur on the remote location before the snapshot. (This could either be an *MpiRecv* or an *MpiIrecv* event.)

Parameters

| | |
|-----------------------|---|
| <i>locationID</i> | The location where this snap happened. |
| <i>time</i> | The time of this snapshot. |
| <i>userData</i> | User data as set by OTF2_Reader_RegisterGlobalSnapCallbacks or OTF2_GlobalSnapReader_SetCallbacks . |
| <i>attributeList</i> | Additional attributes for this snap. |
| <i>origEvent-Time</i> | The original time this event happened. |
| <i>receiver</i> | MPI rank of receiver in <i>communicator</i> . |
| <i>communi-cator</i> | Communicator ID. References a Comm definition and will be mapped to the global definition if a mapping table of type OTF2_MAPPING_-COMM is available. |
| <i>msgTag</i> | Message tag |
| <i>msgLength</i> | Message length |
| <i>requestID</i> | ID of the related request |

Since

Version 1.2

Returns

[OTF2_CALLBACK_SUCCESS](#) or [OTF2_CALLBACK_INTERRUPT](#).

J.21.2.9 `typedef OTF2_CallbackCode(* OTF2_GlobalSnapReaderCallback_-MpiIsendComplete)(OTF2_LocationRef locationID, OTF2_TimeStamp snapTime, void *userData, OTF2_AttributeList *attributeList, OTF2_TimeStamp origEventTime, uint64_t requestID)`

Callback for the *MpiIsendComplete* snap record.

This record exists for each *MpiIsend* event where the corresponding *MpiIsendComplete* event occurred, but where the matching receive message event did not occur on the remote location before the snapshot. (This could either be an *MpiRecv* or an *MpiIrecv* event.) .

Parameters

| | |
|-------------------|--|
| <i>locationID</i> | The location where this snap happened. |
| <i>time</i> | The time of this snapshot. |

APPENDIX J. FILE DOCUMENTATION

| | |
|-----------------------|---|
| <i>userData</i> | User data as set by OTF2_Reader_RegisterGlobalSnapCallbacks or OTF2_GlobalSnapReader_SetCallbacks . |
| <i>attributeList</i> | Additional attributes for this snap. |
| <i>origEvent-Time</i> | The original time this event happened. |
| <i>requestID</i> | ID of the related request |

Since

Version 1.2

Returns

[OTF2_CALLBACK_SUCCESS](#) or [OTF2_CALLBACK_INTERRUPT](#).

J.21.2.10 `typedef OTF2_CallbackCode(* OTF2_GlobalSnapReaderCallback_-MpiRecv)(OTF2_LocationRef locationID, OTF2_TimeStamp snapTime, void *userData, OTF2_AttributeList *attributeList, OTF2_TimeStamp origEventTime, uint32_t sender, OTF2_CommRef communicator, uint32_t msgTag, uint64_t msgLength)`

Callback for the *MpiRecv* snap record.

This record exists for each *MpiRecv* event where the matching send message event did not occur on the remote location before the snapshot. This could either be an *MpiSend* or an *MpiSendComplete* event. Or an *MpiRecvRequest* occurred before this event but the corresponding *MpiRecv* event did not occur before this snapshot. In this case the message matching couldn't be performed yet, because the envelope of the ongoing *MpiRecvRequest* is not yet known.

Parameters

| | |
|-----------------------|---|
| <i>locationID</i> | The location where this snap happened. |
| <i>time</i> | The time of this snapshot. |
| <i>userData</i> | User data as set by OTF2_Reader_RegisterGlobalSnapCallbacks or OTF2_GlobalSnapReader_SetCallbacks . |
| <i>attributeList</i> | Additional attributes for this snap. |
| <i>origEvent-Time</i> | The original time this event happened. |
| <i>sender</i> | MPI rank of sender in <i>communicator</i> . |
| <i>communicator</i> | Communicator ID. References a Comm definition and will be mapped to the global definition if a mapping table of type OTF2_MAPPING_-COMM is available. |
| <i>msgTag</i> | Message tag |
| <i>msgLength</i> | Message length |

J.21 OTF2_GlobalSnapReaderCallbacks.h File Reference

Since

Version 1.2

Returns

[OTF2_CALLBACK_SUCCESS](#) or [OTF2_CALLBACK_INTERRUPT](#).

J.21.2.11 `typedef OTF2_CallbackCode(* OTF2_GlobalSnapReaderCallback_
MpiSend)(OTF2_LocationRef locationID, OTF2_TimeStamp snapTime,
void *userData, OTF2_AttributeList *attributeList, OTF2_TimeStamp
origEventTime, uint32_t receiver, OTF2_CommRef communicator, uint32_t
msgTag, uint64_t msgLength)`

Callback for the MpiSend snap record.

This record exists for each *MpiSend* event where the matching receive message event did not occur on the remote location before the snapshot. This could either be an *MpiRecv* or an *MpiIrecv* event. Note that it may so, that a previous *MpiSend* with the same envelope than this one is neither completed not canceled yet, thus the matching receive may already occurred, but the matching couldn't be done yet.

Parameters

| | |
|----------------------------|--|
| <i>locationID</i> | The location where this snap happened. |
| <i>time</i> | The time of this snapshot. |
| <i>userData</i> | User data as set by OTF2_Reader_RegisterGlobalSnapCallbacks or OTF2_GlobalSnapReader_SetCallbacks . |
| <i>attributeList</i> | Additional attributes for this snap. |
| <i>origEvent- Time</i> | The original time this event happened. |
| <i>receiver</i> | MPI rank of receiver in <i>communicator</i> . |
| <i>communi- cator</i> | Communicator ID. References a Comm definition and will be mapped to the global definition if a mapping table of type OTF2_MAPPING_- COMM is available. |
| <i>msgTag</i> | Message tag |
| <i>msgLength</i> | Message length |

Since

Version 1.2

Returns

[OTF2_CALLBACK_SUCCESS](#) or [OTF2_CALLBACK_INTERRUPT](#).

APPENDIX J. FILE DOCUMENTATION

J.21.2.12 `typedef OTF2_CallbackCode(* OTF2_GlobalSnapReaderCallback_
OmpAcquireLock)(OTF2_LocationRef locationID, OTF2_TimeStamp
snapTime, void *userData, OTF2_AttributeList *attributeList,
OTF2_TimeStamp origEventTime, uint32_t lockID, uint32_t acquisitionOrder)`

Callback for the OmpAcquireLock snap record.

This record exists for each *OmpAcquireLock* event where the corresponding *OmpReleaseLock* did not occurred before this snapshot yet.

Parameters

| | |
|-------------------------|---|
| <i>locationID</i> | The location where this snap happened. |
| <i>time</i> | The time of this snapshot. |
| <i>userData</i> | User data as set by OTF2_Reader_RegisterGlobalSnapCallbacks or OTF2_GlobalSnapReader_SetCallbacks . |
| <i>attributeList</i> | Additional attributes for this snap. |
| <i>origEventTime</i> | The original time this event happened. |
| <i>lockID</i> | ID of the lock. |
| <i>acquisitionOrder</i> | A monotonically increasing number to determine the order of lock acquisitions (with unsynchronized clocks this is otherwise not possible). Corresponding acquire-release events have same number. |

Since

Version 1.2

Returns

[OTF2_CALLBACK_SUCCESS](#) or [OTF2_CALLBACK_INTERRUPT](#).

J.21.2.13 `typedef OTF2_CallbackCode(* OTF2_GlobalSnapReaderCallback_
OmpFork)(OTF2_LocationRef locationID, OTF2_TimeStamp
snapTime, void *userData, OTF2_AttributeList *attributeList,
OTF2_TimeStamp origEventTime, uint32_t numberOfRequestedThreads)`

Callback for the OmpFork snap record.

This record exists for each *OmpFork* event where the corresponding *OmpJoin* did not occurred before this snapshot.

Parameters

| | |
|-------------------|--|
| <i>locationID</i> | The location where this snap happened. |
|-------------------|--|

J.21 OTF2_GlobalSnapReaderCallbacks.h File Reference

| | |
|---------------------------------|---|
| <i>time</i> | The time of this snapshot. |
| <i>userData</i> | User data as set by OTF2_Reader_RegisterGlobalSnapCallbacks or OTF2_GlobalSnapReader_SetCallbacks . |
| <i>attributeList</i> | Additional attributes for this snap. |
| <i>origEventTime</i> | The original time this event happened. |
| <i>numberOfRequestedThreads</i> | Requested size of the team. |

Since

Version 1.2

Returns

[OTF2_CALLBACK_SUCCESS](#) or [OTF2_CALLBACK_INTERRUPT](#).

J.21.2.14 `typedef OTF2_CallbackCode(* OTF2_GlobalSnapReaderCallback_OmpTaskCreate)(OTF2_LocationRef locationID, OTF2_TimeStamp snapTime, void *userData, OTF2_AttributeList *attributeList, OTF2_TimeStamp origEventTime, uint64_t taskID)`

Callback for the `OmpTaskCreate` snap record.

This record exists for each [OmpTaskCreate](#) event where the corresponding [OmpTaskComplete](#) event did not occurred before this snapshot. Neither on this location nor on any other location in the current thread team.

Parameters

| | |
|----------------------|---|
| <i>locationID</i> | The location where this snap happened. |
| <i>time</i> | The time of this snapshot. |
| <i>userData</i> | User data as set by OTF2_Reader_RegisterGlobalSnapCallbacks or OTF2_GlobalSnapReader_SetCallbacks . |
| <i>attributeList</i> | Additional attributes for this snap. |
| <i>origEventTime</i> | The original time this event happened. |
| <i>taskID</i> | Identifier of the newly created task instance. |

Since

Version 1.2

Returns

OTF2_CALLBACK_SUCCESS or *OTF2_CALLBACK_INTERRUPT*.

J.21.2.15 `typedef OTF2_CallbackCode(* OTF2_GlobalSnapReaderCallback_
OmpTaskSwitch)(OTF2_LocationRef locationID, OTF2_TimeStamp
snapTime, void *userData, OTF2_AttributeList *attributeList,
OTF2_TimeStamp origEventTime, uint64_t taskID)`

Callback for the OmpTaskSwitch snap record.

This record exists for each *OmpTaskSwitch* event where the corresponding *OmpTaskComplete* event did not occurred before this snapshot. Neither on this location nor on any other location in the current thread team.

Parameters

| | |
|----------------------|---|
| <i>locationID</i> | The location where this snap happened. |
| <i>time</i> | The time of this snapshot. |
| <i>userData</i> | User data as set by OTF2_Reader_RegisterGlobalSnapCallbacks or OTF2_GlobalSnapReader_SetCallbacks . |
| <i>attributeList</i> | Additional attributes for this snap. |
| <i>origEventTime</i> | The original time this event happened. |
| <i>taskID</i> | Identifier of the now active task instance. |

Since

Version 1.2

Returns

OTF2_CALLBACK_SUCCESS or *OTF2_CALLBACK_INTERRUPT*.

J.21.2.16 `typedef OTF2_CallbackCode(* OTF2_GlobalSnapReaderCallback_
ParameterInt)(OTF2_LocationRef locationID, OTF2_TimeStamp
snapTime, void *userData, OTF2_AttributeList *attributeList,
OTF2_TimeStamp origEventTime, OTF2_ParameterRef parameter,
int64_t value)`

Callback for the ParameterInt snap record.

This record must be included in the snapshot until the leave event for the enter event occurs which has the greatest timestamp less or equal the timestamp of this record.

J.21 OTF2_GlobalSnapReaderCallbacks.h File Reference

Parameters

| | |
|-----------------------|---|
| <i>locationID</i> | The location where this snap happened. |
| <i>time</i> | The time of this snapshot. |
| <i>userData</i> | User data as set by OTF2_Reader_RegisterGlobalSnapCallbacks or OTF2_GlobalSnapReader_SetCallbacks . |
| <i>attributeList</i> | Additional attributes for this snap. |
| <i>origEvent-Time</i> | The original time this event happened. |
| <i>parameter</i> | Parameter ID. References a Parameter definition and will be mapped to the global definition if a mapping table of type OTF2_MAPPING_PARAMETER is available. |
| <i>value</i> | Value of the recorded parameter. |

Since

Version 1.2

Returns

[OTF2_CALLBACK_SUCCESS](#) or [OTF2_CALLBACK_INTERRUPT](#).

```
J.21.2.17 typedef OTF2_CallbackCode(* OTF2_GlobalSnapReaderCallback_  
ParameterString)(OTF2_LocationRef locationID, OTF2_TimeStamp  
snapTime, void *userData, OTF2_AttributeList *attributeList,  
OTF2_TimeStamp origEventTime, OTF2_ParameterRef parameter,  
OTF2_StringRef string)
```

Callback for the ParameterString snap record.

This record must be included in the snapshot until the leave event for the enter event occurs which has the greatest timestamp less or equal the timestamp of this record.

Parameters

| | |
|-----------------------|---|
| <i>locationID</i> | The location where this snap happened. |
| <i>time</i> | The time of this snapshot. |
| <i>userData</i> | User data as set by OTF2_Reader_RegisterGlobalSnapCallbacks or OTF2_GlobalSnapReader_SetCallbacks . |
| <i>attributeList</i> | Additional attributes for this snap. |
| <i>origEvent-Time</i> | The original time this event happened. |
| <i>parameter</i> | Parameter ID. References a Parameter definition and will be mapped to the global definition if a mapping table of type OTF2_MAPPING_PARAMETER is available. |

APPENDIX J. FILE DOCUMENTATION

| | |
|---------------|--|
| <i>string</i> | Value: Handle of a string definition References a String definition and will be mapped to the global definition if a mapping table of type OTF2_MAPPING_STRING is available. |
|---------------|--|

Since

Version 1.2

Returns

[OTF2_CALLBACK_SUCCESS](#) or [OTF2_CALLBACK_INTERRUPT](#).

J.21.2.18 `typedef OTF2_CallbackCode(* OTF2_GlobalSnapReaderCallback_ -
ParameterUnsignedInt)(OTF2_LocationRef locationID,
OTF2_TimeStamp snapTime, void *userData, OTF2_AttributeList
*attributeList, OTF2_TimeStamp origEventTime, OTF2_ParameterRef
parameter, uint64_t value)`

Callback for the ParameterUnsignedInt snap record.

This record must be included in the snapshot until the leave event for the enter event occurs which has the greatest timestamp less or equal the timestamp of this record.

Parameters

| | |
|-----------------------|--|
| <i>locationID</i> | The location where this snap happened. |
| <i>time</i> | The time of this snapshot. |
| <i>userData</i> | User data as set by OTF2_Reader_RegisterGlobalSnapCallbacks or OTF2_GlobalSnapReader_SetCallbacks . |
| <i>attributeList</i> | Additional attributes for this snap. |
| <i>origEvent-Time</i> | The original time this event happened. |
| <i>parameter</i> | Parameter ID. References a Parameter definition and will be mapped to the global definition if a mapping table of type OTF2_MAPPING_-PARAMETER is available. |
| <i>value</i> | Value of the recorded parameter. |

Since

Version 1.2

Returns

[OTF2_CALLBACK_SUCCESS](#) or [OTF2_CALLBACK_INTERRUPT](#).

J.21 OTF2_GlobalSnapReaderCallbacks.h File Reference

J.21.2.19 `typedef OTF2_CallbackCode(* OTF2_GlobalSnapReaderCallback_ - SnapshotEnd)(OTF2_LocationRef locationID, OTF2_TimeStamp snapTime, void *userData, OTF2_AttributeList *attributeList, uint64_t contReadPos)`

Callback for the SnapshotEnd snap record.

This record marks the end of a snapshot. It contains the position to continue reading in the event trace for this location. Use [OTF2_EvtReader_Seek](#) with *contReadPos* as the position.

Parameters

| | |
|----------------------|---|
| <i>locationID</i> | The location where this snap happened. |
| <i>time</i> | The time of this snapshot. |
| <i>userData</i> | User data as set by OTF2_Reader_RegisterGlobalSnapCallbacks or OTF2_GlobalSnapReader_SetCallbacks . |
| <i>attributeList</i> | Additional attributes for this snap. |
| <i>contRead-Pos</i> | Position to continue reading in the event trace. |

Since

Version 1.2

Returns

[OTF2_CALLBACK_SUCCESS](#) or [OTF2_CALLBACK_INTERRUPT](#).

J.21.2.20 `typedef OTF2_CallbackCode(* OTF2_GlobalSnapReaderCallback_ - SnapshotStart)(OTF2_LocationRef locationID, OTF2_TimeStamp snapTime, void *userData, OTF2_AttributeList *attributeList, uint64_t numberOfRecords)`

Callback for the SnapshotStart snap record.

This record marks the start of a snapshot.

A snapshot consists of an timestamp and a set of snapshot records. All these snapshot records have the same snapshot time. A snapshot starts with one [SnapshotStart](#) record and closes with one [SnapshotEnd](#) record. All snapshot records inbetween are ordered by the *origEventTime*, which are also less than the snapshot timestamp. Ie. The timestamp of the next event read from the event stream is greater or equal to the snapshot time.

APPENDIX J. FILE DOCUMENTATION

Parameters

| | |
|-----------------------------|---|
| <i>locationID</i> | The location where this snap happened. |
| <i>time</i> | The time of this snapshot. |
| <i>userData</i> | User data as set by OTF2_Reader_RegisterGlobalSnapCallbacks or OTF2_GlobalSnapReader_SetCallbacks . |
| <i>attributeList</i> | Additional attributes for this snap. |
| <i>num- berOfRecord</i> | Number of snapshot event records in this snapshot. Excluding the <i>Snap-shotEnd</i> record. |

Since

Version 1.2

Returns

[OTF2_CALLBACK_SUCCESS](#) or [OTF2_CALLBACK_INTERRUPT](#).

J.21.2.21 `typedef OTF2_CallbackCode(* OTF2_GlobalSnapReaderCallback_ -
Unknown)(OTF2_LocationRef locationID, OTF2_TimeStamp
snapTime, void *userData, OTF2_AttributeList *attributeList)`

Callback for an unknown snap record.

Parameters

| | |
|----------------------|---|
| <i>locationID</i> | The location where this snap happened. |
| <i>snapTime</i> | The time of this snapshot. |
| <i>userData</i> | User data as set by OTF2_Reader_RegisterGlobalSnapCallbacks or OTF2_GlobalSnapReader_SetCallbacks . |
| <i>attributeList</i> | Additional attributes for this snap. |

Since

Version 1.2

Returns

[OTF2_CALLBACK_SUCCESS](#) or [OTF2_CALLBACK_INTERRUPT](#).

J.21.2.22 `typedef struct OTF2_GlobalSnapReaderCallbacks_struct
OTF2_GlobalSnapReaderCallbacks`

Opaque struct which holds all snap record callbacks.

J.21 OTF2_GlobalSnapReaderCallbacks.h File Reference

Since

Version 1.2

J.21.3 Function Documentation

J.21.3.1 void OTF2_GlobalSnapReaderCallbacks_Clear (OTF2_GlobalSnapReaderCallbacks * *globalSnapReaderCallbacks*)

Clears a struct for the global snap callbacks.

Parameters

| | |
|----------------------------------|---|
| <i>globalSnapReaderCallbacks</i> | Handle to a struct previously allocated with OTF2_GlobalSnapReaderCallbacks_New . |
|----------------------------------|---|

Since

Version 1.2

J.21.3.2 void OTF2_GlobalSnapReaderCallbacks_Delete (OTF2_GlobalSnapReaderCallbacks * *globalSnapReaderCallbacks*)

Deallocates a struct for the global snap callbacks.

Parameters

| | |
|----------------------------------|---|
| <i>globalSnapReaderCallbacks</i> | Handle to a struct previously allocated with OTF2_GlobalSnapReaderCallbacks_New . |
|----------------------------------|---|

Since

Version 1.2

J.21.3.3 OTF2_GlobalSnapReaderCallbacks* OTF2_GlobalSnapReaderCallbacks_New (void)

Allocates a new struct for the snap callbacks.

APPENDIX J. FILE DOCUMENTATION

Since

Version 1.2

Returns

A newly allocated struct of type [OTF2_GlobalSnapReaderCallbacks](#).

J.21.3.4 `OTF2_StatusCode OTF2_GlobalSnapReaderCallbacks_SetEnterCallback (OTF2_GlobalSnapReaderCallbacks * globalSnapReaderCallbacks, OTF2_GlobalSnapReaderCallback_Enter enterCallback)`

Registers the callback for the Enter snap.

Parameters

| | |
|-----------------------------------|--|
| <i>global-SnapReaderCallbacks</i> | Struct for all callbacks. |
| <i>enterCallback</i> | Function which should be called for all Enter snaps. |

Since

Version 1.2

Returns

[OTF2_SUCCESS](#) if successful

[OTF2_ERROR_INVALID_ARGUMENT](#) for an invalid `defReaderCallbacks` argument

J.21.3.5 `OTF2_StatusCode OTF2_GlobalSnapReaderCallbacks_SetMeasurementOnOffCallback (OTF2_GlobalSnapReaderCallbacks * globalSnapReaderCallbacks, OTF2_GlobalSnapReaderCallback_MeasurementOnOff measurementOnOffCallback)`

Registers the callback for the MeasurementOnOff snap.

Parameters

| | |
|-----------------------------------|---------------------------|
| <i>global-SnapReaderCallbacks</i> | Struct for all callbacks. |
|-----------------------------------|---------------------------|

J.21 OTF2_GlobalSnapReaderCallbacks.h File Reference

| | |
|----------------------------------|---|
| <i>measurementOnOff-Callback</i> | Function which should be called for all MeasurementOnOff snaps. |
|----------------------------------|---|

Since

Version 1.2

Returns

OTF2_SUCCESS if successful

OTF2_ERROR_INVALID_ARGUMENT for an invalid `defReaderCallbacks` argument

J.21.3.6 OTF2_StatusCode OTF2_GlobalSnapReaderCallbacks_SetMetricCallback (OTF2_GlobalSnapReaderCallbacks * *globalSnapReaderCallbacks*, OTF2_GlobalSnapReaderCallback_Metric *metricCallback*)

Registers the callback for the Metric snap.

Parameters

| | |
|-----------------------------------|---|
| <i>global-SnapReaderCallbacks</i> | Struct for all callbacks. |
| <i>metricCallback</i> | Function which should be called for all Metric snaps. |

Since

Version 1.2

Returns

OTF2_SUCCESS if successful

OTF2_ERROR_INVALID_ARGUMENT for an invalid `defReaderCallbacks` argument

**J.21.3.7 OTF2_StatusCode OTF2_GlobalSnapReaderCallbacks_-
SetMpiCollectiveBeginCallback (OTF2_GlobalSnapReaderCallbacks
* *globalSnapReaderCallbacks*, OTF2_GlobalSnapReaderCallback_-
MpiCollectiveBegin *mpiCollectiveBeginCallback*
)**

Registers the callback for the MpiCollectiveBegin snap.

Parameters

| | |
|-----------------------------------|---|
| <i>global-SnapReaderCallbacks</i> | Struct for all callbacks. |
| <i>mpiCollectiveBeginCallback</i> | Function which should be called for all MpiCollectiveBegin snaps. |

Since

Version 1.2

Returns

OTF2_SUCCESS if successful
OTF2_ERROR_INVALID_ARGUMENT for an invalid *defReaderCallbacks* argument

**J.21.3.8 OTF2_StatusCode OTF2_GlobalSnapReaderCallbacks_-
SetMpiCollectiveEndCallback (OTF2_GlobalSnapReaderCallbacks *
globalSnapReaderCallbacks, OTF2_GlobalSnapReaderCallback_-
MpiCollectiveEnd *mpiCollectiveEndCallback*)**

Registers the callback for the MpiCollectiveEnd snap.

Parameters

| | |
|-----------------------------------|---|
| <i>global-SnapReaderCallbacks</i> | Struct for all callbacks. |
| <i>mpiCollectiveEndCallback</i> | Function which should be called for all MpiCollectiveEnd snaps. |

J.21 OTF2_GlobalSnapReaderCallbacks.h File Reference

Since

Version 1.2

Returns

OTF2_SUCCESS if successful

OTF2_ERROR_INVALID_ARGUMENT for an invalid `defReaderCallbacks` argument

J.21.3.9 **OTF2_StatusCode** `OTF2_GlobalSnapReaderCallbacks_SetMpiIrecvCallback (OTF2_GlobalSnapReaderCallbacks * globalSnapReaderCallbacks, OTF2_GlobalSnapReaderCallback_MpiIrecv mpiIrecvCallback)`

Registers the callback for the `MpiIrecv` snap.

Parameters

| | |
|-----------------------------------|--|
| <i>global-SnapReaderCallbacks</i> | Struct for all callbacks. |
| <i>mpiIrecv-Callback</i> | Function which should be called for all <code>MpiIrecv</code> snaps. |

Since

Version 1.2

Returns

OTF2_SUCCESS if successful

OTF2_ERROR_INVALID_ARGUMENT for an invalid `defReaderCallbacks` argument

J.21.3.10 **OTF2_StatusCode** `OTF2_GlobalSnapReaderCallbacks_SetMpiIrecvRequestCallback (OTF2_GlobalSnapReaderCallbacks * globalSnapReaderCallbacks, OTF2_GlobalSnapReaderCallback_MpiIrecvRequest mpiIrecvRequestCallback)`

Registers the callback for the `MpiIrecvRequest` snap.

Parameters

APPENDIX J. FILE DOCUMENTATION

| | |
|-----------------------------------|--|
| <i>global-SnapReaderCallbacks</i> | Struct for all callbacks. |
| <i>mpiIrecvRequestCallback</i> | Function which should be called for all MpiIrecvRequest snaps. |

Since

Version 1.2

Returns

OTF2_SUCCESS if successful

OTF2_ERROR_INVALID_ARGUMENT for an invalid `defReaderCallbacks` argument

J.21.3.11 **OTF2_StatusCode** **OTF2_GlobalSnapReaderCallbacks_SetMpiIrecvCallback**
(**OTF2_GlobalSnapReaderCallbacks** * *globalSnapReaderCallbacks*,
OTF2_GlobalSnapReaderCallback_MpiIrecv *mpiIrecvCallback*)

Registers the callback for the MpiIrecv snap.

Parameters

| | |
|-----------------------------------|---|
| <i>global-SnapReaderCallbacks</i> | Struct for all callbacks. |
| <i>mpiIrecvCallback</i> | Function which should be called for all MpiIrecv snaps. |

Since

Version 1.2

Returns

OTF2_SUCCESS if successful

OTF2_ERROR_INVALID_ARGUMENT for an invalid `defReaderCallbacks` argument

J.21 OTF2_GlobalSnapReaderCallbacks.h File Reference

J.21.3.12 OTF2_ErrorCode OTF2_GlobalSnapReaderCallbacks_-SetMpiIsendCompleteCallback (OTF2_GlobalSnapReaderCallbacks * *globalSnapReaderCallbacks*, OTF2_GlobalSnapReaderCallback_-MpiIsendComplete *mpiIsendCompleteCallback*)

Registers the callback for the MpiIsendComplete snap.

Parameters

| | |
|-----------------------------------|---|
| <i>global-SnapReaderCallbacks</i> | Struct for all callbacks. |
| <i>mpiIsend-Complete-Callback</i> | Function which should be called for all MpiIsendComplete snaps. |

Since

Version 1.2

Returns

OTF2_SUCCESS if successful

OTF2_ERROR_INVALID_ARGUMENT for an invalid *defReaderCallbacks* argument

J.21.3.13 OTF2_ErrorCode OTF2_GlobalSnapReaderCallbacks_SetMpiRecvCallback (OTF2_GlobalSnapReaderCallbacks * *globalSnapReaderCallbacks*, OTF2_GlobalSnapReaderCallback_MpiRecv *mpiRecvCallback*)

Registers the callback for the MpiRecv snap.

Parameters

| | |
|-----------------------------------|--|
| <i>global-SnapReaderCallbacks</i> | Struct for all callbacks. |
| <i>mpiRecv-Callback</i> | Function which should be called for all MpiRecv snaps. |

Since

Version 1.2

APPENDIX J. FILE DOCUMENTATION

Returns

OTF2_SUCCESS if successful

OTF2_ERROR_INVALID_ARGUMENT for an invalid `defReaderCallbacks` argument

J.21.3.14 **OTF2_StatusCode** **OTF2_GlobalSnapReaderCallbacks_SetMpiSendCallback**
(**OTF2_GlobalSnapReaderCallbacks** * *globalSnapReaderCallbacks*,
OTF2_GlobalSnapReaderCallback_MpiSend *mpiSendCallback*)

Registers the callback for the MpiSend snap.

Parameters

| | |
|-----------------------------------|--|
| <i>global-SnapReaderCallbacks</i> | Struct for all callbacks. |
| <i>mpiSend-Callback</i> | Function which should be called for all MpiSend snaps. |

Since

Version 1.2

Returns

OTF2_SUCCESS if successful

OTF2_ERROR_INVALID_ARGUMENT for an invalid `defReaderCallbacks` argument

J.21.3.15 **OTF2_StatusCode** **OTF2_GlobalSnapReaderCallbacks_SetOmpAcquireLockCallback**
(**OTF2_GlobalSnapReaderCallbacks** *
globalSnapReaderCallbacks, **OTF2_GlobalSnapReaderCallback_-**
OmpAcquireLock *ompAcquireLockCallback*)

Registers the callback for the OmpAcquireLock snap.

Parameters

| | |
|-----------------------------------|---|
| <i>global-SnapReaderCallbacks</i> | Struct for all callbacks. |
| <i>ompAcquireLock-Callback</i> | Function which should be called for all OmpAcquireLock snaps. |

J.21 OTF2_GlobalSnapReaderCallbacks.h File Reference

Since

Version 1.2

Returns

OTF2_SUCCESS if successful

OTF2_ERROR_INVALID_ARGUMENT for an invalid `defReaderCallbacks` argument

J.21.3.16 **OTF2_StatusCode** `OTF2_GlobalSnapReaderCallbacks_SetOmpForkCallback`
(`OTF2_GlobalSnapReaderCallbacks * globalSnapReaderCallbacks`,
`OTF2_GlobalSnapReaderCallback_OmpFork ompForkCallback`)

Registers the callback for the OmpFork snap.

Parameters

| | |
|-----------------------------------|--|
| <i>global-SnapReaderCallbacks</i> | Struct for all callbacks. |
| <i>ompFork-Callback</i> | Function which should be called for all OmpFork snaps. |

Since

Version 1.2

Returns

OTF2_SUCCESS if successful

OTF2_ERROR_INVALID_ARGUMENT for an invalid `defReaderCallbacks` argument

J.21.3.17 **OTF2_StatusCode** `OTF2_GlobalSnapReaderCallbacks_SetOmpTaskCreateCallback`
(`OTF2_GlobalSnapReaderCallbacks * globalSnapReaderCallbacks`,
`OTF2_GlobalSnapReaderCallback_OmpTaskCreate ompTaskCreateCallback`)

Registers the callback for the OmpTaskCreate snap.

Parameters

APPENDIX J. FILE DOCUMENTATION

| | |
|-----------------------------------|--|
| <i>global-SnapReaderCallbacks</i> | Struct for all callbacks. |
| <i>omp-TaskCreate-Callback</i> | Function which should be called for all OmpTaskCreate snaps. |

Since

Version 1.2

Returns

OTF2_SUCCESS if successful

OTF2_ERROR_INVALID_ARGUMENT for an invalid `defReaderCallbacks` argument

J.21.3.18 **OTF2_ErrorCode** **OTF2_GlobalSnapReaderCallbacks_-SetOmpTaskSwitchCallback** (**OTF2_GlobalSnapReaderCallbacks** * **globalSnapReaderCallbacks**, **OTF2_GlobalSnapReaderCallback_-OmpTaskSwitch** **ompTaskSwitchCallback**)

Registers the callback for the OmpTaskSwitch snap.

Parameters

| | |
|-----------------------------------|--|
| <i>global-SnapReaderCallbacks</i> | Struct for all callbacks. |
| <i>omp-TaskSwitch-Callback</i> | Function which should be called for all OmpTaskSwitch snaps. |

Since

Version 1.2

Returns

OTF2_SUCCESS if successful

OTF2_ERROR_INVALID_ARGUMENT for an invalid `defReaderCallbacks` argument

J.21 OTF2_GlobalSnapReaderCallbacks.h File Reference

J.21.3.19 **OTF2_ErrorCode** **OTF2_GlobalSnapReaderCallbacks_-SetParameterIntCallback** (**OTF2_GlobalSnapReaderCallbacks** * *globalSnapReaderCallbacks*, **OTF2_GlobalSnapReaderCallback_-ParameterInt** *parameterIntCallback*)

Registers the callback for the ParameterInt snap.

Parameters

| | |
|-----------------------------------|---|
| <i>global-SnapReaderCallbacks</i> | Struct for all callbacks. |
| <i>parameter-IntCallback</i> | Function which should be called for all ParameterInt snaps. |

Since

Version 1.2

Returns

OTF2_SUCCESS if successful

OTF2_ERROR_INVALID_ARGUMENT for an invalid `defReaderCallbacks` argument

J.21.3.20 **OTF2_ErrorCode** **OTF2_GlobalSnapReaderCallbacks_-SetParameterStringCallback** (**OTF2_GlobalSnapReaderCallbacks** * *globalSnapReaderCallbacks*, **OTF2_GlobalSnapReaderCallback_-ParameterString** *parameterStringCallback*)

Registers the callback for the ParameterString snap.

Parameters

| | |
|-----------------------------------|--|
| <i>global-SnapReaderCallbacks</i> | Struct for all callbacks. |
| <i>parameter-StringCallback</i> | Function which should be called for all ParameterString snaps. |

Since

Version 1.2

Returns

OTF2_SUCCESS if successful
OTF2_ERROR_INVALID_ARGUMENT for an invalid `defReaderCallbacks` argument

J.21.3.21 `OTF2_StatusCode OTF2_GlobalSnapReaderCallbacks_-SetParameterUnsignedIntCallback (OTF2_GlobalSnapReaderCallbacks * globalSnapReaderCallbacks, OTF2_GlobalSnapReaderCallback_-ParameterUnsignedInt parameterUnsignedIntCallback)`

Registers the callback for the `ParameterUnsignedInt` snap.

Parameters

| | |
|-------------------------------------|--|
| <i>global-SnapReaderCallbacks</i> | Struct for all callbacks. |
| <i>parameterUnsignedIntCallback</i> | Function which should be called for all <code>ParameterUnsignedInt</code> snaps. |

Since

Version 1.2

Returns

OTF2_SUCCESS if successful
OTF2_ERROR_INVALID_ARGUMENT for an invalid `defReaderCallbacks` argument

J.21.3.22 `OTF2_StatusCode OTF2_GlobalSnapReaderCallbacks_-SetSnapshotEndCallback (OTF2_GlobalSnapReaderCallbacks * globalSnapReaderCallbacks, OTF2_GlobalSnapReaderCallback_-SnapshotEnd snapshotEndCallback)`

Registers the callback for the `SnapshotEnd` snap.

Parameters

J.21 OTF2_GlobalSnapReaderCallbacks.h File Reference

| | |
|-----------------------------------|--|
| <i>global-SnapReaderCallbacks</i> | Struct for all callbacks. |
| <i>snapshotEndCallback</i> | Function which should be called for all SnapshotEnd snaps. |

Since

Version 1.2

Returns

OTF2_SUCCESS if successful

OTF2_ERROR_INVALID_ARGUMENT for an invalid `defReaderCallbacks` argument

J.21.3.23 OTF2_ErrorCode OTF2_GlobalSnapReaderCallbacks_-SetSnapshotStartCallback (OTF2_GlobalSnapReaderCallbacks * *globalSnapReaderCallbacks*, OTF2_GlobalSnapReaderCallback_-SnapshotStart *snapshotStartCallback*)

Registers the callback for the SnapshotStart snap.

Parameters

| | |
|-----------------------------------|--|
| <i>global-SnapReaderCallbacks</i> | Struct for all callbacks. |
| <i>snapshotStartCallback</i> | Function which should be called for all SnapshotStart snaps. |

Since

Version 1.2

Returns

OTF2_SUCCESS if successful

OTF2_ERROR_INVALID_ARGUMENT for an invalid `defReaderCallbacks` argument

**J.21.3.24 OTF2_ErrorCode OTF2_GlobalSnapReaderCallbacks_SetUnknownCallback
(OTF2_GlobalSnapReaderCallbacks * globalSnapReaderCallbacks,
OTF2_GlobalSnapReaderCallback_Unknown unknownCallback)**

Registers the callback for unknown snaps.

Parameters

| | |
|-----------------------------------|--|
| <i>global-SnapReaderCallbacks</i> | Struct for all callbacks. |
| <i>unknown-Callback</i> | Function which should be called for all unknown snaps. |

Since

Version 1.2

Returns

OTF2_SUCCESS if successful

OTF2_ERROR_INVALID_ARGUMENT for an invalid defReaderCallbacks argument

J.22 OTF2_IdMap.h File Reference

Identifier mapping data structure, based on Scalasca's epk_idmap.h.

```
#include <stddef.h>
#include <stdint.h>
#include <stdbool.h>
#include <otf2/OTF2_ErrorCodes.h>
```

Typedefs

- typedef struct OTF2_IdMap_struct **OTF2_IdMap**
- typedef void(* **OTF2_IdMap_TraverseCallback**)(uint64_t localId, uint64_t globalId, void *userData)
Function prototype for use in OTF2_IdMap_Traverse.
- typedef uint8_t **OTF2_IdMapMode**

J.22 OTF2_IdMap.h File Reference

Enumerations

- enum [OTF2_IdMapMode_enum](#) {
 [OTF2_ID_MAP_DENSE](#),
 [OTF2_ID_MAP_SPARSE](#) }

Functions

- [OTF2_ErrorCode OTF2_IdMap_AddIdPair](#) ([OTF2_IdMap](#) *instance, [uint64_t](#) localId, [uint64_t](#) globalId)
- [OTF2_ErrorCode OTF2_IdMap_Clear](#) ([OTF2_IdMap](#) *instance)
- [OTF2_IdMap](#) * [OTF2_IdMap_Create](#) ([OTF2_IdMapMode](#) mode, [uint64_t](#) capacity)
- [OTF2_IdMap](#) * [OTF2_IdMap_CreateFromUint32Array](#) ([uint64_t](#) length, const [uint32_t](#) *mappings, bool optimizeSize)
- [OTF2_IdMap](#) * [OTF2_IdMap_CreateFromUint64Array](#) ([uint64_t](#) length, const [uint64_t](#) *mappings, bool optimizeSize)
- void [OTF2_IdMap_Free](#) ([OTF2_IdMap](#) *instance)
- [OTF2_ErrorCode OTF2_IdMap_GetGlobalId](#) (const [OTF2_IdMap](#) *instance, [uint64_t](#) localId, [uint64_t](#) *globalId)
- [OTF2_ErrorCode OTF2_IdMap_GetMode](#) (const [OTF2_IdMap](#) *instance, [OTF2_IdMapMode](#) *mode)
- [OTF2_ErrorCode OTF2_IdMap_GetSize](#) (const [OTF2_IdMap](#) *instance, [uint64_t](#) *size)
- [OTF2_ErrorCode OTF2_IdMap_Traverse](#) (const [OTF2_IdMap](#) *instance, [OTF2_IdMap_TraverseCallback](#) callback, void *userData)

J.22.1 Detailed Description

Identifier mapping data structure, based on Scalasca's `epk_idmap.h`.

Maintainer:

Christian Rössel <c.roessel@fz-juelich.de>

This file provides type definitions and function prototypes for an identifier mapping data structure which is used to store mapping tables for converting local into global identifiers.

This mapping data structure can operate in two different modes (see [OTF2_IdMapMode](#)): A dense mapping can be used if the local identifiers are consecutively enumerated from 0 to N-1. In this case, only the global identifier are stored in the table at the

APPENDIX J. FILE DOCUMENTATION

corresponding entry, leading to compact storage and fast look-up. By contrast, if the local identifiers can consist of arbitrary numbers, a sparse mapping is necessary. Here, (localId, globalId) tuples are stored, which requires a more complicated look-up procedure.

J.22.2 Typedef Documentation

J.22.2.1 typedef struct OTF2_IdMap_struct OTF2_IdMap

Opaque data structure representing an ID mapping table.

J.22.2.2 typedef uint8_t OTF2_IdMapMode

Wrapper around enum OTF2_IdMapMode_enum, so that it is guaranteed that it is a uint8_t

J.22.3 Enumeration Type Documentation

J.22.3.1 enum OTF2_IdMapMode_enum

Enumeration type defining the two different modes of an identifier mapping table.

Enumerator:

OTF2_ID_MAP_DENSE Dense mapping table

OTF2_ID_MAP_SPARSE Sparse mapping table

J.22.4 Function Documentation

J.22.4.1 OTF2_ErrorCode OTF2_IdMap_AddIdPair (OTF2_IdMap * *instance*, uint64_t *localId*, uint64_t *globalId*)

Adds the given mapping from *localId* to *globalId* to the mapping table *instance*. If the current capacity does not suffice, the data structure is automatically resized.

Note

If the mapping table operates in dense mapping mode, the parameter *localId* has to correspond to the next entry in the mapping table.

Parameters

J.22 OTF2_IdMap.h File Reference

| | |
|-----------------|-------------------------------|
| <i>instance</i> | Object to add the mapping to. |
| <i>localId</i> | Local identifier. |
| <i>globalId</i> | Global identifier. |

Returns

OTF2_SUCCESS, or error code.

J.22.4.2 OTF2_ErrorCode OTF2_IdMap_Clear (OTF2_IdMap * *instance*)

Removes all entries in the given mapping table *instance*. It can be used, e.g., to reuse an mapping table object for new input data.

Parameters

| | |
|-----------------|--------------------------------|
| <i>instance</i> | Object to remove entries from. |
|-----------------|--------------------------------|

Returns

OTF2_SUCCESS, or error code.

J.22.4.3 OTF2_IdMap* OTF2_IdMap_Create (OTF2_IdMapMode *mode*, uint64_t *capacity*)

Creates and returns a new instance of OTF2_IdMap with the given *mode* and initial *capacity*. If the memory allocation request can not be fulfilled, NULL is returned.

Parameters

| | |
|-----------------|-------------------|
| <i>mode</i> | Mapping mode. |
| <i>capacity</i> | Initial capacity. |

Returns

Pointer to new instance or NULL if memory request couldn't be fulfilled.

J.22.4.4 OTF2_IdMap* OTF2_IdMap_CreateFromUint32Array (uint64_t *length*, const uint32_t * *mappings*, bool *optimizeSize*)

Creates and returns a new instance of OTF2_IdMap from the array given by *mappings*.

APPENDIX J. FILE DOCUMENTATION

Same as *OTF2_IdMap_CreateFromUint64Array*, excpet from a *uint32_t* array.

Parameters

| | |
|----------------------|--|
| <i>length</i> | Number of elements in the <i>mappings</i> array. |
| <i>mappings</i> | Array with a dense mapping. |
| <i>optimize-Size</i> | Creates a SPARSE mapping, if the number of non- identities is less than half the array length. |

Returns

Pointer to new instance or NULL if memory request couldn't be fulfilled.

J.22.4.5 `OTF2_IdMap* OTF2_IdMap_CreateFromUint64Array (uint64_t length, const uint64_t * mappings, bool optimizeSize)`

Creates and returns a new instance of *OTF2_IdMap* from the array given by *mappings*.

This creates always a DENSE mapping if *optimizeSize* is false. If it is true, it creates a SPARSE mapping, if the number of non-identity entries in the *mappings* array (ie. `mapping[i] != i`) is less than half the *length*.

Returns NULL when *optimizeSize* is true and the number of non-identity entries equals zero, ie. the given map is the identity map.

Parameters

| | |
|----------------------|--|
| <i>length</i> | Number of elements in the <i>mappings</i> array. |
| <i>mappings</i> | Array with a dense mapping. |
| <i>optimize-Size</i> | Creates a SPARSE mapping, if the number of non- identities is less than half the array length. |

Returns

Pointer to new instance or NULL if memory request couldn't be fulfilled.

J.22.4.6 `void OTF2_IdMap_Free (OTF2_IdMap * instance)`

Destroys the given *instance* of *OTF2_IdMap* and releases the allocated memory.

Parameters

| | |
|-----------------|--------------------|
| <i>instance</i> | Object to be freed |
|-----------------|--------------------|

J.22 OTF2_IdMap.h File Reference

J.22.4.7 `OTF2_ErrorCode OTF2_IdMap_GetGlobalId (const OTF2_IdMap * instance, uint64_t localId, uint64_t * globalId)`

Maps the given *localId* to the global id and store it in the starge provide by *globalId*.

If the given *localId* is not in the mapping, sets *globalId* to the *localId*.

Parameters

| | | |
|-----|-----------------|-------------------------------|
| | <i>instance</i> | Object to add the mapping to. |
| | <i>localId</i> | Local identifier. |
| out | <i>globalId</i> | Global identifier. |

Returns

OTF2_SUCCESS, or error code.

J.22.4.8 `OTF2_ErrorCode OTF2_IdMap_GetMode (const OTF2_IdMap * instance, OTF2_IdMapMode * mode)`

Returns the identifier mapping mode (dense/sparse) used for the given mapping table *instance*.

Parameters

| | | |
|-----|-----------------|--------------------------|
| | <i>instance</i> | Queried object. |
| out | <i>mode</i> | Identifier mapping mode. |

Returns

OTF2_SUCCESS, or error code.

J.22.4.9 `OTF2_ErrorCode OTF2_IdMap_GetSize (const OTF2_IdMap * instance, uint64_t * size)`

Returns the actual number of entries stored in the given OTF2_IdMap *instance*.

Parameters

| | | |
|-----|-----------------|--------------------|
| | <i>instance</i> | Queried object. |
| out | <i>size</i> | Number of entries. |

Returns

OTF2_SUCCESS, or error code.

J.22.4.10 `OTF2_StatusCode` `OTF2.IdMap.Traverse (const OTF2_IdMap * instance, OTF2_IdMap_TraverseCallback callback, void * userData)`

Calls for each mapping pair the callback *callback*.

Parameters

| | |
|-----------------|---|
| <i>instance</i> | Object to add the mapping to. |
| <i>callback</i> | Callback function which is called for eaach mapping pair. |
| <i>userData</i> | Data which is passed to the <i>callback</i> function. |

Returns

OTF2_SUCCESS, or error code.

J.23 OTF2_Marker.h File Reference

This file provides types and enums for markers.

```
#include <stdint.h>
#include <otf2/OTF2_ErrorCodes.h>
#include <otf2/OTF2_Definitions.h>
```

Defines

- #define `OTF2_UNDEFINED_MARKER` ((`OTF2_MarkerRef`) `OTF2_UNDEFINED_UINT32`)

The invalid value for a reference to a Marker definition.

Typedefs

- typedef uint32_t `OTF2_MarkerRef`
Type used to indicate a reference to a Marker definition.
- typedef uint8_t `OTF2_MarkerScope`
Wrapper for enum `OTF2_MarkerScope_enum`.

J.23 OTF2_Marker.h File Reference

- typedef uint8_t `OTF2_MarkerSeverity`
Wrapper for enum `OTF2_MarkerSeverity_enum`.

Enumerations

- enum `OTF2_MarkerScope_enum` {
 `OTF2_MARKER_SCOPE_GLOBAL`,
 `OTF2_MARKER_SCOPE_LOCATION`,
 `OTF2_MARKER_SCOPE_LOCATION_GROUP`,
 `OTF2_MARKER_SCOPE_SYSTEM_TREE_NODE`,
 `OTF2_MARKER_SCOPE_GROUP`,
 `OTF2_MARKER_SCOPE_COMM` }
- enum `OTF2_MarkerSeverity_enum` {
 `OTF2_SEVERITY_NONE`,
 `OTF2_SEVERITY_LOW`,
 `OTF2_SEVERITY_MEDIUM`,
 `OTF2_SEVERITY_HIGH` }

J.23.1 Detailed Description

This file provides types and enums for markers.

J.23.2 Enumeration Type Documentation

J.23.2.1 enum `OTF2_MarkerScope_enum`

A user marker does have a scope of it validity.

Enumerator:

`OTF2_MARKER_SCOPE_GLOBAL` The user marker has a global scope (could also be NONE).

`OTF2_MARKER_SCOPE_LOCATION` The user marker has a scope of a location.

`OTF2_MARKER_SCOPE_LOCATION_GROUP` The user marker has a scope of a location group.

OTF2_MARKER_SCOPE_SYSTEM_TREE_NODE The user marker has a scope of a system tree.

OTF2_MARKER_SCOPE_GROUP The user marker has a scope of a group.

OTF2_MARKER_SCOPE_COMM The user marker has a scope of a communicator.

J.23.2.2 enum OTF2_MarkerSeverity_enum

A list of possible severities of user markers.

Enumerator:

OTF2_SEVERITY_NONE The marker does not have a severity.

OTF2_SEVERITY_LOW The marker has a low severity.

OTF2_SEVERITY_MEDIUM The marker has a medium severity.

OTF2_SEVERITY_HIGH The marker has a high severity.

J.24 OTF2_MarkerReader.h File Reference

This file provides all routines that read marker records.

```
#include <stdint.h>
#include <otf2/OTF2_ErrorCodes.h>
#include <otf2/OTF2_Marker.h>
#include <otf2/OTF2_MarkerReaderCallbacks.h>
```

Functions

- [OTF2_ErrorCode OTF2_MarkerReader_ReadMarkers](#) ([OTF2_MarkerReader](#) *reader, uint64_t recordsToRead, uint64_t *recordsRead)

After callback registration, the markers could be read with the following function. The user of this function tells the system how many markers it is able to handle (recordsToRead) and the function returns how many markers where in the stream (recordsRead). It should usually be the case that both values are the same. If this is not the case, then there where less records than requested in the stream.

- [OTF2_ErrorCode OTF2_MarkerReader_SetCallbacks](#) ([OTF2_MarkerReader](#) *reader, const [OTF2_MarkerReaderCallbacks](#) *callbacks, void *userData)

J.24 OTF2_MarkerReader.h File Reference

Sets the callback functions for the given reader object. Everytime when OTF2 reads a record, a callback function is called and the records data is passed to this function. Therefore the programmer needs to set function pointers at the "callbacks" struct for the record type he wants to read.

J.24.1 Detailed Description

This file provides all routines that read marker records.

J.24.2 Function Documentation

J.24.2.1 OTF2_ErrorCode OTF2_MarkerReader_ReadMarkers (OTF2_MarkerReader * reader, uint64_t recordsToRead, uint64_t * recordsRead)

After callback registration, the markers could be read with the following function. The user of this function tells the system how many markers it is able to handle (recordsToRead) and the function returns how many markers where in the stream (recordsRead). It should usually be the case that both values are the same. If this is not the case, then there where less records than requested in the stream.

Parameters

| | |
|----------------------|--|
| <i>reader</i> | Reader Object. |
| <i>recordsToRead</i> | How many records have to be read next. |
| <i>recordsRead</i> | How many records where read? |

Since

Version 1.2

Returns

OTF2_ErrorCode with !=OTF2_SUCCESS if there was an error.

J.24.2.2 OTF2_ErrorCode OTF2_MarkerReader_SetCallbacks (OTF2_MarkerReader * reader, const OTF2_MarkerReaderCallbacks * callbacks, void * userData)

Sets the callback functions for the given reader object. Everytime when OTF2 reads a record, a callback function is called and the records data is passed to this function.

APPENDIX J. FILE DOCUMENTATION

Therefore the programmer needs to set function pointers at the "callbacks" struct for the record type he wants to read.

Parameters

| | |
|------------------|--|
| <i>reader</i> | This given reader object will be setted up with new callback functions. |
| <i>callbacks</i> | Struct which holds a function pointer for each record type. OTF2_MarkerReaderCallbacks_New . |
| <i>userData</i> | Data passed as argument <i>userData</i> to the record callbacks. |

Since

Version 1.2

Returns

[OTF2_SUCCESS](#) if successful, an error code if an error occurs.

J.25 OTF2_MarkerReaderCallbacks.h File Reference

This defines the callbacks for the marker reader.

```
#include <stdint.h>
#include <otf2/OTF2_ErrorCodes.h>
#include <otf2/OTF2_GeneralDefinitions.h>
#include <otf2/OTF2_Definitions.h>
#include <otf2/OTF2_IdMap.h>
#include <otf2/OTF2_Marker.h>
```

Typedefs

- typedef [OTF2_CallbackCode](#)(* [OTF2_MarkerReaderCallback_DefMarker](#))(void *userData, [OTF2_MarkerRef](#) self, const char *markerGroup, const char *markerCategory, [OTF2_MarkerSeverity](#) severity)

Function pointer definition for the callback which is triggered by a Marker definition record.

- typedef [OTF2_CallbackCode](#)(* [OTF2_MarkerReaderCallback_Marker](#))(void *userData, [OTF2_TimeStamp](#) timestamp, [OTF2_TimeStamp](#) duration, [OTF2_MarkerRef](#) marker, [OTF2_MarkerScope](#) scope, uint64_t scopeRef, const char *text)

J.25 OTF2_MarkerReaderCallbacks.h File Reference

Function pointer definition for the callback which is triggered by a Marker record.

- typedef [OTF2_CallbackCode](#)(* [OTF2_MarkerReaderCallback_Unknown](#))(void *userData)

Function pointer definition for the callback which is triggered for an unknown marker.

- typedef struct [OTF2_MarkerReaderCallbacks_struct](#) [OTF2_MarkerReaderCallbacks](#)

Opaque struct which holds all definition record callbacks.

Functions

- void [OTF2_MarkerReaderCallbacks_Clear](#) ([OTF2_MarkerReaderCallbacks](#) *markerReaderCallbacks)

Clears a struct for the marker callbacks.

- void [OTF2_MarkerReaderCallbacks_Delete](#) ([OTF2_MarkerReaderCallbacks](#) *markerReaderCallbacks)

Deallocates a struct for the marker callbacks.

- [OTF2_MarkerReaderCallbacks](#) * [OTF2_MarkerReaderCallbacks_New](#) (void)

Allocates a new struct for the marker callbacks.

- [OTF2_ErrorCode](#) [OTF2_MarkerReaderCallbacks_SetDefMarkerCallback](#) ([OTF2_MarkerReaderCallbacks](#) *markerReaderCallbacks, [OTF2_MarkerReaderCallback_DefMarker](#) defMarkerCallback)

Registers the callback for the Marker definition.

- [OTF2_ErrorCode](#) [OTF2_MarkerReaderCallbacks_SetMarkerCallback](#) ([OTF2_MarkerReaderCallbacks](#) *markerReaderCallbacks, [OTF2_MarkerReaderCallback_Marker](#) markerCallback)

Registers the callback for the Marker record.

- [OTF2_ErrorCode](#) [OTF2_MarkerReaderCallbacks_SetUnknownCallback](#) ([OTF2_MarkerReaderCallbacks](#) *markerReaderCallbacks, [OTF2_MarkerReaderCallback_Unknown](#) unknownCallback)

Registers the callback for an unknown marker.

J.25.1 Detailed Description

This defines the callbacks for the marker reader.

J.25.2 Typedef Documentation

J.25.2.1 `typedef OTF2_CallbackCode(* OTF2_MarkerReaderCallback_ -
DefMarker)(void *userData, OTF2_MarkerRef self, const char
*markerGroup, const char *markerCategory, OTF2_MarkerSeverity severity)`

Function pointer definition for the callback which is triggered by a Marker definition record.

Parameters

| | |
|-----------------------|--|
| <i>userData</i> | User data as set by OTF2_Reader_RegisterMarkerCallbacks or OTF2_MarkerReader_SetCallbacks . |
| <i>self</i> | Reference to this marker definition. |
| <i>markerGroup</i> | Group name, e.g., "MUST", ... |
| <i>markerCategory</i> | Category, e.g., "Argument type error", ... The tuple (markerGroup, markerCategory) must be unique over all marker definitions. |
| <i>severity</i> | The severity for this marker category. |

Since

Version 1.2

Returns

[OTF2_CALLBACK_SUCCESS](#) or [OTF2_CALLBACK_INTERRUPT](#).

J.25.2.2 `typedef OTF2_CallbackCode(* OTF2_MarkerReaderCallback_ -
Marker)(void *userData, OTF2_TimeStamp timestamp,
OTF2_TimeStamp duration, OTF2_MarkerRef marker,
OTF2_MarkerScope scope, uint64_t scopeRef, const char *text)`

Function pointer definition for the callback which is triggered by a Marker record.

Parameters

| | |
|------------------|---|
| <i>userData</i> | User data as set by OTF2_Reader_RegisterMarkerCallbacks or OTF2_MarkerReader_SetCallbacks . |
| <i>timestamp</i> | Timestamp of the marker. |

J.25 OTF2_MarkerReaderCallbacks.h File Reference

| | |
|-----------------|--|
| <i>duration</i> | Duration the marker applies. |
| <i>marker</i> | Reference to the marker definition. |
| <i>scope</i> | The type of scope of this marker instance. |
| <i>scopeRef</i> | The reference to an element of the scope of this marker. Depends on scope. |
| <i>text</i> | A textual description for this marker. |

Since

Version 1.2

Returns

[*OTF2_CALLBACK_SUCCESS*](#) or [*OTF2_CALLBACK_INTERRUPT*](#).

J.25.2.3 typedef OTF2_CallbackCode(* OTF2_MarkerReaderCallback_Unknown)(void *userData)

Function pointer definition for the callback which is triggered for an unknown marker.

Parameters

| | |
|-----------------|---|
| <i>userData</i> | User data as set by OTF2_Reader_RegisterMarkerCallbacks or OTF2_MarkerReader_SetCallbacks . |
|-----------------|---|

Since

Version 1.2

Returns

[*OTF2_CALLBACK_SUCCESS*](#) or [*OTF2_CALLBACK_INTERRUPT*](#).

J.25.3 Function Documentation

J.25.3.1 void OTF2_MarkerReaderCallbacks.Clear (OTF2_MarkerReaderCallbacks * markerReaderCallbacks)

Clears a struct for the marker callbacks.

Since

Version 1.2

APPENDIX J. FILE DOCUMENTATION

Parameters

| | |
|-------------------------------|---|
| <i>marker-ReaderCallbacks</i> | Handle to a struct previously allocated with OTF2_MarkerReaderCallbacks_New . |
|-------------------------------|---|

J.25.3.2 void [OTF2_MarkerReaderCallbacks_Delete](#) ([OTF2_MarkerReaderCallbacks](#) * *markerReaderCallbacks*)

Deallocates a struct for the marker callbacks.

Since

Version 1.2

Parameters

| | |
|-------------------------------|---|
| <i>marker-ReaderCallbacks</i> | Handle to a struct previously allocated with OTF2_MarkerReaderCallbacks_New . |
|-------------------------------|---|

J.25.3.3 [OTF2_MarkerReaderCallbacks*](#) [OTF2_MarkerReaderCallbacks_New](#) (void)

Allocates a new struct for the marker callbacks.

Since

Version 1.2

Returns

A newly allocated struct of type [OTF2_MarkerReaderCallbacks](#).

J.25.3.4 [OTF2_ErrorCode](#) [OTF2_MarkerReaderCallbacks_SetDefMarkerCallback](#) ([OTF2_MarkerReaderCallbacks](#) * *markerReaderCallbacks*, [OTF2_MarkerReaderCallback_DefMarker](#) *defMarkerCallback*)

Registers the callback for the Marker definition.

Parameters

J.25 OTF2_MarkerReaderCallbacks.h File Reference

| | |
|--------------------------------|---|
| <i>marker-Reader-Callbacks</i> | Struct for all callbacks. |
| <i>defMarker-Callback</i> | Function which should be called for all Marker definitions. |

Since

Version 1.2

Returns

OTF2_SUCCESS if successful

OTF2_ERROR_INVALID_ARGUMENT for an invalid `defReaderCallbacks` argument

J.25.3.5 OTF2_ErrorCode OTF2_MarkerReaderCallbacks_SetMarkerCallback (OTF2_MarkerReaderCallbacks * *markerReaderCallbacks*, OTF2_MarkerReaderCallback_Marker *markerCallback*)

Registers the callback for the Marker record.

Parameters

| | |
|--------------------------------|---|
| <i>marker-Reader-Callbacks</i> | Struct for all callbacks. |
| <i>marker-Callback</i> | Function which should be called for all Marker records. |

Since

Version 1.2

Returns

OTF2_SUCCESS if successful

OTF2_ERROR_INVALID_ARGUMENT for an invalid `defReaderCallbacks` argument

APPENDIX J. FILE DOCUMENTATION

J.25.3.6 `OTF2_ErrorCode` `OTF2_MarkerReaderCallbacks_SetUnknownCallback`
(`OTF2_MarkerReaderCallbacks` * *markerReaderCallbacks*,
`OTF2_MarkerReaderCallback_Unknown` *unknownCallback*)

Registers the callback for an unknown marker.

Parameters

| | |
|--------------------------------|--|
| <i>marker-Reader-Callbacks</i> | Struct for all callbacks. |
| <i>unknown-Callback</i> | Function which should be called for all unknown definitions. |

Since

Version 1.2

Returns

`OTF2_SUCCESS` if successful

`OTF2_ERROR_INVALID_ARGUMENT` for an invalid `defReaderCallbacks` argument

J.26 OTF2_MarkerWriter.h File Reference

This file provides all routines that write marker records.

```
#include <stdint.h>
#include <otf2/OTF2_ErrorCodes.h>
#include <otf2/OTF2_Definitions.h>
#include <otf2/OTF2_Marker.h>
```

Typedefs

- typedef struct `OTF2_MarkerWriter_struct` `OTF2_MarkerWriter`
Handle definition for the external marker writer.

Functions

- `OTF2_ErrorCode` `OTF2_MarkerWriter_WriteDefMarker` (`OTF2_MarkerWriter` **writerHandle*, `OTF2_MarkerRef` *self*, const char **markerGroup*, const char

J.26 OTF2_MarkerWriter.h File Reference

*markerCategory, [OTF2_MarkerSeverity](#) severity)

Write a marker definition.

- [OTF2_ErrorCode](#) [OTF2_MarkerWriter_WriteMarker](#) ([OTF2_MarkerWriter](#) *writerHandle, uint64_t time, uint64_t duration, [OTF2_MarkerRef](#) marker, [OTF2_MarkerScope](#) scope, uint64_t scopeRef, const char *text)

Write a marker record.

J.26.1 Detailed Description

This file provides all routines that write marker records.

J.26.2 Function Documentation

J.26.2.1 [OTF2_ErrorCode](#) [OTF2_MarkerWriter_WriteDefMarker](#) (
[OTF2_MarkerWriter](#) * *writerHandle*, [OTF2_MarkerRef](#) *self*, const
char * *markerGroup*, const char * *markerCategory*, [OTF2_MarkerSeverity](#)
severity)

Write a marker definition.

Parameters

| | |
|-----------------------|--|
| <i>writerHandle</i> | Marker writer handle. |
| <i>self</i> | Reference to this marker definition. |
| <i>markerGroup</i> | Group name e.g. "MUST". |
| <i>markerCategory</i> | Category name e.g "Argument type error". The tuple (markerGroup, markerCategory) must be unique over all marker definitions. |
| <i>severity</i> | The severity for this marker category. |

Since

Version 1.2

Returns

[OTF2_SUCCESS](#) if successful, an error code if an error occurs.

APPENDIX J. FILE DOCUMENTATION

J.26.2.2 `OTF2_ErrorCode OTF2_MarkerWriter_WriteMarker (OTF2_MarkerWriter * writerHandle, uint64.t time, uint64.t duration, OTF2_MarkerRef marker, OTF2_MarkerScope scope, uint64.t scopeRef, const char * text)`

Write a marker record.

Parameters

| | |
|---------------------|--|
| <i>writerHandle</i> | Marker writer handle. |
| <i>time</i> | Time of the marker. |
| <i>duration</i> | A possible duration of this marker. May be 0. |
| <i>marker</i> | Reference to a marker definition. |
| <i>scope</i> | The type of scope of this marker instance: OTF2_MARKER_SCOPE_GLOBAL , OTF2_MARKER_SCOPE_LOCATION , OTF2_MARKER_SCOPE_LOCATION_GROUP , OTF2_MARKER_SCOPE_SYSTEM_TREE_NODE , OTF2_MARKER_SCOPE_GROUP , or OTF2_MARKER_SCOPE_COMM . |
| <i>scopeRef</i> | The reference to an element of the scope of this marker. Depends on scope. |
| <i>text</i> | A textual description for this marker. |

Since

Version 1.2

Returns

[OTF2_SUCCESS](#) if successful, an error code if an error occurs.

J.27 OTF2_Reader.h File Reference

Reading interface for OTF2 archives.

```
#include <stdint.h>
#include <otf2/OTF2_ErrorCodes.h>
#include <otf2/OTF2_Archive.h>
```

Typedefs

- typedef struct OTF2_Reader_struct [OTF2_Reader](#)
Keeps all necessary information for the reader.

J.27 OTF2_Reader.h File Reference

Functions

- [OTF2_ErrorCode](#) [OTF2_Reader_Close](#) ([OTF2_Reader](#) *reader)
Close a reader handle.
- [OTF2_ErrorCode](#) [OTF2_Reader_CloseDefReader](#) ([OTF2_Reader](#) *reader, [OTF2_DefReader](#) *defReader)
Close a local definition reader.
- [OTF2_ErrorCode](#) [OTF2_Reader_CloseEvtReader](#) ([OTF2_Reader](#) *reader, [OTF2_EvtReader](#) *evtReader)
Close a local event reader.
- [OTF2_ErrorCode](#) [OTF2_Reader_CloseGlobalDefReader](#) ([OTF2_Reader](#) *reader, [OTF2_GlobalDefReader](#) *globalDefReader)
Closes the global definition reader.
- [OTF2_ErrorCode](#) [OTF2_Reader_CloseGlobalEvtReader](#) ([OTF2_Reader](#) *reader, [OTF2_GlobalEvtReader](#) *globalEvtReader)
Closes the global event reader.
- [OTF2_ErrorCode](#) [OTF2_Reader_CloseGlobalSnapReader](#) ([OTF2_Reader](#) *reader, [OTF2_GlobalSnapReader](#) *globalSnapReader)
Closes the global snapshot reader.
- [OTF2_ErrorCode](#) [OTF2_Reader_CloseMarkerReader](#) ([OTF2_Reader](#) *reader, [OTF2_MarkerReader](#) *markerReader)
Closes the marker reader.
- [OTF2_ErrorCode](#) [OTF2_Reader_CloseMarkerWriter](#) ([OTF2_Reader](#) *reader, [OTF2_MarkerWriter](#) *markerWriter)
Closes the marker writer.
- [OTF2_ErrorCode](#) [OTF2_Reader_CloseSnapReader](#) ([OTF2_Reader](#) *reader, [OTF2_SnapReader](#) *snapReader)
Close a local snapshot reader.
- [OTF2_ErrorCode](#) [OTF2_Reader_CloseThumbReader](#) ([OTF2_Reader](#) *reader, [OTF2_ThumbReader](#) *thumbReader)
Close an opened thumbnail reader.

APPENDIX J. FILE DOCUMENTATION

- `OTF2_ErrorCode OTF2_Reader_GetBoolProperty (OTF2_Reader *reader, const char *name, bool *value)`
Get the value of the named trace file property as boolean.
- `OTF2_ErrorCode OTF2_Reader_GetChunkSize (OTF2_Reader *reader, uint64_t *chunkSizeEvents, uint64_t *chunkSizeDefinitions)`
Get event and definition chunk sizes.
- `OTF2_ErrorCode OTF2_Reader_GetCompression (OTF2_Reader *reader, OTF2_Compression *compression)`
Get copression mode.
- `OTF2_ErrorCode OTF2_Reader_GetCreator (OTF2_Reader *reader, char **creator)`
Get creator name.
- `OTF2_DefReader * OTF2_Reader_GetDefReader (OTF2_Reader *reader, OTF2_LocationRef location)`
Get a local definition reader.
- `OTF2_ErrorCode OTF2_Reader_GetDescription (OTF2_Reader *reader, char **description)`
Get description.
- `OTF2_EvtReader * OTF2_Reader_GetEvtReader (OTF2_Reader *reader, OTF2_LocationRef location)`
Get a local event reader.
- `OTF2_ErrorCode OTF2_Reader_GetFileSubstrate (OTF2_Reader *reader, OTF2_FileSubstrate *substrate)`
Get file substrate information.
- `OTF2_GlobalDefReader * OTF2_Reader_GetGlobalDefReader (OTF2_Reader *reader)`
Get a global definition reader.
- `OTF2_GlobalEvtReader * OTF2_Reader_GetGlobalEvtReader (OTF2_Reader *reader)`
Get a global event reader.
- `OTF2_GlobalSnapReader * OTF2_Reader_GetGlobalSnapReader (OTF2_Reader *reader)`

J.27 OTF2_Reader.h File Reference

Get a global snap reader.

- [OTF2_Reader_GetMachineName](#) (OTF2_Reader *reader, char **machineName)

Get machine name.

- [OTF2_Reader_GetMarkerReader](#) (OTF2_Reader *reader)

Get a marker reader.

- [OTF2_Reader_GetMarkerWriter](#) (OTF2_Reader *reader)

Get a marker writer.

- [OTF2_Reader_GetNumberOfGlobalDefinitions](#) (OTF2_Reader *reader, uint64_t *numberOfDefinitions)

Get number of global definitions.

- [OTF2_Reader_GetNumberOfLocations](#) (OTF2_Reader *reader, uint64_t *numberOfLocations)

Get number of locations.

- [OTF2_Reader_GetNumberOfSnapshots](#) (OTF2_Reader *reader, uint32_t *number)

Get number of snapshots.

- [OTF2_Reader_GetNumberOfThumbnails](#) (OTF2_Reader *reader, uint32_t *number)

Get number of thumbs.

- [OTF2_Reader_GetProperty](#) (OTF2_Reader *reader, const char *name, char **value)

Get the value of the named trace file property.

- [OTF2_Reader_GetPropertyNames](#) (OTF2_Reader *reader, uint32_t *numberOfProperties, char ***names)

Get the names of all trace file properties.

- [OTF2_Reader_GetSnapReader](#) (OTF2_Reader *reader, OTF2_LocationRef location)

Get a local snapshot reader.

APPENDIX J. FILE DOCUMENTATION

- `OTF2_ThumbReader * OTF2_Reader_GetThumbReader (OTF2_Reader *reader, uint32_t number)`
Get a thumb reader.
- `OTF2_ErrorCode OTF2_Reader_GetTraceId (OTF2_Reader *reader, uint64_t *id)`
Get the identifier of the trace file.
- `OTF2_ErrorCode OTF2_Reader_GetVersion (OTF2_Reader *reader, uint8_t *major, uint8_t *minor, uint8_t *bugfix)`
Get OTF2 version.
- `OTF2_ErrorCode OTF2_Reader_HasGlobalEvent (OTF2_Reader *reader, OTF2_GlobalEvtReader *evtReader, int *flag)`
Has the global event reader at least one more event to deliver.
- `OTF2_Reader * OTF2_Reader_Open (const char *anchorFilePath)`
Create a new reader handle.
- `OTF2_ErrorCode OTF2_Reader_ReadAllGlobalDefinitions (OTF2_Reader *reader, OTF2_GlobalDefReader *defReader, uint64_t *definitionsRead)`
Read all definitions via a global definition reader.
- `OTF2_ErrorCode OTF2_Reader_ReadAllGlobalEvents (OTF2_Reader *reader, OTF2_GlobalEvtReader *evtReader, uint64_t *eventsRead)`
Read all events via a global event reader.
- `OTF2_ErrorCode OTF2_Reader_ReadAllGlobalSnapshots (OTF2_Reader *reader, OTF2_GlobalSnapReader *snapReader, uint64_t *recordsRead)`
Read all records via a global snapshot reader.
- `OTF2_ErrorCode OTF2_Reader_ReadAllLocalDefinitions (OTF2_Reader *reader, OTF2_DefReader *defReader, uint64_t *definitionsRead)`
Read all definitions via a local definition reader.
- `OTF2_ErrorCode OTF2_Reader_ReadAllLocalEvents (OTF2_Reader *reader, OTF2_EvtReader *evtReader, uint64_t *eventsRead)`
Read all events via a local event reader.
- `OTF2_ErrorCode OTF2_Reader_ReadAllLocalSnapshots (OTF2_Reader *reader, OTF2_SnapReader *snapReader, uint64_t *recordsRead)`
Read all records via a local snapshot reader.

J.27 OTF2_Reader.h File Reference

- [OTF2_ErrorCode OTF2_Reader_ReadAllMarkers](#) ([OTF2_Reader](#) *reader, [OTF2_MarkerReader](#) *markerReader, [uint64_t](#) *markersRead)
Read all markers via a marker reader.
- [OTF2_ErrorCode OTF2_Reader_ReadGlobalDefinitions](#) ([OTF2_Reader](#) *reader, [OTF2_GlobalDefReader](#) *defReader, [uint64_t](#) definitionsToRead, [uint64_t](#) *definitionsRead)
Read a given number of definitions via a global definition reader.
- [OTF2_ErrorCode OTF2_Reader_ReadGlobalEvent](#) ([OTF2_Reader](#) *reader, [OTF2_GlobalEvtReader](#) *evtReader)
Read an event via a global event reader.
- [OTF2_ErrorCode OTF2_Reader_ReadGlobalEvents](#) ([OTF2_Reader](#) *reader, [OTF2_GlobalEvtReader](#) *evtReader, [uint64_t](#) eventsToRead, [uint64_t](#) *eventsRead)

Read a given number of events via a global event reader.
- [OTF2_ErrorCode OTF2_Reader_ReadGlobalSnapshots](#) ([OTF2_Reader](#) *reader, [OTF2_GlobalSnapReader](#) *snapReader, [uint64_t](#) recordsToRead, [uint64_t](#) *recordsRead)
Read a given number of records via a global snapshot reader.
- [OTF2_ErrorCode OTF2_Reader_ReadLocalDefinitions](#) ([OTF2_Reader](#) *reader, [OTF2_DefReader](#) *defReader, [uint64_t](#) definitionsToRead, [uint64_t](#) *definitionsRead)

Read a given number of definitions via a local definition reader.
- [OTF2_ErrorCode OTF2_Reader_ReadLocalEvents](#) ([OTF2_Reader](#) *reader, [OTF2_EvtReader](#) *evtReader, [uint64_t](#) eventsToRead, [uint64_t](#) *eventsRead)

Read a given number of events via a local event reader.
- [OTF2_ErrorCode OTF2_Reader_ReadLocalEventsBackward](#) ([OTF2_Reader](#) *reader, [OTF2_EvtReader](#) *evtReader, [uint64_t](#) eventsToRead, [uint64_t](#) *eventsRead)

Read a given number of events via a local event reader backwards.
- [OTF2_ErrorCode OTF2_Reader_ReadLocalSnapshots](#) ([OTF2_Reader](#) *reader, [OTF2_SnapReader](#) *snapReader, [uint64_t](#) recordsToRead, [uint64_t](#) *recordsRead)

APPENDIX J. FILE DOCUMENTATION

Read a given number of records via a local snapshot reader.

- [OTF2_ErrorCode](#) [OTF2_Reader_ReadMarkers](#) ([OTF2_Reader](#) *reader, [OTF2_MarkerReader](#) *markerReader, [uint64_t](#) markersToRead, [uint64_t](#) *markersRead)

Read a given number of markers via a marker reader.

- [OTF2_ErrorCode](#) [OTF2_Reader_RegisterDefCallbacks](#) ([OTF2_Reader](#) *reader, [OTF2_DefReader](#) *defReader, [const](#) [OTF2_DefReaderCallbacks](#) *callbacks, [void](#) *userData)

Register local definition reader callbacks.

- [OTF2_ErrorCode](#) [OTF2_Reader_RegisterEvtCallbacks](#) ([OTF2_Reader](#) *reader, [OTF2_EvtReader](#) *evtReader, [const](#) [OTF2_EvtReaderCallbacks](#) *callbacks, [void](#) *userData)

Register event reader callbacks.

- [OTF2_ErrorCode](#) [OTF2_Reader_RegisterGlobalDefCallbacks](#) ([OTF2_Reader](#) *reader, [OTF2_GlobalDefReader](#) *defReader, [const](#) [OTF2_GlobalDefReaderCallbacks](#) *callbacks, [void](#) *userData)

Register global definition reader callbacks.

- [OTF2_ErrorCode](#) [OTF2_Reader_RegisterGlobalEvtCallbacks](#) ([OTF2_Reader](#) *reader, [OTF2_GlobalEvtReader](#) *evtReader, [const](#) [OTF2_GlobalEvtReaderCallbacks](#) *callbacks, [void](#) *userData)

Register global event reader callbacks.

- [OTF2_ErrorCode](#) [OTF2_Reader_RegisterGlobalSnapCallbacks](#) ([OTF2_Reader](#) *reader, [OTF2_GlobalSnapReader](#) *evtReader, [const](#) [OTF2_GlobalSnapReaderCallbacks](#) *callbacks, [void](#) *userData)

Register global event reader callbacks.

- [OTF2_ErrorCode](#) [OTF2_Reader_RegisterMarkerCallbacks](#) ([OTF2_Reader](#) *reader, [OTF2_MarkerReader](#) *markerReader, [const](#) [OTF2_MarkerReaderCallbacks](#) *callbacks, [void](#) *userData)

Register marker reader callbacks.

- [OTF2_ErrorCode](#) [OTF2_Reader_RegisterSnapCallbacks](#) ([OTF2_Reader](#) *reader, [OTF2_SnapReader](#) *snapReader, [const](#) [OTF2_SnapReaderCallbacks](#) *callbacks, [void](#) *userData)

Register snapshot event reader callbacks.

J.27 OTF2_Reader.h File Reference

- [OTF2_Reader_SetFileSionCallbacks](#) ([OTF2_Reader](#) *reader, const [OTF2_FileSionCallbacks](#) *fileSionCallbacks, void *fileSionData)

Register SION callbacks to the reader.

J.27.1 Detailed Description

Reading interface for OTF2 archives.

Maintainer:

Michael Wagner <michael.wagner@zih.tu-dresden.de>

Authors

Dominic Eschweiler <d.eschweiler@fz-juelich.de>, Michael Wagner <michael.wagner@zih.tu-dresden.de>

J.27.2 Function Documentation

J.27.2.1 [OTF2_Reader_Close](#) ([OTF2_Reader](#) * reader)

Close a reader handle.

Closes a reader handle and releases all associated handles. Does nothing if NULL is provided.

Parameters

| | |
|---------------|----------------|
| <i>reader</i> | Reader handle. |
|---------------|----------------|

Returns

[OTF2_SUCCESS](#) if successful, an error code if an error occurs.

J.27.2.2 [OTF2_Reader_CloseDefReader](#) ([OTF2_Reader](#) * reader, [OTF2_DefReader](#) * defReader)

Close a local definition reader.

Parameters

| | |
|------------------|---------------------------------|
| <i>reader</i> | Valid reader handle. |
| <i>defReader</i> | Definition reader to be closed. |

Returns

OTF2_SUCCESS if successful, an error code if an error occurs.

J.27.2.3 *OTF2_ErrorCode* *OTF2_Reader_CloseEvtReader* (*OTF2_Reader * reader*,
*OTF2_EvtReader * evtReader*)

Close a local event reader.

Parameters

| | |
|------------------|----------------------------|
| <i>reader</i> | Valid reader handle. |
| <i>evtReader</i> | Event reader to be closed. |

Returns

OTF2_SUCCESS if successful, an error code if an error occurs.

J.27.2.4 *OTF2_ErrorCode* *OTF2_Reader_CloseGlobalDefReader* (*OTF2_Reader * reader*,
*OTF2_GlobalDefReader * globalDefReader*)

Closes the global definition reader.

Parameters

| | |
|-------------------------|-------------------------------|
| <i>reader</i> | Valid reader handle. |
| <i>globalDef-Reader</i> | The global definition reader. |

Returns

OTF2_SUCCESS if successful, an error code if an error occurs.

J.27.2.5 *OTF2_ErrorCode* *OTF2_Reader_CloseGlobalEvtReader* (*OTF2_Reader * reader*,
*OTF2_GlobalEvtReader * globalEvtReader*)

Closes the global event reader.

This closes also all local event readers.

Parameters

| | |
|---------------|----------------------|
| <i>reader</i> | Valid reader handle. |
|---------------|----------------------|

J.27 OTF2_Reader.h File Reference

| | |
|------------------------|--------------------------|
| <i>globalEvtReader</i> | The global event reader. |
|------------------------|--------------------------|

Returns

[OTF2_SUCCESS](#) if successful, an error code if an error occurs.

J.27.2.6 OTF2_ErrorCode OTF2_Reader_CloseGlobalSnapReader (OTF2_Reader * reader, OTF2_GlobalSnapReader * globalSnapReader)

Closes the global snapshot reader.

Parameters

| | |
|-------------------------|-----------------------------|
| <i>reader</i> | Valid reader handle. |
| <i>globalSnapReader</i> | The global snapshot reader. |

Returns

[OTF2_SUCCESS](#) if successful, an error code if an error occurs.

Since

Version 1.2

J.27.2.7 OTF2_ErrorCode OTF2_Reader_CloseMarkerReader (OTF2_Reader * reader, OTF2_MarkerReader * markerReader)

Closes the marker reader.

Parameters

| | |
|---------------------|----------------------|
| <i>reader</i> | Valid reader handle. |
| <i>markerReader</i> | The marker reader. |

Since

Version 1.2

Returns

[OTF2_SUCCESS](#) if successful, an error code if an error occurs.

APPENDIX J. FILE DOCUMENTATION

J.27.2.8 `OTF2_StatusCode` `OTF2_Reader_CloseMarkerWriter (OTF2_Reader *
reader, OTF2_MarkerWriter * markerWriter)`

Closes the marker writer.

Parameters

| | |
|---------------------------|----------------------|
| <i>reader</i> | Valid reader handle. |
| <i>marker- Writer</i> | The marker writer. |

Since

Version 1.2

Returns

[*OTF2_SUCCESS*](#) if successful, an error code if an error occurs.

J.27.2.9 `OTF2_StatusCode` `OTF2_Reader_CloseSnapReader (OTF2_Reader *
reader, OTF2_SnapReader * snapReader)`

Close a local snapshot reader.

Parameters

| | |
|-------------------|-------------------------------|
| <i>reader</i> | Valid reader handle. |
| <i>snapReader</i> | snapshot reader to be closed. |

Returns

[*OTF2_SUCCESS*](#) if successful, an error code if an error occurs.

Since

Version 1.2

J.27.2.10 `OTF2_StatusCode` `OTF2_Reader_CloseThumbReader (OTF2_Reader *
reader, OTF2_ThumbReader * thumbReader)`

Close an opened thumbnail reader.

Parameters

J.27 OTF2_Reader.h File Reference

| | |
|--------------------|------------------------------------|
| <i>reader</i> | Reader handle. |
| <i>thumbReader</i> | Thumbn reader handle to be closed. |

Since

Version 1.2

Returns

[*OTF2_SUCCESS*](#) if successful, an error code if an error occurs.

J.27.2.11 **OTF2_ErrorCode** OTF2_Reader_GetBoolProperty (OTF2_Reader * *reader*, const char * *name*, bool * *value*)

Get the value of the named trace file property as boolean.

Parameters

| | | |
|-----|---------------|---|
| | <i>reader</i> | Reader handle. |
| | <i>name</i> | Name of the property. |
| out | <i>value</i> | Returned boolean value of the property. |

Returns

[*OTF2_SUCCESS*](#) if successful

[*OTF2_ERROR_PROPERTY_NOT_FOUND*](#) if the named property was not found

[*OTF2_ERROR_PROPERTY_VALUE_INVALID*](#) if the value could not be interpreted as an boolean value

J.27.2.12 **OTF2_ErrorCode** OTF2_Reader_GetChunkSize (OTF2_Reader * *reader*, uint64_t * *chunkSizeEvents*, uint64_t * *chunkSizeDefinitions*)

Get event and definition chunk sizes.

Parameters

| | | |
|-----|------------------------|-------------------------------|
| | <i>reader</i> | Reader handle. |
| out | <i>chunkSizeEvents</i> | Returned size of event chunks |

APPENDIX J. FILE DOCUMENTATION

| | | |
|-----|------------------------------|-------------------------------------|
| out | <i>chunk-SizeDefinitions</i> | Returned size of definition chunks. |
|-----|------------------------------|-------------------------------------|

Returns

OTF2_SUCCESS if successful, an error code if an error occurs.

J.27.2.13 `OTF2_StatusCode OTF2_Reader_GetCompression (OTF2_Reader * reader, OTF2_Compression * compression)`

Get copression mode.

Parameters

| | | |
|-----|--------------------|----------------------------|
| | <i>reader</i> | Reader handle. |
| out | <i>compression</i> | Returned compression mode. |

Returns

OTF2_SUCCESS if successful, an error code if an error occurs.

J.27.2.14 `OTF2_StatusCode OTF2_Reader_GetCreator (OTF2_Reader * reader, char ** creator)`

Get creator name.

Parameters

| | | |
|-----|----------------|--|
| | <i>reader</i> | Reader handle. |
| out | <i>creator</i> | Returned creator. Allocated with <i>malloc</i> . |

Returns

OTF2_SUCCESS if successful, an error code if an error occurs.

J.27.2.15 `OTF2_DefReader* OTF2_Reader_GetDefReader (OTF2_Reader * reader, OTF2_LocationRef location)`

Get a local definition reader.

J.27 OTF2_Reader.h File Reference

Parameters

| | |
|-----------------|---|
| <i>reader</i> | Valid reader handle. |
| <i>location</i> | Location ID for the requested local reader. |

Returns

Returns a handle to the local definition reader if successful, NULL otherwise.

J.27.2.16 `OTF2_ErrorCode OTF2_Reader_GetDescription (OTF2_Reader * reader, char ** description)`

Get description.

Parameters

| | | |
|-----|--------------------|--|
| | <i>reader</i> | Reader handle. |
| out | <i>description</i> | Returned description. Allocated with <i>malloc</i> . |

Returns

[*OTF2_SUCCESS*](#) if successful, an error code if an error occurs.

J.27.2.17 `OTF2_EvtReader* OTF2_Reader_GetEvtReader (OTF2_Reader * reader, OTF2_LocationRef location)`

Get a local event reader.

Parameters

| | |
|-----------------|---|
| <i>reader</i> | Valid reader handle. |
| <i>location</i> | Location ID for the requested local reader. |

Returns

Returns a handle to the local event reader if successful, NULL otherwise.

J.27.2.18 `OTF2_ErrorCode OTF2_Reader_GetFileSubstrate (OTF2_Reader * reader, OTF2_FileSubstrate * substrate)`

Get file substrate information.

APPENDIX J. FILE DOCUMENTATION

Parameters

| | | |
|-----|------------------|--------------------------|
| | <i>reader</i> | Reader handle. |
| out | <i>substrate</i> | Returned file substrate. |

Returns

OTF2_SUCCESS if successful, an error code if an error occurs.

J.27.2.19 *OTF2_GlobalDefReader** *OTF2_Reader_GetGlobalDefReader* (
*OTF2_Reader * reader*)

Get a global definition reader.

Parameters

| | |
|---------------|----------------------|
| <i>reader</i> | Valid reader handle. |
|---------------|----------------------|

Returns

Returns a handle to the global definition reader if successful, NULL otherwise.

J.27.2.20 *OTF2_GlobalEvtReader** *OTF2_Reader_GetGlobalEvtReader* (
*OTF2_Reader * reader*)

Get a global event reader.

Parameters

| | |
|---------------|----------------------|
| <i>reader</i> | Valid reader handle. |
|---------------|----------------------|

Returns

Returns a handle to the global event reader if successful, NULL otherwise.

J.27.2.21 *OTF2_GlobalSnapReader** *OTF2_Reader_GetGlobalSnapReader* (
*OTF2_Reader * reader*)

Get a global snap reader.

Parameters

| | |
|---------------|----------------------|
| <i>reader</i> | Valid reader handle. |
|---------------|----------------------|

J.27 OTF2_Reader.h File Reference

Returns

Returns a handle to the global snap reader if successful, NULL otherwise.

Since

Version 1.2

J.27.2.22 **OTF2_ErrorCode** **OTF2_Reader_GetMachineName** (**OTF2_Reader *** **reader**, **char **** *machineName*)

Get machine name.

Parameters

| | | |
|-----|---------------------|---|
| | <i>reader</i> | Reader handle. |
| out | <i>machine-Name</i> | Returned machine name. Allocated with <i>malloc</i> . |

Returns

[*OTF2_SUCCESS*](#) if successful, an error code if an error occurs.

J.27.2.23 **OTF2_MarkerReader*** **OTF2_Reader_GetMarkerReader** (**OTF2_Reader *** **reader**)

Get a marker reader.

Parameters

| | | |
|--|---------------|----------------------|
| | <i>reader</i> | Valid reader handle. |
|--|---------------|----------------------|

Since

Version 1.2

Returns

Returns a handle to the marker reader if successful, NULL otherwise.

J.27.2.24 **OTF2_MarkerWriter*** **OTF2_Reader_GetMarkerWriter** (**OTF2_Reader *** **reader**)

Get a marker writer.

APPENDIX J. FILE DOCUMENTATION

Parameters

| | |
|---------------|----------------------|
| <i>reader</i> | Valid reader handle. |
|---------------|----------------------|

Since

Version 1.2

Returns

Returns a handle to the marker writer if successful, NULL otherwise.

J.27.2.25 **OTF2_ErrorCode** **OTF2_Reader_GetNumberOfGlobalDefinitions** (**OTF2_Reader * reader**, **uint64_t * numberOfDefinitions**)

Get number of global definitions.

Parameters

| | | |
|-----|----------------------------|--|
| | <i>reader</i> | Reader handle. |
| out | <i>numberOfDefinitions</i> | Returned number of global definitions. |

Returns

[*OTF2_SUCCESS*](#) if successful, an error code if an error occurs.

J.27.2.26 **OTF2_ErrorCode** **OTF2_Reader_GetNumberOfLocations** (**OTF2_Reader * reader**, **uint64_t * numberOfLocations**)

Get number of locations.

Parameters

| | | |
|-----|--------------------------|-------------------------------|
| | <i>reader</i> | Reader handle. |
| out | <i>numberOfLocations</i> | Returned number of locations. |

Returns

[*OTF2_SUCCESS*](#) if successful, an error code if an error occurs.

J.27 OTF2_Reader.h File Reference

J.27.2.27 `OTF2_Reader_GetNumberOfSnapshots (OTF2_Reader * reader, uint32_t * number)`

Get number of snapshots.

Parameters

| | | |
|-----|---------------|-------------------------------|
| | <i>reader</i> | Reader handle. |
| out | <i>number</i> | Returned number of snapshots. |

Returns

[*OTF2_SUCCESS*](#) if successful, an error code if an error occurs.

Since

Version 1.2

J.27.2.28 `OTF2_Reader_GetNumberOfThumbnails (OTF2_Reader * reader, uint32_t * number)`

Get number of thumbs.

Parameters

| | | |
|-----|---------------|----------------------------|
| | <i>reader</i> | Reader handle. |
| out | <i>number</i> | Returned number of thumbs. |

Returns

[*OTF2_SUCCESS*](#) if successful, an error code if an error occurs.

Since

Version 1.2

J.27.2.29 `OTF2_Reader_GetProperty (OTF2_Reader * reader, const char * name, char ** value)`

Get the value of the named trace file property.

Parameters

| | | |
|-----|---------------|--|
| | <i>reader</i> | Reader handle. |
| | <i>name</i> | Name of the property. |
| out | <i>value</i> | Returned value of the property. Allocated with <i>malloc</i> . |

APPENDIX J. FILE DOCUMENTATION

Returns

OTF2_SUCCESS if successful

OTF2_ERROR_PROPERTY_NOT_FOUND if the named property was not found

J.27.2.30 *OTF2_ErrorCode* *OTF2_Reader_GetPropertyNames* (*OTF2_Reader* * *reader*, *uint32_t* * *numberOfProperties*, *char* *** *names*)

Get the names of all trace file properties.

Parameters

| | | |
|-----|---------------------------|--|
| | <i>reader</i> | Reader handle. |
| out | <i>numberOfProperties</i> | Returned number of trace file properties. |
| out | <i>names</i> | Returned list of property names. Allocated with <i>malloc</i> . To release memory, just pass * <i>names</i> to <i>free</i> . |

Returns

OTF2_SUCCESS if successful, an error code if an error occurs.

J.27.2.31 *OTF2_SnapReader** *OTF2_Reader_GetSnapReader* (*OTF2_Reader* * *reader*, *OTF2_LocationRef* *location*)

Get a local snapshot reader.

Parameters

| | | |
|--|-----------------|---|
| | <i>reader</i> | Valid reader handle. |
| | <i>location</i> | Location ID for the requested local reader. |

Returns

Returns a handle to the local event reader if successful, NULL otherwise.

Since

Version 1.2

J.27 OTF2_Reader.h File Reference

J.27.2.32 OTF2_ThumbReader* OTF2_Reader_GetThumbReader (OTF2_Reader * reader, uint32_t number)

Get a thumb reader.

Parameters

| | |
|---------------|-------------------|
| <i>reader</i> | Reader handle. |
| <i>number</i> | Thumbnail number. |

Since

Version 1.2

Returns

Returns a global definition writer handle if successful, NULL if an error occurs.

J.27.2.33 OTF2_ErrorCode OTF2_Reader_GetTraceId (OTF2_Reader * reader, uint64_t * id)

Get the identifier of the trace file.

Parameters

| | | |
|-----|---------------|-------------------|
| | <i>reader</i> | Reader handle. |
| out | <i>id</i> | Trace identifier. |

Returns

[*OTF2_SUCCESS*](#) if successful, an error code if an error occurs.

J.27.2.34 OTF2_ErrorCode OTF2_Reader_GetVersion (OTF2_Reader * reader, uint8_t * major, uint8_t * minor, uint8_t * bugfix)

Get OTF2 version.

Parameters

| | | |
|-----|---------------|----------------------|
| | <i>reader</i> | Valid reader handle. |
| out | <i>major</i> | Major version. |
| out | <i>minor</i> | Minor version. |
| out | <i>bugfix</i> | Bugfix revision. |

APPENDIX J. FILE DOCUMENTATION

Returns

OTF2_SUCCESS if successful, an error code if an error occurs.

J.27.2.35 `OTF2_Reader_HasGlobalEvent (OTF2_Reader * reader, OTF2_GlobalEvtReader * evtReader, int * flag)`

Has the global event reader at least one more event to deliver.

Parameters

| | | |
|-----|------------------|--|
| | <i>reader</i> | Global event reader handle. |
| | <i>evtReader</i> | Global event reader handle. |
| out | <i>flag</i> | In case of success, the flag will be set to 1 when there is at least more more event to read. To 0 if not. Otherwise the value is undefined. |

Returns

OTF2_SUCCESS if successful, an error code if an error occurs.

J.27.2.36 `OTF2_Reader* OTF2_Reader_Open (const char * anchorFilePath)`

Create a new reader handle.

Creates a new reader handle, opens an according archive handle, and calls a routine to register all necessary function pointers.

Parameters

| | |
|------------------------|--|
| <i>anchor-FilePath</i> | Path to the anchor file e.g. 'trace.otf2'. This can be a relative as well as an absolute path. |
|------------------------|--|

Returns

Returns a handle to the reader if successful, NULL otherwise.

J.27.2.37 `OTF2_Reader_ReadAllGlobalDefinitions (OTF2_Reader * reader, OTF2_GlobalDefReader * defReader, uint64_t * definitionsRead)`

Read all definitions via a global definition reader.

J.27 OTF2_Reader.h File Reference

Parameters

| | | |
|-----|------------------------|--|
| | <i>reader</i> | Reader handle. |
| | <i>defReader</i> | Global definition reader handle. |
| out | <i>definitionsRead</i> | Return pointer to the number of definitions actually read. |

Returns

OTF2_SUCCESS if successful, an error code if an error occurs.

J.27.2.38 `OTF2_ErrorCode OTF2_Reader_ReadAllGlobalEvents (OTF2_Reader * reader, OTF2_GlobalEvtReader * evtReader, uint64_t * eventsRead)`

Read all events via a global event reader.

Parameters

| | | |
|-----|-------------------|---|
| | <i>reader</i> | Reader handle. |
| | <i>evtReader</i> | Global event reader handle. |
| out | <i>eventsRead</i> | Return pointer to the number of events actually read. |

Returns

OTF2_SUCCESS if successful, an error code if an error occurs.

J.27.2.39 `OTF2_ErrorCode OTF2_Reader_ReadAllGlobalSnapshots (OTF2_Reader * reader, OTF2_GlobalSnapReader * snapReader, uint64_t * recordsRead)`

Read all records via a global snapshot reader.

Parameters

| | | |
|-----|--------------------|---|
| | <i>reader</i> | Reader handle. |
| | <i>snapReader</i> | Global snapshot reader handle. |
| out | <i>recordsRead</i> | Return pointer to the number of records |

Returns

OTF2_SUCCESS if successful, an error code if an error occurs.

Since

Version 1.2

J.27.2.40 `OTF2_StatusCode OTF2_Reader_ReadAllLocalDefinitions (OTF2_Reader * reader, OTF2_DefReader * defReader, uint64_t * definitionsRead)`

Read all definitions via a local definition reader.

Parameters

| | | |
|-----|------------------------|--|
| | <i>reader</i> | Reader handle. |
| | <i>defReader</i> | Local definition reader handle. |
| out | <i>definitionsRead</i> | Return pointer to the number of definitions actually read. |

Returns

OTF2_SUCCESS if successful

OTF2_ERROR_INTERRUPTED_BY_CALLBACK if an user supplied callback returned `OTF2_CALLBACK_INTERRUPT`

OTF2_ERROR_DUPLICATE_MAPPING_TABLE if an duplicate mapping table definition was read

otherwise the error code

J.27.2.41 `OTF2_StatusCode OTF2_Reader_ReadAllLocalEvents (OTF2_Reader * reader, OTF2_EvtReader * evtReader, uint64_t * eventsRead)`

Read all events via a local event reader.

Parameters

| | | |
|-----|-------------------|---|
| | <i>reader</i> | Reader handle. |
| | <i>evtReader</i> | Local event reader handle. |
| out | <i>eventsRead</i> | Return pointer to the number of events actually read. |

Returns

OTF2_SUCCESS if successful, an error code if an error occurs.

J.27 OTF2_Reader.h File Reference

J.27.2.42 `OTF2_Reader_ReadAllLocalSnapshots (OTF2_Reader * reader, OTF2_SnapReader * snapReader, uint64_t * recordsRead)`

Read all records via a local snapshot reader.

Parameters

| | | |
|-----|--------------------|---|
| | <i>reader</i> | Reader handle. |
| | <i>snapReader</i> | Local snapshot reader handle. |
| out | <i>recordsRead</i> | Return pointer to the number of records |

Returns

[*OTF2_SUCCESS*](#) if successful, an error code if an error occurs.

Since

Version 1.2

J.27.2.43 `OTF2_Reader_ReadAllMarkers (OTF2_Reader * reader, OTF2_MarkerReader * markerReader, uint64_t * markersRead)`

Read all markers via a marker reader.

Parameters

| | | |
|-----|---------------------|--|
| | <i>reader</i> | Reader handle. |
| | <i>markerReader</i> | Marker reader handle. |
| out | <i>markersRead</i> | Return pointer to the number of markers actually read. |

Since

Version 1.2

Returns

[*OTF2_SUCCESS*](#) if successful, an error code if an error occurs.

APPENDIX J. FILE DOCUMENTATION

J.27.2.44 **OTF2_StatusCode** **OTF2_Reader_ReadGlobalDefinitions** (**OTF2_Reader** * *reader*, **OTF2_GlobalDefReader** * *defReader*, **uint64_t** *definitionsToRead*, **uint64_t** * *definitionsRead*)

Read a given number of definitions via a global definition reader.

Parameters

| | | |
|-----|--------------------------|--|
| | <i>reader</i> | Reader handle. |
| | <i>defReader</i> | Global definition reader handle. |
| | <i>definitionsToRead</i> | Number definitions to be read. |
| out | <i>definitionsRead</i> | Return pointer to the number of definitions actually read. |

Returns

[*OTF2_SUCCESS*](#) if successful, an error code if an error occurs.

J.27.2.45 **OTF2_StatusCode** **OTF2_Reader_ReadGlobalEvent** (**OTF2_Reader** * *reader*, **OTF2_GlobalEvtReader** * *evtReader*)

Read an event via a global event reader.

Parameters

| | | |
|--|------------------|-----------------------------|
| | <i>reader</i> | Reader handle. |
| | <i>evtReader</i> | Global event reader handle. |

Returns

[*OTF2_SUCCESS*](#) if successful, an error code if an error occurs.

J.27.2.46 **OTF2_StatusCode** **OTF2_Reader_ReadGlobalEvents** (**OTF2_Reader** * *reader*, **OTF2_GlobalEvtReader** * *evtReader*, **uint64_t** *eventsToRead*, **uint64_t** * *eventsRead*)

Read a given number of events via a global event reader.

Parameters

| | | |
|--|------------------|-----------------------------|
| | <i>reader</i> | Reader handle. |
| | <i>evtReader</i> | Global event reader handle. |

J.27 OTF2_Reader.h File Reference

| | | |
|-----|---------------------|---|
| | <i>eventsToRead</i> | Number events to be read. |
| out | <i>eventsRead</i> | Return pointer to the number of events actually read. |

Returns

OTF2_SUCCESS if successful, an error code if an error occurs.

J.27.2.47 `OTF2_StatusCode OTF2_Reader_ReadGlobalSnapshots (OTF2_Reader * reader, OTF2_GlobalSnapReader * snapReader, uint64_t recordsToRead, uint64_t * recordsRead)`

Read a given number of records via a global snapshot reader.

Parameters

| | | |
|-----|----------------------|--|
| | <i>reader</i> | Reader handle. |
| | <i>snapReader</i> | Global snapshot reader handle. |
| | <i>recordsToRead</i> | Number records to be read. |
| out | <i>recordsRead</i> | Return pointer to the number of records actually read. |

Returns

OTF2_SUCCESS if successful, an error code if an error occurs.

Since

Version 1.2

J.27.2.48 `OTF2_StatusCode OTF2_Reader_ReadLocalDefinitions (OTF2_Reader * reader, OTF2_DefReader * defReader, uint64_t definitionsToRead, uint64_t * definitionsRead)`

Read a given number of definitions via a local definition reader.

Parameters

| | | |
|--|--------------------------|---------------------------------|
| | <i>reader</i> | Reader handle. |
| | <i>defReader</i> | Local definition reader handle. |
| | <i>definitionsToRead</i> | Number definitions to be read. |

APPENDIX J. FILE DOCUMENTATION

| | | |
|-----|------------------------------|--|
| out | <i>definition- sRead</i> | Return pointer to the number of definitions actually read. |
|-----|------------------------------|--|

Returns

OTF2_SUCCESS if successful

OTF2_ERROR_INTERRUPTED_BY_CALLBACK if an user supplied call-back returned *OTF2_CALLBACK_INTERRUPT*

OTF2_ERROR_DUPLICATE_MAPPING_TABLE if an duplicate mapping table definition was read

otherwise the error code

J.27.2.49 *OTF2_Reader_ReadLocalEvents* (*OTF2_Reader* * *reader*, *OTF2_EvtReader* * *evtReader*, *uint64_t* *eventsToRead*, *uint64_t* * *eventsRead*)

Read a given number of events via a local event reader.

Parameters

| | |
|---------------------|---|
| <i>reader</i> | Reader handle. |
| <i>evtReader</i> | Local event reader handle. |
| <i>eventsToRead</i> | Number events to be read. |
| <i>eventsRead</i> | Return pointer to the number of events actually read. |

Returns

OTF2_SUCCESS if successful, an error code if an error occurs.

J.27.2.50 *OTF2_Reader_ReadLocalEventsBackward* (*OTF2_Reader* * *reader*, *OTF2_EvtReader* * *evtReader*, *uint64_t* *eventsToRead*, *uint64_t* * *eventsRead*)

Read a given number of events via a local event reader backwards.

Parameters

| | |
|------------------|----------------------------|
| <i>reader</i> | Reader handle. |
| <i>evtReader</i> | Local event reader handle. |

J.27 OTF2_Reader.h File Reference

| | | |
|-----|---------------------|---|
| | <i>eventsToRead</i> | Number events to be read. |
| out | <i>eventsRead</i> | Return pointer to the number of events actually read. |

Returns

[*OTF2_SUCCESS*](#) if successful, an error code if an error occurs.

J.27.2.51 `OTF2_StatusCode OTF2_Reader_ReadLocalSnapshots (OTF2_Reader * reader, OTF2_SnapReader * snapReader, uint64_t recordsToRead, uint64_t * recordsRead)`

Read a given number of records via a local snapshot reader.

Parameters

| | |
|----------------------|--|
| <i>reader</i> | Reader handle. |
| <i>snapReader</i> | Local snapshot reader handle. |
| <i>recordsToRead</i> | Number records to be read. |
| <i>recordsRead</i> | Return pointer to the number of records actually read. |

Returns

[*OTF2_SUCCESS*](#) if successful, an error code if an error occurs.

Since

Version 1.2

J.27.2.52 `OTF2_StatusCode OTF2_Reader_ReadMarkers (OTF2_Reader * reader, OTF2_MarkerReader * markerReader, uint64_t markersToRead, uint64_t * markersRead)`

Read a given number of markers via a marker reader.

Parameters

| | | |
|--|---------------------|-----------------------|
| | <i>reader</i> | Reader handle. |
| | <i>markerReader</i> | Marker reader handle. |

APPENDIX J. FILE DOCUMENTATION

| | | |
|-----|----------------------------|--|
| | <i>marker- sToRead</i> | Number markers to be read. |
| out | <i>marker- sRead</i> | Return pointer to the number of markers actually read. |

Since

Version 1.2

Returns

OTF2_SUCCESS if successful, an error code if an error occurs.

J.27.2.53 **OTF2_StatusCode** **OTF2_Reader_RegisterDefCallbacks** (
OTF2_Reader * reader, OTF2_DefReader * defReader, const
OTF2_DefReaderCallbacks * callbacks, void * userData)

Register local definition reader callbacks.

Parameters

| | |
|------------------|---|
| <i>reader</i> | OTF2_Reader handle. |
| <i>defReader</i> | Local definition reader handle. |
| <i>callbacks</i> | Callbacks for the local definition readers. |
| <i>userData</i> | Addition user data. |

Returns

OTF2_SUCCESS if successful, an error code if an error occurs.

J.27.2.54 **OTF2_StatusCode** **OTF2_Reader_RegisterEvtCallbacks** (
OTF2_Reader * reader, OTF2_EvtReader * evtReader, const
OTF2_EvtReaderCallbacks * callbacks, void * userData)

Register event reader callbacks.

Parameters

| | |
|------------------|----------------------------------|
| <i>reader</i> | OTF2_Reader handle. |
| <i>evtReader</i> | Local event reader handle. |
| <i>callbacks</i> | Callbacks for the event readers. |
| <i>userData</i> | Addition user data. |

J.27 OTF2_Reader.h File Reference

Returns

OTF2_SUCCESS if successful, an error code if an error occurs.

J.27.2.55 `OTF2_Reader_RegisterGlobalDefCallbacks (OTF2_Reader * reader, OTF2_GlobalDefReader * defReader, const OTF2_GlobalDefReaderCallbacks * callbacks, void * userData)`

Register global definition reader callbacks.

Parameters

| | |
|------------------|--|
| <i>reader</i> | OTF2_Reader handle. |
| <i>defReader</i> | Global definition reader handle. |
| <i>callbacks</i> | Callbacks for the global definition readers. |
| <i>userData</i> | Addition user data. |

Returns

OTF2_SUCCESS if successful, an error code if an error occurs.

J.27.2.56 `OTF2_Reader_RegisterGlobalEvtCallbacks (OTF2_Reader * reader, OTF2_GlobalEvtReader * evtReader, const OTF2_GlobalEvtReaderCallbacks * callbacks, void * userData)`

Register global event reader callbacks.

Parameters

| | |
|------------------|--|
| <i>reader</i> | OTF2_Reader handle. |
| <i>evtReader</i> | Global event reader handle. |
| <i>callbacks</i> | Callbacks for the global event reader. |
| <i>userData</i> | Addition user data. |

Returns

Returns *OTF2_SUCCESS* if successful, an error code if an error occurs.

APPENDIX J. FILE DOCUMENTATION

J.27.2.57 **OTF2_ErrorCode** **OTF2_Reader_RegisterGlobalSnapCallbacks** (
OTF2_Reader * *reader*, **OTF2_GlobalSnapReader** * *evtReader*, **const**
OTF2_GlobalSnapReaderCallbacks * *callbacks*, **void** * *userData*)

Register global event reader callbacks.

Parameters

| | |
|------------------|--|
| <i>reader</i> | OTF2_Reader handle. |
| <i>evtReader</i> | Global event reader handle. |
| <i>callbacks</i> | Callbacks for the global event reader. |
| <i>userData</i> | Addition user data. |

Since

Version 1.2

Returns

Returns *OTF2_SUCCESS* if successful, an error code if an error occurs.

J.27.2.58 **OTF2_ErrorCode** **OTF2_Reader_RegisterMarkerCallbacks** (
OTF2_Reader * *reader*, **OTF2_MarkerReader** * *markerReader*, **const**
OTF2_MarkerReaderCallbacks * *callbacks*, **void** * *userData*)

Register marker reader callbacks.

Parameters

| | |
|----------------------|----------------------------------|
| <i>reader</i> | OTF2_Reader handle. |
| <i>marker-Reader</i> | Marker reader handle. |
| <i>callbacks</i> | Callbacks for the marker reader. |
| <i>userData</i> | Addition user data. |

Since

Version 1.2

Returns

OTF2_SUCCESS if successful, an error code if an error occurs.

J.27 OTF2_Reader.h File Reference

J.27.2.59 `OTF2_Reader_RegisterSnapCallbacks (OTF2_Reader * reader, OTF2_SnapReader * snapReader, const OTF2_SnapReaderCallbacks * callbacks, void * userData)`

Register snapshot event reader callbacks.

Parameters

| | |
|-------------------|----------------------------------|
| <i>reader</i> | OTF2_Reader handle. |
| <i>snapReader</i> | Local snap reader handle. |
| <i>callbacks</i> | Callbacks for the event readers. |
| <i>userData</i> | Addition user data. |

Since

Version 1.2

Returns

[*OTF2_SUCCESS*](#) if successful, an error code if an error occurs.

J.27.2.60 `OTF2_Reader_SetFileSionCallbacks (OTF2_Reader * reader, const OTF2_FileSionCallbacks * fileSionCallbacks, void * fileSionData)`

Register SION callbacks to the reader.

It suffice to provide a function for *OTF2_FileSionGetRank*. The necessary information for the rank mapping can be extracted from the global group definition of type *OTF2_GROUP_TYPE_MPI_LOCATIONS* or by the *locationGroupId* attribute of the Location definitions.

Parameters

| | |
|---------------------------|--|
| <i>reader</i> | Reader handle. |
| <i>fileSion-Callbacks</i> | Struct holding the callbacks. |
| <i>fileSion-Data</i> | Pointer passed to the callbacks by the caller. |

Returns

[*OTF2_SUCCESS*](#) if successful, an error code if an error occurs.

J.28 OTF2_SnapReader.h File Reference

This is the local snap reader, which reads snapshot events from one location.

```
#include <stdint.h>
#include <otf2/OTF2_ErrorCodes.h>
#include <otf2/OTF2_Events.h>
#include <otf2/OTF2_Definitions.h>
#include <otf2/OTF2_AttributeList.h>
#include <otf2/OTF2_SnapReaderCallbacks.h>
```

Functions

- [OTF2_ErrorCode OTF2_SnapReader_GetLocationID](#) (const [OTF2_SnapReader](#) *reader, [OTF2_LocationRef](#) *location)
Return the location ID of the reading related location.
- [OTF2_ErrorCode OTF2_SnapReader_ReadSnapshots](#) ([OTF2_SnapReader](#) *reader, [uint64_t](#) recordsToRead, [uint64_t](#) *recordsRead)
After callback registration, the local events could be read with the following function. Readn reads recordsToRead records. The reader indicates that it reached the end of the trace by just reading less records than requested.
- [OTF2_ErrorCode OTF2_SnapReader_Seek](#) ([OTF2_SnapReader](#) *reader, [uint64_t](#) req_time, [bool](#) *found)
Seek jumps to start of latest snapshot that was made before a given time 'req_time'.
- [OTF2_ErrorCode OTF2_SnapReader_SetCallbacks](#) ([OTF2_SnapReader](#) *reader, const [OTF2_SnapReaderCallbacks](#) *callbacks, void *userData)
Sets the callback functions for the given reader object. Everytime when OTF2 reads a record, a callback function is called and the records data is passed to this function. Therefore the programmer needs to set function pointers at the "callbacks" struct for the record type he wants to read.

J.28.1 Detailed Description

This is the local snap reader, which reads snapshot events from one location.

J.28 OTF2_SnapReader.h File Reference

J.28.2 Function Documentation

J.28.2.1 `OTF2_StatusCode OTF2_SnapReader_GetLocationID (const OTF2_SnapReader * reader, OTF2_LocationRef * location)`

Return the location ID of the reading related location.

Parameters

| | | |
|-----|-----------------|--|
| | <i>reader</i> | Reader object which reads the snapshot events from its buffer. |
| out | <i>location</i> | ID of the location. |

Since

Version 1.2

Returns

[OTF2_SUCCESS](#) if successful, an error code if an error occurs.

J.28.2.2 `OTF2_StatusCode OTF2_SnapReader_ReadSnapshots (OTF2_SnapReader * reader, uint64_t recordsToRead, uint64_t * recordsRead)`

After callback registration, the local events could be read with the following function. `Readn` reads *recordsToRead* records. The reader indicates that it reached the end of the trace by just reading less records than requested.

Parameters

| | | |
|-----|----------------------|---|
| | <i>reader</i> | Reader object which reads the events from its buffer. |
| | <i>recordsToRead</i> | How many records can be read next. |
| out | <i>recordsRead</i> | Return how many records were really read. |

Since

Version 1.2

Returns

[OTF2_SUCCESS](#) if successful, an error code if an error occurs.

APPENDIX J. FILE DOCUMENTATION

J.28.2.3 `OTF2_ErrorCode OTF2_SnapReader.Seek (OTF2_SnapReader * reader, uint64_t req_time, bool * found)`

Seek jumps to start of latest snapshot that was made before a given time 'req_time'.

Parameters

| | |
|-----------------|---|
| <i>reader</i> | Reader object which reads the events from its buffer. |
| <i>req_time</i> | Requested time (see above) |
| <i>found</i> | returns if a matching snapshot was found |

Since

Version 1.2

Returns

OTF2_Error_Code with !=OTF2_SUCCESS if there was an error.

J.28.2.4 `OTF2_ErrorCode OTF2_SnapReader.SetCallbacks (OTF2_SnapReader * reader, const OTF2_SnapReaderCallbacks * callbacks, void * userData)`

Sets the callback functions for the given reader object. Everytime when OTF2 reads a record, a callback function is called and the records data is passed to this function. Therefore the programmer needs to set function pointers at the "callbacks" struct for the record type he wants to read.

These callbacks are ignored, if the events are read by an global event reader.

Parameters

| | |
|------------------|--|
| <i>reader</i> | Reader object which reads the events from its buffer. |
| <i>callbacks</i> | Struct which holds a function pointer for each record type. OTF2_SnapReaderCallbacks_New . |
| <i>userData</i> | Data passed as argument <i>userData</i> to the record callbacks. |

Since

Version 1.2

Returns

[OTF2_SUCCESS](#) if successful, an error code if an error occurs.

J.29 OTF2_SnapReaderCallbacks.h File Reference

J.29 OTF2_SnapReaderCallbacks.h File Reference

This defines the callbacks for the snap reader.

```
#include <stdint.h>
#include <otf2/OTF2_ErrorCodes.h>
#include <otf2/OTF2_GeneralDefinitions.h>
#include <otf2/OTF2_AttributeList.h>
#include <otf2/OTF2_Events.h>
```

Typedefs

- typedef OTF2_CallbackCode(* OTF2_SnapReaderCallback_Enter)(OTF2_LocationRef location, OTF2_TimeStamp snapTime, void *userData, OTF2_AttributeList *attributeList, OTF2_TimeStamp origEventTime, OTF2_RegionRef region)
Callback for the Enter snap event record.
- typedef OTF2_CallbackCode(* OTF2_SnapReaderCallback_MeasurementOnOff)(OTF2_LocationRef location, OTF2_TimeStamp snapTime, void *userData, OTF2_AttributeList *attributeList, OTF2_TimeStamp origEventTime, OTF2_MeasurementMode measurementMode)
Callback for the MeasurementOnOff snap event record.
- typedef OTF2_CallbackCode(* OTF2_SnapReaderCallback_Metric)(OTF2_LocationRef location, OTF2_TimeStamp snapTime, void *userData, OTF2_AttributeList *attributeList, OTF2_TimeStamp origEventTime, OTF2_MetricRef metric, uint8_t numberOfMetrics, const OTF2_Type *typeIDs, const OTF2_MetricValue *metricValues)
Callback for the Metric snap event record.
- typedef OTF2_CallbackCode(* OTF2_SnapReaderCallback_MpiCollectiveBegin)(OTF2_LocationRef location, OTF2_TimeStamp snapTime, void *userData, OTF2_AttributeList *attributeList, OTF2_TimeStamp origEventTime)
Callback for the MpiCollectiveBegin snap event record.
- typedef OTF2_CallbackCode(* OTF2_SnapReaderCallback_MpiCollectiveEnd)(OTF2_LocationRef location, OTF2_TimeStamp snapTime, void *userData, OTF2_AttributeList *attributeList, OTF2_TimeStamp origEventTime, OTF2_CollectiveOp collectiveOp, OTF2_CommRef communicator, uint32_t root, uint64_t sizeSent, uint64_t sizeReceived)

APPENDIX J. FILE DOCUMENTATION

Callback for the `MpiCollectiveEnd` snap event record.

- `typedef OTF2_CallbackCode>(* OTF2_SnapReaderCallback_MpiIrecv)(OTF2_LocationRef location, OTF2_TimeStamp snapTime, void *userData, OTF2_AttributeList *attributeList, OTF2_TimeStamp origEventTime, uint32_t sender, OTF2_CommRef communicator, uint32_t msgTag, uint64_t msgLength, uint64_t requestID)`

Callback for the `MpiIrecv` snap event record.

- `typedef OTF2_CallbackCode(* OTF2_SnapReaderCallback_MpiIrecvRequest)(OTF2_LocationRef location, OTF2_TimeStamp snapTime, void *userData, OTF2_AttributeList *attributeList, OTF2_TimeStamp origEventTime, uint64_t requestID)`

Callback for the `MpiIrecvRequest` snap event record.

- `typedef OTF2_CallbackCode(* OTF2_SnapReaderCallback_MpiIsend)(OTF2_LocationRef location, OTF2_TimeStamp snapTime, void *userData, OTF2_AttributeList *attributeList, OTF2_TimeStamp origEventTime, uint32_t receiver, OTF2_CommRef communicator, uint32_t msgTag, uint64_t msgLength, uint64_t requestID)`

Callback for the `MpiIsend` snap event record.

- `typedef OTF2_CallbackCode(* OTF2_SnapReaderCallback_MpiIsendComplete)(OTF2_LocationRef location, OTF2_TimeStamp snapTime, void *userData, OTF2_AttributeList *attributeList, OTF2_TimeStamp origEventTime, uint64_t requestID)`

Callback for the `MpiIsendComplete` snap event record.

- `typedef OTF2_CallbackCode(* OTF2_SnapReaderCallback_MpiRecv)(OTF2_LocationRef location, OTF2_TimeStamp snapTime, void *userData, OTF2_AttributeList *attributeList, OTF2_TimeStamp origEventTime, uint32_t sender, OTF2_CommRef communicator, uint32_t msgTag, uint64_t msgLength)`

Callback for the `MpiRecv` snap event record.

- `typedef OTF2_CallbackCode(* OTF2_SnapReaderCallback_MpiSend)(OTF2_LocationRef location, OTF2_TimeStamp snapTime, void *userData, OTF2_AttributeList *attributeList, OTF2_TimeStamp origEventTime, uint32_t receiver, OTF2_CommRef communicator, uint32_t msgTag, uint64_t msgLength)`

Callback for the `MpiSend` snap event record.

- `typedef OTF2_CallbackCode(* OTF2_SnapReaderCallback_OmpAcquireLock)(OTF2_LocationRef location, OTF2_TimeStamp snapTime, void *userData,`

J.29 OTF2_SnapReaderCallbacks.h File Reference

`OTF2_AttributeList *attributeList, OTF2_TimeStamp origEventTime, uint32_t lockID, uint32_t acquisitionOrder)`

Callback for the OmpAcquireLock snap event record.

- `typedef OTF2_CallbackCode(* OTF2_SnapReaderCallback_OmpFork)(OTF2_LocationRef location, OTF2_TimeStamp snapTime, void *userData, OTF2_AttributeList *attributeList, OTF2_TimeStamp origEventTime, uint32_t numberOfRequestedThreads)`

Callback for the OmpFork snap event record.

- `typedef OTF2_CallbackCode(* OTF2_SnapReaderCallback_OmpTaskCreate)(OTF2_LocationRef location, OTF2_TimeStamp snapTime, void *userData, OTF2_AttributeList *attributeList, OTF2_TimeStamp origEventTime, uint64_t taskID)`

Callback for the OmpTaskCreate snap event record.

- `typedef OTF2_CallbackCode(* OTF2_SnapReaderCallback_OmpTaskSwitch)(OTF2_LocationRef location, OTF2_TimeStamp snapTime, void *userData, OTF2_AttributeList *attributeList, OTF2_TimeStamp origEventTime, uint64_t taskID)`

Callback for the OmpTaskSwitch snap event record.

- `typedef OTF2_CallbackCode(* OTF2_SnapReaderCallback_ParameterInt)(OTF2_LocationRef location, OTF2_TimeStamp snapTime, void *userData, OTF2_AttributeList *attributeList, OTF2_TimeStamp origEventTime, OTF2_ParameterRef parameter, int64_t value)`

Callback for the ParameterInt snap event record.

- `typedef OTF2_CallbackCode(* OTF2_SnapReaderCallback_ParameterString)(OTF2_LocationRef location, OTF2_TimeStamp snapTime, void *userData, OTF2_AttributeList *attributeList, OTF2_TimeStamp origEventTime, OTF2_ParameterRef parameter, OTF2_StringRef string)`

Callback for the ParameterString snap event record.

- `typedef OTF2_CallbackCode(* OTF2_SnapReaderCallback_ParameterUnsignedInt)(OTF2_LocationRef location, OTF2_TimeStamp snapTime, void *userData, OTF2_AttributeList *attributeList, OTF2_TimeStamp origEventTime, OTF2_ParameterRef parameter, uint64_t value)`

Callback for the ParameterUnsignedInt snap event record.

- `typedef OTF2_CallbackCode(* OTF2_SnapReaderCallback_SnapshotEnd)(OTF2_LocationRef location, OTF2_TimeStamp snapTime, void *userData, OTF2_AttributeList *attributeList, uint64_t contReadPos)`

APPENDIX J. FILE DOCUMENTATION

Callback for the SnapshotEnd snap event record.

- typedef OTF2_CallbackCode(* OTF2_SnapReaderCallback_SnapshotStart)(OTF2_LocationRef location, OTF2_TimeStamp snapTime, void *userData, OTF2_AttributeList *attributeList, uint64_t numberOfRecords)

Callback for the SnapshotStart snap event record.

- typedef OTF2_CallbackCode(* OTF2_SnapReaderCallback_Unknown)(OTF2_LocationRef location, OTF2_TimeStamp snapTime, void *userData, OTF2_AttributeList *attributeList)

Callback for an unknown snap event record.

- typedef struct OTF2_SnapReaderCallbacks_struct OTF2_SnapReaderCallbacks

Opaque struct which holds all snap event record callbacks.

Functions

- void OTF2_SnapReaderCallbacks_Clear (OTF2_SnapReaderCallbacks *snapReaderCallbacks)

Clears a struct for the snap event callbacks.

- void OTF2_SnapReaderCallbacks_Delete (OTF2_SnapReaderCallbacks *snapReaderCallbacks)

Deallocates a struct for the snap event callbacks.

- OTF2_SnapReaderCallbacks * OTF2_SnapReaderCallbacks_New (void)

Allocates a new struct for the snap event callbacks.

- OTF2_ErrorCode OTF2_SnapReaderCallbacks_SetEnterCallback (OTF2_SnapReaderCallbacks *snapReaderCallbacks, OTF2_SnapReaderCallback_Enter enterCallback)

Registers the callback for the Enter snap event.

- OTF2_ErrorCode OTF2_SnapReaderCallbacks_SetMeasurementOnOffCallback (OTF2_SnapReaderCallbacks *snapReaderCallbacks, OTF2_SnapReaderCallback_MeasurementOnOff measurementOnOffCallback)

Registers the callback for the MeasurementOnOff snap event.

J.29 OTF2_SnapReaderCallbacks.h File Reference

- [OTF2_ErrorCode](#) [OTF2_SnapReaderCallbacks_SetMetricCallback](#) ([OTF2_SnapReaderCallbacks](#) *snapReaderCallbacks, [OTF2_SnapReaderCallback_Metric](#) metricCallback)
Registers the callback for the Metric snap event.
- [OTF2_ErrorCode](#) [OTF2_SnapReaderCallbacks_SetMpiCollectiveBeginCallback](#) ([OTF2_SnapReaderCallbacks](#) *snapReaderCallbacks, [OTF2_SnapReaderCallback_MpiCollectiveBegin](#) mpiCollectiveBeginCallback)
Registers the callback for the MpiCollectiveBegin snap event.
- [OTF2_ErrorCode](#) [OTF2_SnapReaderCallbacks_SetMpiCollectiveEndCallback](#) ([OTF2_SnapReaderCallbacks](#) *snapReaderCallbacks, [OTF2_SnapReaderCallback_MpiCollectiveEnd](#) mpiCollectiveEndCallback)
Registers the callback for the MpiCollectiveEnd snap event.
- [OTF2_ErrorCode](#) [OTF2_SnapReaderCallbacks_SetMpiIrecvCallback](#) ([OTF2_SnapReaderCallbacks](#) *snapReaderCallbacks, [OTF2_SnapReaderCallback_MpiIrecv](#) mpiIrecvCallback)
Registers the callback for the MpiIrecv snap event.
- [OTF2_ErrorCode](#) [OTF2_SnapReaderCallbacks_SetMpiIrecvRequestCallback](#) ([OTF2_SnapReaderCallbacks](#) *snapReaderCallbacks, [OTF2_SnapReaderCallback_MpiIrecvRequest](#) mpiIrecvRequestCallback)
Registers the callback for the MpiIrecvRequest snap event.
- [OTF2_ErrorCode](#) [OTF2_SnapReaderCallbacks_SetMpiIsendCallback](#) ([OTF2_SnapReaderCallbacks](#) *snapReaderCallbacks, [OTF2_SnapReaderCallback_MpiIsend](#) mpiIsendCallback)
Registers the callback for the MpiIsend snap event.
- [OTF2_ErrorCode](#) [OTF2_SnapReaderCallbacks_SetMpiIsendCompleteCallback](#) ([OTF2_SnapReaderCallbacks](#) *snapReaderCallbacks, [OTF2_SnapReaderCallback_MpiIsendComplete](#) mpiIsendCompleteCallback)
Registers the callback for the MpiIsendComplete snap event.
- [OTF2_ErrorCode](#) [OTF2_SnapReaderCallbacks_SetMpiRecvCallback](#) ([OTF2_SnapReaderCallbacks](#) *snapReaderCallbacks, [OTF2_SnapReaderCallback_MpiRecv](#) mpiRecvCallback)
Registers the callback for the MpiRecv snap event.
- [OTF2_ErrorCode](#) [OTF2_SnapReaderCallbacks_SetMpiSendCallback](#) ([OTF2_SnapReaderCallbacks](#) *snapReaderCallbacks, [OTF2_SnapReaderCallback_MpiSend](#) mpiSendCallback)

APPENDIX J. FILE DOCUMENTATION

Registers the callback for the MpiSend snap event.

- [OTF2_ErrorCode](#) [OTF2_SnapReaderCallbacks_SetOmpAcquireLockCallback](#) ([OTF2_SnapReaderCallbacks](#) *snapReaderCallbacks, [OTF2_SnapReaderCallback_-OmpAcquireLock](#) ompAcquireLockCallback)

Registers the callback for the OmpAcquireLock snap event.

- [OTF2_ErrorCode](#) [OTF2_SnapReaderCallbacks_SetOmpForkCallback](#) ([OTF2_SnapReaderCallbacks](#) *snapReaderCallbacks, [OTF2_SnapReaderCallback_-OmpFork](#) ompForkCallback)

Registers the callback for the OmpFork snap event.

- [OTF2_ErrorCode](#) [OTF2_SnapReaderCallbacks_SetOmpTaskCreateCallback](#) ([OTF2_SnapReaderCallbacks](#) *snapReaderCallbacks, [OTF2_SnapReaderCallback_-OmpTaskCreate](#) ompTaskCreateCallback)

Registers the callback for the OmpTaskCreate snap event.

- [OTF2_ErrorCode](#) [OTF2_SnapReaderCallbacks_SetOmpTaskSwitchCallback](#) ([OTF2_SnapReaderCallbacks](#) *snapReaderCallbacks, [OTF2_SnapReaderCallback_-OmpTaskSwitch](#) ompTaskSwitchCallback)

Registers the callback for the OmpTaskSwitch snap event.

- [OTF2_ErrorCode](#) [OTF2_SnapReaderCallbacks_SetParameterIntCallback](#) ([OTF2_SnapReaderCallbacks](#) *snapReaderCallbacks, [OTF2_SnapReaderCallback_-ParameterInt](#) parameterIntCallback)

Registers the callback for the ParameterInt snap event.

- [OTF2_ErrorCode](#) [OTF2_SnapReaderCallbacks_SetParameterStringCallback](#) ([OTF2_SnapReaderCallbacks](#) *snapReaderCallbacks, [OTF2_SnapReaderCallback_-ParameterString](#) parameterStringCallback)

Registers the callback for the ParameterString snap event.

- [OTF2_ErrorCode](#) [OTF2_SnapReaderCallbacks_SetParameterUnsignedIntCallback](#) ([OTF2_SnapReaderCallbacks](#) *snapReaderCallbacks, [OTF2_SnapReaderCallback_-ParameterUnsignedInt](#) parameterUnsignedIntCallback)

Registers the callback for the ParameterUnsignedInt snap event.

- [OTF2_ErrorCode](#) [OTF2_SnapReaderCallbacks_SetSnapshotEndCallback](#) ([OTF2_SnapReaderCallbacks](#) *snapReaderCallbacks, [OTF2_SnapReaderCallback_-SnapshotEnd](#) snapshotEndCallback)

Registers the callback for the SnapshotEnd snap event.

J.29 OTF2_SnapReaderCallbacks.h File Reference

- [OTF2_ErrorCode](#) [OTF2_SnapReaderCallbacks_SetSnapshotStartCallback](#) ([OTF2_SnapReaderCallbacks](#) *snapReaderCallbacks, [OTF2_SnapReaderCallback_SnapshotStart](#) snapshotStartCallback)
Registers the callback for the SnapshotStart snap event.
- [OTF2_ErrorCode](#) [OTF2_SnapReaderCallbacks_SetUnknownCallback](#) ([OTF2_SnapReaderCallbacks](#) *snapReaderCallbacks, [OTF2_SnapReaderCallback_Unknown](#) unknownCallback)
Registers the callback for the Unknown snap event.

J.29.1 Detailed Description

This defines the callbacks for the snap reader.

Source Template:

templates/OTF2_SnapReaderCallbacks.templ.h

J.29.2 Typedef Documentation

J.29.2.1 `typedef OTF2_CallbackCode(* OTF2_SnapReaderCallback_Enter)(OTF2_LocationRef location, OTF2_TimeStamp snapTime, void *userData, OTF2_AttributeList *attributeList, OTF2_TimeStamp origEventTime, OTF2_RegionRef region)`

Callback for the Enter snap event record.

This record exists for each *Enter* event where the corresponding *Leave* event did not occur before the snapshot.

Parameters

| | |
|----------------------|--|
| <i>location</i> | The location where this snap event happened. |
| <i>snapTime</i> | Snapshot time. |
| <i>userData</i> | User data as set by OTF2_Reader_RegisterSnapCallbacks or OTF2_SnapReader_SetCallbacks . |
| <i>attributeList</i> | Additional attributes for this event. |
| <i>origEventTime</i> | The original time this event happened. |
| <i>region</i> | Needs to be defined in a definition record References a Region definition and will be mapped to the global definition if a mapping table of type OTF2_MAPPING_REGION is available. |

Since

Version 1.2

Returns

OTF2_CALLBACK_SUCCESS or *OTF2_CALLBACK_INTERRUPT*.

J.29.2.2 typedef OTF2_CallbackCode(* OTF2_SnapReaderCallback_
 MeasurementOnOff)(OTF2_LocationRef location, OTF2_TimeStamp
 snapTime, void *userData, OTF2_AttributeList *attributeList,
 OTF2_TimeStamp origEventTime, OTF2_MeasurementMode
 measurementMode)

Callback for the MeasurementOnOff snap event record.

The last occurrence of an *MeasurementOnOff* event of this location, if any.

Parameters

| | |
|------------------------|---|
| <i>location</i> | The location where this snap event happened. |
| <i>snapTime</i> | Snapshot time. |
| <i>userData</i> | User data as set by <i>OTF2_Reader_RegisterSnapCallbacks</i> or <i>OTF2_SnapReader_SetCallbacks</i> . |
| <i>attributeList</i> | Additional attributes for this event. |
| <i>origEventTime</i> | The original time this event happened. |
| <i>measurementMode</i> | Is the measurement turned on (<i>OTF2_MEASUREMENT_ON</i>) or off (<i>OTF2_MEASUREMENT_OFF</i>)? |

Since

Version 1.2

Returns

OTF2_CALLBACK_SUCCESS or *OTF2_CALLBACK_INTERRUPT*.

J.29.2.3 typedef OTF2_CallbackCode(* OTF2_SnapReaderCallback_
 Metric)(OTF2_LocationRef location, OTF2_TimeStamp snapTime, void
 *userData, OTF2_AttributeList *attributeList, OTF2_TimeStamp
 origEventTime, OTF2_MetricRef metric, uint8_t numberOfMetrics, const
 OTF2_Type *typeIDs, const OTF2_MetricValue *metricValues)

Callback for the Metric snap event record.

J.29 OTF2_SnapReaderCallbacks.h File Reference

This record exists for each referenced metric class or metric instance event this location recorded metrics before and provides the last known recorded metric values.

As an exception for metric classes where the metric mode detontes an *OTF2_-METRIC_VALUE_RELATIVE* mode the value indicates the accumulation of all previous metric values recorded.

Parameters

| | |
|-------------------------|--|
| <i>location</i> | The location where this snap event happened. |
| <i>snapTime</i> | Snapshot time. |
| <i>userData</i> | User data as set by OTF2_Reader_RegisterSnapCallbacks or OTF2_-SnapReader_SetCallbacks . |
| <i>attributeList</i> | Additional attributes for this event. |
| <i>origEvent-Time</i> | The original time this event happended. |
| <i>metric</i> | Could be a metric class or a metric instance. References a MetricClass , or a MetricInstance definition and will be mapped to the global definition if a mapping table of type OTF2_MAPPING_METRIC is available. |
| <i>numberOf-Metrics</i> | Number of metrics with in the set. |
| <i>typeIDs</i> | List of metric types. |
| <i>metricVal-ues</i> | List of metric values. |

Since

Version 1.2

Returns

[OTF2_CALLBACK_SUCCESS](#) or [OTF2_CALLBACK_INTERRUPT](#).

```
J.29.2.4 typedef OTF2_CallbackCode( * OTF2_SnapReaderCallback_-  
MpiCollectiveBegin)(OTF2_LocationRef location, OTF2_TimeStamp  
snapTime, void *userData, OTF2_AttributeList *attributeList,  
OTF2_TimeStamp origEventTime)
```

Callback for the MpiCollectiveBegin snap event record.

Indicates that this location started a collective operation but not all of the participating locations completed the operation yet, including this location.

Parameters

APPENDIX J. FILE DOCUMENTATION

| | |
|-----------------------|---|
| <i>location</i> | The location where this snap event happened. |
| <i>snapTime</i> | Snapshot time. |
| <i>userData</i> | User data as set by OTF2_Reader_RegisterSnapCallbacks or OTF2_SnapReader_SetCallbacks . |
| <i>attributeList</i> | Additional attributes for this event. |
| <i>origEvent-Time</i> | The original time this event happened. |

Since

Version 1.2

Returns

[OTF2_CALLBACK_SUCCESS](#) or [OTF2_CALLBACK_INTERRUPT](#).

J.29.2.5 `typedef OTF2_CallbackCode(* OTF2_SnapReaderCallback_ -
MpiCollectiveEnd)(OTF2_LocationRef location, OTF2_TimeStamp
snapTime, void *userData, OTF2_AttributeList *attributeList,
OTF2_TimeStamp origEventTime, OTF2_CollectiveOp collectiveOp,
OTF2_CommRef communicator, uint32_t root, uint64_t sizeSent, uint64_t
sizeReceived)`

Callback for the `MpiCollectiveEnd` snap event record.

Indicates that this location completed a collective operation locally but not all of the participating locations completed the operation yet. The corresponding `MpiCollectiveBeginSnaps` record is still in the snapshot though.

Parameters

| | |
|-----------------------|--|
| <i>location</i> | The location where this snap event happened. |
| <i>snapTime</i> | Snapshot time. |
| <i>userData</i> | User data as set by OTF2_Reader_RegisterSnapCallbacks or OTF2_SnapReader_SetCallbacks . |
| <i>attributeList</i> | Additional attributes for this event. |
| <i>origEvent-Time</i> | The original time this event happened. |
| <i>collectiveOp</i> | Determines which collective operation it is. |
| <i>communicator</i> | Communicator References a Comm definition and will be mapped to the global definition if a mapping table of type OTF2_MAPPING_COMM is available. |

J.29 OTF2_SnapReaderCallbacks.h File Reference

| | |
|---------------------|---|
| <i>root</i> | MPI rank of root in <i>communicator</i> . |
| <i>sizeSent</i> | Size of the sent message. |
| <i>sizeReceived</i> | Size of the received message. |

Since

Version 1.2

Returns

[OTF2_CALLBACK_SUCCESS](#) or [OTF2_CALLBACK_INTERRUPT](#).

J.29.2.6 typedef OTF2_CallbackCode(* OTF2_SnapReaderCallback_
MpiIrecv)(OTF2_LocationRef location, OTF2_TimeStamp snapTime,
void *userData, OTF2_AttributeList *attributeList, OTF2_TimeStamp
origEventTime, uint32_t sender, OTF2_CommRef communicator, uint32_t
msgTag, uint64_t msgLength, uint64_t requestID)

Callback for the MpiIrecv snap event record.

This record exists for each [MpiIrecv](#) event where the matching send message event did not occur on the remote location before the snapshot. This could either be an [MpiSend](#) or an [MpiSendComplete](#) event. Or an [MpiIrecvRequest](#) occurred before this event but the corresponding [MpiIrecv](#) event did not occur before this snapshot. In this case the message matching couldn't be performed yet, because the envelope of the ongoing [MpiIrecvRequest](#) is not yet known.

Parameters

| | |
|----------------------|--|
| <i>location</i> | The location where this snap event happened. |
| <i>snapTime</i> | Snapshot time. |
| <i>userData</i> | User data as set by OTF2_Reader_RegisterSnapCallbacks or OTF2_SnapReader_SetCallbacks . |
| <i>attributeList</i> | Additional attributes for this event. |
| <i>origEventTime</i> | The original time this event happened. |
| <i>sender</i> | MPI rank of sender in <i>communicator</i> . |
| <i>communicator</i> | Communicator ID. References a Comm definition and will be mapped to the global definition if a mapping table of type OTF2_MAPPING_COMM is available. |
| <i>msgTag</i> | Message tag |
| <i>msgLength</i> | Message length |
| <i>requestID</i> | ID of the related request |

Since

Version 1.2

Returns

OTF2_CALLBACK_SUCCESS or *OTF2_CALLBACK_INTERRUPT*.

J.29.2.7 `typedef OTF2_CallbackCode(* OTF2_SnapReaderCallback_
MpiIrecvRequest)(OTF2_LocationRef location, OTF2_TimeStamp
snapTime, void *userData, OTF2_AttributeList *attributeList,
OTF2_TimeStamp origEventTime, uint64_t requestID)`

Callback for the MpiIrecvRequest snap event record.

This record exists for each *MpiIrecvRequest* event where an corresponding *MpiIrecv* or *MpiRequestCancelled* event did not occur on this location before the snapshot. Or the corresponding *MpiIrecv* did occurred (the *MpiIrecvSnap* record exists in the snapshot) but the matching receive message event did not occur on the remote location before the snapshot. This could either be an *MpiRecv* or an *MpiIrecv* event.

Parameters

| | |
|----------------------|---|
| <i>location</i> | The location where this snap event happened. |
| <i>snapTime</i> | Snapshot time. |
| <i>userData</i> | User data as set by OTF2_Reader_RegisterSnapCallbacks or OTF2_SnapReader_SetCallbacks . |
| <i>attributeList</i> | Additional attributes for this event. |
| <i>origEventTime</i> | The original time this event happened. |
| <i>requestID</i> | ID of the requested receive |

Since

Version 1.2

Returns

OTF2_CALLBACK_SUCCESS or *OTF2_CALLBACK_INTERRUPT*.

J.29 OTF2_SnapReaderCallbacks.h File Reference

J.29.2.8 typedef OTF2_CallbackCode(* OTF2_SnapReaderCallback_
MpiIsend)(OTF2_LocationRef location, OTF2_TimeStamp snapTime,
void *userData, OTF2_AttributeList *attributeList, OTF2_TimeStamp
origEventTime, uint32_t receiver, OTF2_CommRef communicator, uint32_t
msgTag, uint64_t msgLength, uint64_t requestID)

Callback for the MpiIsend snap event record.

This record exists for each *MpiIsend* event where an corresponding *MpiIsendComplete* or *MpiRequestCancelled* event did not occur on this location before the snapshot. Or the corresponding *MpiIsendComplete* did occurred (the *MpiIsendCompleteSnap* record exists in the snapshot) but the matching receive message event did not occur on the remote location before the snapshot. (This could either be an *MpiRecv* or an *MpiIrecv* event.)

Parameters

| | |
|----------------------|--|
| <i>location</i> | The location where this snap event happened. |
| <i>snapTime</i> | Snapshot time. |
| <i>userData</i> | User data as set by OTF2_Reader_RegisterSnapCallbacks or OTF2_SnapReader_SetCallbacks . |
| <i>attributeList</i> | Additional attributes for this event. |
| <i>origEventTime</i> | The original time this event happened. |
| <i>receiver</i> | MPI rank of receiver in <i>communicator</i> . |
| <i>communicator</i> | Communicator ID. References a Comm definition and will be mapped to the global definition if a mapping table of type OTF2_MAPPING_COMM is available. |
| <i>msgTag</i> | Message tag |
| <i>msgLength</i> | Message length |
| <i>requestID</i> | ID of the related request |

Since

Version 1.2

Returns

[OTF2_CALLBACK_SUCCESS](#) or [OTF2_CALLBACK_INTERRUPT](#).

J.29.2.9 `typedef OTF2_CallbackCode(* OTF2_SnapReaderCallback_-
MpiIsendComplete)(OTF2_LocationRef location, OTF2_TimeStamp
snapTime, void *userData, OTF2_AttributeList *attributeList,
OTF2_TimeStamp origEventTime, uint64_t requestID)`

Callback for the MpiIsendComplete snap event record.

This record exists for each *MpiIsend* event where the corresponding *MpiIsendComplete* event occurred, but where the matching receive message event did not occur on the remote location before the snapshot. (This could either be an *MpiRecv* or an *MpiIrecv* event.) .

Parameters

| | |
|-----------------------|--|
| <i>location</i> | The location where this snap event happened. |
| <i>snapTime</i> | Snapshot time. |
| <i>userData</i> | User data as set by OTF2_Reader_RegisterSnapCallbacks or OTF2_-SnapReader_SetCallbacks . |
| <i>attributeList</i> | Additional attributes for this event. |
| <i>origEvent-Time</i> | The original time this event happened. |
| <i>requestID</i> | ID of the related request |

Since

Version 1.2

Returns

[OTF2_CALLBACK_SUCCESS](#) or [OTF2_CALLBACK_INTERRUPT](#).

J.29.2.10 `typedef OTF2_CallbackCode(* OTF2_SnapReaderCallback_-
MpiRecv)(OTF2_LocationRef location, OTF2_TimeStamp snapTime,
void *userData, OTF2_AttributeList *attributeList, OTF2_TimeStamp
origEventTime, uint32_t sender, OTF2_CommRef communicator, uint32_t
msgTag, uint64_t msgLength)`

Callback for the MpiRecv snap event record.

This record exists for each *MpiRecv* event where the matching send message event did not occur on the remote location before the snapshot. This could either be an *MpiSend* or an *MpiIsendComplete* event. Or an *MpiIrecvRequest* occurred before this event but the corresponding *MpiIrecv* event did not occurred before this snapshot. In this case the message matching couldn't performed yet, because the envelope of the ongoing *MpiIrecvRequest* is not yet known.

J.29 OTF2_SnapReaderCallbacks.h File Reference

Parameters

| | |
|----------------------|--|
| <i>location</i> | The location where this snap event happened. |
| <i>snapTime</i> | Snapshot time. |
| <i>userData</i> | User data as set by OTF2_Reader_RegisterSnapCallbacks or OTF2_SnapReader_SetCallbacks . |
| <i>attributeList</i> | Additional attributes for this event. |
| <i>origEventTime</i> | The original time this event happened. |
| <i>sender</i> | MPI rank of sender in <i>communicator</i> . |
| <i>communicator</i> | Communicator ID. References a Comm definition and will be mapped to the global definition if a mapping table of type OTF2_MAPPING_COMM is available. |
| <i>msgTag</i> | Message tag |
| <i>msgLength</i> | Message length |

Since

Version 1.2

Returns

[OTF2_CALLBACK_SUCCESS](#) or [OTF2_CALLBACK_INTERRUPT](#).

J.29.2.11 `typedef OTF2_CallbackCode(* OTF2_SnapReaderCallback_MpiSend)(OTF2_LocationRef location, OTF2_TimeStamp snapTime, void *userData, OTF2_AttributeList *attributeList, OTF2_TimeStamp origEventTime, uint32_t receiver, OTF2_CommRef communicator, uint32_t msgTag, uint64_t msgLength)`

Callback for the `MpiSend` snap event record.

This record exists for each [MpiSend](#) event where the matching receive message event did not occur on the remote location before the snapshot. This could either be an [MpiRecv](#) or an [MpiRecv](#) event. Note that it may so, that a previous [MpiSend](#) with the same envelope than this one is neither completed not canceled yet, thus the matching receive may already occurred, but the matching couldn't be done yet.

Parameters

| | |
|----------------------|---|
| <i>location</i> | The location where this snap event happened. |
| <i>snapTime</i> | Snapshot time. |
| <i>userData</i> | User data as set by OTF2_Reader_RegisterSnapCallbacks or OTF2_SnapReader_SetCallbacks . |
| <i>attributeList</i> | Additional attributes for this event. |

APPENDIX J. FILE DOCUMENTATION

| | |
|-----------------------|--|
| <i>origEvent-Time</i> | The original time this event happened. |
| <i>receiver</i> | MPI rank of receiver in <i>communicator</i> . |
| <i>communicator</i> | Communicator ID. References a Comm definition and will be mapped to the global definition if a mapping table of type OTF2_MAPPING_COMM is available. |
| <i>msgTag</i> | Message tag |
| <i>msgLength</i> | Message length |

Since

Version 1.2

Returns

[OTF2_CALLBACK_SUCCESS](#) or [OTF2_CALLBACK_INTERRUPT](#).

J.29.2.12 `typedef OTF2_CallbackCode(* OTF2_SnapReaderCallback_
OmpAcquireLock)(OTF2_LocationRef location, OTF2_TimeStamp
snapTime, void *userData, OTF2_AttributeList *attributeList,
OTF2_TimeStamp origEventTime, uint32_t lockID, uint32_t acquisitionOrder)`

Callback for the `OmpAcquireLock` snap event record.

This record exists for each [OmpAcquireLock](#) event where the corresponding [OmpReleaseLock](#) did not occurred before this snapshot yet.

Parameters

| | |
|-------------------------|---|
| <i>location</i> | The location where this snap event happened. |
| <i>snapTime</i> | Snapshot time. |
| <i>userData</i> | User data as set by OTF2_Reader_RegisterSnapCallbacks or OTF2_SnapReader_SetCallbacks . |
| <i>attributeList</i> | Additional attributes for this event. |
| <i>origEvent-Time</i> | The original time this event happened. |
| <i>lockID</i> | ID of the lock. |
| <i>acquisitionOrder</i> | A monotonically increasing number to determine the order of lock acquisitions (with unsynchronized clocks this is otherwise not possible). Corresponding acquire-release events have same number. |

Since

Version 1.2

J.29 OTF2_SnapReaderCallbacks.h File Reference

Returns

[OTF2_CALLBACK_SUCCESS](#) or [OTF2_CALLBACK_INTERRUPT](#).

J.29.2.13 `typedef OTF2_CallbackCode(* OTF2_SnapReaderCallback_ - OmpFork)(OTF2_LocationRef location, OTF2_TimeStamp snapTime, void *userData, OTF2_AttributeList *attributeList, OTF2_TimeStamp origEventTime, uint32_t numberOfRequestedThreads)`

Callback for the OmpFork snap event record.

This record exists for each *OmpFork* event where the corresponding *OmpJoin* did not occur before this snapshot.

Parameters

| | |
|---------------------------------|---|
| <i>location</i> | The location where this snap event happened. |
| <i>snapTime</i> | Snapshot time. |
| <i>userData</i> | User data as set by OTF2_Reader_RegisterSnapCallbacks or OTF2_SnapReader_SetCallbacks . |
| <i>attributeList</i> | Additional attributes for this event. |
| <i>origEventTime</i> | The original time this event happened. |
| <i>numberOfRequestedThreads</i> | Requested size of the team. |

Since

Version 1.2

Returns

[OTF2_CALLBACK_SUCCESS](#) or [OTF2_CALLBACK_INTERRUPT](#).

J.29.2.14 `typedef OTF2_CallbackCode(* OTF2_SnapReaderCallback_ - OmpTaskCreate)(OTF2_LocationRef location, OTF2_TimeStamp snapTime, void *userData, OTF2_AttributeList *attributeList, OTF2_TimeStamp origEventTime, uint64_t taskID)`

Callback for the OmpTaskCreate snap event record.

This record exists for each *OmpTaskCreate* event where the corresponding *OmpTaskComplete* event did not occur before this snapshot. Neither on this location

APPENDIX J. FILE DOCUMENTATION

nor on any other location in the current thread team.

Parameters

| | |
|-----------------------|---|
| <i>location</i> | The location where this snap event happened. |
| <i>snapTime</i> | Snapshot time. |
| <i>userData</i> | User data as set by OTF2_Reader_RegisterSnapCallbacks or OTF2_SnapReader_SetCallbacks . |
| <i>attributeList</i> | Additional attributes for this event. |
| <i>origEvent-Time</i> | The original time this event happened. |
| <i>taskID</i> | Identifier of the newly created task instance. |

Since

Version 1.2

Returns

[OTF2_CALLBACK_SUCCESS](#) or [OTF2_CALLBACK_INTERRUPT](#).

J.29.2.15 `typedef OTF2_CallbackCode(* OTF2_SnapReaderCallback_
OmpTaskSwitch)(OTF2_LocationRef location, OTF2_TimeStamp
snapTime, void *userData, OTF2_AttributeList *attributeList,
OTF2_TimeStamp origEventTime, uint64_t taskID)`

Callback for the `OmpTaskSwitch` snap event record.

This record exists for each [OmpTaskSwitch](#) event where the corresponding [OmpTaskComplete](#) event did not occurred before this snapshot. Neither on this location nor on any other location in the current thread team.

Parameters

| | |
|-----------------------|---|
| <i>location</i> | The location where this snap event happened. |
| <i>snapTime</i> | Snapshot time. |
| <i>userData</i> | User data as set by OTF2_Reader_RegisterSnapCallbacks or OTF2_SnapReader_SetCallbacks . |
| <i>attributeList</i> | Additional attributes for this event. |
| <i>origEvent-Time</i> | The original time this event happened. |
| <i>taskID</i> | Identifier of the now active task instance. |

J.29 OTF2_SnapReaderCallbacks.h File Reference

Since

Version 1.2

Returns

[OTF2_CALLBACK_SUCCESS](#) or [OTF2_CALLBACK_INTERRUPT](#).

J.29.2.16 typedef OTF2_CallbackCode(* OTF2_SnapReaderCallback_
ParameterInt)(OTF2_LocationRef location, OTF2_TimeStamp
snapTime, void *userData, OTF2_AttributeList *attributeList,
OTF2_TimeStamp origEventTime, OTF2_ParameterRef parameter,
int64_t value)

Callback for the ParameterInt snap event record.

This record must be included in the snapshot until the leave event for the enter event occurs which has the greatest timestamp less or equal the timestamp of this record.

Parameters

| | |
|----------------------|---|
| <i>location</i> | The location where this snap event happened. |
| <i>snapTime</i> | Snapshot time. |
| <i>userData</i> | User data as set by OTF2_Reader_RegisterSnapCallbacks or OTF2_SnapReader_SetCallbacks . |
| <i>attributeList</i> | Additional attributes for this event. |
| <i>origEventTime</i> | The original time this event happened. |
| <i>parameter</i> | Parameter ID. References a Parameter definition and will be mapped to the global definition if a mapping table of type OTF2_MAPPING_PARAMETER is available. |
| <i>value</i> | Value of the recorded parameter. |

Since

Version 1.2

Returns

[OTF2_CALLBACK_SUCCESS](#) or [OTF2_CALLBACK_INTERRUPT](#).

APPENDIX J. FILE DOCUMENTATION

J.29.2.17 typedef OTF2_CallbackCode(* OTF2_SnapReaderCallback_
ParameterString)(OTF2_LocationRef location, OTF2_TimeStamp
snapTime, void *userData, OTF2_AttributeList *attributeList,
OTF2_TimeStamp origEventTime, OTF2_ParameterRef parameter,
OTF2_StringRef string)

Callback for the ParameterString snap event record.

This record must be included in the snapshot until the leave event for the enter event occurs which has the greatest timestamp less or equal the timestamp of this record.

Parameters

| | |
|-----------------------|--|
| <i>location</i> | The location where this snap event happened. |
| <i>snapTime</i> | Snapshot time. |
| <i>userData</i> | User data as set by OTF2_Reader_RegisterSnapCallbacks or OTF2_SnapReader_SetCallbacks . |
| <i>attributeList</i> | Additional attributes for this event. |
| <i>origEvent-Time</i> | The original time this event happened. |
| <i>parameter</i> | Parameter ID. References a Parameter definition and will be mapped to the global definition if a mapping table of type OTF2_MAPPING_PARAMETER is available. |
| <i>string</i> | Value: Handle of a string definition References a String definition and will be mapped to the global definition if a mapping table of type OTF2_MAPPING_STRING is available. |

Since

Version 1.2

Returns

[OTF2_CALLBACK_SUCCESS](#) or [OTF2_CALLBACK_INTERRUPT](#).

J.29.2.18 typedef OTF2_CallbackCode(* OTF2_SnapReaderCallback_
ParameterUnsignedInt)(OTF2_LocationRef location,
OTF2_TimeStamp snapTime, void *userData, OTF2_AttributeList
*attributeList, OTF2_TimeStamp origEventTime, OTF2_ParameterRef
parameter, uint64_t value)

Callback for the ParameterUnsignedInt snap event record.

This record must be included in the snapshot until the leave event for the enter

J.29 OTF2_SnapReaderCallbacks.h File Reference

event occurs which has the greatest timestamp less or equal the timestamp of this record.

Parameters

| | |
|-----------------------|---|
| <i>location</i> | The location where this snap event happened. |
| <i>snapTime</i> | Snapshot time. |
| <i>userData</i> | User data as set by OTF2_Reader_RegisterSnapCallbacks or OTF2_SnapReader_SetCallbacks . |
| <i>attributeList</i> | Additional attributes for this event. |
| <i>origEvent-Time</i> | The original time this event happened. |
| <i>parameter</i> | Parameter ID. References a Parameter definition and will be mapped to the global definition if a mapping table of type OTF2_MAPPING_PARAMETER is available. |
| <i>value</i> | Value of the recorded parameter. |

Since

Version 1.2

Returns

[OTF2_CALLBACK_SUCCESS](#) or [OTF2_CALLBACK_INTERRUPT](#).

J.29.2.19 `typedef OTF2_CallbackCode(* OTF2_SnapReaderCallback_SnapshotEnd)(OTF2_LocationRef location, OTF2_TimeStamp snapTime, void *userData, OTF2_AttributeList *attributeList, uint64_t contReadPos)`

Callback for the SnapshotEnd snap event record.

This record marks the end of a snapshot. It contains the position to continue reading in the event trace for this location. Use [OTF2_EvtReader_Seek](#) with *contReadPos* as the position.

Parameters

| | |
|----------------------|---|
| <i>location</i> | The location where this snap event happened. |
| <i>snapTime</i> | Snapshot time. |
| <i>userData</i> | User data as set by OTF2_Reader_RegisterSnapCallbacks or OTF2_SnapReader_SetCallbacks . |
| <i>attributeList</i> | Additional attributes for this event. |
| <i>contRead-Pos</i> | Position to continue reading in the event trace. |

Since

Version 1.2

Returns

OTF2_CALLBACK_SUCCESS or *OTF2_CALLBACK_INTERRUPT*.

J.29.2.20 typedef OTF2_CallbackCode(* OTF2_SnapReaderCallback_ - SnapshotStart)(OTF2_LocationRef location, OTF2_TimeStamp snapTime, void *userData, OTF2_AttributeList *attributeList, uint64_t numberOfRecords)

Callback for the SnapshotStart snap event record.

This record marks the start of a snapshot.

A snapshot consists of an timestamp and a set of snapshot records. All these snapshot records have the same snapshot time. A snapshot starts with one *SnapshotStart* record and closes with one *SnapshotEnd* record. All snapshot records inbetween are ordered by the *origEventTime*, which are also less than the snapshot timestamp. Ie. The timestamp of the next event read from the event stream is greater or equal to the snapshot time.

Parameters

| | |
|-----------------------|---|
| <i>location</i> | The location where this snap event happened. |
| <i>snapTime</i> | Snapshot time. |
| <i>userData</i> | User data as set by <i>OTF2_Reader_RegisterSnapCallbacks</i> or <i>OTF2_SnapReader_SetCallbacks</i> . |
| <i>attributeList</i> | Additional attributes for this event. |
| <i>numberOfRecord</i> | Number of snapshot event records in this snapshot. Excluding the <i>SnapshotEnd</i> record. |

Since

Version 1.2

Returns

OTF2_CALLBACK_SUCCESS or *OTF2_CALLBACK_INTERRUPT*.

J.29 OTF2_SnapReaderCallbacks.h File Reference

J.29.2.21 `typedef OTF2_CallbackCode(* OTF2_SnapReaderCallback_Unknown)(OTF2_LocationRef location, OTF2_TimeStamp snapTime, void *userData, OTF2_AttributeList *attributeList)`

Callback for an unknown snap event record.

Parameters

| | |
|----------------------|---|
| <i>location</i> | The location where this event happened. |
| <i>time</i> | Snapshot time. |
| <i>userData</i> | User data as set by OTF2_Reader_RegisterSnapCallbacks or OTF2_SnapReader_SetCallbacks . |
| <i>attributeList</i> | Additional attributes for this event. |

Since

Version 1.2

Returns

[OTF2_CALLBACK_SUCCESS](#) or [OTF2_CALLBACK_INTERRUPT](#).

J.29.2.22 `typedef struct OTF2_SnapReaderCallbacks_struct OTF2_SnapReaderCallbacks`

Opaque struct which holds all snap event record callbacks.

Since

Version 1.2

J.29.3 Function Documentation

J.29.3.1 `void OTF2_SnapReaderCallbacks_Clear (OTF2_SnapReaderCallbacks * snapReaderCallbacks)`

Clears a struct for the snap event callbacks.

Parameters

| | |
|----------------------------|---|
| <i>snapReaderCallbacks</i> | Handle to a struct previously allocated with OTF2_SnapReaderCallbacks_New . |
|----------------------------|---|

Since

Version 1.2

J.29.3.2 void `OTF2_SnapReaderCallbacks_Delete` (`OTF2_SnapReaderCallbacks *`
`snapReaderCallbacks`)

Deallocates a struct for the snap event callbacks.

Parameters

| | |
|----------------------------|---|
| <i>snapReaderCallbacks</i> | Handle to a struct previously allocated with OTF2_SnapReaderCallbacks_New . |
|----------------------------|---|

Since

Version 1.2

J.29.3.3 `OTF2_SnapReaderCallbacks*` `OTF2_SnapReaderCallbacks_New` (void)

Allocates a new struct for the snap event callbacks.

Since

Version 1.2

Returns

A newly allocated struct of type [OTF2_SnapReaderCallbacks](#).

J.29.3.4 `OTF2_ErrorCode` `OTF2_SnapReaderCallbacks_SetEnterCallback`
(`OTF2_SnapReaderCallbacks *` `snapReaderCallbacks`,
`OTF2_SnapReaderCallback_Enter` `enterCallback`)

Registers the callback for the Enter snap event.

Parameters

| | |
|----------------------------|---|
| <i>snapReaderCallbacks</i> | Struct for all callbacks. |
| <i>enterCallback</i> | Function which should be called for all Enter events. |

J.29 OTF2_SnapReaderCallbacks.h File Reference

Since

Version 1.2

Returns

OTF2_SUCCESS if successful

OTF2_ERROR_INVALID_ARGUMENT for an invalid `defReaderCallbacks` argument

J.29.3.5 **OTF2_ErrorCode** **OTF2_SnapReaderCallbacks_SetMeasurementOnOffCallback**
(**OTF2_SnapReaderCallbacks** * *snapReaderCallbacks*,
OTF2_SnapReaderCallback_MeasurementOnOff
measurementOnOffCallback)

Registers the callback for the MeasurementOnOff snap event.

Parameters

| | |
|---------------------------------|--|
| <i>snapReaderCallbacks</i> | Struct for all callbacks. |
| <i>measurementOnOffCallback</i> | Function which should be called for all MeasurementOnOff events. |

Since

Version 1.2

Returns

OTF2_SUCCESS if successful

OTF2_ERROR_INVALID_ARGUMENT for an invalid `defReaderCallbacks` argument

J.29.3.6 **OTF2_ErrorCode** **OTF2_SnapReaderCallbacks_SetMetricCallback**
(**OTF2_SnapReaderCallbacks** * *snapReaderCallbacks*,
OTF2_SnapReaderCallback_Metric *metricCallback*)

Registers the callback for the Metric snap event.

Parameters

APPENDIX J. FILE DOCUMENTATION

| | |
|----------------------------|--|
| <i>snapReaderCallbacks</i> | Struct for all callbacks. |
| <i>metricCallback</i> | Function which should be called for all Metric events. |

Since

Version 1.2

Returns

OTF2_SUCCESS if successful

OTF2_ERROR_INVALID_ARGUMENT for an invalid `defReaderCallbacks` argument

J.29.3.7 **OTF2_StatusCode** **OTF2_SnapReaderCallbacks_SetMpiCollectiveBeginCallback**
(**OTF2_SnapReaderCallbacks** * *snapReaderCallbacks*,
OTF2_SnapReaderCallback_MpiCollectiveBegin
mpiCollectiveBeginCallback)

Registers the callback for the MpiCollectiveBegin snap event.

Parameters

| | |
|-----------------------------------|--|
| <i>snapReaderCallbacks</i> | Struct for all callbacks. |
| <i>mpiCollectiveBeginCallback</i> | Function which should be called for all MpiCollectiveBegin events. |

Since

Version 1.2

Returns

OTF2_SUCCESS if successful

OTF2_ERROR_INVALID_ARGUMENT for an invalid `defReaderCallbacks` argument

J.29 OTF2_SnapReaderCallbacks.h File Reference

J.29.3.8 `OTF2_ErrorCode OTF2_SnapReaderCallbacks_SetMpiCollectiveEndCallback (OTF2_SnapReaderCallbacks * snapReaderCallbacks, OTF2_SnapReaderCallback_MpiCollectiveEnd mpiCollectiveEndCallback)`

Registers the callback for the MpiCollectiveEnd snap event.

Parameters

| | |
|---------------------------------|--|
| <i>snapReaderCallbacks</i> | Struct for all callbacks. |
| <i>mpiCollectiveEndCallback</i> | Function which should be called for all MpiCollectiveEnd events. |

Since

Version 1.2

Returns

[*OTF2_SUCCESS*](#) if successful

[*OTF2_ERROR_INVALID_ARGUMENT*](#) for an invalid `defReaderCallbacks` argument

J.29.3.9 `OTF2_ErrorCode OTF2_SnapReaderCallbacks_SetMpiIrecvCallback (OTF2_SnapReaderCallbacks * snapReaderCallbacks, OTF2_SnapReaderCallback_MpiIrecv mpiIrecvCallback)`

Registers the callback for the MpiIrecv snap event.

Parameters

| | |
|----------------------------|--|
| <i>snapReaderCallbacks</i> | Struct for all callbacks. |
| <i>mpiIrecvCallback</i> | Function which should be called for all MpiIrecv events. |

Since

Version 1.2

Returns

[*OTF2_SUCCESS*](#) if successful

APPENDIX J. FILE DOCUMENTATION

OTF2_ERROR_INVALID_ARGUMENT for an invalid `defReaderCallbacks` argument

J.29.3.10 **OTF2_ErrorCode** `OTF2_SnapReaderCallbacks_SetMpiIrecvRequestCallback`
(**OTF2_SnapReaderCallbacks** * *snapReaderCallbacks*,
OTF2_SnapReaderCallback_MpiIrecvRequest
mpiIrecvRequestCallback)

Registers the callback for the `MpiIrecvRequest` snap event.

Parameters

| | |
|--------------------------------|--|
| <i>snapReaderCallbacks</i> | Struct for all callbacks. |
| <i>mpiIrecvRequestCallback</i> | Function which should be called for all <code>MpiIrecvRequest</code> events. |

Since

Version 1.2

Returns

OTF2_SUCCESS if successful

OTF2_ERROR_INVALID_ARGUMENT for an invalid `defReaderCallbacks` argument

J.29.3.11 **OTF2_ErrorCode** `OTF2_SnapReaderCallbacks_SetMpiIsendCallback`
(**OTF2_SnapReaderCallbacks** * *snapReaderCallbacks*,
OTF2_SnapReaderCallback_MpiIsend *mpiIsendCallback*)

Registers the callback for the `MpiIsend` snap event.

Parameters

| | |
|----------------------------|---|
| <i>snapReaderCallbacks</i> | Struct for all callbacks. |
| <i>mpiIsendCallback</i> | Function which should be called for all <code>MpiIsend</code> events. |

J.29 OTF2_SnapReaderCallbacks.h File Reference

Since

Version 1.2

Returns

OTF2_SUCCESS if successful

OTF2_ERROR_INVALID_ARGUMENT for an invalid `defReaderCallbacks` argument

J.29.3.12 **OTF2_ErrorCode** `OTF2_SnapReaderCallbacks_SetMpiSendCompleteCallback`
(**OTF2_SnapReaderCallbacks** * *snapReaderCallbacks*,
OTF2_SnapReaderCallback_MpiSendComplete
mpisendCompleteCallback)

Registers the callback for the `MpiSendComplete` snap event.

Parameters

| | |
|--------------------------------|--|
| <i>snapReaderCallbacks</i> | Struct for all callbacks. |
| <i>mpisendCompleteCallback</i> | Function which should be called for all <code>MpiSendComplete</code> events. |

Since

Version 1.2

Returns

OTF2_SUCCESS if successful

OTF2_ERROR_INVALID_ARGUMENT for an invalid `defReaderCallbacks` argument

J.29.3.13 **OTF2_ErrorCode** `OTF2_SnapReaderCallbacks_SetMpiRecvCallback`
(**OTF2_SnapReaderCallbacks** * *snapReaderCallbacks*,
OTF2_SnapReaderCallback_MpiRecv *mpiRecvCallback*)

Registers the callback for the `MpiRecv` snap event.

Parameters

APPENDIX J. FILE DOCUMENTATION

| | |
|----------------------------|---|
| <i>snapReaderCallbacks</i> | Struct for all callbacks. |
| <i>mpiRecvCallback</i> | Function which should be called for all MpiRecv events. |

Since

Version 1.2

Returns

OTF2_SUCCESS if successful

OTF2_ERROR_INVALID_ARGUMENT for an invalid `defReaderCallbacks` argument

J.29.3.14 **OTF2_ErrorCode** `OTF2_SnapReaderCallbacks_SetMpiSendCallback`
(**OTF2_SnapReaderCallbacks** * *snapReaderCallbacks*,
OTF2_SnapReaderCallback_MpiSend *mpiSendCallback*)

Registers the callback for the MpiSend snap event.

Parameters

| | |
|----------------------------|---|
| <i>snapReaderCallbacks</i> | Struct for all callbacks. |
| <i>mpiSendCallback</i> | Function which should be called for all MpiSend events. |

Since

Version 1.2

Returns

OTF2_SUCCESS if successful

OTF2_ERROR_INVALID_ARGUMENT for an invalid `defReaderCallbacks` argument

J.29 OTF2_SnapReaderCallbacks.h File Reference

J.29.3.15 **OTF2_ErrorCode** **OTF2_SnapReaderCallbacks_SetOmpAcquireLockCallback**
(**OTF2_SnapReaderCallbacks** * *snapReaderCallbacks*,
OTF2_SnapReaderCallback_OmpAcquireLock
ompAcquireLockCallback)

Registers the callback for the OmpAcquireLock snap event.

Parameters

| | |
|-------------------------------|--|
| <i>snapReaderCallbacks</i> | Struct for all callbacks. |
| <i>ompAcquireLockCallback</i> | Function which should be called for all OmpAcquireLock events. |

Since

Version 1.2

Returns

OTF2_SUCCESS if successful

OTF2_ERROR_INVALID_ARGUMENT for an invalid *defReaderCallbacks* argument

J.29.3.16 **OTF2_ErrorCode** **OTF2_SnapReaderCallbacks_SetOmpForkCallback**
(**OTF2_SnapReaderCallbacks** * *snapReaderCallbacks*,
OTF2_SnapReaderCallback_OmpFork *ompForkCallback*)

Registers the callback for the OmpFork snap event.

Parameters

| | |
|----------------------------|---|
| <i>snapReaderCallbacks</i> | Struct for all callbacks. |
| <i>ompForkCallback</i> | Function which should be called for all OmpFork events. |

Since

Version 1.2

Returns

OTF2_SUCCESS if successful

APPENDIX J. FILE DOCUMENTATION

OTF2_ERROR_INVALID_ARGUMENT for an invalid `defReaderCallbacks` argument

J.29.3.17 **OTF2_ErrorCode** `OTF2_SnapReaderCallbacks_SetOmpTaskCreateCallback`
(**OTF2_SnapReaderCallbacks** * *snapReaderCallbacks*,
OTF2_SnapReaderCallback_OmpTaskCreate *ompTaskCreateCallback*
)

Registers the callback for the `OmpTaskCreate` snap event.

Parameters

| | |
|------------------------------|--|
| <i>snapReaderCallbacks</i> | Struct for all callbacks. |
| <i>ompTaskCreateCallback</i> | Function which should be called for all <code>OmpTaskCreate</code> events. |

Since

Version 1.2

Returns

OTF2_SUCCESS if successful

OTF2_ERROR_INVALID_ARGUMENT for an invalid `defReaderCallbacks` argument

J.29.3.18 **OTF2_ErrorCode** `OTF2_SnapReaderCallbacks_SetOmpTaskSwitchCallback`
(**OTF2_SnapReaderCallbacks** * *snapReaderCallbacks*,
OTF2_SnapReaderCallback_OmpTaskSwitch *ompTaskSwitchCallback*
)

Registers the callback for the `OmpTaskSwitch` snap event.

Parameters

| | |
|------------------------------|--|
| <i>snapReaderCallbacks</i> | Struct for all callbacks. |
| <i>ompTaskSwitchCallback</i> | Function which should be called for all <code>OmpTaskSwitch</code> events. |

J.29 OTF2_SnapReaderCallbacks.h File Reference

Since

Version 1.2

Returns

OTF2_SUCCESS if successful

OTF2_ERROR_INVALID_ARGUMENT for an invalid `defReaderCallbacks` argument

J.29.3.19 **OTF2_StatusCode** `OTF2_SnapReaderCallbacks.SetParameterIntCallback`
(`OTF2_SnapReaderCallbacks * snapReaderCallbacks`,
`OTF2_SnapReaderCallback_ParameterInt parameterIntCallback`)

Registers the callback for the ParameterInt snap event.

Parameters

| | |
|-----------------------------|--|
| <i>snapReaderCallbacks</i> | Struct for all callbacks. |
| <i>parameterIntCallback</i> | Function which should be called for all ParameterInt events. |

Since

Version 1.2

Returns

OTF2_SUCCESS if successful

OTF2_ERROR_INVALID_ARGUMENT for an invalid `defReaderCallbacks` argument

J.29.3.20 **OTF2_StatusCode** `OTF2_SnapReaderCallbacks.SetParameterStringCallback`
(`OTF2_SnapReaderCallbacks * snapReaderCallbacks`,
`OTF2_SnapReaderCallback_ParameterString parameterStringCallback`
)

Registers the callback for the ParameterString snap event.

Parameters

| | |
|----------------------------|---------------------------|
| <i>snapReaderCallbacks</i> | Struct for all callbacks. |
|----------------------------|---------------------------|

APPENDIX J. FILE DOCUMENTATION

| | |
|---------------------------------|---|
| <i>parameter-StringCallback</i> | Function which should be called for all ParameterString events. |
|---------------------------------|---|

Since

Version 1.2

Returns

OTF2_SUCCESS if successful

OTF2_ERROR_INVALID_ARGUMENT for an invalid `defReaderCallbacks` argument

J.29.3.21 ***OTF2_ErrorCode*** ***OTF2_SnapReaderCallbacks_***
SetParameterUnsignedIntCallback (OTF2_SnapReaderCallbacks
**** snapReaderCallbacks, OTF2_SnapReaderCallback_***
ParameterUnsignedInt parameterUnsignedIntCallback
)

Registers the callback for the `ParameterUnsignedInt` snap event.

Parameters

| | |
|-------------------------------------|---|
| <i>snapReaderCallbacks</i> | Struct for all callbacks. |
| <i>parameterUnsignedIntCallback</i> | Function which should be called for all <code>ParameterUnsignedInt</code> events. |

Since

Version 1.2

Returns

OTF2_SUCCESS if successful

OTF2_ERROR_INVALID_ARGUMENT for an invalid `defReaderCallbacks` argument

J.29 OTF2_SnapReaderCallbacks.h File Reference

J.29.3.22 **OTF2_ErrorCode** **OTF2_SnapReaderCallbacks.SetSnapshotEndCallback**
(**OTF2_SnapReaderCallbacks** * *snapReaderCallbacks*,
OTF2_SnapReaderCallback_SnapshotEnd *snapshotEndCallback*)

Registers the callback for the SnapshotEnd snap event.

Parameters

| | |
|----------------------------|---|
| <i>snapReaderCallbacks</i> | Struct for all callbacks. |
| <i>snapshotEndCallback</i> | Function which should be called for all SnapshotEnd events. |

Since

Version 1.2

Returns

OTF2_SUCCESS if successful

OTF2_ERROR_INVALID_ARGUMENT for an invalid *defReaderCallbacks* argument

J.29.3.23 **OTF2_ErrorCode** **OTF2_SnapReaderCallbacks.SetSnapshotStartCallback**
(**OTF2_SnapReaderCallbacks** * *snapReaderCallbacks*,
OTF2_SnapReaderCallback_SnapshotStart *snapshotStartCallback*)

Registers the callback for the SnapshotStart snap event.

Parameters

| | |
|------------------------------|---|
| <i>snapReaderCallbacks</i> | Struct for all callbacks. |
| <i>snapshotStartCallback</i> | Function which should be called for all SnapshotStart events. |

Since

Version 1.2

Returns

OTF2_SUCCESS if successful

APPENDIX J. FILE DOCUMENTATION

OTF2_ERROR_INVALID_ARGUMENT for an invalid `defReaderCallbacks` argument

J.29.3.24 **OTF2_ErrorCode** **OTF2_SnapReaderCallbacks_SetUnknownCallback**
(**OTF2_SnapReaderCallbacks** * *snapReaderCallbacks*,
OTF2_SnapReaderCallback_Unknown *unknownCallback*)

Registers the callback for the Unknown snap event.

Parameters

| | |
|----------------------------|--|
| <i>snapReaderCallbacks</i> | Struct for all callbacks. |
| <i>unknownCallback</i> | Function which should be called for all unknown snap events. |

Since

Version 1.2

Returns

OTF2_SUCCESS if successful

OTF2_ERROR_INVALID_ARGUMENT for an invalid `defReaderCallbacks` argument

J.30 OTF2_SnapWriter.h File Reference

This lowest user-visible layer provides write routines to write snapshot records for a single location.

```
#include <stdint.h>
#include <otf2/OTF2_ErrorCodes.h>
#include <otf2/OTF2_Events.h>
#include <otf2/OTF2_AttributeList.h>
```

Typedefs

- typedef struct OTF2_SnapWriter_struct **OTF2_SnapWriter**
Keeps all necessary information about the snap writer. See OTF2_SnapWriter_struct for detailed information.

J.30 OTF2_SnapWriter.h File Reference

Functions

- [OTF2_ErrorCode](#) [OTF2_SnapWriter_Enter](#) ([OTF2_SnapWriter](#) *writer, [OTF2_AttributeList](#) *attributeList, [OTF2_TimeStamp](#) snapTime, [OTF2_TimeStamp](#) origEventTime, [OTF2_RegionRef](#) region)
Records an Enter snapshot record.
- [OTF2_ErrorCode](#) [OTF2_SnapWriter_GetLocationID](#) (const [OTF2_SnapWriter](#) *writer, [OTF2_LocationRef](#) *locationID)
Function to get the location ID of a snap writer object.
- [OTF2_ErrorCode](#) [OTF2_SnapWriter_MeasurementOnOff](#) ([OTF2_SnapWriter](#) *writer, [OTF2_AttributeList](#) *attributeList, [OTF2_TimeStamp](#) snapTime, [OTF2_TimeStamp](#) origEventTime, [OTF2_MeasurementMode](#) measurementMode)
Records an MeasurementOnOff snapshot record.
- [OTF2_ErrorCode](#) [OTF2_SnapWriter_Metric](#) ([OTF2_SnapWriter](#) *writer, [OTF2_AttributeList](#) *attributeList, [OTF2_TimeStamp](#) snapTime, [OTF2_TimeStamp](#) origEventTime, [OTF2_MetricRef](#) metric, [uint8_t](#) numberOfMetrics, const [OTF2_Type](#) *typeIDs, const [OTF2_MetricValue](#) *metricValues)
Records an Metric snapshot record.
- [OTF2_ErrorCode](#) [OTF2_SnapWriter_MpiCollectiveBegin](#) ([OTF2_SnapWriter](#) *writer, [OTF2_AttributeList](#) *attributeList, [OTF2_TimeStamp](#) snapTime, [OTF2_TimeStamp](#) origEventTime)
Records an MpiCollectiveBegin snapshot record.
- [OTF2_ErrorCode](#) [OTF2_SnapWriter_MpiCollectiveEnd](#) ([OTF2_SnapWriter](#) *writer, [OTF2_AttributeList](#) *attributeList, [OTF2_TimeStamp](#) snapTime, [OTF2_TimeStamp](#) origEventTime, [OTF2_CollectiveOp](#) collectiveOp, [OTF2_CommRef](#) communicator, [uint32_t](#) root, [uint64_t](#) sizeSent, [uint64_t](#) sizeReceived)
Records an MpiCollectiveEnd snapshot record.
- [OTF2_ErrorCode](#) [OTF2_SnapWriter_MpiIrecv](#) ([OTF2_SnapWriter](#) *writer, [OTF2_AttributeList](#) *attributeList, [OTF2_TimeStamp](#) snapTime, [OTF2_TimeStamp](#) origEventTime, [uint32_t](#) sender, [OTF2_CommRef](#) communicator, [uint32_t](#) msgTag, [uint64_t](#) msgLength, [uint64_t](#) requestID)
Records an MpiIrecv snapshot record.
- [OTF2_ErrorCode](#) [OTF2_SnapWriter_MpiIrecvRequest](#) ([OTF2_SnapWriter](#) *writer, [OTF2_AttributeList](#) *attributeList, [OTF2_TimeStamp](#) snapTime, [OTF2_TimeStamp](#) origEventTime, [uint64_t](#) requestID)

APPENDIX J. FILE DOCUMENTATION

Records an MpiIrecvRequest snapshot record.

- [OTF2_ErrorCode](#) [OTF2_SnapWriter_MpiIrecv](#) ([OTF2_SnapWriter](#) *writer, [OTF2_AttributeList](#) *attributeList, [OTF2_TimeStamp](#) snapTime, [OTF2_TimeStamp](#) origEventTime, [uint32_t](#) receiver, [OTF2_CommRef](#) communicator, [uint32_t](#) msgTag, [uint64_t](#) msgLength, [uint64_t](#) requestID)

Records an MpiIrecv snapshot record.

- [OTF2_ErrorCode](#) [OTF2_SnapWriter_MpiIrecvComplete](#) ([OTF2_SnapWriter](#) *writer, [OTF2_AttributeList](#) *attributeList, [OTF2_TimeStamp](#) snapTime, [OTF2_TimeStamp](#) origEventTime, [uint64_t](#) requestID)

Records an MpiIrecvComplete snapshot record.

- [OTF2_ErrorCode](#) [OTF2_SnapWriter_MpiRecv](#) ([OTF2_SnapWriter](#) *writer, [OTF2_AttributeList](#) *attributeList, [OTF2_TimeStamp](#) snapTime, [OTF2_TimeStamp](#) origEventTime, [uint32_t](#) sender, [OTF2_CommRef](#) communicator, [uint32_t](#) msgTag, [uint64_t](#) msgLength)

Records an MpiRecv snapshot record.

- [OTF2_ErrorCode](#) [OTF2_SnapWriter_MpiSend](#) ([OTF2_SnapWriter](#) *writer, [OTF2_AttributeList](#) *attributeList, [OTF2_TimeStamp](#) snapTime, [OTF2_TimeStamp](#) origEventTime, [uint32_t](#) receiver, [OTF2_CommRef](#) communicator, [uint32_t](#) msgTag, [uint64_t](#) msgLength)

Records an MpiSend snapshot record.

- [OTF2_ErrorCode](#) [OTF2_SnapWriter_OmpAcquireLock](#) ([OTF2_SnapWriter](#) *writer, [OTF2_AttributeList](#) *attributeList, [OTF2_TimeStamp](#) snapTime, [OTF2_TimeStamp](#) origEventTime, [uint32_t](#) lockID, [uint32_t](#) acquisitionOrder)

Records an OmpAcquireLock snapshot record.

- [OTF2_ErrorCode](#) [OTF2_SnapWriter_OmpFork](#) ([OTF2_SnapWriter](#) *writer, [OTF2_AttributeList](#) *attributeList, [OTF2_TimeStamp](#) snapTime, [OTF2_TimeStamp](#) origEventTime, [uint32_t](#) numberOfRequestedThreads)

Records an OmpFork snapshot record.

- [OTF2_ErrorCode](#) [OTF2_SnapWriter_OmpTaskCreate](#) ([OTF2_SnapWriter](#) *writer, [OTF2_AttributeList](#) *attributeList, [OTF2_TimeStamp](#) snapTime, [OTF2_TimeStamp](#) origEventTime, [uint64_t](#) taskID)

Records an OmpTaskCreate snapshot record.

- [OTF2_ErrorCode](#) [OTF2_SnapWriter_OmpTaskSwitch](#) ([OTF2_SnapWriter](#) *writer, [OTF2_AttributeList](#) *attributeList, [OTF2_TimeStamp](#) snapTime, [OTF2_TimeStamp](#) origEventTime, [uint64_t](#) taskID)

J.30 OTF2_SnapWriter.h File Reference

Records an OmpTaskSwitch snapshot record.

- [OTF2_ErrorCode](#) [OTF2_SnapWriter_ParameterInt](#) ([OTF2_SnapWriter](#) *writer, [OTF2_AttributeList](#) *attributeList, [OTF2_TimeStamp](#) snapTime, [OTF2_TimeStamp](#) origEventTime, [OTF2_ParameterRef](#) parameter, int64_t value)

Records an ParameterInt snapshot record.

- [OTF2_ErrorCode](#) [OTF2_SnapWriter_ParameterString](#) ([OTF2_SnapWriter](#) *writer, [OTF2_AttributeList](#) *attributeList, [OTF2_TimeStamp](#) snapTime, [OTF2_TimeStamp](#) origEventTime, [OTF2_ParameterRef](#) parameter, [OTF2_StringRef](#) string)

Records an ParameterString snapshot record.

- [OTF2_ErrorCode](#) [OTF2_SnapWriter_ParameterUnsignedInt](#) ([OTF2_SnapWriter](#) *writer, [OTF2_AttributeList](#) *attributeList, [OTF2_TimeStamp](#) snapTime, [OTF2_TimeStamp](#) origEventTime, [OTF2_ParameterRef](#) parameter, uint64_t value)

Records an ParameterUnsignedInt snapshot record.

- [OTF2_ErrorCode](#) [OTF2_SnapWriter_SnapshotEnd](#) ([OTF2_SnapWriter](#) *writer, [OTF2_AttributeList](#) *attributeList, [OTF2_TimeStamp](#) snapTime, uint64_t contReadPos)

Records an SnapshotEnd snapshot record.

- [OTF2_ErrorCode](#) [OTF2_SnapWriter_SnapshotStart](#) ([OTF2_SnapWriter](#) *writer, [OTF2_AttributeList](#) *attributeList, [OTF2_TimeStamp](#) snapTime, uint64_t numberOfRecords)

Records an SnapshotStart snapshot record.

J.30.1 Detailed Description

This lowest user-visible layer provides write routines to write snapshot records for a single location.

Source Template:

templates/OTF2_SnapWriter.templ.h

J.30.2 Typedef Documentation

J.30.2.1 typedef struct OTF2_SnapWriter_struct OTF2_SnapWriter

Keeps all necessary information about the snap writer. See OTF2_SnapWriter_struct for detailed information.

Since

Version 1.2

J.30.3 Function Documentation

J.30.3.1 OTF2_ErrorCode OTF2_SnapWriter_Enter (OTF2_SnapWriter * *writer*, OTF2_AttributeList * *attributeList*, OTF2_TimeStamp *snapTime*, OTF2_TimeStamp *origEventTime*, OTF2_RegionRef *region*)

Records an Enter snapshot record.

This record exists for each *Enter* event where the corresponding *Leave* event did not occur before the snapshot.

Parameters

| | |
|----------------------|--|
| <i>writer</i> | Writer object. |
| <i>attributeList</i> | Generic attributes for the record. |
| <i>snapTime</i> | Snapshot time. |
| <i>origEventTime</i> | The original time this event happended. |
| <i>region</i> | Needs to be defined in a definition record References a Region definition and will be mapped to the global definition if a mapping table of type OTF2_MAPPING_REGION is available. |

Since

Version 1.2

Returns

[OTF2_SUCCESS](#) if successful, an error code if an error occurs.

J.30.3.2 OTF2_ErrorCode OTF2_SnapWriter_GetLocationID (const OTF2_SnapWriter * *writer*, OTF2_LocationRef * *locationID*)

Function to get the location ID of a snap writer object.

J.30 OTF2_SnapWriter.h File Reference

Parameters

| | |
|-------------------|---|
| <i>writer</i> | Snap writer object of interest |
| <i>locationID</i> | Pointer to a variable where the ID is returned in |

Since

Version 1.2

Returns

[OTF2_SUCCESS](#) if successful, an error code if an error occurs.

J.30.3.3 OTF2_ErrorCode OTF2_SnapWriter_MeasurementOnOff (
OTF2_SnapWriter * *writer*, OTF2_AttributeList * *attributeList*,
OTF2_TimeStamp *snapTime*, OTF2_TimeStamp *origEventTime*,
OTF2_MeasurementMode *measurementMode*)

Records an MeasurementOnOff snapshot record.

The last occurrence of an [MeasurementOnOff](#) event of this location, if any.

Parameters

| | |
|------------------------|---|
| <i>writer</i> | Writer object. |
| <i>attributeList</i> | Generic attributes for the record. |
| <i>snapTime</i> | Snapshot time. |
| <i>origEventTime</i> | The original time this event happended. |
| <i>measurementMode</i> | Is the measurement turned on (OTF2_MEASUREMENT_ON) or off (OTF2_MEASUREMENT_OFF)? |

Since

Version 1.2

Returns

[OTF2_SUCCESS](#) if successful, an error code if an error occurs.

J.30.3.4 `OTF2_ErrorCode OTF2_SnapWriter_Metric (OTF2_SnapWriter * writer, OTF2_AttributeList * attributeList, OTF2_TimeStamp snapTime, OTF2_TimeStamp origEventTime, OTF2_MetricRef metric, uint8_t numberOfMetrics, const OTF2_Type * typeIDs, const OTF2_MetricValue * metricValues)`

Records an Metric snapshot record.

This record exists for each referenced metric class or metric instance event this location recorded metrics before and provides the last known recorded metric values.

As an exception for metric classes where the metric mode detontes an [OTF2_METRIC_VALUE_RELATIVE](#) mode the value indicates the accumulation of all previous metric values recorded.

Parameters

| | |
|-------------------------|--|
| <i>writer</i> | Writer object. |
| <i>attributeList</i> | Generic attributes for the record. |
| <i>snapTime</i> | Snapshot time. |
| <i>origEvent-Time</i> | The original time this event happended. |
| <i>metric</i> | Could be a metric class or a metric instance. References a MetricClass , or a MetricInstance definition and will be mapped to the global definition if a mapping table of type OTF2_MAPPING_METRIC is available. |
| <i>numberOf-Metrics</i> | Number of metrics with in the set. |
| <i>typeIDs</i> | List of metric types. |
| <i>metricVal-ues</i> | List of metric values. |

Since

Version 1.2

Returns

[OTF2_SUCCESS](#) if successful, an error code if an error occurs.

J.30.3.5 `OTF2_ErrorCode OTF2_SnapWriter_MpiCollectiveBegin (OTF2_SnapWriter * writer, OTF2_AttributeList * attributeList, OTF2_TimeStamp snapTime, OTF2_TimeStamp origEventTime)`

Records an MpiCollectiveBegin snapshot record.

J.30 OTF2_SnapWriter.h File Reference

Indicates that this location started a collective operation but not all of the participating locations completed the operation yet, including this location.

Parameters

| | |
|----------------------|--|
| <i>writer</i> | Writer object. |
| <i>attributeList</i> | Generic attributes for the record. |
| <i>snapTime</i> | Snapshot time. |
| <i>origEventTime</i> | The original time this event happened. |

Since

Version 1.2

Returns

[OTF2_SUCCESS](#) if successful, an error code if an error occurs.

J.30.3.6 OTF2_ErrorCode OTF2_SnapWriter_MpiCollectiveEnd (
OTF2_SnapWriter * *writer*, OTF2_AttributeList * *attributeList*,
OTF2_TimeStamp *snapTime*, OTF2_TimeStamp *origEventTime*,
OTF2_CollectiveOp *collectiveOp*, OTF2_CommRef *communicator*,
uint32_t *root*, uint64_t *sizeSent*, uint64_t *sizeReceived*)

Records an MpiCollectiveEnd snapshot record.

Indicates that this location completed a collective operation locally but not all of the participating locations completed the operation yet. The corresponding *MpiCollectiveBeginSnaps* record is still in the snapshot though.

Parameters

| | |
|----------------------|--|
| <i>writer</i> | Writer object. |
| <i>attributeList</i> | Generic attributes for the record. |
| <i>snapTime</i> | Snapshot time. |
| <i>origEventTime</i> | The original time this event happened. |
| <i>collectiveOp</i> | Determines which collective operation it is. |
| <i>communicator</i> | Communicator References a Comm definition and will be mapped to the global definition if a mapping table of type OTF2_MAPPING_COMM is available. |
| <i>root</i> | MPI rank of root in <i>communicator</i> . |
| <i>sizeSent</i> | Size of the sent message. |

APPENDIX J. FILE DOCUMENTATION

| | |
|---------------------|-------------------------------|
| <i>sizeReceived</i> | Size of the received message. |
|---------------------|-------------------------------|

Since

Version 1.2

Returns

[OTF2_SUCCESS](#) if successful, an error code if an error occurs.

J.30.3.7 `OTF2_ErrorCode OTF2_SnapWriter_Mpilrecv (OTF2_SnapWriter * writer, OTF2_AttributeList * attributeList, OTF2_TimeStamp snapTime, OTF2_TimeStamp origEventTime, uint32_t sender, OTF2_CommRef communicator, uint32_t msgTag, uint64_t msgLength, uint64_t requestID)`

Records an `Mpilrecv` snapshot record.

This record exists for each `Mpilrecv` event where the matching send message event did not occur on the remote location before the snapshot. This could either be an `MpilSend` or an `MpilSendComplete` event. Or an `MpilrecvRequest` occurred before this event but the corresponding `Mpilrecv` event did not occur before this snapshot. In this case the message matching couldn't be performed yet, because the envelope of the ongoing `MpilrecvRequest` is not yet known.

Parameters

| | |
|----------------------|--|
| <i>writer</i> | Writer object. |
| <i>attributeList</i> | Generic attributes for the record. |
| <i>snapTime</i> | Snapshot time. |
| <i>origEventTime</i> | The original time this event happened. |
| <i>sender</i> | MPI rank of sender in <i>communicator</i> . |
| <i>communicator</i> | Communicator ID. References a Comm definition and will be mapped to the global definition if a mapping table of type OTF2_MAPPING_COMM is available. |
| <i>msgTag</i> | Message tag |
| <i>msgLength</i> | Message length |
| <i>requestID</i> | ID of the related request |

Since

Version 1.2

J.30 OTF2_SnapWriter.h File Reference

Returns

OTF2_SUCCESS if successful, an error code if an error occurs.

J.30.3.8 `OTF2_ErrorCode OTF2_SnapWriter_MpilrecvRequest (OTF2_SnapWriter * writer, OTF2_AttributeList * attributeList, OTF2_TimeStamp snapTime, OTF2_TimeStamp origEventTime, uint64_t requestID)`

Records an `MpilrecvRequest` snapshot record.

This record exists for each *MpilrecvRequest* event where an corresponding *Mpilrecv* or *MpiRequestCancelled* event did not occur on this location before the snapshot. Or the corresponding *Mpilrecv* did occurred (the *MpilrecvSnap* record exists in the snapshot) but the matching receive message event did not occur on the remote location before the snapshot. This could either be an *MpiRecv* or an *Mpilrecv* event.

Parameters

| | |
|----------------------|---|
| <i>writer</i> | Writer object. |
| <i>attributeList</i> | Generic attributes for the record. |
| <i>snapTime</i> | Snapshot time. |
| <i>origEventTime</i> | The original time this event happended. |
| <i>requestID</i> | ID of the requested receive |

Since

Version 1.2

Returns

OTF2_SUCCESS if successful, an error code if an error occurs.

J.30.3.9 `OTF2_ErrorCode OTF2_SnapWriter_Mpilsend (OTF2_SnapWriter * writer, OTF2_AttributeList * attributeList, OTF2_TimeStamp snapTime, OTF2_TimeStamp origEventTime, uint32_t receiver, OTF2_CommRef communicator, uint32_t msgTag, uint64_t msgLength, uint64_t requestID)`

Records an `Mpilsend` snapshot record.

This record exists for each *Mpilsend* event where an corresponding *MpilsendComplete* or *MpiRequestCancelled* event did not occur on this location before the snapshot. Or the corresponding *MpilsendComplete* did occurred (the *MpilsendCompleteSnap* record exists in the snapshot) but the matching receive message event

APPENDIX J. FILE DOCUMENTATION

did not occur on the remote location before the snapshot. (This could either be an *MpiRecv* or an *MpiIrecv* event.)

Parameters

| | |
|----------------------|--|
| <i>writer</i> | Writer object. |
| <i>attributeList</i> | Generic attributes for the record. |
| <i>snapTime</i> | Snapshot time. |
| <i>origEventTime</i> | The original time this event happened. |
| <i>receiver</i> | MPI rank of receiver in <i>communicator</i> . |
| <i>communicator</i> | Communicator ID. References a <i>Comm</i> definition and will be mapped to the global definition if a mapping table of type <i>OTF2_MAPPING_COMM</i> is available. |
| <i>msgTag</i> | Message tag |
| <i>msgLength</i> | Message length |
| <i>requestID</i> | ID of the related request |

Since

Version 1.2

Returns

OTF2_SUCCESS if successful, an error code if an error occurs.

J.30.3.10 *OTF2_ErrorCode* *OTF2_SnapWriter_MpilsendComplete* (
OTF2_SnapWriter * *writer*, *OTF2_AttributeList* * *attributeList*,
OTF2_TimeStamp *snapTime*, *OTF2_TimeStamp* *origEventTime*, *uint64_t*
requestID)

Records an *MpilsendComplete* snapshot record.

This record exists for each *Mpilsend* event where the corresponding *MpilsendComplete* event occurred, but where the matching receive message event did not occur on the remote location before the snapshot. (This could either be an *MpiRecv* or an *MpiIrecv* event.) .

Parameters

| | |
|----------------------|--|
| <i>writer</i> | Writer object. |
| <i>attributeList</i> | Generic attributes for the record. |
| <i>snapTime</i> | Snapshot time. |
| <i>origEventTime</i> | The original time this event happened. |
| <i>requestID</i> | ID of the related request |

J.30 OTF2_SnapWriter.h File Reference

Since

Version 1.2

Returns

[OTF2_SUCCESS](#) if successful, an error code if an error occurs.

J.30.3.11 `OTF2_ErrorCode OTF2_SnapWriter.MpiRecv (OTF2_SnapWriter * writer, OTF2_AttributeList * attributeList, OTF2_TimeStamp snapTime, OTF2_TimeStamp origEventTime, uint32_t sender, OTF2_CommRef communicator, uint32_t msgTag, uint64_t msgLength)`

Records an MpiRecv snapshot record.

This record exists for each [MpiRecv](#) event where the matching send message event did not occur on the remote location before the snapshot. This could either be an [MpiSend](#) or an [MpiIsendComplete](#) event. Or an [MpiRecvRequest](#) occurred before this event but the corresponding [MpiRecv](#) event did not occur before this snapshot. In this case the message matching couldn't performed yet, because the envelope of the ongoing [MpiRecvRequest](#) is not yet known.

Parameters

| | |
|----------------------|--|
| <i>writer</i> | Writer object. |
| <i>attributeList</i> | Generic attributes for the record. |
| <i>snapTime</i> | Snapshot time. |
| <i>origEventTime</i> | The original time this event happened. |
| <i>sender</i> | MPI rank of sender in <i>communicator</i> . |
| <i>communicator</i> | Communicator ID. References a Comm definition and will be mapped to the global definition if a mapping table of type OTF2_MAPPING_COMM is available. |
| <i>msgTag</i> | Message tag |
| <i>msgLength</i> | Message length |

Since

Version 1.2

Returns

[OTF2_SUCCESS](#) if successful, an error code if an error occurs.

APPENDIX J. FILE DOCUMENTATION

J.30.3.12 **OTF2_ErrorCode** **OTF2_SnapWriter_MpiSend** (**OTF2_SnapWriter** * *writer*, **OTF2_AttributeList** * *attributeList*, **OTF2_TimeStamp** *snapTime*, **OTF2_TimeStamp** *origEventTime*, **uint32_t** *receiver*, **OTF2_CommRef** *communicator*, **uint32_t** *msgTag*, **uint64_t** *msgLength*)

Records an MpiSend snapshot record.

This record exists for each *MpiSend* event where the matching receive message event did not occur on the remote location before the snapshot. This could either be an *MpiRecv* or an *MpiIrecv* event. Note that it may so, that a previous *MpiIrecv* with the same envelope than this one is neither completed not canceled yet, thus the matching receive may already occurred, but the matching couldn't be done yet.

Parameters

| | |
|----------------------|--|
| <i>writer</i> | Writer object. |
| <i>attributeList</i> | Generic attributes for the record. |
| <i>snapTime</i> | Snapshot time. |
| <i>origEventTime</i> | The original time this event happended. |
| <i>receiver</i> | MPI rank of receiver in <i>communicator</i> . |
| <i>communicator</i> | Communicator ID. References a Comm definition and will be mapped to the global definition if a mapping table of type OTF2_MAPPING_COMM is available. |
| <i>msgTag</i> | Message tag |
| <i>msgLength</i> | Message length |

Since

Version 1.2

Returns

[OTF2_SUCCESS](#) if successful, an error code if an error occurs.

J.30.3.13 **OTF2_ErrorCode** **OTF2_SnapWriter_OmpAcquireLock** (**OTF2_SnapWriter** * *writer*, **OTF2_AttributeList** * *attributeList*, **OTF2_TimeStamp** *snapTime*, **OTF2_TimeStamp** *origEventTime*, **uint32_t** *lockID*, **uint32_t** *acquisitionOrder*)

Records an OmpAcquireLock snapshot record.

This record exists for each *OmpAcquireLock* event where the corresponding *OmpReleaseLock* did not occurred before this snapshot yet.

J.30 OTF2_SnapWriter.h File Reference

Parameters

| | |
|-------------------------|---|
| <i>writer</i> | Writer object. |
| <i>attributeList</i> | Generic attributes for the record. |
| <i>snapTime</i> | Snapshot time. |
| <i>origEventTime</i> | The original time this event happened. |
| <i>lockID</i> | ID of the lock. |
| <i>acquisitionOrder</i> | A monotonically increasing number to determine the order of lock acquisitions (with unsynchronized clocks this is otherwise not possible). Corresponding acquire-release events have same number. |

Since

Version 1.2

Returns

[*OTF2_SUCCESS*](#) if successful, an error code if an error occurs.

J.30.3.14 `OTF2_StatusCode OTF2_SnapWriter_OmpFork (OTF2_SnapWriter * writer, OTF2_AttributeList * attributeList, OTF2_TimeStamp snapTime, OTF2_TimeStamp origEventTime, uint32_t numberOfRequestedThreads)`

Records an OmpFork snapshot record.

This record exists for each [*OmpFork*](#) event where the corresponding [*OmpJoin*](#) did not occurred before this snapshot.

Parameters

| | |
|---------------------------------|--|
| <i>writer</i> | Writer object. |
| <i>attributeList</i> | Generic attributes for the record. |
| <i>snapTime</i> | Snapshot time. |
| <i>origEventTime</i> | The original time this event happened. |
| <i>numberOfRequestedThreads</i> | Requested size of the team. |

Since

Version 1.2

APPENDIX J. FILE DOCUMENTATION

Returns

OTF2_SUCCESS if successful, an error code if an error occurs.

J.30.3.15 `OTF2_StatusCode OTF2.SnapWriter.OmpTaskCreate (OTF2_SnapWriter * writer, OTF2_AttributeList * attributeList, OTF2_TimeStamp snapTime, OTF2_TimeStamp origEventTime, uint64_t taskID)`

Records an OmpTaskCreate snapshot record.

This record exists for each *OmpTaskCreate* event where the corresponding *OmpTaskComplete* event did not occurred before this snapshot. Neither on this location nor on any other location in the current thread team.

Parameters

| | |
|----------------------|--|
| <i>writer</i> | Writer object. |
| <i>attributeList</i> | Generic attributes for the record. |
| <i>snapTime</i> | Snapshot time. |
| <i>origEventTime</i> | The original time this event happended. |
| <i>taskID</i> | Identifier of the newly created task instance. |

Since

Version 1.2

Returns

OTF2_SUCCESS if successful, an error code if an error occurs.

J.30.3.16 `OTF2_StatusCode OTF2.SnapWriter.OmpTaskSwitch (OTF2_SnapWriter * writer, OTF2_AttributeList * attributeList, OTF2_TimeStamp snapTime, OTF2_TimeStamp origEventTime, uint64_t taskID)`

Records an OmpTaskSwitch snapshot record.

This record exists for each *OmpTaskSwitch* event where the corresponding *OmpTaskComplete* event did not occurred before this snapshot. Neither on this location nor on any other location in the current thread team.

Parameters

| | |
|----------------------|------------------------------------|
| <i>writer</i> | Writer object. |
| <i>attributeList</i> | Generic attributes for the record. |

J.30 OTF2_SnapWriter.h File Reference

| | |
|-----------------------|---|
| <i>snapTime</i> | Snapshot time. |
| <i>origEvent-Time</i> | The original time this event happended. |
| <i>taskID</i> | Identifier of the now active task instance. |

Since

Version 1.2

Returns

[OTF2_SUCCESS](#) if successful, an error code if an error occurs.

J.30.3.17 `OTF2_StatusCode OTF2_SnapWriter_ParameterInt (OTF2_SnapWriter * writer, OTF2_AttributeList * attributeList, OTF2_TimeStamp snapTime, OTF2_TimeStamp origEventTime, OTF2_ParameterRef parameter, int64_t value)`

Records an ParameterInt snapshot record.

This record must be included in the snapshot until the leave event for the enter event occurs which has the greatest timestamp less or equal the timestamp of this record.

Parameters

| | |
|-----------------------|---|
| <i>writer</i> | Writer object. |
| <i>attributeList</i> | Generic attributes for the record. |
| <i>snapTime</i> | Snapshot time. |
| <i>origEvent-Time</i> | The original time this event happended. |
| <i>parameter</i> | Parameter ID. References a Parameter definition and will be mapped to the global definition if a mapping table of type OTF2_MAPPING_PARAMETER is available. |
| <i>value</i> | Value of the recorded parameter. |

Since

Version 1.2

Returns

[OTF2_SUCCESS](#) if successful, an error code if an error occurs.

APPENDIX J. FILE DOCUMENTATION

J.30.3.18 `OTF2_ErrorCode OTF2_SnapWriter_ParameterString (`
`OTF2_SnapWriter * writer, OTF2_AttributeList * attributeList,`
`OTF2_TimeStamp snapTime, OTF2_TimeStamp origEventTime,`
`OTF2_ParameterRef parameter, OTF2_StringRef string)`

Records an ParameterString snapshot record.

This record must be included in the snapshot until the leave event for the enter event occurs which has the greatest timestamp less or equal the timestamp of this record.

Parameters

| | |
|----------------------|--|
| <i>writer</i> | Writer object. |
| <i>attributeList</i> | Generic attributes for the record. |
| <i>snapTime</i> | Snapshot time. |
| <i>origEventTime</i> | The original time this event happened. |
| <i>parameter</i> | Parameter ID. References a Parameter definition and will be mapped to the global definition if a mapping table of type OTF2_MAPPING_PARAMETER is available. |
| <i>string</i> | Value: Handle of a string definition References a String definition and will be mapped to the global definition if a mapping table of type OTF2_MAPPING_STRING is available. |

Since

Version 1.2

Returns

[OTF2_SUCCESS](#) if successful, an error code if an error occurs.

J.30.3.19 `OTF2_ErrorCode OTF2_SnapWriter_ParameterUnsignedInt (`
`OTF2_SnapWriter * writer, OTF2_AttributeList * attributeList,`
`OTF2_TimeStamp snapTime, OTF2_TimeStamp origEventTime,`
`OTF2_ParameterRef parameter, uint64_t value)`

Records an ParameterUnsignedInt snapshot record.

This record must be included in the snapshot until the leave event for the enter event occurs which has the greatest timestamp less or equal the timestamp of this record.

Parameters

J.30 OTF2_SnapWriter.h File Reference

| | |
|-----------------------|--|
| <i>writer</i> | Writer object. |
| <i>attributeList</i> | Generic attributes for the record. |
| <i>snapTime</i> | Snapshot time. |
| <i>origEvent-Time</i> | The original time this event happened. |
| <i>parameter</i> | Parameter ID. References a Parameter definition and will be mapped to the global definition if a mapping table of type OTF2_MAPPING_-PARAMETER is available. |
| <i>value</i> | Value of the recorded parameter. |

Since

Version 1.2

Returns

[OTF2_SUCCESS](#) if successful, an error code if an error occurs.

J.30.3.20 `OTF2_StatusCode OTF2_SnapWriter_SnapshotEnd (OTF2_SnapWriter * writer, OTF2_AttributeList * attributeList, OTF2_TimeStamp snapTime, uint64_t contReadPos)`

Records an SnapshotEnd snapshot record.

This record marks the end of a snapshot. It contains the position to continue reading in the event trace for this location. Use [OTF2_EvtReader_Seek](#) with *contReadPos* as the position.

Parameters

| | |
|----------------------|--|
| <i>writer</i> | Writer object. |
| <i>attributeList</i> | Generic attributes for the record. |
| <i>snapTime</i> | Snapshot time. |
| <i>contRead-Pos</i> | Position to continue reading in the event trace. |

Since

Version 1.2

Returns

[OTF2_SUCCESS](#) if successful, an error code if an error occurs.

J.30.3.21 `OTF2_ErrorCode` `OTF2_SnapWriter_SnapshotStart` (`OTF2_SnapWriter` * `writer`, `OTF2_AttributeList` * `attributeList`, `OTF2_TimeStamp` `snapTime`, `uint64_t` `numberOfRecords`)

Records an `SnapshotStart` snapshot record.

This record marks the start of a snapshot.

A snapshot consists of an timestamp and a set of snapshot records. All these snapshot records have the same snapshot time. A snapshot starts with one *SnapshotStart* record and closes with one *SnapshotEnd* record. All snapshot records inbetween are ordered by the *origEventTime*, which are also less than the snapshot timestamp. Ie. The timestamp of the next event read from the event stream is greater or equal to the snapshot time.

Parameters

| | |
|-----------------------|---|
| <i>writer</i> | Writer object. |
| <i>attributeList</i> | Generic attributes for the record. |
| <i>snapTime</i> | Snapshot time. |
| <i>numberOfRecord</i> | Number of snapshot event records in this snapshot. Excluding the <i>SnapshotEnd</i> record. |

Since

Version 1.2

Returns

OTF2_SUCCESS if successful, an error code if an error occurs.

J.31 OTF2_Thumbnail.h File Reference

This lowest user-visible layer provides write routines to read and write thumbnail data.

```
#include <stdint.h>
#include <otf2/OTF2_GeneralDefinitions.h>
```

Typedefs

- typedef struct `OTF2_ThumbReader_struct` `OTF2_ThumbReader`
Keeps all necessary information about the event reader. See OTF2_ThumbReader_struct for detailed information.

J.31 OTF2_Thumbnail.h File Reference

- typedef struct OTF2_ThumbWriter_struct [OTF2_ThumbWriter](#)
Keeps all necessary information about the thumb writer. See OTF2_ThumbWriter_struct for detailed information.

Functions

- [OTF2_ErrorCode](#) [OTF2_ThumbReader_GetHeader](#) ([OTF2_ThumbReader](#) *reader, char **const name, char **const description, [OTF2_ThumbnailType](#) *type, uint32_t *numberOfSamples, uint32_t *numberOfMetrics, uint64_t **refsToDefs)

Reads a thumbnail header.

- [OTF2_ErrorCode](#) [OTF2_ThumbReader_ReadSample](#) ([OTF2_ThumbReader](#) *reader, uint64_t *baseline, uint32_t numberOfMetrics, uint64_t *metricSamples)

Reads a thumbnail sample.

- [OTF2_ErrorCode](#) [OTF2_ThumbWriter_WriteSample](#) ([OTF2_ThumbWriter](#) *writer, uint64_t baseline, uint32_t numberOfMetrics, const uint64_t *metricSamples)

Writes a thumbnail sample.

J.31.1 Detailed Description

This lowest user-visible layer provides write routines to read and write thumbnail data.

J.31.2 Function Documentation

J.31.2.1 [OTF2_ErrorCode](#) [OTF2_ThumbReader_GetHeader](#) ([OTF2_ThumbReader](#) * reader, char **const name, char **const description, [OTF2_ThumbnailType](#) * type, uint32_t * numberOfSamples, uint32_t * numberOfMetrics, uint64_t ** refsToDefs)

Reads a thumbnail header.

A thumbnail header contains some meta information for a thumbnail.

Parameters

| | |
|---------------|----------------|
| <i>reader</i> | Reader object. |
|---------------|----------------|

APPENDIX J. FILE DOCUMENTATION

| | |
|------------------------|---------------------------|
| <i>name</i> | Name of thumbnail. |
| <i>description</i> | Description of thumbnail. |
| <i>type</i> | Type of thumbnail. |
| <i>numberOfSamples</i> | Number of samples. |
| <i>numberOfMetrics</i> | Number of metrics. |

Since

Version 1.2

Returns

[*OTF2_SUCCESS*](#) if successful, an error code if an error occurs.

J.31.2.2 OTF2_ErrorCode OTF2_ThumbReader_ReadSample (
OTF2_ThumbReader * reader, uint64_t * baseline, uint32_t
numberOfMetrics, uint64_t * metricSamples)

Reads a thumbnail sample.

Parameters

| | |
|------------------------|---|
| <i>reader</i> | Reader object. |
| <i>baseline</i> | Baseline for this sample. If zero, the baseline is the sum of all metric values in this sample. |
| <i>numberOfMetrics</i> | Number of metric sample values. |
| <i>metricSamples</i> | Metric sample values. |

Since

Version 1.2

Returns

[*OTF2_SUCCESS*](#) if successful, an error code if an error occurs.

J.31 OTF2_Thumbnail.h File Reference

J.31.2.3 `OTF2_ErrorCode OTF2_ThumbWriter_WriteSample (`
`OTF2_ThumbWriter * writer, uint64.t baseline, uint32.t numberOfMetrics,`
`const uint64.t * metricSamples)`

Writes a thumbnail sample.

Parameters

| | |
|------------------------|---|
| <i>writer</i> | Writer object. |
| <i>baseline</i> | Baseline for this sample. If zero, the baseline is the sum of all metric values in this sample. |
| <i>numberOfMetrics</i> | Number of metric sample values. |
| <i>metricSamples</i> | Metric sample values. |

Since

Version 1.2

Returns

[*OTF2_SUCCESS*](#) if successful, an error code if an error occurs.

Index

- otf2.h, [95](#)
- OTF2_ABORT
 - OTF2_ErrorCodes.h, [225](#)
- OTF2_Archive.h
 - OTF2_MASTER, [103](#)
 - OTF2_SLAVE, [103](#)
- OTF2_BASE_BINARY
 - OTF2_Definitions.h, [165](#)
- OTF2_BASE_DECIMAL
 - OTF2_Definitions.h, [165](#)
- OTF2_CALLBACK_INTERRUPT
 - OTF2_GeneralDefinitions.h, [372](#)
- OTF2_CALLBACK_SUCCESS
 - OTF2_GeneralDefinitions.h, [372](#)
- OTF2_COLLECTIVE_OP_ALLOCATE
 - OTF2_Events.h, [232](#)
- OTF2_COLLECTIVE_OP_CREATE_HANDLE
 - OTF2_Events.h, [232](#)
- OTF2_COLLECTIVE_OP_CREATE_HANDLE_AND_ALLOCATE
 - OTF2_Events.h, [232](#)
- OTF2_COLLECTIVE_OP_DEALLOCATE
 - OTF2_Events.h, [232](#)
- OTF2_COLLECTIVE_OP_DESTROY_HANDLE
 - OTF2_Events.h, [232](#)
- OTF2_COLLECTIVE_OP_DESTROY_HANDLE_AND_DEALLOCATE
 - OTF2_Events.h, [232](#)
- OTF2_COMPRESSION_NONE
 - OTF2_GeneralDefinitions.h, [372](#)
- OTF2_COMPRESSION_UNDEFINED
 - OTF2_GeneralDefinitions.h, [372](#)
- OTF2_COMPRESSION_ZLIB
 - OTF2_GeneralDefinitions.h, [372](#)
- OTF2_Definitions.h
- OTF2_BASE_BINARY, [165](#)
- OTF2_BASE_DECIMAL, [165](#)
- OTF2_GROUP_FLAG_GLOBAL_MEMBERS, [164](#)
- OTF2_GROUP_FLAG_NONE, [164](#)
- OTF2_GROUP_TYPE_COMM_GROUP, [164](#)
- OTF2_GROUP_TYPE_COMM_LOCATIONS, [164](#)
- OTF2_GROUP_TYPE_COMM_SELF, [164](#)
- OTF2_GROUP_TYPE_LOCATIONS, [164](#)
- OTF2_GROUP_TYPE_METRIC, [164](#)
- OTF2_GROUP_TYPE_REGIONS, [164](#)
- OTF2_GROUP_TYPE_UNKNOWN, [164](#)
- OTF2_LOCATION_GROUP_TYPE_PROCESS, [165](#)
- OTF2_LOCATION_GROUP_TYPE_UNKNOWN, [165](#)
- OTF2_LOCATION_TYPE_CPU_THREAD, [165](#)
- OTF2_LOCATION_TYPE_GPU, [165](#)
- OTF2_LOCATION_TYPE_METRIC, [165](#)
- OTF2_LOCATION_TYPE_UNKNOWN, [165](#)
- OTF2_METRIC_ABSOLUTE_LAST, [166](#)
- OTF2_METRIC_ABSOLUTE_NEXT, [166](#)
- OTF2_METRIC_ABSOLUTE_POINT, [166](#)

INDEX

- OTF2_METRIC_ACCUMULATED_-LAST, [166](#)
- OTF2_METRIC_ACCUMULATED_-NEXT, [166](#)
- OTF2_METRIC_ACCUMULATED_-POINT, [166](#)
- OTF2_METRIC_ACCUMULATED_-START, [166](#)
- OTF2_METRIC_ASYNCHRONOUS, [166](#)
- OTF2_METRIC_RELATIVE_LAST, [166](#)
- OTF2_METRIC_RELATIVE_NEXT, [166](#)
- OTF2_METRIC_RELATIVE_POINT, [166](#)
- OTF2_METRIC_SYNCHRONOUS, [166](#)
- OTF2_METRIC_SYNCHRONOUS_-STRICT, [166](#)
- OTF2_METRIC_TIMING_LAST, [167](#)
- OTF2_METRIC_TIMING_MASK, [167](#)
- OTF2_METRIC_TIMING_NEXT, [167](#)
- OTF2_METRIC_TIMING_POINT, [167](#)
- OTF2_METRIC_TIMING_START, [167](#)
- OTF2_METRIC_TYPE_OTHER, [168](#)
- OTF2_METRIC_TYPE_PAPI, [168](#)
- OTF2_METRIC_TYPE_RUSAGE, [168](#)
- OTF2_METRIC_TYPE_USER, [168](#)
- OTF2_METRIC_VALUE_ABSOLUTE, [168](#)
- OTF2_METRIC_VALUE_ACCUMULATED, [168](#)
- OTF2_METRIC_VALUE_MASK, [168](#)
- OTF2_METRIC_VALUE_RELATIVE, [168](#)
- OTF2_PARAMETER_TYPE_INT64, [169](#)
- OTF2_PARAMETER_TYPE_STRING, [169](#)
- OTF2_PARAMETER_TYPE_UINT64, [169](#)
- OTF2_RECORDER_KIND_ABSTRACT, [169](#)
- OTF2_RECORDER_KIND_CPU, [169](#)
- OTF2_RECORDER_KIND_GPU, [169](#)
- OTF2_RECORDER_KIND_UNKNOWN, [169](#)
- OTF2_REGION_FLAG_DYNAMIC, [169](#)
- OTF2_REGION_FLAG_NONE, [169](#)
- OTF2_REGION_FLAG_PHASE, [169](#)
- OTF2_REGION_ROLE_ARTIFICIAL, [171](#)
- OTF2_REGION_ROLE_ATOMIC, [170](#)
- OTF2_REGION_ROLE_BARRIER, [170](#)
- OTF2_REGION_ROLE_CODE, [170](#)
- OTF2_REGION_ROLE_COLL_ALL2ALL, [171](#)
- OTF2_REGION_ROLE_COLL_ALL2ONE, [171](#)
- OTF2_REGION_ROLE_COLL_ONE2ALL, [171](#)
- OTF2_REGION_ROLE_COLL_OTHER, [171](#)
- OTF2_REGION_ROLE_CRITICAL, [170](#)
- OTF2_REGION_ROLE_CRITICAL_-SBLOCK, [170](#)
- OTF2_REGION_ROLE_DATA_TRANSFER, [171](#)
- OTF2_REGION_ROLE_FILE_IO, [171](#)
- OTF2_REGION_ROLE_FLUSH, [170](#)
- OTF2_REGION_ROLE_FUNCTION, [170](#)
- OTF2_REGION_ROLE_IMPLICIT_-BARRIER, [170](#)
- OTF2_REGION_ROLE_LOOP, [170](#)
- OTF2_REGION_ROLE_MASTER, [170](#)
- OTF2_REGION_ROLE_ORDERED, [170](#)

OTF2_REGION_ROLE_ORDERED_- SBLOCK, [170](#) OTF2_SYSTEM_TREE_DOMAIN_- SOCKET, [171](#)
 OTF2_REGION_ROLE_PARALLEL_ OTF2_DEPRECATED
[170](#) OTF2_ErrorCodes.h, [225](#)
 OTF2_REGION_ROLE_POINT2POINT_ OTF2_ERROR_DUPLICATE_MAPPING_-
[171](#) TABLE
 OTF2_REGION_ROLE_RMA, [171](#) OTF2_ErrorCodes.h, [228](#)
 OTF2_REGION_ROLE_SECTION, OTF2_ERROR_E2BIG
[170](#) OTF2_ErrorCodes.h, [225](#)
 OTF2_REGION_ROLE_SECTIONS, OTF2_ERROR_EACCES
[170](#) OTF2_ErrorCodes.h, [225](#)
 OTF2_REGION_ROLE_SINGLE, [170](#) OTF2_ERROR_EADDRNOTAVAIL
 OTF2_REGION_ROLE_SINGLE_- OTF2_ErrorCodes.h, [225](#)
 SBLOCK, [170](#) OTF2_ERROR_EAFNOSUPPORT
 OTF2_REGION_ROLE_TASK, [170](#) OTF2_ErrorCodes.h, [225](#)
 OTF2_REGION_ROLE_TASK_CREATE, OTF2_ERROR_EAGAIN
[170](#) OTF2_ErrorCodes.h, [225](#)
 OTF2_REGION_ROLE_TASK_WAIT, OTF2_ERROR_EALREADY
[170](#) OTF2_ErrorCodes.h, [225](#)
 OTF2_REGION_ROLE_UNKNOWN, OTF2_ERROR_EBADF
[170](#) OTF2_ErrorCodes.h, [225](#)
 OTF2_REGION_ROLE_WORKSHARE, OTF2_ERROR_EBADMSG
[170](#) OTF2_ErrorCodes.h, [225](#)
 OTF2_REGION_ROLE_WRAPPER, OTF2_ERROR_EBUSY
[170](#) OTF2_ErrorCodes.h, [225](#)
 OTF2_SCOPE_GROUP, [167](#) OTF2_ERROR_ECANCELED
 OTF2_SCOPE_LOCATION, [167](#) OTF2_ErrorCodes.h, [225](#)
 OTF2_SCOPE_LOCATION_GROUP, OTF2_ERROR_ECHILD
[167](#) OTF2_ErrorCodes.h, [225](#)
 OTF2_SCOPE_SYSTEM_TREE_- OTF2_ERROR_ECONNREFUSED
 NODE, [167](#) OTF2_ErrorCodes.h, [225](#)
 OTF2_SYSTEM_TREE_DOMAIN_- OTF2_ERROR_ECONNRESET
 CACHE, [171](#) OTF2_ErrorCodes.h, [225](#)
 OTF2_SYSTEM_TREE_DOMAIN_- OTF2_ERROR_EDEADLK
 CORE, [172](#) OTF2_ErrorCodes.h, [225](#)
 OTF2_SYSTEM_TREE_DOMAIN_- OTF2_ERROR_EDESTADDRREQ
 MACHINE, [171](#) OTF2_ErrorCodes.h, [225](#)
 OTF2_SYSTEM_TREE_DOMAIN_- OTF2_ERROR_EDOM
 NUMA, [171](#) OTF2_ErrorCodes.h, [225](#)
 OTF2_SYSTEM_TREE_DOMAIN_- OTF2_ERROR_EDQUOT
 PU, [172](#) OTF2_ErrorCodes.h, [225](#)
 OTF2_SYSTEM_TREE_DOMAIN_- OTF2_ERROR_EEXIST
 SHARED_MEMORY, [171](#) OTF2_ErrorCodes.h, [225](#)
 OTF2_ERROR_EFAULT

INDEX

OTF2_ErrorCodes.h, [225](#)
OTF2_ERROR_EFBIG
OTF2_ErrorCodes.h, [226](#)
OTF2_ERROR_EINPROGRESS
OTF2_ErrorCodes.h, [226](#)
OTF2_ERROR_EINTR
OTF2_ErrorCodes.h, [226](#)
OTF2_ERROR_EINVAL
OTF2_ErrorCodes.h, [226](#)
OTF2_ERROR_EIO
OTF2_ErrorCodes.h, [226](#)
OTF2_ERROR_EISCONN
OTF2_ErrorCodes.h, [226](#)
OTF2_ERROR_EISDIR
OTF2_ErrorCodes.h, [226](#)
OTF2_ERROR_ELOOP
OTF2_ErrorCodes.h, [226](#)
OTF2_ERROR_EMFILE
OTF2_ErrorCodes.h, [226](#)
OTF2_ERROR_EMLINK
OTF2_ErrorCodes.h, [226](#)
OTF2_ERROR_MSGSIZE
OTF2_ErrorCodes.h, [226](#)
OTF2_ERROR_EMULTIHOP
OTF2_ErrorCodes.h, [226](#)
OTF2_ERROR_ENAMETOOLONG
OTF2_ErrorCodes.h, [226](#)
OTF2_ERROR_END_OF_BUFFER
OTF2_ErrorCodes.h, [228](#)
OTF2_ERROR_END_OF_FUNCTION
OTF2_ErrorCodes.h, [227](#)
OTF2_ERROR_ENETDOWN
OTF2_ErrorCodes.h, [226](#)
OTF2_ERROR_ENETRESET
OTF2_ErrorCodes.h, [226](#)
OTF2_ERROR_ENETUNREACH
OTF2_ErrorCodes.h, [226](#)
OTF2_ERROR_ENFILE
OTF2_ErrorCodes.h, [226](#)
OTF2_ERROR_ENOBUFS
OTF2_ErrorCodes.h, [226](#)
OTF2_ERROR_ENODATA
OTF2_ErrorCodes.h, [226](#)
OTF2_ERROR_ENODEV
OTF2_ErrorCodes.h, [226](#)
OTF2_ERROR_ENOENT
OTF2_ErrorCodes.h, [226](#)
OTF2_ERROR_ENOEXEC
OTF2_ErrorCodes.h, [226](#)
OTF2_ERROR_ENOLCK
OTF2_ErrorCodes.h, [226](#)
OTF2_ERROR_ENOLINK
OTF2_ErrorCodes.h, [226](#)
OTF2_ERROR_ENOMEM
OTF2_ErrorCodes.h, [226](#)
OTF2_ERROR_ENOMSG
OTF2_ErrorCodes.h, [226](#)
OTF2_ERROR_ENOPROTOOPT
OTF2_ErrorCodes.h, [226](#)
OTF2_ERROR_ENOSPC
OTF2_ErrorCodes.h, [226](#)
OTF2_ERROR_ENOSR
OTF2_ErrorCodes.h, [226](#)
OTF2_ERROR_ENOSTR
OTF2_ErrorCodes.h, [226](#)
OTF2_ERROR_ENOSYS
OTF2_ErrorCodes.h, [226](#)
OTF2_ERROR_ENOTCONN
OTF2_ErrorCodes.h, [226](#)
OTF2_ERROR_ENOTDIR
OTF2_ErrorCodes.h, [226](#)
OTF2_ERROR_ENOTEMPTY
OTF2_ErrorCodes.h, [226](#)
OTF2_ERROR_ENOTSOCK
OTF2_ErrorCodes.h, [227](#)
OTF2_ERROR_ENOTSUP
OTF2_ErrorCodes.h, [227](#)
OTF2_ERROR_ENOTTY
OTF2_ErrorCodes.h, [227](#)
OTF2_ERROR_ENXIO
OTF2_ErrorCodes.h, [227](#)
OTF2_ERROR_EOPNOTSUPP
OTF2_ErrorCodes.h, [227](#)
OTF2_ERROR_EOVERFLOW
OTF2_ErrorCodes.h, [227](#)
OTF2_ERROR_EPERM
OTF2_ErrorCodes.h, [227](#)
OTF2_ERROR_EPIPE

| | |
|---|---|
| <p>OTF2_ErrorCodes.h, 227</p> <p>OTF2_ERROR_EPROTO OTF2_ErrorCodes.h, 227</p> <p>OTF2_ERROR_EPROTONOSUPPORT OTF2_ErrorCodes.h, 227</p> <p>OTF2_ERROR_EPROTOTYPE OTF2_ErrorCodes.h, 227</p> <p>OTF2_ERROR_ERANGE OTF2_ErrorCodes.h, 227</p> <p>OTF2_ERROR_EROFS OTF2_ErrorCodes.h, 227</p> <p>OTF2_ERROR_ESPIPE OTF2_ErrorCodes.h, 227</p> <p>OTF2_ERROR_ESRCH OTF2_ErrorCodes.h, 227</p> <p>OTF2_ERROR_ESTALE OTF2_ErrorCodes.h, 227</p> <p>OTF2_ERROR_ETIME OTF2_ErrorCodes.h, 227</p> <p>OTF2_ERROR_ETIMEDOUT OTF2_ErrorCodes.h, 227</p> <p>OTF2_ERROR_ETXTBSY OTF2_ErrorCodes.h, 227</p> <p>OTF2_ERROR_EWOULDBLOCK OTF2_ErrorCodes.h, 227</p> <p>OTF2_ERROR_EXDEV OTF2_ErrorCodes.h, 227</p> <p>OTF2_ERROR_FILE_CAN_NOT_OPEN OTF2_ErrorCodes.h, 228</p> <p>OTF2_ERROR_FILE_COMPRESSION_- NOT_SUPPORTED OTF2_ErrorCodes.h, 228</p> <p>OTF2_ERROR_FILE_INTERACTION OTF2_ErrorCodes.h, 228</p> <p>OTF2_ERROR_INDEX_OUT_OF_BOUNDS OTF2_ErrorCodes.h, 228</p> <p>OTF2_ERROR_INTEGRITY_FAULT OTF2_ErrorCodes.h, 227</p> <p>OTF2_ERROR_INTERRUPTED_BY_- CALLBACK OTF2_ErrorCodes.h, 228</p> <p>OTF2_ERROR_INVALID OTF2_ErrorCodes.h, 225</p> <p>OTF2_ERROR_INVALID_ARGUMENT</p> | <p>OTF2_ErrorCodes.h, 227</p> <p>OTF2_ERROR_INVALID_CALL OTF2_ErrorCodes.h, 227</p> <p>OTF2_ERROR_INVALID_DATA OTF2_ErrorCodes.h, 227</p> <p>OTF2_ERROR_INVALID_FILE_MODE_- TRANSITION OTF2_ErrorCodes.h, 228</p> <p>OTF2_ERROR_INVALID_LINENO OTF2_ErrorCodes.h, 228</p> <p>OTF2_ERROR_INVALID_RECORD OTF2_ErrorCodes.h, 227</p> <p>OTF2_ERROR_INVALID_SIZE_GIVEN OTF2_ErrorCodes.h, 227</p> <p>OTF2_ERROR_MEM_ALLOC_FAILED OTF2_ErrorCodes.h, 227</p> <p>OTF2_ERROR_MEM_FAULT OTF2_ErrorCodes.h, 227</p> <p>OTF2_ERROR_PROCESSED_WITH_- FAULTS OTF2_ErrorCodes.h, 227</p> <p>OTF2_ERROR_PROPERTY_EXISTS OTF2_ErrorCodes.h, 228</p> <p>OTF2_ERROR_PROPERTY_NAME_INVALID OTF2_ErrorCodes.h, 228</p> <p>OTF2_ERROR_PROPERTY_NOT_FOUND OTF2_ErrorCodes.h, 228</p> <p>OTF2_ERROR_PROPERTY_VALUE_- INVALID OTF2_ErrorCodes.h, 228</p> <p>OTF2_ERROR_UNKNOWN_TYPE OTF2_ErrorCodes.h, 227</p> <p>OTF2_ABORT, 225</p> <p>OTF2_DEPRECATED, 225</p> <p>OTF2_ERROR_DUPLICATE_MAPPING_- TABLE, 228</p> <p>OTF2_ERROR_E2BIG, 225</p> <p>OTF2_ERROR_EACCES, 225</p> <p>OTF2_ERROR_EADDRNOTAVAIL, 225</p> <p>OTF2_ERROR_EAFNOSUPPORT, 225</p> <p>OTF2_ERROR_EAGAIN, 225</p> |
|---|---|

INDEX

OTF2_ERROR_EALREADY, 225
OTF2_ERROR_EBADF, 225
OTF2_ERROR_EBADMSG, 225
OTF2_ERROR_EBUSY, 225
OTF2_ERROR_ECANCELED, 225
OTF2_ERROR_ECHILD, 225
OTF2_ERROR_ECONNREFUSED,
225
OTF2_ERROR_ECONNRESET, 225
OTF2_ERROR_EDEADLK, 225
OTF2_ERROR_EDESTADDRREQ,
225
OTF2_ERROR_EDOM, 225
OTF2_ERROR_EDQUOT, 225
OTF2_ERROR_EEXIST, 225
OTF2_ERROR_EFAULT, 225
OTF2_ERROR_EFBIG, 226
OTF2_ERROR_EINPROGRESS, 226
OTF2_ERROR_EINTR, 226
OTF2_ERROR_EINVAL, 226
OTF2_ERROR_EIO, 226
OTF2_ERROR_EISCONN, 226
OTF2_ERROR_EISDIR, 226
OTF2_ERROR_ELOOP, 226
OTF2_ERROR_EMFILE, 226
OTF2_ERROR_EMLINK, 226
OTF2_ERROR_EMMSGSIZE, 226
OTF2_ERROR_EMULTIHOP, 226
OTF2_ERROR_ENAMETOOLONG,
226
OTF2_ERROR_END_OF_BUFFER,
228
OTF2_ERROR_END_OF_FUNCTION,
227
OTF2_ERROR_ENETDOWN, 226
OTF2_ERROR_ENETRESET, 226
OTF2_ERROR_ENETUNREACH,
226
OTF2_ERROR_ENFILE, 226
OTF2_ERROR_ENOBUFS, 226
OTF2_ERROR_ENODATA, 226
OTF2_ERROR_ENODEV, 226
OTF2_ERROR_ENOENT, 226
OTF2_ERROR_ENOEXEC, 226
OTF2_ERROR_ENOLCK, 226
OTF2_ERROR_ENOLINK, 226
OTF2_ERROR_ENOMEM, 226
OTF2_ERROR_ENOMSG, 226
OTF2_ERROR_ENOPROTOPT, 226
OTF2_ERROR_ENOSPC, 226
OTF2_ERROR_ENOSR, 226
OTF2_ERROR_ENOSTR, 226
OTF2_ERROR_ENOSYS, 226
OTF2_ERROR_ENOTCONN, 226
OTF2_ERROR_ENOTDIR, 226
OTF2_ERROR_ENOTEMPTY, 226
OTF2_ERROR_ENOTSOCK, 227
OTF2_ERROR_ENOTSUP, 227
OTF2_ERROR_ENOTTY, 227
OTF2_ERROR_ENXIO, 227
OTF2_ERROR_EOPNOTSUPP, 227
OTF2_ERROR_EOVERFLOW, 227
OTF2_ERROR_EPERM, 227
OTF2_ERROR_EPIPE, 227
OTF2_ERROR_EPROTO, 227
OTF2_ERROR_EPROTONOSUPPORT,
227
OTF2_ERROR_EPROTOTYPE, 227
OTF2_ERROR_ERANGE, 227
OTF2_ERROR_EROFS, 227
OTF2_ERROR_ESPIPE, 227
OTF2_ERROR_ESRCH, 227
OTF2_ERROR_ESTALE, 227
OTF2_ERROR_ETIME, 227
OTF2_ERROR_ETIMEDOUT, 227
OTF2_ERROR_ETXTBSY, 227
OTF2_ERROR_EWOULDBLOCK,
227
OTF2_ERROR_EXDEV, 227
OTF2_ERROR_FILE_CAN_NOT_-
OPEN, 228
OTF2_ERROR_FILE_COMPRESSION_-
NOT_SUPPORTED, 228
OTF2_ERROR_FILE_INTERACTION,
228
OTF2_ERROR_INDEX_OUT_OF_-
BOUNDS, 228

OTF2_ERROR_INTEGRITY_FAULT, 227
 OTF2_ERROR_INTERRUPTED_-
 BY_CALLBACK, 228
 OTF2_ERROR_INVALID, 225
 OTF2_ERROR_INVALID_ARGUMENT, 227
 OTF2_ERROR_INVALID_CALL, 227
 OTF2_ERROR_INVALID_DATA, 227
 OTF2_ERROR_INVALID_FILE_MODE,
 TRANSITION, 228
 OTF2_ERROR_INVALID_LINENO,
 228
 OTF2_ERROR_INVALID_RECORD,
 227
 OTF2_ERROR_INVALID_SIZE_GIVEN,
 227
 OTF2_ERROR_MEM_ALLOC_FAILED,
 227
 OTF2_ERROR_MEM_FAULT, 227
 OTF2_ERROR_PROCESSED_WITH_-
 FAULTS, 227
 OTF2_ERROR_PROPERTY_EXISTS,
 228
 OTF2_ERROR_PROPERTY_NAME_-
 INVALID, 228
 OTF2_ERROR_PROPERTY_NOT_-
 FOUND, 228
 OTF2_ERROR_PROPERTY_VALUE_-
 INVALID, 228
 OTF2_ERROR_UNKNOWN_TYPE,
 227
 OTF2_SUCCESS, 225
 OTF2_WARNING, 225
 OTF2_Events.h
 OTF2_COLLECTIVE_OP_ALLOCATE,
 232
 OTF2_COLLECTIVE_OP_CREATE_
 HANDLE, 232
 OTF2_COLLECTIVE_OP_CREATE_
 HANDLE_AND_ALLOCATE,
 232
 OTF2_COLLECTIVE_OP_DEALLOCATE,
 232
 OTF2_COLLECTIVE_OP_DESTROY_-
 HANDLE, 232
 OTF2_COLLECTIVE_OP_DESTROY_-
 HANDLE_AND_DEALLOCATE,
 232
 OTF2_LOCK_EXCLUSIVE, 232
 OTF2_LOCK_SHARED, 232
 OTF2_MEASUREMENT_OFF, 233
 OTF2_MEASUREMENT_ON, 233
 OTF2_RMA_SYNC_LEVEL_MEMORY,
 233
 OTF2_RMA_SYNC_LEVEL_NONE,
 233
 OTF2_RMA_SYNC_LEVEL_PROCESS,
 233
 OTF2_RMA_SYNC_TYPE_MEMORY,
 234
 OTF2_RMA_SYNC_TYPE_NOTIFY_-
 IN, 234
 OTF2_RMA_SYNC_TYPE_NOTIFY_-
 OUT, 234
 OTF2_FILEMODE_MODIFY
 OTF2_FileModeRead.h, 372
 OTF2_FILEMODE_READ
 OTF2_FileModeWrite.h, 372
 OTF2_FILEMODE_WRITE
 OTF2_FileTypeAnchor.h, 372
 OTF2_FILETYPE_ANCHOR
 OTF2_FileTypeEvents.h, 373
 OTF2_FILETYPE_EVENTS
 OTF2_FileTypeGlobalDefs.h, 373
 OTF2_FILETYPE_GLOBAL_DEFS
 OTF2_FileTypeLocalDefs.h, 373
 OTF2_FILETYPE_LOCAL_DEFS
 OTF2_FileTypeMarker.h, 373
 OTF2_FILETYPE_MARKER
 OTF2_FileTypeSnapshots.h, 373
 OTF2_FILETYPE_SNAPSHOTS
 OTF2_FileTypeThumbnail.h, 373
 OTF2_FILETYPE_THUMBNAIL
 OTF2_Flush.h, 373
 OTF2_FLUSH
 OTF2_GeneralDefinitions.h, 373
 OTF2_GeneralDefinitions.h

INDEX

- OTF2_CALLBACK_INTERRUPT, [372](#)
- OTF2_CALLBACK_SUCCESS, [372](#)
- OTF2_COMPRESSION_NONE, [372](#)
- OTF2_COMPRESSION_UNDEFINED, [372](#)
- OTF2_COMPRESSION_ZLIB, [372](#)
- OTF2_FILEMODE_MODIFY, [372](#)
- OTF2_FILEMODE_READ, [372](#)
- OTF2_FILEMODE_WRITE, [372](#)
- OTF2_FILETYPE_ANCHOR, [373](#)
- OTF2_FILETYPE_EVENTS, [373](#)
- OTF2_FILETYPE_GLOBAL_DEFS, [373](#)
- OTF2_FILETYPE_LOCAL_DEFS, [373](#)
- OTF2_FILETYPE_MARKER, [373](#)
- OTF2_FILETYPE_SNAPSHOTS, [373](#)
- OTF2_FILETYPE_THUMBNAIL, [373](#)
- OTF2_FLUSH, [373](#)
- OTF2_MAPPING_ATTRIBUTE, [374](#)
- OTF2_MAPPING_COMM, [374](#)
- OTF2_MAPPING_GROUP, [374](#)
- OTF2_MAPPING_LOCATION, [374](#)
- OTF2_MAPPING_MAX, [374](#)
- OTF2_MAPPING_METRIC, [374](#)
- OTF2_MAPPING_PARAMETER, [374](#)
- OTF2_MAPPING_REGION, [374](#)
- OTF2_MAPPING_RMA_WIN, [374](#)
- OTF2_MAPPING_STRING, [374](#)
- OTF2_NO_FLUSH, [373](#)
- OTF2_PARADIGM_COMPILER, [374](#)
- OTF2_PARADIGM_CUDA, [374](#)
- OTF2_PARADIGM_MEASUREMENT_SYSTEM, [374](#)
- OTF2_PARADIGM_MPI, [374](#)
- OTF2_PARADIGM_OPENMP, [374](#)
- OTF2_PARADIGM_UNKNOWN, [374](#)
- OTF2_PARADIGM_USER, [374](#)
- OTF2_SUBSTRATE_NONE, [373](#)
- OTF2_SUBSTRATE_POSIX, [372](#)
- OTF2_SUBSTRATE_SION, [373](#)
- OTF2_SUBSTRATE_UNDEFINED, [372](#)
- OTF2_THUMBNAIL_TYPE_ATTRIBUTES, [375](#)
- OTF2_THUMBNAIL_TYPE_METRIC, [375](#)
- OTF2_THUMBNAIL_TYPE_REGION, [375](#)
- OTF2_TYPE_DOUBLE, [375](#)
- OTF2_TYPE_FLOAT, [375](#)
- OTF2_TYPE_INT16, [375](#)
- OTF2_TYPE_INT32, [375](#)
- OTF2_TYPE_INT64, [375](#)
- OTF2_TYPE_INT8, [375](#)
- OTF2_TYPE_NONE, [375](#)
- OTF2_TYPE_UINT16, [375](#)
- OTF2_TYPE_UINT32, [375](#)
- OTF2_TYPE_UINT64, [375](#)
- OTF2_TYPE_UINT8, [375](#)
- OTF2_GROUP_FLAG_GLOBAL_MEMBERS
OTF2_Definitions.h, [164](#)
- OTF2_GROUP_FLAG_NONE
OTF2_Definitions.h, [164](#)
- OTF2_GROUP_TYPE_COMM_GROUP
OTF2_Definitions.h, [164](#)
- OTF2_GROUP_TYPE_COMM_LOCATIONS
OTF2_Definitions.h, [164](#)
- OTF2_GROUP_TYPE_COMM_SELF
OTF2_Definitions.h, [164](#)
- OTF2_GROUP_TYPE_LOCATIONS
OTF2_Definitions.h, [164](#)
- OTF2_GROUP_TYPE_METRIC
OTF2_Definitions.h, [164](#)
- OTF2_GROUP_TYPE_REGIONS
OTF2_Definitions.h, [164](#)
- OTF2_GROUP_TYPE_UNKNOWN
OTF2_Definitions.h, [164](#)
- OTF2_ID_MAP_DENSE
OTF2_IdMap.h, [546](#)
- OTF2_ID_MAP_SPARSE
OTF2_IdMap.h, [546](#)
- OTF2_IdMap.h
- OTF2_ID_MAP_DENSE, [546](#)
- OTF2_ID_MAP_SPARSE, [546](#)

OTF2_LOCATION_GROUP_TYPE_PROCESSOR, OTF2_MARKER_SCOPE_LOCATION,
 OTF2_Definitions.h, 165 551
 OTF2_LOCATION_GROUP_TYPE_UNKNOWN, OTF2_MARKER_SCOPE_LOCATION_-
 OTF2_Definitions.h, 165 GROUP, 551
 OTF2_LOCATION_TYPE_CPU_THREAD, OTF2_MARKER_SCOPE_SYSTEM_-
 OTF2_Definitions.h, 165 TREE_NODE, 551
 OTF2_LOCATION_TYPE_GPU, OTF2_SEVERITY_HIGH, 552
 OTF2_Definitions.h, 165 OTF2_SEVERITY_LOW, 552
 OTF2_LOCATION_TYPE_METRIC, OTF2_SEVERITY_MEDIUM, 552
 OTF2_Definitions.h, 165 OTF2_SEVERITY_NONE, 552
 OTF2_LOCATION_TYPE_UNKNOWN, OTF2_MARKER_SCOPE_COMM
 OTF2_Definitions.h, 165 OTF2_Marker.h, 552
 OTF2_LOCK_EXCLUSIVE, OTF2_MARKER_SCOPE_GLOBAL
 OTF2_Events.h, 232 OTF2_Marker.h, 551
 OTF2_LOCK_SHARED, OTF2_MARKER_SCOPE_GROUP
 OTF2_Events.h, 232 OTF2_Marker.h, 552
 OTF2_MAPPING_ATTRIBUTE, OTF2_MARKER_SCOPE_LOCATION
 OTF2_GeneralDefinitions.h, 374 OTF2_Marker.h, 551
 OTF2_MAPPING_COMM, OTF2_MARKER_SCOPE_LOCATION_-
 OTF2_GeneralDefinitions.h, 374 GROUP
 OTF2_MAPPING_GROUP, OTF2_MARKER_SCOPE_LOCATION_-
 OTF2_GeneralDefinitions.h, 374 OTF2_Marker.h, 551
 OTF2_MAPPING_LOCATION, OTF2_MARKER_SCOPE_SYSTEM_-
 OTF2_GeneralDefinitions.h, 374 TREE_NODE
 OTF2_Marker.h, 551
 OTF2_MAPPING_MAX, OTF2_MASTER
 OTF2_GeneralDefinitions.h, 374 OTF2_Archive.h, 103
 OTF2_MAPPING_METRIC, OTF2_MEASUREMENT_OFF
 OTF2_GeneralDefinitions.h, 374 OTF2_Events.h, 233
 OTF2_MAPPING_PARAMETER, OTF2_MEASUREMENT_ON
 OTF2_GeneralDefinitions.h, 374 OTF2_Events.h, 233
 OTF2_MAPPING_REGION, OTF2_METRIC_ABSOLUTE_LAST
 OTF2_GeneralDefinitions.h, 374 OTF2_Definitions.h, 166
 OTF2_MAPPING_RMA_WIN, OTF2_METRIC_ABSOLUTE_NEXT
 OTF2_GeneralDefinitions.h, 374 OTF2_Definitions.h, 166
 OTF2_MAPPING_STRING, OTF2_METRIC_ABSOLUTE_POINT
 OTF2_GeneralDefinitions.h, 374 OTF2_Definitions.h, 166
 OTF2_Marker.h, OTF2_METRIC_ACCUMULATED_LAST
 OTF2_MARKER_SCOPE_COMM, 552 OTF2_Definitions.h, 166
 OTF2_MARKER_SCOPE_GLOBAL, 551 OTF2_Definitions.h, 166
 OTF2_MARKER_SCOPE_GROUP, 552 OTF2_METRIC_ACCUMULATED_NEXT
 OTF2_MARKER_SCOPE_SYSTEM_TREE_NODE, 551 OTF2_Definitions.h, 166
 OTF2_SEVERITY_HIGH, 552 OTF2_METRIC_ABSOLUTE_POINT
 OTF2_SEVERITY_LOW, 552 OTF2_Definitions.h, 166
 OTF2_SEVERITY_MEDIUM, 552 OTF2_METRIC_ACCUMULATED_START
 OTF2_SEVERITY_NONE, 552 OTF2_Definitions.h, 166

INDEX

OTF2_METRIC_ASYNCHRONOUS
OTF2_Definitions.h, 166

OTF2_METRIC_RELATIVE_LAST
OTF2_Definitions.h, 166

OTF2_METRIC_RELATIVE_NEXT
OTF2_Definitions.h, 166

OTF2_METRIC_RELATIVE_POINT
OTF2_Definitions.h, 166

OTF2_METRIC_SYNCHRONOUS
OTF2_Definitions.h, 166

OTF2_METRIC_SYNCHRONOUS_STRICT
OTF2_Definitions.h, 166

OTF2_METRIC_TIMING_LAST
OTF2_Definitions.h, 167

OTF2_METRIC_TIMING_MASK
OTF2_Definitions.h, 167

OTF2_METRIC_TIMING_NEXT
OTF2_Definitions.h, 167

OTF2_METRIC_TIMING_POINT
OTF2_Definitions.h, 167

OTF2_METRIC_TIMING_START
OTF2_Definitions.h, 167

OTF2_METRIC_TYPE_OTHER
OTF2_Definitions.h, 168

OTF2_METRIC_TYPE_PAPI
OTF2_Definitions.h, 168

OTF2_METRIC_TYPE_RUSAGE
OTF2_Definitions.h, 168

OTF2_METRIC_TYPE_USER
OTF2_Definitions.h, 168

OTF2_METRIC_VALUE_ABSOLUTE
OTF2_Definitions.h, 168

OTF2_METRIC_VALUE_ACCUMULATED
OTF2_Definitions.h, 168

OTF2_METRIC_VALUE_MASK
OTF2_Definitions.h, 168

OTF2_METRIC_VALUE_RELATIVE
OTF2_Definitions.h, 168

OTF2_NO_FLUSH
OTF2_GeneralDefinitions.h, 373

OTF2_PARADIGM_COMPILER
OTF2_GeneralDefinitions.h, 374

OTF2_PARADIGM_CUDA
OTF2_GeneralDefinitions.h, 374

OTF2_PARADIGM_MEASUREMENT_
SYSTEM
OTF2_GeneralDefinitions.h, 374

OTF2_PARADIGM_MPI
OTF2_GeneralDefinitions.h, 374

OTF2_PARADIGM_OPENMP
OTF2_GeneralDefinitions.h, 374

OTF2_PARADIGM_UNKNOWN
OTF2_GeneralDefinitions.h, 374

OTF2_PARADIGM_USER
OTF2_GeneralDefinitions.h, 374

OTF2_PARAMETER_TYPE_INT64
OTF2_Definitions.h, 169

OTF2_PARAMETER_TYPE_STRING
OTF2_Definitions.h, 169

OTF2_PARAMETER_TYPE_UINT64
OTF2_Definitions.h, 169

OTF2_RECORDER_KIND_ABSTRACT
OTF2_Definitions.h, 169

OTF2_RECORDER_KIND_CPU
OTF2_Definitions.h, 169

OTF2_RECORDER_KIND_GPU
OTF2_Definitions.h, 169

OTF2_RECORDER_KIND_UNKNOWN
OTF2_Definitions.h, 169

OTF2_REGION_FLAG_DYNAMIC
OTF2_Definitions.h, 169

OTF2_REGION_FLAG_NONE
OTF2_Definitions.h, 169

OTF2_REGION_FLAG_PHASE
OTF2_Definitions.h, 169

OTF2_REGION_ROLE_ARTIFICIAL
OTF2_Definitions.h, 171

OTF2_REGION_ROLE_ATOMIC
OTF2_Definitions.h, 170

OTF2_REGION_ROLE_BARRIER
OTF2_Definitions.h, 170

OTF2_REGION_ROLE_CODE
OTF2_Definitions.h, 170

OTF2_REGION_ROLE_COLL_ALL2ALL
OTF2_Definitions.h, 171

OTF2_REGION_ROLE_COLL_ALL2ONE
OTF2_Definitions.h, 171

OTF2_REGION_ROLE_COLL_ONE2ALL

| | |
|---|--|
| OTF2_Definitions.h, 171 | OTF2_Definitions.h, 170 |
| OTF2_REGION_ROLE_COLL_OTHER | OTF2_REGION_ROLE_UNKNOWN |
| OTF2_Definitions.h, 171 | OTF2_Definitions.h, 170 |
| OTF2_REGION_ROLE_CRITICAL | OTF2_REGION_ROLE_WORKSHARE |
| OTF2_Definitions.h, 170 | OTF2_Definitions.h, 170 |
| OTF2_REGION_ROLE_CRITICAL_SBLOCK | OTF2_REGION_ROLE_WRAPPER |
| OTF2_Definitions.h, 170 | OTF2_Definitions.h, 170 |
| OTF2_REGION_ROLE_DATA_TRANSFER | OTF2_RMA_SYNC_LEVEL_MEMORY |
| OTF2_Definitions.h, 171 | OTF2_Events.h, 233 |
| OTF2_REGION_ROLE_FILE_IO | OTF2_RMA_SYNC_LEVEL_NONE |
| OTF2_Definitions.h, 171 | OTF2_Events.h, 233 |
| OTF2_REGION_ROLE_FLUSH | OTF2_RMA_SYNC_LEVEL_PROCESS |
| OTF2_Definitions.h, 170 | OTF2_Events.h, 233 |
| OTF2_REGION_ROLE_FUNCTION | OTF2_RMA_SYNC_TYPE_MEMORY |
| OTF2_Definitions.h, 170 | OTF2_Events.h, 234 |
| OTF2_REGION_ROLE_IMPLICIT_BARRIER | OTF2_RMA_SYNC_TYPE_NOTIFY_IN |
| OTF2_Definitions.h, 170 | OTF2_Events.h, 234 |
| OTF2_REGION_ROLE_LOOP | OTF2_RMA_SYNC_TYPE_NOTIFY_OUT |
| OTF2_Definitions.h, 170 | OTF2_Events.h, 234 |
| OTF2_REGION_ROLE_MASTER | OTF2_SCOPE_GROUP |
| OTF2_Definitions.h, 170 | OTF2_Definitions.h, 167 |
| OTF2_REGION_ROLE_ORDERED | OTF2_SCOPE_LOCATION |
| OTF2_Definitions.h, 170 | OTF2_Definitions.h, 167 |
| OTF2_REGION_ROLE_ORDERED_SBLOCK | OTF2_SCOPE_LOCATION_GROUP |
| OTF2_Definitions.h, 170 | OTF2_Definitions.h, 167 |
| OTF2_REGION_ROLE_PARALLEL | OTF2_SCOPE_SYSTEM_TREE_NODE |
| OTF2_Definitions.h, 170 | OTF2_Definitions.h, 167 |
| OTF2_REGION_ROLE_POINT2POINT | OTF2_SEVERITY_HIGH |
| OTF2_Definitions.h, 171 | OTF2_Marker.h, 552 |
| OTF2_REGION_ROLE_RMA | OTF2_SEVERITY_LOW |
| OTF2_Definitions.h, 171 | OTF2_Marker.h, 552 |
| OTF2_REGION_ROLE_SECTION | OTF2_SEVERITY_MEDIUM |
| OTF2_Definitions.h, 170 | OTF2_Marker.h, 552 |
| OTF2_REGION_ROLE_SECTIONS | OTF2_SEVERITY_NONE |
| OTF2_Definitions.h, 170 | OTF2_Marker.h, 552 |
| OTF2_REGION_ROLE_SINGLE | OTF2_SLAVE |
| OTF2_Definitions.h, 170 | OTF2_Archive.h, 103 |
| OTF2_REGION_ROLE_SINGLE_SBLOCK | OTF2_SUBSTRATE_NONE |
| OTF2_Definitions.h, 170 | OTF2_GeneralDefinitions.h, 373 |
| OTF2_REGION_ROLE_TASK | OTF2_SUBSTRATE_POSIX |
| OTF2_Definitions.h, 170 | OTF2_GeneralDefinitions.h, 372 |
| OTF2_REGION_ROLE_TASK_CREATE | OTF2_SUBSTRATE_SION |
| OTF2_Definitions.h, 170 | |

INDEX

- OTF2_GeneralDefinitions.h, [373](#)
- OTF2_SUBSTRATE_UNDEFINED
 - OTF2_GeneralDefinitions.h, [372](#)
- OTF2_SUCCESS
 - OTF2_ErrorCodes.h, [225](#)
- OTF2_SYSTEM_TREE_DOMAIN_CACHE
 - OTF2_Definitions.h, [171](#)
- OTF2_SYSTEM_TREE_DOMAIN_CORE
 - OTF2_Definitions.h, [172](#)
- OTF2_SYSTEM_TREE_DOMAIN_MACHINE
 - OTF2_Definitions.h, [171](#)
- OTF2_SYSTEM_TREE_DOMAIN_NUMA
 - OTF2_Definitions.h, [171](#)
- OTF2_SYSTEM_TREE_DOMAIN_PU
 - OTF2_Definitions.h, [172](#)
- OTF2_SYSTEM_TREE_DOMAIN_SHARED_MEMORY
 - OTF2_Definitions.h, [171](#)
- OTF2_SYSTEM_TREE_DOMAIN_SOCKET
 - OTF2_Definitions.h, [171](#)
- OTF2_THUMBNAIL_TYPE_ATTRIBUTES
 - OTF2_GeneralDefinitions.h, [375](#)
- OTF2_THUMBNAIL_TYPE_METRIC
 - OTF2_GeneralDefinitions.h, [375](#)
- OTF2_THUMBNAIL_TYPE_REGION
 - OTF2_GeneralDefinitions.h, [375](#)
- OTF2_TYPE_DOUBLE
 - OTF2_GeneralDefinitions.h, [375](#)
- OTF2_TYPE_FLOAT
 - OTF2_GeneralDefinitions.h, [375](#)
- OTF2_TYPE_INT16
 - OTF2_GeneralDefinitions.h, [375](#)
- OTF2_TYPE_INT32
 - OTF2_GeneralDefinitions.h, [375](#)
- OTF2_TYPE_INT64
 - OTF2_GeneralDefinitions.h, [375](#)
- OTF2_TYPE_INT8
 - OTF2_GeneralDefinitions.h, [375](#)
- OTF2_TYPE_NONE
 - OTF2_GeneralDefinitions.h, [375](#)
- OTF2_TYPE_UINT16
 - OTF2_GeneralDefinitions.h, [375](#)
- OTF2_TYPE_UINT32
 - OTF2_GeneralDefinitions.h, [375](#)
- OTF2_TYPE_UINT64
 - OTF2_GeneralDefinitions.h, [375](#)
- OTF2_TYPE_UINT8
 - OTF2_GeneralDefinitions.h, [375](#)
- OTF2_WARNING
 - OTF2_ErrorCodes.h, [225](#)
- OTF2_Archive
 - OTF2_Archive.h, [103](#)
 - OTF2_Archive.h, [95](#)
 - OTF2_Archive, [103](#)
 - OTF2_Archive_Close, [103](#)
 - OTF2_Archive_CloseDefReader, [104](#)
 - OTF2_Archive_CloseDefWriter, [104](#)
 - OTF2_Archive_CloseEvtReader, [104](#)
 - OTF2_Archive_CloseEvtWriter, [105](#)
 - OTF2_Archive_CloseGlobalDefReader, [105](#)
 - OTF2_Archive_CloseGlobalEvtReader, [105](#)
 - OTF2_Archive_CloseGlobalSnapReader, [106](#)
 - OTF2_Archive_CloseMarkerReader, [106](#)
 - OTF2_Archive_CloseMarkerWriter, [106](#)
 - OTF2_Archive_CloseSnapReader, [107](#)
 - OTF2_Archive_CloseSnapWriter, [107](#)
 - OTF2_Archive_CloseThumbReader, [108](#)
 - OTF2_Archive_GetChunkSize, [108](#)
 - OTF2_Archive_GetCompression, [108](#)
 - OTF2_Archive_GetCreator, [109](#)
 - OTF2_Archive_GetDefReader, [109](#)
 - OTF2_Archive_GetDefWriter, [109](#)
 - OTF2_Archive_GetDescription, [110](#)
 - OTF2_Archive_GetEvtReader, [110](#)
 - OTF2_Archive_GetEvtWriter, [110](#)
 - OTF2_Archive_GetFileSubstrate, [111](#)
 - OTF2_Archive_GetGlobalDefReader, [111](#)
 - OTF2_Archive_GetGlobalDefWriter, [111](#)
 - OTF2_Archive_GetGlobalEvtReader, [112](#)

[OTF2_Archive_GetGlobalSnapReader](#), [112](#)
[OTF2_Archive_GetMachineName](#), [112](#)
[OTF2_Archive_GetMarkerReader](#), [113](#)
[OTF2_Archive_GetMarkerWriter](#), [113](#)
[OTF2_Archive_GetMasterSlaveMode](#), [114](#)
[OTF2_Archive_GetNumberOfGlobalDefinitions](#), [114](#)
[OTF2_Archive_GetNumberOfLocations](#), [114](#)
[OTF2_Archive_GetNumberOfSnapshots](#), [115](#)
[OTF2_Archive_GetNumberOfThumbnails](#), [115](#)
[OTF2_Archive_GetProperty](#), [115](#)
[OTF2_Archive_GetPropertyNames](#), [116](#)
[OTF2_Archive_GetSnapReader](#), [116](#)
[OTF2_Archive_GetSnapWriter](#), [117](#)
[OTF2_Archive_GetThumbReader](#), [117](#)
[OTF2_Archive_GetThumbWriter](#), [117](#)
[OTF2_Archive_GetTraceId](#), [118](#)
[OTF2_Archive_GetVersion](#), [118](#)
[OTF2_Archive_Open](#), [119](#)
[OTF2_Archive_SetBoolProperty](#), [120](#)
[OTF2_Archive_SetCreator](#), [121](#)
[OTF2_Archive_SetDescription](#), [121](#)
[OTF2_Archive_SetFileSionCallbacks](#), [122](#)
[OTF2_Archive_SetFlushCallbacks](#), [122](#)
[OTF2_Archive_SetMachineName](#), [122](#)
[OTF2_Archive_SetMasterSlaveMode](#), [123](#)
[OTF2_Archive_SetMemoryCallbacks](#), [123](#)
[OTF2_Archive_SetNumberOfSnapshots](#), [124](#)
[OTF2_Archive_SetProperty](#), [124](#)
[OTF2_Archive_SwitchFileMode](#), [125](#)
[OTF2_CHUNK_SIZE_DEFINITIONS](#)
 [DEFAULT](#), [102](#)
[OTF2_CHUNK_SIZE_EVENTS](#)
 [DEFAULT](#), [102](#)
[OTF2_MasterSlaveMode](#), [103](#)
[OTF2_MasterSlaveMode_enum](#), [103](#)
[OTF2_Archive_Close](#)
[OTF2_Archive.h](#), [103](#)
[OTF2_Archive_CloseDefReader](#)
[OTF2_Archive.h](#), [104](#)
[OTF2_Archive_CloseDefWriter](#)
[OTF2_Archive.h](#), [104](#)
[OTF2_Archive_CloseEvtReader](#)
[OTF2_Archive.h](#), [104](#)
[OTF2_Archive_CloseEvtWriter](#)
[OTF2_Archive.h](#), [105](#)
[OTF2_Archive_CloseGlobalDefReader](#)
[OTF2_Archive.h](#), [105](#)
[OTF2_Archive_CloseGlobalEvtReader](#)
[OTF2_Archive.h](#), [105](#)
[OTF2_Archive_CloseGlobalSnapReader](#)
[OTF2_Archive.h](#), [106](#)
[OTF2_Archive_CloseMarkerReader](#)
[OTF2_Archive.h](#), [106](#)
[OTF2_Archive_CloseMarkerWriter](#)
[OTF2_Archive.h](#), [106](#)
[OTF2_Archive_CloseSnapReader](#)
[OTF2_Archive.h](#), [107](#)
[OTF2_Archive_CloseSnapWriter](#)
[OTF2_Archive.h](#), [107](#)
[OTF2_Archive_CloseThumbReader](#)
[OTF2_Archive.h](#), [108](#)
[OTF2_Archive_GetChunkSize](#)
[OTF2_Archive.h](#), [108](#)
[OTF2_Archive_GetCompression](#)
[OTF2_Archive.h](#), [108](#)
[OTF2_Archive_GetCreator](#)
[OTF2_Archive.h](#), [109](#)
[OTF2_Archive_GetDefReader](#)
[OTF2_Archive.h](#), [109](#)
[OTF2_Archive_GetDefWriter](#)
[OTF2_Archive.h](#), [109](#)
[OTF2_Archive_GetDescription](#)
[OTF2_Archive.h](#), [110](#)
[OTF2_Archive_GetEvtReader](#)
[OTF2_Archive.h](#), [110](#)

INDEX

- OTF2_Archive_GetEvtWriter
OTF2_Archive.h, [110](#)
- OTF2_Archive_GetFileSubstrate
OTF2_Archive.h, [111](#)
- OTF2_Archive_GetGlobalDefReader
OTF2_Archive.h, [111](#)
- OTF2_Archive_GetGlobalDefWriter
OTF2_Archive.h, [111](#)
- OTF2_Archive_GetGlobalEvtReader
OTF2_Archive.h, [112](#)
- OTF2_Archive_GetGlobalSnapReader
OTF2_Archive.h, [112](#)
- OTF2_Archive_GetMachineName
OTF2_Archive.h, [112](#)
- OTF2_Archive_GetMarkerReader
OTF2_Archive.h, [113](#)
- OTF2_Archive_GetMarkerWriter
OTF2_Archive.h, [113](#)
- OTF2_Archive_GetMasterSlaveMode
OTF2_Archive.h, [114](#)
- OTF2_Archive_GetNumberOfGlobalDefinitions
OTF2_Archive.h, [114](#)
- OTF2_Archive_GetNumberOfLocations
OTF2_Archive.h, [114](#)
- OTF2_Archive_GetNumberOfSnapshots
OTF2_Archive.h, [115](#)
- OTF2_Archive_GetNumberOfThumbnails
OTF2_Archive.h, [115](#)
- OTF2_Archive_GetProperty
OTF2_Archive.h, [115](#)
- OTF2_Archive_GetPropertyNames
OTF2_Archive.h, [116](#)
- OTF2_Archive_GetSnapReader
OTF2_Archive.h, [116](#)
- OTF2_Archive_GetSnapWriter
OTF2_Archive.h, [117](#)
- OTF2_Archive_GetThumbReader
OTF2_Archive.h, [117](#)
- OTF2_Archive_GetThumbWriter
OTF2_Archive.h, [117](#)
- OTF2_Archive_GetTraceId
OTF2_Archive.h, [118](#)
- OTF2_Archive_GetVersion
OTF2_Archive.h, [118](#)
- OTF2_Archive_Open
OTF2_Archive.h, [119](#)
- OTF2_Archive_SetBoolProperty
OTF2_Archive.h, [120](#)
- OTF2_Archive_SetCreator
OTF2_Archive.h, [121](#)
- OTF2_Archive_SetDescription
OTF2_Archive.h, [121](#)
- OTF2_Archive_SetFileSionCallbacks
OTF2_Archive.h, [122](#)
- OTF2_Archive_SetFlushCallbacks
OTF2_Archive.h, [122](#)
- OTF2_Archive_SetMachineName
OTF2_Archive.h, [122](#)
- OTF2_Archive_SetMasterSlaveMode
OTF2_Archive.h, [123](#)
- OTF2_Archive_SetMemoryCallbacks
OTF2_Archive.h, [123](#)
- OTF2_Archive_SetNumberOfSnapshots
OTF2_Archive.h, [124](#)
- OTF2_Archive_SetProperty
OTF2_Archive.h, [124](#)
- OTF2_Archive_SwitchFileMode
OTF2_Archive.h, [125](#)
- OTF2_AttributeList.h, [125](#)
- OTF2_AttributeList_AddAttribute, [132](#)
- OTF2_AttributeList_AddAttributeRef,
[133](#)
- OTF2_AttributeList_AddCommRef,
[133](#)
- OTF2_AttributeList_AddDouble, [133](#)
- OTF2_AttributeList_AddFloat, [134](#)
- OTF2_AttributeList_AddGroupRef,
[134](#)
- OTF2_AttributeList_AddInt16, [135](#)
- OTF2_AttributeList_AddInt32, [135](#)
- OTF2_AttributeList_AddInt64, [135](#)
- OTF2_AttributeList_AddInt8, [136](#)
- OTF2_AttributeList_AddLocationRef,
[136](#)
- OTF2_AttributeList_AddMetricRef,
[136](#)
- OTF2_AttributeList_AddParameterRef,
[137](#)

-
- OTF2_AttributeList_AddRegionRef, 137
 - OTF2_AttributeList_AddRmaWinRef, 138
 - OTF2_AttributeList_AddString, 138
 - OTF2_AttributeList_AddStringRef, 139
 - OTF2_AttributeList_AddUInt16, 139
 - OTF2_AttributeList_AddUInt32, 139
 - OTF2_AttributeList_AddUInt64, 140
 - OTF2_AttributeList_AddUInt8, 140
 - OTF2_AttributeList_Delete, 140
 - OTF2_AttributeList_GetAttributeByID, 141
 - OTF2_AttributeList_GetAttributeByIndex, 141
 - OTF2_AttributeList_GetAttributeRef, 142
 - OTF2_AttributeList_GetCommRef, 142
 - OTF2_AttributeList_GetDouble, 142
 - OTF2_AttributeList_GetFloat, 143
 - OTF2_AttributeList_GetGroupRef, 143
 - OTF2_AttributeList_GetInt16, 144
 - OTF2_AttributeList_GetInt32, 144
 - OTF2_AttributeList_GetInt64, 144
 - OTF2_AttributeList_GetInt8, 145
 - OTF2_AttributeList_GetLocationRef, 145
 - OTF2_AttributeList_GetMetricRef, 146
 - OTF2_AttributeList_GetNumberOfElements, 146
 - OTF2_AttributeList_GetParameterRef, 146
 - OTF2_AttributeList_GetRegionRef, 147
 - OTF2_AttributeList_GetRmaWinRef, 147
 - OTF2_AttributeList_GetString, 148
 - OTF2_AttributeList_GetStringRef, 148
 - OTF2_AttributeList_GetUInt16, 149
 - OTF2_AttributeList_GetUInt32, 149
 - OTF2_AttributeList_GetUInt64, 149
 - OTF2_AttributeList_GetUInt8, 150
 - OTF2_AttributeList_New, 150
 - OTF2_AttributeList_PopAttribute, 150
 - OTF2_AttributeList_RemoveAllAttributes, 151
 - OTF2_AttributeList_RemoveAttribute, 151
 - OTF2_AttributeList_TestAttributeByID, 152
 - OTF2_AttributeList_AddAttribute, 132
 - OTF2_AttributeList_AddAttributeRef, 133
 - OTF2_AttributeList_AddCommRef, 133
 - OTF2_AttributeList_AddDouble, 133
 - OTF2_AttributeList_AddFloat, 134
 - OTF2_AttributeList_AddGroupRef, 134
 - OTF2_AttributeList_AddInt16, 135
 - OTF2_AttributeList_AddInt32, 135
 - OTF2_AttributeList_AddInt64, 135
 - OTF2_AttributeList_AddInt8, 136
 - OTF2_AttributeList_AddLocationRef, 136
 - OTF2_AttributeList_AddMetricRef, 136
 - OTF2_AttributeList_AddParameterRef, 137
 - OTF2_AttributeList_AddRegionRef, 137
 - OTF2_AttributeList_AddRmaWinRef, 138
 - OTF2_AttributeList_AddString, 138
 - OTF2_AttributeList_AddStringRef, 139
 - OTF2_AttributeList_AddUInt16, 139
 - OTF2_AttributeList_AddUInt32, 139
 - OTF2_AttributeList_AddUInt64, 140
 - OTF2_AttributeList_AddUInt8, 140

INDEX

- OTF2_AttributeList_AddUInt16
OTF2_AttributeList.h, [139](#)
- OTF2_AttributeList_AddUInt32
OTF2_AttributeList.h, [139](#)
- OTF2_AttributeList_AddUInt64
OTF2_AttributeList.h, [140](#)
- OTF2_AttributeList_AddUInt8
OTF2_AttributeList.h, [140](#)
- OTF2_AttributeList_Delete
OTF2_AttributeList.h, [140](#)
- OTF2_AttributeList_GetAttributeByID
OTF2_AttributeList.h, [141](#)
- OTF2_AttributeList_GetAttributeByIndex
OTF2_AttributeList.h, [141](#)
- OTF2_AttributeList_GetAttributeRef
OTF2_AttributeList.h, [142](#)
- OTF2_AttributeList_GetCommRef
OTF2_AttributeList.h, [142](#)
- OTF2_AttributeList_GetDouble
OTF2_AttributeList.h, [142](#)
- OTF2_AttributeList_GetFloat
OTF2_AttributeList.h, [143](#)
- OTF2_AttributeList_GetGroupRef
OTF2_AttributeList.h, [143](#)
- OTF2_AttributeList_GetInt16
OTF2_AttributeList.h, [144](#)
- OTF2_AttributeList_GetInt32
OTF2_AttributeList.h, [144](#)
- OTF2_AttributeList_GetInt64
OTF2_AttributeList.h, [144](#)
- OTF2_AttributeList_GetInt8
OTF2_AttributeList.h, [145](#)
- OTF2_AttributeList_GetLocationRef
OTF2_AttributeList.h, [145](#)
- OTF2_AttributeList_GetMetricRef
OTF2_AttributeList.h, [146](#)
- OTF2_AttributeList_GetNumberOfElements
OTF2_AttributeList.h, [146](#)
- OTF2_AttributeList_GetParameterRef
OTF2_AttributeList.h, [146](#)
- OTF2_AttributeList_GetRegionRef
OTF2_AttributeList.h, [147](#)
- OTF2_AttributeList_GetRmaWinRef
OTF2_AttributeList.h, [147](#)
- OTF2_AttributeList_GetString
OTF2_AttributeList.h, [148](#)
- OTF2_AttributeList_GetStringRef
OTF2_AttributeList.h, [148](#)
- OTF2_AttributeList_GetUInt16
OTF2_AttributeList.h, [149](#)
- OTF2_AttributeList_GetUInt32
OTF2_AttributeList.h, [149](#)
- OTF2_AttributeList_GetUInt64
OTF2_AttributeList.h, [149](#)
- OTF2_AttributeList_GetUInt8
OTF2_AttributeList.h, [150](#)
- OTF2_AttributeList_New
OTF2_AttributeList.h, [150](#)
- OTF2_AttributeList_PopAttribute
OTF2_AttributeList.h, [150](#)
- OTF2_AttributeList_RemoveAllAttributes
OTF2_AttributeList.h, [151](#)
- OTF2_AttributeList_RemoveAttribute
OTF2_AttributeList.h, [151](#)
- OTF2_AttributeList_TestAttributeByID
OTF2_AttributeList.h, [152](#)
- OTF2_AttributeValue, [89](#)
- OTF2_CallbackCode
OTF2_GeneralDefinitions.h, [371](#)
- OTF2_Callbacks.h, [152](#)
- OTF2_FileSionClose, [154](#)
- OTF2_FileSionGetRank, [154](#)
- OTF2_FileSionOpen, [154](#)
- OTF2_MemoryAllocate, [155](#)
- OTF2_MemoryFreeAll, [156](#)
- OTF2_PostFlushCallback, [156](#)
- OTF2_PreFlushCallback, [157](#)
- OTF2_CHUNK_SIZE_DEFINITIONS_
DEFAULT
OTF2_Archive.h, [102](#)
- OTF2_CHUNK_SIZE_EVENTS_DEFAULT
OTF2_Archive.h, [102](#)
- OTF2_CollectiveOp_enum
OTF2_Events.h, [232](#)
- OTF2_Compression_enum
OTF2_GeneralDefinitions.h, [372](#)
- OTF2_Definitions.h, [157](#)
- OTF2_GroupFlag_enum, [163](#)

-
- OTF2_GroupType_enum, 164
 - OTF2_LocationGroupType_enum, 164
 - OTF2_LocationType_enum, 165
 - OTF2_MetricBase_enum, 165
 - OTF2_MetricMode_enum, 165
 - OTF2_MetricOccurrence_enum, 166
 - OTF2_MetricScope_enum, 166
 - OTF2_MetricTiming_enum, 167
 - OTF2_MetricType_enum, 167
 - OTF2_MetricValueProperty_enum, 168
 - OTF2_ParameterType_enum, 168
 - OTF2_RecorderKind_enum, 169
 - OTF2_RegionFlag_enum, 169
 - OTF2_RegionRole_enum, 169
 - OTF2_SystemTreeDomain_enum, 171
 - OTF2_DefReader.h, 172
 - OTF2_DefReader_GetLocationID, 173
 - OTF2_DefReader_ReadDefinitions, 173
 - OTF2_DefReader_SetCallbacks, 174
 - OTF2_DefReader_GetLocationID
OTF2_DefReader.h, 173
 - OTF2_DefReader_ReadDefinitions
OTF2_DefReader.h, 173
 - OTF2_DefReader_SetCallbacks
OTF2_DefReader.h, 174
 - OTF2_DefReaderCallback_Attribute
OTF2_DefReaderCallbacks.h, 181
 - OTF2_DefReaderCallback_Callpath
OTF2_DefReaderCallbacks.h, 181
 - OTF2_DefReaderCallback_Callsite
OTF2_DefReaderCallbacks.h, 182
 - OTF2_DefReaderCallback_ClockOffset
OTF2_DefReaderCallbacks.h, 182
 - OTF2_DefReaderCallback_Comm
OTF2_DefReaderCallbacks.h, 183
 - OTF2_DefReaderCallback_Group
OTF2_DefReaderCallbacks.h, 184
 - OTF2_DefReaderCallback_Location
OTF2_DefReaderCallbacks.h, 184
 - OTF2_DefReaderCallback_LocationGroup
OTF2_DefReaderCallbacks.h, 185
 - OTF2_DefReaderCallback_MappingTable
OTF2_DefReaderCallbacks.h, 186
 - OTF2_DefReaderCallback_MetricClass
OTF2_DefReaderCallbacks.h, 186
 - OTF2_DefReaderCallback_MetricClassRecorder
OTF2_DefReaderCallbacks.h, 187
 - OTF2_DefReaderCallback_MetricInstance
OTF2_DefReaderCallbacks.h, 188
 - OTF2_DefReaderCallback_MetricMember
OTF2_DefReaderCallbacks.h, 189
 - OTF2_DefReaderCallback_Parameter
OTF2_DefReaderCallbacks.h, 189
 - OTF2_DefReaderCallback_Region
OTF2_DefReaderCallbacks.h, 190
 - OTF2_DefReaderCallback_RmaWin
OTF2_DefReaderCallbacks.h, 191
 - OTF2_DefReaderCallback_String
OTF2_DefReaderCallbacks.h, 192
 - OTF2_DefReaderCallback_SystemTreeNode
OTF2_DefReaderCallbacks.h, 192
 - OTF2_DefReaderCallback_SystemTreeNodeDomain
OTF2_DefReaderCallbacks.h, 193
 - OTF2_DefReaderCallback_SystemTreeNodeProperty
OTF2_DefReaderCallbacks.h, 193
 - OTF2_DefReaderCallback_Unknown
OTF2_DefReaderCallbacks.h, 194
 - OTF2_DefReaderCallbacks.h, 174
 - OTF2_DefReaderCallback_Attribute,
181
 - OTF2_DefReaderCallback_Callpath,
181
 - OTF2_DefReaderCallback_Callsite,
182
 - OTF2_DefReaderCallback_ClockOffset,
182
 - OTF2_DefReaderCallback_Comm,
183
 - OTF2_DefReaderCallback_Group, 184
 - OTF2_DefReaderCallback_Location,
184
 - OTF2_DefReaderCallback_LocationGroup,
185
 - OTF2_DefReaderCallback_MappingTable,
186

INDEX

OTF2_DefReaderCallback_MetricClass, 186
OTF2_DefReaderCallback_MetricClassRecorder, 187
OTF2_DefReaderCallback_MetricInstance, 188
OTF2_DefReaderCallback_MetricMember, 189
OTF2_DefReaderCallback_Parameter, 189
OTF2_DefReaderCallback_Region, 190
OTF2_DefReaderCallback_RmaWin, 191
OTF2_DefReaderCallback_String, 192
OTF2_DefReaderCallback_SystemTreeNode, 192
OTF2_DefReaderCallback_SystemTreeNodeDomain, 193
OTF2_DefReaderCallback_SystemTreeNodeProperty, 193
OTF2_DefReaderCallback_Unknown, 194
OTF2_DefReaderCallbacks_Clear, 194
OTF2_DefReaderCallbacks_Delete, 194
OTF2_DefReaderCallbacks_New, 195
OTF2_DefReaderCallbacks_SetAttributeCallback, 195
OTF2_DefReaderCallbacks_SetCallpathCallback, 195
OTF2_DefReaderCallbacks_SetCallsiteCallback, 196
OTF2_DefReaderCallbacks_SetClockOffsetCallback, 196
OTF2_DefReaderCallbacks_SetCommCallback, 197
OTF2_DefReaderCallbacks_SetGroupCallback, 197
OTF2_DefReaderCallbacks_SetLocationCallback, 198
OTF2_DefReaderCallbacks_SetLocationCallback, 198
OTF2_DefReaderCallbacks_SetMappingTableCallback, 198
OTF2_DefReaderCallbacks_SetMetricClassCallback, 199
OTF2_DefReaderCallbacks_SetMetricClassRecorderCallback, 199
OTF2_DefReaderCallbacks_SetMetricInstanceCallback, 200
OTF2_DefReaderCallbacks_SetMetricMemberCallback, 200
OTF2_DefReaderCallbacks_SetParameterCallback, 201
OTF2_DefReaderCallbacks_SetRegionCallback, 201
OTF2_DefReaderCallbacks_SetRmaWinCallback, 202
OTF2_DefReaderCallbacks_SetStringCallback, 202
OTF2_DefReaderCallbacks_SetSystemTreeNodeCallback, 203
OTF2_DefReaderCallbacks_SetSystemTreeNodeDomainCallback, 203
OTF2_DefReaderCallbacks_SetSystemTreeNodePropertyCallback, 203
OTF2_DefReaderCallbacks_SetUnknownCallback, 204
OTF2_DefReaderCallbacks_Clear, 195
OTF2_DefReaderCallbacks.h, 194
OTF2_DefReaderCallbacks_Delete, 195
OTF2_DefReaderCallbacks.h, 194
OTF2_DefReaderCallbacks_New, 195
OTF2_DefReaderCallbacks.h, 195
OTF2_DefReaderCallbacks_SetAttributeCallback, 195
OTF2_DefReaderCallbacks.h, 195
OTF2_DefReaderCallbacks_SetCallpathCallback, 195
OTF2_DefReaderCallbacks.h, 195
OTF2_DefReaderCallbacks_SetCallsiteCallback, 196
OTF2_DefReaderCallbacks.h, 196
OTF2_DefReaderCallbacks_SetClockOffsetCallback, 196
OTF2_DefReaderCallbacks.h, 196
OTF2_DefReaderCallbacks_SetCommCallback, 197
OTF2_DefReaderCallbacks.h, 196
OTF2_DefReaderCallbacks_SetGroupCallback, 197
OTF2_DefReaderCallbacks.h, 196
OTF2_DefReaderCallbacks_SetLocationCallback, 198
OTF2_DefReaderCallbacks.h, 197
OTF2_DefReaderCallbacks_SetLocationCallback, 198
OTF2_DefReaderCallbacks.h, 197

[OTF2_DefReaderCallbacks_SetLocationCallback](#), [OTF2_DefWriter_WriteMetricClass](#),
[OTF2_DefReaderCallbacks.h](#), 198 [213](#)

[OTF2_DefReaderCallbacks_SetLocationGroupCallback](#), [OTF2_DefWriter_WriteMetricClassRecorder](#),
[OTF2_DefReaderCallbacks.h](#), 198 [214](#)

[OTF2_DefReaderCallbacks_SetMappingTableCallback](#), [OTF2_DefWriter_WriteMetricInstance](#),
[OTF2_DefReaderCallbacks.h](#), 198 [214](#)

[OTF2_DefReaderCallbacks_SetMetricClassCallback](#), [OTF2_DefWriter_WriteMetricMember](#),
[OTF2_DefReaderCallbacks.h](#), 199 [215](#)

[OTF2_DefReaderCallbacks_SetMetricClassRecorderCallback](#), [OTF2_DefWriter_WriteParameter](#), 216
[OTF2_DefReaderCallbacks.h](#), 199 [OTF2_DefWriter_WriteRegion](#), 217

[OTF2_DefReaderCallbacks_SetMetricInstanceCallback](#), [OTF2_DefWriter_WriteRmaWin](#), 217
[OTF2_DefReaderCallbacks.h](#), 200 [OTF2_DefWriter_WriteString](#), 218

[OTF2_DefReaderCallbacks_SetMetricMemberCallback](#), [OTF2_DefWriter_WriteSystemTreeNode](#),
[OTF2_DefReaderCallbacks.h](#), 200 [218](#)

[OTF2_DefReaderCallbacks_SetParameterCallback](#), [OTF2_DefWriter_WriteSystemTreeNodeDomain](#),
[OTF2_DefReaderCallbacks.h](#), 201 [219](#)

[OTF2_DefReaderCallbacks_SetRegionCallback](#), [OTF2_DefWriter_WriteSystemTreeNodeProperty](#),
[OTF2_DefReaderCallbacks.h](#), 201 [219](#)

[OTF2_DefReaderCallbacks_SetRmaWinCallback](#), [OTF2_DefWriter_GetLocationID](#)
[OTF2_DefReaderCallbacks.h](#), 202 [OTF2_DefWriter.h](#), 208

[OTF2_DefReaderCallbacks_SetStringCallback](#), [OTF2_DefWriter_WriteAttribute](#)
[OTF2_DefReaderCallbacks.h](#), 202 [OTF2_DefWriter.h](#), 208

[OTF2_DefReaderCallbacks_SetSystemTreeNodeCallback](#), [OTF2_DefWriter_WriteCallpath](#)
[OTF2_DefReaderCallbacks.h](#), 203 [OTF2_DefWriter.h](#), 209

[OTF2_DefReaderCallbacks_SetSystemTreeNodePropertyCallback](#), [OTF2_DefWriter_WriteCallsite](#)
[OTF2_DefReaderCallbacks.h](#), 203 [OTF2_DefWriter.h](#), 209

[OTF2_DefReaderCallbacks_SetSystemTreeNodePropertyCallback](#), [OTF2_DefWriter_WriteClockOffset](#)
[OTF2_DefReaderCallbacks.h](#), 204 [OTF2_DefWriter.h](#), 210

[OTF2_DefReaderCallbacks_SetUnknownCallback](#), [OTF2_DefWriter_WriteComm](#)
[OTF2_DefReaderCallbacks.h](#), 204 [OTF2_DefWriter.h](#), 210

[OTF2_DefWriter.h](#), 205 [OTF2_DefWriter_WriteGroup](#)
[OTF2_DefWriter_GetLocationID](#), 208 [OTF2_DefWriter.h](#), 211
[OTF2_DefWriter_WriteAttribute](#), 208 [OTF2_DefWriter_WriteLocation](#)
[OTF2_DefWriter_WriteCallpath](#), 209 [OTF2_DefWriter.h](#), 211
[OTF2_DefWriter_WriteCallsite](#), 209 [OTF2_DefWriter_WriteLocationGroup](#)
[OTF2_DefWriter_WriteClockOffset](#), [OTF2_DefWriter.h](#), 212
[210](#) [OTF2_DefWriter_WriteMappingTable](#)
[OTF2_DefWriter_WriteComm](#), 210 [OTF2_DefWriter.h](#), 213
[OTF2_DefWriter_WriteGroup](#), 211 [OTF2_DefWriter_WriteMetricClass](#)
[OTF2_DefWriter_WriteLocation](#), 211 [OTF2_DefWriter.h](#), 213
[OTF2_DefWriter_WriteLocationGroup](#), [OTF2_DefWriter_WriteMetricClassRecorder](#)
[212](#) [OTF2_DefWriter.h](#), 214
[OTF2_DefWriter_WriteMappingTable](#), [OTF2_DefWriter_WriteMetricInstance](#)
[213](#) [OTF2_DefWriter.h](#), 214

INDEX

- OTF2_DefWriter_WriteMetricMember
OTF2_DefWriter.h, 215
- OTF2_DefWriter_WriteParameter
OTF2_DefWriter.h, 216
- OTF2_DefWriter_WriteRegion
OTF2_DefWriter.h, 217
- OTF2_DefWriter_WriteRmaWin
OTF2_DefWriter.h, 217
- OTF2_DefWriter_WriteString
OTF2_DefWriter.h, 218
- OTF2_DefWriter_WriteSystemTreeNode
OTF2_DefWriter.h, 218
- OTF2_DefWriter_WriteSystemTreeNodeDomain
OTF2_DefWriter.h, 219
- OTF2_DefWriter_WriteSystemTreeNodeProperty
OTF2_DefWriter.h, 219
- OTF2_Error_GetDescription
OTF2_ErrorCodes.h, 228
- OTF2_Error_GetName
OTF2_ErrorCodes.h, 228
- OTF2_Error_RegisterCallback
OTF2_ErrorCodes.h, 229
- OTF2_ErrorCallback
OTF2_ErrorCodes.h, 224
- OTF2_ErrorCode
OTF2_ErrorCodes.h, 225
- OTF2_ErrorCodes.h, 220
 - OTF2_Error_GetDescription, 228
 - OTF2_Error_GetName, 228
 - OTF2_Error_RegisterCallback, 229
 - OTF2_ErrorCallback, 224
 - OTF2_ErrorCode, 225
- OTF2_Events.h, 229
 - OTF2_CollectiveOp_enum, 232
 - OTF2_LockType_enum, 232
 - OTF2_MeasurementMode_enum, 232
 - OTF2_RmaAtomicType_enum, 233
 - OTF2_RmaSyncLevel_enum, 233
 - OTF2_RmaSyncType_enum, 233
- OTF2_EvtReader.h, 234
 - OTF2_EvtReader_ApplyClockOffsets, 236
 - OTF2_EvtReader_ApplyMappingTables, 236
 - OTF2_EvtReader_GetLocationID, 236
 - OTF2_EvtReader_GetPos, 237
 - OTF2_EvtReader_ReadEvents, 237
 - OTF2_EvtReader_ReadEventsBackward, 238
 - OTF2_EvtReader_Seek, 238
 - OTF2_EvtReader_SetCallbacks, 238
 - OTF2_EvtReader_TimeStampRewrite, 239
 - OTF2_EvtReader_ApplyClockOffsets
OTF2_EvtReader.h, 236
 - OTF2_EvtReader_GetPos
OTF2_EvtReader.h, 237
 - OTF2_EvtReader_ReadEvents
OTF2_EvtReader.h, 237
 - OTF2_EvtReader_ReadEventsBackward
OTF2_EvtReader.h, 238
 - OTF2_EvtReader_Seek
OTF2_EvtReader.h, 238
 - OTF2_EvtReader_SetCallbacks
OTF2_EvtReader.h, 238
 - OTF2_EvtReader_TimeStampRewrite
OTF2_EvtReader.h, 239
 - OTF2_EvtReaderCallback_BufferFlush
OTF2_EvtReaderCallbacks.h, 254
 - OTF2_EvtReaderCallback_Enter
OTF2_EvtReaderCallbacks.h, 255
 - OTF2_EvtReaderCallback_Leave
OTF2_EvtReaderCallbacks.h, 255
 - OTF2_EvtReaderCallback_MeasurementOnOff
OTF2_EvtReaderCallbacks.h, 256
 - OTF2_EvtReaderCallback_Metric
OTF2_EvtReaderCallbacks.h, 257
 - OTF2_EvtReaderCallback_MpiCollectiveBegin
OTF2_EvtReaderCallbacks.h, 258
 - OTF2_EvtReaderCallback_MpiCollectiveEnd
OTF2_EvtReaderCallbacks.h, 258
 - OTF2_EvtReaderCallback_MpiIrecv
OTF2_EvtReaderCallbacks.h, 259
 - OTF2_EvtReaderCallback_MpiIrecvRequest

INDEX

OTF2_EvtReaderCallbacks.h, 260
OTF2_EvtReaderCallback_MpiIsend
OTF2_EvtReaderCallbacks.h, 261
OTF2_EvtReaderCallback_MpiIsendComplete
OTF2_EvtReaderCallbacks.h, 261
OTF2_EvtReaderCallback_MpiRecv
OTF2_EvtReaderCallbacks.h, 262
OTF2_EvtReaderCallback_MpiRequestCancel
OTF2_EvtReaderCallbacks.h, 263
OTF2_EvtReaderCallback_MpiRequestTest
OTF2_EvtReaderCallbacks.h, 264
OTF2_EvtReaderCallback_MpiSend
OTF2_EvtReaderCallbacks.h, 264
OTF2_EvtReaderCallback_OmpAcquireLock
OTF2_EvtReaderCallbacks.h, 265
OTF2_EvtReaderCallback_OmpFork
OTF2_EvtReaderCallbacks.h, 266
OTF2_EvtReaderCallback_OmpJoin
OTF2_EvtReaderCallbacks.h, 267
OTF2_EvtReaderCallback_OmpReleaseLock
OTF2_EvtReaderCallbacks.h, 267
OTF2_EvtReaderCallback_OmpTaskComplete
OTF2_EvtReaderCallbacks.h, 268
OTF2_EvtReaderCallback_OmpTaskCreate
OTF2_EvtReaderCallbacks.h, 269
OTF2_EvtReaderCallback_OmpTaskSwitch
OTF2_EvtReaderCallbacks.h, 269
OTF2_EvtReaderCallback_ParameterInt
OTF2_EvtReaderCallbacks.h, 270
OTF2_EvtReaderCallback_ParameterString
OTF2_EvtReaderCallbacks.h, 271
OTF2_EvtReaderCallback_ParameterUnsignedInt
OTF2_EvtReaderCallbacks.h, 272
OTF2_EvtReaderCallback_RmaAcquireLock
OTF2_EvtReaderCallbacks.h, 272
OTF2_EvtReaderCallback_RmaAtomic
OTF2_EvtReaderCallbacks.h, 273
OTF2_EvtReaderCallback_RmaCollectiveBegin
OTF2_EvtReaderCallbacks.h, 274
OTF2_EvtReaderCallback_RmaCollectiveEnd
OTF2_EvtReaderCallbacks.h, 275
OTF2_EvtReaderCallback_RmaGet
OTF2_EvtReaderCallbacks.h, 275
OTF2_EvtReaderCallback_RmaGroupSync
OTF2_EvtReaderCallbacks.h, 276
OTF2_EvtReaderCallback_RmaOpCompleteBlocking
OTF2_EvtReaderCallbacks.h, 277
OTF2_EvtReaderCallback_RmaOpCompleteNonBlocking
OTF2_EvtReaderCallbacks.h, 278
OTF2_EvtReaderCallback_RmaOpCompleteRemote
OTF2_EvtReaderCallbacks.h, 278
OTF2_EvtReaderCallback_RmaOpTest
OTF2_EvtReaderCallbacks.h, 279
OTF2_EvtReaderCallback_RmaPut
OTF2_EvtReaderCallbacks.h, 280
OTF2_EvtReaderCallback_RmaReleaseLock
OTF2_EvtReaderCallbacks.h, 281
OTF2_EvtReaderCallback_RmaRequestLock
OTF2_EvtReaderCallbacks.h, 281
OTF2_EvtReaderCallback_RmaSync
OTF2_EvtReaderCallbacks.h, 282
OTF2_EvtReaderCallback_RmaTryLock
OTF2_EvtReaderCallbacks.h, 283
OTF2_EvtReaderCallback_RmaWaitChange
OTF2_EvtReaderCallbacks.h, 284
OTF2_EvtReaderCallback_RmaWinCreate
OTF2_EvtReaderCallbacks.h, 284
OTF2_EvtReaderCallback_RmaWinDestroy
OTF2_EvtReaderCallbacks.h, 285
OTF2_EvtReaderCallback_ThreadAcquireLock
OTF2_EvtReaderCallbacks.h, 286
OTF2_EvtReaderCallback_ThreadFork
OTF2_EvtReaderCallbacks.h, 287
OTF2_EvtReaderCallback_ThreadJoin
OTF2_EvtReaderCallbacks.h, 287
OTF2_EvtReaderCallback_ThreadReleaseLock
OTF2_EvtReaderCallbacks.h, 288
OTF2_EvtReaderCallback_ThreadTaskComplete
OTF2_EvtReaderCallbacks.h, 289
OTF2_EvtReaderCallback_ThreadTaskCreate
OTF2_EvtReaderCallbacks.h, 289
OTF2_EvtReaderCallback_ThreadTaskSwitch
OTF2_EvtReaderCallbacks.h, 290
OTF2_EvtReaderCallback_ThreadTeamBegin
OTF2_EvtReaderCallbacks.h, 291
OTF2_EvtReaderCallback_ThreadTeamEnd
OTF2_EvtReaderCallbacks.h, 292
OTF2_EvtReaderCallback_Unknown

INDEX

- OTF2_EvtReaderCallbacks.h, [292](#)
- OTF2_EvtReaderCallbacks.h, [239](#)
- OTF2_EvtReaderCallback_BufferFlush, [254](#)
- OTF2_EvtReaderCallback_Enter, [255](#)
- OTF2_EvtReaderCallback_Leave, [255](#)
- OTF2_EvtReaderCallback_MeasurementOnOff, [256](#)
- OTF2_EvtReaderCallback_Metric, [257](#)
- OTF2_EvtReaderCallback_MpiCollectiveBegin, [258](#)
- OTF2_EvtReaderCallback_MpiCollectiveEnd, [258](#)
- OTF2_EvtReaderCallback_MpiIrecv, [259](#)
- OTF2_EvtReaderCallback_MpiIrecvRequest, [260](#)
- OTF2_EvtReaderCallback_MpiIsend, [261](#)
- OTF2_EvtReaderCallback_MpiIsendComplete, [261](#)
- OTF2_EvtReaderCallback_MpiRecv, [262](#)
- OTF2_EvtReaderCallback_MpiRequestCancelled, [263](#)
- OTF2_EvtReaderCallback_MpiRequestTest, [264](#)
- OTF2_EvtReaderCallback_MpiSend, [264](#)
- OTF2_EvtReaderCallback_OmpAcquireLock, [265](#)
- OTF2_EvtReaderCallback_OmpFork, [266](#)
- OTF2_EvtReaderCallback_OmpJoin, [267](#)
- OTF2_EvtReaderCallback_OmpReleaseLock, [267](#)
- OTF2_EvtReaderCallback_OmpTaskComplete, [268](#)
- OTF2_EvtReaderCallback_OmpTaskCreate, [269](#)
- OTF2_EvtReaderCallback_OmpTaskSwitch, [269](#)
- OTF2_EvtReaderCallback_ParameterInt, [270](#)
- OTF2_EvtReaderCallback_ParameterString, [271](#)
- OTF2_EvtReaderCallback_ParameterUnsignedInt, [272](#)
- OTF2_EvtReaderCallback_RmaAcquireLock, [272](#)
- OTF2_EvtReaderCallback_RmaAtomic, [273](#)
- OTF2_EvtReaderCallback_RmaCollectiveBegin, [274](#)
- OTF2_EvtReaderCallback_RmaCollectiveEnd, [275](#)
- OTF2_EvtReaderCallback_RmaGet, [275](#)
- OTF2_EvtReaderCallback_RmaGroupSync, [276](#)
- OTF2_EvtReaderCallback_RmaOpCompleteBlocking, [277](#)
- OTF2_EvtReaderCallback_RmaOpCompleteNonBlocking, [278](#)
- OTF2_EvtReaderCallback_RmaOpCompleteRemote, [278](#)
- OTF2_EvtReaderCallback_RmaOpTest, [279](#)
- OTF2_EvtReaderCallback_RmaPut, [280](#)
- OTF2_EvtReaderCallback_RmaReleaseLock, [281](#)
- OTF2_EvtReaderCallback_RmaRequestLock, [281](#)
- OTF2_EvtReaderCallback_RmaSync, [282](#)
- OTF2_EvtReaderCallback_RmaTryLock, [283](#)
- OTF2_EvtReaderCallback_RmaWaitChange, [284](#)
- OTF2_EvtReaderCallback_RmaWinCreate, [284](#)
- OTF2_EvtReaderCallback_RmaWinDestroy, [285](#)
- OTF2_EvtReaderCallback_ThreadAcquireLock, [286](#)

INDEX

- OTF2_EvtReaderCallback_ThreadFork, 287
OTF2_EvtReaderCallbacks_SetMpiRecvCallback, 299
- OTF2_EvtReaderCallback_ThreadJoin, 287
OTF2_EvtReaderCallbacks_SetMpiRequestCancelledCallback, 299
- OTF2_EvtReaderCallback_ThreadRelease, 288
OTF2_EvtReaderCallbacks_SetMpiRequestTestCallback, 300
- OTF2_EvtReaderCallback_ThreadTaskComplete, 289
OTF2_EvtReaderCallbacks_SetMpiSendCallback, 300
- OTF2_EvtReaderCallback_ThreadTaskCreate, 289
OTF2_EvtReaderCallbacks_SetOmpAcquireLockCallback, 301
- OTF2_EvtReaderCallback_ThreadTaskSwitch, 290
OTF2_EvtReaderCallbacks_SetOmpForkCallback, 301
- OTF2_EvtReaderCallback_ThreadTeamBegin, 291
OTF2_EvtReaderCallbacks_SetOmpJoinCallback, 302
- OTF2_EvtReaderCallback_ThreadTeamEnd, 292
OTF2_EvtReaderCallbacks_SetOmpReleaseLockCallback, 302
- OTF2_EvtReaderCallback_Unknown, 292
OTF2_EvtReaderCallbacks_SetOmpTaskCompleteCallback, 303
- OTF2_EvtReaderCallbacks_Clear, 293
OTF2_EvtReaderCallbacks_Delete, 293
OTF2_EvtReaderCallbacks_SetOmpTaskCreateCallback, 303
OTF2_EvtReaderCallbacks_SetOmpTaskSwitchCallback, 304
- OTF2_EvtReaderCallbacks_New, 293
OTF2_EvtReaderCallbacks_SetBufferFlushCallback, 294
OTF2_EvtReaderCallbacks_SetEnterCallback, 294
OTF2_EvtReaderCallbacks_SetLeaveCallback, 295
OTF2_EvtReaderCallbacks_SetMeasurementCallback, 295
OTF2_EvtReaderCallbacks_SetMetricCallback, 296
OTF2_EvtReaderCallbacks_SetMpiCollectiveBeginCallback, 296
OTF2_EvtReaderCallbacks_SetMpiCollectiveEndCallback, 296
OTF2_EvtReaderCallbacks_SetMpiIrecvCallback, 297
OTF2_EvtReaderCallbacks_SetMpiIrecvRequestCallback, 297
OTF2_EvtReaderCallbacks_SetMpiIsendCallback, 298
OTF2_EvtReaderCallbacks_SetMpiIsendRequestCallback, 298
- OTF2_EvtReaderCallbacks_SetParameterIntCallback, 304
OTF2_EvtReaderCallbacks_SetParameterStringCallback, 305
OTF2_EvtReaderCallbacks_SetParameterUnsignedIntCallback, 305
OTF2_EvtReaderCallbacks_SetRmaAcquireLockCallback, 306
OTF2_EvtReaderCallbacks_SetRmaAtomicCallback, 306
OTF2_EvtReaderCallbacks_SetRmaCollectiveBeginCallback, 307
OTF2_EvtReaderCallbacks_SetRmaCollectiveEndCallback, 307
OTF2_EvtReaderCallbacks_SetRmaGetCallback, 308
OTF2_EvtReaderCallbacks_SetRmaGroupSyncCallback, 308
OTF2_EvtReaderCallbacks_SetRmaOpCompleteBlockingCallback, 309
OTF2_EvtReaderCallbacks_SetRmaOpCompleteNonBlockingCallback, 309

INDEX

- OTF2_EvtReaderCallbacks_SetRmaOpOTF2_EvtReaderCallbacks_New
310 OTF2_EvtReaderCallbacks.h, 293
- OTF2_EvtReaderCallbacks_SetRmaOpOTF2_EvtReaderCallbacks_SetBufferFlushCallback
311 OTF2_EvtReaderCallbacks.h, 294
- OTF2_EvtReaderCallbacks_SetRmaOpOTF2_EvtReaderCallbacks_SetEnterCallback
311 OTF2_EvtReaderCallbacks.h, 294
- OTF2_EvtReaderCallbacks_SetRmaOpOTF2_EvtReaderCallbacks_SetLeaveCallback
311 OTF2_EvtReaderCallbacks.h, 295
- OTF2_EvtReaderCallbacks_SetRmaOpOTF2_EvtReaderCallbacks_SetMeasurementOnOffCallback
312 OTF2_EvtReaderCallbacks.h, 295
- OTF2_EvtReaderCallbacks_SetRmaOpOTF2_EvtReaderCallbacks_SetMetricCallback
312 OTF2_EvtReaderCallbacks.h, 296
- OTF2_EvtReaderCallbacks_SetRmaOpOTF2_EvtReaderCallbacks_SetMpiCollectiveBeginCallback
313 OTF2_EvtReaderCallbacks.h, 296
- OTF2_EvtReaderCallbacks_SetRmaOpOTF2_EvtReaderCallbacks_SetMpiCollectiveEndCallback
313 OTF2_EvtReaderCallbacks.h, 296
- OTF2_EvtReaderCallbacks_SetRmaOpOTF2_EvtReaderCallbacks_SetMpiIrecvCallback
314 OTF2_EvtReaderCallbacks.h, 297
- OTF2_EvtReaderCallbacks_SetRmaOpOTF2_EvtReaderCallbacks_SetMpiIrecvRequestCallback
314 OTF2_EvtReaderCallbacks.h, 297
- OTF2_EvtReaderCallbacks_SetThreadOTF2_EvtReaderCallbacks_SetMpiIsendCallback
315 OTF2_EvtReaderCallbacks.h, 298
- OTF2_EvtReaderCallbacks_SetThreadOTF2_EvtReaderCallbacks_SetMpiIsendCompleteCallback
315 OTF2_EvtReaderCallbacks.h, 298
- OTF2_EvtReaderCallbacks_SetThreadOTF2_EvtReaderCallbacks_SetMpiRecvCallback
316 OTF2_EvtReaderCallbacks.h, 299
- OTF2_EvtReaderCallbacks_SetThreadOTF2_EvtReaderCallbacks_SetMpiRequestCancelledCallback
316 OTF2_EvtReaderCallbacks.h, 299
- OTF2_EvtReaderCallbacks_SetThreadOTF2_EvtReaderCallbacks_SetMpiRequestTestCallback
317 OTF2_EvtReaderCallbacks.h, 300
- OTF2_EvtReaderCallbacks_SetThreadOTF2_EvtReaderCallbacks_SetMpiSendCallback
317 OTF2_EvtReaderCallbacks.h, 300
- OTF2_EvtReaderCallbacks_SetThreadOTF2_EvtReaderCallbacks_SetOmpAcquireLockCallback
318 OTF2_EvtReaderCallbacks.h, 301
- OTF2_EvtReaderCallbacks_SetThreadOTF2_EvtReaderCallbacks_SetOmpForkCallback
318 OTF2_EvtReaderCallbacks.h, 301
- OTF2_EvtReaderCallbacks_SetThreadOTF2_EvtReaderCallbacks_SetOmpJoinCallback
319 OTF2_EvtReaderCallbacks.h, 302
- OTF2_EvtReaderCallbacks_SetUnknownOTF2_EvtReaderCallbacks_SetOmpReleaseLockCallback
319 OTF2_EvtReaderCallbacks.h, 302
- OTF2_EvtReaderCallbacks_Clear OTF2_EvtReaderCallbacks_SetOmpTaskCompleteCallback
OTF2_EvtReaderCallbacks.h, 293 OTF2_EvtReaderCallbacks.h, 303
- OTF2_EvtReaderCallbacks_Delete OTF2_EvtReaderCallbacks_SetOmpTaskCreateCallback
OTF2_EvtReaderCallbacks.h, 293 OTF2_EvtReaderCallbacks.h, 303
-

[OTF2_EvtReaderCallbacks_SetOmpTaskSetCallback](#), [OTF2_EvtReaderCallbacks_SetThreadAcquireLockCallback](#)
[OTF2_EvtReaderCallbacks.h](#), [304](#) [OTF2_EvtReaderCallbacks.h](#), [315](#)
[OTF2_EvtReaderCallbacks_SetParameterCallback](#), [OTF2_EvtReaderCallbacks_SetThreadForkCallback](#)
[OTF2_EvtReaderCallbacks.h](#), [304](#) [OTF2_EvtReaderCallbacks.h](#), [315](#)
[OTF2_EvtReaderCallbacks_SetParameterCallback](#), [OTF2_EvtReaderCallbacks_SetThreadJoinCallback](#)
[OTF2_EvtReaderCallbacks.h](#), [305](#) [OTF2_EvtReaderCallbacks.h](#), [316](#)
[OTF2_EvtReaderCallbacks_SetParameterCallback](#), [OTF2_EvtReaderCallbacks_SetThreadReleaseLockCallback](#)
[OTF2_EvtReaderCallbacks.h](#), [305](#) [OTF2_EvtReaderCallbacks.h](#), [316](#)
[OTF2_EvtReaderCallbacks_SetRmaAcquireLockCallback](#), [OTF2_EvtReaderCallbacks_SetThreadTaskCompleteCallback](#)
[OTF2_EvtReaderCallbacks.h](#), [306](#) [OTF2_EvtReaderCallbacks.h](#), [317](#)
[OTF2_EvtReaderCallbacks_SetRmaAtomCallback](#), [OTF2_EvtReaderCallbacks_SetThreadTaskCreateCallback](#)
[OTF2_EvtReaderCallbacks.h](#), [306](#) [OTF2_EvtReaderCallbacks.h](#), [317](#)
[OTF2_EvtReaderCallbacks_SetRmaCollectiveBeginCallback](#), [OTF2_EvtReaderCallbacks_SetThreadTaskSwitchCallback](#)
[OTF2_EvtReaderCallbacks.h](#), [307](#) [OTF2_EvtReaderCallbacks.h](#), [318](#)
[OTF2_EvtReaderCallbacks_SetRmaCollectiveEndCallback](#), [OTF2_EvtReaderCallbacks_SetThreadTeamBeginCallback](#)
[OTF2_EvtReaderCallbacks.h](#), [307](#) [OTF2_EvtReaderCallbacks.h](#), [318](#)
[OTF2_EvtReaderCallbacks_SetRmaGetCallback](#), [OTF2_EvtReaderCallbacks_SetThreadTeamEndCallback](#)
[OTF2_EvtReaderCallbacks.h](#), [308](#) [OTF2_EvtReaderCallbacks.h](#), [319](#)
[OTF2_EvtReaderCallbacks_SetRmaGroupSyncCallback](#), [OTF2_EvtReaderCallbacks_SetUnknownCallback](#)
[OTF2_EvtReaderCallbacks.h](#), [308](#) [OTF2_EvtReaderCallbacks.h](#), [319](#)
[OTF2_EvtReaderCallbacks_SetRmaOpCompleteCallback](#), [OTF2_EvtWriter_BufferFlush](#), [328](#)
[OTF2_EvtReaderCallbacks_SetRmaOpCompleteCallback](#), [OTF2_EvtWriter_RewindPoint](#),
[OTF2_EvtReaderCallbacks.h](#), [309](#) [328](#)
[OTF2_EvtReaderCallbacks_SetRmaOpCompleteCallback](#), [OTF2_EvtWriter_Enter](#), [329](#)
[OTF2_EvtReaderCallbacks.h](#), [310](#) [OTF2_EvtWriter_GetLocationID](#), [329](#)
[OTF2_EvtReaderCallbacks_SetRmaOpTestCallback](#), [OTF2_EvtWriter_GetNumberOfEvents](#),
[OTF2_EvtReaderCallbacks.h](#), [311](#) [330](#)
[OTF2_EvtReaderCallbacks_SetRmaPutCallback](#), [OTF2_EvtWriter_GetUserData](#), [330](#)
[OTF2_EvtReaderCallbacks.h](#), [311](#) [OTF2_EvtWriter_Leave](#), [331](#)
[OTF2_EvtReaderCallbacks_SetRmaReleaseLockCallback](#), [OTF2_EvtWriter_MeasurementOnOff](#),
[OTF2_EvtReaderCallbacks.h](#), [311](#) [331](#)
[OTF2_EvtReaderCallbacks_SetRmaRequestLockCallback](#), [OTF2_EvtWriter_Metric](#), [332](#)
[OTF2_EvtReaderCallbacks.h](#), [312](#) [OTF2_EvtWriter_MpiCollectiveBegin](#),
[OTF2_EvtReaderCallbacks_SetRmaSyncCallback](#) [332](#)
[OTF2_EvtReaderCallbacks.h](#), [312](#) [OTF2_EvtWriter_MpiCollectiveEnd](#),
[OTF2_EvtReaderCallbacks_SetRmaTryLockCallback](#) [333](#)
[OTF2_EvtReaderCallbacks.h](#), [313](#) [OTF2_EvtWriter_MpiIrecv](#), [334](#)
[OTF2_EvtReaderCallbacks_SetRmaWaitChangeCallback](#), [OTF2_EvtWriter_MpiIrecvRequest](#),
[OTF2_EvtReaderCallbacks.h](#), [313](#) [334](#)
[OTF2_EvtReaderCallbacks_SetRmaWinCreateCallback](#), [OTF2_EvtWriter_MpiIsend](#), [335](#)
[OTF2_EvtReaderCallbacks.h](#), [314](#) [OTF2_EvtWriter_MpiIsendComplete](#),
[OTF2_EvtReaderCallbacks_SetRmaWinDestroyCallback](#)
[OTF2_EvtReaderCallbacks.h](#), [314](#) [OTF2_EvtWriter_MpiRecv](#), [336](#)

INDEX

- OTF2_EvtWriter_MpiRequestCancelled, [337](#)
- OTF2_EvtWriter_MpiRequestTest, [337](#)
- OTF2_EvtWriter_MpiSend, [338](#)
- OTF2_EvtWriter_OmpAcquireLock, [339](#)
- OTF2_EvtWriter_OmpFork, [339](#)
- OTF2_EvtWriter_OmpJoin, [340](#)
- OTF2_EvtWriter_OmpReleaseLock, [341](#)
- OTF2_EvtWriter_OmpTaskComplete, [341](#)
- OTF2_EvtWriter_OmpTaskCreate, [342](#)
- OTF2_EvtWriter_OmpTaskSwitch, [343](#)
- OTF2_EvtWriter_ParameterInt, [343](#)
- OTF2_EvtWriter_ParameterString, [344](#)
- OTF2_EvtWriter_ParameterUnsignedInt, [345](#)
- OTF2_EvtWriter_Rewind, [345](#)
- OTF2_EvtWriter_RmaAcquireLock, [346](#)
- OTF2_EvtWriter_RmaAtomic, [346](#)
- OTF2_EvtWriter_RmaCollectiveBegin, [347](#)
- OTF2_EvtWriter_RmaCollectiveEnd, [347](#)
- OTF2_EvtWriter_RmaGet, [348](#)
- OTF2_EvtWriter_RmaGroupSync, [349](#)
- OTF2_EvtWriter_RmaOpCompleteBlocking, [350](#)
- OTF2_EvtWriter_RmaOpCompleteNonBlocking, [350](#)
- OTF2_EvtWriter_RmaOpCompleteRemote, [351](#)
- OTF2_EvtWriter_RmaOpTest, [351](#)
- OTF2_EvtWriter_RmaPut, [352](#)
- OTF2_EvtWriter_RmaReleaseLock, [353](#)
- OTF2_EvtWriter_RmaRequestLock, [353](#)
- OTF2_EvtWriter_RmaSync, [354](#)
- OTF2_EvtWriter_RmaTryLock, [355](#)
- OTF2_EvtWriter_RmaWaitChange, [355](#)
- OTF2_EvtWriter_RmaWinCreate, [356](#)
- OTF2_EvtWriter_RmaWinDestroy, [356](#)
- OTF2_EvtWriter_SetLocationID, [357](#)
- OTF2_EvtWriter_SetUserData, [357](#)
- OTF2_EvtWriter_StoreRewindPoint, [358](#)
- OTF2_EvtWriter_ThreadAcquireLock, [358](#)
- OTF2_EvtWriter_ThreadFork, [359](#)
- OTF2_EvtWriter_ThreadJoin, [359](#)
- OTF2_EvtWriter_ThreadReleaseLock, [360](#)
- OTF2_EvtWriter_ThreadTaskComplete, [360](#)
- OTF2_EvtWriter_ThreadTaskCreate, [361](#)
- OTF2_EvtWriter_ThreadTaskSwitch, [362](#)
- OTF2_EvtWriter_ThreadTeamBegin, [362](#)
- OTF2_EvtWriter_ThreadTeamEnd, [363](#)
- OTF2_EvtWriter_BufferFlush
- OTF2_EvtWriter.h, [328](#)
- OTF2_EvtWriter_ClearRewindPoint
- OTF2_EvtWriter.h, [328](#)
- OTF2_EvtWriter_Enter
- OTF2_EvtWriter.h, [329](#)
- OTF2_EvtWriter_GetLocationID
- OTF2_EvtWriter.h, [329](#)
- OTF2_EvtWriter_GetNumberOfEvents
- OTF2_EvtWriter.h, [330](#)
- OTF2_EvtWriter_GetUserData
- OTF2_EvtWriter.h, [330](#)
- OTF2_EvtWriter_Leave
- OTF2_EvtWriter.h, [331](#)
- OTF2_EvtWriter_MeasurementOnOff
- OTF2_EvtWriter.h, [331](#)
- OTF2_EvtWriter_Metric
- OTF2_EvtWriter.h, [332](#)
- OTF2_EvtWriter_MpiCollectiveBegin

-
- OTF2_EvtWriter.h, 332
- OTF2_EvtWriter_MpiCollectiveEnd
OTF2_EvtWriter.h, 333
- OTF2_EvtWriter_MpiIrecv
OTF2_EvtWriter.h, 334
- OTF2_EvtWriter_MpiIrecvRequest
OTF2_EvtWriter.h, 334
- OTF2_EvtWriter_MpiIsend
OTF2_EvtWriter.h, 335
- OTF2_EvtWriter_MpiIsendComplete
OTF2_EvtWriter.h, 336
- OTF2_EvtWriter_MpiRecv
OTF2_EvtWriter.h, 336
- OTF2_EvtWriter_MpiRequestCancelled
OTF2_EvtWriter.h, 337
- OTF2_EvtWriter_MpiRequestTest
OTF2_EvtWriter.h, 337
- OTF2_EvtWriter_MpiSend
OTF2_EvtWriter.h, 338
- OTF2_EvtWriter_OmpAcquireLock
OTF2_EvtWriter.h, 339
- OTF2_EvtWriter_OmpFork
OTF2_EvtWriter.h, 339
- OTF2_EvtWriter_OmpJoin
OTF2_EvtWriter.h, 340
- OTF2_EvtWriter_OmpReleaseLock
OTF2_EvtWriter.h, 341
- OTF2_EvtWriter_OmpTaskComplete
OTF2_EvtWriter.h, 341
- OTF2_EvtWriter_OmpTaskCreate
OTF2_EvtWriter.h, 342
- OTF2_EvtWriter_OmpTaskSwitch
OTF2_EvtWriter.h, 343
- OTF2_EvtWriter_ParameterInt
OTF2_EvtWriter.h, 343
- OTF2_EvtWriter_ParameterString
OTF2_EvtWriter.h, 344
- OTF2_EvtWriter_ParameterUnsignedInt
OTF2_EvtWriter.h, 345
- OTF2_EvtWriter_Rewind
OTF2_EvtWriter.h, 345
- OTF2_EvtWriter_RmaAcquireLock
OTF2_EvtWriter.h, 346
- OTF2_EvtWriter_RmaAtomic
OTF2_EvtWriter.h, 346
- OTF2_EvtWriter_RmaCollectiveBegin
OTF2_EvtWriter.h, 347
- OTF2_EvtWriter_RmaCollectiveEnd
OTF2_EvtWriter.h, 347
- OTF2_EvtWriter_RmaGet
OTF2_EvtWriter.h, 348
- OTF2_EvtWriter_RmaGroupSync
OTF2_EvtWriter.h, 349
- OTF2_EvtWriter_RmaOpCompleteBlocking
OTF2_EvtWriter.h, 350
- OTF2_EvtWriter_RmaOpCompleteNonBlocking
OTF2_EvtWriter.h, 350
- OTF2_EvtWriter_RmaOpCompleteRemote
OTF2_EvtWriter.h, 351
- OTF2_EvtWriter_RmaOpTest
OTF2_EvtWriter.h, 351
- OTF2_EvtWriter_RmaPut
OTF2_EvtWriter.h, 352
- OTF2_EvtWriter_RmaReleaseLock
OTF2_EvtWriter.h, 353
- OTF2_EvtWriter_RmaRequestLock
OTF2_EvtWriter.h, 353
- OTF2_EvtWriter_RmaSync
OTF2_EvtWriter.h, 354
- OTF2_EvtWriter_RmaTryLock
OTF2_EvtWriter.h, 355
- OTF2_EvtWriter_RmaWaitChange
OTF2_EvtWriter.h, 355
- OTF2_EvtWriter_RmaWinCreate
OTF2_EvtWriter.h, 356
- OTF2_EvtWriter_RmaWinDestroy
OTF2_EvtWriter.h, 356
- OTF2_EvtWriter_SetLocationID
OTF2_EvtWriter.h, 357
- OTF2_EvtWriter_SetUserData
OTF2_EvtWriter.h, 357
- OTF2_EvtWriter_StoreRewindPoint
OTF2_EvtWriter.h, 358
- OTF2_EvtWriter_ThreadAcquireLock
OTF2_EvtWriter.h, 358
- OTF2_EvtWriter_ThreadFork
OTF2_EvtWriter.h, 359
- OTF2_EvtWriter_ThreadJoin

INDEX

- OTF2_EvtWriter.h, 359
- OTF2_EvtWriter_ThreadReleaseLock
 - OTF2_EvtWriter.h, 360
- OTF2_EvtWriter_ThreadTaskComplete
 - OTF2_EvtWriter.h, 360
- OTF2_EvtWriter_ThreadTaskCreate
 - OTF2_EvtWriter.h, 361
- OTF2_EvtWriter_ThreadTaskSwitch
 - OTF2_EvtWriter.h, 362
- OTF2_EvtWriter_ThreadTeamBegin
 - OTF2_EvtWriter.h, 362
- OTF2_EvtWriter_ThreadTeamEnd
 - OTF2_EvtWriter.h, 363
- OTF2_FileMode_enum
 - OTF2_GeneralDefinitions.h, 372
- OTF2_FileSionCallbacks, 91
- OTF2_FileSionClose
 - OTF2_Callbacks.h, 154
- OTF2_FileSionGetRank
 - OTF2_Callbacks.h, 154
- OTF2_FileSionOpen
 - OTF2_Callbacks.h, 154
- OTF2_FileSubstrate_enum
 - OTF2_GeneralDefinitions.h, 372
- OTF2_FileType_enum
 - OTF2_GeneralDefinitions.h, 373
- OTF2_FlushCallbacks, 92
- OTF2_FlushType_enum
 - OTF2_GeneralDefinitions.h, 373
- OTF2_GeneralDefinitions.h, 363
 - OTF2_CallbackCode, 371
 - OTF2_Compression_enum, 372
 - OTF2_FileMode_enum, 372
 - OTF2_FileSubstrate_enum, 372
 - OTF2_FileType_enum, 373
 - OTF2_FlushType_enum, 373
 - OTF2_MappingType_enum, 373
 - OTF2_Paradigm_enum, 374
 - OTF2_ThumbnailType_enum, 375
 - OTF2_Type_enum, 375
 - OTF2_UNDEFINED_TYPE, 371
- OTF2_GlobalDefReader.h, 376
 - OTF2_GlobalDefReader_ReadDefinitions, 377
- OTF2_GlobalDefReader_SetCallbacks, 377
- OTF2_GlobalDefReader_ReadDefinitions
 - OTF2_GlobalDefReader.h, 377
- OTF2_GlobalDefReader_SetCallbacks
 - OTF2_GlobalDefReader.h, 377
- OTF2_GlobalDefReaderCallback_Attribute
 - OTF2_GlobalDefReaderCallbacks.h, 384
- OTF2_GlobalDefReaderCallback_Callpath
 - OTF2_GlobalDefReaderCallbacks.h, 384
- OTF2_GlobalDefReaderCallback_Callsite
 - OTF2_GlobalDefReaderCallbacks.h, 385
- OTF2_GlobalDefReaderCallback_ClockProperties
 - OTF2_GlobalDefReaderCallbacks.h, 386
- OTF2_GlobalDefReaderCallback_Comm
 - OTF2_GlobalDefReaderCallbacks.h, 386
- OTF2_GlobalDefReaderCallback_Group
 - OTF2_GlobalDefReaderCallbacks.h, 387
- OTF2_GlobalDefReaderCallback_Location
 - OTF2_GlobalDefReaderCallbacks.h, 388
- OTF2_GlobalDefReaderCallback_LocationGroup
 - OTF2_GlobalDefReaderCallbacks.h, 388
- OTF2_GlobalDefReaderCallback_MetricClass
 - OTF2_GlobalDefReaderCallbacks.h, 389
- OTF2_GlobalDefReaderCallback_MetricClassRecorder
 - OTF2_GlobalDefReaderCallbacks.h, 390
- OTF2_GlobalDefReaderCallback_MetricInstance
 - OTF2_GlobalDefReaderCallbacks.h, 390
- OTF2_GlobalDefReaderCallback_MetricMember
 - OTF2_GlobalDefReaderCallbacks.h, 391
- OTF2_GlobalDefReaderCallback_Parameter

- OTF2_GlobalDefReaderCallbacks.h, 392
- OTF2_GlobalDefReaderCallback_Region
OTF2_GlobalDefReaderCallbacks.h, 393
- OTF2_GlobalDefReaderCallback_RmaWin
OTF2_GlobalDefReaderCallbacks.h, 393
- OTF2_GlobalDefReaderCallback_String
OTF2_GlobalDefReaderCallbacks.h, 394
- OTF2_GlobalDefReaderCallback_SystemTreeNodeDomain
OTF2_GlobalDefReaderCallbacks.h, 395
- OTF2_GlobalDefReaderCallback_SystemTreeNodeDomainProperty
OTF2_GlobalDefReaderCallbacks.h, 395
- OTF2_GlobalDefReaderCallback_SystemTreeNodeProperty
OTF2_GlobalDefReaderCallbacks.h, 396
- OTF2_GlobalDefReaderCallback_Unknown
OTF2_GlobalDefReaderCallbacks.h, 396
- OTF2_GlobalDefReaderCallbacks.h, 378
- OTF2_GlobalDefReaderCallback_-
Attribute, 384
- OTF2_GlobalDefReaderCallback_-
Callpath, 384
- OTF2_GlobalDefReaderCallback_-
Callsite, 385
- OTF2_GlobalDefReaderCallback_-
ClockProperties, 386
- OTF2_GlobalDefReaderCallback_-
Comm, 386
- OTF2_GlobalDefReaderCallback_-
Group, 387
- OTF2_GlobalDefReaderCallback_-
Location, 388
- OTF2_GlobalDefReaderCallback_-
LocationGroup, 388
- OTF2_GlobalDefReaderCallback_-
MetricClass, 389
- OTF2_GlobalDefReaderCallback_-
MetricClassRecorder, 390
- OTF2_GlobalDefReaderCallback_-
MetricInstance, 390
- OTF2_GlobalDefReaderCallback_-
MetricMember, 391
- OTF2_GlobalDefReaderCallback_-
Parameter, 392
- OTF2_GlobalDefReaderCallback_-
Region, 393
- OTF2_GlobalDefReaderCallback_-
RmaWin, 393
- OTF2_GlobalDefReaderCallback_-
String, 394
- OTF2_GlobalDefReaderCallback_-
SystemTreeNode, 395
- OTF2_GlobalDefReaderCallback_-
SystemTreeNodeDomain, 395
- OTF2_GlobalDefReaderCallback_-
SystemTreeNodeProperty, 396
- OTF2_GlobalDefReaderCallback_-
Unknown, 396
- OTF2_GlobalDefReaderCallbacks_-
Clear, 397
- OTF2_GlobalDefReaderCallbacks_-
Delete, 397
- OTF2_GlobalDefReaderCallbacks_-
New, 397
- OTF2_GlobalDefReaderCallbacks_-
SetAttributeCallback, 397
- OTF2_GlobalDefReaderCallbacks_-
SetCallpathCallback, 398
- OTF2_GlobalDefReaderCallbacks_-
SetCallsiteCallback, 398
- OTF2_GlobalDefReaderCallbacks_-
SetClockPropertiesCallback, 399
- OTF2_GlobalDefReaderCallbacks_-
SetCommCallback, 399
- OTF2_GlobalDefReaderCallbacks_-
SetGroupCallback, 400
- OTF2_GlobalDefReaderCallbacks_-
SetLocationCallback, 400
- OTF2_GlobalDefReaderCallbacks_-
SetLocationGroupCallback, 401
- OTF2_GlobalDefReaderCallbacks_-
SetMetricClassCallback, 401

INDEX

- OTF2_GlobalDefReaderCallbacks_- SetMetricClassRecorderCallback, 402
OTF2_GlobalDefReaderCallbacks.h, 399
- OTF2_GlobalDefReaderCallbacks_- SetMetricInstanceCallback, 403
OTF2_GlobalDefReaderCallbacks_SetCommCallback
OTF2_GlobalDefReaderCallbacks.h, 399
- OTF2_GlobalDefReaderCallbacks_- SetMetricMemberCallback, 403
OTF2_GlobalDefReaderCallbacks_SetGroupCallback
OTF2_GlobalDefReaderCallbacks.h, 400
- OTF2_GlobalDefReaderCallbacks_- SetParameterCallback, 403
OTF2_GlobalDefReaderCallbacks_SetLocationCallback
OTF2_GlobalDefReaderCallbacks.h, 400
- OTF2_GlobalDefReaderCallbacks_- SetRegionCallback, 404
OTF2_GlobalDefReaderCallbacks_SetLocationGroupCallback
OTF2_GlobalDefReaderCallbacks.h, 401
- OTF2_GlobalDefReaderCallbacks_- SetRmaWinCallback, 404
OTF2_GlobalDefReaderCallbacks_SetMetricClassCallback
OTF2_GlobalDefReaderCallbacks.h, 401
- OTF2_GlobalDefReaderCallbacks_- SetStringCallback, 405
OTF2_GlobalDefReaderCallbacks_SetMetricClassRecorderCallback
OTF2_GlobalDefReaderCallbacks_SetSystemTreeNodeDomainCallback, 406
OTF2_GlobalDefReaderCallbacks.h, 406
- OTF2_GlobalDefReaderCallbacks_- SetSystemTreeNodePropertyCallback, 407
OTF2_GlobalDefReaderCallbacks_SetMetricInstanceCallback
OTF2_GlobalDefReaderCallbacks.h, 403
- OTF2_GlobalDefReaderCallbacks_- SetUnknownCallback, 407
OTF2_GlobalDefReaderCallbacks_SetMetricMemberCallback
OTF2_GlobalDefReaderCallbacks.h, 403
- OTF2_GlobalDefReaderCallbacks_Clear
OTF2_GlobalDefReaderCallbacks.h, 397
OTF2_GlobalDefReaderCallbacks_SetParameterCallback
OTF2_GlobalDefReaderCallbacks.h, 397
- OTF2_GlobalDefReaderCallbacks_Delete
OTF2_GlobalDefReaderCallbacks.h, 397
OTF2_GlobalDefReaderCallbacks_SetRegionCallback
OTF2_GlobalDefReaderCallbacks.h, 397
- OTF2_GlobalDefReaderCallbacks_New
OTF2_GlobalDefReaderCallbacks.h, 397
OTF2_GlobalDefReaderCallbacks_SetRmaWinCallback
OTF2_GlobalDefReaderCallbacks.h, 397
- OTF2_GlobalDefReaderCallbacks_SetAttributeCallback
OTF2_GlobalDefReaderCallbacks.h, 397
OTF2_GlobalDefReaderCallbacks_SetStringCallback
OTF2_GlobalDefReaderCallbacks.h, 397
- OTF2_GlobalDefReaderCallbacks_SetCallpathCallback
OTF2_GlobalDefReaderCallbacks.h, 398
OTF2_GlobalDefReaderCallbacks_SetSystemTreeNodeCallback
OTF2_GlobalDefReaderCallbacks.h, 398
- OTF2_GlobalDefReaderCallbacks_SetCallsiteCallback
OTF2_GlobalDefReaderCallbacks.h, 398
OTF2_GlobalDefReaderCallbacks_SetSystemTreeNodeDomainCallback
OTF2_GlobalDefReaderCallbacks.h, 398
- OTF2_GlobalDefReaderCallbacks_SetClockPropertyCallback

INDEX

- OTF2_GlobalDefReaderCallbacks_SetSystemTreeCallback, OTF2_GlobalDefWriter_WriteSystemTreeNode,
OTF2_GlobalDefReaderCallbacks.h, 423
407 OTF2_GlobalDefWriter_WriteSystemTreeNodeDomain,
OTF2_GlobalDefReaderCallbacks_SetUnknownCallback, 403
OTF2_GlobalDefReaderCallbacks.h, OTF2_GlobalDefWriter_WriteSystemTreeNodeProperty,
407 424
- OTF2_GlobalDefWriter.h, 408 OTF2_GlobalDefWriter_GetNumberOfDefinitions
OTF2_GlobalDefWriter_GetNumberOfDefinitions, OTF2_GlobalDefWriter.h, 411
411 OTF2_GlobalDefWriter_GetNumberOfLocations
OTF2_GlobalDefWriter_GetNumberOfLocations, OTF2_GlobalDefWriter.h, 412
412 OTF2_GlobalDefWriter_WriteAttribute
OTF2_GlobalDefWriter_WriteAttribute, OTF2_GlobalDefWriter.h, 412
412 OTF2_GlobalDefWriter_WriteCallpath
OTF2_GlobalDefWriter_WriteCallpath, OTF2_GlobalDefWriter.h, 413
413 OTF2_GlobalDefWriter_WriteCallsite
OTF2_GlobalDefWriter_WriteCallsite, OTF2_GlobalDefWriter.h, 413
413 OTF2_GlobalDefWriter_WriteClockProperties
OTF2_GlobalDefWriter_WriteClockProperties, OTF2_GlobalDefWriter.h, 414
414 OTF2_GlobalDefWriter_WriteComm
OTF2_GlobalDefWriter_WriteComm, OTF2_GlobalDefWriter.h, 414
414 OTF2_GlobalDefWriter_WriteGroup
OTF2_GlobalDefWriter_WriteGroup, OTF2_GlobalDefWriter.h, 415
415 OTF2_GlobalDefWriter_WriteLocation
OTF2_GlobalDefWriter_WriteLocation, OTF2_GlobalDefWriter.h, 416
416 OTF2_GlobalDefWriter_WriteLocationGroup
OTF2_GlobalDefWriter_WriteLocationGroup, OTF2_GlobalDefWriter.h, 416
416 OTF2_GlobalDefWriter_WriteMetricClass
OTF2_GlobalDefWriter_WriteMetricClass, OTF2_GlobalDefWriter.h, 417
417 OTF2_GlobalDefWriter_WriteMetricClassRecorder
OTF2_GlobalDefWriter_WriteMetricClassRecorder, OTF2_GlobalDefWriter.h, 418
418 OTF2_GlobalDefWriter_WriteMetricInstance
OTF2_GlobalDefWriter_WriteMetricInstance, OTF2_GlobalDefWriter.h, 418
418 OTF2_GlobalDefWriter_WriteMetricMember
OTF2_GlobalDefWriter_WriteMetricMember, OTF2_GlobalDefWriter.h, 419
419 OTF2_GlobalDefWriter_WriteMetricMember
OTF2_GlobalDefWriter_WriteMetricMember, OTF2_GlobalDefWriter.h, 419
419 OTF2_GlobalDefWriter_WriteParameter
OTF2_GlobalDefWriter_WriteParameter, OTF2_GlobalDefWriter.h, 420
420 OTF2_GlobalDefWriter_WriteRegion
OTF2_GlobalDefWriter_WriteRegion, OTF2_GlobalDefWriter.h, 421
421 OTF2_GlobalDefWriter_WriteRegion
OTF2_GlobalDefWriter_WriteRegion, OTF2_GlobalDefWriter.h, 421
421 OTF2_GlobalDefWriter_WriteRmaWin
OTF2_GlobalDefWriter_WriteRmaWin, OTF2_GlobalDefWriter.h, 422
422 OTF2_GlobalDefWriter_WriteString
OTF2_GlobalDefWriter_WriteString, OTF2_GlobalDefWriter.h, 422
422 OTF2_GlobalDefWriter_WriteSystemTreeNode
OTF2_GlobalDefWriter_WriteSystemTreeNode, OTF2_GlobalDefWriter.h, 423
422

INDEX

OTF2_GlobalDefWriter_WriteSystemTreeNode, 423
OTF2_GlobalDefWriter.h, 423

OTF2_GlobalDefWriter_WriteSystemTree, 424
OTF2_GlobalDefWriter.h, 424

OTF2_GlobalEvtReader.h, 424

OTF2_GlobalEvtReader_HasEvent, 426

OTF2_GlobalEvtReader_ReadEvent, 426

OTF2_GlobalEvtReader_ReadEvents, 426

OTF2_GlobalEvtReader_SetCallbacks, 427

OTF2_GlobalEvtReader_HasEvent
OTF2_GlobalEvtReader.h, 426

OTF2_GlobalEvtReader_ReadEvent
OTF2_GlobalEvtReader.h, 426

OTF2_GlobalEvtReader_ReadEvents
OTF2_GlobalEvtReader.h, 426

OTF2_GlobalEvtReader_SetCallbacks
OTF2_GlobalEvtReader.h, 427

OTF2_GlobalEvtReaderCallback_BufferFlush
OTF2_GlobalEvtReaderCallbacks.h, 442

OTF2_GlobalEvtReaderCallback_Enter
OTF2_GlobalEvtReaderCallbacks.h, 442

OTF2_GlobalEvtReaderCallback_Leave
OTF2_GlobalEvtReaderCallbacks.h, 443

OTF2_GlobalEvtReaderCallback_MeasurementOnOff
OTF2_GlobalEvtReaderCallbacks.h, 444

OTF2_GlobalEvtReaderCallback_Metric
OTF2_GlobalEvtReaderCallbacks.h, 444

OTF2_GlobalEvtReaderCallback_MpiCollectiveBegin
OTF2_GlobalEvtReaderCallbacks.h, 445

OTF2_GlobalEvtReaderCallback_MpiCollectiveEnd
OTF2_GlobalEvtReaderCallbacks.h, 446

OTF2_GlobalEvtReaderCallback_MpiRecv
OTF2_GlobalEvtReaderCallbacks.h, 446

OTF2_GlobalEvtReaderCallback_MpiRecvRequest
OTF2_GlobalEvtReaderCallbacks.h, 447

OTF2_GlobalEvtReaderCallback_MpiSend
OTF2_GlobalEvtReaderCallbacks.h, 448

OTF2_GlobalEvtReaderCallback_MpiSendComplete
OTF2_GlobalEvtReaderCallbacks.h, 449

OTF2_GlobalEvtReaderCallback_MpiRecv
OTF2_GlobalEvtReaderCallbacks.h, 449

OTF2_GlobalEvtReaderCallback_MpiRequestCancelled
OTF2_GlobalEvtReaderCallbacks.h, 450

OTF2_GlobalEvtReaderCallback_MpiRequestTest
OTF2_GlobalEvtReaderCallbacks.h, 451

OTF2_GlobalEvtReaderCallback_MpiSend
OTF2_GlobalEvtReaderCallbacks.h, 451

OTF2_GlobalEvtReaderCallback_OmpAcquireLock
OTF2_GlobalEvtReaderCallbacks.h, 452

OTF2_GlobalEvtReaderCallback_OmpFork
OTF2_GlobalEvtReaderCallbacks.h, 453

OTF2_GlobalEvtReaderCallback_OmpJoin
OTF2_GlobalEvtReaderCallbacks.h, 453

OTF2_GlobalEvtReaderCallback_OmpReleaseLock
OTF2_GlobalEvtReaderCallbacks.h, 454

OTF2_GlobalEvtReaderCallback_OmpTaskComplete
OTF2_GlobalEvtReaderCallbacks.h, 455

OTF2_GlobalEvtReaderCallback_OmpTaskCreate
OTF2_GlobalEvtReaderCallbacks.h, 455

OTF2_GlobalEvtReaderCallback_OmpTaskSwitch
OTF2_GlobalEvtReaderCallbacks.h, 456

INDEX

OTF2_GlobalEvtReaderCallback_ParameterInOTF2_GlobalEvtReaderCallbacks.h,
OTF2_GlobalEvtReaderCallbacks.h, 467
457 OTF2_GlobalEvtReaderCallback_RmaRequestLock

OTF2_GlobalEvtReaderCallback_ParameterStorageOTF2_GlobalEvtReaderCallbacks.h,
OTF2_GlobalEvtReaderCallbacks.h, 467
457 OTF2_GlobalEvtReaderCallback_RmaSync

OTF2_GlobalEvtReaderCallback_ParameterUnsignedIntOTF2_GlobalEvtReaderCallbacks.h,
OTF2_GlobalEvtReaderCallbacks.h, 468
458 OTF2_GlobalEvtReaderCallback_RmaTryLock

OTF2_GlobalEvtReaderCallback_RmaAcquireLockOTF2_GlobalEvtReaderCallbacks.h,
OTF2_GlobalEvtReaderCallbacks.h, 469
459 OTF2_GlobalEvtReaderCallback_RmaWaitChange

OTF2_GlobalEvtReaderCallback_RmaAtomicOTF2_GlobalEvtReaderCallbacks.h,
OTF2_GlobalEvtReaderCallbacks.h, 469
459 OTF2_GlobalEvtReaderCallback_RmaWinCreate

OTF2_GlobalEvtReaderCallback_RmaCollectiveBeginOTF2_GlobalEvtReaderCallbacks.h,
OTF2_GlobalEvtReaderCallbacks.h, 470
460 OTF2_GlobalEvtReaderCallback_RmaWinDestroy

OTF2_GlobalEvtReaderCallback_RmaCollectiveEndOTF2_GlobalEvtReaderCallbacks.h,
OTF2_GlobalEvtReaderCallbacks.h, 471
461 OTF2_GlobalEvtReaderCallback_ThreadAcquireLock

OTF2_GlobalEvtReaderCallback_RmaGetOTF2_GlobalEvtReaderCallbacks.h,
OTF2_GlobalEvtReaderCallbacks.h, 471
462 OTF2_GlobalEvtReaderCallback_ThreadFork

OTF2_GlobalEvtReaderCallback_RmaGroupSyncOTF2_GlobalEvtReaderCallbacks.h,
OTF2_GlobalEvtReaderCallbacks.h, 472
462 OTF2_GlobalEvtReaderCallback_ThreadJoin

OTF2_GlobalEvtReaderCallback_RmaOpCompleteBlockingOTF2_GlobalEvtReaderCallbacks.h,
OTF2_GlobalEvtReaderCallbacks.h, 473
463 OTF2_GlobalEvtReaderCallback_ThreadReleaseLock

OTF2_GlobalEvtReaderCallback_RmaOpCompleteNonBlockingOTF2_GlobalEvtReaderCallbacks.h,
OTF2_GlobalEvtReaderCallbacks.h, 473
464 OTF2_GlobalEvtReaderCallback_ThreadTaskComplete

OTF2_GlobalEvtReaderCallback_RmaOpCompleteRemoteOTF2_GlobalEvtReaderCallbacks.h,
OTF2_GlobalEvtReaderCallbacks.h, 474
465 OTF2_GlobalEvtReaderCallback_ThreadTaskCreate

OTF2_GlobalEvtReaderCallback_RmaOpTestOTF2_GlobalEvtReaderCallbacks.h,
OTF2_GlobalEvtReaderCallbacks.h, 475
465 OTF2_GlobalEvtReaderCallback_ThreadTaskSwitch

OTF2_GlobalEvtReaderCallback_RmaPutOTF2_GlobalEvtReaderCallbacks.h,
OTF2_GlobalEvtReaderCallbacks.h, 475
466 OTF2_GlobalEvtReaderCallback_ThreadTeamBegin

OTF2_GlobalEvtReaderCallback_RmaReleaseLockOTF2_GlobalEvtReaderCallbacks.h,
476

INDEX

OTF2_GlobalEvtReaderCallback_ThreadPool, 477
OTF2_GlobalEvtReaderCallbacks.h, 477
OTF2_GlobalEvtReaderCallback_Unknown, 477
OTF2_GlobalEvtReaderCallbacks.h, 427
OTF2_GlobalEvtReaderCallback_-BufferFlush, 442
OTF2_GlobalEvtReaderCallback_-Enter, 442
OTF2_GlobalEvtReaderCallback_-Leave, 443
OTF2_GlobalEvtReaderCallback_-MeasurementOnOff, 444
OTF2_GlobalEvtReaderCallback_-Metric, 444
OTF2_GlobalEvtReaderCallback_-MpiCollectiveBegin, 445
OTF2_GlobalEvtReaderCallback_-MpiCollectiveEnd, 446
OTF2_GlobalEvtReaderCallback_-MpiIrecv, 446
OTF2_GlobalEvtReaderCallback_-MpiIrecvRequest, 447
OTF2_GlobalEvtReaderCallback_-MpiIsend, 448
OTF2_GlobalEvtReaderCallback_-MpiIsendComplete, 449
OTF2_GlobalEvtReaderCallback_-MpiRecv, 449
OTF2_GlobalEvtReaderCallback_-MpiRequestCancelled, 450
OTF2_GlobalEvtReaderCallback_-MpiRequestTest, 451
OTF2_GlobalEvtReaderCallback_-MpiSend, 451
OTF2_GlobalEvtReaderCallback_-OmpAcquireLock, 452
OTF2_GlobalEvtReaderCallback_-OmpFork, 453
OTF2_GlobalEvtReaderCallback_-OmpJoin, 453
OTF2_GlobalEvtReaderCallback_-OmpReleaseLock, 454
OTF2_GlobalEvtReaderCallback_-OmpTaskComplete, 455
OTF2_GlobalEvtReaderCallback_-OmpTaskCreate, 455
OTF2_GlobalEvtReaderCallback_-OmpTaskSwitch, 456
OTF2_GlobalEvtReaderCallback_-ParameterInt, 457
OTF2_GlobalEvtReaderCallback_-ParameterString, 457
OTF2_GlobalEvtReaderCallback_-ParameterUnsignedInt, 458
OTF2_GlobalEvtReaderCallback_-RmaAcquireLock, 459
OTF2_GlobalEvtReaderCallback_-RmaAtomic, 459
OTF2_GlobalEvtReaderCallback_-RmaCollectiveBegin, 460
OTF2_GlobalEvtReaderCallback_-RmaCollectiveEnd, 461
OTF2_GlobalEvtReaderCallback_-RmaGet, 462
OTF2_GlobalEvtReaderCallback_-RmaGroupSync, 462
OTF2_GlobalEvtReaderCallback_-RmaOpCompleteBlocking, 463
OTF2_GlobalEvtReaderCallback_-RmaOpCompleteNonBlocking, 464
OTF2_GlobalEvtReaderCallback_-RmaOpCompleteRemote, 465
OTF2_GlobalEvtReaderCallback_-RmaOpTest, 465
OTF2_GlobalEvtReaderCallback_-RmaPut, 466
OTF2_GlobalEvtReaderCallback_-RmaReleaseLock, 467
OTF2_GlobalEvtReaderCallback_-RmaRequestLock, 467
OTF2_GlobalEvtReaderCallback_-RmaSync, 468

-
- OTF2_GlobalEvtReaderCallback_-
RmaTryLock, [469](#)
 - OTF2_GlobalEvtReaderCallback_-
RmaWaitChange, [469](#)
 - OTF2_GlobalEvtReaderCallback_-
RmaWinCreate, [470](#)
 - OTF2_GlobalEvtReaderCallback_-
RmaWinDestroy, [471](#)
 - OTF2_GlobalEvtReaderCallback_-
ThreadAcquireLock, [471](#)
 - OTF2_GlobalEvtReaderCallback_-
ThreadFork, [472](#)
 - OTF2_GlobalEvtReaderCallback_-
ThreadJoin, [473](#)
 - OTF2_GlobalEvtReaderCallback_-
ThreadReleaseLock, [473](#)
 - OTF2_GlobalEvtReaderCallback_-
ThreadTaskComplete, [474](#)
 - OTF2_GlobalEvtReaderCallback_-
ThreadTaskCreate, [475](#)
 - OTF2_GlobalEvtReaderCallback_-
ThreadTaskSwitch, [475](#)
 - OTF2_GlobalEvtReaderCallback_-
ThreadTeamBegin, [476](#)
 - OTF2_GlobalEvtReaderCallback_-
ThreadTeamEnd, [477](#)
 - OTF2_GlobalEvtReaderCallback_-
Unknown, [477](#)
 - OTF2_GlobalEvtReaderCallbacks_-
Clear, [478](#)
 - OTF2_GlobalEvtReaderCallbacks_-
Delete, [478](#)
 - OTF2_GlobalEvtReaderCallbacks_-
New, [478](#)
 - OTF2_GlobalEvtReaderCallbacks_-
SetBufferFlushCallback, [479](#)
 - OTF2_GlobalEvtReaderCallbacks_-
SetEnterCallback, [479](#)
 - OTF2_GlobalEvtReaderCallbacks_-
SetLeaveCallback, [480](#)
 - OTF2_GlobalEvtReaderCallbacks_-
SetMeasurementOnOffCallback,
[480](#)
 - OTF2_GlobalEvtReaderCallbacks_-
SetMetricCallback, [481](#)
 - OTF2_GlobalEvtReaderCallbacks_-
SetMpiCollectiveBeginCallback,
[481](#)
 - OTF2_GlobalEvtReaderCallbacks_-
SetMpiCollectiveEndCallback,
[482](#)
 - OTF2_GlobalEvtReaderCallbacks_-
SetMpiIrecvCallback, [482](#)
 - OTF2_GlobalEvtReaderCallbacks_-
SetMpiIrecvRequestCallback, [483](#)
 - OTF2_GlobalEvtReaderCallbacks_-
SetMpiIsendCallback, [483](#)
 - OTF2_GlobalEvtReaderCallbacks_-
SetMpiIsendCompleteCallback,
[484](#)
 - OTF2_GlobalEvtReaderCallbacks_-
SetMpiRecvCallback, [484](#)
 - OTF2_GlobalEvtReaderCallbacks_-
SetMpiRequestCancelledCallback,
[485](#)
 - OTF2_GlobalEvtReaderCallbacks_-
SetMpiRequestTestCallback, [485](#)
 - OTF2_GlobalEvtReaderCallbacks_-
SetMpiSendCallback, [486](#)
 - OTF2_GlobalEvtReaderCallbacks_-
SetOmpAcquireLockCallback,
[486](#)
 - OTF2_GlobalEvtReaderCallbacks_-
SetOmpForkCallback, [487](#)
 - OTF2_GlobalEvtReaderCallbacks_-
SetOmpJoinCallback, [487](#)
 - OTF2_GlobalEvtReaderCallbacks_-
SetOmpReleaseLockCallback, [488](#)
 - OTF2_GlobalEvtReaderCallbacks_-
SetOmpTaskCompleteCallback,
[488](#)
 - OTF2_GlobalEvtReaderCallbacks_-
SetOmpTaskCreateCallback, [489](#)
 - OTF2_GlobalEvtReaderCallbacks_-
SetOmpTaskSwitchCallback, [489](#)
 - OTF2_GlobalEvtReaderCallbacks_-
SetParameterIntCallback, [490](#)

INDEX

- OTF2_GlobalEvtReaderCallbacks_-
 SetParameterStringCallback, [490](#)
- OTF2_GlobalEvtReaderCallbacks_-
 SetParameterUnsignedIntCallback,
 [491](#)
- OTF2_GlobalEvtReaderCallbacks_-
 SetRmaAcquireLockCallback, [492](#)
- OTF2_GlobalEvtReaderCallbacks_-
 SetRmaAtomicCallback, [492](#)
- OTF2_GlobalEvtReaderCallbacks_-
 SetRmaCollectiveBeginCallback,
 [493](#)
- OTF2_GlobalEvtReaderCallbacks_-
 SetRmaCollectiveEndCallback,
 [493](#)
- OTF2_GlobalEvtReaderCallbacks_-
 SetRmaGetCallback, [494](#)
- OTF2_GlobalEvtReaderCallbacks_-
 SetRmaGroupSyncCallback, [494](#)
- OTF2_GlobalEvtReaderCallbacks_-
 SetRmaOpCompleteBlockingCallback,
 [495](#)
- OTF2_GlobalEvtReaderCallbacks_-
 SetRmaOpCompleteNonBlockingCallback,
 [495](#)
- OTF2_GlobalEvtReaderCallbacks_-
 SetRmaOpCompleteRemoteCallback,
 [496](#)
- OTF2_GlobalEvtReaderCallbacks_-
 SetRmaOpTestCallback, [496](#)
- OTF2_GlobalEvtReaderCallbacks_-
 SetRmaPutCallback, [497](#)
- OTF2_GlobalEvtReaderCallbacks_-
 SetRmaReleaseLockCallback, [497](#)
- OTF2_GlobalEvtReaderCallbacks_-
 SetRmaRequestLockCallback, [498](#)
- OTF2_GlobalEvtReaderCallbacks_-
 SetRmaSyncCallback, [498](#)
- OTF2_GlobalEvtReaderCallbacks_-
 SetRmaTryLockCallback, [499](#)
- OTF2_GlobalEvtReaderCallbacks_-
 SetRmaWaitChangeCallback, [499](#)
- OTF2_GlobalEvtReaderCallbacks_-
 SetRmaWinCreateCallback, [500](#)
- OTF2_GlobalEvtReaderCallbacks_-
 SetRmaWinDestroyCallback, [500](#)
- OTF2_GlobalEvtReaderCallbacks_-
 SetThreadAcquireLockCallback,
 [501](#)
- OTF2_GlobalEvtReaderCallbacks_-
 SetThreadForkCallback, [501](#)
- OTF2_GlobalEvtReaderCallbacks_-
 SetThreadJoinCallback, [502](#)
- OTF2_GlobalEvtReaderCallbacks_-
 SetThreadReleaseLockCallback,
 [502](#)
- OTF2_GlobalEvtReaderCallbacks_-
 SetThreadTaskCompleteCallback,
 [503](#)
- OTF2_GlobalEvtReaderCallbacks_-
 SetThreadTaskCreateCallback,
 [503](#)
- OTF2_GlobalEvtReaderCallbacks_-
 SetThreadTaskSwitchCallback,
 [504](#)
- OTF2_GlobalEvtReaderCallbacks_-
 SetThreadTeamBeginCallback,
 [504](#)
- OTF2_GlobalEvtReaderCallbacks_-
 SetThreadTeamEndCallback, [505](#)
- OTF2_GlobalEvtReaderCallbacks_-
 SetUnknownCallback, [505](#)
- OTF2_GlobalEvtReaderCallbacks_Clear
- OTF2_GlobalEvtReaderCallbacks.h,
 [478](#)
- OTF2_GlobalEvtReaderCallbacks_Delete
- OTF2_GlobalEvtReaderCallbacks.h,
 [478](#)
- OTF2_GlobalEvtReaderCallbacks_New
- OTF2_GlobalEvtReaderCallbacks.h,
 [478](#)
- OTF2_GlobalEvtReaderCallbacks_SetBufferFlushCallback
- OTF2_GlobalEvtReaderCallbacks.h,
 [479](#)
- OTF2_GlobalEvtReaderCallbacks_SetEnterCallback
- OTF2_GlobalEvtReaderCallbacks.h,
 [479](#)
- OTF2_GlobalEvtReaderCallbacks_SetLeaveCallback

INDEX

- OTF2_GlobalEvtReaderCallbacks.h, OTF2_GlobalEvtReaderCallbacks_SetOmpJoinCallback
480 OTF2_GlobalEvtReaderCallbacks.h,
OTF2_GlobalEvtReaderCallbacks_SetMeasurementOffCallback
OTF2_GlobalEvtReaderCallbacks.h, OTF2_GlobalEvtReaderCallbacks_SetOmpReleaseLockCallback
480 OTF2_GlobalEvtReaderCallbacks.h,
OTF2_GlobalEvtReaderCallbacks_SetMetricCallback
488 OTF2_GlobalEvtReaderCallbacks.h, OTF2_GlobalEvtReaderCallbacks_SetOmpTaskCompleteCallback
481 OTF2_GlobalEvtReaderCallbacks.h,
OTF2_GlobalEvtReaderCallbacks_SetMpiCollectiveBeginCallback
488 OTF2_GlobalEvtReaderCallbacks.h, OTF2_GlobalEvtReaderCallbacks_SetOmpTaskCreateCallback
481 OTF2_GlobalEvtReaderCallbacks.h,
OTF2_GlobalEvtReaderCallbacks_SetMpiCollectiveEndCallback
489 OTF2_GlobalEvtReaderCallbacks.h, OTF2_GlobalEvtReaderCallbacks_SetOmpTaskSwitchCallback
482 OTF2_GlobalEvtReaderCallbacks.h,
OTF2_GlobalEvtReaderCallbacks_SetMpiIrecvCallback
489 OTF2_GlobalEvtReaderCallbacks.h, OTF2_GlobalEvtReaderCallbacks_SetParameterIntCallback
482 OTF2_GlobalEvtReaderCallbacks.h,
OTF2_GlobalEvtReaderCallbacks_SetMpiIrecvRequestCallback
490 OTF2_GlobalEvtReaderCallbacks.h, OTF2_GlobalEvtReaderCallbacks_SetParameterStringCallback
483 OTF2_GlobalEvtReaderCallbacks.h,
OTF2_GlobalEvtReaderCallbacks_SetMpiIsendCallback
490 OTF2_GlobalEvtReaderCallbacks.h, OTF2_GlobalEvtReaderCallbacks_SetParameterUnsignedIntCallback
483 OTF2_GlobalEvtReaderCallbacks.h,
OTF2_GlobalEvtReaderCallbacks_SetMpiIsendCompleteCallback
491 OTF2_GlobalEvtReaderCallbacks.h, OTF2_GlobalEvtReaderCallbacks_SetRmaAcquireLockCallback
484 OTF2_GlobalEvtReaderCallbacks.h,
OTF2_GlobalEvtReaderCallbacks_SetMpiRecvCallback
492 OTF2_GlobalEvtReaderCallbacks.h,
OTF2_GlobalEvtReaderCallbacks_SetRmaAtomicCallback
484 OTF2_GlobalEvtReaderCallbacks.h,
OTF2_GlobalEvtReaderCallbacks_SetMpiRequestCancelledCallback
492 OTF2_GlobalEvtReaderCallbacks.h,
OTF2_GlobalEvtReaderCallbacks_SetRmaCollectiveBeginCallback
485 OTF2_GlobalEvtReaderCallbacks.h,
OTF2_GlobalEvtReaderCallbacks_SetMpiRequestFestCallback
493 OTF2_GlobalEvtReaderCallbacks.h,
OTF2_GlobalEvtReaderCallbacks_SetRmaCollectiveEndCallback
485 OTF2_GlobalEvtReaderCallbacks.h,
OTF2_GlobalEvtReaderCallbacks_SetMpiSendCallback
493 OTF2_GlobalEvtReaderCallbacks.h,
OTF2_GlobalEvtReaderCallbacks_SetRmaGetCallback
486 OTF2_GlobalEvtReaderCallbacks.h,
OTF2_GlobalEvtReaderCallbacks_SetOmpAcquireLockCallback
494 OTF2_GlobalEvtReaderCallbacks.h,
OTF2_GlobalEvtReaderCallbacks_SetRmaGroupSyncCallback
486 OTF2_GlobalEvtReaderCallbacks.h,
OTF2_GlobalEvtReaderCallbacks_SetOmpForwardCallback
494 OTF2_GlobalEvtReaderCallbacks.h,
OTF2_GlobalEvtReaderCallbacks_SetRmaOpCompleteBlockingCallback
487

INDEX

- OTF2_GlobalEvtReaderCallbacks.h, OTF2_GlobalEvtReaderCallbacks_SetThreadReleaseLockCallback
495 OTF2_GlobalEvtReaderCallbacks.h,
OTF2_GlobalEvtReaderCallbacks_SetRmaOpCompleteNonBlockingCallback
OTF2_GlobalEvtReaderCallbacks.h, OTF2_GlobalEvtReaderCallbacks_SetThreadTaskCompleteCallback
495 OTF2_GlobalEvtReaderCallbacks.h,
OTF2_GlobalEvtReaderCallbacks_SetRmaOpCompleteRemoteCallback
OTF2_GlobalEvtReaderCallbacks.h, OTF2_GlobalEvtReaderCallbacks_SetThreadTaskCreateCallback
496 OTF2_GlobalEvtReaderCallbacks.h,
OTF2_GlobalEvtReaderCallbacks_SetRmaOpTestCallback
OTF2_GlobalEvtReaderCallbacks.h, OTF2_GlobalEvtReaderCallbacks_SetThreadTaskSwitchCallback
496 OTF2_GlobalEvtReaderCallbacks.h,
OTF2_GlobalEvtReaderCallbacks_SetRmaPutCallback
OTF2_GlobalEvtReaderCallbacks.h, OTF2_GlobalEvtReaderCallbacks_SetThreadTeamBeginCallback
497 OTF2_GlobalEvtReaderCallbacks.h,
OTF2_GlobalEvtReaderCallbacks_SetRmaReleaseLockCallback
OTF2_GlobalEvtReaderCallbacks.h, OTF2_GlobalEvtReaderCallbacks_SetThreadTeamEndCallback
497 OTF2_GlobalEvtReaderCallbacks.h,
OTF2_GlobalEvtReaderCallbacks_SetRmaRequestLockCallback
OTF2_GlobalEvtReaderCallbacks.h, OTF2_GlobalEvtReaderCallbacks_SetUnknownCallback
498 OTF2_GlobalEvtReaderCallbacks.h,
OTF2_GlobalEvtReaderCallbacks_SetRmaSyncCallback
OTF2_GlobalEvtReaderCallbacks.h, OTF2_GlobalSnapReader.h, 506
OTF2_GlobalEvtReaderCallbacks_SetRmaTryLockCallback
OTF2_GlobalEvtReaderCallbacks.h, OTF2_GlobalSnapReader_ReadSnapshots,
499 OTF2_GlobalSnapReader_SetCallbacks,
OTF2_GlobalEvtReaderCallbacks_SetRmaWaitChangeCallback
OTF2_GlobalEvtReaderCallbacks.h, OTF2_GlobalSnapReader_ReadSnapshots
499 OTF2_GlobalSnapReader.h, 507
OTF2_GlobalEvtReaderCallbacks_SetRmaWinCreateCallback
OTF2_GlobalEvtReaderCallbacks.h, OTF2_GlobalSnapReader_SetCallbacks
500 OTF2_GlobalSnapReader.h, 507
OTF2_GlobalEvtReaderCallbacks_SetRmaWinDestroyCallback
OTF2_GlobalEvtReaderCallbacks.h, OTF2_GlobalSnapReaderCallback_Enter
500 OTF2_GlobalSnapReaderCallbacks.h,
OTF2_GlobalEvtReaderCallbacks_SetThreadAcquireLockCallback
OTF2_GlobalEvtReaderCallbacks.h, OTF2_GlobalSnapReaderCallback_MeasurementOnOff
501 OTF2_GlobalSnapReaderCallbacks.h,
OTF2_GlobalEvtReaderCallbacks_SetThreadForkCallback
OTF2_GlobalEvtReaderCallbacks.h, OTF2_GlobalSnapReaderCallback_Metric
501 OTF2_GlobalSnapReaderCallbacks.h,
OTF2_GlobalEvtReaderCallbacks_SetThreadJoinCallback
OTF2_GlobalEvtReaderCallbacks.h, OTF2_GlobalSnapReaderCallback_MpiCollectiveBegin
502 OTF2_GlobalSnapReaderCallbacks.h,
OTF2_GlobalSnapReaderCallback_MpiCollectiveEnd

[OTF2_GlobalSnapReaderCallbacks.h](#)[OTF2_GlobalSnapReaderCallback_SnapshotStart](#)
[517](#) [OTF2_GlobalSnapReaderCallbacks.h,](#)
[OTF2_GlobalSnapReaderCallback_MpiIrecv](#) [529](#)
[OTF2_GlobalSnapReaderCallbacks.h](#)[OTF2_GlobalSnapReaderCallback_Unknown](#)
[518](#) [OTF2_GlobalSnapReaderCallbacks.h,](#)
[OTF2_GlobalSnapReaderCallback_MpiIrecvRequest](#) [530](#)
[OTF2_GlobalSnapReaderCallbacks.h](#)[OTF2_GlobalSnapReaderCallbacks](#)
[519](#) [OTF2_GlobalSnapReaderCallbacks.h,](#)
[OTF2_GlobalSnapReaderCallback_MpiIsend](#) [530](#)
[OTF2_GlobalSnapReaderCallbacks.h](#)[OTF2_GlobalSnapReaderCallbacks.h,](#) [508](#)
[520](#) [OTF2_GlobalSnapReaderCallback_-](#)
[OTF2_GlobalSnapReaderCallback_MpiIsendComplete](#), [515](#)
[OTF2_GlobalSnapReaderCallbacks.h,](#) [OTF2_GlobalSnapReaderCallback_-](#)
[521](#) [MeasurementOnOff,](#) [515](#)
[OTF2_GlobalSnapReaderCallback_MpiRecv](#) [OTF2_GlobalSnapReaderCallback_-](#)
[OTF2_GlobalSnapReaderCallbacks.h,](#) [Metric,](#) [516](#)
[522](#) [OTF2_GlobalSnapReaderCallback_-](#)
[OTF2_GlobalSnapReaderCallback_MpiSend](#) [MpiCollectiveBegin,](#) [517](#)
[OTF2_GlobalSnapReaderCallbacks.h,](#) [OTF2_GlobalSnapReaderCallback_-](#)
[523](#) [MpiCollectiveEnd,](#) [517](#)
[OTF2_GlobalSnapReaderCallback_OmpAcquireLock](#) [OTF2_GlobalSnapReaderCallback_-](#)
[OTF2_GlobalSnapReaderCallbacks.h,](#) [MpiIrecv,](#) [518](#)
[523](#) [OTF2_GlobalSnapReaderCallback_-](#)
[OTF2_GlobalSnapReaderCallback_OmpFork](#) [MpiIrecvRequest,](#) [519](#)
[OTF2_GlobalSnapReaderCallbacks.h,](#) [OTF2_GlobalSnapReaderCallback_-](#)
[524](#) [MpiIsend,](#) [520](#)
[OTF2_GlobalSnapReaderCallback_OmpTaskCreate](#) [OTF2_GlobalSnapReaderCallback_-](#)
[OTF2_GlobalSnapReaderCallbacks.h,](#) [MpiIsendComplete,](#) [521](#)
[525](#) [OTF2_GlobalSnapReaderCallback_-](#)
[OTF2_GlobalSnapReaderCallback_OmpTaskSwitch](#) [MpiRecv,](#) [522](#)
[OTF2_GlobalSnapReaderCallbacks.h,](#) [OTF2_GlobalSnapReaderCallback_-](#)
[526](#) [MpiSend,](#) [523](#)
[OTF2_GlobalSnapReaderCallback_ParameterInt](#) [OTF2_GlobalSnapReaderCallback_-](#)
[OTF2_GlobalSnapReaderCallbacks.h,](#) [OmpAcquireLock,](#) [523](#)
[526](#) [OTF2_GlobalSnapReaderCallback_-](#)
[OTF2_GlobalSnapReaderCallback_ParameterString](#) [OmpFork,](#) [524](#)
[OTF2_GlobalSnapReaderCallbacks.h,](#) [OTF2_GlobalSnapReaderCallback_-](#)
[527](#) [OmpTaskCreate,](#) [525](#)
[OTF2_GlobalSnapReaderCallback_ParameterOmpGlobal](#) [OTF2_GlobalSnapReaderCallback_-](#)
[OTF2_GlobalSnapReaderCallbacks.h,](#) [OmpTaskSwitch,](#) [526](#)
[528](#) [OTF2_GlobalSnapReaderCallback_-](#)
[OTF2_GlobalSnapReaderCallback_SnapshotEnd](#) [ParameterInt,](#) [526](#)
[OTF2_GlobalSnapReaderCallbacks.h,](#) [OTF2_GlobalSnapReaderCallback_-](#)
[529](#) [ParameterString,](#) [527](#)

INDEX

- OTF2_GlobalSnapReaderCallback_ - ParameterUnsignedInt, [528](#)
- OTF2_GlobalSnapReaderCallback_ - SnapshotEnd, [529](#)
- OTF2_GlobalSnapReaderCallback_ - SnapshotStart, [529](#)
- OTF2_GlobalSnapReaderCallback_ - Unknown, [530](#)
- OTF2_GlobalSnapReaderCallbacks, [530](#)
- OTF2_GlobalSnapReaderCallbacks_ - Clear, [531](#)
- OTF2_GlobalSnapReaderCallbacks_ - Delete, [531](#)
- OTF2_GlobalSnapReaderCallbacks_ - New, [531](#)
- OTF2_GlobalSnapReaderCallbacks_ - SetEnterCallback, [532](#)
- OTF2_GlobalSnapReaderCallbacks_ - SetMeasurementOnOffCallback, [532](#)
- OTF2_GlobalSnapReaderCallbacks_ - SetMetricCallback, [533](#)
- OTF2_GlobalSnapReaderCallbacks_ - OTF2_GlobalSnapReaderCallbacks_DeleteSetMpiCollectiveBeginCallback, [533](#)
- OTF2_GlobalSnapReaderCallbacks_ - OTF2_GlobalSnapReaderCallbacks_NewSetMpiCollectiveEndCallback, [534](#)
- OTF2_GlobalSnapReaderCallbacks_ - OTF2_GlobalSnapReaderCallbacks_SetEnterCallbackSetMpiIrecvCallback, [535](#)
- OTF2_GlobalSnapReaderCallbacks_ - SetMpiIrecvRequestCallback, [535](#)
- OTF2_GlobalSnapReaderCallbacks_ - SetMpiIsendCallback, [536](#)
- OTF2_GlobalSnapReaderCallbacks_ - OTF2_GlobalSnapReaderCallbacks_SetMetricCallbackSetMpiIsendCompleteCallback, [536](#)
- OTF2_GlobalSnapReaderCallbacks_ - OTF2_GlobalSnapReaderCallbacks_SetMpiCollectiveBeginCallbackSetMpiRecvCallback, [537](#)
- OTF2_GlobalSnapReaderCallbacks_ - SetMpiSendCallback, [538](#)
- OTF2_GlobalSnapReaderCallbacks_ - SetOmpAcquireLockCallback, [538](#)
- OTF2_GlobalSnapReaderCallbacks_ - SetOmpForkCallback, [539](#)
- OTF2_GlobalSnapReaderCallbacks_ - SetOmpTaskCreateCallback, [539](#)
- OTF2_GlobalSnapReaderCallbacks_ - SetOmpTaskSwitchCallback, [540](#)
- OTF2_GlobalSnapReaderCallbacks_ - SetParameterIntCallback, [540](#)
- OTF2_GlobalSnapReaderCallbacks_ - SetParameterStringCallback, [541](#)
- OTF2_GlobalSnapReaderCallbacks_ - SetParameterUnsignedIntCallback, [542](#)
- OTF2_GlobalSnapReaderCallbacks_ - SetSnapshotEndCallback, [542](#)
- OTF2_GlobalSnapReaderCallbacks_ - SetSnapshotStartCallback, [543](#)
- OTF2_GlobalSnapReaderCallbacks_ - SetUnknownCallback, [543](#)
- OTF2_GlobalSnapReaderCallbacks_Clear
- OTF2_GlobalSnapReaderCallbacks.h, [531](#)
- OTF2_GlobalSnapReaderCallbacks_Delete
- OTF2_GlobalSnapReaderCallbacks.h, [531](#)
- OTF2_GlobalSnapReaderCallbacks_New
- OTF2_GlobalSnapReaderCallbacks.h, [531](#)
- OTF2_GlobalSnapReaderCallbacks_SetEnterCallback
- OTF2_GlobalSnapReaderCallbacks.h, [532](#)
- OTF2_GlobalSnapReaderCallbacks_SetMeasurementOnOffCallback
- OTF2_GlobalSnapReaderCallbacks.h, [532](#)
- OTF2_GlobalSnapReaderCallbacks_SetMetricCallback
- OTF2_GlobalSnapReaderCallbacks.h, [533](#)
- OTF2_GlobalSnapReaderCallbacks_SetMpiCollectiveBeginCallback
- OTF2_GlobalSnapReaderCallbacks.h, [533](#)
- OTF2_GlobalSnapReaderCallbacks_SetMpiCollectiveEndCallback
- OTF2_GlobalSnapReaderCallbacks.h, [533](#)
- OTF2_GlobalSnapReaderCallbacks_SetMpiRecvCallback
- OTF2_GlobalSnapReaderCallbacks.h, [537](#)
- OTF2_GlobalSnapReaderCallbacks_SetMpiSendCallback
- OTF2_GlobalSnapReaderCallbacks.h, [538](#)
- OTF2_GlobalSnapReaderCallbacks_SetOmpAcquireLockCallback
- OTF2_GlobalSnapReaderCallbacks.h, [538](#)
- OTF2_GlobalSnapReaderCallbacks_SetOmpForkCallback
- OTF2_GlobalSnapReaderCallbacks.h, [539](#)
- OTF2_GlobalSnapReaderCallbacks_SetOmpTaskCreateCallback
- OTF2_GlobalSnapReaderCallbacks.h, [539](#)
- OTF2_GlobalSnapReaderCallbacks_SetOmpTaskSwitchCallback
- OTF2_GlobalSnapReaderCallbacks.h, [540](#)
- OTF2_GlobalSnapReaderCallbacks_SetParameterIntCallback
- OTF2_GlobalSnapReaderCallbacks.h, [540](#)
- OTF2_GlobalSnapReaderCallbacks_SetParameterStringCallback
- OTF2_GlobalSnapReaderCallbacks.h, [541](#)
- OTF2_GlobalSnapReaderCallbacks_SetParameterUnsignedIntCallback
- OTF2_GlobalSnapReaderCallbacks.h, [542](#)
- OTF2_GlobalSnapReaderCallbacks_SetSnapshotEndCallback
- OTF2_GlobalSnapReaderCallbacks.h, [542](#)
- OTF2_GlobalSnapReaderCallbacks_SetSnapshotStartCallback
- OTF2_GlobalSnapReaderCallbacks.h, [543](#)
- OTF2_GlobalSnapReaderCallbacks_SetUnknownCallback
- OTF2_GlobalSnapReaderCallbacks.h, [543](#)

INDEX

- OTF2_IdMap.h, 549
- OTF2_IdMap_Traverse
 - OTF2_IdMap.h, 550
- OTF2_IdMapMode
 - OTF2_IdMap.h, 546
- OTF2_IdMapMode_enum
 - OTF2_IdMap.h, 546
- OTF2_LocationGroupType_enum
 - OTF2_Definitions.h, 164
- OTF2_LocationType_enum
 - OTF2_Definitions.h, 165
- OTF2_LockType_enum
 - OTF2_Events.h, 232
- OTF2_MappingType_enum
 - OTF2_GeneralDefinitions.h, 373
- OTF2_Marker.h, 550
 - OTF2_MarkerScope_enum, 551
 - OTF2_MarkerSeverity_enum, 552
- OTF2_MarkerReader.h, 552
 - OTF2_MarkerReader_ReadMarkers, 553
 - OTF2_MarkerReader_SetCallbacks, 553
- OTF2_MarkerReader_ReadMarkers
 - OTF2_MarkerReader.h, 553
- OTF2_MarkerReader_SetCallbacks
 - OTF2_MarkerReader.h, 553
- OTF2_MarkerReaderCallback_DefMarker
 - OTF2_MarkerReaderCallbacks.h, 556
- OTF2_MarkerReaderCallback_Marker
 - OTF2_MarkerReaderCallbacks.h, 556
- OTF2_MarkerReaderCallback_Unknown
 - OTF2_MarkerReaderCallbacks.h, 557
- OTF2_MarkerReaderCallbacks.h, 554
 - OTF2_MarkerReaderCallback_DefMarker, 556
 - OTF2_MarkerReaderCallback_Marker, 556
 - OTF2_MarkerReaderCallback_Unknown, 557
- OTF2_MarkerReaderCallbacks_Clear,
 - OTF2_Callbacks.h, 155
- OTF2_MarkerReaderCallbacks_Delete,
 - OTF2_Callbacks.h, 156
- OTF2_MarkerReaderCallbacks_New,
 - 558
- OTF2_MarkerReaderCallbacks_SetDefMarkerCallback,
 - 558
- OTF2_MarkerReaderCallbacks_SetMarkerCallback,
 - 559
- OTF2_MarkerReaderCallbacks_SetUnknownCallback,
 - 559
- OTF2_MarkerReaderCallbacks_Clear
 - OTF2_MarkerReaderCallbacks.h, 557
- OTF2_MarkerReaderCallbacks_Delete
 - OTF2_MarkerReaderCallbacks.h, 558
- OTF2_MarkerReaderCallbacks_New
 - OTF2_MarkerReaderCallbacks.h, 558
- OTF2_MarkerReaderCallbacks_SetDefMarkerCallback
 - OTF2_MarkerReaderCallbacks.h, 558
- OTF2_MarkerReaderCallbacks_SetMarkerCallback
 - OTF2_MarkerReaderCallbacks.h, 559
- OTF2_MarkerReaderCallbacks_SetUnknownCallback
 - OTF2_MarkerReaderCallbacks.h, 559
- OTF2_MarkerScope_enum
 - OTF2_Marker.h, 551
- OTF2_MarkerSeverity_enum
 - OTF2_Marker.h, 552
- OTF2_MarkerWriter.h, 560
 - OTF2_MarkerWriter_WriteDefMarker, 561
 - OTF2_MarkerWriter_WriteMarker, 561
- OTF2_MarkerWriter_WriteDefMarker
 - OTF2_MarkerWriter.h, 561
- OTF2_MarkerWriter_WriteMarker
 - OTF2_MarkerWriter.h, 561
- OTF2_MasterSlaveMode
 - OTF2_Archive.h, 103
- OTF2_MasterSlaveMode_enum
 - OTF2_Archive.h, 103
- OTF2_MeasurementMode_enum
 - OTF2_Events.h, 232
- OTF2_MemoryAllocate
 - OTF2_Callbacks.h, 155
- OTF2_MemoryCallbacks, 92
- OTF2_MemoryFreeAll
 - OTF2_Callbacks.h, 156

- OTF2_MetricBase_enum
 - OTF2_Definitions.h, [165](#)
- OTF2_MetricMode_enum
 - OTF2_Definitions.h, [165](#)
- OTF2_MetricOccurrence_enum
 - OTF2_Definitions.h, [166](#)
- OTF2_MetricScope_enum
 - OTF2_Definitions.h, [166](#)
- OTF2_MetricTiming_enum
 - OTF2_Definitions.h, [167](#)
- OTF2_MetricType_enum
 - OTF2_Definitions.h, [167](#)
- OTF2_MetricValue_union, [93](#)
- OTF2_MetricValueProperty_enum
 - OTF2_Definitions.h, [168](#)
- OTF2_Paradigm_enum
 - OTF2_GeneralDefinitions.h, [374](#)
- OTF2_ParameterType_enum
 - OTF2_Definitions.h, [168](#)
- OTF2_PostFlushCallback
 - OTF2_Callbacks.h, [156](#)
- OTF2_PreFlushCallback
 - OTF2_Callbacks.h, [157](#)
- OTF2_Reader.h, [562](#)
 - OTF2_Reader_Close, [569](#)
 - OTF2_Reader_CloseDefReader, [569](#)
 - OTF2_Reader_CloseEvtReader, [570](#)
 - OTF2_Reader_CloseGlobalDefReader, [570](#)
 - OTF2_Reader_CloseGlobalEvtReader, [570](#)
 - OTF2_Reader_CloseGlobalSnapReader, [571](#)
 - OTF2_Reader_CloseMarkerReader, [571](#)
 - OTF2_Reader_CloseMarkerWriter, [572](#)
 - OTF2_Reader_CloseSnapReader, [572](#)
 - OTF2_Reader_CloseThumbReader, [572](#)
 - OTF2_Reader_GetBoolProperty, [573](#)
 - OTF2_Reader_GetChunkSize, [573](#)
 - OTF2_Reader_GetCompression, [574](#)
 - OTF2_Reader_GetCreator, [574](#)
 - OTF2_Reader_GetDefReader, [574](#)
 - OTF2_Reader_GetDescription, [575](#)
 - OTF2_Reader_GetEvtReader, [575](#)
 - OTF2_Reader_GetFileSubstrate, [575](#)
 - OTF2_Reader_GetGlobalDefReader, [576](#)
 - OTF2_Reader_GetGlobalEvtReader, [576](#)
 - OTF2_Reader_GetGlobalSnapReader, [576](#)
 - OTF2_Reader_GetMachineName, [577](#)
 - OTF2_Reader_GetMarkerReader, [577](#)
 - OTF2_Reader_GetMarkerWriter, [577](#)
 - OTF2_Reader_GetNumberOfGlobalDefinitions, [578](#)
 - OTF2_Reader_GetNumberOfLocations, [578](#)
 - OTF2_Reader_GetNumberOfSnapshots, [578](#)
 - OTF2_Reader_GetNumberOfThumbnails, [579](#)
 - OTF2_Reader_GetProperty, [579](#)
 - OTF2_Reader_GetPropertyNames, [580](#)
 - OTF2_Reader_GetSnapReader, [580](#)
 - OTF2_Reader_GetThumbReader, [580](#)
 - OTF2_Reader_GetTraceId, [581](#)
 - OTF2_Reader_GetVersion, [581](#)
 - OTF2_Reader_HasGlobalEvent, [582](#)
 - OTF2_Reader_Open, [582](#)
 - OTF2_Reader_ReadAllGlobalDefinitions, [582](#)
 - OTF2_Reader_ReadAllGlobalEvents, [583](#)
 - OTF2_Reader_ReadAllGlobalSnapshots, [583](#)
 - OTF2_Reader_ReadAllLocalDefinitions, [584](#)
 - OTF2_Reader_ReadAllLocalEvents, [584](#)
 - OTF2_Reader_ReadAllLocalSnapshots, [584](#)
 - OTF2_Reader_ReadAllMarkers, [585](#)
 - OTF2_Reader_ReadGlobalDefinitions, [585](#)

INDEX

- OTF2_Reader_ReadGlobalEvent, [586](#) OTF2_Reader_CloseSnapReader
OTF2_Reader_ReadGlobalEvents, [586](#) OTF2_Reader.h, [572](#)
OTF2_Reader_ReadGlobalSnapshots, OTF2_Reader_CloseThumbReader
[587](#) OTF2_Reader.h, [572](#)
OTF2_Reader_ReadLocalDefinitions, OTF2_Reader_GetBoolProperty
[587](#) OTF2_Reader.h, [573](#)
OTF2_Reader_ReadLocalEvents, [588](#) OTF2_Reader_GetChunkSize
OTF2_Reader_ReadLocalEventsBackward, OTF2_Reader.h, [573](#)
[588](#) OTF2_Reader_GetCompression
OTF2_Reader_ReadLocalSnapshots, OTF2_Reader.h, [574](#)
[589](#) OTF2_Reader_GetCreator
OTF2_Reader_ReadMarkers, [589](#) OTF2_Reader.h, [574](#)
OTF2_Reader_RegisterDefCallbacks, OTF2_Reader_GetDefReader
[590](#) OTF2_Reader.h, [574](#)
OTF2_Reader_RegisterEvtCallbacks, OTF2_Reader_GetDescription
[590](#) OTF2_Reader.h, [575](#)
OTF2_Reader_RegisterGlobalDefCallbacks, OTF2_Reader_GetEvtReader
[591](#) OTF2_Reader.h, [575](#)
OTF2_Reader_RegisterGlobalEvtCallbacks, OTF2_Reader_GetFileSubstrate
[591](#) OTF2_Reader.h, [575](#)
OTF2_Reader_RegisterGlobalSnapCallbacks, OTF2_Reader_GetGlobalDefReader
[591](#) OTF2_Reader.h, [576](#)
OTF2_Reader_RegisterMarkerCallbacks, OTF2_Reader_GetGlobalEvtReader
[592](#) OTF2_Reader.h, [576](#)
OTF2_Reader_RegisterSnapCallbacks, OTF2_Reader_GetGlobalSnapReader
[592](#) OTF2_Reader.h, [576](#)
OTF2_Reader_SetFileSionCallbacks, OTF2_Reader_GetMachineName
[593](#) OTF2_Reader.h, [577](#)
OTF2_Reader_Close OTF2_Reader_GetMarkerReader
OTF2_Reader.h, [569](#) OTF2_Reader.h, [577](#)
OTF2_Reader_CloseDefReader OTF2_Reader_GetMarkerWriter
OTF2_Reader.h, [569](#) OTF2_Reader.h, [577](#)
OTF2_Reader_CloseEvtReader OTF2_Reader_GetNumberOfGlobalDefinitions
OTF2_Reader.h, [570](#) OTF2_Reader.h, [578](#)
OTF2_Reader_CloseGlobalDefReader OTF2_Reader_GetNumberOfLocations
OTF2_Reader.h, [570](#) OTF2_Reader.h, [578](#)
OTF2_Reader_CloseGlobalEvtReader OTF2_Reader_GetNumberOfSnapshots
OTF2_Reader.h, [570](#) OTF2_Reader.h, [578](#)
OTF2_Reader_CloseGlobalSnapReader OTF2_Reader_GetNumberOfThumbnails
OTF2_Reader.h, [571](#) OTF2_Reader.h, [579](#)
OTF2_Reader_CloseMarkerReader OTF2_Reader_GetProperty
OTF2_Reader.h, [571](#) OTF2_Reader.h, [579](#)
OTF2_Reader_CloseMarkerWriter OTF2_Reader_GetPropertyNames
OTF2_Reader.h, [572](#) OTF2_Reader.h, [580](#)

- | | |
|--|---|
| OTF2_Reader_GetSnapReader OTF2_Reader.h, 580 | OTF2_Reader_RegisterDefCallbacks OTF2_Reader.h, 590 |
| OTF2_Reader_GetThumbReader OTF2_Reader.h, 580 | OTF2_Reader_RegisterEvtCallbacks OTF2_Reader.h, 590 |
| OTF2_Reader_GetTraceId OTF2_Reader.h, 581 | OTF2_Reader_RegisterGlobalDefCallbacks OTF2_Reader.h, 591 |
| OTF2_Reader_GetVersion OTF2_Reader.h, 581 | OTF2_Reader_RegisterGlobalEvtCallbacks OTF2_Reader.h, 591 |
| OTF2_Reader_HasGlobalEvent OTF2_Reader.h, 582 | OTF2_Reader_RegisterGlobalSnapCallbacks OTF2_Reader.h, 591 |
| OTF2_Reader_Open OTF2_Reader.h, 582 | OTF2_Reader_RegisterMarkerCallbacks OTF2_Reader.h, 592 |
| OTF2_Reader_ReadAllGlobalDefinitions OTF2_Reader.h, 582 | OTF2_Reader_RegisterSnapCallbacks OTF2_Reader.h, 592 |
| OTF2_Reader_ReadAllGlobalEvents OTF2_Reader.h, 583 | OTF2_Reader_SetFileSionCallbacks OTF2_Reader.h, 593 |
| OTF2_Reader_ReadAllGlobalSnapshots OTF2_Reader.h, 583 | OTF2_RecorderKind_enum OTF2_Definitions.h, 169 |
| OTF2_Reader_ReadAllLocalDefinitions OTF2_Reader.h, 584 | OTF2_RegionFlag_enum OTF2_Definitions.h, 169 |
| OTF2_Reader_ReadAllLocalEvents OTF2_Reader.h, 584 | OTF2_RegionRole_enum OTF2_Definitions.h, 169 |
| OTF2_Reader_ReadAllLocalSnapshots OTF2_Reader.h, 584 | OTF2_RmaAtomicType_enum OTF2_Events.h, 233 |
| OTF2_Reader_ReadAllMarkers OTF2_Reader.h, 585 | OTF2_RmaSyncLevel_enum OTF2_Events.h, 233 |
| OTF2_Reader_ReadGlobalDefinitions OTF2_Reader.h, 585 | OTF2_RmaSyncType_enum OTF2_Events.h, 233 |
| OTF2_Reader_ReadGlobalEvent OTF2_Reader.h, 586 | OTF2_SnapReader.h, 594 |
| OTF2_Reader_ReadGlobalEvents OTF2_Reader.h, 586 | OTF2_SnapReader_GetLocationID, 595 |
| OTF2_Reader_ReadGlobalSnapshots OTF2_Reader.h, 587 | OTF2_SnapReader_ReadSnapshots, 595 |
| OTF2_Reader_ReadLocalDefinitions OTF2_Reader.h, 587 | OTF2_SnapReader_Seek, 595 |
| OTF2_Reader_ReadLocalEvents OTF2_Reader.h, 588 | OTF2_SnapReader_SetCallbacks, 596 |
| OTF2_Reader_ReadLocalEventsBackward OTF2_Reader.h, 588 | OTF2_SnapReader_GetLocationID OTF2_SnapReader.h, 595 |
| OTF2_Reader_ReadLocalSnapshots OTF2_Reader.h, 589 | OTF2_SnapReader_ReadSnapshots OTF2_SnapReader.h, 595 |
| OTF2_Reader_ReadMarkers OTF2_Reader.h, 589 | OTF2_SnapReader_Seek OTF2_SnapReader.h, 595 |
| | OTF2_SnapReader_SetCallbacks OTF2_SnapReader.h, 596 |
| | OTF2_SnapReaderCallback_Enter |

INDEX

OTF2_SnapReaderCallbacks.h, 603
OTF2_SnapReaderCallback_Enter, 603
OTF2_SnapReaderCallback_MeasurementOnOff, 604
OTF2_SnapReaderCallback_Metric, 604
OTF2_SnapReaderCallback_MpiCollectiveBegin, 605
OTF2_SnapReaderCallback_MpiCollectiveEnd, 606
OTF2_SnapReaderCallback_MpiIrecv, 607
OTF2_SnapReaderCallback_MpiIrecvRequest, 608
OTF2_SnapReaderCallback_MpiIsend, 608
OTF2_SnapReaderCallback_MpiIsendComplete, 609
OTF2_SnapReaderCallback_MpiRecv, 610
OTF2_SnapReaderCallback_MpiSend, 611
OTF2_SnapReaderCallback_OmpAcquireLock, 612
OTF2_SnapReaderCallback_OmpFork, 613
OTF2_SnapReaderCallback_OmpTaskCreate, 613
OTF2_SnapReaderCallback_OmpTaskSwitch, 614
OTF2_SnapReaderCallback_ParameterInt, 615
OTF2_SnapReaderCallback_ParameterString, 615
OTF2_SnapReaderCallback_ParameterUnsignedInt, 616
OTF2_SnapReaderCallback_SnapshotEnd, 617
OTF2_SnapReaderCallback_SnapshotStart, 618
OTF2_SnapReaderCallback_Unknown, 618
OTF2_SnapReaderCallbacks, 619
OTF2_SnapReaderCallbacks_Clear, 619

- OTF2_SnapReaderCallbacks_Delete, 620
- OTF2_SnapReaderCallbacks_SetUnknownCallback, 632
- OTF2_SnapReaderCallbacks_New, 620
- OTF2_SnapReaderCallbacks_Clear, 619
- OTF2_SnapReaderCallbacks_SetEnterCallback, 620
- OTF2_SnapReaderCallbacks_Delete, 620
- OTF2_SnapReaderCallbacks_SetMeasurementOnOffCallback, 621
- OTF2_SnapReaderCallbacks_New, 620
- OTF2_SnapReaderCallbacks_SetMetricCallback, 621
- OTF2_SnapReaderCallbacks_SetEnterCallback, 620
- OTF2_SnapReaderCallbacks_SetMpiCollectiveBeginCallback, 622
- OTF2_SnapReaderCallbacks_SetMeasurementOnOffCallback, 621
- OTF2_SnapReaderCallbacks_SetMpiCollectiveEndCallback, 622
- OTF2_SnapReaderCallbacks_SetMetricCallback, 621
- OTF2_SnapReaderCallbacks_SetMpiCollectiveBeginCallback, 623
- OTF2_SnapReaderCallbacks_SetMpiCollectiveEndCallback, 624
- OTF2_SnapReaderCallbacks_SetMpiIrecvCallback, 624
- OTF2_SnapReaderCallbacks_SetMpiIrecvRequestCallback, 625
- OTF2_SnapReaderCallbacks_SetMpiIsendCallback, 625
- OTF2_SnapReaderCallbacks_SetMpiIsendCompleteCallback, 626
- OTF2_SnapReaderCallbacks_SetMpiRecvCallback, 626
- OTF2_SnapReaderCallbacks_SetMpiSendCallback, 627
- OTF2_SnapReaderCallbacks_SetMpiSendCompleteCallback, 628
- OTF2_SnapReaderCallbacks_SetMpiForkCallback, 628
- OTF2_SnapReaderCallbacks_SetParameterIntCallback, 629
- OTF2_SnapReaderCallbacks_SetMpiTaskCreateCallback, 628
- OTF2_SnapReaderCallbacks_SetParameterStringCallback, 629
- OTF2_SnapReaderCallbacks_SetMpiTaskSwitchCallback, 628
- OTF2_SnapReaderCallbacks_SetParameterUnsignedIntCallback, 630
- OTF2_SnapReaderCallbacks_SetParameterIntCallback, 629
- OTF2_SnapReaderCallbacks_SetSnapReaderCallback, 630
- OTF2_SnapReaderCallbacks_SetParameterStringCallback, 629
- OTF2_SnapReaderCallbacks_SetSnapReaderCallback, 631
- OTF2_SnapReaderCallbacks_SetParameterUnsignedIntCallback, 630

INDEX

OTF2_SnapReaderCallbacks_SetSnapshotCallback, 630
OTF2_SnapReaderCallbacks.h, 630
OTF2_SnapReaderCallbacks_SetSnapshotCallback, 631
OTF2_SnapReaderCallbacks.h, 631
OTF2_SnapReaderCallbacks_SetUnknownCallback, 632
OTF2_SnapReaderCallbacks.h, 632
OTF2_SnapWriter
OTF2_SnapWriter.h, 636
OTF2_SnapWriter.h, 632
OTF2_SnapWriter, 636
OTF2_SnapWriter_Enter, 636
OTF2_SnapWriter_GetLocationID, 636
OTF2_SnapWriter_GetLocationID, 636
OTF2_SnapWriter_MeasurementOnOff, 637
OTF2_SnapWriter_MeasurementOnOff, 637
OTF2_SnapWriter_Metric, 637
OTF2_SnapWriter_Metric, 637
OTF2_SnapWriter_MpiCollectiveBegin, 638
OTF2_SnapWriter_MpiCollectiveBegin, 638
OTF2_SnapWriter_MpiCollectiveEnd, 639
OTF2_SnapWriter_MpiCollectiveEnd, 639
OTF2_SnapWriter_MpiIrecv, 640
OTF2_SnapWriter_MpiIrecv, 640
OTF2_SnapWriter_MpiIrecvRequest, 641
OTF2_SnapWriter_MpiIrecvRequest, 641
OTF2_SnapWriter_MpiIsend, 641
OTF2_SnapWriter_MpiIsend, 641
OTF2_SnapWriter_MpiIsendComplete, 642
OTF2_SnapWriter_MpiIsendComplete, 642
OTF2_SnapWriter_MpiRecv, 643
OTF2_SnapWriter_MpiRecv, 643
OTF2_SnapWriter_MpiSend, 643
OTF2_SnapWriter_MpiSend, 643
OTF2_SnapWriter_MpiSendRequest, 644
OTF2_SnapWriter_MpiSendRequest, 644
OTF2_SnapWriter_OmpAcquireLock, 645
OTF2_SnapWriter_OmpAcquireLock, 645
OTF2_SnapWriter_OmpFork, 645
OTF2_SnapWriter_OmpFork, 645
OTF2_SnapWriter_OmpTaskCreate, 646
OTF2_SnapWriter_OmpTaskCreate, 646
OTF2_SnapWriter_OmpTaskSwitch, 646
OTF2_SnapWriter_OmpTaskSwitch, 646
OTF2_SnapWriter_ParameterInt, 647
OTF2_SnapWriter_ParameterInt, 647
OTF2_SnapWriter_ParameterString, 647
OTF2_SnapWriter_ParameterString, 647
OTF2_SnapWriter_ParameterUnsignedInt, 648
OTF2_SnapWriter_ParameterUnsignedInt, 648
OTF2_SnapWriter_SnapshotEnd, 649
OTF2_SnapWriter_SnapshotEnd, 649
OTF2_SnapWriter_SnapshotStart, 649
OTF2_SnapWriter_SnapshotStart, 649
OTF2_SnapWriter_SnapshotEnd, 649
OTF2_SnapWriter_SnapshotStart, 649
OTF2_SnapWriter_Enter, 636
OTF2_SnapWriter.h, 636
OTF2_SnapWriter_GetLocationID, 636
OTF2_SnapWriter_MeasurementOnOff, 637
OTF2_SnapWriter_Metric, 637
OTF2_SnapWriter_MpiCollectiveBegin, 638
OTF2_SnapWriter_MpiCollectiveEnd, 639
OTF2_SnapWriter_MpiIrecv, 640
OTF2_SnapWriter_MpiIrecvRequest, 641
OTF2_SnapWriter_MpiIsend, 641
OTF2_SnapWriter_MpiIsendComplete, 642
OTF2_SnapWriter_MpiRecv, 643
OTF2_SnapWriter_MpiSend, 643
OTF2_SnapWriter_MpiSendRequest, 644
OTF2_SnapWriter_OmpAcquireLock, 645
OTF2_SnapWriter_OmpFork, 645
OTF2_SnapWriter_OmpTaskCreate, 646
OTF2_SnapWriter_OmpTaskSwitch, 646
OTF2_SnapWriter_ParameterInt, 647
OTF2_SnapWriter_ParameterString, 647
OTF2_SnapWriter_ParameterUnsignedInt, 648
OTF2_SnapWriter_SnapshotEnd, 649
OTF2_SnapWriter_SnapshotStart, 649
OTF2_SystemTreeDomain_enum, 171
OTF2_Definitions.h, 171
OTF2_Thumbnail.h, 650
OTF2_ThumbReader_GetHeader, 651

OTF2_ThumbReader_ReadSample,
652
OTF2_ThumbWriter_WriteSample,
652
OTF2_ThumbnailType_enum
OTF2_GeneralDefinitions.h, 375
OTF2_ThumbReader_GetHeader
OTF2_Thumbnail.h, 651
OTF2_ThumbReader_ReadSample
OTF2_Thumbnail.h, 652
OTF2_ThumbWriter_WriteSample
OTF2_Thumbnail.h, 652
OTF2_Type_enum
OTF2_GeneralDefinitions.h, 375
OTF2_UNDEFINED_TYPE
OTF2_GeneralDefinitions.h, 371